

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P331853-940

Luminaire Tested: **S122RDIW-S1005D970U940-4F0-1E-UDD-A**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P331853-940
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-2,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S122RDIW-S1005D970U940-4F0-1E-UDD-A
Description: DEFINE 2 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 1005 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING
UPLIGHT 970 LUMENS PER FOOT, NO LENS
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6852.5 lumens
Efficiency: N/A
Efficacy: 101.7 lumens/watt
Spacing Criteria (0/90/45): 0.86 / 1.16 / 1.02
Luminous Opening: Rectangular (W 4' x L: 0.17' x H: 0')
CIE Type: General Diffuse


Input Watts (W): 67.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

Luminous Intensity Polar Plot



— 0°-180° - - - 45°-225° ···· 90°-270° - · - · 135°-315°



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	107	107	107	107	99	99	99	99	83	83	83	69	69	69	56	56	56	50
1	98	94	91	88	91	87	84	81	74	72	70	62	60	59	50	49	49	43
2	90	83	78	73	83	77	72	68	66	62	59	55	53	50	45	44	42	38
3	83	74	67	62	76	69	63	58	59	54	51	50	46	44	41	39	37	33
4	76	66	59	53	70	62	55	50	53	48	44	45	41	38	37	35	33	29
5	70	59	52	46	65	55	49	44	48	43	39	41	37	34	34	31	29	26
6	65	54	46	40	60	50	43	38	43	38	34	37	33	30	31	28	26	23
7	61	49	41	36	56	46	39	34	40	34	31	34	30	27	29	26	24	21
8	56	45	37	32	52	42	35	31	36	31	27	31	27	24	27	24	21	19
9	53	41	34	29	49	38	32	28	34	28	25	29	25	22	25	22	20	17
10	49	38	31	26	46	35	29	25	31	26	23	27	23	20	23	20	18	16

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	31752	31752	31752	31752
5°	35462	31951	28329	31951
10°	39346	31727	24556	31727
15°	41279	31263	19348	31263
20°	35787	30574	16744	30574
25°	23469	29630	14949	29630
30°	15797	28486	13530	28486
35°	12796	27045	12203	27045
40°	11377	25478	11291	25478
45°	10298	23640	10079	23640
50°	9372	21815	9339	21815
55°	8811	19792	8695	19792
60°	7369	17938	7282	17938
65°	6212	16290	7049	16290
70°	5740	14549	6647	14549
75°	5371	12664	6138	12664
80°	4956	10423	5467	10423
85°	4557	8225	4798	8225



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	186.4	2.7
10°-20°	519.5	7.6
20°-30°	669.4	9.8
30°-40°	636.1	9.3
40°-50°	544.9	8.0
50°-60°	415.0	6.1
60°-70°	262.3	3.8
70°-80°	131.0	1.9
80°-90°	37.0	0.5
90°-100°	39.3	0.6
100°-110°	144.0	2.1
110°-120°	385.0	5.6
120°-130°	635.6	9.3
130°-140°	675.9	9.9
140°-150°	628.3	9.2
150°-160°	505.1	7.4
160°-170°	325.5	4.8
170°-180°	112.0	1.6
0°-30°	1375.3	20.1
0°-40°	2011.4	29.4
0°-60°	2971.3	43.4
0°-90°	3401.6	49.6
90°-120°	568.4	8.3
90°-150°	2508.2	36.6
90°-180°	3451.0	50.4
0°-180°	6852.5	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1967	1967	1967	1967	1967	
5°	2188	1971	1748	1971	2188	216
15°	2470	1870	1158	1870	2470	666
25°	1317	1663	839	1663	1317	625
35°	649	1372	619	1372	649	415
45°	451	1035	441	1035	451	349
55°	313	703	309	703	313	275
65°	163	426	184	426	163	166
75°	86	203	98	203	86	91
85°	25	44	26	44	25	27
90°	23	1	23	1	23	11
95°	37	55	37	55	37	34
105°	65	259	65	259	65	67
115°	70	490	70	490	70	175
125°	728	693	728	693	728	630
135°	885	857	885	857	885	682
145°	1010	994	1010	994	1010	631
155°	1096	1095	1096	1095	1096	506
165°	1151	1154	1151	1154	1151	325
175°	1173	1180	1173	1180	1173	112
180°	1178	1178	1178	1178	1178	



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6
2.5°	2046.4	2048.1	2049.7	2045.9	2045.9	2042.6	2035.5	2030.0	2014.7	2012.5	2012.5
5°	2188.0	2186.7	2189.3	2180.5	2168.2	2165.4	2152.5	2135.4	2117.6	2097.8	2093.7
7.5°	2328.8	2326.7	2321.2	2319.8	2310.3	2289.6	2268.8	2246.5	2217.0	2188.2	2173.6
10°	2399.9	2422.4	2408.7	2384.8	2389.6	2357.5	2340.4	2311.0	2286.4	2243.4	2233.8
12.5°	2469.8	2478.7	2474.3	2460.8	2454.6	2432.3	2409.2	2383.7	2338.3	2299.6	2266.0
15°	2469.5	2482.5	2485.9	2481.8	2485.3	2483.9	2471.6	2450.4	2410.7	2368.4	2331.5
17.5°	2287.2	2296.2	2318.6	2333.8	2353.0	2393.4	2413.3	2421.2	2415.3	2391.1	2365.1
20°	2082.8	2067.7	2130.6	2162.8	2190.0	2258.3	2317.1	2339.7	2375.9	2375.3	2368.4
22.5°	1793.1	1796.6	1856.2	1894.4	1974.2	2042.5	2109.4	2194.3	2264.4	2310.7	2337.8
25°	1317.4	1343.5	1402.8	1454.8	1543.6	1670.7	1786.2	1920.1	2046.6	2146.3	2241.3
27.5°	989.4	991.4	1038.5	1086.5	1139.2	1243.4	1388.8	1548.7	1728.9	1877.7	2048.7
30°	847.3	843.2	863.0	892.4	937.5	1018.2	1127.5	1284.7	1464.4	1688.5	1888.0
32.5°	746.7	747.0	761.9	783.6	821.1	875.5	950.4	1078.0	1247.9	1468.2	1702.2
35°	649.2	648.5	659.4	675.1	690.8	725.7	776.9	843.9	960.7	1166.4	1405.6
37.5°	579.2	582.2	587.5	597.4	614.7	634.1	664.9	709.8	793.1	914.7	1115.7
40°	539.8	541.2	548.7	556.9	567.1	582.2	607.4	643.7	704.5	801.6	948.4
42.5°	503.7	505.2	510.4	518.1	526.2	541.2	562.1	593.4	642.7	718.5	839.6
45°	451.0	451.0	455.8	459.2	468.1	481.7	498.8	524.8	558.9	615.0	695.6
47.5°	401.5	401.6	404.8	410.7	416.3	427.0	443.7	464.9	489.8	533.2	602.0
50°	373.1	373.8	375.9	380.6	384.1	393.6	406.6	425.0	451.0	484.5	541.9
52.5°	350.2	349.7	352.3	354.4	356.7	363.6	373.3	389.5	412.7	441.8	489.4
55°	313.0	310.2	314.3	317.7	319.8	322.5	328.0	338.2	358.0	382.6	418.2
57.5°	266.5	265.4	268.3	271.4	277.9	285.3	289.9	296.4	306.7	324.3	359.5
60°	228.2	228.2	234.3	236.4	244.0	253.5	263.1	268.6	278.8	290.4	316.4
62.5°	194.3	194.9	197.8	199.8	204.0	215.8	229.2	241.2	250.9	262.0	279.2
65°	162.6	164.0	164.0	165.3	168.1	170.9	176.3	185.8	203.0	218.6	231.7
67.5°	138.0	138.5	138.8	140.2	140.9	143.9	146.1	150.3	154.3	169.2	185.3
70°	121.6	123.7	123.0	124.4	125.0	126.4	129.1	131.2	137.3	140.8	150.3
72.5°	106.3	107.8	107.7	108.5	110.3	110.6	112.7	114.8	118.8	121.6	126.8
75°	86.1	85.4	86.1	87.5	88.2	88.8	88.8	91.6	93.6	96.3	99.8
77.5°	66.4	67.1	67.0	67.1	67.2	68.5	68.3	69.6	71.6	72.9	74.6
80°	53.3	53.9	53.3	53.9	54.7	55.4	54.7	55.4	57.4	58.8	58.8
82.5°	41.3	41.4	41.8	42.0	42.1	42.3	43.2	43.3	44.9	44.6	45.1
85°	24.6	23.9	23.9	23.9	24.6	25.3	24.6	24.6	25.3	25.3	25.3
87.5°	13.4	13.8	13.7	13.6	13.6	13.5	13.3	13.6	12.9	13.3	12.4
90°	23.0	22.6	22.2	21.8	21.5	20.9	19.9	18.9	18.0	17.0	15.5
92.5°	23.0	22.7	22.6	22.3	22.1	21.8	21.2	20.8	20.2	19.8	19.0
95°	36.6	36.8	37.0	37.2	37.4	37.0	36.1	35.1	34.2	33.3	31.9
97.5°	48.9	48.7	48.4	48.2	48.0	47.5	46.7	46.0	45.2	44.5	41.4
100°	57.1	56.7	56.4	55.9	55.6	54.7	53.1	51.6	50.1	48.6	45.4
102.5°	61.2	60.6	60.1	59.6	59.0	57.8	55.8	53.9	51.9	49.9	46.9
105°	64.7	64.0	63.2	62.5	61.7	60.3	58.2	56.2	54.0	52.0	49.7
107.5°	66.6	65.9	65.1	64.4	63.6	64.3	66.4	68.5	70.6	72.8	74.7
110°	67.3	66.5	65.8	65.0	64.3	73.4	92.3	111.2	130.2	149.1	203.8



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	68.0	67.4	66.8	66.2	65.5	99.8	168.9	237.9	307.0	376.1	389.6
115°	69.9	83.5	97.1	110.8	124.4	175.0	262.7	350.4	438.0	525.8	521.0
117.5°	285.3	330.1	374.9	419.6	464.5	497.5	518.7	539.8	561.1	582.3	579.1
120°	519.8	545.3	570.9	596.5	622.0	633.6	631.3	629.1	626.9	624.6	621.2
122.5°	648.6	653.5	658.5	663.4	668.4	670.2	668.9	667.5	666.1	664.8	661.0
125°	728.5	727.9	727.4	726.8	726.2	725.3	724.0	722.6	721.3	720.0	716.4
127.5°	778.9	778.8	778.7	778.6	778.5	777.5	775.5	773.6	771.7	769.7	767.0
130°	810.3	810.5	810.7	810.8	811.1	810.1	808.1	805.9	803.9	801.8	799.7
132.5°	841.0	841.2	841.3	841.5	841.8	841.0	839.2	837.4	835.6	833.8	831.7
135°	885.3	885.6	886.0	886.4	886.8	886.0	884.1	882.3	880.4	878.5	876.7
137.5°	925.7	926.3	926.9	927.6	928.3	927.6	925.8	923.9	922.1	920.2	918.3
140°	950.9	951.8	952.8	953.8	954.7	954.3	952.6	950.9	949.2	947.5	945.4
142.5°	975.4	976.4	977.3	978.3	979.2	978.9	977.4	975.8	974.3	972.7	970.4
145°	1009.7	1010.7	1011.6	1012.5	1013.5	1013.3	1012.0	1010.7	1009.3	1008.0	1004.8
147.5°	1039.8	1040.6	1041.4	1042.2	1043.0	1042.9	1042.0	1041.0	1040.0	1039.0	1035.8
150°	1058.3	1059.2	1060.2	1061.1	1062.0	1061.9	1060.8	1059.7	1058.5	1057.4	1054.4
152.5°	1074.0	1075.2	1076.5	1077.7	1079.0	1079.0	1077.8	1076.7	1075.6	1074.4	1071.6
155°	1095.7	1097.3	1098.8	1100.3	1101.8	1102.0	1100.8	1099.7	1098.6	1097.4	1095.2
157.5°	1115.7	1117.1	1118.7	1120.1	1121.6	1121.7	1120.4	1119.1	1117.8	1116.5	1114.9
160°	1127.3	1128.6	1129.9	1131.2	1132.6	1132.7	1131.5	1130.4	1129.3	1128.1	1127.0
162.5°	1136.8	1138.4	1140.1	1141.7	1143.4	1143.5	1142.2	1140.9	1139.6	1138.4	1137.4
165°	1151.1	1152.4	1153.8	1155.1	1156.5	1156.5	1155.1	1153.8	1152.4	1151.1	1150.6
167.5°	1160.2	1161.9	1163.6	1165.3	1167.0	1167.2	1165.8	1164.5	1163.1	1161.9	1161.4
170°	1165.6	1167.3	1169.0	1170.7	1172.4	1172.6	1171.3	1170.0	1168.7	1167.3	1167.0
172.5°	1169.7	1171.4	1173.1	1174.8	1176.5	1176.7	1175.4	1174.0	1172.8	1171.4	1171.0
175°	1173.3	1175.2	1177.1	1178.9	1180.9	1181.2	1179.8	1178.5	1177.1	1175.8	1175.5
177.5°	1175.5	1176.9	1178.2	1179.6	1181.0	1181.1	1180.0	1179.0	1177.9	1176.9	1176.7
180°	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6
2.5°	2013.7	2009.2	2005.5	1995.6	1990.7	1979.7	1978.1	1977.5	1963.4	1949.6	1945.8
5°	2082.8	2071.8	2055.5	2036.3	2016.5	1996.0	1982.4	1971.4	1944.0	1918.1	1903.1
7.5°	2152.5	2129.0	2100.7	2064.5	2034.3	2000.4	1975.2	1952.7	1913.9	1876.7	1851.6
10°	2204.4	2166.1	2128.5	2078.7	2039.7	2001.4	1966.0	1935.2	1891.4	1842.3	1807.4
12.5°	2236.7	2194.6	2142.8	2094.0	2043.5	1994.9	1947.3	1907.8	1856.5	1805.6	1764.2
15°	2280.3	2235.2	2172.3	2102.6	2037.6	1974.2	1919.5	1870.3	1803.3	1742.5	1691.9
17.5°	2316.0	2253.9	2186.4	2105.8	2030.6	1949.8	1879.5	1816.6	1742.0	1668.7	1609.1
20°	2327.4	2265.9	2188.0	2107.4	2018.6	1923.6	1847.7	1779.4	1699.4	1619.4	1551.1
22.5°	2320.3	2272.4	2185.9	2089.4	1998.3	1899.0	1813.3	1734.0	1645.3	1563.7	1484.4
25°	2272.1	2255.7	2173.6	2068.4	1964.5	1849.1	1750.0	1663.2	1562.1	1474.6	1388.5
27.5°	2159.5	2194.9	2144.1	2032.0	1916.6	1792.8	1681.4	1582.6	1477.7	1379.2	1293.4
30°	2051.4	2132.6	2110.8	2006.9	1877.8	1756.1	1631.1	1527.9	1415.9	1314.7	1230.0
32.5°	1903.2	2037.6	2058.9	1971.9	1838.4	1704.8	1573.7	1471.1	1354.1	1247.5	1164.9
35°	1667.3	1868.2	1960.4	1905.1	1771.2	1627.0	1491.7	1372.1	1254.5	1149.3	1067.4
37.5°	1385.9	1659.6	1813.3	1817.2	1694.3	1544.4	1397.0	1278.3	1158.0	1054.6	966.0
40°	1203.4	1499.9	1700.1	1744.5	1640.7	1478.7	1329.7	1208.8	1091.3	990.2	888.3
42.5°	1039.4	1334.8	1580.9	1658.1	1575.7	1414.8	1265.2	1138.8	1024.6	928.9	824.9
45°	840.5	1098.8	1370.0	1508.1	1462.3	1313.3	1155.5	1035.3	927.9	845.3	745.5
47.5°	709.0	891.1	1153.6	1340.2	1339.4	1203.5	1048.2	933.0	833.5	756.0	675.3
50°	634.1	792.6	1014.8	1226.5	1244.3	1130.2	982.6	868.5	775.6	694.3	629.4
52.5°	566.9	697.5	897.2	1100.3	1150.8	1052.0	908.8	803.4	713.3	638.5	582.9
55°	479.0	580.1	731.8	921.8	998.4	928.6	801.6	703.1	630.0	567.1	519.3
57.5°	405.2	481.1	602.8	755.7	844.9	801.0	696.2	616.3	553.7	496.8	459.1
60°	358.7	420.9	524.1	651.9	750.3	719.5	630.0	555.5	502.2	453.1	417.5
62.5°	315.0	368.5	456.9	560.6	650.8	638.1	565.0	502.5	455.8	411.0	380.8
65°	253.5	292.5	361.5	442.8	515.2	521.4	468.8	426.4	384.7	349.2	322.5
67.5°	201.9	227.3	275.9	344.4	398.7	418.0	385.9	353.6	320.5	293.0	269.9
70°	170.1	190.6	226.1	281.5	331.4	351.9	333.5	308.2	279.5	256.9	237.1
72.5°	137.9	157.8	184.0	224.7	267.4	289.6	283.2	265.0	241.7	223.0	204.3
75°	103.9	110.0	127.8	155.2	188.6	207.8	212.5	203.0	184.5	170.1	159.2
77.5°	76.8	80.5	89.0	103.3	125.2	142.2	149.3	148.1	135.5	127.1	116.8
80°	61.5	63.6	67.7	73.8	90.2	107.3	112.1	112.1	103.2	99.8	89.5
82.5°	46.7	48.2	50.7	54.1	61.8	76.7	82.0	83.1	77.5	72.9	64.9
85°	26.7	25.9	27.4	29.4	30.8	34.9	43.1	44.4	43.1	37.5	35.5
87.5°	12.1	12.3	12.0	11.1	11.2	11.4	13.7	16.1	14.3	13.0	12.4
90°	14.0	12.5	11.0	9.2	7.1	5.0	2.9	0.9	2.9	5.0	7.1
92.5°	18.3	17.5	16.8	16.5	16.7	16.9	17.0	17.2	17.0	16.9	16.7
95°	30.6	29.2	27.9	30.4	36.6	42.9	49.1	55.4	49.1	42.9	36.6
97.5°	38.3	35.3	32.2	39.5	57.1	74.7	92.3	109.9	92.3	74.7	57.1
100°	42.1	38.9	35.7	47.1	73.0	98.9	124.8	150.8	124.8	98.9	73.0
102.5°	103.8	130.7	157.7	173.8	179.3	184.9	190.3	195.8	190.3	184.9	179.3
105°	155.3	207.1	258.8	281.8	276.1	270.4	264.7	259.0	264.7	270.4	276.1
107.5°	196.7	258.8	320.7	349.5	344.8	340.3	335.7	331.1	335.7	340.3	344.8
110°	258.6	313.3	368.0	393.3	389.4	385.4	381.5	377.5	381.5	385.4	389.4



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	403.1	416.7	430.2	435.2	431.7	428.1	424.6	421.1	424.6	428.1	431.7
115°	516.2	511.5	506.8	502.8	499.6	496.4	493.1	489.9	493.1	496.4	499.6
117.5°	575.8	572.6	569.3	565.9	562.2	558.7	555.1	551.4	555.1	558.7	562.2
120°	617.8	614.3	610.9	607.8	604.9	602.1	599.3	596.5	599.3	602.1	604.9
122.5°	657.4	653.6	650.0	646.6	643.5	640.6	637.6	634.6	637.6	640.6	643.5
125°	712.8	709.2	705.6	702.6	700.1	697.7	695.2	692.7	695.2	697.7	700.1
127.5°	764.4	761.7	759.0	756.3	753.6	750.8	748.1	745.4	748.1	750.8	753.6
130°	797.6	795.5	793.4	790.9	787.8	784.9	781.9	778.8	781.9	784.9	787.8
132.5°	829.6	827.6	825.5	823.1	820.6	818.1	815.5	812.9	815.5	818.1	820.6
135°	875.0	873.3	871.6	869.3	866.3	863.3	860.2	857.2	860.2	863.3	866.3
137.5°	916.3	914.4	912.5	910.4	908.4	906.2	904.1	902.0	904.1	906.2	908.4
140°	943.3	941.2	939.1	937.4	935.9	934.3	932.8	931.3	932.8	934.3	935.9
142.5°	968.0	965.5	963.1	961.3	959.9	958.6	957.2	955.8	957.2	958.6	959.9
145°	1001.6	998.4	995.1	993.6	993.8	994.0	994.2	994.3	994.2	994.0	993.8
147.5°	1032.6	1029.5	1026.3	1025.0	1025.7	1026.4	1027.2	1028.0	1027.2	1026.4	1025.7
150°	1051.3	1048.3	1045.3	1044.5	1045.8	1047.0	1048.4	1049.7	1048.4	1047.0	1045.8
152.5°	1068.7	1065.8	1062.9	1062.2	1063.7	1065.1	1066.7	1068.2	1066.7	1065.1	1063.7
155°	1092.9	1090.7	1088.3	1088.1	1089.8	1091.5	1093.1	1094.9	1093.1	1091.5	1089.8
157.5°	1113.4	1111.8	1110.2	1110.1	1111.5	1112.9	1114.5	1115.9	1114.5	1112.9	1111.5
160°	1125.9	1124.7	1123.6	1123.6	1124.7	1125.9	1127.0	1128.1	1127.0	1125.9	1124.7
162.5°	1136.4	1135.4	1134.4	1134.5	1135.6	1136.8	1137.9	1139.1	1137.9	1136.8	1135.6
165°	1150.0	1149.4	1148.9	1149.1	1150.3	1151.4	1152.5	1153.7	1152.5	1151.4	1150.3
167.5°	1160.8	1160.3	1159.8	1160.0	1161.2	1162.3	1163.4	1164.6	1163.4	1162.3	1161.2
170°	1166.5	1166.2	1165.8	1166.2	1167.3	1168.5	1169.6	1170.7	1169.6	1168.5	1167.3
172.5°	1170.6	1170.3	1169.9	1170.3	1171.4	1172.5	1173.7	1174.8	1173.7	1172.5	1171.4
175°	1175.1	1174.7	1174.3	1174.8	1176.2	1177.4	1178.8	1180.1	1178.8	1177.4	1176.2
177.5°	1176.5	1176.4	1176.3	1176.7	1177.8	1178.8	1179.9	1181.0	1179.9	1178.8	1177.8
180°	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6
2.5°	1938.8	1934.9	1927.8	1916.8	1910.3	1898.8	1891.1	1895.5	1896.7	1895.5	1894.4
5°	1886.7	1872.3	1852.5	1833.4	1815.6	1796.4	1785.6	1780.7	1771.2	1765.7	1763.0
7.5°	1823.6	1798.9	1770.9	1737.6	1709.2	1679.6	1664.5	1656.9	1637.4	1626.7	1617.4
10°	1776.6	1737.7	1709.7	1666.0	1639.3	1600.4	1573.7	1574.4	1547.7	1532.7	1521.8
12.5°	1724.7	1681.9	1635.3	1596.0	1559.0	1527.7	1495.5	1482.6	1454.3	1439.8	1410.2
15°	1638.6	1588.8	1539.5	1486.2	1448.7	1400.2	1353.7	1297.0	1251.2	1211.6	1200.6
17.5°	1544.6	1482.8	1433.5	1370.9	1306.5	1224.9	1171.1	1138.2	1110.5	1089.7	1074.1
20°	1480.1	1417.2	1364.6	1270.3	1183.5	1128.2	1088.5	1063.3	1034.6	1012.0	999.7
22.5°	1412.3	1346.7	1275.0	1169.7	1102.1	1057.7	1022.3	993.3	973.8	956.3	945.0
25°	1316.1	1244.3	1126.1	1053.6	999.0	952.5	927.9	910.2	889.7	865.8	854.9
27.5°	1214.4	1100.3	1015.4	961.5	909.4	879.1	857.0	830.5	812.2	801.4	790.1
30°	1138.4	1024.3	958.1	899.3	862.4	828.8	802.9	787.9	770.1	751.6	744.1
32.5°	1053.6	962.5	899.0	850.1	812.6	784.1	763.6	739.2	726.4	715.1	699.3
35°	948.4	879.4	821.4	781.8	746.2	723.0	699.0	684.7	661.5	651.9	645.8
37.5°	859.3	799.5	756.2	714.3	686.2	660.5	645.9	623.0	613.0	599.7	586.7
40°	809.0	750.3	708.6	674.4	643.0	623.8	605.4	587.0	571.9	565.8	550.1
42.5°	757.7	709.8	668.2	630.7	609.7	589.4	566.1	552.5	537.0	527.0	517.3
45°	686.7	644.4	608.9	578.1	554.8	533.7	518.6	496.1	487.2	467.4	459.2
47.5°	624.5	585.1	551.2	521.9	499.3	485.4	463.4	445.8	431.6	419.5	408.9
50°	580.1	547.3	514.5	488.6	468.1	448.3	425.7	416.8	394.9	388.8	382.6
52.5°	539.7	508.5	478.5	453.1	432.6	413.3	393.4	381.8	367.1	361.0	356.4
55°	483.1	453.1	424.4	401.8	381.3	361.5	349.2	334.8	328.0	323.2	317.7
57.5°	426.2	399.2	377.2	354.4	333.8	318.0	303.8	295.2	288.1	281.8	275.3
60°	390.2	364.2	344.4	323.2	302.0	289.0	278.1	267.9	259.7	250.1	247.4
62.5°	351.9	329.2	311.0	290.4	272.0	260.1	249.7	240.0	230.2	216.2	212.4
65°	299.3	281.5	262.4	245.3	228.9	217.3	202.2	191.4	187.3	185.8	185.2
67.5°	251.7	235.0	218.6	201.0	186.1	175.3	167.7	166.0	163.2	162.4	160.4
70°	220.1	204.3	187.9	171.5	157.2	155.2	152.4	149.6	146.2	144.9	143.5
72.5°	191.6	175.3	158.9	145.8	139.6	137.1	134.4	131.6	129.3	128.0	127.1
75°	147.0	131.9	120.9	116.2	112.7	110.7	106.6	104.5	103.2	101.1	100.4
77.5°	105.8	97.3	92.3	89.3	85.7	83.5	81.1	79.1	77.7	77.2	76.2
80°	80.6	76.5	73.1	69.0	67.7	64.9	64.2	62.2	62.9	60.8	60.8
82.5°	62.6	57.4	54.6	52.6	51.3	49.0	48.4	47.4	47.5	46.0	46.0
85°	32.1	30.8	29.4	28.0	28.0	25.9	26.7	25.9	25.9	24.6	23.9
87.5°	12.2	12.0	11.2	11.6	11.9	11.6	11.8	11.4	11.6	11.9	11.4
90°	9.2	11.0	12.5	14.0	15.5	17.0	18.0	18.9	19.9	20.9	21.5
92.5°	16.5	16.8	17.5	18.3	19.0	19.8	20.2	20.8	21.2	21.8	22.1
95°	30.4	27.9	29.2	30.6	31.9	33.3	34.2	35.1	36.1	37.0	37.4
97.5°	39.5	32.2	35.3	38.3	41.4	44.5	45.2	46.0	46.7	47.5	48.0
100°	47.1	35.7	38.9	42.1	45.4	48.6	50.1	51.6	53.1	54.7	55.6
102.5°	173.8	157.7	130.7	103.8	76.9	49.9	51.9	53.9	55.8	57.8	59.0
105°	281.8	258.8	207.1	155.3	103.7	52.0	54.0	56.2	58.2	60.3	61.7
107.5°	349.5	320.7	258.8	196.7	134.7	72.8	70.6	68.5	66.4	64.3	63.6
110°	393.3	368.0	313.3	258.6	203.8	149.1	130.2	111.2	92.3	73.4	64.3



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	435.2	430.2	416.7	403.1	389.6	376.1	307.0	237.9	168.9	99.8	65.5
115°	502.8	506.8	511.5	516.2	521.0	525.8	438.0	350.4	262.7	175.0	124.4
117.5°	565.9	569.3	572.6	575.8	579.1	582.3	561.1	539.8	518.7	497.5	464.5
120°	607.8	610.9	614.3	617.8	621.2	624.6	626.9	629.1	631.3	633.6	622.0
122.5°	646.6	650.0	653.6	657.4	661.0	664.8	666.1	667.5	668.9	670.2	668.4
125°	702.6	705.6	709.2	712.8	716.4	720.0	721.3	722.6	724.0	725.3	726.2
127.5°	756.3	759.0	761.7	764.4	767.0	769.7	771.7	773.6	775.5	777.5	778.5
130°	790.9	793.4	795.5	797.6	799.7	801.8	803.9	805.9	808.1	810.1	811.1
132.5°	823.1	825.5	827.6	829.6	831.7	833.8	835.6	837.4	839.2	841.0	841.8
135°	869.3	871.6	873.3	875.0	876.7	878.5	880.4	882.3	884.1	886.0	886.8
137.5°	910.4	912.5	914.4	916.3	918.3	920.2	922.1	923.9	925.8	927.6	928.3
140°	937.4	939.1	941.2	943.3	945.4	947.5	949.2	950.9	952.6	954.3	954.7
142.5°	961.3	963.1	965.5	968.0	970.4	972.7	974.3	975.8	977.4	978.9	979.2
145°	993.6	995.1	998.4	1001.6	1004.8	1008.0	1009.3	1010.7	1012.0	1013.3	1013.5
147.5°	1025.0	1026.3	1029.5	1032.6	1035.8	1039.0	1040.0	1041.0	1042.0	1042.9	1043.0
150°	1044.5	1045.3	1048.3	1051.3	1054.4	1057.4	1058.5	1059.7	1060.8	1061.9	1062.0
152.5°	1062.2	1062.9	1065.8	1068.7	1071.6	1074.4	1075.6	1076.7	1077.8	1079.0	1079.0
155°	1088.1	1088.3	1090.7	1092.9	1095.2	1097.4	1098.6	1099.7	1100.8	1102.0	1101.8
157.5°	1110.1	1110.2	1111.8	1113.4	1114.9	1116.5	1117.8	1119.1	1120.4	1121.7	1121.6
160°	1123.6	1123.6	1124.7	1125.9	1127.0	1128.1	1129.3	1130.4	1131.5	1132.7	1132.6
162.5°	1134.5	1134.4	1135.4	1136.4	1137.4	1138.4	1139.6	1140.9	1142.2	1143.5	1143.4
165°	1149.1	1148.9	1149.4	1150.0	1150.6	1151.1	1152.4	1153.8	1155.1	1156.5	1156.5
167.5°	1160.0	1159.8	1160.3	1160.8	1161.4	1161.9	1163.1	1164.5	1165.8	1167.2	1167.0
170°	1166.2	1165.8	1166.2	1166.5	1167.0	1167.3	1168.7	1170.0	1171.3	1172.6	1172.4
172.5°	1170.3	1169.9	1170.3	1170.6	1171.0	1171.4	1172.8	1174.0	1175.4	1176.7	1176.5
175°	1174.8	1174.3	1174.7	1175.1	1175.5	1175.8	1177.1	1178.5	1179.8	1181.2	1180.9
177.5°	1176.7	1176.3	1176.4	1176.5	1176.7	1176.9	1177.9	1179.0	1180.0	1181.1	1181.0
180°	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6
2.5°	1888.5	1889.5	1887.9	1889.0	1887.9	1889.5	1888.5	1894.4	1895.5	1896.7	1895.5
5°	1759.5	1751.3	1750.0	1747.9	1750.0	1751.3	1759.5	1763.0	1765.7	1771.2	1780.7
7.5°	1605.7	1604.5	1601.1	1596.3	1601.1	1604.5	1605.7	1617.4	1626.7	1637.4	1656.9
10°	1506.7	1503.3	1502.6	1497.8	1502.6	1503.3	1506.7	1521.8	1532.7	1547.7	1574.4
12.5°	1390.8	1368.9	1366.5	1354.6	1366.5	1368.9	1390.8	1410.2	1439.8	1454.3	1482.6
15°	1184.2	1180.1	1166.4	1157.5	1166.4	1180.1	1184.2	1200.6	1211.6	1251.2	1297.0
17.5°	1066.1	1052.8	1048.5	1046.6	1048.5	1052.8	1066.1	1074.1	1089.7	1110.5	1138.2
20°	990.2	977.9	975.8	974.5	975.8	977.9	990.2	999.7	1012.0	1034.6	1063.3
22.5°	937.6	924.8	919.4	915.3	919.4	924.8	937.6	945.0	956.3	973.8	993.3
25°	848.0	843.2	840.5	839.1	840.5	843.2	848.0	854.9	865.8	889.7	910.2
27.5°	777.9	767.4	765.4	761.8	765.4	767.4	777.9	790.1	801.4	812.2	830.5
30°	738.0	734.6	729.8	725.7	729.8	734.6	738.0	744.1	751.6	770.1	787.9
32.5°	691.0	688.1	683.9	682.0	683.9	688.1	691.0	699.3	715.1	726.4	739.2
35°	638.9	629.4	625.3	619.1	625.3	629.4	638.9	645.8	651.9	661.5	684.7
37.5°	583.8	578.8	573.0	575.1	573.0	578.8	583.8	586.7	599.7	613.0	623.0
40°	541.2	537.8	536.5	535.7	536.5	537.8	541.2	550.1	565.8	571.9	587.0
42.5°	507.3	497.8	494.3	494.2	494.3	497.8	507.3	517.3	527.0	537.0	552.5
45°	455.8	446.9	440.8	441.4	440.8	446.9	455.8	459.2	467.4	487.2	496.1
47.5°	403.1	402.8	399.0	400.1	399.0	402.8	403.1	408.9	419.5	431.6	445.8
50°	377.9	373.8	371.0	371.8	371.0	373.8	377.9	382.6	388.8	394.9	416.8
52.5°	353.8	350.3	348.1	351.0	348.1	350.3	353.8	356.4	361.0	367.1	381.8
55°	314.3	310.2	309.5	308.9	309.5	310.2	314.3	317.7	323.2	328.0	334.8
57.5°	270.2	267.4	263.3	261.5	263.3	267.4	270.2	275.3	281.8	288.1	295.2
60°	238.4	233.0	226.1	225.5	226.1	233.0	238.4	247.4	250.1	259.7	267.9
62.5°	209.5	208.4	207.1	206.9	207.1	208.4	209.5	212.4	216.2	230.2	240.0
65°	183.8	183.2	183.8	184.5	183.8	183.2	183.8	185.2	185.8	187.3	191.4
67.5°	160.2	158.9	157.7	158.3	157.7	158.9	160.2	160.4	162.4	163.2	166.0
70°	142.1	141.4	140.8	140.8	140.8	141.4	142.1	143.5	144.9	146.2	149.6
72.5°	124.7	124.5	123.9	123.2	123.9	124.5	124.7	127.1	128.0	129.3	131.6
75°	99.8	98.4	98.4	98.4	98.4	98.4	99.8	100.4	101.1	103.2	104.5
77.5°	76.0	75.3	74.6	74.1	74.6	75.3	76.0	76.2	77.2	77.7	79.1
80°	60.1	59.5	58.8	58.8	58.8	59.5	60.1	60.8	60.8	62.9	62.2
82.5°	45.9	45.2	45.1	44.6	45.1	45.2	45.9	46.0	46.0	47.5	47.4
85°	24.6	25.3	24.6	25.9	24.6	25.3	24.6	23.9	24.6	25.9	25.9
87.5°	11.5	11.0	11.6	11.1	11.6	11.0	11.5	11.4	11.9	11.6	11.4
90°	21.8	22.2	22.6	23.0	22.6	22.2	21.8	21.5	20.9	19.9	18.9
92.5°	22.3	22.6	22.7	23.0	22.7	22.6	22.3	22.1	21.8	21.2	20.8
95°	37.2	37.0	36.8	36.6	36.8	37.0	37.2	37.4	37.0	36.1	35.1
97.5°	48.2	48.4	48.7	48.9	48.7	48.4	48.2	48.0	47.5	46.7	46.0
100°	55.9	56.4	56.7	57.1	56.7	56.4	55.9	55.6	54.7	53.1	51.6
102.5°	59.6	60.1	60.6	61.2	60.6	60.1	59.6	59.0	57.8	55.8	53.9
105°	62.5	63.2	64.0	64.7	64.0	63.2	62.5	61.7	60.3	58.2	56.2
107.5°	64.4	65.1	65.9	66.6	65.9	65.1	64.4	63.6	64.3	66.4	68.5
110°	65.0	65.8	66.5	67.3	66.5	65.8	65.0	64.3	73.4	92.3	111.2



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	66.2	66.8	67.4	68.0	67.4	66.8	66.2	65.5	99.8	168.9	237.9
115°	110.8	97.1	83.5	69.9	83.5	97.1	110.8	124.4	175.0	262.7	350.4
117.5°	419.6	374.9	330.1	285.3	330.1	374.9	419.6	464.5	497.5	518.7	539.8
120°	596.5	570.9	545.3	519.8	545.3	570.9	596.5	622.0	633.6	631.3	629.1
122.5°	663.4	658.5	653.5	648.6	653.5	658.5	663.4	668.4	670.2	668.9	667.5
125°	726.8	727.4	727.9	728.5	727.9	727.4	726.8	726.2	725.3	724.0	722.6
127.5°	778.6	778.7	778.8	778.9	778.8	778.7	778.6	778.5	777.5	775.5	773.6
130°	810.8	810.7	810.5	810.3	810.5	810.7	810.8	811.1	810.1	808.1	805.9
132.5°	841.5	841.3	841.2	841.0	841.2	841.3	841.5	841.8	841.0	839.2	837.4
135°	886.4	886.0	885.6	885.3	885.6	886.0	886.4	886.8	886.0	884.1	882.3
137.5°	927.6	926.9	926.3	925.7	926.3	926.9	927.6	928.3	927.6	925.8	923.9
140°	953.8	952.8	951.8	950.9	951.8	952.8	953.8	954.7	954.3	952.6	950.9
142.5°	978.3	977.3	976.4	975.4	976.4	977.3	978.3	979.2	978.9	977.4	975.8
145°	1012.5	1011.6	1010.7	1009.7	1010.7	1011.6	1012.5	1013.5	1013.3	1012.0	1010.7
147.5°	1042.2	1041.4	1040.6	1039.8	1040.6	1041.4	1042.2	1043.0	1042.9	1042.0	1041.0
150°	1061.1	1060.2	1059.2	1058.3	1059.2	1060.2	1061.1	1062.0	1061.9	1060.8	1059.7
152.5°	1077.7	1076.5	1075.2	1074.0	1075.2	1076.5	1077.7	1079.0	1079.0	1077.8	1076.7
155°	1100.3	1098.8	1097.3	1095.7	1097.3	1098.8	1100.3	1101.8	1102.0	1100.8	1099.7
157.5°	1120.1	1118.7	1117.1	1115.7	1117.1	1118.7	1120.1	1121.6	1121.7	1120.4	1119.1
160°	1131.2	1129.9	1128.6	1127.3	1128.6	1129.9	1131.2	1132.6	1132.7	1131.5	1130.4
162.5°	1141.7	1140.1	1138.4	1136.8	1138.4	1140.1	1141.7	1143.4	1143.5	1142.2	1140.9
165°	1155.1	1153.8	1152.4	1151.1	1152.4	1153.8	1155.1	1156.5	1156.5	1155.1	1153.8
167.5°	1165.3	1163.6	1161.9	1160.2	1161.9	1163.6	1165.3	1167.0	1167.2	1165.8	1164.5
170°	1170.7	1169.0	1167.3	1165.6	1167.3	1169.0	1170.7	1172.4	1172.6	1171.3	1170.0
172.5°	1174.8	1173.1	1171.4	1169.7	1171.4	1173.1	1174.8	1176.5	1176.7	1175.4	1174.0
175°	1178.9	1177.1	1175.2	1173.3	1175.2	1177.1	1178.9	1180.9	1181.2	1179.8	1178.5
177.5°	1179.6	1178.2	1176.9	1175.5	1176.9	1178.2	1179.6	1181.0	1181.1	1180.0	1179.0
180°	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6
2.5°	1891.1	1898.8	1910.3	1916.8	1927.8	1934.9	1938.8	1945.8	1949.6	1963.4	1977.5
5°	1785.6	1796.4	1815.6	1833.4	1852.5	1872.3	1886.7	1903.1	1918.1	1944.0	1971.4
7.5°	1664.5	1679.6	1709.2	1737.6	1770.9	1798.9	1823.6	1851.6	1876.7	1913.9	1952.7
10°	1573.7	1600.4	1639.3	1666.0	1709.7	1737.7	1776.6	1807.4	1842.3	1891.4	1935.2
12.5°	1495.5	1527.7	1559.0	1596.0	1635.3	1681.9	1724.7	1764.2	1805.6	1856.5	1907.8
15°	1353.7	1400.2	1448.7	1486.2	1539.5	1588.8	1638.6	1691.9	1742.5	1803.3	1870.3
17.5°	1171.1	1224.9	1306.5	1370.9	1433.5	1482.8	1544.6	1609.1	1668.7	1742.0	1816.6
20°	1088.5	1128.2	1183.5	1270.3	1364.6	1417.2	1480.1	1551.1	1619.4	1699.4	1779.4
22.5°	1022.3	1057.7	1102.1	1169.7	1275.0	1346.7	1412.3	1484.4	1563.7	1645.3	1734.0
25°	927.9	952.5	999.0	1053.6	1126.1	1244.3	1316.1	1388.5	1474.6	1562.1	1663.2
27.5°	857.0	879.1	909.4	961.5	1015.4	1100.3	1214.4	1293.4	1379.2	1477.7	1582.6
30°	802.9	828.8	862.4	899.3	958.1	1024.3	1138.4	1230.0	1314.7	1415.9	1527.9
32.5°	763.6	784.1	812.6	850.1	899.0	962.5	1053.6	1164.9	1247.5	1354.1	1471.1
35°	699.0	723.0	746.2	781.8	821.4	879.4	948.4	1067.4	1149.3	1254.5	1372.1
37.5°	645.9	660.5	686.2	714.3	756.2	799.5	859.3	966.0	1054.6	1158.0	1278.3
40°	605.4	623.8	643.0	674.4	708.6	750.3	809.0	888.3	990.2	1091.3	1208.8
42.5°	566.1	589.4	609.7	630.7	668.2	709.8	757.7	824.9	928.9	1024.6	1138.8
45°	518.6	533.7	554.8	578.1	608.9	644.4	686.7	745.5	845.3	927.9	1035.3
47.5°	463.4	485.4	499.3	521.9	551.2	585.1	624.5	675.3	756.0	833.5	933.0
50°	425.7	448.3	468.1	488.6	514.5	547.3	580.1	629.4	694.3	775.6	868.5
52.5°	393.4	413.3	432.6	453.1	478.5	508.5	539.7	582.9	638.5	713.3	803.4
55°	349.2	361.5	381.3	401.8	424.4	453.1	483.1	519.3	567.1	630.0	703.1
57.5°	303.8	318.0	333.8	354.4	377.2	399.2	426.2	459.1	496.8	553.7	616.3
60°	278.1	289.0	302.0	323.2	344.4	364.2	390.2	417.5	453.1	502.2	555.5
62.5°	249.7	260.1	272.0	290.4	311.0	329.2	351.9	380.8	411.0	455.8	502.5
65°	202.2	217.3	228.9	245.3	262.4	281.5	299.3	322.5	349.2	384.7	426.4
67.5°	167.7	175.3	186.1	201.0	218.6	235.0	251.7	269.9	293.0	320.5	353.6
70°	152.4	155.2	157.2	171.5	187.9	204.3	220.1	237.1	256.9	279.5	308.2
72.5°	134.4	137.1	139.6	145.8	158.9	175.3	191.6	204.3	223.0	241.7	265.0
75°	106.6	110.7	112.7	116.2	120.9	131.9	147.0	159.2	170.1	184.5	203.0
77.5°	81.1	83.5	85.7	89.3	92.3	97.3	105.8	116.8	127.1	135.5	148.1
80°	64.2	64.9	67.7	69.0	73.1	76.5	80.6	89.5	99.8	103.2	112.1
82.5°	48.4	49.0	51.3	52.6	54.6	57.4	62.6	64.9	72.9	77.5	83.1
85°	26.7	25.9	28.0	28.0	29.4	30.8	32.1	35.5	37.5	43.1	44.4
87.5°	11.8	11.6	11.9	11.6	11.2	12.0	12.2	12.4	13.0	14.3	16.1
90°	18.0	17.0	15.5	14.0	12.5	11.0	9.2	7.1	5.0	2.9	0.9
92.5°	20.2	19.8	19.0	18.3	17.5	16.8	16.5	16.7	16.9	17.0	17.2
95°	34.2	33.3	31.9	30.6	29.2	27.9	30.4	36.6	42.9	49.1	55.4
97.5°	45.2	44.5	41.4	38.3	35.3	32.2	39.5	57.1	74.7	92.3	109.9
100°	50.1	48.6	45.4	42.1	38.9	35.7	47.1	73.0	98.9	124.8	150.8
102.5°	51.9	49.9	76.9	103.8	130.7	157.7	173.8	179.3	184.9	190.3	195.8
105°	54.0	52.0	103.7	155.3	207.1	258.8	281.8	276.1	270.4	264.7	259.0
107.5°	70.6	72.8	134.7	196.7	258.8	320.7	349.5	344.8	340.3	335.7	331.1
110°	130.2	149.1	203.8	258.6	313.3	368.0	393.3	389.4	385.4	381.5	377.5



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	307.0	376.1	389.6	403.1	416.7	430.2	435.2	431.7	428.1	424.6	421.1
115°	438.0	525.8	521.0	516.2	511.5	506.8	502.8	499.6	496.4	493.1	489.9
117.5°	561.1	582.3	579.1	575.8	572.6	569.3	565.9	562.2	558.7	555.1	551.4
120°	626.9	624.6	621.2	617.8	614.3	610.9	607.8	604.9	602.1	599.3	596.5
122.5°	666.1	664.8	661.0	657.4	653.6	650.0	646.6	643.5	640.6	637.6	634.6
125°	721.3	720.0	716.4	712.8	709.2	705.6	702.6	700.1	697.7	695.2	692.7
127.5°	771.7	769.7	767.0	764.4	761.7	759.0	756.3	753.6	750.8	748.1	745.4
130°	803.9	801.8	799.7	797.6	795.5	793.4	790.9	787.8	784.9	781.9	778.8
132.5°	835.6	833.8	831.7	829.6	827.6	825.5	823.1	820.6	818.1	815.5	812.9
135°	880.4	878.5	876.7	875.0	873.3	871.6	869.3	866.3	863.3	860.2	857.2
137.5°	922.1	920.2	918.3	916.3	914.4	912.5	910.4	908.4	906.2	904.1	902.0
140°	949.2	947.5	945.4	943.3	941.2	939.1	937.4	935.9	934.3	932.8	931.3
142.5°	974.3	972.7	970.4	968.0	965.5	963.1	961.3	959.9	958.6	957.2	955.8
145°	1009.3	1008.0	1004.8	1001.6	998.4	995.1	993.6	993.8	994.0	994.2	994.3
147.5°	1040.0	1039.0	1035.8	1032.6	1029.5	1026.3	1025.0	1025.7	1026.4	1027.2	1028.0
150°	1058.5	1057.4	1054.4	1051.3	1048.3	1045.3	1044.5	1045.8	1047.0	1048.4	1049.7
152.5°	1075.6	1074.4	1071.6	1068.7	1065.8	1062.9	1062.2	1063.7	1065.1	1066.7	1068.2
155°	1098.6	1097.4	1095.2	1092.9	1090.7	1088.3	1088.1	1089.8	1091.5	1093.1	1094.9
157.5°	1117.8	1116.5	1114.9	1113.4	1111.8	1110.2	1110.1	1111.5	1112.9	1114.5	1115.9
160°	1129.3	1128.1	1127.0	1125.9	1124.7	1123.6	1123.6	1124.7	1125.9	1127.0	1128.1
162.5°	1139.6	1138.4	1137.4	1136.4	1135.4	1134.4	1134.5	1135.6	1136.8	1137.9	1139.1
165°	1152.4	1151.1	1150.6	1150.0	1149.4	1148.9	1149.1	1150.3	1151.4	1152.5	1153.7
167.5°	1163.1	1161.9	1161.4	1160.8	1160.3	1159.8	1160.0	1161.2	1162.3	1163.4	1164.6
170°	1168.7	1167.3	1167.0	1166.5	1166.2	1165.8	1166.2	1167.3	1168.5	1169.6	1170.7
172.5°	1172.8	1171.4	1171.0	1170.6	1170.3	1169.9	1170.3	1171.4	1172.5	1173.7	1174.8
175°	1177.1	1175.8	1175.5	1175.1	1174.7	1174.3	1174.8	1176.2	1177.4	1178.8	1180.1
177.5°	1177.9	1176.9	1176.7	1176.5	1176.4	1176.3	1176.7	1177.8	1178.8	1179.9	1181.0
180°	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6
2.5°	1978.1	1979.7	1990.7	1995.6	2005.5	2009.2	2013.7	2012.5	2012.5	2014.7	2030.0
5°	1982.4	1996.0	2016.5	2036.3	2055.5	2071.8	2082.8	2093.7	2097.8	2117.6	2135.4
7.5°	1975.2	2000.4	2034.3	2064.5	2100.7	2129.0	2152.5	2173.6	2188.2	2217.0	2246.5
10°	1966.0	2001.4	2039.7	2078.7	2128.5	2166.1	2204.4	2233.8	2243.4	2286.4	2311.0
12.5°	1947.3	1994.9	2043.5	2094.0	2142.8	2194.6	2236.7	2266.0	2299.6	2338.3	2383.7
15°	1919.5	1974.2	2037.6	2102.6	2172.3	2235.2	2280.3	2331.5	2368.4	2410.7	2450.4
17.5°	1879.5	1949.8	2030.6	2105.8	2186.4	2253.9	2316.0	2365.1	2391.1	2415.3	2421.2
20°	1847.7	1923.6	2018.6	2107.4	2188.0	2265.9	2327.4	2368.4	2375.3	2375.9	2339.7
22.5°	1813.3	1899.0	1998.3	2089.4	2185.9	2272.4	2320.3	2337.8	2310.7	2264.4	2194.3
25°	1750.0	1849.1	1964.5	2068.4	2173.6	2255.7	2272.1	2241.3	2146.3	2046.6	1920.1
27.5°	1681.4	1792.8	1916.6	2032.0	2144.1	2194.9	2159.5	2048.7	1877.7	1728.9	1548.7
30°	1631.1	1756.1	1877.8	2006.9	2110.8	2132.6	2051.4	1888.0	1688.5	1464.4	1284.7
32.5°	1573.7	1704.8	1838.4	1971.9	2058.9	2037.6	1903.2	1702.2	1468.2	1247.9	1078.0
35°	1491.7	1627.0	1771.2	1905.1	1960.4	1868.2	1667.3	1405.6	1166.4	960.7	843.9
37.5°	1397.0	1544.4	1694.3	1817.2	1813.3	1659.6	1385.9	1115.7	914.7	793.1	709.8
40°	1329.7	1478.7	1640.7	1744.5	1700.1	1499.9	1203.4	948.4	801.6	704.5	643.7
42.5°	1265.2	1414.8	1575.7	1658.1	1580.9	1334.8	1039.4	839.6	718.5	642.7	593.4
45°	1155.5	1313.3	1462.3	1508.1	1370.0	1098.8	840.5	695.6	615.0	558.9	524.8
47.5°	1048.2	1203.5	1339.4	1340.2	1153.6	891.1	709.0	602.0	533.2	489.8	464.9
50°	982.6	1130.2	1244.3	1226.5	1014.8	792.6	634.1	541.9	484.5	451.0	425.0
52.5°	908.8	1052.0	1150.8	1100.3	897.2	697.5	566.9	489.4	441.8	412.7	389.5
55°	801.6	928.6	998.4	921.8	731.8	580.1	479.0	418.2	382.6	358.0	338.2
57.5°	696.2	801.0	844.9	755.7	602.8	481.1	405.2	359.5	324.3	306.7	296.4
60°	630.0	719.5	750.3	651.9	524.1	420.9	358.7	316.4	290.4	278.8	268.6
62.5°	565.0	638.1	650.8	560.6	456.9	368.5	315.0	279.2	262.0	250.9	241.2
65°	468.8	521.4	515.2	442.8	361.5	292.5	253.5	231.7	218.6	203.0	185.8
67.5°	385.9	418.0	398.7	344.4	275.9	227.3	201.9	185.3	169.2	154.3	150.3
70°	333.5	351.9	331.4	281.5	226.1	190.6	170.1	150.3	140.8	137.3	131.2
72.5°	283.2	289.6	267.4	224.7	184.0	157.8	137.9	126.8	121.6	118.8	114.8
75°	212.5	207.8	188.6	155.2	127.8	110.0	103.9	99.8	96.3	93.6	91.6
77.5°	149.3	142.2	125.2	103.3	89.0	80.5	76.8	74.6	72.9	71.6	69.6
80°	112.1	107.3	90.2	73.8	67.7	63.6	61.5	58.8	58.8	57.4	55.4
82.5°	82.0	76.7	61.8	54.1	50.7	48.2	46.7	45.1	44.6	44.9	43.3
85°	43.1	34.9	30.8	29.4	27.4	25.9	26.7	25.3	25.3	25.3	24.6
87.5°	13.7	11.4	11.2	11.1	12.0	12.3	12.1	12.4	13.3	12.9	13.6
90°	2.9	5.0	7.1	9.2	11.0	12.5	14.0	15.5	17.0	18.0	18.9
92.5°	17.0	16.9	16.7	16.5	16.8	17.5	18.3	19.0	19.8	20.2	20.8
95°	49.1	42.9	36.6	30.4	27.9	29.2	30.6	31.9	33.3	34.2	35.1
97.5°	92.3	74.7	57.1	39.5	32.2	35.3	38.3	41.4	44.5	45.2	46.0
100°	124.8	98.9	73.0	47.1	35.7	38.9	42.1	45.4	48.6	50.1	51.6
102.5°	190.3	184.9	179.3	173.8	157.7	130.7	103.8	76.9	49.9	51.9	53.9
105°	264.7	270.4	276.1	281.8	258.8	207.1	155.3	103.7	52.0	54.0	56.2
107.5°	335.7	340.3	344.8	349.5	320.7	258.8	196.7	134.7	72.8	70.6	68.5
110°	381.5	385.4	389.4	393.3	368.0	313.3	258.6	203.8	149.1	130.2	111.2



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	424.6	428.1	431.7	435.2	430.2	416.7	403.1	389.6	376.1	307.0	237.9
115°	493.1	496.4	499.6	502.8	506.8	511.5	516.2	521.0	525.8	438.0	350.4
117.5°	555.1	558.7	562.2	565.9	569.3	572.6	575.8	579.1	582.3	561.1	539.8
120°	599.3	602.1	604.9	607.8	610.9	614.3	617.8	621.2	624.6	626.9	629.1
122.5°	637.6	640.6	643.5	646.6	650.0	653.6	657.4	661.0	664.8	666.1	667.5
125°	695.2	697.7	700.1	702.6	705.6	709.2	712.8	716.4	720.0	721.3	722.6
127.5°	748.1	750.8	753.6	756.3	759.0	761.7	764.4	767.0	769.7	771.7	773.6
130°	781.9	784.9	787.8	790.9	793.4	795.5	797.6	799.7	801.8	803.9	805.9
132.5°	815.5	818.1	820.6	823.1	825.5	827.6	829.6	831.7	833.8	835.6	837.4
135°	860.2	863.3	866.3	869.3	871.6	873.3	875.0	876.7	878.5	880.4	882.3
137.5°	904.1	906.2	908.4	910.4	912.5	914.4	916.3	918.3	920.2	922.1	923.9
140°	932.8	934.3	935.9	937.4	939.1	941.2	943.3	945.4	947.5	949.2	950.9
142.5°	957.2	958.6	959.9	961.3	963.1	965.5	968.0	970.4	972.7	974.3	975.8
145°	994.2	994.0	993.8	993.6	995.1	998.4	1001.6	1004.8	1008.0	1009.3	1010.7
147.5°	1027.2	1026.4	1025.7	1025.0	1026.3	1029.5	1032.6	1035.8	1039.0	1040.0	1041.0
150°	1048.4	1047.0	1045.8	1044.5	1045.3	1048.3	1051.3	1054.4	1057.4	1058.5	1059.7
152.5°	1066.7	1065.1	1063.7	1062.2	1062.9	1065.8	1068.7	1071.6	1074.4	1075.6	1076.7
155°	1093.1	1091.5	1089.8	1088.1	1088.3	1090.7	1092.9	1095.2	1097.4	1098.6	1099.7
157.5°	1114.5	1112.9	1111.5	1110.1	1110.2	1111.8	1113.4	1114.9	1116.5	1117.8	1119.1
160°	1127.0	1125.9	1124.7	1123.6	1123.6	1124.7	1125.9	1127.0	1128.1	1129.3	1130.4
162.5°	1137.9	1136.8	1135.6	1134.5	1134.4	1135.4	1136.4	1137.4	1138.4	1139.6	1140.9
165°	1152.5	1151.4	1150.3	1149.1	1148.9	1149.4	1150.0	1150.6	1151.1	1152.4	1153.8
167.5°	1163.4	1162.3	1161.2	1160.0	1159.8	1160.3	1160.8	1161.4	1161.9	1163.1	1164.5
170°	1169.6	1168.5	1167.3	1166.2	1165.8	1166.2	1166.5	1167.0	1167.3	1168.7	1170.0
172.5°	1173.7	1172.5	1171.4	1170.3	1169.9	1170.3	1170.6	1171.0	1171.4	1172.8	1174.0
175°	1178.8	1177.4	1176.2	1174.8	1174.3	1174.7	1175.1	1175.5	1175.8	1177.1	1178.5
177.5°	1179.9	1178.8	1177.8	1176.7	1176.3	1176.4	1176.5	1176.7	1176.9	1177.9	1179.0
180°	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6	1966.6
2.5°	2035.5	2042.6	2045.9	2045.9	2049.7	2048.1	2046.4
5°	2152.5	2165.4	2168.2	2180.5	2189.3	2186.7	2188.0
7.5°	2268.8	2289.6	2310.3	2319.8	2321.2	2326.7	2328.8
10°	2340.4	2357.5	2389.6	2384.8	2408.7	2422.4	2399.9
12.5°	2409.2	2432.3	2454.6	2460.8	2474.3	2478.7	2469.8
15°	2471.6	2483.9	2485.3	2481.8	2485.9	2482.5	2469.5
17.5°	2413.3	2393.4	2353.0	2333.8	2318.6	2296.2	2287.2
20°	2317.1	2258.3	2190.0	2162.8	2130.6	2067.7	2082.8
22.5°	2109.4	2042.5	1974.2	1894.4	1856.2	1796.6	1793.1
25°	1786.2	1670.7	1543.6	1454.8	1402.8	1343.5	1317.4
27.5°	1388.8	1243.4	1139.2	1086.5	1038.5	991.4	989.4
30°	1127.5	1018.2	937.5	892.4	863.0	843.2	847.3
32.5°	950.4	875.5	821.1	783.6	761.9	747.0	746.7
35°	776.9	725.7	690.8	675.1	659.4	648.5	649.2
37.5°	664.9	634.1	614.7	597.4	587.5	582.2	579.2
40°	607.4	582.2	567.1	556.9	548.7	541.2	539.8
42.5°	562.1	541.2	526.2	518.1	510.4	505.2	503.7
45°	498.8	481.7	468.1	459.2	455.8	451.0	451.0
47.5°	443.7	427.0	416.3	410.7	404.8	401.6	401.5
50°	406.6	393.6	384.1	380.6	375.9	373.8	373.1
52.5°	373.3	363.6	356.7	354.4	352.3	349.7	350.2
55°	328.0	322.5	319.8	317.7	314.3	310.2	313.0
57.5°	289.9	285.3	277.9	271.4	268.3	265.4	266.5
60°	263.1	253.5	244.0	236.4	234.3	228.2	228.2
62.5°	229.2	215.8	204.0	199.8	197.8	194.9	194.3
65°	176.3	170.9	168.1	165.3	164.0	164.0	162.6
67.5°	146.1	143.9	140.9	140.2	138.8	138.5	138.0
70°	129.1	126.4	125.0	124.4	123.0	123.7	121.6
72.5°	112.7	110.6	110.3	108.5	107.7	107.8	106.3
75°	88.8	88.8	88.2	87.5	86.1	85.4	86.1
77.5°	68.3	68.5	67.2	67.1	67.0	67.1	66.4
80°	54.7	55.4	54.7	53.9	53.3	53.9	53.3
82.5°	43.2	42.3	42.1	42.0	41.8	41.4	41.3
85°	24.6	25.3	24.6	23.9	23.9	23.9	24.6
87.5°	13.3	13.5	13.6	13.6	13.7	13.8	13.4
90°	19.9	20.9	21.5	21.8	22.2	22.6	23.0
92.5°	21.2	21.8	22.1	22.3	22.6	22.7	23.0
95°	36.1	37.0	37.4	37.2	37.0	36.8	36.6
97.5°	46.7	47.5	48.0	48.2	48.4	48.7	48.9
100°	53.1	54.7	55.6	55.9	56.4	56.7	57.1
102.5°	55.8	57.8	59.0	59.6	60.1	60.6	61.2
105°	58.2	60.3	61.7	62.5	63.2	64.0	64.7
107.5°	66.4	64.3	63.6	64.4	65.1	65.9	66.6
110°	92.3	73.4	64.3	65.0	65.8	66.5	67.3



TEST NUMBER: P331853-940

CATALOG NUMBER: S122RDIW-S1005D970U940-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	168.9	99.8	65.5	66.2	66.8	67.4	68.0
115°	262.7	175.0	124.4	110.8	97.1	83.5	69.9
117.5°	518.7	497.5	464.5	419.6	374.9	330.1	285.3
120°	631.3	633.6	622.0	596.5	570.9	545.3	519.8
122.5°	668.9	670.2	668.4	663.4	658.5	653.5	648.6
125°	724.0	725.3	726.2	726.8	727.4	727.9	728.5
127.5°	775.5	777.5	778.5	778.6	778.7	778.8	778.9
130°	808.1	810.1	811.1	810.8	810.7	810.5	810.3
132.5°	839.2	841.0	841.8	841.5	841.3	841.2	841.0
135°	884.1	886.0	886.8	886.4	886.0	885.6	885.3
137.5°	925.8	927.6	928.3	927.6	926.9	926.3	925.7
140°	952.6	954.3	954.7	953.8	952.8	951.8	950.9
142.5°	977.4	978.9	979.2	978.3	977.3	976.4	975.4
145°	1012.0	1013.3	1013.5	1012.5	1011.6	1010.7	1009.7
147.5°	1042.0	1042.9	1043.0	1042.2	1041.4	1040.6	1039.8
150°	1060.8	1061.9	1062.0	1061.1	1060.2	1059.2	1058.3
152.5°	1077.8	1079.0	1079.0	1077.7	1076.5	1075.2	1074.0
155°	1100.8	1102.0	1101.8	1100.3	1098.8	1097.3	1095.7
157.5°	1120.4	1121.7	1121.6	1120.1	1118.7	1117.1	1115.7
160°	1131.5	1132.7	1132.6	1131.2	1129.9	1128.6	1127.3
162.5°	1142.2	1143.5	1143.4	1141.7	1140.1	1138.4	1136.8
165°	1155.1	1156.5	1156.5	1155.1	1153.8	1152.4	1151.1
167.5°	1165.8	1167.2	1167.0	1165.3	1163.6	1161.9	1160.2
170°	1171.3	1172.6	1172.4	1170.7	1169.0	1167.3	1165.6
172.5°	1175.4	1176.7	1176.5	1174.8	1173.1	1171.4	1169.7
175°	1179.8	1181.2	1180.9	1178.9	1177.1	1175.2	1173.3
177.5°	1180.0	1181.1	1181.0	1179.6	1178.2	1176.9	1175.5
180°	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5	1177.5

(END OF REPORT)