

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P332479-927

Luminaire Tested: **S123RDIW-S1165D1030U927-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P332479-927
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-9,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1
Description: DEFINE 3 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 1165 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING
UPLIGHT 1030 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6455.1 lumens
Efficiency: N/A
Efficacy: 95.8 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.22 / 1.36
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')
CIE Type: General Diffuse


Input Watts (W): 67.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

Luminous Intensity Polar Plot





TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	109	109	109	109	101	101	101	101	87	87	87	74	74	74	62	62	62	56
1	100	96	92	89	93	89	86	83	77	75	73	66	64	63	56	54	53	49
2	91	84	78	74	85	79	74	69	68	64	61	59	56	53	50	48	46	42
3	84	75	68	62	78	70	64	59	61	56	52	52	49	46	45	42	40	36
4	77	67	59	53	71	62	56	50	54	49	45	47	43	40	40	37	35	32
5	71	60	52	46	66	56	49	44	49	44	39	43	38	35	37	33	31	28
6	66	54	46	40	61	51	43	38	44	39	35	39	34	31	33	30	27	25
7	61	49	41	36	57	46	39	34	41	35	31	35	31	28	31	27	25	22
8	57	44	37	32	53	42	35	30	37	32	28	33	28	25	28	25	22	20
9	53	41	33	28	49	38	32	27	34	29	25	30	26	22	26	23	20	18
10	49	37	30	26	46	35	29	25	32	26	22	28	23	20	24	21	18	17

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	15655	15655	15655	15655
5°	18662	15722	13846	15722
10°	23302	15632	12508	15632
15°	27351	15473	11407	15473
20°	30525	15234	10470	15234
25°	30037	14982	9894	14982
30°	21592	14751	9302	14751
35°	14416	14448	8918	14448
40°	10621	14085	8521	14085
45°	8910	13449	8132	13449
50°	7860	12616	7591	12616
55°	6893	11661	6848	11661
60°	6140	10749	6273	10749
65°	5392	9770	5835	9770
70°	4233	8897	5331	8897
75°	3730	7769	4870	7769
80°	3242	6602	4785	6602
85°	2618	5298	5076	5298



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	143.0	2.2
10°-20°	446.9	6.9
20°-30°	702.0	10.9
30°-40°	732.4	11.3
40°-50°	626.8	9.7
50°-60°	477.7	7.4
60°-70°	306.2	4.7
70°-80°	147.3	2.3
80°-90°	42.0	0.7
90°-100°	66.6	1.0
100°-110°	199.2	3.1
110°-120°	338.8	5.2
120°-130°	445.7	6.9
130°-140°	500.9	7.8
140°-150°	492.4	7.6
150°-160°	414.5	6.4
160°-170°	275.9	4.3
170°-180°	96.6	1.5
0°-30°	1291.9	20.0
0°-40°	2024.3	31.4
0°-60°	3128.9	48.5
0°-90°	3624.4	56.1
90°-120°	604.6	9.4
90°-150°	2043.6	31.7
90°-180°	2831.0	43.9
0°-180°	6455.1	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1454	1454	1454	1454	1454	
5°	1727	1455	1281	1455	1727	178
15°	2454	1388	1024	1388	2454	696
25°	2529	1262	833	1262	2529	1087
35°	1097	1100	679	1100	1097	719
45°	585	884	534	884	585	460
55°	367	621	365	621	367	332
65°	212	384	229	384	212	208
75°	90	187	117	187	90	96
85°	21	43	41	43	21	25
90°	24	1	24	1	24	12
95°	63	47	63	47	63	64
105°	191	181	191	181	191	203
115°	342	341	342	341	342	339
125°	494	499	494	499	494	441
135°	647	648	647	648	647	497
145°	786	786	786	786	786	490
155°	898	900	898	900	898	414
165°	977	980	977	980	977	275
175°	1015	1019	1015	1019	1015	96
180°	1022	1022	1022	1022	1022	



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4
2.5°	1549.1	1551.1	1544.6	1543.6	1536.1	1534.1	1534.1	1523.7	1517.2	1508.8	1503.8
5°	1727.2	1737.2	1732.2	1720.9	1702.2	1697.9	1686.1	1667.4	1646.2	1620.1	1607.7
7.5°	1949.6	1963.2	1958.0	1940.6	1921.0	1905.3	1871.8	1840.9	1797.4	1759.3	1726.6
10°	2131.9	2117.6	2106.3	2089.5	2071.5	2042.2	2007.4	1959.4	1904.0	1860.4	1811.9
12.5°	2268.3	2266.0	2251.8	2234.5	2209.0	2181.2	2138.3	2080.0	2015.5	1952.6	1897.0
15°	2454.4	2458.1	2448.8	2430.7	2394.6	2345.4	2280.7	2256.5	2164.2	2095.8	2027.3
17.5°	2583.1	2582.4	2581.2	2556.1	2519.3	2484.3	2424.2	2360.4	2277.0	2180.5	2088.2
20°	2664.8	2658.6	2659.9	2631.9	2604.5	2564.0	2505.4	2412.7	2344.2	2232.8	2137.5
22.5°	2662.8	2661.7	2666.3	2656.7	2636.9	2605.8	2559.8	2481.4	2394.1	2281.6	2174.4
25°	2529.1	2524.1	2553.4	2561.5	2593.3	2598.8	2585.1	2542.2	2459.4	2343.6	2211.0
27.5°	2116.7	2113.9	2168.3	2236.3	2322.4	2389.4	2454.2	2485.4	2459.4	2376.5	2243.6
30°	1737.2	1795.6	1823.0	1921.4	2031.0	2161.8	2276.3	2385.3	2412.0	2376.0	2267.0
32.5°	1442.2	1493.3	1516.2	1600.7	1702.8	1855.9	2027.7	2182.1	2291.1	2318.6	2253.0
35°	1097.1	1097.7	1150.0	1187.3	1282.0	1439.6	1606.4	1813.1	2018.6	2174.2	2190.4
37.5°	875.4	878.5	910.1	947.4	1018.4	1101.7	1248.6	1420.5	1657.8	1896.8	2036.9
40°	755.9	761.4	785.1	821.9	872.9	935.8	1050.4	1212.3	1410.2	1676.1	1893.4
42.5°	679.1	688.2	700.4	728.7	760.3	819.3	911.9	1037.0	1217.0	1468.4	1719.1
45°	585.3	590.3	599.6	612.7	641.3	682.4	744.7	828.7	978.2	1180.5	1431.4
47.5°	516.3	513.7	523.5	534.1	553.2	581.1	622.9	691.5	798.1	960.4	1173.3
50°	469.4	468.8	475.7	483.8	501.8	522.4	556.7	608.3	693.0	827.5	1022.4
52.5°	425.6	428.0	432.8	442.9	456.0	472.6	503.4	540.6	613.3	729.4	891.8
55°	367.3	369.2	376.0	381.7	391.0	407.8	427.1	458.3	508.1	589.0	722.9
57.5°	318.1	317.2	323.8	325.1	335.7	349.4	364.3	388.5	424.6	484.8	575.0
60°	285.2	283.3	288.9	293.3	298.9	310.1	322.5	346.2	374.9	419.1	496.2
62.5°	255.2	254.4	258.5	262.8	267.5	277.7	288.1	306.3	329.0	366.2	427.5
65°	211.7	213.6	215.4	217.3	219.8	226.0	236.0	248.4	264.0	290.2	334.4
67.5°	166.4	168.3	168.9	172.7	178.1	182.0	188.1	199.2	209.9	232.0	257.1
70°	134.5	133.9	134.5	136.3	143.2	150.0	158.1	166.3	173.1	188.6	209.8
72.5°	115.6	114.5	116.1	116.5	119.8	121.7	126.7	134.4	143.2	153.8	169.0
75°	89.7	89.7	89.7	89.7	92.1	93.4	95.3	97.1	100.2	105.2	116.5
77.5°	66.2	66.4	67.3	67.9	68.4	69.1	70.3	72.1	73.2	75.8	80.7
80°	52.3	52.9	52.3	52.9	52.9	54.2	54.8	56.6	57.3	60.4	62.3
82.5°	39.4	39.0	39.4	40.0	40.0	41.2	41.4	42.7	42.9	44.4	46.3
85°	21.2	20.0	21.2	20.5	21.8	20.5	21.2	22.4	22.4	23.1	25.5
87.5°	9.8	10.7	9.7	10.1	10.0	10.4	10.2	10.1	10.9	10.3	10.4
90°	24.1	23.7	23.4	23.0	22.7	22.1	21.4	20.7	20.0	19.3	17.0
92.5°	32.4	32.6	32.9	33.0	33.3	33.1	32.6	31.9	31.4	30.8	29.5
95°	62.6	62.6	62.6	62.6	62.6	62.3	61.6	60.8	60.1	59.4	58.0
97.5°	96.3	96.4	96.5	96.5	96.6	96.3	95.4	94.6	93.8	92.9	91.9
100°	122.0	121.6	121.3	120.9	120.6	120.1	119.6	119.1	118.5	118.0	117.1
102.5°	148.3	148.4	148.5	148.5	148.6	148.4	147.8	147.3	146.8	146.2	145.0
105°	191.0	190.7	190.3	190.0	189.6	189.4	189.4	189.4	189.4	189.4	187.8
107.5°	235.4	235.7	235.9	236.1	236.3	236.1	235.6	235.0	234.4	233.9	233.2
110°	265.6	266.0	266.3	266.7	267.0	266.9	266.2	265.5	264.7	264.0	263.7



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	297.8	297.9	297.9	297.9	298.0	297.6	296.8	296.0	295.1	294.2	294.1
115°	341.9	342.1	342.2	342.5	342.6	342.6	342.5	342.2	342.1	341.9	342.2
117.5°	386.7	387.1	387.7	388.2	388.6	389.0	389.0	389.0	389.0	389.1	389.5
120°	418.1	418.5	418.8	419.2	419.5	419.9	420.0	420.2	420.3	420.6	421.4
122.5°	448.3	448.9	449.3	449.8	450.3	450.8	451.2	451.7	452.2	452.7	453.1
125°	493.6	494.3	495.0	495.7	496.5	497.2	497.9	498.6	499.3	500.0	500.3
127.5°	538.7	539.5	540.3	541.1	541.9	542.9	543.9	544.9	545.9	546.8	547.2
130°	568.2	569.5	570.7	572.0	573.2	574.2	574.9	575.6	576.3	577.0	577.6
132.5°	599.0	600.0	600.9	601.9	602.9	603.8	604.7	605.5	606.3	607.2	607.6
135°	646.9	647.2	647.6	647.9	648.3	648.8	649.5	650.2	650.9	651.6	651.9
137.5°	689.1	689.8	690.5	691.1	691.8	692.5	693.2	694.0	694.7	695.5	695.1
140°	716.7	718.0	719.2	720.4	721.7	722.4	722.5	722.8	722.9	723.1	722.9
142.5°	745.0	745.9	746.9	747.8	748.8	749.4	749.6	749.7	749.9	750.1	749.8
145°	785.7	786.4	787.1	787.8	788.5	789.0	789.2	789.4	789.6	789.7	789.2
147.5°	822.0	823.1	824.1	825.2	826.2	826.8	826.8	826.8	826.8	826.8	826.3
150°	845.1	846.2	847.2	848.3	849.4	849.9	849.9	849.9	849.9	849.9	849.5
152.5°	867.6	868.5	869.4	870.4	871.3	871.6	871.3	871.0	870.8	870.4	870.3
155°	898.1	899.4	900.6	901.8	903.1	903.3	902.6	901.9	901.2	900.5	900.3
157.5°	925.8	926.9	927.9	928.8	929.9	929.9	929.2	928.4	927.7	926.9	926.9
160°	943.8	944.5	945.2	945.9	946.7	946.6	945.7	944.8	943.9	943.0	943.0
162.5°	957.3	958.5	959.6	960.8	961.9	962.0	961.1	960.2	959.3	958.5	958.3
165°	976.8	977.9	979.2	980.5	981.8	981.8	980.7	979.7	978.6	977.6	977.6
167.5°	993.2	994.3	995.5	996.6	997.7	997.7	996.6	995.5	994.3	993.2	993.2
170°	1001.6	1002.8	1004.1	1005.4	1006.6	1006.6	1005.4	1004.1	1002.8	1001.6	1001.6
172.5°	1008.1	1009.2	1010.5	1011.8	1013.0	1013.1	1012.0	1010.9	1009.8	1008.7	1008.7
175°	1015.3	1016.5	1017.7	1019.0	1020.3	1020.3	1019.3	1018.2	1017.2	1016.1	1016.1
177.5°	1019.1	1020.1	1021.1	1022.1	1023.1	1023.2	1022.3	1021.4	1020.6	1019.8	1019.8
180°	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4
2.5°	1501.8	1500.3	1493.3	1485.3	1474.9	1467.9	1462.4	1459.4	1450.5	1439.6	1432.0
5°	1594.6	1575.9	1555.9	1531.7	1509.3	1486.2	1471.9	1455.1	1434.6	1411.5	1395.3
7.5°	1693.9	1657.3	1617.9	1577.2	1536.9	1500.8	1468.9	1441.6	1408.9	1375.9	1352.7
10°	1770.1	1716.6	1661.2	1604.5	1552.8	1504.3	1466.9	1430.2	1391.0	1353.0	1324.4
12.5°	1839.4	1768.9	1705.0	1635.4	1569.3	1511.2	1457.5	1414.2	1367.1	1326.6	1294.0
15°	1927.1	1854.8	1777.6	1671.7	1584.0	1510.5	1445.1	1388.5	1331.2	1281.4	1249.6
17.5°	2009.0	1900.3	1796.5	1708.3	1594.2	1502.4	1422.6	1354.9	1292.0	1239.1	1200.1
20°	2042.9	1937.6	1825.0	1712.2	1600.1	1497.5	1404.6	1329.9	1264.6	1204.8	1168.7
22.5°	2063.2	1944.1	1825.4	1704.3	1585.2	1478.5	1386.7	1304.6	1233.7	1176.9	1132.3
25°	2087.1	1945.1	1814.3	1694.8	1573.4	1457.6	1348.6	1261.5	1184.9	1124.5	1077.1
27.5°	2102.8	1935.8	1781.2	1648.4	1525.2	1409.8	1310.0	1217.6	1140.0	1076.0	1025.2
30°	2105.7	1928.3	1755.8	1612.0	1486.8	1381.0	1275.2	1186.8	1104.5	1036.6	989.4
32.5°	2109.7	1909.9	1721.4	1568.7	1440.5	1335.7	1239.8	1155.3	1071.2	1004.3	956.0
35°	2093.3	1899.7	1669.3	1493.7	1365.4	1263.9	1177.4	1099.5	1016.8	952.0	902.9
37.5°	2022.5	1859.2	1615.3	1409.3	1275.2	1181.1	1110.6	1042.7	966.9	897.0	850.6
40°	1951.3	1819.3	1573.4	1358.0	1217.9	1121.3	1057.9	1002.4	929.0	863.6	813.8
42.5°	1845.2	1765.1	1533.5	1304.2	1153.1	1060.1	1006.5	954.6	890.1	823.7	776.9
45°	1650.6	1661.2	1452.0	1218.5	1063.4	970.0	919.6	883.5	826.2	771.4	723.5
47.5°	1406.5	1505.5	1356.2	1127.2	968.9	881.3	837.2	805.6	767.1	713.3	669.6
50°	1247.1	1388.5	1279.5	1066.0	909.7	822.5	778.9	753.4	719.8	677.4	635.7
52.5°	1100.2	1252.0	1186.8	997.7	845.4	765.7	723.1	702.1	675.4	635.6	597.9
55°	897.2	1051.0	1036.1	894.7	749.0	677.4	645.1	621.4	603.3	573.5	543.6
57.5°	725.7	871.6	879.2	780.1	664.1	593.3	565.5	547.6	535.8	513.3	485.7
60°	617.7	751.5	777.7	703.0	603.3	541.1	513.7	499.3	490.0	472.0	450.8
62.5°	528.0	641.9	671.5	617.7	545.0	486.8	465.3	451.5	445.2	429.6	410.9
65°	404.1	498.8	527.4	497.5	459.5	412.8	395.4	383.6	378.0	369.2	355.5
67.5°	303.9	372.8	404.3	383.2	369.5	339.9	328.8	322.5	317.5	311.6	300.1
70°	244.1	295.1	327.5	321.9	310.7	295.1	287.0	282.7	277.7	272.7	262.8
72.5°	196.2	231.4	261.7	264.6	255.4	252.3	245.2	243.4	240.3	234.3	228.9
75°	130.2	154.4	175.5	183.7	187.4	190.5	187.4	186.8	186.2	181.2	178.1
77.5°	85.3	98.4	111.7	125.6	131.3	135.6	136.6	138.9	137.2	134.6	133.1
80°	65.4	68.5	77.8	89.7	99.0	102.7	105.2	106.5	105.8	105.2	102.7
82.5°	47.5	50.1	54.4	62.7	70.6	76.8	78.3	78.1	79.5	79.9	77.8
85°	25.5	26.1	27.4	28.7	33.0	39.8	41.7	42.9	44.2	44.2	40.5
87.5°	10.9	9.9	10.5	10.1	11.2	11.3	13.9	16.1	17.0	15.3	15.7
90°	14.7	12.3	10.0	7.9	6.2	4.4	2.6	0.8	2.6	4.4	6.2
92.5°	28.2	26.9	25.5	24.2	23.1	21.9	20.6	19.4	20.6	21.9	23.1
95°	56.6	55.1	53.7	52.4	51.1	49.8	48.6	47.4	48.6	49.8	51.1
97.5°	90.9	89.8	88.8	87.9	86.9	86.0	85.0	84.1	85.0	86.0	86.9
100°	116.2	115.3	114.4	113.4	112.3	111.3	110.2	109.2	110.2	111.3	112.3
102.5°	143.9	142.7	141.5	140.6	140.0	139.3	138.7	138.1	138.7	139.3	140.0
105°	186.2	184.6	183.0	182.0	181.6	181.3	180.9	180.6	180.9	181.3	181.6
107.5°	232.6	232.0	231.3	230.8	230.7	230.4	230.2	230.0	230.2	230.4	230.7
110°	263.3	263.0	262.6	262.3	261.9	261.6	261.2	260.9	261.2	261.6	261.9



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	294.1	294.0	293.9	293.8	293.6	293.3	293.2	292.9	293.2	293.3	293.6
115°	342.6	342.9	343.3	343.3	342.7	342.1	341.6	341.1	341.6	342.1	342.7
117.5°	390.0	390.5	390.9	391.0	390.6	390.3	389.9	389.6	389.9	390.3	390.6
120°	422.3	423.2	424.1	424.1	422.9	421.9	420.8	419.8	420.8	421.9	422.9
122.5°	453.6	454.1	454.5	454.3	453.5	452.8	452.0	451.2	452.0	452.8	453.5
125°	500.7	501.1	501.5	501.4	500.8	500.3	499.7	499.2	499.7	500.3	500.8
127.5°	547.6	548.0	548.4	548.0	546.9	545.8	544.6	543.5	544.6	545.8	546.9
130°	578.1	578.7	579.2	578.8	577.3	575.9	574.5	573.1	574.5	575.9	577.3
132.5°	608.0	608.4	608.8	608.3	606.9	605.4	604.0	602.5	604.0	605.4	606.9
135°	652.0	652.2	652.4	652.0	650.9	649.8	648.7	647.7	648.7	649.8	650.9
137.5°	694.6	694.1	693.6	693.0	692.1	691.2	690.3	689.4	690.3	691.2	692.1
140°	722.8	722.5	722.4	721.8	721.0	720.1	719.2	718.3	719.2	720.1	721.0
142.5°	749.4	749.1	748.8	748.2	747.3	746.4	745.5	744.7	745.5	746.4	747.3
145°	788.7	788.1	787.6	787.1	786.8	786.4	786.1	785.7	786.1	786.4	786.8
147.5°	825.9	825.3	824.8	824.3	823.6	822.9	822.3	821.7	822.3	822.9	823.6
150°	849.2	848.8	848.5	848.1	847.8	847.4	847.1	846.7	847.1	847.4	847.8
152.5°	870.1	869.8	869.6	869.3	868.8	868.2	867.8	867.3	867.8	868.2	868.8
155°	900.2	899.9	899.8	899.7	899.7	899.7	899.7	899.7	899.7	899.7	899.7
157.5°	926.7	926.5	926.4	926.5	926.6	926.9	927.1	927.3	927.1	926.9	926.6
160°	943.0	943.0	943.0	943.2	943.6	943.9	944.3	944.6	944.3	943.9	943.6
162.5°	958.1	958.0	957.8	958.1	958.5	959.0	959.6	960.0	959.6	959.0	958.5
165°	977.6	977.6	977.6	977.8	978.3	978.9	979.4	979.9	979.4	978.9	978.3
167.5°	993.0	992.8	992.7	993.0	993.7	994.4	995.1	995.9	995.1	994.4	993.7
170°	1001.6	1001.6	1001.6	1002.0	1002.7	1003.4	1004.1	1004.8	1004.1	1003.4	1002.7
172.5°	1008.7	1008.7	1008.7	1009.0	1009.7	1010.4	1011.1	1011.9	1011.1	1010.4	1009.7
175°	1016.1	1016.1	1016.1	1016.4	1017.2	1017.9	1018.6	1019.3	1018.6	1017.9	1017.2
177.5°	1019.8	1019.8	1019.8	1020.0	1020.6	1021.2	1021.8	1022.3	1021.8	1021.2	1020.6
180°	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4
2.5°	1429.6	1423.1	1418.6	1408.7	1402.2	1395.2	1388.2	1392.7	1392.2	1391.7	1391.7
5°	1381.6	1367.3	1354.2	1337.4	1326.8	1313.8	1303.8	1302.5	1305.0	1296.3	1291.3
7.5°	1334.0	1314.5	1295.9	1277.4	1257.7	1242.1	1232.2	1227.6	1221.2	1215.8	1210.3
10°	1300.7	1277.6	1259.6	1236.5	1215.4	1196.7	1184.9	1176.8	1172.4	1168.1	1160.0
12.5°	1266.3	1243.8	1220.8	1194.7	1174.6	1152.9	1144.0	1135.0	1126.6	1121.7	1110.6
15°	1216.0	1186.8	1162.4	1135.0	1112.6	1091.5	1079.0	1061.0	1058.4	1052.3	1041.0
17.5°	1165.5	1133.8	1100.3	1080.0	1054.7	1032.7	1013.8	1007.7	989.8	983.1	973.4
20°	1125.7	1096.5	1071.0	1044.2	1007.4	986.9	971.9	963.8	949.5	940.8	934.5
22.5°	1091.3	1061.6	1032.1	1000.8	970.6	947.5	936.6	924.0	916.2	904.0	897.2
25°	1042.3	1009.9	974.4	940.8	919.0	901.6	884.2	872.9	861.7	856.1	843.7
27.5°	985.2	951.4	918.2	892.7	865.9	848.7	833.0	823.0	809.5	800.1	793.2
30°	953.9	914.0	885.3	862.4	828.1	811.9	800.1	787.7	777.7	767.7	760.9
32.5°	917.5	881.1	854.0	825.5	799.2	781.5	766.2	755.3	746.8	737.3	730.5
35°	860.5	830.0	801.9	773.3	754.0	735.9	717.9	708.5	700.4	691.7	685.6
37.5°	808.9	780.4	753.8	726.6	702.7	688.0	673.4	666.3	655.4	649.5	643.2
40°	777.1	749.0	720.4	694.3	669.3	658.1	645.1	634.5	624.5	620.1	613.3
42.5°	742.2	714.2	690.0	661.9	641.4	626.2	614.2	602.6	595.1	588.7	584.9
45°	690.5	665.6	641.9	613.9	594.6	581.5	567.8	557.2	550.4	546.1	539.2
47.5°	640.3	615.4	591.4	567.0	548.3	533.4	519.7	512.3	503.2	497.9	493.2
50°	604.0	581.5	556.0	533.6	514.9	499.9	488.8	479.4	471.3	464.5	461.4
52.5°	570.6	546.7	524.7	503.7	484.0	467.1	456.9	447.0	440.9	433.1	429.5
55°	515.6	492.5	473.8	453.3	434.0	419.6	407.2	398.5	392.3	383.6	378.6
57.5°	463.8	443.2	420.9	403.1	383.2	371.1	360.8	349.0	341.4	334.5	329.6
60°	429.0	405.4	386.0	369.2	351.8	336.2	326.9	317.5	309.4	302.6	298.3
62.5°	392.6	371.9	353.6	335.3	319.4	305.9	295.0	287.2	280.0	275.7	271.3
65°	336.8	320.7	302.0	287.0	272.1	262.1	253.4	246.5	241.6	238.4	234.7
67.5°	285.5	269.8	253.5	238.8	228.9	221.3	215.6	209.7	207.2	203.2	200.7
70°	252.2	236.0	221.7	210.5	200.5	194.9	191.2	186.8	184.3	179.4	176.8
72.5°	215.8	204.1	193.8	184.6	176.6	171.5	166.8	161.4	157.4	151.9	149.4
75°	170.0	159.4	151.3	145.0	140.1	133.2	126.4	120.8	118.9	117.1	116.5
77.5°	125.9	119.1	113.3	108.1	101.9	96.9	95.4	94.1	93.8	92.8	92.8
80°	99.0	92.8	88.4	82.1	78.4	78.4	78.4	77.2	77.8	77.8	77.8
82.5°	73.6	67.9	65.5	63.3	62.5	63.0	63.0	63.3	62.9	63.8	63.4
85°	37.9	38.6	39.8	39.2	39.8	39.8	41.1	40.5	41.1	39.8	41.1
87.5°	15.5	17.4	18.4	19.3	20.4	20.3	20.9	21.1	21.7	21.9	21.9
90°	7.9	10.0	12.3	14.7	17.0	19.3	20.0	20.7	21.4	22.1	22.7
92.5°	24.2	25.5	26.9	28.2	29.5	30.8	31.4	31.9	32.6	33.1	33.3
95°	52.4	53.7	55.1	56.6	58.0	59.4	60.1	60.8	61.6	62.3	62.6
97.5°	87.9	88.8	89.8	90.9	91.9	92.9	93.8	94.6	95.4	96.3	96.6
100°	113.4	114.4	115.3	116.2	117.1	118.0	118.5	119.1	119.6	120.1	120.6
102.5°	140.6	141.5	142.7	143.9	145.0	146.2	146.8	147.3	147.8	148.4	148.6
105°	182.0	183.0	184.6	186.2	187.8	189.4	189.4	189.4	189.4	189.4	189.6
107.5°	230.8	231.3	232.0	232.6	233.2	233.9	234.4	235.0	235.6	236.1	236.3
110°	262.3	262.6	263.0	263.3	263.7	264.0	264.7	265.5	266.2	266.9	267.0



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	293.8	293.9	294.0	294.1	294.1	294.2	295.1	296.0	296.8	297.6	298.0
115°	343.3	343.3	342.9	342.6	342.2	341.9	342.1	342.2	342.5	342.6	342.6
117.5°	391.0	390.9	390.5	390.0	389.5	389.1	389.0	389.0	389.0	389.0	388.6
120°	424.1	424.1	423.2	422.3	421.4	420.6	420.3	420.2	420.0	419.9	419.5
122.5°	454.3	454.5	454.1	453.6	453.1	452.7	452.2	451.7	451.2	450.8	450.3
125°	501.4	501.5	501.1	500.7	500.3	500.0	499.3	498.6	497.9	497.2	496.5
127.5°	548.0	548.4	548.0	547.6	547.2	546.8	545.9	544.9	543.9	542.9	541.9
130°	578.8	579.2	578.7	578.1	577.6	577.0	576.3	575.6	574.9	574.2	573.2
132.5°	608.3	608.8	608.4	608.0	607.6	607.2	606.3	605.5	604.7	603.8	602.9
135°	652.0	652.4	652.2	652.0	651.9	651.6	650.9	650.2	649.5	648.8	648.3
137.5°	693.0	693.6	694.1	694.6	695.1	695.5	694.7	694.0	693.2	692.5	691.8
140°	721.8	722.4	722.5	722.8	722.9	723.1	722.9	722.8	722.5	722.4	721.7
142.5°	748.2	748.8	749.1	749.4	749.8	750.1	749.9	749.7	749.6	749.4	748.8
145°	787.1	787.6	788.1	788.7	789.2	789.7	789.6	789.4	789.2	789.0	788.5
147.5°	824.3	824.8	825.3	825.9	826.3	826.8	826.8	826.8	826.8	826.8	826.2
150°	848.1	848.5	848.8	849.2	849.5	849.9	849.9	849.9	849.9	849.9	849.4
152.5°	869.3	869.6	869.8	870.1	870.3	870.4	870.8	871.0	871.3	871.6	871.3
155°	899.7	899.8	899.9	900.2	900.3	900.5	901.2	901.9	902.6	903.3	903.1
157.5°	926.5	926.4	926.5	926.7	926.9	926.9	927.7	928.4	929.2	929.9	929.9
160°	943.2	943.0	943.0	943.0	943.0	943.0	943.9	944.8	945.7	946.6	946.7
162.5°	958.1	957.8	958.0	958.1	958.3	958.5	959.3	960.2	961.1	962.0	961.9
165°	977.8	977.6	977.6	977.6	977.6	977.6	978.6	979.7	980.7	981.8	981.8
167.5°	993.0	992.7	992.8	993.0	993.2	993.2	994.3	995.5	996.6	997.7	997.7
170°	1002.0	1001.6	1001.6	1001.6	1001.6	1001.6	1002.8	1004.1	1005.4	1006.6	1006.6
172.5°	1009.0	1008.7	1008.7	1008.7	1008.7	1008.7	1009.8	1010.9	1012.0	1013.1	1013.0
175°	1016.4	1016.1	1016.1	1016.1	1016.1	1016.1	1017.2	1018.2	1019.3	1020.3	1020.3
177.5°	1020.0	1019.8	1019.8	1019.8	1019.8	1019.8	1020.6	1021.4	1022.3	1023.2	1023.1
180°	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4
2.5°	1385.8	1385.2	1385.8	1383.7	1385.8	1385.2	1385.8	1391.7	1391.7	1392.2	1392.7
5°	1289.4	1288.9	1287.0	1281.4	1287.0	1288.9	1289.4	1291.3	1296.3	1305.0	1302.5
7.5°	1205.4	1204.5	1199.0	1199.2	1199.0	1204.5	1205.4	1210.3	1215.8	1221.2	1227.6
10°	1155.6	1156.2	1148.7	1144.4	1148.7	1156.2	1155.6	1160.0	1168.1	1172.4	1176.8
12.5°	1107.3	1104.5	1098.4	1093.6	1098.4	1104.5	1107.3	1110.6	1121.7	1126.6	1135.0
15°	1043.5	1037.3	1022.4	1023.6	1022.4	1037.3	1043.5	1041.0	1052.3	1058.4	1061.0
17.5°	968.4	963.8	963.6	954.9	963.6	963.8	968.4	973.4	983.1	989.8	1007.7
20°	924.6	921.5	922.7	914.0	922.7	921.5	924.6	934.5	940.8	949.5	963.8
22.5°	890.3	887.1	881.9	879.2	881.9	887.1	890.3	897.2	904.0	916.2	924.0
25°	840.0	835.0	830.0	833.1	830.0	835.0	840.0	843.7	856.1	861.7	872.9
27.5°	789.6	785.9	780.9	780.3	780.9	785.9	789.6	793.2	800.1	809.5	823.0
30°	757.7	754.0	751.5	748.4	751.5	754.0	757.7	760.9	767.7	777.7	787.7
32.5°	725.4	724.6	720.2	719.5	720.2	724.6	725.4	730.5	737.3	746.8	755.3
35°	683.0	679.3	678.0	678.7	678.0	679.3	683.0	685.6	691.7	700.4	708.5
37.5°	642.8	637.8	635.6	633.3	635.6	637.8	642.8	643.2	649.5	655.4	666.3
40°	613.9	609.0	607.7	606.4	607.7	609.0	613.9	613.3	620.1	624.5	634.5
42.5°	581.5	579.6	578.8	576.6	578.8	579.6	581.5	584.9	588.7	595.1	602.6
45°	537.3	536.7	533.0	534.2	533.0	536.7	537.3	539.2	546.1	550.4	557.2
47.5°	490.8	488.0	485.4	487.1	485.4	488.0	490.8	493.2	497.9	503.2	512.3
50°	458.9	457.6	452.0	453.3	452.0	457.6	458.9	461.4	464.5	471.3	479.4
52.5°	427.0	422.2	420.2	419.4	420.2	422.2	427.0	429.5	433.1	440.9	447.0
55°	374.2	368.6	366.1	364.9	366.1	368.6	374.2	378.6	383.6	392.3	398.5
57.5°	322.4	320.9	318.9	320.3	318.9	320.9	322.4	329.6	334.5	341.4	349.0
60°	292.0	292.0	292.0	291.4	292.0	292.0	292.0	298.3	302.6	309.4	317.5
62.5°	268.6	267.1	266.6	267.5	266.6	267.1	268.6	271.3	275.7	280.0	287.2
65°	232.9	232.3	229.7	229.1	229.7	232.3	232.9	234.7	238.4	241.6	246.5
67.5°	199.2	196.9	196.1	195.3	196.1	196.9	199.2	200.7	203.2	207.2	209.7
70°	173.7	172.5	168.7	169.4	168.7	172.5	173.7	176.8	179.4	184.3	186.8
72.5°	146.3	145.0	144.3	143.5	144.3	145.0	146.3	149.4	151.9	157.4	161.4
75°	115.8	115.2	114.5	117.1	114.5	115.2	115.8	116.5	117.1	118.9	120.8
77.5°	92.8	92.8	93.2	92.1	93.2	92.8	92.8	92.8	92.8	93.8	94.1
80°	77.8	77.8	77.2	77.2	77.2	77.8	77.8	77.8	77.8	77.8	77.2
82.5°	62.4	62.9	63.3	62.3	63.3	62.9	62.4	63.4	63.8	62.9	63.3
85°	41.1	40.5	41.7	41.1	41.7	40.5	41.1	41.1	39.8	41.1	40.5
87.5°	23.1	22.1	22.2	22.7	22.2	22.1	23.1	21.9	21.9	21.7	21.1
90°	23.0	23.4	23.7	24.1	23.7	23.4	23.0	22.7	22.1	21.4	20.7
92.5°	33.0	32.9	32.6	32.4	32.6	32.9	33.0	33.3	33.1	32.6	31.9
95°	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.6	62.3	61.6	60.8
97.5°	96.5	96.5	96.4	96.3	96.4	96.5	96.5	96.6	96.3	95.4	94.6
100°	120.9	121.3	121.6	122.0	121.6	121.3	120.9	120.6	120.1	119.6	119.1
102.5°	148.5	148.5	148.4	148.3	148.4	148.5	148.5	148.6	148.4	147.8	147.3
105°	190.0	190.3	190.7	191.0	190.7	190.3	190.0	189.6	189.4	189.4	189.4
107.5°	236.1	235.9	235.7	235.4	235.7	235.9	236.1	236.3	236.1	235.6	235.0
110°	266.7	266.3	266.0	265.6	266.0	266.3	266.7	267.0	266.9	266.2	265.5



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	297.9	297.9	297.9	297.8	297.9	297.9	297.9	298.0	297.6	296.8	296.0
115°	342.5	342.2	342.1	341.9	342.1	342.2	342.5	342.6	342.6	342.5	342.2
117.5°	388.2	387.7	387.1	386.7	387.1	387.7	388.2	388.6	389.0	389.0	389.0
120°	419.2	418.8	418.5	418.1	418.5	418.8	419.2	419.5	419.9	420.0	420.2
122.5°	449.8	449.3	448.9	448.3	448.9	449.3	449.8	450.3	450.8	451.2	451.7
125°	495.7	495.0	494.3	493.6	494.3	495.0	495.7	496.5	497.2	497.9	498.6
127.5°	541.1	540.3	539.5	538.7	539.5	540.3	541.1	541.9	542.9	543.9	544.9
130°	572.0	570.7	569.5	568.2	569.5	570.7	572.0	573.2	574.2	574.9	575.6
132.5°	601.9	600.9	600.0	599.0	600.0	600.9	601.9	602.9	603.8	604.7	605.5
135°	647.9	647.6	647.2	646.9	647.2	647.6	647.9	648.3	648.8	649.5	650.2
137.5°	691.1	690.5	689.8	689.1	689.8	690.5	691.1	691.8	692.5	693.2	694.0
140°	720.4	719.2	718.0	716.7	718.0	719.2	720.4	721.7	722.4	722.5	722.8
142.5°	747.8	746.9	745.9	745.0	745.9	746.9	747.8	748.8	749.4	749.6	749.7
145°	787.8	787.1	786.4	785.7	786.4	787.1	787.8	788.5	789.0	789.2	789.4
147.5°	825.2	824.1	823.1	822.0	823.1	824.1	825.2	826.2	826.8	826.8	826.8
150°	848.3	847.2	846.2	845.1	846.2	847.2	848.3	849.4	849.9	849.9	849.9
152.5°	870.4	869.4	868.5	867.6	868.5	869.4	870.4	871.3	871.6	871.3	871.0
155°	901.8	900.6	899.4	898.1	899.4	900.6	901.8	903.1	903.3	902.6	901.9
157.5°	928.8	927.9	926.9	925.8	926.9	927.9	928.8	929.9	929.9	929.2	928.4
160°	945.9	945.2	944.5	943.8	944.5	945.2	945.9	946.7	946.6	945.7	944.8
162.5°	960.8	959.6	958.5	957.3	958.5	959.6	960.8	961.9	962.0	961.1	960.2
165°	980.5	979.2	977.9	976.8	977.9	979.2	980.5	981.8	981.8	980.7	979.7
167.5°	996.6	995.5	994.3	993.2	994.3	995.5	996.6	997.7	997.7	996.6	995.5
170°	1005.4	1004.1	1002.8	1001.6	1002.8	1004.1	1005.4	1006.6	1006.6	1005.4	1004.1
172.5°	1011.8	1010.5	1009.2	1008.1	1009.2	1010.5	1011.8	1013.0	1013.1	1012.0	1010.9
175°	1019.0	1017.7	1016.5	1015.3	1016.5	1017.7	1019.0	1020.3	1020.3	1019.3	1018.2
177.5°	1022.1	1021.1	1020.1	1019.1	1020.1	1021.1	1022.1	1023.1	1023.2	1022.3	1021.4
180°	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4
2.5°	1388.2	1395.2	1402.2	1408.7	1418.6	1423.1	1429.6	1432.0	1439.6	1450.5	1459.4
5°	1303.8	1313.8	1326.8	1337.4	1354.2	1367.3	1381.6	1395.3	1411.5	1434.6	1455.1
7.5°	1232.2	1242.1	1257.7	1277.4	1295.9	1314.5	1334.0	1352.7	1375.9	1408.9	1441.6
10°	1184.9	1196.7	1215.4	1236.5	1259.6	1277.6	1300.7	1324.4	1353.0	1391.0	1430.2
12.5°	1144.0	1152.9	1174.6	1194.7	1220.8	1243.8	1266.3	1294.0	1326.6	1367.1	1414.2
15°	1079.0	1091.5	1112.6	1135.0	1162.4	1186.8	1216.0	1249.6	1281.4	1331.2	1388.5
17.5°	1013.8	1032.7	1054.7	1080.0	1100.3	1133.8	1165.5	1200.1	1239.1	1292.0	1354.9
20°	971.9	986.9	1007.4	1044.2	1071.0	1096.5	1125.7	1168.7	1204.8	1264.6	1329.9
22.5°	936.6	947.5	970.6	1000.8	1032.1	1061.6	1091.3	1132.3	1176.9	1233.7	1304.6
25°	884.2	901.6	919.0	940.8	974.4	1009.9	1042.3	1077.1	1124.5	1184.9	1261.5
27.5°	833.0	848.7	865.9	892.7	918.2	951.4	985.2	1025.2	1076.0	1140.0	1217.6
30°	800.1	811.9	828.1	862.4	885.3	914.0	953.9	989.4	1036.6	1104.5	1186.8
32.5°	766.2	781.5	799.2	825.5	854.0	881.1	917.5	956.0	1004.3	1071.2	1155.3
35°	717.9	735.9	754.0	773.3	801.9	830.0	860.5	902.9	952.0	1016.8	1099.5
37.5°	673.4	688.0	702.7	726.6	753.8	780.4	808.9	850.6	897.0	966.9	1042.7
40°	645.1	658.1	669.3	694.3	720.4	749.0	777.1	813.8	863.6	929.0	1002.4
42.5°	614.2	626.2	641.4	661.9	690.0	714.2	742.2	776.9	823.7	890.1	954.6
45°	567.8	581.5	594.6	613.9	641.9	665.6	690.5	723.5	771.4	826.2	883.5
47.5°	519.7	533.4	548.3	567.0	591.4	615.4	640.3	669.6	713.3	767.1	805.6
50°	488.8	499.9	514.9	533.6	556.0	581.5	604.0	635.7	677.4	719.8	753.4
52.5°	456.9	467.1	484.0	503.7	524.7	546.7	570.6	597.9	635.6	675.4	702.1
55°	407.2	419.6	434.0	453.3	473.8	492.5	515.6	543.6	573.5	603.3	621.4
57.5°	360.8	371.1	383.2	403.1	420.9	443.2	463.8	485.7	513.3	535.8	547.6
60°	326.9	336.2	351.8	369.2	386.0	405.4	429.0	450.8	472.0	490.0	499.3
62.5°	295.0	305.9	319.4	335.3	353.6	371.9	392.6	410.9	429.6	445.2	451.5
65°	253.4	262.1	272.1	287.0	302.0	320.7	336.8	355.5	369.2	378.0	383.6
67.5°	215.6	221.3	228.9	238.8	253.5	269.8	285.5	300.1	311.6	317.5	322.5
70°	191.2	194.9	200.5	210.5	221.7	236.0	252.2	262.8	272.7	277.7	282.7
72.5°	166.8	171.5	176.6	184.6	193.8	204.1	215.8	228.9	234.3	240.3	243.4
75°	126.4	133.2	140.1	145.0	151.3	159.4	170.0	178.1	181.2	186.2	186.8
77.5°	95.4	96.9	101.9	108.1	113.3	119.1	125.9	133.1	134.6	137.2	138.9
80°	78.4	78.4	78.4	82.1	88.4	92.8	99.0	102.7	105.2	105.8	106.5
82.5°	63.0	63.0	62.5	63.3	65.5	67.9	73.6	77.8	79.9	79.5	78.1
85°	41.1	39.8	39.8	39.2	39.8	38.6	37.9	40.5	44.2	44.2	42.9
87.5°	20.9	20.3	20.4	19.3	18.4	17.4	15.5	15.7	15.3	17.0	16.1
90°	20.0	19.3	17.0	14.7	12.3	10.0	7.9	6.2	4.4	2.6	0.8
92.5°	31.4	30.8	29.5	28.2	26.9	25.5	24.2	23.1	21.9	20.6	19.4
95°	60.1	59.4	58.0	56.6	55.1	53.7	52.4	51.1	49.8	48.6	47.4
97.5°	93.8	92.9	91.9	90.9	89.8	88.8	87.9	86.9	86.0	85.0	84.1
100°	118.5	118.0	117.1	116.2	115.3	114.4	113.4	112.3	111.3	110.2	109.2
102.5°	146.8	146.2	145.0	143.9	142.7	141.5	140.6	140.0	139.3	138.7	138.1
105°	189.4	189.4	187.8	186.2	184.6	183.0	182.0	181.6	181.3	180.9	180.6
107.5°	234.4	233.9	233.2	232.6	232.0	231.3	230.8	230.7	230.4	230.2	230.0
110°	264.7	264.0	263.7	263.3	263.0	262.6	262.3	261.9	261.6	261.2	260.9



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	295.1	294.2	294.1	294.1	294.0	293.9	293.8	293.6	293.3	293.2	292.9
115°	342.1	341.9	342.2	342.6	342.9	343.3	343.3	342.7	342.1	341.6	341.1
117.5°	389.0	389.1	389.5	390.0	390.5	390.9	391.0	390.6	390.3	389.9	389.6
120°	420.3	420.6	421.4	422.3	423.2	424.1	424.1	422.9	421.9	420.8	419.8
122.5°	452.2	452.7	453.1	453.6	454.1	454.5	454.3	453.5	452.8	452.0	451.2
125°	499.3	500.0	500.3	500.7	501.1	501.5	501.4	500.8	500.3	499.7	499.2
127.5°	545.9	546.8	547.2	547.6	548.0	548.4	548.0	546.9	545.8	544.6	543.5
130°	576.3	577.0	577.6	578.1	578.7	579.2	578.8	577.3	575.9	574.5	573.1
132.5°	606.3	607.2	607.6	608.0	608.4	608.8	608.3	606.9	605.4	604.0	602.5
135°	650.9	651.6	651.9	652.0	652.2	652.4	652.0	650.9	649.8	648.7	647.7
137.5°	694.7	695.5	695.1	694.6	694.1	693.6	693.0	692.1	691.2	690.3	689.4
140°	722.9	723.1	722.9	722.8	722.5	722.4	721.8	721.0	720.1	719.2	718.3
142.5°	749.9	750.1	749.8	749.4	749.1	748.8	748.2	747.3	746.4	745.5	744.7
145°	789.6	789.7	789.2	788.7	788.1	787.6	787.1	786.8	786.4	786.1	785.7
147.5°	826.8	826.8	826.3	825.9	825.3	824.8	824.3	823.6	822.9	822.3	821.7
150°	849.9	849.9	849.5	849.2	848.8	848.5	848.1	847.8	847.4	847.1	846.7
152.5°	870.8	870.4	870.3	870.1	869.8	869.6	869.3	868.8	868.2	867.8	867.3
155°	901.2	900.5	900.3	900.2	899.9	899.8	899.7	899.7	899.7	899.7	899.7
157.5°	927.7	926.9	926.9	926.7	926.5	926.4	926.5	926.6	926.9	927.1	927.3
160°	943.9	943.0	943.0	943.0	943.0	943.0	943.2	943.6	943.9	944.3	944.6
162.5°	959.3	958.5	958.3	958.1	958.0	957.8	958.1	958.5	959.0	959.6	960.0
165°	978.6	977.6	977.6	977.6	977.6	977.6	977.8	978.3	978.9	979.4	979.9
167.5°	994.3	993.2	993.2	993.0	992.8	992.7	993.0	993.7	994.4	995.1	995.9
170°	1002.8	1001.6	1001.6	1001.6	1001.6	1001.6	1002.0	1002.7	1003.4	1004.1	1004.8
172.5°	1009.8	1008.7	1008.7	1008.7	1008.7	1008.7	1009.0	1009.7	1010.4	1011.1	1011.9
175°	1017.2	1016.1	1016.1	1016.1	1016.1	1016.1	1016.4	1017.2	1017.9	1018.6	1019.3
177.5°	1020.6	1019.8	1019.8	1019.8	1019.8	1019.8	1020.0	1020.6	1021.2	1021.8	1022.3
180°	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4
2.5°	1462.4	1467.9	1474.9	1485.3	1493.3	1500.3	1501.8	1503.8	1508.8	1517.2	1523.7
5°	1471.9	1486.2	1509.3	1531.7	1555.9	1575.9	1594.6	1607.7	1620.1	1646.2	1667.4
7.5°	1468.9	1500.8	1536.9	1577.2	1617.9	1657.3	1693.9	1726.6	1759.3	1797.4	1840.9
10°	1466.9	1504.3	1552.8	1604.5	1661.2	1716.6	1770.1	1811.9	1860.4	1904.0	1959.4
12.5°	1457.5	1511.2	1569.3	1635.4	1705.0	1768.9	1839.4	1897.0	1952.6	2015.5	2080.0
15°	1445.1	1510.5	1584.0	1671.7	1777.6	1854.8	1927.1	2027.3	2095.8	2164.2	2256.5
17.5°	1422.6	1502.4	1594.2	1708.3	1796.5	1900.3	2009.0	2088.2	2180.5	2277.0	2360.4
20°	1404.6	1497.5	1600.1	1712.2	1825.0	1937.6	2042.9	2137.5	2232.8	2344.2	2412.7
22.5°	1386.7	1478.5	1585.2	1704.3	1825.4	1944.1	2063.2	2174.4	2281.6	2394.1	2481.4
25°	1348.6	1457.6	1573.4	1694.8	1814.3	1945.1	2087.1	2211.0	2343.6	2459.4	2542.2
27.5°	1310.0	1409.8	1525.2	1648.4	1781.2	1935.8	2102.8	2243.6	2376.5	2459.4	2485.4
30°	1275.2	1381.0	1486.8	1612.0	1755.8	1928.3	2105.7	2267.0	2376.0	2412.0	2385.3
32.5°	1239.8	1335.7	1440.5	1568.7	1721.4	1909.9	2109.7	2253.0	2318.6	2291.1	2182.1
35°	1177.4	1263.9	1365.4	1493.7	1669.3	1899.7	2093.3	2190.4	2174.2	2018.6	1813.1
37.5°	1110.6	1181.1	1275.2	1409.3	1615.3	1859.2	2022.5	2036.9	1896.8	1657.8	1420.5
40°	1057.9	1121.3	1217.9	1358.0	1573.4	1819.3	1951.3	1893.4	1676.1	1410.2	1212.3
42.5°	1006.5	1060.1	1153.1	1304.2	1533.5	1765.1	1845.2	1719.1	1468.4	1217.0	1037.0
45°	919.6	970.0	1063.4	1218.5	1452.0	1661.2	1650.6	1431.4	1180.5	978.2	828.7
47.5°	837.2	881.3	968.9	1127.2	1356.2	1505.5	1406.5	1173.3	960.4	798.1	691.5
50°	778.9	822.5	909.7	1066.0	1279.5	1388.5	1247.1	1022.4	827.5	693.0	608.3
52.5°	723.1	765.7	845.4	997.7	1186.8	1252.0	1100.2	891.8	729.4	613.3	540.6
55°	645.1	677.4	749.0	894.7	1036.1	1051.0	897.2	722.9	589.0	508.1	458.3
57.5°	565.5	593.3	664.1	780.1	879.2	871.6	725.7	575.0	484.8	424.6	388.5
60°	513.7	541.1	603.3	703.0	777.7	751.5	617.7	496.2	419.1	374.9	346.2
62.5°	465.3	486.8	545.0	617.7	671.5	641.9	528.0	427.5	366.2	329.0	306.3
65°	395.4	412.8	459.5	497.5	527.4	498.8	404.1	334.4	290.2	264.0	248.4
67.5°	328.8	339.9	369.5	383.2	404.3	372.8	303.9	257.1	232.0	209.9	199.2
70°	287.0	295.1	310.7	321.9	327.5	295.1	244.1	209.8	188.6	173.1	166.3
72.5°	245.2	252.3	255.4	264.6	261.7	231.4	196.2	169.0	153.8	143.2	134.4
75°	187.4	190.5	187.4	183.7	175.5	154.4	130.2	116.5	105.2	100.2	97.1
77.5°	136.6	135.6	131.3	125.6	111.7	98.4	85.3	80.7	75.8	73.2	72.1
80°	105.2	102.7	99.0	89.7	77.8	68.5	65.4	62.3	60.4	57.3	56.6
82.5°	78.3	76.8	70.6	62.7	54.4	50.1	47.5	46.3	44.4	42.9	42.7
85°	41.7	39.8	33.0	28.7	27.4	26.1	25.5	25.5	23.1	22.4	22.4
87.5°	13.9	11.3	11.2	10.1	10.5	9.9	10.9	10.4	10.3	10.9	10.1
90°	2.6	4.4	6.2	7.9	10.0	12.3	14.7	17.0	19.3	20.0	20.7
92.5°	20.6	21.9	23.1	24.2	25.5	26.9	28.2	29.5	30.8	31.4	31.9
95°	48.6	49.8	51.1	52.4	53.7	55.1	56.6	58.0	59.4	60.1	60.8
97.5°	85.0	86.0	86.9	87.9	88.8	89.8	90.9	91.9	92.9	93.8	94.6
100°	110.2	111.3	112.3	113.4	114.4	115.3	116.2	117.1	118.0	118.5	119.1
102.5°	138.7	139.3	140.0	140.6	141.5	142.7	143.9	145.0	146.2	146.8	147.3
105°	180.9	181.3	181.6	182.0	183.0	184.6	186.2	187.8	189.4	189.4	189.4
107.5°	230.2	230.4	230.7	230.8	231.3	232.0	232.6	233.2	233.9	234.4	235.0
110°	261.2	261.6	261.9	262.3	262.6	263.0	263.3	263.7	264.0	264.7	265.5



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	293.2	293.3	293.6	293.8	293.9	294.0	294.1	294.1	294.2	295.1	296.0
115°	341.6	342.1	342.7	343.3	343.3	342.9	342.6	342.2	341.9	342.1	342.2
117.5°	389.9	390.3	390.6	391.0	390.9	390.5	390.0	389.5	389.1	389.0	389.0
120°	420.8	421.9	422.9	424.1	424.1	423.2	422.3	421.4	420.6	420.3	420.2
122.5°	452.0	452.8	453.5	454.3	454.5	454.1	453.6	453.1	452.7	452.2	451.7
125°	499.7	500.3	500.8	501.4	501.5	501.1	500.7	500.3	500.0	499.3	498.6
127.5°	544.6	545.8	546.9	548.0	548.4	548.0	547.6	547.2	546.8	545.9	544.9
130°	574.5	575.9	577.3	578.8	579.2	578.7	578.1	577.6	577.0	576.3	575.6
132.5°	604.0	605.4	606.9	608.3	608.8	608.4	608.0	607.6	607.2	606.3	605.5
135°	648.7	649.8	650.9	652.0	652.4	652.2	652.0	651.9	651.6	650.9	650.2
137.5°	690.3	691.2	692.1	693.0	693.6	694.1	694.6	695.1	695.5	694.7	694.0
140°	719.2	720.1	721.0	721.8	722.4	722.5	722.8	722.9	723.1	722.9	722.8
142.5°	745.5	746.4	747.3	748.2	748.8	749.1	749.4	749.8	750.1	749.9	749.7
145°	786.1	786.4	786.8	787.1	787.6	788.1	788.7	789.2	789.7	789.6	789.4
147.5°	822.3	822.9	823.6	824.3	824.8	825.3	825.9	826.3	826.8	826.8	826.8
150°	847.1	847.4	847.8	848.1	848.5	848.8	849.2	849.5	849.9	849.9	849.9
152.5°	867.8	868.2	868.8	869.3	869.6	869.8	870.1	870.3	870.4	870.8	871.0
155°	899.7	899.7	899.7	899.7	899.8	899.9	900.2	900.3	900.5	901.2	901.9
157.5°	927.1	926.9	926.6	926.5	926.4	926.5	926.7	926.9	926.9	927.7	928.4
160°	944.3	943.9	943.6	943.2	943.0	943.0	943.0	943.0	943.0	943.9	944.8
162.5°	959.6	959.0	958.5	958.1	957.8	958.0	958.1	958.3	958.5	959.3	960.2
165°	979.4	978.9	978.3	977.8	977.6	977.6	977.6	977.6	977.6	978.6	979.7
167.5°	995.1	994.4	993.7	993.0	992.7	992.8	993.0	993.2	993.2	994.3	995.5
170°	1004.1	1003.4	1002.7	1002.0	1001.6	1001.6	1001.6	1001.6	1001.6	1002.8	1004.1
172.5°	1011.1	1010.4	1009.7	1009.0	1008.7	1008.7	1008.7	1008.7	1008.7	1009.8	1010.9
175°	1018.6	1017.9	1017.2	1016.4	1016.1	1016.1	1016.1	1016.1	1016.1	1017.2	1018.2
177.5°	1021.8	1021.2	1020.6	1020.0	1019.8	1019.8	1019.8	1019.8	1019.8	1020.6	1021.4
180°	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4	1454.4
2.5°	1534.1	1534.1	1536.1	1543.6	1544.6	1551.1	1549.1
5°	1686.1	1697.9	1702.2	1720.9	1732.2	1737.2	1727.2
7.5°	1871.8	1905.3	1921.0	1940.6	1958.0	1963.2	1949.6
10°	2007.4	2042.2	2071.5	2089.5	2106.3	2117.6	2131.9
12.5°	2138.3	2181.2	2209.0	2234.5	2251.8	2266.0	2268.3
15°	2280.7	2345.4	2394.6	2430.7	2448.8	2458.1	2454.4
17.5°	2424.2	2484.3	2519.3	2556.1	2581.2	2582.4	2583.1
20°	2505.4	2564.0	2604.5	2631.9	2659.9	2658.6	2664.8
22.5°	2559.8	2605.8	2636.9	2656.7	2666.3	2661.7	2662.8
25°	2585.1	2598.8	2593.3	2561.5	2553.4	2524.1	2529.1
27.5°	2454.2	2389.4	2322.4	2236.3	2168.3	2113.9	2116.7
30°	2276.3	2161.8	2031.0	1921.4	1823.0	1795.6	1737.2
32.5°	2027.7	1855.9	1702.8	1600.7	1516.2	1493.3	1442.2
35°	1606.4	1439.6	1282.0	1187.3	1150.0	1097.7	1097.1
37.5°	1248.6	1101.7	1018.4	947.4	910.1	878.5	875.4
40°	1050.4	935.8	872.9	821.9	785.1	761.4	755.9
42.5°	911.9	819.3	760.3	728.7	700.4	688.2	679.1
45°	744.7	682.4	641.3	612.7	599.6	590.3	585.3
47.5°	622.9	581.1	553.2	534.1	523.5	513.7	516.3
50°	556.7	522.4	501.8	483.8	475.7	468.8	469.4
52.5°	503.4	472.6	456.0	442.9	432.8	428.0	425.6
55°	427.1	407.8	391.0	381.7	376.0	369.2	367.3
57.5°	364.3	349.4	335.7	325.1	323.8	317.2	318.1
60°	322.5	310.1	298.9	293.3	288.9	283.3	285.2
62.5°	288.1	277.7	267.5	262.8	258.5	254.4	255.2
65°	236.0	226.0	219.8	217.3	215.4	213.6	211.7
67.5°	188.1	182.0	178.1	172.7	168.9	168.3	166.4
70°	158.1	150.0	143.2	136.3	134.5	133.9	134.5
72.5°	126.7	121.7	119.8	116.5	116.1	114.5	115.6
75°	95.3	93.4	92.1	89.7	89.7	89.7	89.7
77.5°	70.3	69.1	68.4	67.9	67.3	66.4	66.2
80°	54.8	54.2	52.9	52.9	52.3	52.9	52.3
82.5°	41.4	41.2	40.0	40.0	39.4	39.0	39.4
85°	21.2	20.5	21.8	20.5	21.2	20.0	21.2
87.5°	10.2	10.4	10.0	10.1	9.7	10.7	9.8
90°	21.4	22.1	22.7	23.0	23.4	23.7	24.1
92.5°	32.6	33.1	33.3	33.0	32.9	32.6	32.4
95°	61.6	62.3	62.6	62.6	62.6	62.6	62.6
97.5°	95.4	96.3	96.6	96.5	96.5	96.4	96.3
100°	119.6	120.1	120.6	120.9	121.3	121.6	122.0
102.5°	147.8	148.4	148.6	148.5	148.5	148.4	148.3
105°	189.4	189.4	189.6	190.0	190.3	190.7	191.0
107.5°	235.6	236.1	236.3	236.1	235.9	235.7	235.4
110°	266.2	266.9	267.0	266.7	266.3	266.0	265.6



TEST NUMBER: P332479-927

CATALOG NUMBER: S123RDIW-S1165D1030U927-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	296.8	297.6	298.0	297.9	297.9	297.9	297.8
115°	342.5	342.6	342.6	342.5	342.2	342.1	341.9
117.5°	389.0	389.0	388.6	388.2	387.7	387.1	386.7
120°	420.0	419.9	419.5	419.2	418.8	418.5	418.1
122.5°	451.2	450.8	450.3	449.8	449.3	448.9	448.3
125°	497.9	497.2	496.5	495.7	495.0	494.3	493.6
127.5°	543.9	542.9	541.9	541.1	540.3	539.5	538.7
130°	574.9	574.2	573.2	572.0	570.7	569.5	568.2
132.5°	604.7	603.8	602.9	601.9	600.9	600.0	599.0
135°	649.5	648.8	648.3	647.9	647.6	647.2	646.9
137.5°	693.2	692.5	691.8	691.1	690.5	689.8	689.1
140°	722.5	722.4	721.7	720.4	719.2	718.0	716.7
142.5°	749.6	749.4	748.8	747.8	746.9	745.9	745.0
145°	789.2	789.0	788.5	787.8	787.1	786.4	785.7
147.5°	826.8	826.8	826.2	825.2	824.1	823.1	822.0
150°	849.9	849.9	849.4	848.3	847.2	846.2	845.1
152.5°	871.3	871.6	871.3	870.4	869.4	868.5	867.6
155°	902.6	903.3	903.1	901.8	900.6	899.4	898.1
157.5°	929.2	929.9	929.9	928.8	927.9	926.9	925.8
160°	945.7	946.6	946.7	945.9	945.2	944.5	943.8
162.5°	961.1	962.0	961.9	960.8	959.6	958.5	957.3
165°	980.7	981.8	981.8	980.5	979.2	977.9	976.8
167.5°	996.6	997.7	997.7	996.6	995.5	994.3	993.2
170°	1005.4	1006.6	1006.6	1005.4	1004.1	1002.8	1001.6
172.5°	1012.0	1013.1	1013.0	1011.8	1010.5	1009.2	1008.1
175°	1019.3	1020.3	1020.3	1019.0	1017.7	1016.5	1015.3
177.5°	1022.3	1023.2	1023.1	1022.1	1021.1	1020.1	1019.1
180°	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7	1021.7

(END OF REPORT)