

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P332458-930

Luminaire Tested: **S123RDIW-S1000D1030U930-4F0-1E-UDD-A**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P332458-930
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-5,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S123RDIW-S1000D1030U930-4F0-1E-UDD-A
Description: DEFINE 3 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 1000 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING
UPLIGHT 1030 LUMENS PER FOOT, NO LENS
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6591.4 lumens
Efficiency: N/A
Efficacy: 107.7 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.22 / 1.36
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')
CIE Type: General Diffuse


Input Watts (W): 61.2
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

Luminous Intensity Polar Plot





TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	107	107	107	107	98	98	98	98	83	83	83	68	68	68	55	55	55	49
1	98	94	90	87	90	87	84	81	73	71	69	61	60	58	50	49	48	42
2	90	83	77	72	83	77	72	67	65	61	58	54	52	49	44	43	41	36
3	82	73	66	61	76	68	62	57	58	53	50	49	45	42	40	38	36	32
4	76	65	58	52	69	61	54	49	52	47	43	44	40	37	36	33	31	28
5	70	58	50	45	64	54	47	42	47	41	37	39	35	32	33	30	27	24
6	64	53	45	39	59	49	42	37	42	37	33	36	32	29	30	27	24	22
7	59	48	40	34	55	44	37	33	38	33	29	33	28	25	27	24	22	19
8	55	43	36	31	51	40	34	29	35	30	26	30	26	23	25	22	20	17
9	52	40	32	27	48	37	30	26	32	27	23	28	24	21	23	20	18	16
10	48	36	29	25	45	34	28	23	30	25	21	26	22	19	22	19	16	14

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	13951	13951	13951	13951
5°	16630	14011	12337	14011
10°	20764	13930	11146	13930
15°	24373	13788	10165	13788
20°	27202	13575	9330	13575
25°	26766	13351	8817	13351
30°	19240	13144	8289	13144
35°	12846	12875	7947	12875
40°	9465	12552	7593	12552
45°	7939	11985	7247	11985
50°	7005	11241	6764	11241
55°	6142	10393	6101	10393
60°	5470	9580	5591	9580
65°	4806	8706	5201	8706
70°	3770	7928	4749	7928
75°	3323	6924	4338	6924
80°	2889	5883	4265	5883
85°	2322	4730	4520	4730



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	127.5	1.9
10°-20°	398.2	6.0
20°-30°	625.6	9.5
30°-40°	652.7	9.9
40°-50°	558.6	8.5
50°-60°	425.7	6.5
60°-70°	272.9	4.1
70°-80°	131.3	2.0
80°-90°	37.8	0.6
90°-100°	40.1	0.6
100°-110°	191.0	2.9
110°-120°	458.8	7.0
120°-130°	584.2	8.9
130°-140°	624.2	9.5
140°-150°	583.7	8.9
150°-160°	470.8	7.1
160°-170°	303.9	4.6
170°-180°	104.7	1.6
0°-30°	1151.2	17.5
0°-40°	1803.9	27.4
0°-60°	2788.2	42.3
0°-90°	3230.2	49.0
90°-120°	689.8	10.5
90°-150°	2481.9	37.7
90°-180°	3361.0	51.0
0°-180°	6591.4	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1296	1296	1296	1296	1296	
5°	1539	1297	1142	1297	1539	159
15°	2187	1237	912	1237	2187	620
25°	2254	1124	742	1124	2254	969
35°	978	980	605	980	978	641
45°	522	787	476	787	522	410
55°	327	554	325	554	327	296
65°	189	342	204	342	189	186
75°	80	166	104	166	80	86
85°	19	38	37	38	19	22
90°	24	1	24	1	24	12
95°	31	50	31	50	31	26
105°	36	244	36	244	36	82
115°	482	458	482	458	482	445
125°	658	645	658	645	658	588
135°	812	803	812	803	812	626
145°	936	927	936	927	936	584
155°	1020	1021	1020	1021	1020	470
165°	1074	1077	1074	1077	1074	303
175°	1098	1102	1098	1102	1098	105
180°	1102	1102	1102	1102	1102	



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1
2.5°	1380.5	1382.2	1376.5	1375.6	1368.9	1367.1	1367.1	1357.8	1352.0	1344.5	1340.0
5°	1539.1	1548.0	1543.5	1533.6	1516.9	1513.0	1502.5	1485.9	1467.0	1443.7	1432.6
7.5°	1737.3	1749.4	1744.7	1729.3	1711.9	1697.8	1668.1	1640.5	1601.7	1567.7	1538.7
10°	1899.7	1887.0	1877.0	1862.1	1845.9	1819.8	1788.8	1746.0	1696.7	1657.8	1614.6
12.5°	2021.4	2019.3	2006.6	1991.2	1968.5	1943.7	1905.5	1853.5	1796.1	1740.0	1690.4
15°	2187.2	2190.5	2182.1	2166.1	2133.9	2090.1	2032.4	2010.8	1928.6	1867.6	1806.5
17.5°	2301.9	2301.3	2300.1	2277.9	2245.0	2213.8	2160.3	2103.4	2029.0	1943.0	1860.8
20°	2374.7	2369.2	2370.2	2345.3	2320.9	2284.8	2232.7	2150.0	2089.0	1989.7	1904.8
22.5°	2372.9	2371.8	2376.0	2367.5	2349.8	2322.1	2281.0	2211.3	2133.3	2033.1	1937.6
25°	2253.7	2249.3	2275.4	2282.6	2310.9	2315.9	2303.7	2265.4	2191.6	2088.4	1970.3
27.5°	1886.2	1883.7	1932.2	1992.8	2069.6	2129.2	2187.0	2214.8	2191.6	2117.7	1999.3
30°	1548.0	1600.2	1624.6	1712.2	1809.9	1926.4	2028.5	2125.6	2149.5	2117.3	2020.1
32.5°	1285.2	1330.7	1351.1	1426.4	1517.4	1653.8	1807.0	1944.5	2041.6	2066.2	2007.8
35°	977.6	978.2	1024.7	1058.1	1142.4	1282.8	1431.5	1615.7	1798.8	1937.5	1951.9
37.5°	780.1	782.9	811.1	844.2	907.5	981.7	1112.6	1265.8	1477.3	1690.3	1815.1
40°	673.6	678.6	699.7	732.4	777.9	833.9	936.0	1080.3	1256.7	1493.6	1687.3
42.5°	605.2	613.3	624.2	649.4	677.6	730.0	812.6	924.1	1084.5	1308.6	1531.9
45°	521.5	525.9	534.3	545.9	571.4	608.1	663.6	738.5	871.6	1052.0	1275.5
47.5°	460.1	457.7	466.5	476.0	492.9	517.9	555.1	616.2	711.2	855.9	1045.5
50°	418.3	417.8	423.9	431.1	447.2	465.5	496.0	542.1	617.5	737.4	911.0
52.5°	379.3	381.4	385.7	394.7	406.3	421.1	448.5	481.7	546.5	650.0	794.8
55°	327.3	329.1	335.1	340.1	348.5	363.4	380.6	408.4	452.7	524.9	644.2
57.5°	283.4	282.7	288.5	289.8	299.1	311.4	324.7	346.3	378.4	432.0	512.3
60°	254.1	252.4	257.5	261.3	266.4	276.3	287.4	308.5	334.0	373.4	442.2
62.5°	227.5	226.7	230.4	234.2	238.4	247.4	256.8	273.0	293.2	326.4	381.0
65°	188.7	190.3	192.0	193.6	195.8	201.4	210.3	221.4	235.2	258.5	297.9
67.5°	148.2	149.9	150.5	153.9	158.7	162.2	167.5	177.4	187.1	206.8	229.2
70°	119.8	119.3	119.8	121.5	127.6	133.7	141.0	148.1	154.3	168.1	186.9
72.5°	103.0	102.0	103.5	103.8	106.7	108.4	113.0	119.8	127.6	137.1	150.6
75°	79.9	79.9	79.9	79.9	82.1	83.2	84.9	86.6	89.4	93.8	103.8
77.5°	59.0	59.1	59.9	60.5	60.9	61.6	62.6	64.2	65.2	67.6	71.9
80°	46.6	47.1	46.6	47.1	47.1	48.3	48.8	50.5	51.0	53.8	55.5
82.5°	35.1	34.7	35.1	35.6	35.6	36.8	36.9	38.1	38.2	39.6	41.3
85°	18.8	17.8	18.8	18.3	19.4	18.3	18.8	20.0	20.0	20.5	22.7
87.5°	9.4	10.2	9.2	9.5	9.5	9.9	9.7	9.5	10.3	9.7	9.7
90°	24.5	24.2	23.8	23.5	23.1	22.6	21.9	21.1	20.4	19.6	17.3
92.5°	27.1	27.0	26.7	26.5	26.3	25.6	24.5	23.3	22.1	21.0	19.2
95°	31.1	31.1	31.1	31.1	31.1	30.5	29.2	28.0	26.7	25.4	23.4
97.5°	33.8	33.6	33.3	33.2	33.0	32.2	30.7	29.3	27.8	26.3	23.9
100°	34.4	34.2	34.0	33.8	33.7	32.9	31.4	29.9	28.5	27.0	25.4
102.5°	35.1	34.7	34.4	34.1	33.8	33.8	32.9	31.4	29.9	28.5	27.0
105°	36.0	35.6	35.3	35.0	34.6	34.6	32.9	31.4	29.9	28.5	27.0
107.5°	113.2	137.5	161.8	186.0	210.3	234.2	257.9	281.4	305.1	328.7	326.1
110°	225.2	251.2	277.2	303.3	329.3	345.3	351.3	357.3	363.3	369.3	367.3



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	386.4	391.8	397.4	402.8	408.3	411.0	410.9	410.8	410.7	410.6	408.6
115°	481.5	480.8	480.0	479.3	478.6	477.4	475.5	473.7	471.9	470.0	468.4
117.5°	534.9	534.8	534.6	534.4	534.3	533.5	532.1	530.6	529.1	527.7	526.8
120°	571.6	571.6	571.6	571.6	571.6	570.9	569.4	567.9	566.5	565.0	564.5
122.5°	607.6	607.5	607.3	607.2	607.1	606.4	605.4	604.4	603.4	602.3	601.7
125°	658.4	658.0	657.6	657.3	657.0	656.6	656.2	655.8	655.5	655.1	654.4
127.5°	707.2	707.6	707.9	708.3	708.7	708.6	707.9	707.4	706.8	706.2	705.3
130°	738.7	739.0	739.4	739.7	740.1	739.9	739.2	738.5	737.8	737.0	736.3
132.5°	767.4	768.0	768.5	769.0	769.5	769.4	768.7	767.9	767.2	766.5	765.9
135°	811.5	812.0	812.6	813.2	813.7	813.7	813.2	812.6	812.0	811.5	810.8
137.5°	853.0	853.3	853.7	854.0	854.4	854.2	853.3	852.4	851.5	850.7	850.3
140°	877.8	878.2	878.6	879.0	879.3	879.1	878.4	877.7	876.9	876.2	875.6
142.5°	900.7	901.3	901.8	902.3	902.8	902.8	902.2	901.6	901.1	900.4	899.9
145°	936.0	936.0	936.0	936.0	936.0	935.8	935.5	935.1	934.7	934.3	934.0
147.5°	962.2	963.0	963.8	964.7	965.6	965.8	965.4	965.1	964.7	964.3	963.9
150°	981.9	982.4	982.9	983.5	984.1	984.1	983.7	983.4	983.0	982.7	982.3
152.5°	997.6	998.4	999.2	1000.0	1000.9	1001.0	1000.4	999.7	999.1	998.4	998.2
155°	1019.5	1020.6	1021.7	1022.8	1023.9	1024.0	1023.0	1022.1	1021.2	1020.3	1020.2
157.5°	1038.0	1039.4	1040.9	1042.3	1043.7	1043.8	1042.8	1041.7	1040.6	1039.5	1039.7
160°	1049.8	1051.1	1052.4	1053.6	1054.9	1055.0	1053.9	1052.8	1051.7	1050.7	1050.8
162.5°	1060.9	1062.1	1063.2	1064.4	1065.4	1065.4	1064.2	1062.9	1061.7	1060.5	1060.6
165°	1074.4	1075.6	1076.9	1078.2	1079.5	1079.4	1077.9	1076.4	1075.1	1073.6	1073.7
167.5°	1084.0	1085.5	1087.0	1088.4	1089.9	1089.9	1088.4	1087.0	1085.5	1084.0	1084.0
170°	1090.0	1091.4	1092.8	1094.3	1095.8	1095.8	1094.3	1092.8	1091.4	1090.0	1090.0
172.5°	1093.2	1094.8	1096.4	1098.0	1099.6	1099.7	1098.2	1096.8	1095.4	1093.9	1093.7
175°	1098.1	1099.6	1101.1	1102.5	1104.0	1104.1	1102.8	1101.5	1100.2	1098.9	1098.8
177.5°	1099.6	1101.1	1102.5	1104.0	1105.5	1105.5	1104.4	1103.3	1102.1	1100.9	1100.7
180°	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1
2.5°	1338.2	1336.9	1330.7	1323.6	1314.3	1308.1	1303.2	1300.6	1292.6	1282.8	1276.1
5°	1420.9	1404.3	1386.6	1364.9	1344.9	1324.4	1311.7	1296.7	1278.3	1257.8	1243.4
7.5°	1509.5	1476.8	1441.7	1405.4	1369.5	1337.4	1309.0	1284.7	1255.5	1226.0	1205.4
10°	1577.4	1529.7	1480.3	1429.8	1383.7	1340.5	1307.2	1274.5	1239.5	1205.7	1180.1
12.5°	1639.1	1576.3	1519.4	1457.3	1398.4	1346.7	1298.8	1260.3	1218.2	1182.1	1153.1
15°	1717.2	1652.9	1584.0	1489.7	1411.5	1346.1	1287.8	1237.3	1186.3	1141.8	1113.5
17.5°	1790.2	1693.4	1600.9	1522.2	1420.6	1338.8	1267.7	1207.3	1151.3	1104.2	1069.4
20°	1820.4	1726.6	1626.2	1525.8	1426.0	1334.4	1251.7	1185.1	1126.9	1073.6	1041.5
22.5°	1838.6	1732.4	1626.7	1518.7	1412.6	1317.5	1235.7	1162.5	1099.3	1048.7	1009.0
25°	1859.8	1733.3	1616.8	1510.3	1402.1	1298.9	1201.8	1124.1	1055.9	1002.0	959.9
27.5°	1873.8	1725.0	1587.3	1468.8	1359.1	1256.4	1167.3	1085.0	1015.8	958.9	913.6
30°	1876.5	1718.3	1564.6	1436.5	1324.9	1230.6	1136.3	1057.5	984.3	923.8	881.7
32.5°	1880.0	1701.9	1534.0	1397.8	1283.7	1190.3	1104.8	1029.6	954.6	895.0	851.9
35°	1865.4	1692.8	1487.5	1331.1	1216.8	1126.3	1049.2	979.8	906.0	848.3	804.5
37.5°	1802.3	1656.8	1439.3	1255.8	1136.3	1052.6	989.7	929.3	861.5	799.3	758.0
40°	1738.9	1621.2	1402.1	1210.1	1085.2	999.2	942.6	893.3	827.9	769.6	725.2
42.5°	1644.3	1572.9	1366.6	1162.1	1027.5	944.7	896.9	850.7	793.2	734.0	692.4
45°	1470.9	1480.3	1293.9	1085.8	947.6	864.5	819.5	787.3	736.3	687.5	644.7
47.5°	1253.4	1341.6	1208.5	1004.4	863.4	785.3	746.0	718.0	683.5	635.6	596.6
50°	1111.3	1237.3	1140.2	949.9	810.7	733.0	694.1	671.3	641.4	603.6	566.5
52.5°	980.4	1115.7	1057.6	889.1	753.3	682.3	644.4	625.7	601.9	566.4	532.7
55°	799.5	936.5	923.2	797.3	667.5	603.6	574.8	553.8	537.6	511.0	484.4
57.5°	646.7	776.7	783.5	695.2	591.8	528.7	503.9	488.0	477.5	457.4	432.8
60°	550.4	669.7	693.0	626.4	537.6	482.2	457.7	445.0	436.7	420.5	401.7
62.5°	470.5	572.0	598.4	550.5	485.7	433.7	414.7	402.4	396.7	382.9	366.2
65°	360.1	444.4	469.9	443.3	409.4	367.9	352.3	341.8	336.8	329.1	316.8
67.5°	270.8	332.2	360.2	341.4	329.2	303.0	293.1	287.4	283.0	277.6	267.4
70°	217.5	263.0	291.9	286.8	276.9	263.0	255.8	251.9	247.4	243.0	234.2
72.5°	174.9	206.2	233.3	235.8	227.6	224.9	218.5	216.9	214.2	208.9	204.0
75°	115.9	137.6	156.5	163.7	167.0	169.7	167.0	166.5	165.9	161.4	158.7
77.5°	76.0	87.6	99.5	111.9	117.1	120.8	121.7	123.8	122.3	119.9	118.6
80°	58.3	61.1	69.4	79.9	88.2	91.6	93.8	94.9	94.3	93.8	91.6
82.5°	42.3	44.6	48.5	55.9	62.9	68.5	69.8	69.5	70.8	71.1	69.4
85°	22.7	23.3	24.4	25.5	29.4	35.5	37.2	38.3	39.4	39.4	36.0
87.5°	10.1	9.1	9.6	9.1	10.1	10.2	12.5	14.3	15.2	13.8	14.1
90°	14.9	12.6	10.2	8.1	6.3	4.5	2.6	0.8	2.6	4.5	6.3
92.5°	17.4	15.7	13.9	13.2	13.7	14.2	14.8	15.2	14.8	14.2	13.7
95°	21.4	19.4	17.4	20.1	27.6	35.1	42.5	50.0	42.5	35.1	27.6
97.5°	52.6	65.7	78.8	87.0	90.3	93.7	97.0	100.4	97.0	93.7	90.3
100°	83.8	112.2	140.6	153.0	149.3	145.7	142.0	138.4	142.0	145.7	149.3
102.5°	115.9	146.9	177.9	192.1	189.5	186.9	184.3	181.6	184.3	186.9	189.5
105°	212.1	228.4	244.8	252.0	250.1	248.0	246.1	244.0	246.1	248.0	250.1
107.5°	323.5	321.0	318.4	316.3	314.7	313.1	311.4	309.9	311.4	313.1	314.7
110°	365.3	363.3	361.3	359.5	358.2	356.7	355.2	353.8	355.2	356.7	358.2



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	406.6	404.6	402.6	401.0	399.7	398.3	397.0	395.7	397.0	398.3	399.7
115°	466.8	465.1	463.5	462.1	461.1	459.9	458.9	457.8	458.9	459.9	461.1
117.5°	526.0	525.2	524.3	523.3	521.9	520.6	519.2	517.9	519.2	520.6	521.9
120°	563.9	563.4	562.9	561.7	560.1	558.5	556.8	555.2	556.8	558.5	560.1
122.5°	601.0	600.3	599.6	598.6	597.2	595.9	594.5	593.2	594.5	595.9	597.2
125°	653.6	652.9	652.2	651.1	649.6	648.2	646.8	645.3	646.8	648.2	649.6
127.5°	704.5	703.6	702.7	701.6	700.1	698.6	697.2	695.7	697.2	698.6	700.1
130°	735.6	734.8	734.1	733.0	731.6	730.1	728.6	727.2	728.6	730.1	731.6
132.5°	765.3	764.8	764.2	763.1	761.7	760.2	758.8	757.3	758.8	760.2	761.7
135°	810.1	809.3	808.6	807.7	806.6	805.5	804.5	803.3	804.5	805.5	806.6
137.5°	849.9	849.5	849.1	848.2	846.8	845.4	844.0	842.6	844.0	845.4	846.8
140°	875.1	874.6	874.0	873.2	872.1	871.1	869.9	868.9	869.9	871.1	872.1
142.5°	899.4	898.8	898.3	897.5	896.3	895.3	894.1	893.1	894.1	895.3	896.3
145°	933.6	933.3	932.9	932.1	930.8	929.5	928.2	927.0	928.2	929.5	930.8
147.5°	963.6	963.2	962.9	962.3	961.4	960.6	959.8	959.0	959.8	960.6	961.4
150°	981.9	981.5	981.2	980.7	980.2	979.7	979.1	978.6	979.1	979.7	980.2
152.5°	997.9	997.8	997.5	997.3	997.0	996.8	996.5	996.3	996.5	996.8	997.0
155°	1019.9	1019.8	1019.6	1019.7	1020.1	1020.4	1020.8	1021.2	1020.8	1020.4	1020.1
157.5°	1039.8	1040.1	1040.2	1040.3	1040.4	1040.4	1040.5	1040.5	1040.5	1040.4	1040.4
160°	1051.0	1051.2	1051.3	1051.6	1051.7	1051.9	1052.1	1052.3	1052.1	1051.9	1051.7
162.5°	1060.9	1061.0	1061.2	1061.5	1062.0	1062.5	1062.9	1063.4	1062.9	1062.5	1062.0
165°	1073.9	1074.1	1074.3	1074.6	1075.2	1075.8	1076.3	1076.8	1076.3	1075.8	1075.2
167.5°	1084.0	1084.0	1084.0	1084.4	1085.2	1085.9	1086.6	1087.3	1086.6	1085.9	1085.2
170°	1090.0	1090.0	1090.0	1090.3	1091.0	1091.8	1092.5	1093.2	1092.5	1091.8	1091.0
172.5°	1093.6	1093.4	1093.3	1093.6	1094.5	1095.4	1096.3	1097.1	1096.3	1095.4	1094.5
175°	1098.6	1098.4	1098.2	1098.6	1099.5	1100.4	1101.3	1102.2	1101.3	1100.4	1099.5
177.5°	1100.7	1100.5	1100.3	1100.7	1101.4	1102.1	1102.8	1103.5	1102.8	1102.1	1101.4
180°	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1
2.5°	1273.9	1268.1	1264.1	1255.2	1249.5	1243.2	1237.1	1241.0	1240.6	1240.2	1240.2
5°	1231.2	1218.4	1206.8	1191.8	1182.3	1170.7	1161.8	1160.7	1162.9	1155.2	1150.7
7.5°	1188.8	1171.3	1154.9	1138.3	1120.8	1106.8	1098.0	1093.9	1088.3	1083.5	1078.5
10°	1159.0	1138.6	1122.4	1101.9	1083.0	1066.4	1055.9	1048.6	1044.7	1040.9	1033.6
12.5°	1128.5	1108.3	1087.9	1064.6	1046.7	1027.4	1019.5	1011.4	1004.0	999.6	989.7
15°	1083.6	1057.5	1035.9	1011.5	991.5	972.7	961.6	945.4	943.2	937.7	927.7
17.5°	1038.7	1010.3	980.5	962.5	939.9	920.2	903.4	898.0	882.1	876.1	867.4
20°	1003.1	977.1	954.3	930.5	897.7	879.4	866.1	858.9	846.1	838.4	832.8
22.5°	972.5	946.0	919.7	891.9	864.9	844.3	834.6	823.4	816.4	805.5	799.5
25°	928.8	899.9	868.3	838.4	819.0	803.4	787.9	777.9	767.9	762.9	751.8
27.5°	878.0	847.8	818.2	795.5	771.7	756.4	742.2	733.4	721.4	713.0	706.9
30°	850.0	814.5	789.0	768.4	737.9	723.5	713.0	701.9	693.0	684.1	678.0
32.5°	817.6	785.2	761.0	735.6	712.2	696.4	682.8	673.0	665.4	657.0	650.9
35°	766.8	739.6	714.6	689.1	671.9	655.8	639.8	631.4	624.2	616.4	610.9
37.5°	720.8	695.5	671.7	647.5	626.1	613.1	600.1	593.8	584.0	578.8	573.2
40°	692.4	667.5	642.0	618.6	596.5	586.4	574.8	565.4	556.5	552.6	546.5
42.5°	661.4	636.4	614.9	589.8	571.6	558.1	547.3	537.0	530.4	524.6	521.2
45°	615.3	593.1	572.0	547.1	529.9	518.2	506.0	496.6	490.5	486.6	480.5
47.5°	570.6	548.4	527.0	505.2	488.6	475.2	463.1	456.5	448.4	443.7	439.5
50°	538.2	518.2	495.5	475.5	458.9	445.6	435.5	427.2	420.0	413.9	411.2
52.5°	508.4	487.1	467.5	448.9	431.3	416.2	407.2	398.4	393.0	386.0	382.7
55°	459.4	438.9	422.2	403.9	386.7	374.0	362.9	355.1	349.5	341.8	337.4
57.5°	413.4	394.9	375.0	359.2	341.4	330.7	321.5	311.0	304.2	298.1	293.8
60°	382.3	361.2	344.0	329.1	313.5	299.6	291.3	283.0	275.7	269.6	265.8
62.5°	349.8	331.5	315.1	298.8	284.6	272.6	262.9	255.9	249.6	245.6	241.8
65°	300.2	285.8	269.1	255.8	242.5	233.6	225.8	219.7	215.2	212.5	209.2
67.5°	254.5	240.4	225.9	212.9	204.0	197.2	192.1	186.9	184.7	181.1	178.9
70°	224.7	210.3	197.5	187.5	178.6	173.7	170.3	166.5	164.2	159.8	157.6
72.5°	192.3	181.9	172.7	164.4	157.4	152.8	148.5	143.8	140.2	135.3	133.1
75°	151.5	142.0	134.9	129.3	124.8	118.7	112.6	107.6	106.0	104.3	103.8
77.5°	112.2	106.2	101.0	96.3	90.7	86.3	85.0	83.9	83.6	82.7	82.7
80°	88.2	82.7	78.8	73.2	69.9	69.9	69.9	68.8	69.4	69.4	69.4
82.5°	65.6	60.5	58.4	56.3	55.7	56.2	56.2	56.3	56.0	56.9	56.5
85°	33.8	34.4	35.5	35.0	35.5	35.5	36.6	36.0	36.6	35.5	36.6
87.5°	14.0	15.8	16.7	17.6	18.6	18.6	19.2	19.3	19.9	20.1	20.1
90°	8.1	10.2	12.6	14.9	17.3	19.6	20.4	21.1	21.9	22.6	23.1
92.5°	13.2	13.9	15.7	17.4	19.2	21.0	22.1	23.3	24.5	25.6	26.3
95°	20.1	17.4	19.4	21.4	23.4	25.4	26.7	28.0	29.2	30.5	31.1
97.5°	87.0	78.8	65.7	52.6	39.5	26.3	27.8	29.3	30.7	32.2	33.0
100°	153.0	140.6	112.2	83.8	55.4	27.0	28.5	29.9	31.4	32.9	33.7
102.5°	192.1	177.9	146.9	115.9	84.9	53.9	49.4	44.8	40.4	35.8	33.8
105°	252.0	244.8	228.4	212.1	195.8	179.4	147.2	115.0	82.7	50.5	34.6
107.5°	316.3	318.4	321.0	323.5	326.1	328.7	305.1	281.4	257.9	234.2	210.3
110°	359.5	361.3	363.3	365.3	367.3	369.3	363.3	357.3	351.3	345.3	329.3



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	401.0	402.6	404.6	406.6	408.6	410.6	410.7	410.8	410.9	411.0	408.3
115°	462.1	463.5	465.1	466.8	468.4	470.0	471.9	473.7	475.5	477.4	478.6
117.5°	523.3	524.3	525.2	526.0	526.8	527.7	529.1	530.6	532.1	533.5	534.3
120°	561.7	562.9	563.4	563.9	564.5	565.0	566.5	567.9	569.4	570.9	571.6
122.5°	598.6	599.6	600.3	601.0	601.7	602.3	603.4	604.4	605.4	606.4	607.1
125°	651.1	652.2	652.9	653.6	654.4	655.1	655.5	655.8	656.2	656.6	657.0
127.5°	701.6	702.7	703.6	704.5	705.3	706.2	706.8	707.4	707.9	708.6	708.7
130°	733.0	734.1	734.8	735.6	736.3	737.0	737.8	738.5	739.2	739.9	740.1
132.5°	763.1	764.2	764.8	765.3	765.9	766.5	767.2	767.9	768.7	769.4	769.5
135°	807.7	808.6	809.3	810.1	810.8	811.5	812.0	812.6	813.2	813.7	813.7
137.5°	848.2	849.1	849.5	849.9	850.3	850.7	851.5	852.4	853.3	854.2	854.4
140°	873.2	874.0	874.6	875.1	875.6	876.2	876.9	877.7	878.4	879.1	879.3
142.5°	897.5	898.3	898.8	899.4	899.9	900.4	901.1	901.6	902.2	902.8	902.8
145°	932.1	932.9	933.3	933.6	934.0	934.3	934.7	935.1	935.5	935.8	936.0
147.5°	962.3	962.9	963.2	963.6	963.9	964.3	964.7	965.1	965.4	965.8	965.6
150°	980.7	981.2	981.5	981.9	982.3	982.7	983.0	983.4	983.7	984.1	984.1
152.5°	997.3	997.5	997.8	997.9	998.2	998.4	999.1	999.7	1000.4	1001.0	1000.9
155°	1019.7	1019.6	1019.8	1019.9	1020.2	1020.3	1021.2	1022.1	1023.0	1024.0	1023.9
157.5°	1040.3	1040.2	1040.1	1039.8	1039.7	1039.5	1040.6	1041.7	1042.8	1043.8	1043.7
160°	1051.6	1051.3	1051.2	1051.0	1050.8	1050.7	1051.7	1052.8	1053.9	1055.0	1054.9
162.5°	1061.5	1061.2	1061.0	1060.9	1060.6	1060.5	1061.7	1062.9	1064.2	1065.4	1065.4
165°	1074.6	1074.3	1074.1	1073.9	1073.7	1073.6	1075.1	1076.4	1077.9	1079.4	1079.5
167.5°	1084.4	1084.0	1084.0	1084.0	1084.0	1084.0	1085.5	1087.0	1088.4	1089.9	1089.9
170°	1090.3	1090.0	1090.0	1090.0	1090.0	1090.0	1091.4	1092.8	1094.3	1095.8	1095.8
172.5°	1093.6	1093.3	1093.4	1093.6	1093.7	1093.9	1095.4	1096.8	1098.2	1099.7	1099.6
175°	1098.6	1098.2	1098.4	1098.6	1098.8	1098.9	1100.2	1101.5	1102.8	1104.1	1104.0
177.5°	1100.7	1100.3	1100.5	1100.7	1100.7	1100.9	1102.1	1103.3	1104.4	1105.5	1105.5
180°	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1
2.5°	1234.9	1234.4	1234.9	1233.1	1234.9	1234.4	1234.9	1240.2	1240.2	1240.6	1241.0
5°	1149.1	1148.5	1146.9	1141.8	1146.9	1148.5	1149.1	1150.7	1155.2	1162.9	1160.7
7.5°	1074.2	1073.4	1068.5	1068.6	1068.5	1073.4	1074.2	1078.5	1083.5	1088.3	1093.9
10°	1029.8	1030.3	1023.7	1019.8	1023.7	1030.3	1029.8	1033.6	1040.9	1044.7	1048.6
12.5°	986.8	984.1	978.8	974.5	978.8	984.1	986.8	989.7	999.6	1004.0	1011.4
15°	929.9	924.4	911.0	912.2	911.0	924.4	929.9	927.7	937.7	943.2	945.4
17.5°	863.0	858.9	858.7	850.9	858.7	858.9	863.0	867.4	876.1	882.1	898.0
20°	823.9	821.2	822.2	814.5	822.2	821.2	823.9	832.8	838.4	846.1	858.9
22.5°	793.3	790.5	785.9	783.4	785.9	790.5	793.3	799.5	805.5	816.4	823.4
25°	748.4	744.0	739.6	742.4	739.6	744.0	748.4	751.8	762.9	767.9	777.9
27.5°	703.7	700.3	695.9	695.3	695.9	700.3	703.7	706.9	713.0	721.4	733.4
30°	675.2	671.9	669.7	666.9	669.7	671.9	675.2	678.0	684.1	693.0	701.9
32.5°	646.4	645.7	641.7	641.2	641.7	645.7	646.4	650.9	657.0	665.4	673.0
35°	608.6	605.4	604.2	604.8	604.2	605.4	608.6	610.9	616.4	624.2	631.4
37.5°	572.8	568.3	566.4	564.4	566.4	568.3	572.8	573.2	578.8	584.0	593.8
40°	547.1	542.7	541.5	540.4	541.5	542.7	547.1	546.5	552.6	556.5	565.4
42.5°	518.2	516.4	515.8	513.8	515.8	516.4	518.2	521.2	524.6	530.4	537.0
45°	478.8	478.3	474.9	476.1	474.9	478.3	478.8	480.5	486.6	490.5	496.6
47.5°	437.3	434.9	432.5	434.1	432.5	434.9	437.3	439.5	443.7	448.4	456.5
50°	409.0	407.8	402.8	403.9	402.8	407.8	409.0	411.2	413.9	420.0	427.2
52.5°	380.5	376.3	374.4	373.7	374.4	376.3	380.5	382.7	386.0	393.0	398.4
55°	333.5	328.5	326.3	325.1	326.3	328.5	333.5	337.4	341.8	349.5	355.1
57.5°	287.3	285.9	284.2	285.4	284.2	285.9	287.3	293.8	298.1	304.2	311.0
60°	260.2	260.2	260.2	259.7	260.2	260.2	260.2	265.8	269.6	275.7	283.0
62.5°	239.4	238.0	237.6	238.4	237.6	238.0	239.4	241.8	245.6	249.6	255.9
65°	207.5	206.9	204.7	204.2	204.7	206.9	207.5	209.2	212.5	215.2	219.7
67.5°	177.4	175.5	174.8	174.0	174.8	175.5	177.4	178.9	181.1	184.7	186.9
70°	154.8	153.7	150.3	150.9	150.3	153.7	154.8	157.6	159.8	164.2	166.5
72.5°	130.4	129.3	128.6	127.8	128.6	129.3	130.4	133.1	135.3	140.2	143.8
75°	103.2	102.6	102.1	104.3	102.1	102.6	103.2	103.8	104.3	106.0	107.6
77.5°	82.7	82.7	83.0	82.1	83.0	82.7	82.7	82.7	82.7	83.6	83.9
80°	69.4	69.4	68.8	68.8	68.8	69.4	69.4	69.4	69.4	69.4	68.8
82.5°	55.6	56.0	56.3	55.5	56.3	56.0	55.6	56.5	56.9	56.0	56.3
85°	36.6	36.0	37.2	36.6	37.2	36.0	36.6	36.6	35.5	36.6	36.0
87.5°	21.1	20.3	20.4	20.9	20.4	20.3	21.1	20.1	20.1	19.9	19.3
90°	23.5	23.8	24.2	24.5	24.2	23.8	23.5	23.1	22.6	21.9	21.1
92.5°	26.5	26.7	27.0	27.1	27.0	26.7	26.5	26.3	25.6	24.5	23.3
95°	31.1	31.1	31.1	31.1	31.1	31.1	31.1	31.1	30.5	29.2	28.0
97.5°	33.2	33.3	33.6	33.8	33.6	33.3	33.2	33.0	32.2	30.7	29.3
100°	33.8	34.0	34.2	34.4	34.2	34.0	33.8	33.7	32.9	31.4	29.9
102.5°	34.1	34.4	34.7	35.1	34.7	34.4	34.1	33.8	35.8	40.4	44.8
105°	35.0	35.3	35.6	36.0	35.6	35.3	35.0	34.6	50.5	82.7	115.0
107.5°	186.0	161.8	137.5	113.2	137.5	161.8	186.0	210.3	234.2	257.9	281.4
110°	303.3	277.2	251.2	225.2	251.2	277.2	303.3	329.3	345.3	351.3	357.3



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	402.8	397.4	391.8	386.4	391.8	397.4	402.8	408.3	411.0	410.9	410.8
115°	479.3	480.0	480.8	481.5	480.8	480.0	479.3	478.6	477.4	475.5	473.7
117.5°	534.4	534.6	534.8	534.9	534.8	534.6	534.4	534.3	533.5	532.1	530.6
120°	571.6	571.6	571.6	571.6	571.6	571.6	571.6	571.6	570.9	569.4	567.9
122.5°	607.2	607.3	607.5	607.6	607.5	607.3	607.2	607.1	606.4	605.4	604.4
125°	657.3	657.6	658.0	658.4	658.0	657.6	657.3	657.0	656.6	656.2	655.8
127.5°	708.3	707.9	707.6	707.2	707.6	707.9	708.3	708.7	708.6	707.9	707.4
130°	739.7	739.4	739.0	738.7	739.0	739.4	739.7	740.1	739.9	739.2	738.5
132.5°	769.0	768.5	768.0	767.4	768.0	768.5	769.0	769.5	769.4	768.7	767.9
135°	813.2	812.6	812.0	811.5	812.0	812.6	813.2	813.7	813.7	813.2	812.6
137.5°	854.0	853.7	853.3	853.0	853.3	853.7	854.0	854.4	854.2	853.3	852.4
140°	879.0	878.6	878.2	877.8	878.2	878.6	879.0	879.3	879.1	878.4	877.7
142.5°	902.3	901.8	901.3	900.7	901.3	901.8	902.3	902.8	902.8	902.2	901.6
145°	936.0	936.0	936.0	936.0	936.0	936.0	936.0	936.0	935.8	935.5	935.1
147.5°	964.7	963.8	963.0	962.2	963.0	963.8	964.7	965.6	965.8	965.4	965.1
150°	983.5	982.9	982.4	981.9	982.4	982.9	983.5	984.1	984.1	983.7	983.4
152.5°	1000.0	999.2	998.4	997.6	998.4	999.2	1000.0	1000.9	1001.0	1000.4	999.7
155°	1022.8	1021.7	1020.6	1019.5	1020.6	1021.7	1022.8	1023.9	1024.0	1023.0	1022.1
157.5°	1042.3	1040.9	1039.4	1038.0	1039.4	1040.9	1042.3	1043.7	1043.8	1042.8	1041.7
160°	1053.6	1052.4	1051.1	1049.8	1051.1	1052.4	1053.6	1054.9	1055.0	1053.9	1052.8
162.5°	1064.4	1063.2	1062.1	1060.9	1062.1	1063.2	1064.4	1065.4	1065.4	1064.2	1062.9
165°	1078.2	1076.9	1075.6	1074.4	1075.6	1076.9	1078.2	1079.5	1079.4	1077.9	1076.4
167.5°	1088.4	1087.0	1085.5	1084.0	1085.5	1087.0	1088.4	1089.9	1089.9	1088.4	1087.0
170°	1094.3	1092.8	1091.4	1090.0	1091.4	1092.8	1094.3	1095.8	1095.8	1094.3	1092.8
172.5°	1098.0	1096.4	1094.8	1093.2	1094.8	1096.4	1098.0	1099.6	1099.7	1098.2	1096.8
175°	1102.5	1101.1	1099.6	1098.1	1099.6	1101.1	1102.5	1104.0	1104.1	1102.8	1101.5
177.5°	1104.0	1102.5	1101.1	1099.6	1101.1	1102.5	1104.0	1105.5	1105.5	1104.4	1103.3
180°	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1
2.5°	1237.1	1243.2	1249.5	1255.2	1264.1	1268.1	1273.9	1276.1	1282.8	1292.6	1300.6
5°	1161.8	1170.7	1182.3	1191.8	1206.8	1218.4	1231.2	1243.4	1257.8	1278.3	1296.7
7.5°	1098.0	1106.8	1120.8	1138.3	1154.9	1171.3	1188.8	1205.4	1226.0	1255.5	1284.7
10°	1055.9	1066.4	1083.0	1101.9	1122.4	1138.6	1159.0	1180.1	1205.7	1239.5	1274.5
12.5°	1019.5	1027.4	1046.7	1064.6	1087.9	1108.3	1128.5	1153.1	1182.1	1218.2	1260.3
15°	961.6	972.7	991.5	1011.5	1035.9	1057.5	1083.6	1113.5	1141.8	1186.3	1237.3
17.5°	903.4	920.2	939.9	962.5	980.5	1010.3	1038.7	1069.4	1104.2	1151.3	1207.3
20°	866.1	879.4	897.7	930.5	954.3	977.1	1003.1	1041.5	1073.6	1126.9	1185.1
22.5°	834.6	844.3	864.9	891.9	919.7	946.0	972.5	1009.0	1048.7	1099.3	1162.5
25°	787.9	803.4	819.0	838.4	868.3	899.9	928.8	959.9	1002.0	1055.9	1124.1
27.5°	742.2	756.4	771.7	795.5	818.2	847.8	878.0	913.6	958.9	1015.8	1085.0
30°	713.0	723.5	737.9	768.4	789.0	814.5	850.0	881.7	923.8	984.3	1057.5
32.5°	682.8	696.4	712.2	735.6	761.0	785.2	817.6	851.9	895.0	954.6	1029.6
35°	639.8	655.8	671.9	689.1	714.6	739.6	766.8	804.5	848.3	906.0	979.8
37.5°	600.1	613.1	626.1	647.5	671.7	695.5	720.8	758.0	799.3	861.5	929.3
40°	574.8	586.4	596.5	618.6	642.0	667.5	692.4	725.2	769.6	827.9	893.3
42.5°	547.3	558.1	571.6	589.8	614.9	636.4	661.4	692.4	734.0	793.2	850.7
45°	506.0	518.2	529.9	547.1	572.0	593.1	615.3	644.7	687.5	736.3	787.3
47.5°	463.1	475.2	488.6	505.2	527.0	548.4	570.6	596.6	635.6	683.5	718.0
50°	435.5	445.6	458.9	475.5	495.5	518.2	538.2	566.5	603.6	641.4	671.3
52.5°	407.2	416.2	431.3	448.9	467.5	487.1	508.4	532.7	566.4	601.9	625.7
55°	362.9	374.0	386.7	403.9	422.2	438.9	459.4	484.4	511.0	537.6	553.8
57.5°	321.5	330.7	341.4	359.2	375.0	394.9	413.4	432.8	457.4	477.5	488.0
60°	291.3	299.6	313.5	329.1	344.0	361.2	382.3	401.7	420.5	436.7	445.0
62.5°	262.9	272.6	284.6	298.8	315.1	331.5	349.8	366.2	382.9	396.7	402.4
65°	225.8	233.6	242.5	255.8	269.1	285.8	300.2	316.8	329.1	336.8	341.8
67.5°	192.1	197.2	204.0	212.9	225.9	240.4	254.5	267.4	277.6	283.0	287.4
70°	170.3	173.7	178.6	187.5	197.5	210.3	224.7	234.2	243.0	247.4	251.9
72.5°	148.5	152.8	157.4	164.4	172.7	181.9	192.3	204.0	208.9	214.2	216.9
75°	112.6	118.7	124.8	129.3	134.9	142.0	151.5	158.7	161.4	165.9	166.5
77.5°	85.0	86.3	90.7	96.3	101.0	106.2	112.2	118.6	119.9	122.3	123.8
80°	69.9	69.9	69.9	73.2	78.8	82.7	88.2	91.6	93.8	94.3	94.9
82.5°	56.2	56.2	55.7	56.3	58.4	60.5	65.6	69.4	71.1	70.8	69.5
85°	36.6	35.5	35.5	35.0	35.5	34.4	33.8	36.0	39.4	39.4	38.3
87.5°	19.2	18.6	18.6	17.6	16.7	15.8	14.0	14.1	13.8	15.2	14.3
90°	20.4	19.6	17.3	14.9	12.6	10.2	8.1	6.3	4.5	2.6	0.8
92.5°	22.1	21.0	19.2	17.4	15.7	13.9	13.2	13.7	14.2	14.8	15.2
95°	26.7	25.4	23.4	21.4	19.4	17.4	20.1	27.6	35.1	42.5	50.0
97.5°	27.8	26.3	39.5	52.6	65.7	78.8	87.0	90.3	93.7	97.0	100.4
100°	28.5	27.0	55.4	83.8	112.2	140.6	153.0	149.3	145.7	142.0	138.4
102.5°	49.4	53.9	84.9	115.9	146.9	177.9	192.1	189.5	186.9	184.3	181.6
105°	147.2	179.4	195.8	212.1	228.4	244.8	252.0	250.1	248.0	246.1	244.0
107.5°	305.1	328.7	326.1	323.5	321.0	318.4	316.3	314.7	313.1	311.4	309.9
110°	363.3	369.3	367.3	365.3	363.3	361.3	359.5	358.2	356.7	355.2	353.8



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	410.7	410.6	408.6	406.6	404.6	402.6	401.0	399.7	398.3	397.0	395.7
115°	471.9	470.0	468.4	466.8	465.1	463.5	462.1	461.1	459.9	458.9	457.8
117.5°	529.1	527.7	526.8	526.0	525.2	524.3	523.3	521.9	520.6	519.2	517.9
120°	566.5	565.0	564.5	563.9	563.4	562.9	561.7	560.1	558.5	556.8	555.2
122.5°	603.4	602.3	601.7	601.0	600.3	599.6	598.6	597.2	595.9	594.5	593.2
125°	655.5	655.1	654.4	653.6	652.9	652.2	651.1	649.6	648.2	646.8	645.3
127.5°	706.8	706.2	705.3	704.5	703.6	702.7	701.6	700.1	698.6	697.2	695.7
130°	737.8	737.0	736.3	735.6	734.8	734.1	733.0	731.6	730.1	728.6	727.2
132.5°	767.2	766.5	765.9	765.3	764.8	764.2	763.1	761.7	760.2	758.8	757.3
135°	812.0	811.5	810.8	810.1	809.3	808.6	807.7	806.6	805.5	804.5	803.3
137.5°	851.5	850.7	850.3	849.9	849.5	849.1	848.2	846.8	845.4	844.0	842.6
140°	876.9	876.2	875.6	875.1	874.6	874.0	873.2	872.1	871.1	869.9	868.9
142.5°	901.1	900.4	899.9	899.4	898.8	898.3	897.5	896.3	895.3	894.1	893.1
145°	934.7	934.3	934.0	933.6	933.3	932.9	932.1	930.8	929.5	928.2	927.0
147.5°	964.7	964.3	963.9	963.6	963.2	962.9	962.3	961.4	960.6	959.8	959.0
150°	983.0	982.7	982.3	981.9	981.5	981.2	980.7	980.2	979.7	979.1	978.6
152.5°	999.1	998.4	998.2	997.9	997.8	997.5	997.3	997.0	996.8	996.5	996.3
155°	1021.2	1020.3	1020.2	1019.9	1019.8	1019.6	1019.7	1020.1	1020.4	1020.8	1021.2
157.5°	1040.6	1039.5	1039.7	1039.8	1040.1	1040.2	1040.3	1040.4	1040.4	1040.5	1040.5
160°	1051.7	1050.7	1050.8	1051.0	1051.2	1051.3	1051.6	1051.7	1051.9	1052.1	1052.3
162.5°	1061.7	1060.5	1060.6	1060.9	1061.0	1061.2	1061.5	1062.0	1062.5	1062.9	1063.4
165°	1075.1	1073.6	1073.7	1073.9	1074.1	1074.3	1074.6	1075.2	1075.8	1076.3	1076.8
167.5°	1085.5	1084.0	1084.0	1084.0	1084.0	1084.0	1084.4	1085.2	1085.9	1086.6	1087.3
170°	1091.4	1090.0	1090.0	1090.0	1090.0	1090.0	1090.3	1091.0	1091.8	1092.5	1093.2
172.5°	1095.4	1093.9	1093.7	1093.6	1093.4	1093.3	1093.6	1094.5	1095.4	1096.3	1097.1
175°	1100.2	1098.9	1098.8	1098.6	1098.4	1098.2	1098.6	1099.5	1100.4	1101.3	1102.2
177.5°	1102.1	1100.9	1100.7	1100.7	1100.5	1100.3	1100.7	1101.4	1102.1	1102.8	1103.5
180°	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1
2.5°	1303.2	1308.1	1314.3	1323.6	1330.7	1336.9	1338.2	1340.0	1344.5	1352.0	1357.8
5°	1311.7	1324.4	1344.9	1364.9	1386.6	1404.3	1420.9	1432.6	1443.7	1467.0	1485.9
7.5°	1309.0	1337.4	1369.5	1405.4	1441.7	1476.8	1509.5	1538.7	1567.7	1601.7	1640.5
10°	1307.2	1340.5	1383.7	1429.8	1480.3	1529.7	1577.4	1614.6	1657.8	1696.7	1746.0
12.5°	1298.8	1346.7	1398.4	1457.3	1519.4	1576.3	1639.1	1690.4	1740.0	1796.1	1853.5
15°	1287.8	1346.1	1411.5	1489.7	1584.0	1652.9	1717.2	1806.5	1867.6	1928.6	2010.8
17.5°	1267.7	1338.8	1420.6	1522.2	1600.9	1693.4	1790.2	1860.8	1943.0	2029.0	2103.4
20°	1251.7	1334.4	1426.0	1525.8	1626.2	1726.6	1820.4	1904.8	1989.7	2089.0	2150.0
22.5°	1235.7	1317.5	1412.6	1518.7	1626.7	1732.4	1838.6	1937.6	2033.1	2133.3	2211.3
25°	1201.8	1298.9	1402.1	1510.3	1616.8	1733.3	1859.8	1970.3	2088.4	2191.6	2265.4
27.5°	1167.3	1256.4	1359.1	1468.8	1587.3	1725.0	1873.8	1999.3	2117.7	2191.6	2214.8
30°	1136.3	1230.6	1324.9	1436.5	1564.6	1718.3	1876.5	2020.1	2117.3	2149.5	2125.6
32.5°	1104.8	1190.3	1283.7	1397.8	1534.0	1701.9	1880.0	2007.8	2066.2	2041.6	1944.5
35°	1049.2	1126.3	1216.8	1331.1	1487.5	1692.8	1865.4	1951.9	1937.5	1798.8	1615.7
37.5°	989.7	1052.6	1136.3	1255.8	1439.3	1656.8	1802.3	1815.1	1690.3	1477.3	1265.8
40°	942.6	999.2	1085.2	1210.1	1402.1	1621.2	1738.9	1687.3	1493.6	1256.7	1080.3
42.5°	896.9	944.7	1027.5	1162.1	1366.6	1572.9	1644.3	1531.9	1308.6	1084.5	924.1
45°	819.5	864.5	947.6	1085.8	1293.9	1480.3	1470.9	1275.5	1052.0	871.6	738.5
47.5°	746.0	785.3	863.4	1004.4	1208.5	1341.6	1253.4	1045.5	855.9	711.2	616.2
50°	694.1	733.0	810.7	949.9	1140.2	1237.3	1111.3	911.0	737.4	617.5	542.1
52.5°	644.4	682.3	753.3	889.1	1057.6	1115.7	980.4	794.8	650.0	546.5	481.7
55°	574.8	603.6	667.5	797.3	923.2	936.5	799.5	644.2	524.9	452.7	408.4
57.5°	503.9	528.7	591.8	695.2	783.5	776.7	646.7	512.3	432.0	378.4	346.3
60°	457.7	482.2	537.6	626.4	693.0	669.7	550.4	442.2	373.4	334.0	308.5
62.5°	414.7	433.7	485.7	550.5	598.4	572.0	470.5	381.0	326.4	293.2	273.0
65°	352.3	367.9	409.4	443.3	469.9	444.4	360.1	297.9	258.5	235.2	221.4
67.5°	293.1	303.0	329.2	341.4	360.2	332.2	270.8	229.2	206.8	187.1	177.4
70°	255.8	263.0	276.9	286.8	291.9	263.0	217.5	186.9	168.1	154.3	148.1
72.5°	218.5	224.9	227.6	235.8	233.3	206.2	174.9	150.6	137.1	127.6	119.8
75°	167.0	169.7	167.0	163.7	156.5	137.6	115.9	103.8	93.8	89.4	86.6
77.5°	121.7	120.8	117.1	111.9	99.5	87.6	76.0	71.9	67.6	65.2	64.2
80°	93.8	91.6	88.2	79.9	69.4	61.1	58.3	55.5	53.8	51.0	50.5
82.5°	69.8	68.5	62.9	55.9	48.5	44.6	42.3	41.3	39.6	38.2	38.1
85°	37.2	35.5	29.4	25.5	24.4	23.3	22.7	22.7	20.5	20.0	20.0
87.5°	12.5	10.2	10.1	9.1	9.6	9.1	10.1	9.7	9.7	10.3	9.5
90°	2.6	4.5	6.3	8.1	10.2	12.6	14.9	17.3	19.6	20.4	21.1
92.5°	14.8	14.2	13.7	13.2	13.9	15.7	17.4	19.2	21.0	22.1	23.3
95°	42.5	35.1	27.6	20.1	17.4	19.4	21.4	23.4	25.4	26.7	28.0
97.5°	97.0	93.7	90.3	87.0	78.8	65.7	52.6	39.5	26.3	27.8	29.3
100°	142.0	145.7	149.3	153.0	140.6	112.2	83.8	55.4	27.0	28.5	29.9
102.5°	184.3	186.9	189.5	192.1	177.9	146.9	115.9	84.9	53.9	49.4	44.8
105°	246.1	248.0	250.1	252.0	244.8	228.4	212.1	195.8	179.4	147.2	115.0
107.5°	311.4	313.1	314.7	316.3	318.4	321.0	323.5	326.1	328.7	305.1	281.4
110°	355.2	356.7	358.2	359.5	361.3	363.3	365.3	367.3	369.3	363.3	357.3



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	397.0	398.3	399.7	401.0	402.6	404.6	406.6	408.6	410.6	410.7	410.8
115°	458.9	459.9	461.1	462.1	463.5	465.1	466.8	468.4	470.0	471.9	473.7
117.5°	519.2	520.6	521.9	523.3	524.3	525.2	526.0	526.8	527.7	529.1	530.6
120°	556.8	558.5	560.1	561.7	562.9	563.4	563.9	564.5	565.0	566.5	567.9
122.5°	594.5	595.9	597.2	598.6	599.6	600.3	601.0	601.7	602.3	603.4	604.4
125°	646.8	648.2	649.6	651.1	652.2	652.9	653.6	654.4	655.1	655.5	655.8
127.5°	697.2	698.6	700.1	701.6	702.7	703.6	704.5	705.3	706.2	706.8	707.4
130°	728.6	730.1	731.6	733.0	734.1	734.8	735.6	736.3	737.0	737.8	738.5
132.5°	758.8	760.2	761.7	763.1	764.2	764.8	765.3	765.9	766.5	767.2	767.9
135°	804.5	805.5	806.6	807.7	808.6	809.3	810.1	810.8	811.5	812.0	812.6
137.5°	844.0	845.4	846.8	848.2	849.1	849.5	849.9	850.3	850.7	851.5	852.4
140°	869.9	871.1	872.1	873.2	874.0	874.6	875.1	875.6	876.2	876.9	877.7
142.5°	894.1	895.3	896.3	897.5	898.3	898.8	899.4	899.9	900.4	901.1	901.6
145°	928.2	929.5	930.8	932.1	932.9	933.3	933.6	934.0	934.3	934.7	935.1
147.5°	959.8	960.6	961.4	962.3	962.9	963.2	963.6	963.9	964.3	964.7	965.1
150°	979.1	979.7	980.2	980.7	981.2	981.5	981.9	982.3	982.7	983.0	983.4
152.5°	996.5	996.8	997.0	997.3	997.5	997.8	997.9	998.2	998.4	999.1	999.7
155°	1020.8	1020.4	1020.1	1019.7	1019.6	1019.8	1019.9	1020.2	1020.3	1021.2	1022.1
157.5°	1040.5	1040.4	1040.4	1040.3	1040.2	1040.1	1039.8	1039.7	1039.5	1040.6	1041.7
160°	1052.1	1051.9	1051.7	1051.6	1051.3	1051.2	1051.0	1050.8	1050.7	1051.7	1052.8
162.5°	1062.9	1062.5	1062.0	1061.5	1061.2	1061.0	1060.9	1060.6	1060.5	1061.7	1062.9
165°	1076.3	1075.8	1075.2	1074.6	1074.3	1074.1	1073.9	1073.7	1073.6	1075.1	1076.4
167.5°	1086.6	1085.9	1085.2	1084.4	1084.0	1084.0	1084.0	1084.0	1084.0	1085.5	1087.0
170°	1092.5	1091.8	1091.0	1090.3	1090.0	1090.0	1090.0	1090.0	1090.0	1091.4	1092.8
172.5°	1096.3	1095.4	1094.5	1093.6	1093.3	1093.4	1093.6	1093.7	1093.9	1095.4	1096.8
175°	1101.3	1100.4	1099.5	1098.6	1098.2	1098.4	1098.6	1098.8	1098.9	1100.2	1101.5
177.5°	1102.8	1102.1	1101.4	1100.7	1100.3	1100.5	1100.7	1100.7	1100.9	1102.1	1103.3
180°	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1	1296.1
2.5°	1367.1	1367.1	1368.9	1375.6	1376.5	1382.2	1380.5
5°	1502.5	1513.0	1516.9	1533.6	1543.5	1548.0	1539.1
7.5°	1668.1	1697.8	1711.9	1729.3	1744.7	1749.4	1737.3
10°	1788.8	1819.8	1845.9	1862.1	1877.0	1887.0	1899.7
12.5°	1905.5	1943.7	1968.5	1991.2	2006.6	2019.3	2021.4
15°	2032.4	2090.1	2133.9	2166.1	2182.1	2190.5	2187.2
17.5°	2160.3	2213.8	2245.0	2277.9	2300.1	2301.3	2301.9
20°	2232.7	2284.8	2320.9	2345.3	2370.2	2369.2	2374.7
22.5°	2281.0	2322.1	2349.8	2367.5	2376.0	2371.8	2372.9
25°	2303.7	2315.9	2310.9	2282.6	2275.4	2249.3	2253.7
27.5°	2187.0	2129.2	2069.6	1992.8	1932.2	1883.7	1886.2
30°	2028.5	1926.4	1809.9	1712.2	1624.6	1600.2	1548.0
32.5°	1807.0	1653.8	1517.4	1426.4	1351.1	1330.7	1285.2
35°	1431.5	1282.8	1142.4	1058.1	1024.7	978.2	977.6
37.5°	1112.6	981.7	907.5	844.2	811.1	782.9	780.1
40°	936.0	833.9	777.9	732.4	699.7	678.6	673.6
42.5°	812.6	730.0	677.6	649.4	624.2	613.3	605.2
45°	663.6	608.1	571.4	545.9	534.3	525.9	521.5
47.5°	555.1	517.9	492.9	476.0	466.5	457.7	460.1
50°	496.0	465.5	447.2	431.1	423.9	417.8	418.3
52.5°	448.5	421.1	406.3	394.7	385.7	381.4	379.3
55°	380.6	363.4	348.5	340.1	335.1	329.1	327.3
57.5°	324.7	311.4	299.1	289.8	288.5	282.7	283.4
60°	287.4	276.3	266.4	261.3	257.5	252.4	254.1
62.5°	256.8	247.4	238.4	234.2	230.4	226.7	227.5
65°	210.3	201.4	195.8	193.6	192.0	190.3	188.7
67.5°	167.5	162.2	158.7	153.9	150.5	149.9	148.2
70°	141.0	133.7	127.6	121.5	119.8	119.3	119.8
72.5°	113.0	108.4	106.7	103.8	103.5	102.0	103.0
75°	84.9	83.2	82.1	79.9	79.9	79.9	79.9
77.5°	62.6	61.6	60.9	60.5	59.9	59.1	59.0
80°	48.8	48.3	47.1	47.1	46.6	47.1	46.6
82.5°	36.9	36.8	35.6	35.6	35.1	34.7	35.1
85°	18.8	18.3	19.4	18.3	18.8	17.8	18.8
87.5°	9.7	9.9	9.5	9.5	9.2	10.2	9.4
90°	21.9	22.6	23.1	23.5	23.8	24.2	24.5
92.5°	24.5	25.6	26.3	26.5	26.7	27.0	27.1
95°	29.2	30.5	31.1	31.1	31.1	31.1	31.1
97.5°	30.7	32.2	33.0	33.2	33.3	33.6	33.8
100°	31.4	32.9	33.7	33.8	34.0	34.2	34.4
102.5°	40.4	35.8	33.8	34.1	34.4	34.7	35.1
105°	82.7	50.5	34.6	35.0	35.3	35.6	36.0
107.5°	257.9	234.2	210.3	186.0	161.8	137.5	113.2
110°	351.3	345.3	329.3	303.3	277.2	251.2	225.2



TEST NUMBER: P332458-930

CATALOG NUMBER: S123RDIW-S1000D1030U930-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	410.9	411.0	408.3	402.8	397.4	391.8	386.4
115°	475.5	477.4	478.6	479.3	480.0	480.8	481.5
117.5°	532.1	533.5	534.3	534.4	534.6	534.8	534.9
120°	569.4	570.9	571.6	571.6	571.6	571.6	571.6
122.5°	605.4	606.4	607.1	607.2	607.3	607.5	607.6
125°	656.2	656.6	657.0	657.3	657.6	658.0	658.4
127.5°	707.9	708.6	708.7	708.3	707.9	707.6	707.2
130°	739.2	739.9	740.1	739.7	739.4	739.0	738.7
132.5°	768.7	769.4	769.5	769.0	768.5	768.0	767.4
135°	813.2	813.7	813.7	813.2	812.6	812.0	811.5
137.5°	853.3	854.2	854.4	854.0	853.7	853.3	853.0
140°	878.4	879.1	879.3	879.0	878.6	878.2	877.8
142.5°	902.2	902.8	902.8	902.3	901.8	901.3	900.7
145°	935.5	935.8	936.0	936.0	936.0	936.0	936.0
147.5°	965.4	965.8	965.6	964.7	963.8	963.0	962.2
150°	983.7	984.1	984.1	983.5	982.9	982.4	981.9
152.5°	1000.4	1001.0	1000.9	1000.0	999.2	998.4	997.6
155°	1023.0	1024.0	1023.9	1022.8	1021.7	1020.6	1019.5
157.5°	1042.8	1043.8	1043.7	1042.3	1040.9	1039.4	1038.0
160°	1053.9	1055.0	1054.9	1053.6	1052.4	1051.1	1049.8
162.5°	1064.2	1065.4	1065.4	1064.4	1063.2	1062.1	1060.9
165°	1077.9	1079.4	1079.5	1078.2	1076.9	1075.6	1074.4
167.5°	1088.4	1089.9	1089.9	1088.4	1087.0	1085.5	1084.0
170°	1094.3	1095.8	1095.8	1094.3	1092.8	1091.4	1090.0
172.5°	1098.2	1099.7	1099.6	1098.0	1096.4	1094.8	1093.2
175°	1102.8	1104.1	1104.0	1102.5	1101.1	1099.6	1098.1
177.5°	1104.4	1105.5	1105.5	1104.0	1102.5	1101.1	1099.6
180°	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2	1102.2

(END OF REPORT)