

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P332471-930

Luminaire Tested: **S123RDIW-S1165D460U930-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P332471-930
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-9,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S123RDIW-S1165D460U930-4F0-1E-UDD-A1
Description: DEFINE 3 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 1165 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING
UPLIGHT 460 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5031.6 lumens
Efficiency: N/A
Efficacy: 96.0 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.22 / 1.36
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')
CIE Type: Semi-Direct


Input Watts (W): 52.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

Luminous Intensity Polar Plot





TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	113	113	113	113	107	107	107	107	97	97	97	87	87	87	78	78	78	74
1	104	100	96	93	99	95	92	89	86	84	81	78	76	74	71	69	68	64
2	95	88	82	77	91	84	79	74	77	72	69	70	66	64	63	61	58	55
3	88	78	71	66	83	75	69	63	68	63	59	62	58	55	57	54	51	48
4	81	70	62	56	77	67	60	55	61	56	51	56	52	48	51	48	44	42
5	75	63	55	49	71	60	53	48	55	49	45	51	46	42	47	43	39	37
6	69	57	49	43	66	55	47	42	50	44	40	46	41	37	43	38	35	33
7	64	52	44	38	61	50	42	37	46	40	35	42	37	33	39	35	31	29
8	60	47	40	34	57	46	38	33	42	36	32	39	34	30	36	32	28	26
9	56	44	36	31	53	42	35	30	39	33	29	36	31	27	33	29	26	24
10	52	40	33	28	50	39	32	27	36	30	26	34	28	25	31	27	24	22

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	16113	16113	16113	16113
5°	19207	16181	14249	16181
10°	23981	16088	12873	16088
15°	28149	15924	11739	15924
20°	31416	15678	10775	15678
25°	30914	15419	10183	15419
30°	22222	15181	9573	15181
35°	14837	14870	9179	14870
40°	10932	14497	8769	14497
45°	9168	13842	8369	13842
50°	8090	12983	7812	12983
55°	7096	12001	7047	12001
60°	6318	11063	6456	11063
65°	5547	10055	6006	10055
70°	4356	9155	5485	9155
75°	3839	7993	5011	7993
80°	3335	6794	4928	6794
85°	2692	5459	5224	5459



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	147.2	2.9
10°-20°	459.9	9.1
20°-30°	722.5	14.4
30°-40°	753.8	15.0
40°-50°	645.1	12.8
50°-60°	491.7	9.8
60°-70°	315.1	6.3
70°-80°	151.6	3.0
80°-90°	41.5	0.8
90°-100°	30.6	0.6
100°-110°	91.7	1.8
110°-120°	156.0	3.1
120°-130°	205.2	4.1
130°-140°	230.6	4.6
140°-150°	226.7	4.5
150°-160°	190.8	3.8
160°-170°	127.0	2.5
170°-180°	44.5	0.9
0°-30°	1329.6	26.4
0°-40°	2083.4	41.4
0°-60°	3220.2	64.0
0°-90°	3728.4	74.1
90°-120°	278.3	5.5
90°-150°	940.8	18.7
90°-180°	1303.0	25.9
0°-180°	5031.6	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1497	1497	1497	1497	1497	
5°	1778	1498	1319	1498	1778	184
15°	2526	1429	1053	1429	2526	716
25°	2603	1298	857	1298	2603	1119
35°	1129	1132	698	1132	1129	740
45°	602	909	550	909	602	474
55°	378	640	376	640	378	342
65°	218	395	236	395	218	214
75°	92	192	120	192	92	99
85°	22	44	42	44	22	25
90°	11	0	11	0	11	6
95°	29	22	29	22	29	30
105°	88	83	88	83	88	93
115°	157	157	157	157	157	156
125°	227	230	227	230	227	203
135°	298	298	298	298	298	229
145°	362	362	362	362	362	226
155°	413	414	413	414	413	190
165°	450	451	450	451	450	127
175°	467	469	467	469	467	44
180°	470	470	470	470	470	



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9
2.5°	1594.3	1596.4	1589.7	1588.7	1580.9	1578.9	1578.9	1568.1	1561.5	1552.8	1547.7
5°	1777.6	1787.9	1782.7	1771.2	1751.9	1747.4	1735.3	1716.0	1694.3	1667.4	1654.6
7.5°	2006.5	2020.5	2015.1	1997.2	1977.1	1960.9	1926.5	1894.6	1849.8	1810.6	1777.0
10°	2194.1	2179.4	2167.8	2150.5	2131.9	2101.8	2066.0	2016.6	1959.6	1914.7	1864.8
12.5°	2334.5	2332.2	2317.5	2299.7	2273.5	2244.8	2200.7	2140.6	2074.4	2009.5	1952.4
15°	2526.0	2529.9	2520.3	2501.7	2464.5	2413.9	2347.2	2322.3	2227.4	2157.0	2086.4
17.5°	2658.5	2657.8	2656.5	2630.7	2592.8	2556.8	2495.0	2429.3	2343.4	2244.1	2149.1
20°	2742.6	2736.2	2737.5	2708.7	2680.5	2638.8	2578.5	2483.1	2412.6	2297.9	2199.8
22.5°	2740.5	2739.3	2744.1	2734.3	2713.8	2681.8	2634.5	2553.8	2463.9	2348.1	2237.8
25°	2602.9	2597.8	2628.0	2636.3	2669.0	2674.7	2660.6	2616.4	2531.2	2412.0	2275.5
27.5°	2178.5	2175.6	2231.6	2301.5	2390.2	2459.1	2525.8	2557.9	2531.2	2445.8	2309.1
30°	1787.9	1848.0	1876.2	1977.5	2090.3	2224.9	2342.8	2454.9	2482.4	2445.3	2333.1
32.5°	1484.3	1536.9	1560.5	1647.4	1752.5	1910.1	2086.9	2245.7	2357.9	2386.3	2318.8
35°	1129.1	1129.8	1183.6	1222.0	1319.4	1481.6	1653.3	1866.0	2077.5	2237.7	2254.3
37.5°	901.0	904.2	936.7	975.0	1048.1	1133.8	1285.1	1461.9	1706.2	1952.2	2096.3
40°	778.0	783.7	808.0	845.9	898.4	963.1	1081.0	1247.7	1451.4	1725.0	1948.6
42.5°	699.0	708.3	720.9	750.0	782.5	843.2	938.5	1067.2	1252.5	1511.2	1769.3
45°	602.3	607.5	617.1	630.6	660.0	702.3	766.4	852.9	1006.7	1215.0	1473.2
47.5°	531.3	528.6	538.7	549.7	569.3	598.1	641.1	711.7	821.4	988.5	1207.5
50°	483.1	482.5	489.6	497.9	516.5	537.6	572.9	626.1	713.2	851.7	1052.2
52.5°	438.1	440.5	445.5	455.8	469.3	486.4	518.0	556.4	631.2	750.6	917.9
55°	378.1	380.0	387.0	392.8	402.4	419.7	439.6	471.7	522.9	606.2	744.0
57.5°	327.3	326.4	333.2	334.6	345.5	359.6	375.0	399.8	437.0	499.0	591.7
60°	293.5	291.6	297.3	301.8	307.6	319.1	331.9	356.3	385.8	431.3	510.7
62.5°	262.7	261.8	266.0	270.5	275.3	285.8	296.5	315.3	338.6	376.9	439.9
65°	217.8	219.8	221.7	223.6	226.2	232.6	242.9	255.7	271.7	298.6	344.1
67.5°	171.2	173.2	173.8	177.7	183.3	187.3	193.6	205.0	216.1	238.8	264.6
70°	138.4	137.8	138.4	140.3	147.4	154.4	162.7	171.1	178.1	194.1	216.0
72.5°	119.0	117.8	119.4	119.8	123.3	125.2	130.4	138.3	147.4	158.2	173.9
75°	92.3	92.3	92.3	92.3	94.8	96.1	98.1	100.0	103.1	108.3	119.8
77.5°	68.2	68.3	69.2	69.9	70.4	71.1	72.3	74.2	75.3	78.0	83.1
80°	53.8	54.5	53.8	54.5	54.5	55.8	56.4	58.3	58.9	62.1	64.1
82.5°	40.5	40.1	40.5	41.2	41.2	42.4	42.6	43.9	44.1	45.7	47.7
85°	21.8	20.5	21.8	21.1	22.4	21.1	21.8	23.1	23.1	23.7	26.3
87.5°	7.3	8.3	7.3	7.7	7.7	8.2	8.2	8.1	9.0	8.4	8.7
90°	11.1	10.9	10.8	10.6	10.4	10.2	9.9	9.5	9.2	8.9	7.8
92.5°	14.9	15.0	15.1	15.2	15.3	15.2	15.0	14.7	14.4	14.2	13.6
95°	28.8	28.8	28.8	28.8	28.8	28.6	28.3	28.0	27.6	27.3	26.7
97.5°	44.4	44.4	44.4	44.4	44.4	44.3	43.9	43.5	43.1	42.8	42.3
100°	56.2	56.0	55.8	55.7	55.5	55.3	55.0	54.8	54.5	54.3	53.9
102.5°	68.2	68.3	68.3	68.4	68.4	68.3	68.1	67.8	67.6	67.3	66.8
105°	88.0	87.8	87.6	87.5	87.2	87.2	87.2	87.2	87.2	87.2	86.4
107.5°	108.4	108.5	108.6	108.7	108.8	108.7	108.4	108.2	107.9	107.7	107.4
110°	122.3	122.5	122.6	122.8	122.9	122.9	122.5	122.2	121.9	121.6	121.4



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	137.1	137.1	137.1	137.1	137.2	137.1	136.6	136.2	135.8	135.4	135.4
115°	157.4	157.5	157.6	157.7	157.8	157.8	157.7	157.6	157.5	157.4	157.6
117.5°	178.0	178.2	178.5	178.7	179.0	179.0	179.0	179.1	179.1	179.1	179.4
120°	192.5	192.7	192.8	193.0	193.1	193.3	193.4	193.5	193.6	193.6	194.0
122.5°	206.4	206.6	206.8	207.1	207.3	207.5	207.7	208.0	208.1	208.4	208.6
125°	227.2	227.6	227.9	228.2	228.5	228.9	229.2	229.5	229.8	230.2	230.3
127.5°	248.0	248.3	248.7	249.2	249.5	249.9	250.4	250.9	251.3	251.8	251.9
130°	261.5	262.2	262.8	263.3	263.9	264.3	264.6	265.0	265.3	265.6	265.9
132.5°	275.7	276.2	276.6	277.1	277.5	277.9	278.3	278.8	279.2	279.6	279.7
135°	297.8	298.0	298.2	298.3	298.5	298.7	299.1	299.4	299.7	300.0	300.1
137.5°	317.2	317.6	317.9	318.1	318.5	318.8	319.2	319.5	319.8	320.2	320.0
140°	330.0	330.5	331.1	331.7	332.2	332.6	332.6	332.7	332.8	332.9	332.8
142.5°	342.9	343.4	343.8	344.3	344.7	345.0	345.0	345.1	345.2	345.3	345.2
145°	361.7	362.1	362.4	362.7	363.1	363.2	363.3	363.4	363.5	363.5	363.3
147.5°	378.4	378.9	379.4	379.9	380.4	380.7	380.7	380.7	380.7	380.7	380.4
150°	389.1	389.6	390.0	390.5	391.0	391.3	391.3	391.3	391.3	391.3	391.1
152.5°	399.4	399.8	400.2	400.7	401.1	401.3	401.1	401.0	400.9	400.7	400.6
155°	413.4	414.0	414.6	415.2	415.7	415.9	415.6	415.2	414.9	414.6	414.5
157.5°	426.2	426.6	427.1	427.6	428.0	428.1	427.8	427.5	427.1	426.7	426.6
160°	434.5	434.8	435.1	435.5	435.8	435.8	435.4	435.0	434.6	434.1	434.1
162.5°	440.7	441.2	441.7	442.3	442.8	442.9	442.5	442.1	441.6	441.2	441.2
165°	449.6	450.2	450.8	451.3	451.9	452.0	451.5	451.0	450.5	450.0	450.0
167.5°	457.2	457.8	458.3	458.8	459.3	459.3	458.8	458.3	457.8	457.2	457.2
170°	461.1	461.7	462.3	462.8	463.4	463.4	462.8	462.3	461.7	461.1	461.1
172.5°	464.1	464.6	465.2	465.8	466.4	466.4	465.9	465.4	464.9	464.3	464.3
175°	467.4	468.0	468.6	469.1	469.7	469.7	469.2	468.7	468.2	467.7	467.7
177.5°	469.1	469.6	470.1	470.5	471.0	471.0	470.7	470.3	469.9	469.4	469.4
180°	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9
2.5°	1545.6	1544.1	1536.9	1528.7	1517.9	1510.7	1505.1	1502.0	1492.8	1481.6	1473.8
5°	1641.1	1621.9	1601.3	1576.4	1553.3	1529.6	1514.8	1497.5	1476.4	1452.7	1436.1
7.5°	1743.4	1705.7	1665.1	1623.2	1581.8	1544.6	1511.8	1483.7	1450.0	1416.0	1392.2
10°	1821.8	1766.7	1709.7	1651.3	1598.1	1548.2	1509.7	1471.9	1431.6	1392.4	1363.0
12.5°	1893.0	1820.5	1754.8	1683.1	1615.1	1555.3	1500.0	1455.5	1407.0	1365.3	1331.7
15°	1983.3	1908.9	1829.5	1720.5	1630.2	1554.6	1487.3	1429.0	1370.0	1318.7	1286.1
17.5°	2067.6	1955.7	1848.9	1758.1	1640.7	1546.2	1464.1	1394.4	1329.7	1275.3	1235.1
20°	2102.5	1994.1	1878.2	1762.2	1646.8	1541.2	1445.6	1368.7	1301.5	1239.9	1202.8
22.5°	2123.4	2000.8	1878.7	1754.0	1631.5	1521.7	1427.2	1342.6	1269.7	1211.2	1165.4
25°	2148.0	2001.9	1867.3	1744.3	1619.3	1500.2	1388.0	1298.3	1219.4	1157.3	1108.6
27.5°	2164.1	1992.3	1833.2	1696.5	1569.7	1451.0	1348.3	1253.1	1173.2	1107.4	1055.2
30°	2167.1	1984.5	1807.0	1659.1	1530.2	1421.3	1312.4	1221.4	1136.8	1066.9	1018.2
32.5°	2171.3	1965.6	1771.6	1614.5	1482.5	1374.7	1275.9	1189.0	1102.4	1033.6	983.9
35°	2154.3	1955.1	1718.0	1537.2	1405.2	1300.8	1211.8	1131.6	1046.4	979.7	929.2
37.5°	2081.5	1913.4	1662.4	1450.4	1312.4	1215.6	1143.0	1073.2	995.1	923.2	875.5
40°	2008.2	1872.4	1619.3	1397.6	1253.4	1154.1	1088.8	1031.7	956.1	888.8	837.6
42.5°	1899.1	1816.6	1578.3	1342.2	1186.7	1091.0	1035.9	982.4	916.1	847.7	799.6
45°	1698.8	1709.7	1494.4	1254.0	1094.5	998.3	946.5	909.3	850.4	793.9	744.6
47.5°	1447.6	1549.5	1395.8	1160.1	997.2	907.0	861.6	829.2	789.5	734.1	689.1
50°	1283.5	1429.0	1316.9	1097.1	936.2	846.5	801.6	775.3	740.8	697.2	654.3
52.5°	1132.3	1288.5	1221.5	1026.8	870.1	788.1	744.2	722.6	695.1	654.1	615.3
55°	923.4	1081.7	1066.3	920.8	770.9	697.2	663.9	639.5	620.9	590.2	559.5
57.5°	746.9	897.0	904.9	802.9	683.5	610.7	582.0	563.6	551.5	528.3	499.9
60°	635.7	773.5	800.4	723.5	620.9	556.8	528.6	513.9	504.3	485.8	463.9
62.5°	543.4	660.6	691.1	635.8	560.9	501.0	478.9	464.7	458.2	442.1	422.9
65°	415.9	513.3	542.7	512.0	472.9	424.9	406.9	394.8	389.0	380.0	365.9
67.5°	312.7	383.7	416.0	394.4	380.3	349.8	338.4	331.9	326.8	320.7	308.8
70°	251.2	303.7	337.0	331.3	319.8	303.7	295.4	290.9	285.8	280.7	270.4
72.5°	201.9	238.1	269.4	272.3	262.9	259.7	252.3	250.5	247.4	241.2	235.5
75°	134.0	158.9	180.7	189.1	192.9	196.1	192.9	192.2	191.6	186.5	183.3
77.5°	87.8	101.3	115.0	129.2	135.2	139.6	140.6	142.9	141.2	138.5	137.0
80°	67.3	70.5	80.1	92.3	101.9	105.7	108.3	109.6	108.9	108.3	105.7
82.5°	48.8	51.5	56.0	64.6	72.6	79.1	80.6	80.4	81.8	82.2	80.1
85°	26.3	26.9	28.2	29.5	34.0	41.0	43.0	44.2	45.5	45.5	41.7
87.5°	9.5	8.8	9.6	9.5	10.8	11.2	14.1	16.5	17.1	15.2	15.4
90°	6.8	5.6	4.6	3.7	2.9	2.0	1.2	0.4	1.2	2.0	2.9
92.5°	13.0	12.4	11.7	11.2	10.6	10.0	9.5	9.0	9.5	10.0	10.6
95°	26.0	25.4	24.7	24.1	23.6	22.9	22.3	21.8	22.3	22.9	23.6
97.5°	41.8	41.3	40.8	40.4	40.0	39.5	39.1	38.7	39.1	39.5	40.0
100°	53.5	53.1	52.7	52.2	51.7	51.2	50.7	50.2	50.7	51.2	51.7
102.5°	66.2	65.7	65.1	64.7	64.4	64.2	63.8	63.5	63.8	64.2	64.4
105°	85.7	85.0	84.2	83.8	83.6	83.5	83.3	83.2	83.3	83.5	83.6
107.5°	107.0	106.8	106.5	106.3	106.2	106.1	106.0	105.9	106.0	106.1	106.2
110°	121.2	121.1	120.9	120.7	120.6	120.4	120.3	120.1	120.3	120.4	120.6



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	135.4	135.3	135.3	135.3	135.2	135.1	134.9	134.9	134.9	135.1	135.2
115°	157.8	157.9	158.1	158.0	157.8	157.5	157.3	157.0	157.3	157.5	157.8
117.5°	179.5	179.8	179.9	180.0	179.9	179.7	179.5	179.4	179.5	179.7	179.9
120°	194.4	194.9	195.3	195.2	194.7	194.2	193.7	193.2	193.7	194.2	194.7
122.5°	208.8	209.0	209.2	209.1	208.8	208.5	208.1	207.7	208.1	208.5	208.8
125°	230.5	230.6	230.8	230.8	230.6	230.3	230.1	229.8	230.1	230.3	230.6
127.5°	252.1	252.3	252.5	252.3	251.8	251.3	250.7	250.2	250.7	251.3	251.8
130°	266.1	266.4	266.6	266.4	265.8	265.1	264.5	263.8	264.5	265.1	265.8
132.5°	279.9	280.1	280.3	280.1	279.4	278.8	278.0	277.4	278.0	278.8	279.4
135°	300.2	300.3	300.4	300.1	299.6	299.1	298.6	298.2	298.6	299.1	299.6
137.5°	319.8	319.5	319.4	319.0	318.6	318.2	317.8	317.4	317.8	318.2	318.6
140°	332.7	332.6	332.6	332.3	331.9	331.5	331.1	330.7	331.1	331.5	331.9
142.5°	345.0	344.9	344.7	344.5	344.1	343.6	343.2	342.8	343.2	343.6	344.1
145°	363.1	362.8	362.6	362.4	362.2	362.1	361.9	361.7	361.9	362.1	362.2
147.5°	380.2	379.9	379.7	379.4	379.1	378.9	378.5	378.3	378.5	378.9	379.1
150°	390.9	390.8	390.6	390.4	390.3	390.1	390.0	389.8	390.0	390.1	390.3
152.5°	400.6	400.4	400.3	400.1	399.9	399.7	399.5	399.3	399.5	399.7	399.9
155°	414.4	414.3	414.3	414.2	414.2	414.2	414.2	414.2	414.2	414.2	414.2
157.5°	426.6	426.6	426.5	426.5	426.6	426.7	426.8	426.9	426.8	426.7	426.6
160°	434.1	434.1	434.1	434.2	434.4	434.6	434.7	434.9	434.7	434.6	434.4
162.5°	441.1	441.0	441.0	441.1	441.2	441.5	441.7	442.0	441.7	441.5	441.2
165°	450.0	450.0	450.0	450.1	450.4	450.6	450.9	451.1	450.9	450.6	450.4
167.5°	457.1	457.1	457.0	457.1	457.5	457.8	458.1	458.4	458.1	457.8	457.5
170°	461.1	461.1	461.1	461.3	461.6	461.9	462.3	462.6	462.3	461.9	461.6
172.5°	464.3	464.3	464.3	464.5	464.9	465.2	465.5	465.9	465.5	465.2	464.9
175°	467.7	467.7	467.7	467.9	468.2	468.6	468.9	469.2	468.9	468.6	468.2
177.5°	469.4	469.4	469.4	469.6	469.9	470.1	470.3	470.7	470.3	470.1	469.9
180°	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9
2.5°	1471.3	1464.6	1460.0	1449.8	1443.1	1435.9	1428.7	1433.4	1432.8	1432.3	1432.3
5°	1422.0	1407.2	1393.8	1376.5	1365.5	1352.1	1341.8	1340.5	1343.1	1334.2	1329.0
7.5°	1373.0	1352.8	1333.7	1314.7	1294.5	1278.3	1268.1	1263.4	1256.9	1251.3	1245.6
10°	1338.6	1314.9	1296.3	1272.6	1250.8	1231.6	1219.4	1211.1	1206.6	1202.2	1193.8
12.5°	1303.3	1280.1	1256.4	1229.6	1208.8	1186.5	1177.4	1168.1	1159.4	1154.5	1143.0
15°	1251.5	1221.4	1196.4	1168.2	1145.1	1123.3	1110.5	1091.9	1089.3	1083.0	1071.4
17.5°	1199.5	1166.9	1132.5	1111.5	1085.5	1062.8	1043.3	1037.1	1018.7	1011.8	1001.8
20°	1158.5	1128.5	1102.2	1074.6	1036.8	1015.7	1000.3	992.0	977.2	968.2	961.8
22.5°	1123.2	1092.6	1062.2	1030.0	998.9	975.2	963.9	951.0	942.9	930.3	923.4
25°	1072.7	1039.3	1002.8	968.2	945.8	927.9	910.0	898.4	886.9	881.1	868.3
27.5°	1014.0	979.2	945.0	918.8	891.2	873.5	857.3	847.0	833.2	823.5	816.4
30°	981.7	940.7	911.2	887.5	852.2	835.6	823.5	810.7	800.4	790.1	783.1
32.5°	944.3	906.9	878.9	849.5	822.6	804.3	788.6	777.3	768.6	758.8	751.8
35°	885.6	854.2	825.3	795.9	776.0	757.4	738.8	729.2	720.9	711.9	705.6
37.5°	832.5	803.2	775.8	747.8	723.2	708.1	693.1	685.7	674.5	668.5	661.9
40°	799.7	770.9	741.4	714.5	688.8	677.4	663.9	653.0	642.7	638.2	631.2
42.5°	763.9	735.0	710.1	681.2	660.1	644.5	632.1	620.2	612.5	605.9	601.9
45°	710.6	685.0	660.6	631.9	612.0	598.5	584.4	573.5	566.5	562.0	554.9
47.5°	659.0	633.4	608.6	583.5	564.3	548.9	534.8	527.3	517.9	512.4	507.6
50°	621.6	598.5	572.3	549.2	529.9	514.5	503.0	493.4	485.1	478.0	474.8
52.5°	587.3	562.6	540.0	518.4	498.1	480.7	470.2	460.1	453.8	445.7	442.1
55°	530.6	506.9	487.6	466.5	446.6	431.9	419.1	410.1	403.7	394.8	389.6
57.5°	477.4	456.2	433.2	414.8	394.4	381.9	371.3	359.1	351.3	344.2	339.2
60°	441.5	417.2	397.3	380.0	362.1	346.0	336.4	326.8	318.5	311.4	307.0
62.5°	404.1	382.8	363.9	345.1	328.7	314.8	303.6	295.5	288.2	283.7	279.2
65°	346.7	330.0	310.8	295.4	280.1	269.8	260.8	253.7	248.7	245.4	241.6
67.5°	293.8	277.7	260.9	245.8	235.5	227.7	221.8	215.8	213.3	209.1	206.6
70°	259.5	242.9	228.1	216.6	206.4	200.6	196.7	192.2	189.6	184.6	182.0
72.5°	222.1	210.0	199.4	190.0	181.7	176.5	171.6	166.1	162.0	156.4	153.8
75°	175.0	164.0	155.7	149.3	144.1	137.1	130.1	124.3	122.4	120.5	119.8
77.5°	129.6	122.6	116.6	111.2	104.8	99.7	98.2	96.9	96.5	95.5	95.5
80°	101.9	95.5	91.0	84.5	80.7	80.7	80.7	79.5	80.1	80.1	80.1
82.5°	75.7	69.9	67.4	65.1	64.3	64.8	64.8	65.1	64.7	65.7	65.2
85°	39.1	39.7	41.0	40.4	41.0	41.0	42.3	41.7	42.3	41.0	42.3
87.5°	15.1	16.8	17.5	18.3	19.0	18.7	19.2	19.3	19.9	20.0	20.1
90°	3.7	4.6	5.6	6.8	7.8	8.9	9.2	9.5	9.9	10.2	10.4
92.5°	11.2	11.7	12.4	13.0	13.6	14.2	14.4	14.7	15.0	15.2	15.3
95°	24.1	24.7	25.4	26.0	26.7	27.3	27.6	28.0	28.3	28.6	28.8
97.5°	40.4	40.8	41.3	41.8	42.3	42.8	43.1	43.5	43.9	44.3	44.4
100°	52.2	52.7	53.1	53.5	53.9	54.3	54.5	54.8	55.0	55.3	55.5
102.5°	64.7	65.1	65.7	66.2	66.8	67.3	67.6	67.8	68.1	68.3	68.4
105°	83.8	84.2	85.0	85.7	86.4	87.2	87.2	87.2	87.2	87.2	87.2
107.5°	106.3	106.5	106.8	107.0	107.4	107.7	107.9	108.2	108.4	108.7	108.8
110°	120.7	120.9	121.1	121.2	121.4	121.6	121.9	122.2	122.5	122.9	122.9



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	135.3	135.3	135.3	135.4	135.4	135.4	135.8	136.2	136.6	137.1	137.2
115°	158.0	158.1	157.9	157.8	157.6	157.4	157.5	157.6	157.7	157.8	157.8
117.5°	180.0	179.9	179.8	179.5	179.4	179.1	179.1	179.1	179.0	179.0	179.0
120°	195.2	195.3	194.9	194.4	194.0	193.6	193.6	193.5	193.4	193.3	193.1
122.5°	209.1	209.2	209.0	208.8	208.6	208.4	208.1	208.0	207.7	207.5	207.3
125°	230.8	230.8	230.6	230.5	230.3	230.2	229.8	229.5	229.2	228.9	228.5
127.5°	252.3	252.5	252.3	252.1	251.9	251.8	251.3	250.9	250.4	249.9	249.5
130°	266.4	266.6	266.4	266.1	265.9	265.6	265.3	265.0	264.6	264.3	263.9
132.5°	280.1	280.3	280.1	279.9	279.7	279.6	279.2	278.8	278.3	277.9	277.5
135°	300.1	300.4	300.3	300.2	300.1	300.0	299.7	299.4	299.1	298.7	298.5
137.5°	319.0	319.4	319.5	319.8	320.0	320.2	319.8	319.5	319.2	318.8	318.5
140°	332.3	332.6	332.6	332.7	332.8	332.9	332.8	332.7	332.6	332.6	332.2
142.5°	344.5	344.7	344.9	345.0	345.2	345.3	345.2	345.1	345.0	345.0	344.7
145°	362.4	362.6	362.8	363.1	363.3	363.5	363.5	363.4	363.3	363.2	363.1
147.5°	379.4	379.7	379.9	380.2	380.4	380.7	380.7	380.7	380.7	380.7	380.4
150°	390.4	390.6	390.8	390.9	391.1	391.3	391.3	391.3	391.3	391.3	391.0
152.5°	400.1	400.3	400.4	400.6	400.6	400.7	400.9	401.0	401.1	401.3	401.1
155°	414.2	414.3	414.3	414.4	414.5	414.6	414.9	415.2	415.6	415.9	415.7
157.5°	426.5	426.5	426.6	426.6	426.6	426.7	427.1	427.5	427.8	428.1	428.0
160°	434.2	434.1	434.1	434.1	434.1	434.1	434.6	435.0	435.4	435.8	435.8
162.5°	441.1	441.0	441.0	441.1	441.2	441.2	441.6	442.1	442.5	442.9	442.8
165°	450.1	450.0	450.0	450.0	450.0	450.0	450.5	451.0	451.5	452.0	451.9
167.5°	457.1	457.0	457.1	457.1	457.2	457.2	457.8	458.3	458.8	459.3	459.3
170°	461.3	461.1	461.1	461.1	461.1	461.1	461.7	462.3	462.8	463.4	463.4
172.5°	464.5	464.3	464.3	464.3	464.3	464.3	464.9	465.4	465.9	466.4	466.4
175°	467.9	467.7	467.7	467.7	467.7	467.7	468.2	468.7	469.2	469.7	469.7
177.5°	469.6	469.4	469.4	469.4	469.4	469.4	469.9	470.3	470.7	471.0	471.0
180°	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9
2.5°	1426.2	1425.6	1426.2	1424.1	1426.2	1425.6	1426.2	1432.3	1432.3	1432.8	1433.4
5°	1327.1	1326.5	1324.5	1318.7	1324.5	1326.5	1327.1	1329.0	1334.2	1343.1	1340.5
7.5°	1240.6	1239.7	1234.0	1234.2	1234.0	1239.7	1240.6	1245.6	1251.3	1256.9	1263.4
10°	1189.4	1189.9	1182.3	1177.8	1182.3	1189.9	1189.4	1193.8	1202.2	1206.6	1211.1
12.5°	1139.6	1136.7	1130.5	1125.5	1130.5	1136.7	1139.6	1143.0	1154.5	1159.4	1168.1
15°	1074.0	1067.6	1052.2	1053.4	1052.2	1067.6	1074.0	1071.4	1083.0	1089.3	1091.9
17.5°	996.7	992.0	991.7	982.8	991.7	992.0	996.7	1001.8	1011.8	1018.7	1037.1
20°	951.6	948.4	949.7	940.7	949.7	948.4	951.6	961.8	968.2	977.2	992.0
22.5°	916.2	913.0	907.6	904.8	907.6	913.0	916.2	923.4	930.3	942.9	951.0
25°	864.5	859.3	854.2	857.4	854.2	859.3	864.5	868.3	881.1	886.9	898.4
27.5°	812.7	808.9	803.7	803.1	803.7	808.9	812.7	816.4	823.5	833.2	847.0
30°	779.8	776.0	773.5	770.2	773.5	776.0	779.8	783.1	790.1	800.4	810.7
32.5°	746.6	745.8	741.2	740.5	741.2	745.8	746.6	751.8	758.8	768.6	777.3
35°	703.0	699.1	697.8	698.5	697.8	699.1	703.0	705.6	711.9	720.9	729.2
37.5°	661.5	656.4	654.1	651.8	654.1	656.4	661.5	661.9	668.5	674.5	685.7
40°	631.9	626.7	625.4	624.1	625.4	626.7	631.9	631.2	638.2	642.7	653.0
42.5°	598.5	596.5	595.7	593.4	595.7	596.5	598.5	601.9	605.9	612.5	620.2
45°	553.0	552.4	548.5	549.8	548.5	552.4	553.0	554.9	562.0	566.5	573.5
47.5°	505.1	502.2	499.5	501.3	499.5	502.2	505.1	507.6	512.4	517.9	527.3
50°	472.3	471.0	465.2	466.5	465.2	471.0	472.3	474.8	478.0	485.1	493.4
52.5°	439.4	434.6	432.4	431.6	432.4	434.6	439.4	442.1	445.7	453.8	460.1
55°	385.1	379.4	376.7	375.5	376.7	379.4	385.1	389.6	394.8	403.7	410.1
57.5°	331.8	330.3	328.2	329.6	328.2	330.3	331.8	339.2	344.2	351.3	359.1
60°	300.5	300.5	300.5	299.9	300.5	300.5	300.5	307.0	311.4	318.5	326.8
62.5°	276.5	274.9	274.4	275.3	274.4	274.9	276.5	279.2	283.7	288.2	295.5
65°	239.7	239.0	236.4	235.8	236.4	239.0	239.7	241.6	245.4	248.7	253.7
67.5°	205.0	202.6	201.9	201.0	201.9	202.6	205.0	206.6	209.1	213.3	215.8
70°	178.8	177.5	173.7	174.3	173.7	177.5	178.8	182.0	184.6	189.6	192.2
72.5°	150.6	149.3	148.5	147.7	148.5	149.3	150.6	153.8	156.4	162.0	166.1
75°	119.2	118.5	117.9	120.5	117.9	118.5	119.2	119.8	120.5	122.4	124.3
77.5°	95.5	95.5	95.9	94.8	95.9	95.5	95.5	95.5	95.5	96.5	96.9
80°	80.1	80.1	79.5	79.5	79.5	80.1	80.1	80.1	80.1	80.1	79.5
82.5°	64.2	64.7	65.1	64.1	65.1	64.7	64.2	65.2	65.7	64.7	65.1
85°	42.3	41.7	43.0	42.3	43.0	41.7	42.3	42.3	41.0	42.3	41.7
87.5°	21.1	20.1	20.1	20.7	20.1	20.1	21.1	20.1	20.0	19.9	19.3
90°	10.6	10.8	10.9	11.1	10.9	10.8	10.6	10.4	10.2	9.9	9.5
92.5°	15.2	15.1	15.0	14.9	15.0	15.1	15.2	15.3	15.2	15.0	14.7
95°	28.8	28.8	28.8	28.8	28.8	28.8	28.8	28.8	28.6	28.3	28.0
97.5°	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.4	44.3	43.9	43.5
100°	55.7	55.8	56.0	56.2	56.0	55.8	55.7	55.5	55.3	55.0	54.8
102.5°	68.4	68.3	68.3	68.2	68.3	68.3	68.4	68.4	68.3	68.1	67.8
105°	87.5	87.6	87.8	88.0	87.8	87.6	87.5	87.2	87.2	87.2	87.2
107.5°	108.7	108.6	108.5	108.4	108.5	108.6	108.7	108.8	108.7	108.4	108.2
110°	122.8	122.6	122.5	122.3	122.5	122.6	122.8	122.9	122.9	122.5	122.2



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	137.1	137.1	137.1	137.1	137.1	137.1	137.1	137.2	137.1	136.6	136.2
115°	157.7	157.6	157.5	157.4	157.5	157.6	157.7	157.8	157.8	157.7	157.6
117.5°	178.7	178.5	178.2	178.0	178.2	178.5	178.7	179.0	179.0	179.0	179.1
120°	193.0	192.8	192.7	192.5	192.7	192.8	193.0	193.1	193.3	193.4	193.5
122.5°	207.1	206.8	206.6	206.4	206.6	206.8	207.1	207.3	207.5	207.7	208.0
125°	228.2	227.9	227.6	227.2	227.6	227.9	228.2	228.5	228.9	229.2	229.5
127.5°	249.2	248.7	248.3	248.0	248.3	248.7	249.2	249.5	249.9	250.4	250.9
130°	263.3	262.8	262.2	261.5	262.2	262.8	263.3	263.9	264.3	264.6	265.0
132.5°	277.1	276.6	276.2	275.7	276.2	276.6	277.1	277.5	277.9	278.3	278.8
135°	298.3	298.2	298.0	297.8	298.0	298.2	298.3	298.5	298.7	299.1	299.4
137.5°	318.1	317.9	317.6	317.2	317.6	317.9	318.1	318.5	318.8	319.2	319.5
140°	331.7	331.1	330.5	330.0	330.5	331.1	331.7	332.2	332.6	332.6	332.7
142.5°	344.3	343.8	343.4	342.9	343.4	343.8	344.3	344.7	345.0	345.0	345.1
145°	362.7	362.4	362.1	361.7	362.1	362.4	362.7	363.1	363.2	363.3	363.4
147.5°	379.9	379.4	378.9	378.4	378.9	379.4	379.9	380.4	380.7	380.7	380.7
150°	390.5	390.0	389.6	389.1	389.6	390.0	390.5	391.0	391.3	391.3	391.3
152.5°	400.7	400.2	399.8	399.4	399.8	400.2	400.7	401.1	401.3	401.1	401.0
155°	415.2	414.6	414.0	413.4	414.0	414.6	415.2	415.7	415.9	415.6	415.2
157.5°	427.6	427.1	426.6	426.2	426.6	427.1	427.6	428.0	428.1	427.8	427.5
160°	435.5	435.1	434.8	434.5	434.8	435.1	435.5	435.8	435.8	435.4	435.0
162.5°	442.3	441.7	441.2	440.7	441.2	441.7	442.3	442.8	442.9	442.5	442.1
165°	451.3	450.8	450.2	449.6	450.2	450.8	451.3	451.9	452.0	451.5	451.0
167.5°	458.8	458.3	457.8	457.2	457.8	458.3	458.8	459.3	459.3	458.8	458.3
170°	462.8	462.3	461.7	461.1	461.7	462.3	462.8	463.4	463.4	462.8	462.3
172.5°	465.8	465.2	464.6	464.1	464.6	465.2	465.8	466.4	466.4	465.9	465.4
175°	469.1	468.6	468.0	467.4	468.0	468.6	469.1	469.7	469.7	469.2	468.7
177.5°	470.5	470.1	469.6	469.1	469.6	470.1	470.5	471.0	471.0	470.7	470.3
180°	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9
2.5°	1428.7	1435.9	1443.1	1449.8	1460.0	1464.6	1471.3	1473.8	1481.6	1492.8	1502.0
5°	1341.8	1352.1	1365.5	1376.5	1393.8	1407.2	1422.0	1436.1	1452.7	1476.4	1497.5
7.5°	1268.1	1278.3	1294.5	1314.7	1333.7	1352.8	1373.0	1392.2	1416.0	1450.0	1483.7
10°	1219.4	1231.6	1250.8	1272.6	1296.3	1314.9	1338.6	1363.0	1392.4	1431.6	1471.9
12.5°	1177.4	1186.5	1208.8	1229.6	1256.4	1280.1	1303.3	1331.7	1365.3	1407.0	1455.5
15°	1110.5	1123.3	1145.1	1168.2	1196.4	1221.4	1251.5	1286.1	1318.7	1370.0	1429.0
17.5°	1043.3	1062.8	1085.5	1111.5	1132.5	1166.9	1199.5	1235.1	1275.3	1329.7	1394.4
20°	1000.3	1015.7	1036.8	1074.6	1102.2	1128.5	1158.5	1202.8	1239.9	1301.5	1368.7
22.5°	963.9	975.2	998.9	1030.0	1062.2	1092.6	1123.2	1165.4	1211.2	1269.7	1342.6
25°	910.0	927.9	945.8	968.2	1002.8	1039.3	1072.7	1108.6	1157.3	1219.4	1298.3
27.5°	857.3	873.5	891.2	918.8	945.0	979.2	1014.0	1055.2	1107.4	1173.2	1253.1
30°	823.5	835.6	852.2	887.5	911.2	940.7	981.7	1018.2	1066.9	1136.8	1221.4
32.5°	788.6	804.3	822.6	849.5	878.9	906.9	944.3	983.9	1033.6	1102.4	1189.0
35°	738.8	757.4	776.0	795.9	825.3	854.2	885.6	929.2	979.7	1046.4	1131.6
37.5°	693.1	708.1	723.2	747.8	775.8	803.2	832.5	875.5	923.2	995.1	1073.2
40°	663.9	677.4	688.8	714.5	741.4	770.9	799.7	837.6	888.8	956.1	1031.7
42.5°	632.1	644.5	660.1	681.2	710.1	735.0	763.9	799.6	847.7	916.1	982.4
45°	584.4	598.5	612.0	631.9	660.6	685.0	710.6	744.6	793.9	850.4	909.3
47.5°	534.8	548.9	564.3	583.5	608.6	633.4	659.0	689.1	734.1	789.5	829.2
50°	503.0	514.5	529.9	549.2	572.3	598.5	621.6	654.3	697.2	740.8	775.3
52.5°	470.2	480.7	498.1	518.4	540.0	562.6	587.3	615.3	654.1	695.1	722.6
55°	419.1	431.9	446.6	466.5	487.6	506.9	530.6	559.5	590.2	620.9	639.5
57.5°	371.3	381.9	394.4	414.8	433.2	456.2	477.4	499.9	528.3	551.5	563.6
60°	336.4	346.0	362.1	380.0	397.3	417.2	441.5	463.9	485.8	504.3	513.9
62.5°	303.6	314.8	328.7	345.1	363.9	382.8	404.1	422.9	442.1	458.2	464.7
65°	260.8	269.8	280.1	295.4	310.8	330.0	346.7	365.9	380.0	389.0	394.8
67.5°	221.8	227.7	235.5	245.8	260.9	277.7	293.8	308.8	320.7	326.8	331.9
70°	196.7	200.6	206.4	216.6	228.1	242.9	259.5	270.4	280.7	285.8	290.9
72.5°	171.6	176.5	181.7	190.0	199.4	210.0	222.1	235.5	241.2	247.4	250.5
75°	130.1	137.1	144.1	149.3	155.7	164.0	175.0	183.3	186.5	191.6	192.2
77.5°	98.2	99.7	104.8	111.2	116.6	122.6	129.6	137.0	138.5	141.2	142.9
80°	80.7	80.7	80.7	84.5	91.0	95.5	101.9	105.7	108.3	108.9	109.6
82.5°	64.8	64.8	64.3	65.1	67.4	69.9	75.7	80.1	82.2	81.8	80.4
85°	42.3	41.0	41.0	40.4	41.0	39.7	39.1	41.7	45.5	45.5	44.2
87.5°	19.2	18.7	19.0	18.3	17.5	16.8	15.1	15.4	15.2	17.1	16.5
90°	9.2	8.9	7.8	6.8	5.6	4.6	3.7	2.9	2.0	1.2	0.4
92.5°	14.4	14.2	13.6	13.0	12.4	11.7	11.2	10.6	10.0	9.5	9.0
95°	27.6	27.3	26.7	26.0	25.4	24.7	24.1	23.6	22.9	22.3	21.8
97.5°	43.1	42.8	42.3	41.8	41.3	40.8	40.4	40.0	39.5	39.1	38.7
100°	54.5	54.3	53.9	53.5	53.1	52.7	52.2	51.7	51.2	50.7	50.2
102.5°	67.6	67.3	66.8	66.2	65.7	65.1	64.7	64.4	64.2	63.8	63.5
105°	87.2	87.2	86.4	85.7	85.0	84.2	83.8	83.6	83.5	83.3	83.2
107.5°	107.9	107.7	107.4	107.0	106.8	106.5	106.3	106.2	106.1	106.0	105.9
110°	121.9	121.6	121.4	121.2	121.1	120.9	120.7	120.6	120.4	120.3	120.1



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	135.8	135.4	135.4	135.4	135.3	135.3	135.3	135.2	135.1	134.9	134.9
115°	157.5	157.4	157.6	157.8	157.9	158.1	158.0	157.8	157.5	157.3	157.0
117.5°	179.1	179.1	179.4	179.5	179.8	179.9	180.0	179.9	179.7	179.5	179.4
120°	193.6	193.6	194.0	194.4	194.9	195.3	195.2	194.7	194.2	193.7	193.2
122.5°	208.1	208.4	208.6	208.8	209.0	209.2	209.1	208.8	208.5	208.1	207.7
125°	229.8	230.2	230.3	230.5	230.6	230.8	230.8	230.6	230.3	230.1	229.8
127.5°	251.3	251.8	251.9	252.1	252.3	252.5	252.3	251.8	251.3	250.7	250.2
130°	265.3	265.6	265.9	266.1	266.4	266.6	266.4	265.8	265.1	264.5	263.8
132.5°	279.2	279.6	279.7	279.9	280.1	280.3	280.1	279.4	278.8	278.0	277.4
135°	299.7	300.0	300.1	300.2	300.3	300.4	300.1	299.6	299.1	298.6	298.2
137.5°	319.8	320.2	320.0	319.8	319.5	319.4	319.0	318.6	318.2	317.8	317.4
140°	332.8	332.9	332.8	332.7	332.6	332.6	332.3	331.9	331.5	331.1	330.7
142.5°	345.2	345.3	345.2	345.0	344.9	344.7	344.5	344.1	343.6	343.2	342.8
145°	363.5	363.5	363.3	363.1	362.8	362.6	362.4	362.2	362.1	361.9	361.7
147.5°	380.7	380.7	380.4	380.2	379.9	379.7	379.4	379.1	378.9	378.5	378.3
150°	391.3	391.3	391.1	390.9	390.8	390.6	390.4	390.3	390.1	390.0	389.8
152.5°	400.9	400.7	400.6	400.6	400.4	400.3	400.1	399.9	399.7	399.5	399.3
155°	414.9	414.6	414.5	414.4	414.3	414.3	414.2	414.2	414.2	414.2	414.2
157.5°	427.1	426.7	426.6	426.6	426.6	426.5	426.5	426.6	426.7	426.8	426.9
160°	434.6	434.1	434.1	434.1	434.1	434.1	434.2	434.4	434.6	434.7	434.9
162.5°	441.6	441.2	441.2	441.1	441.0	441.0	441.1	441.2	441.5	441.7	442.0
165°	450.5	450.0	450.0	450.0	450.0	450.0	450.1	450.4	450.6	450.9	451.1
167.5°	457.8	457.2	457.2	457.1	457.1	457.0	457.1	457.5	457.8	458.1	458.4
170°	461.7	461.1	461.1	461.1	461.1	461.1	461.3	461.6	461.9	462.3	462.6
172.5°	464.9	464.3	464.3	464.3	464.3	464.3	464.5	464.9	465.2	465.5	465.9
175°	468.2	467.7	467.7	467.7	467.7	467.7	467.9	468.2	468.6	468.9	469.2
177.5°	469.9	469.4	469.4	469.4	469.4	469.4	469.6	469.9	470.1	470.3	470.7
180°	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9
2.5°	1505.1	1510.7	1517.9	1528.7	1536.9	1544.1	1545.6	1547.7	1552.8	1561.5	1568.1
5°	1514.8	1529.6	1553.3	1576.4	1601.3	1621.9	1641.1	1654.6	1667.4	1694.3	1716.0
7.5°	1511.8	1544.6	1581.8	1623.2	1665.1	1705.7	1743.4	1777.0	1810.6	1849.8	1894.6
10°	1509.7	1548.2	1598.1	1651.3	1709.7	1766.7	1821.8	1864.8	1914.7	1959.6	2016.6
12.5°	1500.0	1555.3	1615.1	1683.1	1754.8	1820.5	1893.0	1952.4	2009.5	2074.4	2140.6
15°	1487.3	1554.6	1630.2	1720.5	1829.5	1908.9	1983.3	2086.4	2157.0	2227.4	2322.3
17.5°	1464.1	1546.2	1640.7	1758.1	1848.9	1955.7	2067.6	2149.1	2244.1	2343.4	2429.3
20°	1445.6	1541.2	1646.8	1762.2	1878.2	1994.1	2102.5	2199.8	2297.9	2412.6	2483.1
22.5°	1427.2	1521.7	1631.5	1754.0	1878.7	2000.8	2123.4	2237.8	2348.1	2463.9	2553.8
25°	1388.0	1500.2	1619.3	1744.3	1867.3	2001.9	2148.0	2275.5	2412.0	2531.2	2616.4
27.5°	1348.3	1451.0	1569.7	1696.5	1833.2	1992.3	2164.1	2309.1	2445.8	2531.2	2557.9
30°	1312.4	1421.3	1530.2	1659.1	1807.0	1984.5	2167.1	2333.1	2445.3	2482.4	2454.9
32.5°	1275.9	1374.7	1482.5	1614.5	1771.6	1965.6	2171.3	2318.8	2386.3	2357.9	2245.7
35°	1211.8	1300.8	1405.2	1537.2	1718.0	1955.1	2154.3	2254.3	2237.7	2077.5	1866.0
37.5°	1143.0	1215.6	1312.4	1450.4	1662.4	1913.4	2081.5	2096.3	1952.2	1706.2	1461.9
40°	1088.8	1154.1	1253.4	1397.6	1619.3	1872.4	2008.2	1948.6	1725.0	1451.4	1247.7
42.5°	1035.9	1091.0	1186.7	1342.2	1578.3	1816.6	1899.1	1769.3	1511.2	1252.5	1067.2
45°	946.5	998.3	1094.5	1254.0	1494.4	1709.7	1698.8	1473.2	1215.0	1006.7	852.9
47.5°	861.6	907.0	997.2	1160.1	1395.8	1549.5	1447.6	1207.5	988.5	821.4	711.7
50°	801.6	846.5	936.2	1097.1	1316.9	1429.0	1283.5	1052.2	851.7	713.2	626.1
52.5°	744.2	788.1	870.1	1026.8	1221.5	1288.5	1132.3	917.9	750.6	631.2	556.4
55°	663.9	697.2	770.9	920.8	1066.3	1081.7	923.4	744.0	606.2	522.9	471.7
57.5°	582.0	610.7	683.5	802.9	904.9	897.0	746.9	591.7	499.0	437.0	399.8
60°	528.6	556.8	620.9	723.5	800.4	773.5	635.7	510.7	431.3	385.8	356.3
62.5°	478.9	501.0	560.9	635.8	691.1	660.6	543.4	439.9	376.9	338.6	315.3
65°	406.9	424.9	472.9	512.0	542.7	513.3	415.9	344.1	298.6	271.7	255.7
67.5°	338.4	349.8	380.3	394.4	416.0	383.7	312.7	264.6	238.8	216.1	205.0
70°	295.4	303.7	319.8	331.3	337.0	303.7	251.2	216.0	194.1	178.1	171.1
72.5°	252.3	259.7	262.9	272.3	269.4	238.1	201.9	173.9	158.2	147.4	138.3
75°	192.9	196.1	192.9	189.1	180.7	158.9	134.0	119.8	108.3	103.1	100.0
77.5°	140.6	139.6	135.2	129.2	115.0	101.3	87.8	83.1	78.0	75.3	74.2
80°	108.3	105.7	101.9	92.3	80.1	70.5	67.3	64.1	62.1	58.9	58.3
82.5°	80.6	79.1	72.6	64.6	56.0	51.5	48.8	47.7	45.7	44.1	43.9
85°	43.0	41.0	34.0	29.5	28.2	26.9	26.3	26.3	23.7	23.1	23.1
87.5°	14.1	11.2	10.8	9.5	9.6	8.8	9.5	8.7	8.4	9.0	8.1
90°	1.2	2.0	2.9	3.7	4.6	5.6	6.8	7.8	8.9	9.2	9.5
92.5°	9.5	10.0	10.6	11.2	11.7	12.4	13.0	13.6	14.2	14.4	14.7
95°	22.3	22.9	23.6	24.1	24.7	25.4	26.0	26.7	27.3	27.6	28.0
97.5°	39.1	39.5	40.0	40.4	40.8	41.3	41.8	42.3	42.8	43.1	43.5
100°	50.7	51.2	51.7	52.2	52.7	53.1	53.5	53.9	54.3	54.5	54.8
102.5°	63.8	64.2	64.4	64.7	65.1	65.7	66.2	66.8	67.3	67.6	67.8
105°	83.3	83.5	83.6	83.8	84.2	85.0	85.7	86.4	87.2	87.2	87.2
107.5°	106.0	106.1	106.2	106.3	106.5	106.8	107.0	107.4	107.7	107.9	108.2
110°	120.3	120.4	120.6	120.7	120.9	121.1	121.2	121.4	121.6	121.9	122.2



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	134.9	135.1	135.2	135.3	135.3	135.3	135.4	135.4	135.4	135.8	136.2
115°	157.3	157.5	157.8	158.0	158.1	157.9	157.8	157.6	157.4	157.5	157.6
117.5°	179.5	179.7	179.9	180.0	179.9	179.8	179.5	179.4	179.1	179.1	179.1
120°	193.7	194.2	194.7	195.2	195.3	194.9	194.4	194.0	193.6	193.6	193.5
122.5°	208.1	208.5	208.8	209.1	209.2	209.0	208.8	208.6	208.4	208.1	208.0
125°	230.1	230.3	230.6	230.8	230.8	230.6	230.5	230.3	230.2	229.8	229.5
127.5°	250.7	251.3	251.8	252.3	252.5	252.3	252.1	251.9	251.8	251.3	250.9
130°	264.5	265.1	265.8	266.4	266.6	266.4	266.1	265.9	265.6	265.3	265.0
132.5°	278.0	278.8	279.4	280.1	280.3	280.1	279.9	279.7	279.6	279.2	278.8
135°	298.6	299.1	299.6	300.1	300.4	300.3	300.2	300.1	300.0	299.7	299.4
137.5°	317.8	318.2	318.6	319.0	319.4	319.5	319.8	320.0	320.2	319.8	319.5
140°	331.1	331.5	331.9	332.3	332.6	332.6	332.7	332.8	332.9	332.8	332.7
142.5°	343.2	343.6	344.1	344.5	344.7	344.9	345.0	345.2	345.3	345.2	345.1
145°	361.9	362.1	362.2	362.4	362.6	362.8	363.1	363.3	363.5	363.5	363.4
147.5°	378.5	378.9	379.1	379.4	379.7	379.9	380.2	380.4	380.7	380.7	380.7
150°	390.0	390.1	390.3	390.4	390.6	390.8	390.9	391.1	391.3	391.3	391.3
152.5°	399.5	399.7	399.9	400.1	400.3	400.4	400.6	400.6	400.7	400.9	401.0
155°	414.2	414.2	414.2	414.2	414.3	414.3	414.4	414.5	414.6	414.9	415.2
157.5°	426.8	426.7	426.6	426.5	426.5	426.6	426.6	426.6	426.7	427.1	427.5
160°	434.7	434.6	434.4	434.2	434.1	434.1	434.1	434.1	434.1	434.6	435.0
162.5°	441.7	441.5	441.2	441.1	441.0	441.0	441.1	441.2	441.2	441.6	442.1
165°	450.9	450.6	450.4	450.1	450.0	450.0	450.0	450.0	450.0	450.5	451.0
167.5°	458.1	457.8	457.5	457.1	457.0	457.1	457.1	457.2	457.2	457.8	458.3
170°	462.3	461.9	461.6	461.3	461.1	461.1	461.1	461.1	461.1	461.7	462.3
172.5°	465.5	465.2	464.9	464.5	464.3	464.3	464.3	464.3	464.3	464.9	465.4
175°	468.9	468.6	468.2	467.9	467.7	467.7	467.7	467.7	467.7	468.2	468.7
177.5°	470.3	470.1	469.9	469.6	469.4	469.4	469.4	469.4	469.4	469.9	470.3
180°	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3	470.3



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9	1496.9
2.5°	1578.9	1578.9	1580.9	1588.7	1589.7	1596.4	1594.3
5°	1735.3	1747.4	1751.9	1771.2	1782.7	1787.9	1777.6
7.5°	1926.5	1960.9	1977.1	1997.2	2015.1	2020.5	2006.5
10°	2066.0	2101.8	2131.9	2150.5	2167.8	2179.4	2194.1
12.5°	2200.7	2244.8	2273.5	2299.7	2317.5	2332.2	2334.5
15°	2347.2	2413.9	2464.5	2501.7	2520.3	2529.9	2526.0
17.5°	2495.0	2556.8	2592.8	2630.7	2656.5	2657.8	2658.5
20°	2578.5	2638.8	2680.5	2708.7	2737.5	2736.2	2742.6
22.5°	2634.5	2681.8	2713.8	2734.3	2744.1	2739.3	2740.5
25°	2660.6	2674.7	2669.0	2636.3	2628.0	2597.8	2602.9
27.5°	2525.8	2459.1	2390.2	2301.5	2231.6	2175.6	2178.5
30°	2342.8	2224.9	2090.3	1977.5	1876.2	1848.0	1787.9
32.5°	2086.9	1910.1	1752.5	1647.4	1560.5	1536.9	1484.3
35°	1653.3	1481.6	1319.4	1222.0	1183.6	1129.8	1129.1
37.5°	1285.1	1133.8	1048.1	975.0	936.7	904.2	901.0
40°	1081.0	963.1	898.4	845.9	808.0	783.7	778.0
42.5°	938.5	843.2	782.5	750.0	720.9	708.3	699.0
45°	766.4	702.3	660.0	630.6	617.1	607.5	602.3
47.5°	641.1	598.1	569.3	549.7	538.7	528.6	531.3
50°	572.9	537.6	516.5	497.9	489.6	482.5	483.1
52.5°	518.0	486.4	469.3	455.8	445.5	440.5	438.1
55°	439.6	419.7	402.4	392.8	387.0	380.0	378.1
57.5°	375.0	359.6	345.5	334.6	333.2	326.4	327.3
60°	331.9	319.1	307.6	301.8	297.3	291.6	293.5
62.5°	296.5	285.8	275.3	270.5	266.0	261.8	262.7
65°	242.9	232.6	226.2	223.6	221.7	219.8	217.8
67.5°	193.6	187.3	183.3	177.7	173.8	173.2	171.2
70°	162.7	154.4	147.4	140.3	138.4	137.8	138.4
72.5°	130.4	125.2	123.3	119.8	119.4	117.8	119.0
75°	98.1	96.1	94.8	92.3	92.3	92.3	92.3
77.5°	72.3	71.1	70.4	69.9	69.2	68.3	68.2
80°	56.4	55.8	54.5	54.5	53.8	54.5	53.8
82.5°	42.6	42.4	41.2	41.2	40.5	40.1	40.5
85°	21.8	21.1	22.4	21.1	21.8	20.5	21.8
87.5°	8.2	8.2	7.7	7.7	7.3	8.3	7.3
90°	9.9	10.2	10.4	10.6	10.8	10.9	11.1
92.5°	15.0	15.2	15.3	15.2	15.1	15.0	14.9
95°	28.3	28.6	28.8	28.8	28.8	28.8	28.8
97.5°	43.9	44.3	44.4	44.4	44.4	44.4	44.4
100°	55.0	55.3	55.5	55.7	55.8	56.0	56.2
102.5°	68.1	68.3	68.4	68.4	68.3	68.3	68.2
105°	87.2	87.2	87.2	87.5	87.6	87.8	88.0
107.5°	108.4	108.7	108.8	108.7	108.6	108.5	108.4
110°	122.5	122.9	122.9	122.8	122.6	122.5	122.3



TEST NUMBER: P332471-930

CATALOG NUMBER: S123RDIW-S1165D460U930-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	136.6	137.1	137.2	137.1	137.1	137.1	137.1
115°	157.7	157.8	157.8	157.7	157.6	157.5	157.4
117.5°	179.0	179.0	179.0	178.7	178.5	178.2	178.0
120°	193.4	193.3	193.1	193.0	192.8	192.7	192.5
122.5°	207.7	207.5	207.3	207.1	206.8	206.6	206.4
125°	229.2	228.9	228.5	228.2	227.9	227.6	227.2
127.5°	250.4	249.9	249.5	249.2	248.7	248.3	248.0
130°	264.6	264.3	263.9	263.3	262.8	262.2	261.5
132.5°	278.3	277.9	277.5	277.1	276.6	276.2	275.7
135°	299.1	298.7	298.5	298.3	298.2	298.0	297.8
137.5°	319.2	318.8	318.5	318.1	317.9	317.6	317.2
140°	332.6	332.6	332.2	331.7	331.1	330.5	330.0
142.5°	345.0	345.0	344.7	344.3	343.8	343.4	342.9
145°	363.3	363.2	363.1	362.7	362.4	362.1	361.7
147.5°	380.7	380.7	380.4	379.9	379.4	378.9	378.4
150°	391.3	391.3	391.0	390.5	390.0	389.6	389.1
152.5°	401.1	401.3	401.1	400.7	400.2	399.8	399.4
155°	415.6	415.9	415.7	415.2	414.6	414.0	413.4
157.5°	427.8	428.1	428.0	427.6	427.1	426.6	426.2
160°	435.4	435.8	435.8	435.5	435.1	434.8	434.5
162.5°	442.5	442.9	442.8	442.3	441.7	441.2	440.7
165°	451.5	452.0	451.9	451.3	450.8	450.2	449.6
167.5°	458.8	459.3	459.3	458.8	458.3	457.8	457.2
170°	462.8	463.4	463.4	462.8	462.3	461.7	461.1
172.5°	465.9	466.4	466.4	465.8	465.2	464.6	464.1
175°	469.2	469.7	469.7	469.1	468.6	468.0	467.4
177.5°	470.7	471.0	471.0	470.5	470.1	469.6	469.1
180°	470.3	470.3	470.3	470.3	470.3	470.3	470.3

(END OF REPORT)