

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: NEO-RAY

Report Number: P332156

Luminaire Tested: **S123DIW-S775D755U835-4F0-1E-UDD-A**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P332156
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-5,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S123DIW-S775D755U835-4F0-1E-UDD-A
Description: DEFINE 3 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 775 LUMENS PER FOOT, ASYMMETRIC DIFFUSER
UPLIGHT 755 LUMENS PER FOOT, NO LENS
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6284.5 lumens
Efficiency: N/A
Efficacy: 139.7 lumens/watt
Spacing Criteria (0/90/45): 1.37 / 1.23 / 1.49
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')
CIE Type: General Diffuse

Input Watts (W): 45
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P332156
CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

Luminous Intensity Polar Plot





TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	108	108	108	108	100	100	100	100	84	84	84	71	71	71	58	58	58	52
1	99	94	90	87	91	87	84	81	74	72	70	63	61	59	52	51	49	44
2	90	83	77	72	83	77	71	67	66	62	58	55	52	50	46	44	42	38
3	82	73	66	60	76	68	61	56	58	53	49	49	46	43	41	38	36	32
4	75	65	57	51	69	60	53	48	52	46	42	44	40	37	37	34	31	28
5	69	58	50	44	64	54	47	41	46	41	37	39	35	32	33	30	27	24
6	64	52	44	38	59	48	41	36	42	36	32	36	31	28	30	27	24	21
7	59	47	39	33	54	44	37	32	38	32	28	32	28	25	27	24	21	19
8	55	42	35	30	51	40	33	28	35	29	25	30	25	22	25	22	19	17
9	51	39	31	26	47	36	30	25	32	26	22	27	23	20	23	20	17	15
10	48	36	28	24	44	33	27	22	29	24	20	25	21	18	22	18	16	14

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	11630	11630	11630	11630
5°	13870	11681	10351	11681
10°	17361	11622	9349	11622
15°	21293	11528	8704	11528
20°	25366	11381	8287	11381
25°	26935	11204	8195	11204
30°	23086	11074	8238	11074
35°	16056	10889	8324	10889
40°	12094	10673	8297	10673
45°	10041	10353	8193	10353
50°	8994	9696	8118	9696
55°	8409	8989	8017	8989
60°	7890	8249	7935	8249
65°	7414	7521	7679	7521
70°	6952	6688	7314	6688
75°	6226	5856	6704	5856
80°	5455	4804	5777	4804
85°	4273	3495	3878	3495



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	106.4	1.7
10°-20°	341.3	5.4
20°-30°	572.8	9.1
30°-40°	648.6	10.3
40°-50°	581.7	9.3
50°-60°	469.4	7.5
60°-70°	327.1	5.2
70°-80°	171.9	2.7
80°-90°	44.8	0.7
90°-100°	36.0	0.6
100°-110°	171.6	2.7
110°-120°	412.3	6.6
120°-130°	525.0	8.4
130°-140°	560.9	8.9
140°-150°	524.5	8.3
150°-160°	423.1	6.7
160°-170°	273.1	4.3
170°-180°	94.1	1.5
0°-30°	1020.6	16.2
0°-40°	1669.2	26.6
0°-60°	2720.2	43.3
0°-90°	3264.1	51.9
90°-120°	619.9	9.9
90°-150°	2230.2	35.5
90°-180°	3020.0	48.1
0°-180°	6284.5	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1080	1080	1080	1080	1080	
5°	1284	1081	958	1081	1284	133
15°	1911	1034	781	1034	1911	552
25°	2268	943	690	943	2268	995
35°	1222	829	634	829	1222	794
45°	660	680	538	680	660	522
55°	448	479	427	479	448	402
65°	291	295	302	295	291	290
75°	150	141	161	141	150	160
85°	35	28	31	28	35	41
90°	22	1	22	1	22	12
95°	28	45	28	45	28	23
105°	32	219	32	219	32	74
115°	433	411	433	411	433	400
125°	592	580	592	580	592	528
135°	729	722	729	722	729	562
145°	841	833	841	833	841	525
155°	916	918	916	918	916	422
165°	965	968	965	968	965	273
175°	987	990	987	990	987	94
180°	990	990	990	990	990	



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5
2.5°	1146.7	1145.9	1143.8	1145.5	1142.1	1137.5	1137.1	1132.9	1120.7	1119.9	1116.6
5°	1283.7	1279.5	1279.0	1278.4	1271.1	1261.2	1242.3	1240.7	1215.6	1203.0	1187.9
7.5°	1461.0	1463.2	1455.6	1448.9	1426.5	1411.7	1391.5	1365.6	1334.8	1303.5	1282.6
10°	1588.4	1605.6	1584.2	1569.5	1555.9	1530.2	1500.4	1463.2	1426.1	1382.6	1349.6
12.5°	1724.9	1733.4	1729.1	1715.3	1694.1	1655.1	1602.2	1561.2	1527.0	1454.6	1425.4
15°	1910.8	1942.8	1922.4	1875.2	1876.3	1839.1	1770.0	1694.1	1653.8	1590.4	1504.1
17.5°	2108.9	2112.9	2104.2	2065.0	2038.8	1987.7	1923.9	1851.2	1769.5	1692.8	1601.2
20°	2214.5	2211.3	2193.0	2172.6	2127.6	2087.8	2018.2	1937.0	1832.3	1756.9	1656.9
22.5°	2273.1	2267.9	2259.2	2242.1	2204.6	2161.9	2099.4	2010.7	1911.1	1807.2	1691.7
25°	2267.9	2274.7	2275.7	2271.0	2257.9	2232.3	2183.1	2112.4	2012.9	1879.4	1759.0
27.5°	2062.7	2072.3	2100.3	2125.1	2152.8	2181.1	2177.3	2142.2	2068.6	1953.4	1806.1
30°	1857.4	1836.5	1888.3	1953.8	1998.3	2076.8	2120.8	2123.4	2082.0	1983.1	1839.6
32.5°	1572.6	1595.7	1618.6	1699.1	1796.4	1884.6	1972.1	2042.6	2050.6	1984.8	1859.3
35°	1221.9	1250.7	1292.6	1334.4	1439.2	1529.2	1683.1	1817.1	1923.9	1938.1	1861.1
37.5°	984.6	998.9	1025.4	1067.3	1135.8	1242.6	1361.7	1531.1	1685.8	1800.9	1805.9
40°	860.7	864.9	894.7	926.6	982.1	1070.1	1177.4	1327.1	1512.4	1673.2	1740.2
42.5°	767.7	776.9	789.6	820.2	864.4	930.6	1030.4	1154.1	1324.0	1509.0	1640.1
45°	659.6	670.1	678.0	698.4	729.8	774.3	843.9	957.0	1086.3	1277.4	1453.8
47.5°	588.2	589.1	594.9	610.3	631.7	665.1	714.3	787.0	905.7	1060.6	1241.8
50°	537.1	545.5	547.6	559.6	576.4	601.0	641.8	703.6	801.0	937.1	1103.6
52.5°	501.1	503.6	509.5	518.2	532.8	552.0	587.4	635.8	712.2	828.2	981.3
55°	448.1	448.1	453.9	460.7	469.1	486.3	509.9	545.5	603.6	693.7	820.4
57.5°	399.1	401.7	405.8	407.9	415.0	426.5	446.1	473.2	516.5	585.8	686.5
60°	366.5	371.2	370.7	374.8	381.1	390.0	406.8	428.8	467.5	523.0	607.8
62.5°	338.0	337.7	337.6	342.6	348.9	357.4	368.2	387.3	420.2	469.4	541.6
65°	291.1	290.0	293.7	296.8	298.9	305.2	313.6	330.3	352.3	389.0	445.0
67.5°	249.4	246.4	248.4	249.4	253.0	257.9	265.7	276.1	293.6	323.0	365.2
70°	220.9	218.3	217.8	218.8	222.0	225.6	231.4	241.3	257.6	281.1	312.0
72.5°	191.6	189.8	189.7	192.0	193.5	195.9	200.0	209.1	222.0	239.7	268.5
75°	149.7	149.7	149.7	150.2	151.8	153.9	157.1	161.8	171.7	184.3	203.6
77.5°	112.2	112.1	111.5	111.4	113.7	114.7	115.4	119.8	125.3	133.8	147.9
80°	88.0	85.3	86.4	88.0	89.0	89.5	91.1	92.1	96.9	101.6	111.5
82.5°	65.3	63.1	63.3	65.8	66.0	66.5	68.1	69.5	71.3	75.6	80.9
85°	34.6	34.6	35.1	35.1	35.6	35.1	36.6	37.2	37.2	39.8	42.9
87.5°	17.0	16.1	16.4	16.8	16.3	16.6	16.9	17.2	17.5	17.8	17.8
90°	22.1	21.7	21.4	21.1	20.8	20.3	19.6	19.0	18.3	17.7	15.5
92.5°	24.4	24.2	24.0	23.8	23.6	23.0	22.0	20.9	19.9	18.8	17.2
95°	28.0	28.0	28.0	28.0	28.0	27.4	26.2	25.1	24.0	22.8	21.0
97.5°	30.3	30.2	30.0	29.8	29.7	28.9	27.6	26.3	25.0	23.7	35.5
100°	30.9	30.7	30.6	30.4	30.3	29.5	28.2	26.9	25.6	24.3	49.8
102.5°	31.5	31.2	30.9	30.6	30.3	32.2	36.3	40.3	44.4	48.4	76.3
105°	32.4	32.1	31.7	31.4	31.1	45.4	74.3	103.3	132.2	161.2	175.9
107.5°	101.7	123.5	145.3	167.1	189.0	210.5	231.7	252.9	274.1	295.4	293.1
110°	202.4	225.7	249.1	272.5	295.9	310.3	315.7	321.1	326.5	331.9	330.1



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	347.2	352.1	357.1	362.0	366.9	369.4	369.3	369.2	369.1	369.0	367.2
115°	432.7	432.0	431.4	430.7	430.1	428.9	427.3	425.7	424.0	422.4	420.9
117.5°	480.7	480.5	480.4	480.3	480.1	479.4	478.1	476.8	475.5	474.2	473.4
120°	513.6	513.6	513.6	513.6	513.6	513.0	511.7	510.4	509.1	507.7	507.3
122.5°	546.0	545.9	545.7	545.6	545.5	545.0	544.0	543.1	542.2	541.3	540.7
125°	591.6	591.3	591.0	590.7	590.3	590.0	589.7	589.3	589.0	588.7	588.0
127.5°	635.5	635.8	636.1	636.5	636.8	636.7	636.2	635.7	635.1	634.6	633.8
130°	663.7	664.1	664.4	664.7	665.1	664.9	664.2	663.6	662.9	662.3	661.6
132.5°	689.6	690.1	690.6	691.0	691.5	691.4	690.7	690.1	689.4	688.8	688.2
135°	729.2	729.7	730.2	730.7	731.2	731.2	730.7	730.2	729.7	729.2	728.6
137.5°	766.5	766.8	767.1	767.5	767.8	767.6	766.8	766.0	765.2	764.4	764.1
140°	788.8	789.2	789.5	789.8	790.2	790.0	789.3	788.7	788.0	787.4	786.9
142.5°	809.4	809.9	810.4	810.8	811.3	811.2	810.7	810.2	809.7	809.2	808.7
145°	841.1	841.1	841.1	841.1	841.1	840.9	840.6	840.3	839.9	839.6	839.3
147.5°	864.6	865.4	866.1	866.9	867.6	867.9	867.5	867.2	866.9	866.5	866.2
150°	882.3	882.8	883.3	883.8	884.3	884.3	884.0	883.7	883.4	883.0	882.7
152.5°	896.4	897.2	897.9	898.7	899.4	899.5	898.9	898.3	897.7	897.2	897.0
155°	916.1	917.1	918.1	919.1	920.1	920.2	919.3	918.5	917.7	916.9	916.7
157.5°	932.8	934.1	935.3	936.6	937.9	938.0	937.0	936.1	935.1	934.1	934.3
160°	943.4	944.5	945.7	946.8	948.0	948.0	947.1	946.1	945.1	944.1	944.3
162.5°	953.4	954.4	955.4	956.4	957.4	957.4	956.3	955.2	954.1	952.9	953.1
165°	965.4	966.6	967.7	968.9	970.0	969.9	968.6	967.3	966.0	964.7	964.9
167.5°	974.1	975.4	976.7	978.1	979.4	979.4	978.1	976.7	975.4	974.1	974.1
170°	979.4	980.7	982.0	983.4	984.7	984.7	983.4	982.0	980.7	979.4	979.4
172.5°	982.4	983.8	985.3	986.7	988.1	988.2	986.9	985.6	984.3	983.0	982.8
175°	986.8	988.1	989.4	990.7	992.0	992.1	991.0	989.8	988.7	987.5	987.4
177.5°	988.1	989.4	990.7	992.0	993.3	993.5	992.4	991.4	990.3	989.3	989.2
180°	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5
2.5°	1114.0	1110.7	1107.3	1101.5	1096.5	1089.3	1087.2	1084.7	1077.2	1070.5	1065.5
5°	1182.1	1169.5	1151.2	1134.5	1120.9	1102.5	1092.1	1081.1	1065.4	1051.2	1039.7
7.5°	1253.3	1228.6	1200.1	1169.3	1140.6	1113.0	1090.7	1070.8	1048.8	1028.0	1011.8
10°	1309.8	1274.2	1234.5	1191.5	1154.9	1119.3	1089.4	1063.3	1035.0	1010.4	990.0
12.5°	1374.3	1321.6	1266.7	1214.6	1171.2	1121.8	1085.7	1052.4	1020.3	990.7	967.8
15°	1450.7	1383.7	1318.7	1247.0	1181.1	1119.3	1076.4	1034.5	997.3	966.9	937.6
17.5°	1520.2	1444.3	1358.7	1271.5	1191.9	1118.7	1058.6	1011.2	964.7	927.6	898.4
20°	1559.6	1473.2	1376.3	1285.8	1197.8	1116.1	1050.2	993.6	943.4	904.1	871.1
22.5°	1593.5	1492.4	1392.2	1295.4	1197.4	1109.4	1034.7	976.5	922.0	883.6	848.5
25°	1628.7	1507.7	1407.2	1293.6	1184.2	1093.1	1009.3	943.4	888.9	843.9	807.8
27.5°	1658.8	1506.7	1387.4	1265.2	1163.5	1072.2	982.7	912.0	854.2	805.3	768.6
30°	1678.9	1508.8	1366.9	1246.0	1143.4	1049.1	962.2	891.0	830.3	780.6	746.0
32.5°	1691.5	1507.5	1348.1	1219.2	1111.5	1028.2	940.0	866.3	803.9	755.0	721.7
35°	1698.8	1498.3	1315.6	1163.8	1060.1	979.0	905.2	828.7	763.3	717.7	680.1
37.5°	1684.2	1478.9	1277.9	1110.4	996.9	917.0	854.9	789.8	727.2	677.0	644.6
40°	1661.1	1466.4	1248.6	1072.7	953.3	876.4	823.5	759.6	697.8	650.2	619.8
42.5°	1617.1	1440.8	1216.3	1030.8	908.1	831.1	782.5	729.1	670.6	625.9	595.6
45°	1509.8	1385.2	1168.0	968.0	841.3	761.7	718.8	680.1	627.2	583.7	557.5
47.5°	1360.9	1301.6	1098.0	901.7	771.6	695.0	650.4	619.2	580.6	545.5	520.4
50°	1257.5	1232.9	1050.7	856.5	725.1	650.2	607.3	579.0	551.3	516.2	493.2
52.5°	1138.1	1153.3	995.4	809.6	677.7	604.1	563.7	541.3	516.1	487.3	467.2
55°	970.1	1025.0	899.9	730.8	607.3	537.1	498.9	479.0	464.4	442.9	425.6
57.5°	812.7	882.7	796.7	649.7	538.1	477.6	440.9	419.2	409.8	398.6	385.0
60°	719.3	788.4	723.0	595.2	491.6	434.0	401.5	383.2	373.8	365.9	354.4
62.5°	636.0	705.9	650.9	540.0	445.9	392.5	364.3	346.4	339.0	334.9	325.1
65°	521.4	581.6	545.0	453.9	380.6	333.5	307.8	295.3	288.5	286.9	280.6
67.5°	424.4	470.2	443.5	376.5	318.8	278.1	256.3	245.6	240.4	239.9	235.2
70°	360.7	403.6	383.2	322.5	272.8	240.8	222.0	212.5	209.4	208.9	206.3
72.5°	311.3	341.2	325.0	274.3	235.9	206.9	193.1	183.2	179.7	180.4	178.6
75°	230.3	252.9	243.4	208.4	177.5	158.6	147.1	140.8	137.7	139.3	137.2
77.5°	165.7	180.0	171.5	147.2	128.2	114.5	106.1	102.2	99.4	99.3	98.3
80°	125.1	133.5	128.8	114.1	98.4	86.9	80.1	77.5	75.9	75.4	74.9
82.5°	89.1	96.2	90.7	80.6	69.9	63.0	59.2	55.7	54.6	54.9	54.3
85°	45.0	47.6	45.5	39.3	35.1	31.9	29.8	28.3	27.2	27.7	26.7
87.5°	18.2	18.2	16.5	14.4	13.3	11.7	11.4	10.2	9.7	10.0	9.9
90°	13.4	11.3	9.2	7.3	5.6	4.0	2.4	0.7	2.4	4.0	5.6
92.5°	15.6	14.0	12.4	11.9	12.3	12.8	13.2	13.7	13.2	12.8	12.3
95°	19.2	17.4	15.6	18.1	24.8	31.5	38.2	44.9	38.2	31.5	24.8
97.5°	47.2	59.0	70.8	78.2	81.2	84.2	87.2	90.2	87.2	84.2	81.2
100°	75.3	100.8	126.3	137.4	134.2	130.9	127.6	124.4	127.6	130.9	134.2
102.5°	104.1	132.0	159.9	172.6	170.3	167.9	165.6	163.2	165.6	167.9	170.3
105°	190.6	205.3	220.0	226.5	224.7	222.9	221.1	219.3	221.1	222.9	224.7
107.5°	290.7	288.4	286.1	284.2	282.8	281.3	279.9	278.4	279.9	281.3	282.8
110°	328.3	326.5	324.7	323.1	321.8	320.5	319.2	317.9	319.2	320.5	321.8



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	365.4	363.6	361.8	360.3	359.1	357.9	356.7	355.6	356.7	357.9	359.1
115°	419.4	418.0	416.5	415.3	414.3	413.3	412.3	411.3	412.3	413.3	414.3
117.5°	472.7	471.9	471.2	470.2	469.0	467.8	466.6	465.4	466.6	467.8	469.0
120°	506.8	506.3	505.8	504.8	503.3	501.9	500.4	498.9	500.4	501.9	503.3
122.5°	540.1	539.4	538.8	537.9	536.7	535.5	534.3	533.1	534.3	535.5	536.7
125°	587.4	586.7	586.1	585.1	583.8	582.5	581.2	579.9	581.2	582.5	583.8
127.5°	633.0	632.3	631.5	630.4	629.1	627.8	626.5	625.2	626.5	627.8	629.1
130°	661.0	660.3	659.7	658.7	657.4	656.1	654.8	653.4	654.8	656.1	657.4
132.5°	687.7	687.2	686.7	685.8	684.4	683.1	681.8	680.5	681.8	683.1	684.4
135°	727.9	727.3	726.6	725.8	724.8	723.8	722.9	721.9	722.9	723.8	724.8
137.5°	763.7	763.3	763.0	762.2	760.9	759.7	758.4	757.2	758.4	759.7	760.9
140°	786.4	785.9	785.4	784.7	783.7	782.7	781.7	780.7	781.7	782.7	783.7
142.5°	808.2	807.7	807.2	806.5	805.5	804.5	803.5	802.5	803.5	804.5	805.5
145°	839.0	838.6	838.3	837.6	836.4	835.3	834.1	833.0	834.1	835.3	836.4
147.5°	865.9	865.6	865.2	864.7	863.9	863.2	862.4	861.7	862.4	863.2	863.9
150°	882.4	882.1	881.7	881.3	880.8	880.3	879.8	879.4	879.8	880.3	880.8
152.5°	896.8	896.6	896.4	896.2	895.9	895.7	895.5	895.2	895.5	895.7	895.9
155°	916.6	916.4	916.2	916.3	916.6	917.0	917.3	917.6	917.3	917.0	916.6
157.5°	934.4	934.6	934.8	934.9	934.9	934.9	935.0	935.0	935.0	934.9	934.9
160°	944.4	944.6	944.8	944.9	945.1	945.3	945.4	945.6	945.4	945.3	945.1
162.5°	953.3	953.4	953.6	953.9	954.3	954.7	955.2	955.6	955.2	954.7	954.3
165°	965.0	965.2	965.4	965.7	966.2	966.7	967.2	967.7	967.2	966.7	966.2
167.5°	974.1	974.1	974.1	974.5	975.1	975.8	976.4	977.1	976.4	975.8	975.1
170°	979.4	979.4	979.4	979.8	980.4	981.1	981.7	982.4	981.7	981.1	980.4
172.5°	982.7	982.6	982.4	982.8	983.6	984.3	985.1	985.9	985.1	984.3	983.6
175°	987.2	987.0	986.9	987.2	988.0	988.8	989.6	990.5	989.6	988.8	988.0
177.5°	989.0	988.9	988.8	989.0	989.7	990.3	991.0	991.6	991.0	990.3	989.7
180°	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5
2.5°	1062.5	1059.6	1055.4	1049.1	1044.1	1036.1	1036.1	1037.4	1037.4	1037.0	1036.1
5°	1030.3	1022.4	1013.0	1002.0	990.5	979.0	976.9	972.7	969.6	967.5	964.8
7.5°	996.3	982.3	968.6	953.2	939.2	927.6	919.5	912.8	908.5	903.9	900.6
10°	973.2	955.9	939.7	923.5	905.7	891.6	882.7	876.4	871.7	867.5	865.4
12.5°	946.0	926.2	908.3	892.9	873.4	858.9	850.4	847.5	841.9	833.1	828.5
15°	906.2	887.9	866.4	842.9	833.4	815.6	805.7	801.0	797.8	791.0	788.9
17.5°	872.2	848.2	824.1	806.5	789.0	774.6	769.0	763.2	759.0	753.4	751.8
20°	845.0	823.5	801.5	782.7	764.3	748.6	743.9	739.7	735.5	732.9	730.8
22.5°	817.3	795.9	777.6	760.0	740.5	730.2	725.1	720.5	717.5	715.8	713.7
25°	778.5	759.6	739.2	723.5	707.8	701.0	697.8	695.2	693.1	690.5	690.0
27.5°	743.7	723.2	706.6	692.0	680.7	675.0	672.0	670.7	671.2	672.1	672.7
30°	717.7	698.9	685.3	672.7	662.3	657.0	656.5	656.5	658.6	659.1	660.2
32.5°	693.9	678.4	664.8	652.6	644.7	641.1	643.1	643.1	644.8	646.1	648.0
35°	659.1	645.5	635.0	624.6	617.8	619.3	620.4	621.4	624.0	627.2	629.3
37.5°	625.9	614.1	603.2	595.0	591.9	594.7	597.2	599.4	602.5	604.9	607.0
40°	602.0	593.1	582.7	575.3	576.4	578.0	580.1	582.7	585.3	586.9	589.0
42.5°	579.8	570.5	562.6	556.5	558.0	560.0	561.2	562.6	565.6	568.4	569.7
45°	546.0	538.7	531.4	527.7	528.8	529.8	530.8	532.4	535.0	537.1	537.7
47.5°	508.0	502.9	498.0	494.4	496.1	495.7	497.0	500.4	501.2	502.5	505.4
50°	483.7	479.0	473.3	472.2	472.2	472.2	472.7	476.9	476.9	479.0	481.1
52.5°	456.9	453.9	450.2	448.3	447.5	447.5	449.7	451.8	452.6	455.6	457.7
55°	417.2	414.1	411.0	409.4	408.3	409.4	413.6	414.6	417.2	418.8	420.4
57.5°	375.9	373.5	371.0	370.1	369.9	371.3	373.6	376.7	377.4	382.2	384.6
60°	348.7	345.0	342.9	342.9	341.9	346.6	345.5	350.8	351.8	354.9	358.6
62.5°	320.6	315.7	314.8	314.8	316.3	317.7	319.1	321.4	324.2	328.1	331.0
65°	275.4	272.8	276.4	275.9	274.8	278.0	278.0	280.6	283.7	287.4	293.2
67.5°	232.5	231.2	231.5	231.5	233.1	234.9	236.3	238.6	242.4	246.3	250.0
70°	203.6	205.2	202.6	204.7	206.3	206.8	207.8	211.0	215.2	217.8	222.0
72.5°	175.6	175.5	175.8	176.6	178.2	179.1	180.2	183.8	188.4	190.6	193.9
75°	135.1	134.5	136.1	136.1	138.7	139.8	140.8	142.4	146.6	149.7	152.3
77.5°	98.6	99.3	98.9	100.7	100.0	100.2	103.4	105.0	105.4	111.6	113.0
80°	74.3	75.4	75.9	76.4	77.0	75.9	79.6	81.1	81.1	84.8	87.4
82.5°	53.4	54.0	55.4	55.9	56.0	57.1	57.4	58.5	59.8	61.4	64.8
85°	26.7	28.3	28.8	28.3	28.8	27.7	29.3	29.8	30.4	30.4	30.4
87.5°	9.8	10.6	10.6	11.5	11.5	12.3	12.5	11.8	11.9	13.3	11.7
90°	7.3	9.2	11.3	13.4	15.5	17.7	18.3	19.0	19.6	20.3	20.8
92.5°	11.9	12.4	14.0	15.6	17.2	18.8	19.9	20.9	22.0	23.0	23.6
95°	18.1	15.6	17.4	19.2	21.0	22.8	24.0	25.1	26.2	27.4	28.0
97.5°	78.2	70.8	59.0	47.2	35.5	23.7	25.0	26.3	27.6	28.9	29.7
100°	137.4	126.3	100.8	75.3	49.8	24.3	25.6	26.9	28.2	29.5	30.3
102.5°	172.6	159.9	132.0	104.1	76.3	48.4	44.4	40.3	36.3	32.2	30.3
105°	226.5	220.0	205.3	190.6	175.9	161.2	132.2	103.3	74.3	45.4	31.1
107.5°	284.2	286.1	288.4	290.7	293.1	295.4	274.1	252.9	231.7	210.5	189.0
110°	323.1	324.7	326.5	328.3	330.1	331.9	326.5	321.1	315.7	310.3	295.9



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	360.3	361.8	363.6	365.4	367.2	369.0	369.1	369.2	369.3	369.4	366.9
115°	415.3	416.5	418.0	419.4	420.9	422.4	424.0	425.7	427.3	428.9	430.1
117.5°	470.2	471.2	471.9	472.7	473.4	474.2	475.5	476.8	478.1	479.4	480.1
120°	504.8	505.8	506.3	506.8	507.3	507.7	509.1	510.4	511.7	513.0	513.6
122.5°	537.9	538.8	539.4	540.1	540.7	541.3	542.2	543.1	544.0	545.0	545.5
125°	585.1	586.1	586.7	587.4	588.0	588.7	589.0	589.3	589.7	590.0	590.3
127.5°	630.4	631.5	632.3	633.0	633.8	634.6	635.1	635.7	636.2	636.7	636.8
130°	658.7	659.7	660.3	661.0	661.6	662.3	662.9	663.6	664.2	664.9	665.1
132.5°	685.8	686.7	687.2	687.7	688.2	688.8	689.4	690.1	690.7	691.4	691.5
135°	725.8	726.6	727.3	727.9	728.6	729.2	729.7	730.2	730.7	731.2	731.2
137.5°	762.2	763.0	763.3	763.7	764.1	764.4	765.2	766.0	766.8	767.6	767.8
140°	784.7	785.4	785.9	786.4	786.9	787.4	788.0	788.7	789.3	790.0	790.2
142.5°	806.5	807.2	807.7	808.2	808.7	809.2	809.7	810.2	810.7	811.2	811.3
145°	837.6	838.3	838.6	839.0	839.3	839.6	839.9	840.3	840.6	840.9	841.1
147.5°	864.7	865.2	865.6	865.9	866.2	866.5	866.9	867.2	867.5	867.9	867.6
150°	881.3	881.7	882.1	882.4	882.7	883.0	883.4	883.7	884.0	884.3	884.3
152.5°	896.2	896.4	896.6	896.8	897.0	897.2	897.7	898.3	898.9	899.5	899.4
155°	916.3	916.2	916.4	916.6	916.7	916.9	917.7	918.5	919.3	920.2	920.1
157.5°	934.9	934.8	934.6	934.4	934.3	934.1	935.1	936.1	937.0	938.0	937.9
160°	944.9	944.8	944.6	944.4	944.3	944.1	945.1	946.1	947.1	948.0	948.0
162.5°	953.9	953.6	953.4	953.3	953.1	952.9	954.1	955.2	956.3	957.4	957.4
165°	965.7	965.4	965.2	965.0	964.9	964.7	966.0	967.3	968.6	969.9	970.0
167.5°	974.5	974.1	974.1	974.1	974.1	974.1	975.4	976.7	978.1	979.4	979.4
170°	979.8	979.4	979.4	979.4	979.4	979.4	980.7	982.0	983.4	984.7	984.7
172.5°	982.8	982.4	982.6	982.7	982.8	983.0	984.3	985.6	986.9	988.2	988.1
175°	987.2	986.9	987.0	987.2	987.4	987.5	988.7	989.8	991.0	992.1	992.0
177.5°	989.0	988.8	988.9	989.0	989.2	989.3	990.3	991.4	992.4	993.5	993.3
180°	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5
2.5°	1033.2	1032.8	1035.7	1033.6	1035.7	1032.8	1033.2	1036.1	1037.0	1037.4	1037.4
5°	961.7	963.3	958.0	958.0	958.0	963.3	961.7	964.8	967.5	969.6	972.7
7.5°	898.0	895.7	895.9	893.1	895.9	895.7	898.0	900.6	903.9	908.5	912.8
10°	859.1	856.0	854.9	855.4	854.9	856.0	859.1	865.4	867.5	871.7	876.4
12.5°	826.8	826.2	819.3	819.4	819.3	826.2	826.8	828.5	833.1	841.9	847.5
15°	788.9	779.0	777.9	781.1	777.9	779.0	788.9	788.9	791.0	797.8	801.0
17.5°	750.9	745.7	746.0	744.4	746.0	745.7	750.9	751.8	753.4	759.0	763.2
20°	730.8	727.7	727.2	723.5	727.2	727.7	730.8	730.8	732.9	735.5	739.7
22.5°	712.4	711.4	711.7	707.6	711.7	711.4	712.4	713.7	715.8	717.5	720.5
25°	689.5	692.1	690.0	690.0	690.0	692.1	689.5	690.0	690.5	693.1	695.2
27.5°	674.0	673.9	672.8	672.8	672.8	673.9	674.0	672.7	672.1	671.2	670.7
30°	662.3	661.7	662.8	662.8	662.8	661.7	662.3	660.2	659.1	658.6	656.5
32.5°	650.5	651.3	651.5	651.9	651.5	651.3	650.5	648.0	646.1	644.8	643.1
35°	632.4	632.9	634.5	633.5	634.5	632.9	632.4	629.3	627.2	624.0	621.4
37.5°	607.9	610.3	609.8	610.6	609.8	610.3	607.9	607.0	604.9	602.5	599.4
40°	589.5	591.1	590.5	590.5	590.5	591.1	589.5	589.0	586.9	585.3	582.7
42.5°	570.6	571.8	570.4	569.6	570.4	571.8	570.6	569.7	568.4	565.6	562.6
45°	539.7	538.7	540.3	538.2	540.3	538.7	539.7	537.7	537.1	535.0	532.4
47.5°	505.2	506.2	506.7	508.2	506.7	506.2	505.2	505.4	502.5	501.2	500.4
50°	482.2	485.3	485.3	484.8	485.3	485.3	482.2	481.1	479.0	476.9	476.9
52.5°	459.5	461.0	463.1	463.0	463.1	461.0	459.5	457.7	455.6	452.6	451.8
55°	424.6	425.6	426.7	427.2	426.7	425.6	424.6	420.4	418.8	417.2	414.6
57.5°	388.3	387.9	390.4	391.2	390.4	387.9	388.3	384.6	382.2	377.4	376.7
60°	362.8	362.8	367.0	368.6	367.0	362.8	362.8	358.6	354.9	351.8	350.8
62.5°	335.6	337.3	341.4	339.2	341.4	337.3	335.6	331.0	328.1	324.2	321.4
65°	295.8	300.0	299.5	301.5	299.5	300.0	295.8	293.2	287.4	283.7	280.6
67.5°	254.2	256.8	260.6	260.9	260.6	256.8	254.2	250.0	246.3	242.4	238.6
70°	226.2	228.8	230.9	232.4	230.9	228.8	226.2	222.0	217.8	215.2	211.0
72.5°	198.9	200.3	205.3	203.1	205.3	200.3	198.9	193.9	190.6	188.4	183.8
75°	156.0	159.7	162.8	161.2	162.8	159.7	156.0	152.3	149.7	146.6	142.4
77.5°	115.4	119.0	120.5	119.2	120.5	119.0	115.4	113.0	111.6	105.4	105.0
80°	91.1	90.6	93.7	93.2	93.7	90.6	91.1	87.4	84.8	81.1	81.1
82.5°	66.8	66.3	67.7	68.1	67.7	66.3	66.8	64.8	61.4	59.8	58.5
85°	32.5	34.0	31.9	31.4	31.9	34.0	32.5	30.4	30.4	30.4	29.8
87.5°	11.8	11.8	11.5	11.1	11.5	11.8	11.8	11.7	13.3	11.9	11.8
90°	21.1	21.4	21.7	22.1	21.7	21.4	21.1	20.8	20.3	19.6	19.0
92.5°	23.8	24.0	24.2	24.4	24.2	24.0	23.8	23.6	23.0	22.0	20.9
95°	28.0	28.0	28.0	28.0	28.0	28.0	28.0	28.0	27.4	26.2	25.1
97.5°	29.8	30.0	30.2	30.3	30.2	30.0	29.8	29.7	28.9	27.6	26.3
100°	30.4	30.6	30.7	30.9	30.7	30.6	30.4	30.3	29.5	28.2	26.9
102.5°	30.6	30.9	31.2	31.5	31.2	30.9	30.6	30.3	32.2	36.3	40.3
105°	31.4	31.7	32.1	32.4	32.1	31.7	31.4	31.1	45.4	74.3	103.3
107.5°	167.1	145.3	123.5	101.7	123.5	145.3	167.1	189.0	210.5	231.7	252.9
110°	272.5	249.1	225.7	202.4	225.7	249.1	272.5	295.9	310.3	315.7	321.1



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	362.0	357.1	352.1	347.2	352.1	357.1	362.0	366.9	369.4	369.3	369.2
115°	430.7	431.4	432.0	432.7	432.0	431.4	430.7	430.1	428.9	427.3	425.7
117.5°	480.3	480.4	480.5	480.7	480.5	480.4	480.3	480.1	479.4	478.1	476.8
120°	513.6	513.6	513.6	513.6	513.6	513.6	513.6	513.6	513.0	511.7	510.4
122.5°	545.6	545.7	545.9	546.0	545.9	545.7	545.6	545.5	545.0	544.0	543.1
125°	590.7	591.0	591.3	591.6	591.3	591.0	590.7	590.3	590.0	589.7	589.3
127.5°	636.5	636.1	635.8	635.5	635.8	636.1	636.5	636.8	636.7	636.2	635.7
130°	664.7	664.4	664.1	663.7	664.1	664.4	664.7	665.1	664.9	664.2	663.6
132.5°	691.0	690.6	690.1	689.6	690.1	690.6	691.0	691.5	691.4	690.7	690.1
135°	730.7	730.2	729.7	729.2	729.7	730.2	730.7	731.2	731.2	730.7	730.2
137.5°	767.5	767.1	766.8	766.5	766.8	767.1	767.5	767.8	767.6	766.8	766.0
140°	789.8	789.5	789.2	788.8	789.2	789.5	789.8	790.2	790.0	789.3	788.7
142.5°	810.8	810.4	809.9	809.4	809.9	810.4	810.8	811.3	811.2	810.7	810.2
145°	841.1	841.1	841.1	841.1	841.1	841.1	841.1	841.1	840.9	840.6	840.3
147.5°	866.9	866.1	865.4	864.6	865.4	866.1	866.9	867.6	867.9	867.5	867.2
150°	883.8	883.3	882.8	882.3	882.8	883.3	883.8	884.3	884.3	884.0	883.7
152.5°	898.7	897.9	897.2	896.4	897.2	897.9	898.7	899.4	899.5	898.9	898.3
155°	919.1	918.1	917.1	916.1	917.1	918.1	919.1	920.1	920.2	919.3	918.5
157.5°	936.6	935.3	934.1	932.8	934.1	935.3	936.6	937.9	938.0	937.0	936.1
160°	946.8	945.7	944.5	943.4	944.5	945.7	946.8	948.0	948.0	947.1	946.1
162.5°	956.4	955.4	954.4	953.4	954.4	955.4	956.4	957.4	957.4	956.3	955.2
165°	968.9	967.7	966.6	965.4	966.6	967.7	968.9	970.0	969.9	968.6	967.3
167.5°	978.1	976.7	975.4	974.1	975.4	976.7	978.1	979.4	979.4	978.1	976.7
170°	983.4	982.0	980.7	979.4	980.7	982.0	983.4	984.7	984.7	983.4	982.0
172.5°	986.7	985.3	983.8	982.4	983.8	985.3	986.7	988.1	988.2	986.9	985.6
175°	990.7	989.4	988.1	986.8	988.1	989.4	990.7	992.0	992.1	991.0	989.8
177.5°	992.0	990.7	989.4	988.1	989.4	990.7	992.0	993.3	993.5	992.4	991.4
180°	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5
2.5°	1036.1	1036.1	1044.1	1049.1	1055.4	1059.6	1062.5	1065.5	1070.5	1077.2	1084.7
5°	976.9	979.0	990.5	1002.0	1013.0	1022.4	1030.3	1039.7	1051.2	1065.4	1081.1
7.5°	919.5	927.6	939.2	953.2	968.6	982.3	996.3	1011.8	1028.0	1048.8	1070.8
10°	882.7	891.6	905.7	923.5	939.7	955.9	973.2	990.0	1010.4	1035.0	1063.3
12.5°	850.4	858.9	873.4	892.9	908.3	926.2	946.0	967.8	990.7	1020.3	1052.4
15°	805.7	815.6	833.4	842.9	866.4	887.9	906.2	937.6	966.9	997.3	1034.5
17.5°	769.0	774.6	789.0	806.5	824.1	848.2	872.2	898.4	927.6	964.7	1011.2
20°	743.9	748.6	764.3	782.7	801.5	823.5	845.0	871.1	904.1	943.4	993.6
22.5°	725.1	730.2	740.5	760.0	777.6	795.9	817.3	848.5	883.6	922.0	976.5
25°	697.8	701.0	707.8	723.5	739.2	759.6	778.5	807.8	843.9	888.9	943.4
27.5°	672.0	675.0	680.7	692.0	706.6	723.2	743.7	768.6	805.3	854.2	912.0
30°	656.5	657.0	662.3	672.7	685.3	698.9	717.7	746.0	780.6	830.3	891.0
32.5°	643.1	641.1	644.7	652.6	664.8	678.4	693.9	721.7	755.0	803.9	866.3
35°	620.4	619.3	617.8	624.6	635.0	645.5	659.1	680.1	717.7	763.3	828.7
37.5°	597.2	594.7	591.9	595.0	603.2	614.1	625.9	644.6	677.0	727.2	789.8
40°	580.1	578.0	576.4	575.3	582.7	593.1	602.0	619.8	650.2	697.8	759.6
42.5°	561.2	560.0	558.0	556.5	562.6	570.5	579.8	595.6	625.9	670.6	729.1
45°	530.8	529.8	528.8	527.7	531.4	538.7	546.0	557.5	583.7	627.2	680.1
47.5°	497.0	495.7	496.1	494.4	498.0	502.9	508.0	520.4	545.5	580.6	619.2
50°	472.7	472.2	472.2	472.2	473.3	479.0	483.7	493.2	516.2	551.3	579.0
52.5°	449.7	447.5	447.5	448.3	450.2	453.9	456.9	467.2	487.3	516.1	541.3
55°	413.6	409.4	408.3	409.4	411.0	414.1	417.2	425.6	442.9	464.4	479.0
57.5°	373.6	371.3	369.9	370.1	371.0	373.5	375.9	385.0	398.6	409.8	419.2
60°	345.5	346.6	341.9	342.9	342.9	345.0	348.7	354.4	365.9	373.8	383.2
62.5°	319.1	317.7	316.3	314.8	314.8	315.7	320.6	325.1	334.9	339.0	346.4
65°	278.0	278.0	274.8	275.9	276.4	272.8	275.4	280.6	286.9	288.5	295.3
67.5°	236.3	234.9	233.1	231.5	231.5	231.2	232.5	235.2	239.9	240.4	245.6
70°	207.8	206.8	206.3	204.7	202.6	205.2	203.6	206.3	208.9	209.4	212.5
72.5°	180.2	179.1	178.2	176.6	175.8	175.5	175.6	178.6	180.4	179.7	183.2
75°	140.8	139.8	138.7	136.1	136.1	134.5	135.1	137.2	139.3	137.7	140.8
77.5°	103.4	100.2	100.0	100.7	98.9	99.3	98.6	98.3	99.3	99.4	102.2
80°	79.6	75.9	77.0	76.4	75.9	75.4	74.3	74.9	75.4	75.9	77.5
82.5°	57.4	57.1	56.0	55.9	55.4	54.0	53.4	54.3	54.9	54.6	55.7
85°	29.3	27.7	28.8	28.3	28.8	28.3	26.7	26.7	27.7	27.2	28.3
87.5°	12.5	12.3	11.5	11.5	10.6	10.6	9.8	9.9	10.0	9.7	10.2
90°	18.3	17.7	15.5	13.4	11.3	9.2	7.3	5.6	4.0	2.4	0.7
92.5°	19.9	18.8	17.2	15.6	14.0	12.4	11.9	12.3	12.8	13.2	13.7
95°	24.0	22.8	21.0	19.2	17.4	15.6	18.1	24.8	31.5	38.2	44.9
97.5°	25.0	23.7	35.5	47.2	59.0	70.8	78.2	81.2	84.2	87.2	90.2
100°	25.6	24.3	49.8	75.3	100.8	126.3	137.4	134.2	130.9	127.6	124.4
102.5°	44.4	48.4	76.3	104.1	132.0	159.9	172.6	170.3	167.9	165.6	163.2
105°	132.2	161.2	175.9	190.6	205.3	220.0	226.5	224.7	222.9	221.1	219.3
107.5°	274.1	295.4	293.1	290.7	288.4	286.1	284.2	282.8	281.3	279.9	278.4
110°	326.5	331.9	330.1	328.3	326.5	324.7	323.1	321.8	320.5	319.2	317.9



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	369.1	369.0	367.2	365.4	363.6	361.8	360.3	359.1	357.9	356.7	355.6
115°	424.0	422.4	420.9	419.4	418.0	416.5	415.3	414.3	413.3	412.3	411.3
117.5°	475.5	474.2	473.4	472.7	471.9	471.2	470.2	469.0	467.8	466.6	465.4
120°	509.1	507.7	507.3	506.8	506.3	505.8	504.8	503.3	501.9	500.4	498.9
122.5°	542.2	541.3	540.7	540.1	539.4	538.8	537.9	536.7	535.5	534.3	533.1
125°	589.0	588.7	588.0	587.4	586.7	586.1	585.1	583.8	582.5	581.2	579.9
127.5°	635.1	634.6	633.8	633.0	632.3	631.5	630.4	629.1	627.8	626.5	625.2
130°	662.9	662.3	661.6	661.0	660.3	659.7	658.7	657.4	656.1	654.8	653.4
132.5°	689.4	688.8	688.2	687.7	687.2	686.7	685.8	684.4	683.1	681.8	680.5
135°	729.7	729.2	728.6	727.9	727.3	726.6	725.8	724.8	723.8	722.9	721.9
137.5°	765.2	764.4	764.1	763.7	763.3	763.0	762.2	760.9	759.7	758.4	757.2
140°	788.0	787.4	786.9	786.4	785.9	785.4	784.7	783.7	782.7	781.7	780.7
142.5°	809.7	809.2	808.7	808.2	807.7	807.2	806.5	805.5	804.5	803.5	802.5
145°	839.9	839.6	839.3	839.0	838.6	838.3	837.6	836.4	835.3	834.1	833.0
147.5°	866.9	866.5	866.2	865.9	865.6	865.2	864.7	863.9	863.2	862.4	861.7
150°	883.4	883.0	882.7	882.4	882.1	881.7	881.3	880.8	880.3	879.8	879.4
152.5°	897.7	897.2	897.0	896.8	896.6	896.4	896.2	895.9	895.7	895.5	895.2
155°	917.7	916.9	916.7	916.6	916.4	916.2	916.3	916.6	917.0	917.3	917.6
157.5°	935.1	934.1	934.3	934.4	934.6	934.8	934.9	934.9	934.9	935.0	935.0
160°	945.1	944.1	944.3	944.4	944.6	944.8	944.9	945.1	945.3	945.4	945.6
162.5°	954.1	952.9	953.1	953.3	953.4	953.6	953.9	954.3	954.7	955.2	955.6
165°	966.0	964.7	964.9	965.0	965.2	965.4	965.7	966.2	966.7	967.2	967.7
167.5°	975.4	974.1	974.1	974.1	974.1	974.1	974.5	975.1	975.8	976.4	977.1
170°	980.7	979.4	979.4	979.4	979.4	979.4	979.8	980.4	981.1	981.7	982.4
172.5°	984.3	983.0	982.8	982.7	982.6	982.4	982.8	983.6	984.3	985.1	985.9
175°	988.7	987.5	987.4	987.2	987.0	986.9	987.2	988.0	988.8	989.6	990.5
177.5°	990.3	989.3	989.2	989.0	988.9	988.8	989.0	989.7	990.3	991.0	991.6
180°	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5
2.5°	1087.2	1089.3	1096.5	1101.5	1107.3	1110.7	1114.0	1116.6	1119.9	1120.7	1132.9
5°	1092.1	1102.5	1120.9	1134.5	1151.2	1169.5	1182.1	1187.9	1203.0	1215.6	1240.7
7.5°	1090.7	1113.0	1140.6	1169.3	1200.1	1228.6	1253.3	1282.6	1303.5	1334.8	1365.6
10°	1089.4	1119.3	1154.9	1191.5	1234.5	1274.2	1309.8	1349.6	1382.6	1426.1	1463.2
12.5°	1085.7	1121.8	1171.2	1214.6	1266.7	1321.6	1374.3	1425.4	1454.6	1527.0	1561.2
15°	1076.4	1119.3	1181.1	1247.0	1318.7	1383.7	1450.7	1504.1	1590.4	1653.8	1694.1
17.5°	1058.6	1118.7	1191.9	1271.5	1358.7	1444.3	1520.2	1601.2	1692.8	1769.5	1851.2
20°	1050.2	1116.1	1197.8	1285.8	1376.3	1473.2	1559.6	1656.9	1756.9	1832.3	1937.0
22.5°	1034.7	1109.4	1197.4	1295.4	1392.2	1492.4	1593.5	1691.7	1807.2	1911.1	2010.7
25°	1009.3	1093.1	1184.2	1293.6	1407.2	1507.7	1628.7	1759.0	1879.4	2012.9	2112.4
27.5°	982.7	1072.2	1163.5	1265.2	1387.4	1506.7	1658.8	1806.1	1953.4	2068.6	2142.2
30°	962.2	1049.1	1143.4	1246.0	1366.9	1508.8	1678.9	1839.6	1983.1	2082.0	2123.4
32.5°	940.0	1028.2	1111.5	1219.2	1348.1	1507.5	1691.5	1859.3	1984.8	2050.6	2042.6
35°	905.2	979.0	1060.1	1163.8	1315.6	1498.3	1698.8	1861.1	1938.1	1923.9	1817.1
37.5°	854.9	917.0	996.9	1110.4	1277.9	1478.9	1684.2	1805.9	1800.9	1685.8	1531.1
40°	823.5	876.4	953.3	1072.7	1248.6	1466.4	1661.1	1740.2	1673.2	1512.4	1327.1
42.5°	782.5	831.1	908.1	1030.8	1216.3	1440.8	1617.1	1640.1	1509.0	1324.0	1154.1
45°	718.8	761.7	841.3	968.0	1168.0	1385.2	1509.8	1453.8	1277.4	1086.3	957.0
47.5°	650.4	695.0	771.6	901.7	1098.0	1301.6	1360.9	1241.8	1060.6	905.7	787.0
50°	607.3	650.2	725.1	856.5	1050.7	1232.9	1257.5	1103.6	937.1	801.0	703.6
52.5°	563.7	604.1	677.7	809.6	995.4	1153.3	1138.1	981.3	828.2	712.2	635.8
55°	498.9	537.1	607.3	730.8	899.9	1025.0	970.1	820.4	693.7	603.6	545.5
57.5°	440.9	477.6	538.1	649.7	796.7	882.7	812.7	686.5	585.8	516.5	473.2
60°	401.5	434.0	491.6	595.2	723.0	788.4	719.3	607.8	523.0	467.5	428.8
62.5°	364.3	392.5	445.9	540.0	650.9	705.9	636.0	541.6	469.4	420.2	387.3
65°	307.8	333.5	380.6	453.9	545.0	581.6	521.4	445.0	389.0	352.3	330.3
67.5°	256.3	278.1	318.8	376.5	443.5	470.2	424.4	365.2	323.0	293.6	276.1
70°	222.0	240.8	272.8	322.5	383.2	403.6	360.7	312.0	281.1	257.6	241.3
72.5°	193.1	206.9	235.9	274.3	325.0	341.2	311.3	268.5	239.7	222.0	209.1
75°	147.1	158.6	177.5	208.4	243.4	252.9	230.3	203.6	184.3	171.7	161.8
77.5°	106.1	114.5	128.2	147.2	171.5	180.0	165.7	147.9	133.8	125.3	119.8
80°	80.1	86.9	98.4	114.1	128.8	133.5	125.1	111.5	101.6	96.9	92.1
82.5°	59.2	63.0	69.9	80.6	90.7	96.2	89.1	80.9	75.6	71.3	69.5
85°	29.8	31.9	35.1	39.3	45.5	47.6	45.0	42.9	39.8	37.2	37.2
87.5°	11.4	11.7	13.3	14.4	16.5	18.2	18.2	17.8	17.8	17.5	17.2
90°	2.4	4.0	5.6	7.3	9.2	11.3	13.4	15.5	17.7	18.3	19.0
92.5°	13.2	12.8	12.3	11.9	12.4	14.0	15.6	17.2	18.8	19.9	20.9
95°	38.2	31.5	24.8	18.1	15.6	17.4	19.2	21.0	22.8	24.0	25.1
97.5°	87.2	84.2	81.2	78.2	70.8	59.0	47.2	35.5	23.7	25.0	26.3
100°	127.6	130.9	134.2	137.4	126.3	100.8	75.3	49.8	24.3	25.6	26.9
102.5°	165.6	167.9	170.3	172.6	159.9	132.0	104.1	76.3	48.4	44.4	40.3
105°	221.1	222.9	224.7	226.5	220.0	205.3	190.6	175.9	161.2	132.2	103.3
107.5°	279.9	281.3	282.8	284.2	286.1	288.4	290.7	293.1	295.4	274.1	252.9
110°	319.2	320.5	321.8	323.1	324.7	326.5	328.3	330.1	331.9	326.5	321.1



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	356.7	357.9	359.1	360.3	361.8	363.6	365.4	367.2	369.0	369.1	369.2
115°	412.3	413.3	414.3	415.3	416.5	418.0	419.4	420.9	422.4	424.0	425.7
117.5°	466.6	467.8	469.0	470.2	471.2	471.9	472.7	473.4	474.2	475.5	476.8
120°	500.4	501.9	503.3	504.8	505.8	506.3	506.8	507.3	507.7	509.1	510.4
122.5°	534.3	535.5	536.7	537.9	538.8	539.4	540.1	540.7	541.3	542.2	543.1
125°	581.2	582.5	583.8	585.1	586.1	586.7	587.4	588.0	588.7	589.0	589.3
127.5°	626.5	627.8	629.1	630.4	631.5	632.3	633.0	633.8	634.6	635.1	635.7
130°	654.8	656.1	657.4	658.7	659.7	660.3	661.0	661.6	662.3	662.9	663.6
132.5°	681.8	683.1	684.4	685.8	686.7	687.2	687.7	688.2	688.8	689.4	690.1
135°	722.9	723.8	724.8	725.8	726.6	727.3	727.9	728.6	729.2	729.7	730.2
137.5°	758.4	759.7	760.9	762.2	763.0	763.3	763.7	764.1	764.4	765.2	766.0
140°	781.7	782.7	783.7	784.7	785.4	785.9	786.4	786.9	787.4	788.0	788.7
142.5°	803.5	804.5	805.5	806.5	807.2	807.7	808.2	808.7	809.2	809.7	810.2
145°	834.1	835.3	836.4	837.6	838.3	838.6	839.0	839.3	839.6	839.9	840.3
147.5°	862.4	863.2	863.9	864.7	865.2	865.6	865.9	866.2	866.5	866.9	867.2
150°	879.8	880.3	880.8	881.3	881.7	882.1	882.4	882.7	883.0	883.4	883.7
152.5°	895.5	895.7	895.9	896.2	896.4	896.6	896.8	897.0	897.2	897.7	898.3
155°	917.3	917.0	916.6	916.3	916.2	916.4	916.6	916.7	916.9	917.7	918.5
157.5°	935.0	934.9	934.9	934.9	934.8	934.6	934.4	934.3	934.1	935.1	936.1
160°	945.4	945.3	945.1	944.9	944.8	944.6	944.4	944.3	944.1	945.1	946.1
162.5°	955.2	954.7	954.3	953.9	953.6	953.4	953.3	953.1	952.9	954.1	955.2
165°	967.2	966.7	966.2	965.7	965.4	965.2	965.0	964.9	964.7	966.0	967.3
167.5°	976.4	975.8	975.1	974.5	974.1	974.1	974.1	974.1	974.1	975.4	976.7
170°	981.7	981.1	980.4	979.8	979.4	979.4	979.4	979.4	979.4	980.7	982.0
172.5°	985.1	984.3	983.6	982.8	982.4	982.6	982.7	982.8	983.0	984.3	985.6
175°	989.6	988.8	988.0	987.2	986.9	987.0	987.2	987.4	987.5	988.7	989.8
177.5°	991.0	990.3	989.7	989.0	988.8	988.9	989.0	989.2	989.3	990.3	991.4
180°	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5	990.5



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5	1080.5
2.5°	1137.1	1137.5	1142.1	1145.5	1143.8	1145.9	1146.7
5°	1242.3	1261.2	1271.1	1278.4	1279.0	1279.5	1283.7
7.5°	1391.5	1411.7	1426.5	1448.9	1455.6	1463.2	1461.0
10°	1500.4	1530.2	1555.9	1569.5	1584.2	1605.6	1588.4
12.5°	1602.2	1655.1	1694.1	1715.3	1729.1	1733.4	1724.9
15°	1770.0	1839.1	1876.3	1875.2	1922.4	1942.8	1910.8
17.5°	1923.9	1987.7	2038.8	2065.0	2104.2	2112.9	2108.9
20°	2018.2	2087.8	2127.6	2172.6	2193.0	2211.3	2214.5
22.5°	2099.4	2161.9	2204.6	2242.1	2259.2	2267.9	2273.1
25°	2183.1	2232.3	2257.9	2271.0	2275.7	2274.7	2267.9
27.5°	2177.3	2181.1	2152.8	2125.1	2100.3	2072.3	2062.7
30°	2120.8	2076.8	1998.3	1953.8	1888.3	1836.5	1857.4
32.5°	1972.1	1884.6	1796.4	1699.1	1618.6	1595.7	1572.6
35°	1683.1	1529.2	1439.2	1334.4	1292.6	1250.7	1221.9
37.5°	1361.7	1242.6	1135.8	1067.3	1025.4	998.9	984.6
40°	1177.4	1070.1	982.1	926.6	894.7	864.9	860.7
42.5°	1030.4	930.6	864.4	820.2	789.6	776.9	767.7
45°	843.9	774.3	729.8	698.4	678.0	670.1	659.6
47.5°	714.3	665.1	631.7	610.3	594.9	589.1	588.2
50°	641.8	601.0	576.4	559.6	547.6	545.5	537.1
52.5°	587.4	552.0	532.8	518.2	509.5	503.6	501.1
55°	509.9	486.3	469.1	460.7	453.9	448.1	448.1
57.5°	446.1	426.5	415.0	407.9	405.8	401.7	399.1
60°	406.8	390.0	381.1	374.8	370.7	371.2	366.5
62.5°	368.2	357.4	348.9	342.6	337.6	337.7	338.0
65°	313.6	305.2	298.9	296.8	293.7	290.0	291.1
67.5°	265.7	257.9	253.0	249.4	248.4	246.4	249.4
70°	231.4	225.6	222.0	218.8	217.8	218.3	220.9
72.5°	200.0	195.9	193.5	192.0	189.7	189.8	191.6
75°	157.1	153.9	151.8	150.2	149.7	149.7	149.7
77.5°	115.4	114.7	113.7	111.4	111.5	112.1	112.2
80°	91.1	89.5	89.0	88.0	86.4	85.3	88.0
82.5°	68.1	66.5	66.0	65.8	63.3	63.1	65.3
85°	36.6	35.1	35.6	35.1	35.1	34.6	34.6
87.5°	16.9	16.6	16.3	16.8	16.4	16.1	17.0
90°	19.6	20.3	20.8	21.1	21.4	21.7	22.1
92.5°	22.0	23.0	23.6	23.8	24.0	24.2	24.4
95°	26.2	27.4	28.0	28.0	28.0	28.0	28.0
97.5°	27.6	28.9	29.7	29.8	30.0	30.2	30.3
100°	28.2	29.5	30.3	30.4	30.6	30.7	30.9
102.5°	36.3	32.2	30.3	30.6	30.9	31.2	31.5
105°	74.3	45.4	31.1	31.4	31.7	32.1	32.4
107.5°	231.7	210.5	189.0	167.1	145.3	123.5	101.7
110°	315.7	310.3	295.9	272.5	249.1	225.7	202.4



TEST NUMBER: P332156

CATALOG NUMBER: S123DIW-S775D755U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	369.3	369.4	366.9	362.0	357.1	352.1	347.2
115°	427.3	428.9	430.1	430.7	431.4	432.0	432.7
117.5°	478.1	479.4	480.1	480.3	480.4	480.5	480.7
120°	511.7	513.0	513.6	513.6	513.6	513.6	513.6
122.5°	544.0	545.0	545.5	545.6	545.7	545.9	546.0
125°	589.7	590.0	590.3	590.7	591.0	591.3	591.6
127.5°	636.2	636.7	636.8	636.5	636.1	635.8	635.5
130°	664.2	664.9	665.1	664.7	664.4	664.1	663.7
132.5°	690.7	691.4	691.5	691.0	690.6	690.1	689.6
135°	730.7	731.2	731.2	730.7	730.2	729.7	729.2
137.5°	766.8	767.6	767.8	767.5	767.1	766.8	766.5
140°	789.3	790.0	790.2	789.8	789.5	789.2	788.8
142.5°	810.7	811.2	811.3	810.8	810.4	809.9	809.4
145°	840.6	840.9	841.1	841.1	841.1	841.1	841.1
147.5°	867.5	867.9	867.6	866.9	866.1	865.4	864.6
150°	884.0	884.3	884.3	883.8	883.3	882.8	882.3
152.5°	898.9	899.5	899.4	898.7	897.9	897.2	896.4
155°	919.3	920.2	920.1	919.1	918.1	917.1	916.1
157.5°	937.0	938.0	937.9	936.6	935.3	934.1	932.8
160°	947.1	948.0	948.0	946.8	945.7	944.5	943.4
162.5°	956.3	957.4	957.4	956.4	955.4	954.4	953.4
165°	968.6	969.9	970.0	968.9	967.7	966.6	965.4
167.5°	978.1	979.4	979.4	978.1	976.7	975.4	974.1
170°	983.4	984.7	984.7	983.4	982.0	980.7	979.4
172.5°	986.9	988.2	988.1	986.7	985.3	983.8	982.4
175°	991.0	992.1	992.0	990.7	989.4	988.1	986.8
177.5°	992.4	993.5	993.3	992.0	990.7	989.4	988.1
180°	990.5	990.5	990.5	990.5	990.5	990.5	990.5

(END OF REPORT)