

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P332398

Luminaire Tested: **S123RDIW-S340D1030U835-4F0-1E-UDD-A**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P332398
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-5,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S123RDIW-S340D1030U835-4F0-1E-UDD-A
Description: DEFINE 3 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 340 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING
UPLIGHT 1030 LUMENS PER FOOT, NO LENS
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5481.6 lumens
Efficiency: N/A
Efficacy: 144.3 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.22 / 1.36
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')
CIE Type: Semi-Indirect


Input Watts (W): 38
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

Luminous Intensity Polar Plot





TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	101	101	101	101	90	90	90	90	69	69	69	50	50	50	33	33	33	25				25
1	92	88	85	81	82	79	76	73	61	59	57	45	43	42	30	29	28	21				21
2	84	77	72	67	75	69	64	60	54	51	48	39	37	36	26	25	24	18				18
3	77	68	61	56	68	61	55	51	48	44	40	35	33	31	24	22	21	16				16
4	71	60	53	47	63	54	48	43	42	38	35	31	29	26	21	20	18	14				14
5	65	54	46	41	57	48	42	37	38	33	30	28	25	23	19	17	16	12				12
6	60	48	41	35	53	43	37	32	34	29	26	26	22	20	17	16	14	11				11
7	55	43	36	31	49	39	33	28	31	26	23	23	20	18	16	14	13	10				10
8	51	39	32	27	45	35	29	25	28	23	20	21	18	16	15	13	11	9				9
9	47	36	29	24	42	32	26	22	26	21	18	19	16	14	14	12	10	8				8
10	44	33	26	21	39	30	24	20	24	19	16	18	15	13	13	11	9	7				7

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	5858	5858	5858	5858
5°	6983	5883	5181	5883
10°	8719	5850	4680	5850
15°	10234	5789	4268	5789
20°	11423	5700	3918	5700
25°	11240	5606	3702	5606
30°	8079	5520	3480	5520
35°	5394	5406	3336	5406
40°	3974	5271	3188	5271
45°	3334	5033	3043	5033
50°	2942	4721	2840	4721
55°	2580	4363	2562	4363
60°	2297	4021	2347	4021
65°	2017	3655	2183	3655
70°	1583	3330	1995	3330
75°	1393	2907	1822	2907
80°	1215	2467	1791	2467
85°	976	1988	1902	1988



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	53.5	1.0
10°-20°	167.2	3.1
20°-30°	262.7	4.8
30°-40°	274.1	5.0
40°-50°	234.5	4.3
50°-60°	178.8	3.3
60°-70°	114.6	2.1
70°-80°	55.1	1.0
80°-90°	18.4	0.3
90°-100°	49.2	0.9
100°-110°	234.3	4.3
110°-120°	562.7	10.3
120°-130°	716.5	13.1
130°-140°	765.6	14.0
140°-150°	715.9	13.1
150°-160°	577.5	10.5
160°-170°	372.7	6.8
170°-180°	128.4	2.3
0°-30°	483.4	8.8
0°-40°	757.5	13.8
0°-60°	1170.8	21.4
0°-90°	1358.8	24.8
90°-120°	846.1	15.4
90°-150°	3044.1	55.5
90°-180°	4123.0	75.2
0°-180°	5481.6	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	544	544	544	544	544	
5°	646	544	480	544	646	67
15°	918	520	383	520	918	260
25°	946	472	312	472	946	407
35°	410	411	254	411	410	269
45°	219	331	200	331	219	172
55°	138	232	136	232	138	124
65°	79	144	86	144	79	78
75°	34	70	44	70	34	36
85°	8	16	15	16	8	10
90°	30	1	30	1	30	14
95°	38	61	38	61	38	32
105°	44	299	44	299	44	101
115°	591	562	591	562	591	546
125°	808	792	808	792	808	721
135°	995	985	995	985	995	767
145°	1148	1137	1148	1137	1148	717
155°	1250	1252	1250	1252	1250	577
165°	1318	1321	1318	1321	1318	372
175°	1347	1352	1347	1352	1347	128
180°	1352	1352	1352	1352	1352	



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2
2.5°	579.7	580.4	578.0	577.6	574.8	574.1	574.1	570.1	567.7	564.6	562.7
5°	646.3	650.0	648.1	644.0	637.0	635.3	630.9	623.9	616.0	606.2	601.6
7.5°	729.5	734.6	732.6	726.2	718.8	712.9	700.4	688.8	672.6	658.3	646.1
10°	797.7	792.4	788.2	781.9	775.1	764.2	751.1	733.2	712.5	696.1	678.0
12.5°	848.8	847.9	842.6	836.1	826.6	816.2	800.1	778.3	754.2	730.6	709.8
15°	918.4	919.8	916.3	909.6	896.0	877.6	853.4	844.3	809.8	784.2	758.6
17.5°	966.6	966.3	965.8	956.5	942.7	929.6	907.1	883.2	852.0	815.9	781.4
20°	997.2	994.8	995.3	984.8	974.6	959.4	937.5	902.8	877.2	835.5	799.8
22.5°	996.4	995.9	997.7	994.1	986.7	975.1	957.8	928.5	895.8	853.7	813.6
25°	946.4	944.5	955.4	958.5	970.4	972.5	967.3	951.3	920.3	876.9	827.3
27.5°	792.0	791.0	811.3	836.8	869.0	894.1	918.3	930.0	920.3	889.2	839.5
30°	650.0	671.9	682.2	719.0	760.0	808.9	851.8	892.5	902.6	889.0	848.3
32.5°	539.7	558.8	567.4	598.9	637.2	694.5	758.8	816.5	857.3	867.6	843.1
35°	410.5	410.7	430.3	444.3	479.7	538.6	601.1	678.4	755.3	813.6	819.6
37.5°	327.6	328.7	340.6	354.5	381.1	412.2	467.2	531.5	620.3	709.7	762.2
40°	282.8	284.9	293.8	307.5	326.6	350.2	393.0	453.6	527.7	627.2	708.5
42.5°	254.1	257.5	262.1	272.7	284.5	306.6	341.2	388.0	455.4	549.5	643.3
45°	219.0	220.9	224.4	229.3	240.0	255.3	278.6	310.1	366.0	441.7	535.6
47.5°	193.2	192.2	195.9	199.8	207.0	217.5	233.1	258.7	298.6	359.4	439.0
50°	175.7	175.4	178.0	181.0	187.8	195.5	208.3	227.6	259.3	309.6	382.6
52.5°	159.3	160.1	162.0	165.7	170.6	176.8	188.3	202.3	229.5	272.9	333.7
55°	137.5	138.2	140.7	142.8	146.3	152.6	159.8	171.5	190.1	220.4	270.5
57.5°	119.0	118.7	121.1	121.7	125.6	130.7	136.3	145.4	158.9	181.4	215.1
60°	106.7	106.0	108.1	109.7	111.8	116.0	120.7	129.5	140.3	156.8	185.7
62.5°	95.5	95.2	96.7	98.4	100.1	103.9	107.8	114.6	123.1	137.0	160.0
65°	79.2	79.9	80.6	81.3	82.2	84.6	88.3	93.0	98.8	108.6	125.1
67.5°	62.3	63.0	63.2	64.6	66.6	68.1	70.4	74.5	78.6	86.8	96.2
70°	50.3	50.1	50.3	51.0	53.6	56.1	59.2	62.2	64.8	70.6	78.5
72.5°	43.2	42.8	43.4	43.6	44.8	45.5	47.4	50.3	53.6	57.5	63.2
75°	33.5	33.5	33.5	33.5	34.5	34.9	35.6	36.3	37.5	39.4	43.6
77.5°	24.8	24.8	25.2	25.4	25.6	25.9	26.3	27.0	27.4	28.4	30.2
80°	19.6	19.8	19.6	19.8	19.8	20.3	20.5	21.2	21.4	22.6	23.3
82.5°	14.7	14.6	14.7	15.0	15.0	15.4	15.5	16.0	16.0	16.6	17.3
85°	7.9	7.5	7.9	7.7	8.2	7.7	7.9	8.4	8.4	8.6	9.6
87.5°	7.9	8.2	7.7	7.8	7.7	7.8	7.6	7.4	7.6	7.2	6.9
90°	30.1	29.7	29.2	28.8	28.3	27.7	26.8	25.9	25.0	24.1	21.2
92.5°	33.3	33.1	32.8	32.5	32.3	31.4	30.0	28.6	27.1	25.7	23.5
95°	38.2	38.2	38.2	38.2	38.2	37.4	35.8	34.3	32.7	31.1	28.7
97.5°	41.4	41.2	40.9	40.7	40.5	39.5	37.7	35.9	34.1	32.3	28.4
100°	42.2	42.0	41.7	41.5	41.3	40.3	38.5	36.7	34.9	33.1	28.0
102.5°	43.0	42.6	42.2	41.8	41.4	43.9	49.5	55.0	60.6	66.1	104.1
105°	44.2	43.7	43.3	42.9	42.4	61.9	101.4	141.0	180.5	220.0	240.1
107.5°	138.8	168.6	198.4	228.1	257.9	287.3	316.3	345.2	374.2	403.2	400.0
110°	276.2	308.1	340.0	372.0	403.9	423.5	430.9	438.3	445.6	453.0	450.5



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	473.9	480.6	487.4	494.1	500.8	504.1	504.0	503.9	503.7	503.6	501.2
115°	590.6	589.7	588.8	587.9	587.0	585.5	583.2	581.0	578.8	576.5	574.5
117.5°	656.1	655.9	655.7	655.5	655.4	654.4	652.6	650.8	649.0	647.2	646.2
120°	701.1	701.1	701.1	701.1	701.1	700.2	698.4	696.6	694.8	693.0	692.4
122.5°	745.3	745.1	744.9	744.7	744.6	743.8	742.6	741.3	740.1	738.8	738.0
125°	807.5	807.1	806.6	806.2	805.8	805.3	804.9	804.4	804.0	803.5	802.6
127.5°	867.4	867.9	868.3	868.7	869.2	869.1	868.3	867.6	866.9	866.2	865.1
130°	906.0	906.4	906.9	907.3	907.8	907.5	906.6	905.8	904.9	904.0	903.1
132.5°	941.3	942.0	942.6	943.2	943.8	943.7	942.8	941.9	941.0	940.1	939.4
135°	995.4	996.0	996.7	997.4	998.0	998.0	997.4	996.7	996.0	995.4	994.5
137.5°	1046.2	1046.6	1047.1	1047.5	1048.0	1047.7	1046.6	1045.5	1044.4	1043.4	1042.9
140°	1076.7	1077.2	1077.6	1078.1	1078.5	1078.3	1077.4	1076.5	1075.6	1074.7	1074.0
142.5°	1104.8	1105.5	1106.1	1106.7	1107.3	1107.3	1106.6	1105.9	1105.2	1104.4	1103.8
145°	1148.0	1148.0	1148.0	1148.0	1148.0	1147.8	1147.4	1146.9	1146.5	1146.0	1145.6
147.5°	1180.2	1181.2	1182.2	1183.3	1184.3	1184.6	1184.1	1183.7	1183.2	1182.8	1182.3
150°	1204.3	1205.0	1205.6	1206.3	1207.0	1207.1	1206.6	1206.2	1205.7	1205.3	1204.8
152.5°	1223.6	1224.6	1225.6	1226.6	1227.7	1227.8	1227.0	1226.2	1225.4	1224.6	1224.3
155°	1250.5	1251.8	1253.2	1254.5	1255.8	1256.0	1254.8	1253.7	1252.6	1251.5	1251.3
157.5°	1273.2	1274.9	1276.7	1278.4	1280.1	1280.3	1279.0	1277.7	1276.3	1275.0	1275.2
160°	1287.6	1289.2	1290.8	1292.3	1293.9	1294.0	1292.7	1291.3	1290.0	1288.7	1288.9
162.5°	1301.3	1302.7	1304.1	1305.5	1306.8	1306.8	1305.3	1303.7	1302.2	1300.7	1300.9
165°	1317.8	1319.3	1320.9	1322.5	1324.0	1323.9	1322.1	1320.3	1318.6	1316.8	1317.0
167.5°	1329.6	1331.4	1333.2	1335.0	1336.8	1336.8	1335.0	1333.2	1331.4	1329.6	1329.6
170°	1336.9	1338.6	1340.4	1342.2	1344.0	1344.0	1342.2	1340.4	1338.6	1336.9	1336.9
172.5°	1340.9	1342.8	1344.8	1346.8	1348.7	1348.8	1347.0	1345.3	1343.5	1341.7	1341.5
175°	1346.9	1348.7	1350.5	1352.3	1354.1	1354.2	1352.6	1351.0	1349.5	1347.9	1347.7
177.5°	1348.7	1350.5	1352.3	1354.1	1355.9	1356.0	1354.6	1353.2	1351.8	1350.3	1350.1
180°	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2
2.5°	561.9	561.4	558.8	555.8	551.9	549.3	547.2	546.1	542.7	538.6	535.9
5°	596.7	589.7	582.2	573.1	564.7	556.1	550.8	544.5	536.8	528.2	522.1
7.5°	633.8	620.1	605.4	590.1	575.1	561.6	549.6	539.4	527.2	514.8	506.2
10°	662.4	642.3	621.6	600.4	581.1	562.9	548.9	535.2	520.5	506.3	495.5
12.5°	688.3	661.9	638.0	611.9	587.2	565.5	545.4	529.2	511.5	496.4	484.2
15°	721.1	694.0	665.2	625.5	592.7	565.2	540.7	519.5	498.1	479.5	467.6
17.5°	751.7	711.1	672.2	639.2	596.5	562.2	532.3	507.0	483.4	463.7	449.0
20°	764.4	725.0	682.9	640.7	598.8	560.3	525.6	497.6	473.2	450.8	437.3
22.5°	772.0	727.5	683.0	637.7	593.2	553.2	518.9	488.1	461.6	440.4	423.7
25°	780.9	727.8	678.9	634.2	588.7	545.4	504.6	472.0	443.4	420.8	403.1
27.5°	786.8	724.3	666.5	616.8	570.7	527.6	490.2	455.6	426.5	402.6	383.6
30°	787.9	721.5	657.0	603.2	556.4	516.7	477.1	444.1	413.3	387.9	370.2
32.5°	789.4	714.6	644.1	587.0	539.0	499.8	463.9	432.3	400.8	375.8	357.7
35°	783.3	710.8	624.6	558.9	510.9	472.9	440.6	411.4	380.5	356.2	337.8
37.5°	756.8	695.7	604.4	527.3	477.1	442.0	415.6	390.2	361.8	335.6	318.3
40°	730.2	680.8	588.7	508.1	455.7	419.6	395.8	375.1	347.6	323.1	304.5
42.5°	690.5	660.4	573.8	488.0	431.5	396.7	376.6	357.2	333.1	308.2	290.7
45°	617.6	621.6	543.3	455.9	397.9	363.0	344.1	330.6	309.2	288.7	270.7
47.5°	526.3	563.3	507.5	421.8	362.6	329.8	313.3	301.5	287.0	266.9	250.5
50°	466.7	519.5	478.8	398.9	340.4	307.8	291.5	281.9	269.3	253.5	237.9
52.5°	411.7	468.5	444.1	373.3	316.3	286.5	270.6	262.7	252.7	237.8	223.7
55°	335.7	393.3	387.7	334.8	280.3	253.5	241.4	232.5	225.8	214.6	203.4
57.5°	271.6	326.1	329.0	291.9	248.5	222.0	211.6	204.9	200.5	192.1	181.7
60°	231.1	281.2	291.0	263.0	225.8	202.5	192.2	186.8	183.4	176.6	168.7
62.5°	197.6	240.2	251.3	231.2	204.0	182.1	174.1	169.0	166.6	160.8	153.8
65°	151.2	186.6	197.3	186.2	171.9	154.5	147.9	143.5	141.4	138.2	133.0
67.5°	113.7	139.5	151.3	143.4	138.2	127.2	123.1	120.7	118.8	116.6	112.3
70°	91.3	110.4	122.5	120.5	116.3	110.4	107.4	105.8	103.9	102.0	98.3
72.5°	73.4	86.6	97.9	99.0	95.6	94.4	91.7	91.0	89.9	87.7	85.6
75°	48.7	57.8	65.7	68.7	70.1	71.3	70.1	69.9	69.7	67.8	66.6
77.5°	31.9	36.8	41.8	47.0	49.2	50.7	51.1	52.0	51.3	50.4	49.8
80°	24.5	25.6	29.1	33.5	37.0	38.4	39.4	39.8	39.6	39.4	38.4
82.5°	17.8	18.7	20.4	23.5	26.4	28.7	29.3	29.2	29.7	29.9	29.1
85°	9.6	9.8	10.3	10.7	12.3	14.9	15.6	16.1	16.5	16.5	15.1
87.5°	6.6	5.9	5.7	5.2	5.3	5.0	5.7	6.2	6.8	6.5	6.9
90°	18.3	15.4	12.5	9.9	7.7	5.5	3.2	1.0	3.2	5.5	7.7
92.5°	21.3	19.2	17.0	16.2	16.8	17.4	18.1	18.7	18.1	17.4	16.8
95°	26.2	23.8	21.3	24.7	33.8	43.0	52.1	61.3	52.1	43.0	33.8
97.5°	64.5	80.6	96.6	106.7	110.8	114.9	119.0	123.1	119.0	114.9	110.8
100°	102.8	137.6	172.4	187.6	183.1	178.7	174.2	169.7	174.2	178.7	183.1
102.5°	142.2	180.2	218.2	235.6	232.4	229.2	226.0	222.8	226.0	229.2	232.4
105°	260.1	280.2	300.3	309.1	306.7	304.2	301.8	299.3	301.8	304.2	306.7
107.5°	396.8	393.7	390.5	387.9	386.0	384.0	382.0	380.1	382.0	384.0	386.0
110°	448.1	445.6	443.2	441.0	439.3	437.5	435.7	433.9	435.7	437.5	439.3



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	498.7	496.2	493.8	491.8	490.2	488.5	486.9	485.3	486.9	488.5	490.2
115°	572.5	570.5	568.5	566.8	565.5	564.1	562.8	561.5	562.8	564.1	565.5
117.5°	645.2	644.2	643.1	641.8	640.1	638.5	636.8	635.2	636.8	638.5	640.1
120°	691.7	691.0	690.4	689.0	687.0	685.0	683.0	681.0	683.0	685.0	687.0
122.5°	737.1	736.3	735.4	734.2	732.5	730.9	729.2	727.6	729.2	730.9	732.5
125°	801.7	800.8	800.0	798.6	796.8	795.0	793.3	791.5	793.3	795.0	796.8
127.5°	864.1	863.0	861.9	860.5	858.7	856.9	855.1	853.3	855.1	856.9	858.7
130°	902.2	901.3	900.4	899.1	897.3	895.5	893.7	891.9	893.7	895.5	897.3
132.5°	938.7	938.0	937.3	936.0	934.2	932.4	930.7	928.9	930.7	932.4	934.2
135°	993.6	992.7	991.8	990.7	989.3	988.0	986.7	985.3	986.7	988.0	989.3
137.5°	1042.4	1041.9	1041.4	1040.3	1038.6	1036.9	1035.2	1033.5	1035.2	1036.9	1038.6
140°	1073.4	1072.7	1072.0	1071.0	1069.7	1068.4	1067.0	1065.7	1067.0	1068.4	1069.7
142.5°	1103.1	1102.4	1101.8	1100.8	1099.4	1098.1	1096.7	1095.4	1096.7	1098.1	1099.4
145°	1145.1	1144.7	1144.2	1143.2	1141.7	1140.1	1138.5	1137.0	1138.5	1140.1	1141.7
147.5°	1181.9	1181.4	1181.0	1180.3	1179.2	1178.2	1177.2	1176.2	1177.2	1178.2	1179.2
150°	1204.4	1203.9	1203.5	1202.9	1202.3	1201.6	1200.9	1200.3	1200.9	1201.6	1202.3
152.5°	1224.0	1223.8	1223.5	1223.2	1222.9	1222.6	1222.3	1222.0	1222.3	1222.6	1222.9
155°	1251.0	1250.8	1250.6	1250.7	1251.2	1251.6	1252.0	1252.5	1252.0	1251.6	1251.2
157.5°	1275.4	1275.7	1275.9	1276.0	1276.1	1276.1	1276.2	1276.2	1276.2	1276.1	1276.1
160°	1289.1	1289.3	1289.5	1289.8	1290.0	1290.2	1290.4	1290.7	1290.4	1290.2	1290.0
162.5°	1301.2	1301.4	1301.6	1302.0	1302.6	1303.2	1303.7	1304.3	1303.7	1303.2	1302.6
165°	1317.2	1317.4	1317.7	1318.1	1318.8	1319.5	1320.1	1320.8	1320.1	1319.5	1318.8
167.5°	1329.6	1329.6	1329.6	1330.1	1331.0	1331.9	1332.8	1333.6	1332.8	1331.9	1331.0
170°	1336.9	1336.9	1336.9	1337.3	1338.2	1339.1	1340.0	1340.9	1340.0	1339.1	1338.2
172.5°	1341.3	1341.1	1341.0	1341.4	1342.5	1343.6	1344.6	1345.7	1344.6	1343.6	1342.5
175°	1347.5	1347.2	1347.0	1347.5	1348.6	1349.7	1350.8	1351.9	1350.8	1349.7	1348.6
177.5°	1350.0	1349.8	1349.6	1350.0	1350.9	1351.8	1352.6	1353.5	1352.6	1351.8	1350.9
180°	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2
2.5°	534.9	532.5	530.8	527.1	524.7	522.1	519.5	521.1	520.9	520.8	520.8
5°	517.0	511.6	506.7	500.4	496.5	491.6	487.9	487.4	488.3	485.1	483.2
7.5°	499.2	491.9	484.9	478.0	470.6	464.7	461.1	459.3	457.0	455.0	452.9
10°	486.7	478.1	471.3	462.7	454.8	447.8	443.4	440.3	438.7	437.1	434.0
12.5°	473.8	465.4	456.8	447.0	439.5	431.4	428.1	424.7	421.6	419.7	415.6
15°	455.0	444.1	435.0	424.7	416.3	408.4	403.8	397.0	396.1	393.7	389.5
17.5°	436.1	424.3	411.7	404.1	394.7	386.4	379.3	377.1	370.4	367.9	364.2
20°	421.2	410.3	400.7	390.7	377.0	369.3	363.7	360.7	355.3	352.0	349.7
22.5°	408.4	397.2	386.2	374.5	363.2	354.5	350.4	345.7	342.8	338.2	335.7
25°	390.0	377.9	364.6	352.0	343.9	337.4	330.8	326.6	322.4	320.3	315.7
27.5°	368.7	356.0	343.6	334.0	324.0	317.6	311.7	308.0	302.9	299.4	296.8
30°	356.9	342.0	331.3	322.7	309.9	303.8	299.4	294.7	291.0	287.3	284.7
32.5°	343.3	329.7	319.6	308.9	299.1	292.4	286.7	282.6	279.4	275.9	273.3
35°	322.0	310.6	300.1	289.4	282.1	275.4	268.6	265.1	262.1	258.8	256.5
37.5°	302.7	292.0	282.0	271.9	262.9	257.4	252.0	249.3	245.2	243.0	240.7
40°	290.8	280.3	269.6	259.8	250.5	246.3	241.4	237.4	233.7	232.0	229.5
42.5°	277.7	267.2	258.2	247.7	240.0	234.3	229.8	225.5	222.7	220.3	218.9
45°	258.4	249.1	240.2	229.7	222.5	217.6	212.5	208.5	206.0	204.3	201.8
47.5°	239.6	230.3	221.3	212.2	205.2	199.6	194.4	191.7	188.3	186.3	184.6
50°	226.0	217.6	208.1	199.7	192.7	187.1	182.9	179.4	176.4	173.8	172.6
52.5°	213.5	204.6	196.3	188.5	181.1	174.8	171.0	167.3	165.0	162.1	160.7
55°	192.9	184.3	177.3	169.6	162.4	157.0	152.4	149.1	146.8	143.5	141.7
57.5°	173.6	165.8	157.5	150.8	143.4	138.9	135.0	130.6	127.7	125.2	123.3
60°	160.5	151.7	144.4	138.2	131.6	125.8	122.3	118.8	115.8	113.2	111.6
62.5°	146.9	139.2	132.3	125.5	119.5	114.4	110.4	107.5	104.8	103.2	101.5
65°	126.0	120.0	113.0	107.4	101.8	98.1	94.8	92.3	90.4	89.2	87.8
67.5°	106.8	101.0	94.9	89.4	85.6	82.8	80.7	78.5	77.5	76.0	75.1
70°	94.4	88.3	82.9	78.7	75.0	72.9	71.5	69.9	69.0	67.1	66.2
72.5°	80.8	76.4	72.5	69.1	66.1	64.2	62.4	60.4	58.9	56.8	55.9
75°	63.6	59.6	56.6	54.3	52.4	49.9	47.3	45.2	44.5	43.8	43.6
77.5°	47.1	44.6	42.4	40.4	38.1	36.3	35.7	35.2	35.1	34.7	34.7
80°	37.0	34.7	33.1	30.8	29.4	29.4	29.4	28.9	29.1	29.1	29.1
82.5°	27.5	25.4	24.5	23.7	23.4	23.6	23.6	23.7	23.5	23.9	23.7
85°	14.2	14.4	14.9	14.7	14.9	14.9	15.4	15.1	15.4	14.9	15.4
87.5°	7.2	8.3	9.0	9.8	10.6	11.0	11.3	11.5	11.9	12.1	12.2
90°	9.9	12.5	15.4	18.3	21.2	24.1	25.0	25.9	26.8	27.7	28.3
92.5°	16.2	17.0	19.2	21.3	23.5	25.7	27.1	28.6	30.0	31.4	32.3
95°	24.7	21.3	23.8	26.2	28.7	31.1	32.7	34.3	35.8	37.4	38.2
97.5°	106.7	96.6	80.6	64.5	48.4	32.3	34.1	35.9	37.7	39.5	40.5
100°	187.6	172.4	137.6	102.8	68.0	33.1	34.9	36.7	38.5	40.3	41.3
102.5°	235.6	218.2	180.2	142.2	104.1	66.1	60.6	55.0	49.5	43.9	41.4
105°	309.1	300.3	280.2	260.1	240.1	220.0	180.5	141.0	101.4	61.9	42.4
107.5°	387.9	390.5	393.7	396.8	400.0	403.2	374.2	345.2	316.3	287.3	257.9
110°	441.0	443.2	445.6	448.1	450.5	453.0	445.6	438.3	430.9	423.5	403.9



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	491.8	493.8	496.2	498.7	501.2	503.6	503.7	503.9	504.0	504.1	500.8
115°	566.8	568.5	570.5	572.5	574.5	576.5	578.8	581.0	583.2	585.5	587.0
117.5°	641.8	643.1	644.2	645.2	646.2	647.2	649.0	650.8	652.6	654.4	655.4
120°	689.0	690.4	691.0	691.7	692.4	693.0	694.8	696.6	698.4	700.2	701.1
122.5°	734.2	735.4	736.3	737.1	738.0	738.8	740.1	741.3	742.6	743.8	744.6
125°	798.6	800.0	800.8	801.7	802.6	803.5	804.0	804.4	804.9	805.3	805.8
127.5°	860.5	861.9	863.0	864.1	865.1	866.2	866.9	867.6	868.3	869.1	869.2
130°	899.1	900.4	901.3	902.2	903.1	904.0	904.9	905.8	906.6	907.5	907.8
132.5°	936.0	937.3	938.0	938.7	939.4	940.1	941.0	941.9	942.8	943.7	943.8
135°	990.7	991.8	992.7	993.6	994.5	995.4	996.0	996.7	997.4	998.0	998.0
137.5°	1040.3	1041.4	1041.9	1042.4	1042.9	1043.4	1044.4	1045.5	1046.6	1047.7	1048.0
140°	1071.0	1072.0	1072.7	1073.4	1074.0	1074.7	1075.6	1076.5	1077.4	1078.3	1078.5
142.5°	1100.8	1101.8	1102.4	1103.1	1103.8	1104.4	1105.2	1105.9	1106.6	1107.3	1107.3
145°	1143.2	1144.2	1144.7	1145.1	1145.6	1146.0	1146.5	1146.9	1147.4	1147.8	1148.0
147.5°	1180.3	1181.0	1181.4	1181.9	1182.3	1182.8	1183.2	1183.7	1184.1	1184.6	1184.3
150°	1202.9	1203.5	1203.9	1204.4	1204.8	1205.3	1205.7	1206.2	1206.6	1207.1	1207.0
152.5°	1223.2	1223.5	1223.8	1224.0	1224.3	1224.6	1225.4	1226.2	1227.0	1227.8	1227.7
155°	1250.7	1250.6	1250.8	1251.0	1251.3	1251.5	1252.6	1253.7	1254.8	1256.0	1255.8
157.5°	1276.0	1275.9	1275.7	1275.4	1275.2	1275.0	1276.3	1277.7	1279.0	1280.3	1280.1
160°	1289.8	1289.5	1289.3	1289.1	1288.9	1288.7	1290.0	1291.3	1292.7	1294.0	1293.9
162.5°	1302.0	1301.6	1301.4	1301.2	1300.9	1300.7	1302.2	1303.7	1305.3	1306.8	1306.8
165°	1318.1	1317.7	1317.4	1317.2	1317.0	1316.8	1318.6	1320.3	1322.1	1323.9	1324.0
167.5°	1330.1	1329.6	1329.6	1329.6	1329.6	1329.6	1331.4	1333.2	1335.0	1336.8	1336.8
170°	1337.3	1336.9	1336.9	1336.9	1336.9	1336.9	1338.6	1340.4	1342.2	1344.0	1344.0
172.5°	1341.4	1341.0	1341.1	1341.3	1341.5	1341.7	1343.5	1345.3	1347.0	1348.8	1348.7
175°	1347.5	1347.0	1347.2	1347.5	1347.7	1347.9	1349.5	1351.0	1352.6	1354.2	1354.1
177.5°	1350.0	1349.6	1349.8	1350.0	1350.1	1350.3	1351.8	1353.2	1354.6	1356.0	1355.9
180°	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2
2.5°	518.5	518.3	518.5	517.8	518.5	518.3	518.5	520.8	520.8	520.9	521.1
5°	482.5	482.3	481.6	479.5	481.6	482.3	482.5	483.2	485.1	488.3	487.4
7.5°	451.0	450.7	448.7	448.7	448.7	450.7	451.0	452.9	455.0	457.0	459.3
10°	432.4	432.6	429.8	428.2	429.8	432.6	432.4	434.0	437.1	438.7	440.3
12.5°	414.3	413.3	411.0	409.2	411.0	413.3	414.3	415.6	419.7	421.6	424.7
15°	390.5	388.1	382.6	383.0	382.6	388.1	390.5	389.5	393.7	396.1	397.0
17.5°	362.4	360.7	360.6	357.3	360.6	360.7	362.4	364.2	367.9	370.4	377.1
20°	346.0	344.8	345.3	342.0	345.3	344.8	346.0	349.7	352.0	355.3	360.7
22.5°	333.1	331.9	330.0	329.0	330.0	331.9	333.1	335.7	338.2	342.8	345.7
25°	314.3	312.4	310.6	311.7	310.6	312.4	314.3	315.7	320.3	322.4	326.6
27.5°	295.5	294.1	292.2	292.0	292.2	294.1	295.5	296.8	299.4	302.9	308.0
30°	283.5	282.1	281.2	280.0	281.2	282.1	283.5	284.7	287.3	291.0	294.7
32.5°	271.4	271.1	269.5	269.2	269.5	271.1	271.4	273.3	275.9	279.4	282.6
35°	255.6	254.2	253.7	253.9	253.7	254.2	255.6	256.5	258.8	262.1	265.1
37.5°	240.5	238.7	237.8	237.0	237.8	238.7	240.5	240.7	243.0	245.2	249.3
40°	229.7	227.9	227.4	226.9	227.4	227.9	229.7	229.5	232.0	233.7	237.4
42.5°	217.6	216.9	216.6	215.7	216.6	216.9	217.6	218.9	220.3	222.7	225.5
45°	201.1	200.8	199.4	199.9	199.4	200.8	201.1	201.8	204.3	206.0	208.5
47.5°	183.6	182.6	181.6	182.3	181.6	182.6	183.6	184.6	186.3	188.3	191.7
50°	171.7	171.2	169.1	169.6	169.1	171.2	171.7	172.6	173.8	176.4	179.4
52.5°	159.8	158.0	157.2	156.9	157.2	158.0	159.8	160.7	162.1	165.0	167.3
55°	140.0	137.9	137.0	136.5	137.0	137.9	140.0	141.7	143.5	146.8	149.1
57.5°	120.6	120.1	119.3	119.8	119.3	120.1	120.6	123.3	125.2	127.7	130.6
60°	109.3	109.3	109.3	109.0	109.3	109.3	109.3	111.6	113.2	115.8	118.8
62.5°	100.5	99.9	99.8	100.1	99.8	99.9	100.5	101.5	103.2	104.8	107.5
65°	87.1	86.9	86.0	85.7	86.0	86.9	87.1	87.8	89.2	90.4	92.3
67.5°	74.5	73.7	73.4	73.1	73.4	73.7	74.5	75.1	76.0	77.5	78.5
70°	65.0	64.5	63.1	63.4	63.1	64.5	65.0	66.2	67.1	69.0	69.9
72.5°	54.8	54.3	54.0	53.7	54.0	54.3	54.8	55.9	56.8	58.9	60.4
75°	43.3	43.1	42.9	43.8	42.9	43.1	43.3	43.6	43.8	44.5	45.2
77.5°	34.7	34.7	34.9	34.5	34.9	34.7	34.7	34.7	34.7	35.1	35.2
80°	29.1	29.1	28.9	28.9	28.9	29.1	29.1	29.1	29.1	29.1	28.9
82.5°	23.3	23.5	23.7	23.3	23.7	23.5	23.3	23.7	23.9	23.5	23.7
85°	15.4	15.1	15.6	15.4	15.6	15.1	15.4	15.4	14.9	15.4	15.1
87.5°	12.7	12.4	12.5	12.7	12.5	12.4	12.7	12.2	12.1	11.9	11.5
90°	28.8	29.2	29.7	30.1	29.7	29.2	28.8	28.3	27.7	26.8	25.9
92.5°	32.5	32.8	33.1	33.3	33.1	32.8	32.5	32.3	31.4	30.0	28.6
95°	38.2	38.2	38.2	38.2	38.2	38.2	38.2	38.2	37.4	35.8	34.3
97.5°	40.7	40.9	41.2	41.4	41.2	40.9	40.7	40.5	39.5	37.7	35.9
100°	41.5	41.7	42.0	42.2	42.0	41.7	41.5	41.3	40.3	38.5	36.7
102.5°	41.8	42.2	42.6	43.0	42.6	42.2	41.8	41.4	43.9	49.5	55.0
105°	42.9	43.3	43.7	44.2	43.7	43.3	42.9	42.4	61.9	101.4	141.0
107.5°	228.1	198.4	168.6	138.8	168.6	198.4	228.1	257.9	287.3	316.3	345.2
110°	372.0	340.0	308.1	276.2	308.1	340.0	372.0	403.9	423.5	430.9	438.3



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	494.1	487.4	480.6	473.9	480.6	487.4	494.1	500.8	504.1	504.0	503.9
115°	587.9	588.8	589.7	590.6	589.7	588.8	587.9	587.0	585.5	583.2	581.0
117.5°	655.5	655.7	655.9	656.1	655.9	655.7	655.5	655.4	654.4	652.6	650.8
120°	701.1	701.1	701.1	701.1	701.1	701.1	701.1	701.1	700.2	698.4	696.6
122.5°	744.7	744.9	745.1	745.3	745.1	744.9	744.7	744.6	743.8	742.6	741.3
125°	806.2	806.6	807.1	807.5	807.1	806.6	806.2	805.8	805.3	804.9	804.4
127.5°	868.7	868.3	867.9	867.4	867.9	868.3	868.7	869.2	869.1	868.3	867.6
130°	907.3	906.9	906.4	906.0	906.4	906.9	907.3	907.8	907.5	906.6	905.8
132.5°	943.2	942.6	942.0	941.3	942.0	942.6	943.2	943.8	943.7	942.8	941.9
135°	997.4	996.7	996.0	995.4	996.0	996.7	997.4	998.0	998.0	997.4	996.7
137.5°	1047.5	1047.1	1046.6	1046.2	1046.6	1047.1	1047.5	1048.0	1047.7	1046.6	1045.5
140°	1078.1	1077.6	1077.2	1076.7	1077.2	1077.6	1078.1	1078.5	1078.3	1077.4	1076.5
142.5°	1106.7	1106.1	1105.5	1104.8	1105.5	1106.1	1106.7	1107.3	1107.3	1106.6	1105.9
145°	1148.0	1148.0	1148.0	1148.0	1148.0	1148.0	1148.0	1148.0	1147.8	1147.4	1146.9
147.5°	1183.3	1182.2	1181.2	1180.2	1181.2	1182.2	1183.3	1184.3	1184.6	1184.1	1183.7
150°	1206.3	1205.6	1205.0	1204.3	1205.0	1205.6	1206.3	1207.0	1207.1	1206.6	1206.2
152.5°	1226.6	1225.6	1224.6	1223.6	1224.6	1225.6	1226.6	1227.7	1227.8	1227.0	1226.2
155°	1254.5	1253.2	1251.8	1250.5	1251.8	1253.2	1254.5	1255.8	1256.0	1254.8	1253.7
157.5°	1278.4	1276.7	1274.9	1273.2	1274.9	1276.7	1278.4	1280.1	1280.3	1279.0	1277.7
160°	1292.3	1290.8	1289.2	1287.6	1289.2	1290.8	1292.3	1293.9	1294.0	1292.7	1291.3
162.5°	1305.5	1304.1	1302.7	1301.3	1302.7	1304.1	1305.5	1306.8	1306.8	1305.3	1303.7
165°	1322.5	1320.9	1319.3	1317.8	1319.3	1320.9	1322.5	1324.0	1323.9	1322.1	1320.3
167.5°	1335.0	1333.2	1331.4	1329.6	1331.4	1333.2	1335.0	1336.8	1336.8	1335.0	1333.2
170°	1342.2	1340.4	1338.6	1336.9	1338.6	1340.4	1342.2	1344.0	1344.0	1342.2	1340.4
172.5°	1346.8	1344.8	1342.8	1340.9	1342.8	1344.8	1346.8	1348.7	1348.8	1347.0	1345.3
175°	1352.3	1350.5	1348.7	1346.9	1348.7	1350.5	1352.3	1354.1	1354.2	1352.6	1351.0
177.5°	1354.1	1352.3	1350.5	1348.7	1350.5	1352.3	1354.1	1355.9	1356.0	1354.6	1353.2
180°	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2
2.5°	519.5	522.1	524.7	527.1	530.8	532.5	534.9	535.9	538.6	542.7	546.1
5°	487.9	491.6	496.5	500.4	506.7	511.6	517.0	522.1	528.2	536.8	544.5
7.5°	461.1	464.7	470.6	478.0	484.9	491.9	499.2	506.2	514.8	527.2	539.4
10°	443.4	447.8	454.8	462.7	471.3	478.1	486.7	495.5	506.3	520.5	535.2
12.5°	428.1	431.4	439.5	447.0	456.8	465.4	473.8	484.2	496.4	511.5	529.2
15°	403.8	408.4	416.3	424.7	435.0	444.1	455.0	467.6	479.5	498.1	519.5
17.5°	379.3	386.4	394.7	404.1	411.7	424.3	436.1	449.0	463.7	483.4	507.0
20°	363.7	369.3	377.0	390.7	400.7	410.3	421.2	437.3	450.8	473.2	497.6
22.5°	350.4	354.5	363.2	374.5	386.2	397.2	408.4	423.7	440.4	461.6	488.1
25°	330.8	337.4	343.9	352.0	364.6	377.9	390.0	403.1	420.8	443.4	472.0
27.5°	311.7	317.6	324.0	334.0	343.6	356.0	368.7	383.6	402.6	426.5	455.6
30°	299.4	303.8	309.9	322.7	331.3	342.0	356.9	370.2	387.9	413.3	444.1
32.5°	286.7	292.4	299.1	308.9	319.6	329.7	343.3	357.7	375.8	400.8	432.3
35°	268.6	275.4	282.1	289.4	300.1	310.6	322.0	337.8	356.2	380.5	411.4
37.5°	252.0	257.4	262.9	271.9	282.0	292.0	302.7	318.3	335.6	361.8	390.2
40°	241.4	246.3	250.5	259.8	269.6	280.3	290.8	304.5	323.1	347.6	375.1
42.5°	229.8	234.3	240.0	247.7	258.2	267.2	277.7	290.7	308.2	333.1	357.2
45°	212.5	217.6	222.5	229.7	240.2	249.1	258.4	270.7	288.7	309.2	330.6
47.5°	194.4	199.6	205.2	212.2	221.3	230.3	239.6	250.5	266.9	287.0	301.5
50°	182.9	187.1	192.7	199.7	208.1	217.6	226.0	237.9	253.5	269.3	281.9
52.5°	171.0	174.8	181.1	188.5	196.3	204.6	213.5	223.7	237.8	252.7	262.7
55°	152.4	157.0	162.4	169.6	177.3	184.3	192.9	203.4	214.6	225.8	232.5
57.5°	135.0	138.9	143.4	150.8	157.5	165.8	173.6	181.7	192.1	200.5	204.9
60°	122.3	125.8	131.6	138.2	144.4	151.7	160.5	168.7	176.6	183.4	186.8
62.5°	110.4	114.4	119.5	125.5	132.3	139.2	146.9	153.8	160.8	166.6	169.0
65°	94.8	98.1	101.8	107.4	113.0	120.0	126.0	133.0	138.2	141.4	143.5
67.5°	80.7	82.8	85.6	89.4	94.9	101.0	106.8	112.3	116.6	118.8	120.7
70°	71.5	72.9	75.0	78.7	82.9	88.3	94.4	98.3	102.0	103.9	105.8
72.5°	62.4	64.2	66.1	69.1	72.5	76.4	80.8	85.6	87.7	89.9	91.0
75°	47.3	49.9	52.4	54.3	56.6	59.6	63.6	66.6	67.8	69.7	69.9
77.5°	35.7	36.3	38.1	40.4	42.4	44.6	47.1	49.8	50.4	51.3	52.0
80°	29.4	29.4	29.4	30.8	33.1	34.7	37.0	38.4	39.4	39.6	39.8
82.5°	23.6	23.6	23.4	23.7	24.5	25.4	27.5	29.1	29.9	29.7	29.2
85°	15.4	14.9	14.9	14.7	14.9	14.4	14.2	15.1	16.5	16.5	16.1
87.5°	11.3	11.0	10.6	9.8	9.0	8.3	7.2	6.9	6.5	6.8	6.2
90°	25.0	24.1	21.2	18.3	15.4	12.5	9.9	7.7	5.5	3.2	1.0
92.5°	27.1	25.7	23.5	21.3	19.2	17.0	16.2	16.8	17.4	18.1	18.7
95°	32.7	31.1	28.7	26.2	23.8	21.3	24.7	33.8	43.0	52.1	61.3
97.5°	34.1	32.3	48.4	64.5	80.6	96.6	106.7	110.8	114.9	119.0	123.1
100°	34.9	33.1	68.0	102.8	137.6	172.4	187.6	183.1	178.7	174.2	169.7
102.5°	60.6	66.1	104.1	142.2	180.2	218.2	235.6	232.4	229.2	226.0	222.8
105°	180.5	220.0	240.1	260.1	280.2	300.3	309.1	306.7	304.2	301.8	299.3
107.5°	374.2	403.2	400.0	396.8	393.7	390.5	387.9	386.0	384.0	382.0	380.1
110°	445.6	453.0	450.5	448.1	445.6	443.2	441.0	439.3	437.5	435.7	433.9



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	503.7	503.6	501.2	498.7	496.2	493.8	491.8	490.2	488.5	486.9	485.3
115°	578.8	576.5	574.5	572.5	570.5	568.5	566.8	565.5	564.1	562.8	561.5
117.5°	649.0	647.2	646.2	645.2	644.2	643.1	641.8	640.1	638.5	636.8	635.2
120°	694.8	693.0	692.4	691.7	691.0	690.4	689.0	687.0	685.0	683.0	681.0
122.5°	740.1	738.8	738.0	737.1	736.3	735.4	734.2	732.5	730.9	729.2	727.6
125°	804.0	803.5	802.6	801.7	800.8	800.0	798.6	796.8	795.0	793.3	791.5
127.5°	866.9	866.2	865.1	864.1	863.0	861.9	860.5	858.7	856.9	855.1	853.3
130°	904.9	904.0	903.1	902.2	901.3	900.4	899.1	897.3	895.5	893.7	891.9
132.5°	941.0	940.1	939.4	938.7	938.0	937.3	936.0	934.2	932.4	930.7	928.9
135°	996.0	995.4	994.5	993.6	992.7	991.8	990.7	989.3	988.0	986.7	985.3
137.5°	1044.4	1043.4	1042.9	1042.4	1041.9	1041.4	1040.3	1038.6	1036.9	1035.2	1033.5
140°	1075.6	1074.7	1074.0	1073.4	1072.7	1072.0	1071.0	1069.7	1068.4	1067.0	1065.7
142.5°	1105.2	1104.4	1103.8	1103.1	1102.4	1101.8	1100.8	1099.4	1098.1	1096.7	1095.4
145°	1146.5	1146.0	1145.6	1145.1	1144.7	1144.2	1143.2	1141.7	1140.1	1138.5	1137.0
147.5°	1183.2	1182.8	1182.3	1181.9	1181.4	1181.0	1180.3	1179.2	1178.2	1177.2	1176.2
150°	1205.7	1205.3	1204.8	1204.4	1203.9	1203.5	1202.9	1202.3	1201.6	1200.9	1200.3
152.5°	1225.4	1224.6	1224.3	1224.0	1223.8	1223.5	1223.2	1222.9	1222.6	1222.3	1222.0
155°	1252.6	1251.5	1251.3	1251.0	1250.8	1250.6	1250.7	1251.2	1251.6	1252.0	1252.5
157.5°	1276.3	1275.0	1275.2	1275.4	1275.7	1275.9	1276.0	1276.1	1276.1	1276.2	1276.2
160°	1290.0	1288.7	1288.9	1289.1	1289.3	1289.5	1289.8	1290.0	1290.2	1290.4	1290.7
162.5°	1302.2	1300.7	1300.9	1301.2	1301.4	1301.6	1302.0	1302.6	1303.2	1303.7	1304.3
165°	1318.6	1316.8	1317.0	1317.2	1317.4	1317.7	1318.1	1318.8	1319.5	1320.1	1320.8
167.5°	1331.4	1329.6	1329.6	1329.6	1329.6	1329.6	1330.1	1331.0	1331.9	1332.8	1333.6
170°	1338.6	1336.9	1336.9	1336.9	1336.9	1336.9	1337.3	1338.2	1339.1	1340.0	1340.9
172.5°	1343.5	1341.7	1341.5	1341.3	1341.1	1341.0	1341.4	1342.5	1343.6	1344.6	1345.7
175°	1349.5	1347.9	1347.7	1347.5	1347.2	1347.0	1347.5	1348.6	1349.7	1350.8	1351.9
177.5°	1351.8	1350.3	1350.1	1350.0	1349.8	1349.6	1350.0	1350.9	1351.8	1352.6	1353.5
180°	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2	544.2
2.5°	547.2	549.3	551.9	555.8	558.8	561.4	561.9	562.7	564.6	567.7	570.1
5°	550.8	556.1	564.7	573.1	582.2	589.7	596.7	601.6	606.2	616.0	623.9
7.5°	549.6	561.6	575.1	590.1	605.4	620.1	633.8	646.1	658.3	672.6	688.8
10°	548.9	562.9	581.1	600.4	621.6	642.3	662.4	678.0	696.1	712.5	733.2
12.5°	545.4	565.5	587.2	611.9	638.0	661.9	688.3	709.8	730.6	754.2	778.3
15°	540.7	565.2	592.7	625.5	665.2	694.0	721.1	758.6	784.2	809.8	844.3
17.5°	532.3	562.2	596.5	639.2	672.2	711.1	751.7	781.4	815.9	852.0	883.2
20°	525.6	560.3	598.8	640.7	682.9	725.0	764.4	799.8	835.5	877.2	902.8
22.5°	518.9	553.2	593.2	637.7	683.0	727.5	772.0	813.6	853.7	895.8	928.5
25°	504.6	545.4	588.7	634.2	678.9	727.8	780.9	827.3	876.9	920.3	951.3
27.5°	490.2	527.6	570.7	616.8	666.5	724.3	786.8	839.5	889.2	920.3	930.0
30°	477.1	516.7	556.4	603.2	657.0	721.5	787.9	848.3	889.0	902.6	892.5
32.5°	463.9	499.8	539.0	587.0	644.1	714.6	789.4	843.1	867.6	857.3	816.5
35°	440.6	472.9	510.9	558.9	624.6	710.8	783.3	819.6	813.6	755.3	678.4
37.5°	415.6	442.0	477.1	527.3	604.4	695.7	756.8	762.2	709.7	620.3	531.5
40°	395.8	419.6	455.7	508.1	588.7	680.8	730.2	708.5	627.2	527.7	453.6
42.5°	376.6	396.7	431.5	488.0	573.8	660.4	690.5	643.3	549.5	455.4	388.0
45°	344.1	363.0	397.9	455.9	543.3	621.6	617.6	535.6	441.7	366.0	310.1
47.5°	313.3	329.8	362.6	421.8	507.5	563.3	526.3	439.0	359.4	298.6	258.7
50°	291.5	307.8	340.4	398.9	478.8	519.5	466.7	382.6	309.6	259.3	227.6
52.5°	270.6	286.5	316.3	373.3	444.1	468.5	411.7	333.7	272.9	229.5	202.3
55°	241.4	253.5	280.3	334.8	387.7	393.3	335.7	270.5	220.4	190.1	171.5
57.5°	211.6	222.0	248.5	291.9	329.0	326.1	271.6	215.1	181.4	158.9	145.4
60°	192.2	202.5	225.8	263.0	291.0	281.2	231.1	185.7	156.8	140.3	129.5
62.5°	174.1	182.1	204.0	231.2	251.3	240.2	197.6	160.0	137.0	123.1	114.6
65°	147.9	154.5	171.9	186.2	197.3	186.6	151.2	125.1	108.6	98.8	93.0
67.5°	123.1	127.2	138.2	143.4	151.3	139.5	113.7	96.2	86.8	78.6	74.5
70°	107.4	110.4	116.3	120.5	122.5	110.4	91.3	78.5	70.6	64.8	62.2
72.5°	91.7	94.4	95.6	99.0	97.9	86.6	73.4	63.2	57.5	53.6	50.3
75°	70.1	71.3	70.1	68.7	65.7	57.8	48.7	43.6	39.4	37.5	36.3
77.5°	51.1	50.7	49.2	47.0	41.8	36.8	31.9	30.2	28.4	27.4	27.0
80°	39.4	38.4	37.0	33.5	29.1	25.6	24.5	23.3	22.6	21.4	21.2
82.5°	29.3	28.7	26.4	23.5	20.4	18.7	17.8	17.3	16.6	16.0	16.0
85°	15.6	14.9	12.3	10.7	10.3	9.8	9.6	9.6	8.6	8.4	8.4
87.5°	5.7	5.0	5.3	5.2	5.7	5.9	6.6	6.9	7.2	7.6	7.4
90°	3.2	5.5	7.7	9.9	12.5	15.4	18.3	21.2	24.1	25.0	25.9
92.5°	18.1	17.4	16.8	16.2	17.0	19.2	21.3	23.5	25.7	27.1	28.6
95°	52.1	43.0	33.8	24.7	21.3	23.8	26.2	28.7	31.1	32.7	34.3
97.5°	119.0	114.9	110.8	106.7	96.6	80.6	64.5	48.4	32.3	34.1	35.9
100°	174.2	178.7	183.1	187.6	172.4	137.6	102.8	68.0	33.1	34.9	36.7
102.5°	226.0	229.2	232.4	235.6	218.2	180.2	142.2	104.1	66.1	60.6	55.0
105°	301.8	304.2	306.7	309.1	300.3	280.2	260.1	240.1	220.0	180.5	141.0
107.5°	382.0	384.0	386.0	387.9	390.5	393.7	396.8	400.0	403.2	374.2	345.2
110°	435.7	437.5	439.3	441.0	443.2	445.6	448.1	450.5	453.0	445.6	438.3



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	486.9	488.5	490.2	491.8	493.8	496.2	498.7	501.2	503.6	503.7	503.9
115°	562.8	564.1	565.5	566.8	568.5	570.5	572.5	574.5	576.5	578.8	581.0
117.5°	636.8	638.5	640.1	641.8	643.1	644.2	645.2	646.2	647.2	649.0	650.8
120°	683.0	685.0	687.0	689.0	690.4	691.0	691.7	692.4	693.0	694.8	696.6
122.5°	729.2	730.9	732.5	734.2	735.4	736.3	737.1	738.0	738.8	740.1	741.3
125°	793.3	795.0	796.8	798.6	800.0	800.8	801.7	802.6	803.5	804.0	804.4
127.5°	855.1	856.9	858.7	860.5	861.9	863.0	864.1	865.1	866.2	866.9	867.6
130°	893.7	895.5	897.3	899.1	900.4	901.3	902.2	903.1	904.0	904.9	905.8
132.5°	930.7	932.4	934.2	936.0	937.3	938.0	938.7	939.4	940.1	941.0	941.9
135°	986.7	988.0	989.3	990.7	991.8	992.7	993.6	994.5	995.4	996.0	996.7
137.5°	1035.2	1036.9	1038.6	1040.3	1041.4	1041.9	1042.4	1042.9	1043.4	1044.4	1045.5
140°	1067.0	1068.4	1069.7	1071.0	1072.0	1072.7	1073.4	1074.0	1074.7	1075.6	1076.5
142.5°	1096.7	1098.1	1099.4	1100.8	1101.8	1102.4	1103.1	1103.8	1104.4	1105.2	1105.9
145°	1138.5	1140.1	1141.7	1143.2	1144.2	1144.7	1145.1	1145.6	1146.0	1146.5	1146.9
147.5°	1177.2	1178.2	1179.2	1180.3	1181.0	1181.4	1181.9	1182.3	1182.8	1183.2	1183.7
150°	1200.9	1201.6	1202.3	1202.9	1203.5	1203.9	1204.4	1204.8	1205.3	1205.7	1206.2
152.5°	1222.3	1222.6	1222.9	1223.2	1223.5	1223.8	1224.0	1224.3	1224.6	1225.4	1226.2
155°	1252.0	1251.6	1251.2	1250.7	1250.6	1250.8	1251.0	1251.3	1251.5	1252.6	1253.7
157.5°	1276.2	1276.1	1276.1	1276.0	1275.9	1275.7	1275.4	1275.2	1275.0	1276.3	1277.7
160°	1290.4	1290.2	1290.0	1289.8	1289.5	1289.3	1289.1	1288.9	1288.7	1290.0	1291.3
162.5°	1303.7	1303.2	1302.6	1302.0	1301.6	1301.4	1301.2	1300.9	1300.7	1302.2	1303.7
165°	1320.1	1319.5	1318.8	1318.1	1317.7	1317.4	1317.2	1317.0	1316.8	1318.6	1320.3
167.5°	1332.8	1331.9	1331.0	1330.1	1329.6	1329.6	1329.6	1329.6	1329.6	1331.4	1333.2
170°	1340.0	1339.1	1338.2	1337.3	1336.9	1336.9	1336.9	1336.9	1336.9	1338.6	1340.4
172.5°	1344.6	1343.6	1342.5	1341.4	1341.0	1341.1	1341.3	1341.5	1341.7	1343.5	1345.3
175°	1350.8	1349.7	1348.6	1347.5	1347.0	1347.2	1347.5	1347.7	1347.9	1349.5	1351.0
177.5°	1352.6	1351.8	1350.9	1350.0	1349.6	1349.8	1350.0	1350.1	1350.3	1351.8	1353.2
180°	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	544.2	544.2	544.2	544.2	544.2	544.2	544.2
2.5°	574.1	574.1	574.8	577.6	578.0	580.4	579.7
5°	630.9	635.3	637.0	644.0	648.1	650.0	646.3
7.5°	700.4	712.9	718.8	726.2	732.6	734.6	729.5
10°	751.1	764.2	775.1	781.9	788.2	792.4	797.7
12.5°	800.1	816.2	826.6	836.1	842.6	847.9	848.8
15°	853.4	877.6	896.0	909.6	916.3	919.8	918.4
17.5°	907.1	929.6	942.7	956.5	965.8	966.3	966.6
20°	937.5	959.4	974.6	984.8	995.3	994.8	997.2
22.5°	957.8	975.1	986.7	994.1	997.7	995.9	996.4
25°	967.3	972.5	970.4	958.5	955.4	944.5	946.4
27.5°	918.3	894.1	869.0	836.8	811.3	791.0	792.0
30°	851.8	808.9	760.0	719.0	682.2	671.9	650.0
32.5°	758.8	694.5	637.2	598.9	567.4	558.8	539.7
35°	601.1	538.6	479.7	444.3	430.3	410.7	410.5
37.5°	467.2	412.2	381.1	354.5	340.6	328.7	327.6
40°	393.0	350.2	326.6	307.5	293.8	284.9	282.8
42.5°	341.2	306.6	284.5	272.7	262.1	257.5	254.1
45°	278.6	255.3	240.0	229.3	224.4	220.9	219.0
47.5°	233.1	217.5	207.0	199.8	195.9	192.2	193.2
50°	208.3	195.5	187.8	181.0	178.0	175.4	175.7
52.5°	188.3	176.8	170.6	165.7	162.0	160.1	159.3
55°	159.8	152.6	146.3	142.8	140.7	138.2	137.5
57.5°	136.3	130.7	125.6	121.7	121.1	118.7	119.0
60°	120.7	116.0	111.8	109.7	108.1	106.0	106.7
62.5°	107.8	103.9	100.1	98.4	96.7	95.2	95.5
65°	88.3	84.6	82.2	81.3	80.6	79.9	79.2
67.5°	70.4	68.1	66.6	64.6	63.2	63.0	62.3
70°	59.2	56.1	53.6	51.0	50.3	50.1	50.3
72.5°	47.4	45.5	44.8	43.6	43.4	42.8	43.2
75°	35.6	34.9	34.5	33.5	33.5	33.5	33.5
77.5°	26.3	25.9	25.6	25.4	25.2	24.8	24.8
80°	20.5	20.3	19.8	19.8	19.6	19.8	19.6
82.5°	15.5	15.4	15.0	15.0	14.7	14.6	14.7
85°	7.9	7.7	8.2	7.7	7.9	7.5	7.9
87.5°	7.6	7.8	7.7	7.8	7.7	8.2	7.9
90°	26.8	27.7	28.3	28.8	29.2	29.7	30.1
92.5°	30.0	31.4	32.3	32.5	32.8	33.1	33.3
95°	35.8	37.4	38.2	38.2	38.2	38.2	38.2
97.5°	37.7	39.5	40.5	40.7	40.9	41.2	41.4
100°	38.5	40.3	41.3	41.5	41.7	42.0	42.2
102.5°	49.5	43.9	41.4	41.8	42.2	42.6	43.0
105°	101.4	61.9	42.4	42.9	43.3	43.7	44.2
107.5°	316.3	287.3	257.9	228.1	198.4	168.6	138.8
110°	430.9	423.5	403.9	372.0	340.0	308.1	276.2



TEST NUMBER: P332398

CATALOG NUMBER: S123RDIW-S340D1030U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	504.0	504.1	500.8	494.1	487.4	480.6	473.9
115°	583.2	585.5	587.0	587.9	588.8	589.7	590.6
117.5°	652.6	654.4	655.4	655.5	655.7	655.9	656.1
120°	698.4	700.2	701.1	701.1	701.1	701.1	701.1
122.5°	742.6	743.8	744.6	744.7	744.9	745.1	745.3
125°	804.9	805.3	805.8	806.2	806.6	807.1	807.5
127.5°	868.3	869.1	869.2	868.7	868.3	867.9	867.4
130°	906.6	907.5	907.8	907.3	906.9	906.4	906.0
132.5°	942.8	943.7	943.8	943.2	942.6	942.0	941.3
135°	997.4	998.0	998.0	997.4	996.7	996.0	995.4
137.5°	1046.6	1047.7	1048.0	1047.5	1047.1	1046.6	1046.2
140°	1077.4	1078.3	1078.5	1078.1	1077.6	1077.2	1076.7
142.5°	1106.6	1107.3	1107.3	1106.7	1106.1	1105.5	1104.8
145°	1147.4	1147.8	1148.0	1148.0	1148.0	1148.0	1148.0
147.5°	1184.1	1184.6	1184.3	1183.3	1182.2	1181.2	1180.2
150°	1206.6	1207.1	1207.0	1206.3	1205.6	1205.0	1204.3
152.5°	1227.0	1227.8	1227.7	1226.6	1225.6	1224.6	1223.6
155°	1254.8	1256.0	1255.8	1254.5	1253.2	1251.8	1250.5
157.5°	1279.0	1280.3	1280.1	1278.4	1276.7	1274.9	1273.2
160°	1292.7	1294.0	1293.9	1292.3	1290.8	1289.2	1287.6
162.5°	1305.3	1306.8	1306.8	1305.5	1304.1	1302.7	1301.3
165°	1322.1	1323.9	1324.0	1322.5	1320.9	1319.3	1317.8
167.5°	1335.0	1336.8	1336.8	1335.0	1333.2	1331.4	1329.6
170°	1342.2	1344.0	1344.0	1342.2	1340.4	1338.6	1336.9
172.5°	1347.0	1348.8	1348.7	1346.8	1344.8	1342.8	1340.9
175°	1352.6	1354.2	1354.1	1352.3	1350.5	1348.7	1346.9
177.5°	1354.6	1356.0	1355.9	1354.1	1352.3	1350.5	1348.7
180°	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9	1351.9

(END OF REPORT)