

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P332096-840

Luminaire Tested: **S123DIW-S340D755U840-4F0-1E-UDD-A**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P332096-840
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-5,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S123DIW-S340D755U840-4F0-1E-UDD-A
Description: DEFINE 3 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 340 LUMENS PER FOOT, ASYMMETRIC DIFFUSER
UPLIGHT 755 LUMENS PER FOOT, NO LENS
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4518.7 lumens
Efficiency: N/A
Efficacy: 148.6 lumens/watt
Spacing Criteria (0/90/45): 1.37 / 1.23 / 1.49
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')
CIE Type: Semi-Indirect


Input Watts (W): 30.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

Luminous Intensity Polar Plot





TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	103	103	103	103	93	93	93	93	74	74	74	56	56	56	40	40	40	32
1	94	90	86	83	85	81	78	75	65	63	61	50	48	47	36	35	34	28
2	86	79	73	68	77	71	66	62	57	53	50	44	41	39	32	30	29	23
3	78	69	62	57	70	63	57	52	50	46	42	39	36	33	28	26	25	20
4	72	61	54	48	64	55	49	44	45	40	36	35	31	29	25	23	21	17
5	66	54	47	41	59	49	43	38	40	35	31	31	28	25	23	20	19	15
6	60	49	41	35	54	44	38	33	36	31	27	28	24	22	21	18	16	13
7	56	44	36	31	50	40	33	29	32	27	24	25	22	19	19	16	15	12
8	52	40	32	27	46	36	30	25	30	25	21	23	20	17	17	15	13	11
9	48	36	29	24	43	33	27	22	27	22	19	21	18	15	16	14	12	10
10	45	33	26	21	40	30	24	20	25	20	17	20	16	14	15	12	11	9

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	5226	5226	5226	5226
5°	6232	5249	4652	5249
10°	7802	5223	4203	5223
15°	9569	5180	3911	5180
20°	11399	5116	3725	5116
25°	12105	5035	3682	5035
30°	10376	4977	3701	4977
35°	7215	4893	3741	4893
40°	5435	4796	3729	4796
45°	4512	4652	3682	4652
50°	4042	4357	3647	4357
55°	3780	4040	3603	4040
60°	3546	3707	3565	3707
65°	3331	3380	3451	3380
70°	3125	3006	3286	3006
75°	2799	2633	3015	2633
80°	2448	2157	2597	2157
85°	1927	1568	1741	1568



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	47.8	1.1
10°-20°	153.4	3.4
20°-30°	257.4	5.7
30°-40°	291.5	6.5
40°-50°	261.4	5.8
50°-60°	210.9	4.7
60°-70°	147.0	3.3
70°-80°	77.3	1.7
80°-90°	21.7	0.5
90°-100°	36.4	0.8
100°-110°	173.3	3.8
110°-120°	416.3	9.2
120°-130°	530.1	11.7
130°-140°	566.4	12.5
140°-150°	529.7	11.7
150°-160°	427.3	9.5
160°-170°	275.7	6.1
170°-180°	95.0	2.1
0°-30°	458.6	10.1
0°-40°	750.1	16.6
0°-60°	1222.4	27.1
0°-90°	1468.4	32.5
90°-120°	626.0	13.9
90°-150°	2252.2	49.8
90°-180°	3050.0	67.5
0°-180°	4518.7	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	486	486	486	486	486	
5°	577	486	430	486	577	60
15°	859	465	351	465	859	248
25°	1019	424	310	424	1019	447
35°	549	372	285	372	549	357
45°	296	306	242	306	296	235
55°	201	215	192	215	201	181
65°	131	133	136	133	131	130
75°	67	63	72	63	67	72
85°	16	13	14	13	16	19
90°	22	1	22	1	22	11
95°	28	45	28	45	28	24
105°	33	222	33	222	33	75
115°	437	415	437	415	437	404
125°	597	586	597	586	597	534
135°	736	729	736	729	736	568
145°	849	841	849	841	849	530
155°	925	927	925	927	925	427
165°	975	977	975	977	975	275
175°	996	1000	996	1000	996	95
180°	1000	1000	1000	1000	1000	



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5
2.5°	515.3	514.9	514.0	514.7	513.2	511.2	511.0	509.1	503.6	503.3	501.8
5°	576.8	575.0	574.7	574.5	571.2	566.7	558.3	557.5	546.2	540.7	533.8
7.5°	656.6	657.5	654.1	651.2	641.1	634.4	625.3	613.7	599.9	585.7	576.4
10°	713.8	721.5	712.0	705.3	699.2	687.7	674.3	657.5	640.9	621.4	606.5
12.5°	775.2	778.9	777.0	770.8	761.3	743.8	720.0	701.6	686.2	653.7	640.6
15°	858.7	873.0	863.8	842.7	843.1	826.5	795.5	761.3	743.2	714.7	675.9
17.5°	947.8	949.5	945.6	928.0	916.3	893.2	864.5	831.9	795.2	760.7	719.5
20°	995.1	993.7	985.5	976.3	956.1	938.3	907.0	870.5	823.4	789.5	744.6
22.5°	1021.5	1019.2	1015.2	1007.5	990.8	971.6	943.4	903.6	858.8	812.1	760.2
25°	1019.2	1022.2	1022.7	1020.6	1014.7	1003.2	981.1	949.3	904.6	844.6	790.5
27.5°	927.0	931.3	943.8	955.0	967.5	980.2	978.5	962.7	929.6	877.8	811.6
30°	834.8	825.3	848.6	878.0	898.0	933.3	953.0	954.2	935.6	891.2	826.7
32.5°	706.7	717.1	727.4	763.6	807.3	846.9	886.3	917.9	921.5	891.9	835.6
35°	549.1	562.1	580.9	599.7	646.7	687.2	756.4	816.6	864.5	870.9	836.4
37.5°	442.5	448.9	460.8	479.7	510.4	558.5	611.9	688.0	757.6	809.3	811.5
40°	386.8	388.7	402.0	416.4	441.3	480.9	529.1	596.4	679.6	751.9	782.0
42.5°	345.0	349.1	354.9	368.6	388.5	418.2	463.0	518.7	595.0	678.1	737.0
45°	296.4	301.1	304.7	313.9	328.0	348.0	379.2	430.1	488.2	574.0	653.3
47.5°	264.4	264.7	267.3	274.3	283.9	298.9	321.0	353.7	407.0	476.7	558.1
50°	241.4	245.1	246.1	251.5	259.0	270.0	288.4	316.2	359.9	421.1	495.9
52.5°	225.2	226.3	228.9	232.9	239.4	248.0	264.0	285.7	320.0	372.2	441.0
55°	201.4	201.4	204.0	207.0	210.8	218.5	229.1	245.1	271.2	311.7	368.7
57.5°	179.4	180.6	182.4	183.3	186.5	191.7	200.5	212.7	232.1	263.3	308.5
60°	164.7	166.8	166.5	168.4	171.3	175.3	182.8	192.7	210.1	235.0	273.2
62.5°	151.9	151.8	151.7	154.0	156.7	160.6	165.5	174.0	188.8	211.0	243.4
65°	130.8	130.4	132.0	133.4	134.3	137.1	140.9	148.5	158.3	174.8	200.0
67.5°	112.1	110.7	111.6	112.1	113.7	115.9	119.5	124.1	131.9	145.1	164.1
70°	99.3	98.1	97.9	98.4	99.8	101.4	104.0	108.5	115.7	126.3	140.2
72.5°	86.1	85.3	85.2	86.3	86.9	88.1	89.9	93.9	99.8	107.8	120.7
75°	67.3	67.3	67.3	67.6	68.3	69.2	70.6	72.7	77.2	82.8	91.5
77.5°	50.4	50.4	50.1	50.1	51.1	51.5	51.8	53.8	56.4	60.1	66.4
80°	39.5	38.4	38.8	39.5	40.0	40.2	40.9	41.4	43.5	45.6	50.1
82.5°	29.4	28.4	28.5	29.6	29.7	29.9	30.6	31.2	32.0	33.9	36.4
85°	15.6	15.6	15.8	15.8	16.0	15.8	16.5	16.7	16.7	17.9	19.3
87.5°	10.1	9.7	9.8	9.9	9.7	9.7	9.8	9.9	9.9	10.0	9.7
90°	22.3	21.9	21.6	21.3	21.0	20.5	19.8	19.2	18.5	17.9	15.7
92.5°	24.6	24.4	24.2	24.0	23.8	23.2	22.2	21.1	20.1	19.0	17.4
95°	28.3	28.3	28.3	28.3	28.3	27.7	26.5	25.3	24.2	23.0	21.2
97.5°	30.6	30.5	30.3	30.1	30.0	29.2	27.9	26.6	25.2	23.9	35.9
100°	31.2	31.0	30.9	30.7	30.6	29.8	28.5	27.2	25.9	24.5	50.3
102.5°	31.8	31.5	31.2	30.9	30.6	32.5	36.7	40.7	44.8	48.9	77.1
105°	32.7	32.4	32.0	31.7	31.4	45.8	75.0	104.3	133.5	162.8	177.6
107.5°	102.7	124.7	146.7	168.7	190.9	212.6	234.0	255.4	276.8	298.3	296.0
110°	204.4	227.9	251.6	275.2	298.8	313.4	318.8	324.3	329.7	335.2	333.4



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	350.6	355.6	360.6	365.6	370.5	373.0	372.9	372.8	372.7	372.6	370.8
115°	437.0	436.3	435.7	434.9	434.3	433.1	431.5	429.9	428.2	426.6	425.1
117.5°	485.4	485.2	485.1	485.0	484.8	484.1	482.8	481.5	480.2	478.9	478.1
120°	518.7	518.7	518.7	518.7	518.7	518.1	516.7	515.4	514.1	512.7	512.3
122.5°	551.4	551.3	551.1	551.0	550.9	550.4	549.4	548.5	547.5	546.6	546.0
125°	597.4	597.1	596.8	596.5	596.1	595.8	595.5	595.1	594.8	594.5	593.8
127.5°	641.8	642.1	642.4	642.8	643.1	643.0	642.5	642.0	641.4	640.9	640.1
130°	670.2	670.7	671.0	671.3	671.7	671.5	670.8	670.1	669.4	668.8	668.1
132.5°	696.4	696.9	697.4	697.8	698.3	698.2	697.5	696.9	696.2	695.6	695.0
135°	736.4	736.9	737.4	737.9	738.4	738.4	737.9	737.4	736.9	736.4	735.8
137.5°	774.1	774.4	774.7	775.1	775.4	775.2	774.4	773.6	772.7	771.9	771.6
140°	796.6	797.0	797.3	797.6	798.0	797.8	797.1	796.5	795.8	795.2	794.7
142.5°	817.4	817.9	818.4	818.8	819.3	819.2	818.7	818.2	817.7	817.2	816.7
145°	849.4	849.4	849.4	849.4	849.4	849.2	848.9	848.6	848.2	847.9	847.6
147.5°	873.1	873.9	874.6	875.5	876.2	876.5	876.1	875.8	875.5	875.0	874.7
150°	891.0	891.5	892.0	892.5	893.0	893.0	892.7	892.4	892.1	891.7	891.4
152.5°	905.2	906.1	906.8	907.6	908.3	908.4	907.8	907.2	906.6	906.1	905.8
155°	925.1	926.1	927.2	928.2	929.2	929.3	928.4	927.6	926.8	925.9	925.7
157.5°	942.0	943.3	944.5	945.8	947.2	947.3	946.2	945.3	944.3	943.3	943.5
160°	952.7	953.8	955.0	956.1	957.4	957.4	956.4	955.4	954.4	953.4	953.6
162.5°	962.8	963.8	964.8	965.8	966.8	966.8	965.7	964.6	963.5	962.3	962.5
165°	974.9	976.1	977.2	978.5	979.6	979.5	978.2	976.8	975.5	974.2	974.4
167.5°	983.7	985.0	986.3	987.7	989.1	989.1	987.7	986.3	985.0	983.7	983.7
170°	989.1	990.4	991.7	993.1	994.4	994.4	993.1	991.7	990.4	989.1	989.1
172.5°	992.1	993.5	995.0	996.4	997.8	997.9	996.6	995.3	994.0	992.7	992.5
175°	996.5	997.8	999.2	1000.5	1001.8	1001.9	1000.8	999.6	998.5	997.2	997.1
177.5°	997.8	999.2	1000.5	1001.8	1003.1	1003.3	1002.2	1001.2	1000.1	999.1	999.0
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5
2.5°	500.6	499.2	497.7	495.0	492.7	489.6	488.6	487.5	484.0	481.1	478.8
5°	531.2	525.5	517.4	509.8	503.7	495.4	490.8	485.8	478.8	472.4	467.3
7.5°	563.2	552.1	539.3	525.5	512.6	500.2	490.2	481.2	471.3	462.0	454.6
10°	588.7	572.6	554.7	535.4	519.0	503.0	489.6	477.9	465.1	454.0	444.8
12.5°	617.6	593.9	569.3	545.8	526.3	504.1	487.9	472.9	458.5	445.2	434.9
15°	651.9	621.8	592.6	560.4	530.8	503.0	483.7	464.8	448.2	434.5	421.3
17.5°	683.2	649.0	610.6	571.4	535.6	502.7	475.7	454.4	433.5	416.9	403.7
20°	700.8	662.1	618.5	577.8	538.3	501.6	471.9	446.6	423.9	406.3	391.5
22.5°	716.1	670.7	625.6	582.1	538.1	498.6	464.9	438.8	414.3	397.1	381.3
25°	732.0	677.5	632.4	581.4	532.2	491.2	453.6	423.9	399.5	379.2	363.0
27.5°	745.5	677.1	623.5	568.6	522.8	481.8	441.6	409.8	383.8	361.8	345.4
30°	754.5	678.0	614.3	560.0	513.8	471.5	432.4	400.4	373.1	350.8	335.3
32.5°	760.1	677.4	605.8	547.9	499.5	462.0	422.4	389.3	361.2	339.3	324.4
35°	763.5	673.3	591.2	523.0	476.5	439.9	406.8	372.4	343.1	322.6	305.6
37.5°	756.8	664.6	574.3	499.0	448.0	412.1	384.2	355.0	326.8	304.3	289.6
40°	746.5	658.9	561.1	482.0	428.4	393.8	370.1	341.3	313.6	292.2	278.5
42.5°	726.7	647.5	546.6	463.2	408.1	373.5	351.6	327.6	301.3	281.2	267.6
45°	678.5	622.5	524.8	435.0	378.1	342.3	323.1	305.6	281.9	262.4	250.5
47.5°	611.6	584.9	493.4	405.3	346.7	312.4	292.3	278.3	260.9	245.1	233.9
50°	565.1	554.0	472.2	384.9	325.9	292.2	272.9	260.2	247.7	232.0	221.7
52.5°	511.5	518.3	447.4	363.9	304.6	271.5	253.4	243.3	232.0	218.9	210.0
55°	436.0	460.6	404.5	328.4	272.9	241.4	224.2	215.3	208.6	199.0	191.3
57.5°	365.3	396.7	358.0	292.0	241.8	214.6	198.1	188.4	184.2	179.2	173.0
60°	323.3	354.3	324.9	267.5	221.0	195.0	180.5	172.2	167.9	164.4	159.3
62.5°	285.8	317.2	292.6	242.7	200.4	176.4	163.7	155.6	152.4	150.6	146.1
65°	234.3	261.4	244.9	204.0	171.1	149.9	138.4	132.7	129.7	129.0	126.1
67.5°	190.7	211.3	199.3	169.2	143.3	125.0	115.2	110.4	108.1	107.8	105.6
70°	162.1	181.4	172.2	144.9	122.6	108.3	99.8	95.5	94.1	93.9	92.7
72.5°	139.9	153.3	146.0	123.3	106.0	93.0	86.7	82.3	80.8	81.1	80.3
75°	103.5	113.6	109.4	93.6	79.8	71.3	66.1	63.3	61.9	62.6	61.6
77.5°	74.5	80.9	77.1	66.1	57.6	51.5	47.7	45.9	44.6	44.6	44.2
80°	56.2	60.0	57.9	51.3	44.2	39.1	36.0	34.8	34.1	33.8	33.6
82.5°	40.1	43.2	40.7	36.3	31.4	28.3	26.6	25.0	24.5	24.6	24.4
85°	20.2	21.4	20.5	17.7	15.8	14.3	13.4	12.7	12.2	12.4	12.0
87.5°	9.7	9.4	8.5	7.3	6.6	5.7	5.4	4.6	4.6	4.9	5.0
90°	13.5	11.4	9.3	7.4	5.7	4.0	2.4	0.7	2.4	4.0	5.7
92.5°	15.8	14.1	12.5	12.0	12.4	12.9	13.3	13.8	13.3	12.9	12.4
95°	19.4	17.6	15.8	18.3	25.0	31.8	38.6	45.3	38.6	31.8	25.0
97.5°	47.7	59.6	71.5	79.0	82.0	85.0	88.1	91.1	88.1	85.0	82.0
100°	76.0	101.8	127.5	138.8	135.5	132.2	128.9	125.6	128.9	132.2	135.5
102.5°	105.1	133.3	161.5	174.3	172.0	169.6	167.2	164.8	167.2	169.6	172.0
105°	192.5	207.3	222.2	228.7	226.9	225.1	223.3	221.5	223.3	225.1	226.9
107.5°	293.6	291.2	288.9	287.0	285.6	284.1	282.7	281.1	282.7	284.1	285.6
110°	331.5	329.7	327.9	326.3	325.0	323.7	322.3	321.0	322.3	323.7	325.0



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	369.0	367.2	365.4	363.9	362.6	361.4	360.2	359.1	360.2	361.4	362.6
115°	423.5	422.1	420.6	419.4	418.4	417.4	416.4	415.4	416.4	417.4	418.4
117.5°	477.4	476.6	475.8	474.8	473.6	472.4	471.2	470.0	471.2	472.4	473.6
120°	511.8	511.3	510.8	509.8	508.3	506.9	505.3	503.8	505.3	506.9	508.3
122.5°	545.4	544.7	544.1	543.2	542.0	540.8	539.6	538.4	539.6	540.8	542.0
125°	593.2	592.5	591.9	590.9	589.6	588.2	586.9	585.6	586.9	588.2	589.6
127.5°	639.2	638.5	637.7	636.6	635.3	634.0	632.7	631.4	632.7	634.0	635.3
130°	667.5	666.8	666.2	665.2	663.9	662.6	661.3	659.8	661.3	662.6	663.9
132.5°	694.5	694.0	693.5	692.6	691.2	689.8	688.5	687.2	688.5	689.8	691.2
135°	735.1	734.5	733.8	733.0	732.0	730.9	730.0	729.0	730.0	730.9	732.0
137.5°	771.2	770.8	770.5	769.7	768.4	767.2	765.9	764.7	765.9	767.2	768.4
140°	794.2	793.7	793.1	792.4	791.4	790.4	789.4	788.4	789.4	790.4	791.4
142.5°	816.2	815.7	815.2	814.5	813.4	812.4	811.4	810.4	811.4	812.4	813.4
145°	847.3	846.9	846.6	845.9	844.7	843.5	842.3	841.2	842.3	843.5	844.7
147.5°	874.4	874.1	873.7	873.2	872.4	871.7	870.9	870.2	870.9	871.7	872.4
150°	891.1	890.8	890.4	890.0	889.5	889.0	888.5	888.1	888.5	889.0	889.5
152.5°	905.6	905.4	905.2	905.0	904.7	904.5	904.3	904.0	904.3	904.5	904.7
155°	925.6	925.4	925.2	925.3	925.6	926.0	926.3	926.7	926.3	926.0	925.6
157.5°	943.6	943.8	944.0	944.1	944.1	944.1	944.2	944.2	944.2	944.1	944.1
160°	953.7	953.9	954.1	954.2	954.4	954.6	954.7	954.9	954.7	954.6	954.4
162.5°	962.7	962.8	963.0	963.3	963.7	964.1	964.6	965.0	964.6	964.1	963.7
165°	974.5	974.7	974.9	975.2	975.7	976.2	976.7	977.2	976.7	976.2	975.7
167.5°	983.7	983.7	983.7	984.1	984.7	985.4	986.0	986.7	986.0	985.4	984.7
170°	989.1	989.1	989.1	989.5	990.1	990.8	991.4	992.1	991.4	990.8	990.1
172.5°	992.4	992.3	992.1	992.5	993.3	994.0	994.8	995.6	994.8	994.0	993.3
175°	996.9	996.7	996.6	996.9	997.7	998.6	999.4	1000.3	999.4	998.6	997.7
177.5°	998.8	998.7	998.6	998.8	999.5	1000.1	1000.8	1001.4	1000.8	1000.1	999.5
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5
2.5°	477.5	476.2	474.3	471.5	469.2	465.6	465.6	466.2	466.2	466.1	465.6
5°	463.0	459.5	455.2	450.3	445.1	439.9	439.0	437.1	435.8	434.7	433.6
7.5°	447.7	441.4	435.3	428.4	422.0	416.9	413.2	410.2	408.3	406.2	404.7
10°	437.4	429.6	422.3	415.1	407.0	400.6	396.7	393.8	391.7	389.8	388.9
12.5°	425.2	416.3	408.2	401.2	392.5	386.0	382.1	380.8	378.4	374.4	372.3
15°	407.3	399.0	389.4	378.8	374.6	366.6	362.0	359.9	358.5	355.5	354.6
17.5°	391.9	381.2	370.3	362.4	354.6	348.1	345.6	343.0	341.1	338.6	337.8
20°	379.7	370.1	360.2	351.7	343.5	336.4	334.3	332.4	330.5	329.4	328.4
22.5°	367.3	357.7	349.4	341.5	332.8	328.1	325.9	323.8	322.4	321.6	320.7
25°	349.8	341.3	332.1	325.2	318.1	315.0	313.6	312.5	311.4	310.3	310.0
27.5°	334.3	325.0	317.6	310.9	305.9	303.4	301.9	301.4	301.6	302.1	302.4
30°	322.6	314.1	308.0	302.4	297.6	295.3	295.0	295.0	296.0	296.2	296.7
32.5°	311.8	304.9	298.7	293.3	289.7	288.1	289.0	289.0	289.7	290.3	291.2
35°	296.2	290.0	285.4	280.6	277.6	278.3	278.8	279.2	280.4	281.9	282.8
37.5°	281.2	276.0	271.0	267.4	266.0	267.2	268.4	269.3	270.7	271.9	272.8
40°	270.5	266.5	261.9	258.5	259.0	259.7	260.6	261.9	263.1	263.8	264.7
42.5°	260.5	256.4	252.8	250.0	250.7	251.7	252.2	252.8	254.2	255.5	256.0
45°	245.4	242.1	238.8	237.1	237.6	238.1	238.5	239.2	240.4	241.4	241.7
47.5°	228.3	226.0	223.8	222.2	223.0	222.8	223.4	224.9	225.2	225.8	227.1
50°	217.4	215.3	212.7	212.2	212.2	212.2	212.5	214.3	214.3	215.3	216.2
52.5°	205.3	204.0	202.4	201.5	201.1	201.1	202.1	203.0	203.4	204.7	205.7
55°	187.5	186.1	184.7	184.0	183.5	184.0	185.8	186.3	187.5	188.2	188.9
57.5°	169.0	167.8	166.7	166.3	166.2	166.8	167.8	169.3	169.6	171.8	172.8
60°	156.7	155.0	154.1	154.1	153.6	155.7	155.3	157.6	158.1	159.6	161.2
62.5°	144.1	141.9	141.5	141.5	142.2	142.8	143.4	144.4	145.7	147.4	148.8
65°	123.7	122.6	124.2	124.0	123.5	124.9	124.9	126.1	127.5	129.2	131.8
67.5°	104.5	103.9	104.0	104.0	104.7	105.5	106.2	107.2	109.0	110.7	112.4
70°	91.5	92.2	91.1	92.0	92.7	92.9	93.4	94.8	96.6	97.9	99.8
72.5°	78.9	78.9	79.0	79.4	80.1	80.5	81.0	82.6	84.6	85.6	87.2
75°	60.7	60.5	61.2	61.2	62.3	62.8	63.3	64.0	65.8	67.3	68.5
77.5°	44.3	44.6	44.4	45.2	44.9	45.0	46.5	47.2	47.4	50.2	50.8
80°	33.4	33.8	34.1	34.3	34.5	34.1	35.7	36.5	36.5	38.1	39.3
82.5°	24.0	24.2	24.8	25.1	25.1	25.7	25.8	26.3	26.9	27.6	29.1
85°	12.0	12.7	12.9	12.7	12.9	12.4	13.1	13.4	13.6	13.6	13.6
87.5°	5.3	5.8	6.1	6.7	6.9	7.5	7.7	7.4	7.6	8.3	7.6
90°	7.4	9.3	11.4	13.5	15.7	17.9	18.5	19.2	19.8	20.5	21.0
92.5°	12.0	12.5	14.1	15.8	17.4	19.0	20.1	21.1	22.2	23.2	23.8
95°	18.3	15.8	17.6	19.4	21.2	23.0	24.2	25.3	26.5	27.7	28.3
97.5°	79.0	71.5	59.6	47.7	35.9	23.9	25.2	26.6	27.9	29.2	30.0
100°	138.8	127.5	101.8	76.0	50.3	24.5	25.9	27.2	28.5	29.8	30.6
102.5°	174.3	161.5	133.3	105.1	77.1	48.9	44.8	40.7	36.7	32.5	30.6
105°	228.7	222.2	207.3	192.5	177.6	162.8	133.5	104.3	75.0	45.8	31.4
107.5°	287.0	288.9	291.2	293.6	296.0	298.3	276.8	255.4	234.0	212.6	190.9
110°	326.3	327.9	329.7	331.5	333.4	335.2	329.7	324.3	318.8	313.4	298.8



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	363.9	365.4	367.2	369.0	370.8	372.6	372.7	372.8	372.9	373.0	370.5
115°	419.4	420.6	422.1	423.5	425.1	426.6	428.2	429.9	431.5	433.1	434.3
117.5°	474.8	475.8	476.6	477.4	478.1	478.9	480.2	481.5	482.8	484.1	484.8
120°	509.8	510.8	511.3	511.8	512.3	512.7	514.1	515.4	516.7	518.1	518.7
122.5°	543.2	544.1	544.7	545.4	546.0	546.6	547.5	548.5	549.4	550.4	550.9
125°	590.9	591.9	592.5	593.2	593.8	594.5	594.8	595.1	595.5	595.8	596.1
127.5°	636.6	637.7	638.5	639.2	640.1	640.9	641.4	642.0	642.5	643.0	643.1
130°	665.2	666.2	666.8	667.5	668.1	668.8	669.4	670.1	670.8	671.5	671.7
132.5°	692.6	693.5	694.0	694.5	695.0	695.6	696.2	696.9	697.5	698.2	698.3
135°	733.0	733.8	734.5	735.1	735.8	736.4	736.9	737.4	737.9	738.4	738.4
137.5°	769.7	770.5	770.8	771.2	771.6	771.9	772.7	773.6	774.4	775.2	775.4
140°	792.4	793.1	793.7	794.2	794.7	795.2	795.8	796.5	797.1	797.8	798.0
142.5°	814.5	815.2	815.7	816.2	816.7	817.2	817.7	818.2	818.7	819.2	819.3
145°	845.9	846.6	846.9	847.3	847.6	847.9	848.2	848.6	848.9	849.2	849.4
147.5°	873.2	873.7	874.1	874.4	874.7	875.0	875.5	875.8	876.1	876.5	876.2
150°	890.0	890.4	890.8	891.1	891.4	891.7	892.1	892.4	892.7	893.0	893.0
152.5°	905.0	905.2	905.4	905.6	905.8	906.1	906.6	907.2	907.8	908.4	908.3
155°	925.3	925.2	925.4	925.6	925.7	925.9	926.8	927.6	928.4	929.3	929.2
157.5°	944.1	944.0	943.8	943.6	943.5	943.3	944.3	945.3	946.2	947.3	947.2
160°	954.2	954.1	953.9	953.7	953.6	953.4	954.4	955.4	956.4	957.4	957.4
162.5°	963.3	963.0	962.8	962.7	962.5	962.3	963.5	964.6	965.7	966.8	966.8
165°	975.2	974.9	974.7	974.5	974.4	974.2	975.5	976.8	978.2	979.5	979.6
167.5°	984.1	983.7	983.7	983.7	983.7	983.7	985.0	986.3	987.7	989.1	989.1
170°	989.5	989.1	989.1	989.1	989.1	989.1	990.4	991.7	993.1	994.4	994.4
172.5°	992.5	992.1	992.3	992.4	992.5	992.7	994.0	995.3	996.6	997.9	997.8
175°	996.9	996.6	996.7	996.9	997.1	997.2	998.5	999.6	1000.8	1001.9	1001.8
177.5°	998.8	998.6	998.7	998.8	999.0	999.1	1000.1	1001.2	1002.2	1003.3	1003.1
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5
2.5°	464.3	464.1	465.4	464.5	465.4	464.1	464.3	465.6	466.1	466.2	466.2
5°	432.2	432.9	430.5	430.5	430.5	432.9	432.2	433.6	434.7	435.8	437.1
7.5°	403.5	402.5	402.6	401.3	402.6	402.5	403.5	404.7	406.2	408.3	410.2
10°	386.1	384.7	384.2	384.5	384.2	384.7	386.1	388.9	389.8	391.7	393.8
12.5°	371.5	371.3	368.2	368.2	368.2	371.3	371.5	372.3	374.4	378.4	380.8
15°	354.6	350.1	349.6	351.0	349.6	350.1	354.6	354.6	355.5	358.5	359.9
17.5°	337.5	335.1	335.3	334.6	335.3	335.1	337.5	337.8	338.6	341.1	343.0
20°	328.4	327.0	326.8	325.2	326.8	327.0	328.4	328.4	329.4	330.5	332.4
22.5°	320.1	319.7	319.8	318.0	319.8	319.7	320.1	320.7	321.6	322.4	323.8
25°	309.8	311.0	310.0	310.0	310.0	311.0	309.8	310.0	310.3	311.4	312.5
27.5°	302.9	302.9	302.4	302.4	302.4	302.9	302.9	302.4	302.1	301.6	301.4
30°	297.6	297.4	297.8	297.8	297.8	297.4	297.6	296.7	296.2	296.0	295.0
32.5°	292.4	292.7	292.8	293.0	292.8	292.7	292.4	291.2	290.3	289.7	289.0
35°	284.2	284.5	285.2	284.7	285.2	284.5	284.2	282.8	281.9	280.4	279.2
37.5°	273.2	274.3	274.1	274.4	274.1	274.3	273.2	272.8	271.9	270.7	269.3
40°	264.9	265.6	265.4	265.4	265.4	265.6	264.9	264.7	263.8	263.1	261.9
42.5°	256.4	256.9	256.3	256.0	256.3	256.9	256.4	256.0	255.5	254.2	252.8
45°	242.6	242.1	242.8	241.9	242.8	242.1	242.6	241.7	241.4	240.4	239.2
47.5°	227.0	227.5	227.7	228.4	227.7	227.5	227.0	227.1	225.8	225.2	224.9
50°	216.7	218.1	218.1	217.8	218.1	218.1	216.7	216.2	215.3	214.3	214.3
52.5°	206.5	207.1	208.1	208.0	208.1	207.1	206.5	205.7	204.7	203.4	203.0
55°	190.8	191.3	191.8	192.0	191.8	191.3	190.8	188.9	188.2	187.5	186.3
57.5°	174.5	174.3	175.4	175.8	175.4	174.3	174.5	172.8	171.8	169.6	169.3
60°	163.0	163.0	164.9	165.6	164.9	163.0	163.0	161.2	159.6	158.1	157.6
62.5°	150.8	151.6	153.4	152.5	153.4	151.6	150.8	148.8	147.4	145.7	144.4
65°	132.9	134.8	134.6	135.5	134.6	134.8	132.9	131.8	129.2	127.5	126.1
67.5°	114.2	115.4	117.1	117.2	117.1	115.4	114.2	112.4	110.7	109.0	107.2
70°	101.6	102.8	103.7	104.4	103.7	102.8	101.6	99.8	97.9	96.6	94.8
72.5°	89.4	90.0	92.3	91.3	92.3	90.0	89.4	87.2	85.6	84.6	82.6
75°	70.1	71.8	73.2	72.5	73.2	71.8	70.1	68.5	67.3	65.8	64.0
77.5°	51.8	53.5	54.1	53.5	54.1	53.5	51.8	50.8	50.2	47.4	47.2
80°	40.9	40.7	42.1	41.9	42.1	40.7	40.9	39.3	38.1	36.5	36.5
82.5°	30.0	29.8	30.4	30.6	30.4	29.8	30.0	29.1	27.6	26.9	26.3
85°	14.5	15.2	14.3	14.1	14.3	15.2	14.5	13.6	13.6	13.6	13.4
87.5°	7.7	7.7	7.6	7.5	7.6	7.7	7.7	7.6	8.3	7.6	7.4
90°	21.3	21.6	21.9	22.3	21.9	21.6	21.3	21.0	20.5	19.8	19.2
92.5°	24.0	24.2	24.4	24.6	24.4	24.2	24.0	23.8	23.2	22.2	21.1
95°	28.3	28.3	28.3	28.3	28.3	28.3	28.3	28.3	27.7	26.5	25.3
97.5°	30.1	30.3	30.5	30.6	30.5	30.3	30.1	30.0	29.2	27.9	26.6
100°	30.7	30.9	31.0	31.2	31.0	30.9	30.7	30.6	29.8	28.5	27.2
102.5°	30.9	31.2	31.5	31.8	31.5	31.2	30.9	30.6	32.5	36.7	40.7
105°	31.7	32.0	32.4	32.7	32.4	32.0	31.7	31.4	45.8	75.0	104.3
107.5°	168.7	146.7	124.7	102.7	124.7	146.7	168.7	190.9	212.6	234.0	255.4
110°	275.2	251.6	227.9	204.4	227.9	251.6	275.2	298.8	313.4	318.8	324.3



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	365.6	360.6	355.6	350.6	355.6	360.6	365.6	370.5	373.0	372.9	372.8
115°	434.9	435.7	436.3	437.0	436.3	435.7	434.9	434.3	433.1	431.5	429.9
117.5°	485.0	485.1	485.2	485.4	485.2	485.1	485.0	484.8	484.1	482.8	481.5
120°	518.7	518.7	518.7	518.7	518.7	518.7	518.7	518.7	518.1	516.7	515.4
122.5°	551.0	551.1	551.3	551.4	551.3	551.1	551.0	550.9	550.4	549.4	548.5
125°	596.5	596.8	597.1	597.4	597.1	596.8	596.5	596.1	595.8	595.5	595.1
127.5°	642.8	642.4	642.1	641.8	642.1	642.4	642.8	643.1	643.0	642.5	642.0
130°	671.3	671.0	670.7	670.2	670.7	671.0	671.3	671.7	671.5	670.8	670.1
132.5°	697.8	697.4	696.9	696.4	696.9	697.4	697.8	698.3	698.2	697.5	696.9
135°	737.9	737.4	736.9	736.4	736.9	737.4	737.9	738.4	738.4	737.9	737.4
137.5°	775.1	774.7	774.4	774.1	774.4	774.7	775.1	775.4	775.2	774.4	773.6
140°	797.6	797.3	797.0	796.6	797.0	797.3	797.6	798.0	797.8	797.1	796.5
142.5°	818.8	818.4	817.9	817.4	817.9	818.4	818.8	819.3	819.2	818.7	818.2
145°	849.4	849.4	849.4	849.4	849.4	849.4	849.4	849.4	849.2	848.9	848.6
147.5°	875.5	874.6	873.9	873.1	873.9	874.6	875.5	876.2	876.5	876.1	875.8
150°	892.5	892.0	891.5	891.0	891.5	892.0	892.5	893.0	893.0	892.7	892.4
152.5°	907.6	906.8	906.1	905.2	906.1	906.8	907.6	908.3	908.4	907.8	907.2
155°	928.2	927.2	926.1	925.1	926.1	927.2	928.2	929.2	929.3	928.4	927.6
157.5°	945.8	944.5	943.3	942.0	943.3	944.5	945.8	947.2	947.3	946.2	945.3
160°	956.1	955.0	953.8	952.7	953.8	955.0	956.1	957.4	957.4	956.4	955.4
162.5°	965.8	964.8	963.8	962.8	963.8	964.8	965.8	966.8	966.8	965.7	964.6
165°	978.5	977.2	976.1	974.9	976.1	977.2	978.5	979.6	979.5	978.2	976.8
167.5°	987.7	986.3	985.0	983.7	985.0	986.3	987.7	989.1	989.1	987.7	986.3
170°	993.1	991.7	990.4	989.1	990.4	991.7	993.1	994.4	994.4	993.1	991.7
172.5°	996.4	995.0	993.5	992.1	993.5	995.0	996.4	997.8	997.9	996.6	995.3
175°	1000.5	999.2	997.8	996.5	997.8	999.2	1000.5	1001.8	1001.9	1000.8	999.6
177.5°	1001.8	1000.5	999.2	997.8	999.2	1000.5	1001.8	1003.1	1003.3	1002.2	1001.2
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5
2.5°	465.6	465.6	469.2	471.5	474.3	476.2	477.5	478.8	481.1	484.0	487.5
5°	439.0	439.9	445.1	450.3	455.2	459.5	463.0	467.3	472.4	478.8	485.8
7.5°	413.2	416.9	422.0	428.4	435.3	441.4	447.7	454.6	462.0	471.3	481.2
10°	396.7	400.6	407.0	415.1	422.3	429.6	437.4	444.8	454.0	465.1	477.9
12.5°	382.1	386.0	392.5	401.2	408.2	416.3	425.2	434.9	445.2	458.5	472.9
15°	362.0	366.6	374.6	378.8	389.4	399.0	407.3	421.3	434.5	448.2	464.8
17.5°	345.6	348.1	354.6	362.4	370.3	381.2	391.9	403.7	416.9	433.5	454.4
20°	334.3	336.4	343.5	351.7	360.2	370.1	379.7	391.5	406.3	423.9	446.6
22.5°	325.9	328.1	332.8	341.5	349.4	357.7	367.3	381.3	397.1	414.3	438.8
25°	313.6	315.0	318.1	325.2	332.1	341.3	349.8	363.0	379.2	399.5	423.9
27.5°	301.9	303.4	305.9	310.9	317.6	325.0	334.3	345.4	361.8	383.8	409.8
30°	295.0	295.3	297.6	302.4	308.0	314.1	322.6	335.3	350.8	373.1	400.4
32.5°	289.0	288.1	289.7	293.3	298.7	304.9	311.8	324.4	339.3	361.2	389.3
35°	278.8	278.3	277.6	280.6	285.4	290.0	296.2	305.6	322.6	343.1	372.4
37.5°	268.4	267.2	266.0	267.4	271.0	276.0	281.2	289.6	304.3	326.8	355.0
40°	260.6	259.7	259.0	258.5	261.9	266.5	270.5	278.5	292.2	313.6	341.3
42.5°	252.2	251.7	250.7	250.0	252.8	256.4	260.5	267.6	281.2	301.3	327.6
45°	238.5	238.1	237.6	237.1	238.8	242.1	245.4	250.5	262.4	281.9	305.6
47.5°	223.4	222.8	223.0	222.2	223.8	226.0	228.3	233.9	245.1	260.9	278.3
50°	212.5	212.2	212.2	212.2	212.7	215.3	217.4	221.7	232.0	247.7	260.2
52.5°	202.1	201.1	201.1	201.5	202.4	204.0	205.3	210.0	218.9	232.0	243.3
55°	185.8	184.0	183.5	184.0	184.7	186.1	187.5	191.3	199.0	208.6	215.3
57.5°	167.8	166.8	166.2	166.3	166.7	167.8	169.0	173.0	179.2	184.2	188.4
60°	155.3	155.7	153.6	154.1	154.1	155.0	156.7	159.3	164.4	167.9	172.2
62.5°	143.4	142.8	142.2	141.5	141.5	141.9	144.1	146.1	150.6	152.4	155.6
65°	124.9	124.9	123.5	124.0	124.2	122.6	123.7	126.1	129.0	129.7	132.7
67.5°	106.2	105.5	104.7	104.0	104.0	103.9	104.5	105.6	107.8	108.1	110.4
70°	93.4	92.9	92.7	92.0	91.1	92.2	91.5	92.7	93.9	94.1	95.5
72.5°	81.0	80.5	80.1	79.4	79.0	78.9	78.9	80.3	81.1	80.8	82.3
75°	63.3	62.8	62.3	61.2	61.2	60.5	60.7	61.6	62.6	61.9	63.3
77.5°	46.5	45.0	44.9	45.2	44.4	44.6	44.3	44.2	44.6	44.6	45.9
80°	35.7	34.1	34.5	34.3	34.1	33.8	33.4	33.6	33.8	34.1	34.8
82.5°	25.8	25.7	25.1	25.1	24.8	24.2	24.0	24.4	24.6	24.5	25.0
85°	13.1	12.4	12.9	12.7	12.9	12.7	12.0	12.0	12.4	12.2	12.7
87.5°	7.7	7.5	6.9	6.7	6.1	5.8	5.3	5.0	4.9	4.6	4.6
90°	18.5	17.9	15.7	13.5	11.4	9.3	7.4	5.7	4.0	2.4	0.7
92.5°	20.1	19.0	17.4	15.8	14.1	12.5	12.0	12.4	12.9	13.3	13.8
95°	24.2	23.0	21.2	19.4	17.6	15.8	18.3	25.0	31.8	38.6	45.3
97.5°	25.2	23.9	35.9	47.7	59.6	71.5	79.0	82.0	85.0	88.1	91.1
100°	25.9	24.5	50.3	76.0	101.8	127.5	138.8	135.5	132.2	128.9	125.6
102.5°	44.8	48.9	77.1	105.1	133.3	161.5	174.3	172.0	169.6	167.2	164.8
105°	133.5	162.8	177.6	192.5	207.3	222.2	228.7	226.9	225.1	223.3	221.5
107.5°	276.8	298.3	296.0	293.6	291.2	288.9	287.0	285.6	284.1	282.7	281.1
110°	329.7	335.2	333.4	331.5	329.7	327.9	326.3	325.0	323.7	322.3	321.0



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	372.7	372.6	370.8	369.0	367.2	365.4	363.9	362.6	361.4	360.2	359.1
115°	428.2	426.6	425.1	423.5	422.1	420.6	419.4	418.4	417.4	416.4	415.4
117.5°	480.2	478.9	478.1	477.4	476.6	475.8	474.8	473.6	472.4	471.2	470.0
120°	514.1	512.7	512.3	511.8	511.3	510.8	509.8	508.3	506.9	505.3	503.8
122.5°	547.5	546.6	546.0	545.4	544.7	544.1	543.2	542.0	540.8	539.6	538.4
125°	594.8	594.5	593.8	593.2	592.5	591.9	590.9	589.6	588.2	586.9	585.6
127.5°	641.4	640.9	640.1	639.2	638.5	637.7	636.6	635.3	634.0	632.7	631.4
130°	669.4	668.8	668.1	667.5	666.8	666.2	665.2	663.9	662.6	661.3	659.8
132.5°	696.2	695.6	695.0	694.5	694.0	693.5	692.6	691.2	689.8	688.5	687.2
135°	736.9	736.4	735.8	735.1	734.5	733.8	733.0	732.0	730.9	730.0	729.0
137.5°	772.7	771.9	771.6	771.2	770.8	770.5	769.7	768.4	767.2	765.9	764.7
140°	795.8	795.2	794.7	794.2	793.7	793.1	792.4	791.4	790.4	789.4	788.4
142.5°	817.7	817.2	816.7	816.2	815.7	815.2	814.5	813.4	812.4	811.4	810.4
145°	848.2	847.9	847.6	847.3	846.9	846.6	845.9	844.7	843.5	842.3	841.2
147.5°	875.5	875.0	874.7	874.4	874.1	873.7	873.2	872.4	871.7	870.9	870.2
150°	892.1	891.7	891.4	891.1	890.8	890.4	890.0	889.5	889.0	888.5	888.1
152.5°	906.6	906.1	905.8	905.6	905.4	905.2	905.0	904.7	904.5	904.3	904.0
155°	926.8	925.9	925.7	925.6	925.4	925.2	925.3	925.6	926.0	926.3	926.7
157.5°	944.3	943.3	943.5	943.6	943.8	944.0	944.1	944.1	944.1	944.2	944.2
160°	954.4	953.4	953.6	953.7	953.9	954.1	954.2	954.4	954.6	954.7	954.9
162.5°	963.5	962.3	962.5	962.7	962.8	963.0	963.3	963.7	964.1	964.6	965.0
165°	975.5	974.2	974.4	974.5	974.7	974.9	975.2	975.7	976.2	976.7	977.2
167.5°	985.0	983.7	983.7	983.7	983.7	983.7	984.1	984.7	985.4	986.0	986.7
170°	990.4	989.1	989.1	989.1	989.1	989.1	989.5	990.1	990.8	991.4	992.1
172.5°	994.0	992.7	992.5	992.4	992.3	992.1	992.5	993.3	994.0	994.8	995.6
175°	998.5	997.2	997.1	996.9	996.7	996.6	996.9	997.7	998.6	999.4	1000.3
177.5°	1000.1	999.1	999.0	998.8	998.7	998.6	998.8	999.5	1000.1	1000.8	1001.4
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5	485.5
2.5°	488.6	489.6	492.7	495.0	497.7	499.2	500.6	501.8	503.3	503.6	509.1
5°	490.8	495.4	503.7	509.8	517.4	525.5	531.2	533.8	540.7	546.2	557.5
7.5°	490.2	500.2	512.6	525.5	539.3	552.1	563.2	576.4	585.7	599.9	613.7
10°	489.6	503.0	519.0	535.4	554.7	572.6	588.7	606.5	621.4	640.9	657.5
12.5°	487.9	504.1	526.3	545.8	569.3	593.9	617.6	640.6	653.7	686.2	701.6
15°	483.7	503.0	530.8	560.4	592.6	621.8	651.9	675.9	714.7	743.2	761.3
17.5°	475.7	502.7	535.6	571.4	610.6	649.0	683.2	719.5	760.7	795.2	831.9
20°	471.9	501.6	538.3	577.8	618.5	662.1	700.8	744.6	789.5	823.4	870.5
22.5°	464.9	498.6	538.1	582.1	625.6	670.7	716.1	760.2	812.1	858.8	903.6
25°	453.6	491.2	532.2	581.4	632.4	677.5	732.0	790.5	844.6	904.6	949.3
27.5°	441.6	481.8	522.8	568.6	623.5	677.1	745.5	811.6	877.8	929.6	962.7
30°	432.4	471.5	513.8	560.0	614.3	678.0	754.5	826.7	891.2	935.6	954.2
32.5°	422.4	462.0	499.5	547.9	605.8	677.4	760.1	835.6	891.9	921.5	917.9
35°	406.8	439.9	476.5	523.0	591.2	673.3	763.5	836.4	870.9	864.5	816.6
37.5°	384.2	412.1	448.0	499.0	574.3	664.6	756.8	811.5	809.3	757.6	688.0
40°	370.1	393.8	428.4	482.0	561.1	658.9	746.5	782.0	751.9	679.6	596.4
42.5°	351.6	373.5	408.1	463.2	546.6	647.5	726.7	737.0	678.1	595.0	518.7
45°	323.1	342.3	378.1	435.0	524.8	622.5	678.5	653.3	574.0	488.2	430.1
47.5°	292.3	312.4	346.7	405.3	493.4	584.9	611.6	558.1	476.7	407.0	353.7
50°	272.9	292.2	325.9	384.9	472.2	554.0	565.1	495.9	421.1	359.9	316.2
52.5°	253.4	271.5	304.6	363.9	447.4	518.3	511.5	441.0	372.2	320.0	285.7
55°	224.2	241.4	272.9	328.4	404.5	460.6	436.0	368.7	311.7	271.2	245.1
57.5°	198.1	214.6	241.8	292.0	358.0	396.7	365.3	308.5	263.3	232.1	212.7
60°	180.5	195.0	221.0	267.5	324.9	354.3	323.3	273.2	235.0	210.1	192.7
62.5°	163.7	176.4	200.4	242.7	292.6	317.2	285.8	243.4	211.0	188.8	174.0
65°	138.4	149.9	171.1	204.0	244.9	261.4	234.3	200.0	174.8	158.3	148.5
67.5°	115.2	125.0	143.3	169.2	199.3	211.3	190.7	164.1	145.1	131.9	124.1
70°	99.8	108.3	122.6	144.9	172.2	181.4	162.1	140.2	126.3	115.7	108.5
72.5°	86.7	93.0	106.0	123.3	146.0	153.3	139.9	120.7	107.8	99.8	93.9
75°	66.1	71.3	79.8	93.6	109.4	113.6	103.5	91.5	82.8	77.2	72.7
77.5°	47.7	51.5	57.6	66.1	77.1	80.9	74.5	66.4	60.1	56.4	53.8
80°	36.0	39.1	44.2	51.3	57.9	60.0	56.2	50.1	45.6	43.5	41.4
82.5°	26.6	28.3	31.4	36.3	40.7	43.2	40.1	36.4	33.9	32.0	31.2
85°	13.4	14.3	15.8	17.7	20.5	21.4	20.2	19.3	17.9	16.7	16.7
87.5°	5.4	5.7	6.6	7.3	8.5	9.4	9.7	9.7	10.0	9.9	9.9
90°	2.4	4.0	5.7	7.4	9.3	11.4	13.5	15.7	17.9	18.5	19.2
92.5°	13.3	12.9	12.4	12.0	12.5	14.1	15.8	17.4	19.0	20.1	21.1
95°	38.6	31.8	25.0	18.3	15.8	17.6	19.4	21.2	23.0	24.2	25.3
97.5°	88.1	85.0	82.0	79.0	71.5	59.6	47.7	35.9	23.9	25.2	26.6
100°	128.9	132.2	135.5	138.8	127.5	101.8	76.0	50.3	24.5	25.9	27.2
102.5°	167.2	169.6	172.0	174.3	161.5	133.3	105.1	77.1	48.9	44.8	40.7
105°	223.3	225.1	226.9	228.7	222.2	207.3	192.5	177.6	162.8	133.5	104.3
107.5°	282.7	284.1	285.6	287.0	288.9	291.2	293.6	296.0	298.3	276.8	255.4
110°	322.3	323.7	325.0	326.3	327.9	329.7	331.5	333.4	335.2	329.7	324.3



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	360.2	361.4	362.6	363.9	365.4	367.2	369.0	370.8	372.6	372.7	372.8
115°	416.4	417.4	418.4	419.4	420.6	422.1	423.5	425.1	426.6	428.2	429.9
117.5°	471.2	472.4	473.6	474.8	475.8	476.6	477.4	478.1	478.9	480.2	481.5
120°	505.3	506.9	508.3	509.8	510.8	511.3	511.8	512.3	512.7	514.1	515.4
122.5°	539.6	540.8	542.0	543.2	544.1	544.7	545.4	546.0	546.6	547.5	548.5
125°	586.9	588.2	589.6	590.9	591.9	592.5	593.2	593.8	594.5	594.8	595.1
127.5°	632.7	634.0	635.3	636.6	637.7	638.5	639.2	640.1	640.9	641.4	642.0
130°	661.3	662.6	663.9	665.2	666.2	666.8	667.5	668.1	668.8	669.4	670.1
132.5°	688.5	689.8	691.2	692.6	693.5	694.0	694.5	695.0	695.6	696.2	696.9
135°	730.0	730.9	732.0	733.0	733.8	734.5	735.1	735.8	736.4	736.9	737.4
137.5°	765.9	767.2	768.4	769.7	770.5	770.8	771.2	771.6	771.9	772.7	773.6
140°	789.4	790.4	791.4	792.4	793.1	793.7	794.2	794.7	795.2	795.8	796.5
142.5°	811.4	812.4	813.4	814.5	815.2	815.7	816.2	816.7	817.2	817.7	818.2
145°	842.3	843.5	844.7	845.9	846.6	846.9	847.3	847.6	847.9	848.2	848.6
147.5°	870.9	871.7	872.4	873.2	873.7	874.1	874.4	874.7	875.0	875.5	875.8
150°	888.5	889.0	889.5	890.0	890.4	890.8	891.1	891.4	891.7	892.1	892.4
152.5°	904.3	904.5	904.7	905.0	905.2	905.4	905.6	905.8	906.1	906.6	907.2
155°	926.3	926.0	925.6	925.3	925.2	925.4	925.6	925.7	925.9	926.8	927.6
157.5°	944.2	944.1	944.1	944.1	944.0	943.8	943.6	943.5	943.3	944.3	945.3
160°	954.7	954.6	954.4	954.2	954.1	953.9	953.7	953.6	953.4	954.4	955.4
162.5°	964.6	964.1	963.7	963.3	963.0	962.8	962.7	962.5	962.3	963.5	964.6
165°	976.7	976.2	975.7	975.2	974.9	974.7	974.5	974.4	974.2	975.5	976.8
167.5°	986.0	985.4	984.7	984.1	983.7	983.7	983.7	983.7	983.7	985.0	986.3
170°	991.4	990.8	990.1	989.5	989.1	989.1	989.1	989.1	989.1	990.4	991.7
172.5°	994.8	994.0	993.3	992.5	992.1	992.3	992.4	992.5	992.7	994.0	995.3
175°	999.4	998.6	997.7	996.9	996.6	996.7	996.9	997.1	997.2	998.5	999.6
177.5°	1000.8	1000.1	999.5	998.8	998.6	998.7	998.8	999.0	999.1	1000.1	1001.2
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	485.5	485.5	485.5	485.5	485.5	485.5	485.5
2.5°	511.0	511.2	513.2	514.7	514.0	514.9	515.3
5°	558.3	566.7	571.2	574.5	574.7	575.0	576.8
7.5°	625.3	634.4	641.1	651.2	654.1	657.5	656.6
10°	674.3	687.7	699.2	705.3	712.0	721.5	713.8
12.5°	720.0	743.8	761.3	770.8	777.0	778.9	775.2
15°	795.5	826.5	843.1	842.7	863.8	873.0	858.7
17.5°	864.5	893.2	916.3	928.0	945.6	949.5	947.8
20°	907.0	938.3	956.1	976.3	985.5	993.7	995.1
22.5°	943.4	971.6	990.8	1007.5	1015.2	1019.2	1021.5
25°	981.1	1003.2	1014.7	1020.6	1022.7	1022.2	1019.2
27.5°	978.5	980.2	967.5	955.0	943.8	931.3	927.0
30°	953.0	933.3	898.0	878.0	848.6	825.3	834.8
32.5°	886.3	846.9	807.3	763.6	727.4	717.1	706.7
35°	756.4	687.2	646.7	599.7	580.9	562.1	549.1
37.5°	611.9	558.5	510.4	479.7	460.8	448.9	442.5
40°	529.1	480.9	441.3	416.4	402.0	388.7	386.8
42.5°	463.0	418.2	388.5	368.6	354.9	349.1	345.0
45°	379.2	348.0	328.0	313.9	304.7	301.1	296.4
47.5°	321.0	298.9	283.9	274.3	267.3	264.7	264.4
50°	288.4	270.0	259.0	251.5	246.1	245.1	241.4
52.5°	264.0	248.0	239.4	232.9	228.9	226.3	225.2
55°	229.1	218.5	210.8	207.0	204.0	201.4	201.4
57.5°	200.5	191.7	186.5	183.3	182.4	180.6	179.4
60°	182.8	175.3	171.3	168.4	166.5	166.8	164.7
62.5°	165.5	160.6	156.7	154.0	151.7	151.8	151.9
65°	140.9	137.1	134.3	133.4	132.0	130.4	130.8
67.5°	119.5	115.9	113.7	112.1	111.6	110.7	112.1
70°	104.0	101.4	99.8	98.4	97.9	98.1	99.3
72.5°	89.9	88.1	86.9	86.3	85.2	85.3	86.1
75°	70.6	69.2	68.3	67.6	67.3	67.3	67.3
77.5°	51.8	51.5	51.1	50.1	50.1	50.4	50.4
80°	40.9	40.2	40.0	39.5	38.8	38.4	39.5
82.5°	30.6	29.9	29.7	29.6	28.5	28.4	29.4
85°	16.5	15.8	16.0	15.8	15.8	15.6	15.6
87.5°	9.8	9.7	9.7	9.9	9.8	9.7	10.1
90°	19.8	20.5	21.0	21.3	21.6	21.9	22.3
92.5°	22.2	23.2	23.8	24.0	24.2	24.4	24.6
95°	26.5	27.7	28.3	28.3	28.3	28.3	28.3
97.5°	27.9	29.2	30.0	30.1	30.3	30.5	30.6
100°	28.5	29.8	30.6	30.7	30.9	31.0	31.2
102.5°	36.7	32.5	30.6	30.9	31.2	31.5	31.8
105°	75.0	45.8	31.4	31.7	32.0	32.4	32.7
107.5°	234.0	212.6	190.9	168.7	146.7	124.7	102.7
110°	318.8	313.4	298.8	275.2	251.6	227.9	204.4



TEST NUMBER: P332096-840

CATALOG NUMBER: S123DIW-S340D755U840-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	372.9	373.0	370.5	365.6	360.6	355.6	350.6
115°	431.5	433.1	434.3	434.9	435.7	436.3	437.0
117.5°	482.8	484.1	484.8	485.0	485.1	485.2	485.4
120°	516.7	518.1	518.7	518.7	518.7	518.7	518.7
122.5°	549.4	550.4	550.9	551.0	551.1	551.3	551.4
125°	595.5	595.8	596.1	596.5	596.8	597.1	597.4
127.5°	642.5	643.0	643.1	642.8	642.4	642.1	641.8
130°	670.8	671.5	671.7	671.3	671.0	670.7	670.2
132.5°	697.5	698.2	698.3	697.8	697.4	696.9	696.4
135°	737.9	738.4	738.4	737.9	737.4	736.9	736.4
137.5°	774.4	775.2	775.4	775.1	774.7	774.4	774.1
140°	797.1	797.8	798.0	797.6	797.3	797.0	796.6
142.5°	818.7	819.2	819.3	818.8	818.4	817.9	817.4
145°	848.9	849.2	849.4	849.4	849.4	849.4	849.4
147.5°	876.1	876.5	876.2	875.5	874.6	873.9	873.1
150°	892.7	893.0	893.0	892.5	892.0	891.5	891.0
152.5°	907.8	908.4	908.3	907.6	906.8	906.1	905.2
155°	928.4	929.3	929.2	928.2	927.2	926.1	925.1
157.5°	946.2	947.3	947.2	945.8	944.5	943.3	942.0
160°	956.4	957.4	957.4	956.1	955.0	953.8	952.7
162.5°	965.7	966.8	966.8	965.8	964.8	963.8	962.8
165°	978.2	979.5	979.6	978.5	977.2	976.1	974.9
167.5°	987.7	989.1	989.1	987.7	986.3	985.0	983.7
170°	993.1	994.4	994.4	993.1	991.7	990.4	989.1
172.5°	996.6	997.9	997.8	996.4	995.0	993.5	992.1
175°	1000.8	1001.9	1001.8	1000.5	999.2	997.8	996.5
177.5°	1002.2	1003.3	1003.1	1001.8	1000.5	999.2	997.8
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3

(END OF REPORT)