

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P332475-840

Luminaire Tested: **S123RDIW-S1165D755U840-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P332475-840
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-9,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S123RDIW-S1165D755U840-4F0-1E-UDD-A1
Description: DEFINE 3 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 1165 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING
UPLIGHT 755 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7263.0 lumens
Efficiency: N/A
Efficacy: 121.5 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.22 / 1.36
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')
CIE Type: Semi-Direct


Input Watts (W): 59.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

Luminous Intensity Polar Plot





TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	110	110	110	110	104	104	104	104	91	91	91	79	79	79	69	69	69	64
1	102	97	94	90	95	92	88	86	81	78	76	71	69	68	62	61	59	55
2	93	86	80	75	87	81	76	71	72	68	64	63	60	58	55	53	51	47
3	85	76	69	64	80	72	66	61	64	59	55	57	53	50	50	47	44	41
4	79	68	60	54	74	64	57	52	57	52	48	51	47	43	45	42	39	36
5	72	61	53	47	68	58	51	45	52	46	42	46	42	38	41	37	34	32
6	67	55	47	41	63	52	45	40	47	41	37	42	37	34	37	34	31	28
7	62	50	42	37	58	48	40	35	43	37	33	38	34	30	34	30	27	25
8	58	46	38	33	54	43	36	32	39	33	29	35	30	27	32	28	25	23
9	54	42	34	29	51	40	33	28	36	30	26	33	28	24	29	25	23	21
10	51	39	31	27	48	37	30	26	33	28	24	30	26	22	27	23	21	19

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	19957	19957	19957	19957
5°	23791	20042	17650	20042
10°	29704	19928	15946	19928
15°	34867	19724	14540	19724
20°	38913	19420	13347	19420
25°	38292	19099	12613	19099
30°	27524	18804	11857	18804
35°	18378	18419	11369	18419
40°	13540	17956	10863	17956
45°	11357	17145	10368	17145
50°	10021	16083	9676	16083
55°	8788	14865	8728	14865
60°	7828	13702	7995	13702
65°	6872	12455	7440	12455
70°	5397	11339	6795	11339
75°	4754	9902	6209	9902
80°	4135	8412	6106	8412
85°	3335	6756	6472	6756



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	182.3	2.5
10°-20°	569.6	7.8
20°-30°	894.9	12.3
30°-40°	933.7	12.9
40°-50°	799.0	11.0
50°-60°	609.0	8.4
60°-70°	390.4	5.4
70°-80°	187.8	2.6
80°-90°	52.5	0.7
90°-100°	62.2	0.9
100°-110°	186.1	2.6
110°-120°	316.4	4.4
120°-130°	416.2	5.7
130°-140°	467.8	6.4
140°-150°	459.9	6.3
150°-160°	387.1	5.3
160°-170°	257.7	3.5
170°-180°	90.2	1.2
0°-30°	1646.9	22.7
0°-40°	2580.6	35.5
0°-60°	3988.6	54.9
0°-90°	4619.3	63.6
90°-120°	564.7	7.8
90°-150°	1908.6	26.3
90°-180°	2644.0	36.4
0°-180°	7263.0	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1854	1854	1854	1854	1854	
5°	2202	1855	1634	1855	2202	227
15°	3129	1770	1305	1770	3129	887
25°	3224	1608	1062	1608	3224	1386
35°	1399	1402	865	1402	1399	917
45°	746	1126	681	1126	746	587
55°	468	792	465	792	468	423
65°	270	489	292	489	270	265
75°	114	238	149	238	114	123
85°	27	55	52	55	27	32
90°	22	1	22	1	22	12
95°	58	44	58	44	58	60
105°	178	169	178	169	178	189
115°	319	319	319	319	319	316
125°	461	466	461	466	461	412
135°	604	605	604	605	604	464
145°	734	734	734	734	734	458
155°	839	840	839	840	839	386
165°	912	915	912	915	912	257
175°	948	952	948	952	948	90
180°	954	954	954	954	954	



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1
2.5°	1974.8	1977.3	1969.0	1967.8	1958.2	1955.7	1955.7	1942.4	1934.1	1923.4	1917.0
5°	2201.8	2214.5	2208.2	2193.8	2170.0	2164.4	2149.4	2125.6	2098.6	2065.3	2049.4
7.5°	2485.3	2502.6	2496.0	2473.9	2448.9	2428.8	2386.2	2346.7	2291.3	2242.7	2201.1
10°	2717.7	2699.5	2685.1	2663.7	2640.7	2603.4	2559.0	2497.8	2427.2	2371.7	2309.8
12.5°	2891.6	2888.7	2870.5	2848.5	2816.0	2780.6	2725.9	2651.5	2569.4	2489.1	2418.3
15°	3128.9	3133.6	3121.7	3098.7	3052.6	2989.9	2907.4	2876.5	2759.0	2671.7	2584.3
17.5°	3293.0	3292.1	3290.4	3258.5	3211.6	3166.9	3090.4	3009.0	2902.7	2779.7	2662.0
20°	3397.1	3389.2	3390.8	3355.1	3320.1	3268.5	3193.9	3075.6	2988.4	2846.3	2724.8
22.5°	3394.6	3393.0	3399.0	3386.8	3361.4	3321.8	3263.2	3163.3	3051.9	2908.5	2771.9
25°	3224.1	3217.7	3255.1	3265.4	3305.9	3313.0	3295.5	3240.8	3135.2	2987.6	2818.5
27.5°	2698.4	2694.8	2764.1	2850.7	2960.6	3046.0	3128.6	3168.4	3135.2	3029.5	2860.1
30°	2214.5	2289.1	2324.0	2449.4	2589.1	2755.8	2901.8	3040.7	3074.8	3028.9	2889.9
32.5°	1838.6	1903.7	1932.9	2040.5	2170.7	2365.9	2585.0	2781.7	2920.6	2955.8	2872.2
35°	1398.6	1399.4	1466.0	1513.6	1634.3	1835.1	2047.8	2311.3	2573.2	2771.7	2792.3
37.5°	1116.0	1119.9	1160.2	1207.7	1298.2	1404.4	1591.7	1810.8	2113.3	2418.0	2596.6
40°	963.6	970.7	1000.9	1047.7	1112.8	1193.0	1339.0	1545.4	1797.8	2136.7	2413.7
42.5°	865.8	877.4	892.9	929.0	969.3	1044.4	1162.5	1321.9	1551.5	1871.9	2191.5
45°	746.1	752.5	764.4	781.0	817.5	869.9	949.3	1056.4	1247.0	1504.9	1824.7
47.5°	658.1	654.8	667.3	680.9	705.2	740.8	794.1	881.5	1017.4	1224.4	1495.7
50°	598.4	597.6	606.4	616.7	639.7	665.9	709.6	775.5	883.4	1054.9	1303.3
52.5°	542.6	545.6	551.8	564.6	581.3	602.5	641.7	689.1	781.8	929.8	1136.9
55°	468.3	470.7	479.4	486.6	498.5	519.9	544.5	584.2	647.7	750.8	921.5
57.5°	405.5	404.3	412.7	414.4	428.0	445.5	464.4	495.2	541.3	618.0	733.0
60°	363.6	361.1	368.3	373.9	381.0	395.3	411.1	441.3	477.9	534.2	632.6
62.5°	325.4	324.3	329.5	335.1	341.0	354.0	367.3	390.5	419.4	466.9	544.9
65°	269.8	272.3	274.6	277.0	280.1	288.1	300.8	316.7	336.6	369.9	426.3
67.5°	212.1	214.5	215.3	220.2	227.0	232.0	239.7	253.9	267.6	295.8	327.8
70°	171.5	170.7	171.5	173.8	182.6	191.3	201.6	212.0	220.7	240.4	267.5
72.5°	147.3	145.9	147.9	148.5	152.7	155.1	161.6	171.3	182.6	196.0	215.4
75°	114.3	114.3	114.3	114.3	117.4	119.1	121.5	123.8	127.7	134.1	148.5
77.5°	84.4	84.6	85.7	86.5	87.2	88.1	89.6	91.9	93.3	96.6	102.9
80°	66.7	67.5	66.7	67.5	67.5	69.1	69.9	72.2	73.0	77.0	79.4
82.5°	50.2	49.7	50.2	51.0	51.0	52.5	52.7	54.4	54.6	56.7	59.1
85°	27.0	25.4	27.0	26.2	27.8	26.2	27.0	28.6	28.6	29.4	32.5
87.5°	10.8	12.0	10.7	11.3	11.2	11.7	11.6	11.5	12.6	11.8	12.0
90°	22.5	22.1	21.8	21.5	21.1	20.7	20.0	19.3	18.7	18.0	15.9
92.5°	30.3	30.5	30.7	30.9	31.1	30.9	30.4	29.9	29.3	28.8	27.6
95°	58.5	58.5	58.5	58.5	58.5	58.2	57.5	56.8	56.1	55.4	54.1
97.5°	90.0	90.0	90.1	90.2	90.2	89.9	89.1	88.4	87.6	86.8	85.8
100°	113.9	113.6	113.3	112.9	112.6	112.2	111.7	111.2	110.7	110.2	109.4
102.5°	138.6	138.6	138.7	138.8	138.8	138.6	138.0	137.5	137.0	136.5	135.4
105°	178.4	178.0	177.7	177.4	177.0	176.9	176.9	176.9	176.9	176.9	175.4
107.5°	219.9	220.2	220.4	220.6	220.8	220.6	220.0	219.4	218.9	218.4	217.8
110°	248.1	248.4	248.7	249.1	249.4	249.2	248.6	247.9	247.3	246.6	246.3



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	278.1	278.1	278.2	278.3	278.3	278.0	277.2	276.4	275.6	274.8	274.7
115°	319.3	319.5	319.6	319.8	320.0	320.0	319.8	319.6	319.5	319.3	319.6
117.5°	361.1	361.6	362.0	362.5	363.0	363.2	363.2	363.3	363.3	363.3	363.9
120°	390.5	390.8	391.2	391.5	391.8	392.1	392.2	392.4	392.6	392.7	393.6
122.5°	418.7	419.2	419.6	420.1	420.6	421.0	421.4	421.9	422.3	422.7	423.2
125°	461.0	461.6	462.3	463.0	463.6	464.3	464.9	465.6	466.4	467.0	467.3
127.5°	503.1	503.9	504.6	505.4	506.1	507.1	508.0	508.9	509.8	510.8	511.1
130°	530.7	531.9	533.0	534.2	535.3	536.2	536.9	537.7	538.3	539.0	539.5
132.5°	559.5	560.4	561.3	562.2	563.1	563.9	564.7	565.5	566.3	567.1	567.4
135°	604.1	604.5	604.8	605.1	605.5	606.0	606.6	607.3	607.9	608.6	608.8
137.5°	643.6	644.2	644.8	645.5	646.1	646.8	647.4	648.1	648.8	649.5	649.1
140°	669.3	670.6	671.7	672.9	674.0	674.7	674.9	675.0	675.2	675.4	675.2
142.5°	695.7	696.6	697.5	698.4	699.3	699.8	700.0	700.2	700.3	700.5	700.2
145°	733.9	734.5	735.2	735.8	736.5	736.9	737.1	737.2	737.4	737.6	737.1
147.5°	767.7	768.7	769.7	770.7	771.7	772.2	772.2	772.2	772.2	772.2	771.7
150°	789.3	790.3	791.3	792.2	793.2	793.8	793.8	793.8	793.8	793.8	793.5
152.5°	810.3	811.1	812.0	812.8	813.7	814.1	813.7	813.5	813.2	812.9	812.7
155°	838.8	839.9	841.1	842.2	843.4	843.6	843.0	842.3	841.7	841.0	840.8
157.5°	864.6	865.7	866.6	867.5	868.4	868.6	867.9	867.2	866.5	865.8	865.7
160°	881.5	882.1	882.8	883.5	884.1	884.0	883.2	882.4	881.6	880.7	880.7
162.5°	894.0	895.1	896.3	897.3	898.4	898.5	897.7	896.8	896.0	895.1	895.0
165°	912.2	913.4	914.5	915.7	916.9	917.0	915.9	914.9	913.9	912.9	912.9
167.5°	927.7	928.7	929.7	930.8	931.8	931.8	930.8	929.7	928.7	927.7	927.6
170°	935.4	936.6	937.8	939.0	940.1	940.1	939.0	937.8	936.6	935.4	935.4
172.5°	941.5	942.6	943.8	944.9	946.1	946.1	945.1	944.1	943.1	942.0	942.0
175°	948.2	949.4	950.5	951.7	952.9	952.9	951.9	951.0	950.0	949.0	949.0
177.5°	951.8	952.7	953.6	954.6	955.5	955.6	954.8	954.0	953.2	952.4	952.4
180°	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1
2.5°	1914.5	1912.6	1903.7	1893.5	1880.2	1871.3	1864.3	1860.5	1849.1	1835.1	1825.5
5°	2032.8	2008.9	1983.5	1952.6	1924.0	1894.6	1876.3	1854.9	1828.8	1799.4	1778.8
7.5°	2159.4	2112.7	2062.4	2010.5	1959.2	1913.2	1872.6	1837.8	1796.0	1753.9	1724.4
10°	2256.5	2188.3	2117.7	2045.4	1979.5	1917.6	1870.0	1823.2	1773.2	1724.7	1688.3
12.5°	2344.8	2254.9	2173.5	2084.8	2000.5	1926.5	1857.9	1802.8	1742.7	1691.1	1649.5
15°	2456.6	2364.5	2266.0	2131.1	2019.2	1925.6	1842.2	1770.0	1697.0	1633.5	1593.0
17.5°	2561.0	2422.5	2290.2	2177.7	2032.3	1915.2	1813.5	1727.2	1647.0	1579.6	1529.8
20°	2604.2	2470.0	2326.4	2182.7	2039.8	1908.9	1790.6	1695.4	1612.0	1535.8	1489.9
22.5°	2630.2	2478.3	2327.0	2172.6	2020.8	1884.8	1767.8	1663.0	1572.7	1500.3	1443.5
25°	2660.6	2479.6	2312.9	2160.5	2005.7	1858.2	1719.2	1608.1	1510.5	1433.5	1373.1
27.5°	2680.6	2467.7	2270.7	2101.3	1944.3	1797.3	1670.0	1552.2	1453.2	1371.7	1307.0
30°	2684.3	2458.1	2238.3	2055.0	1895.4	1760.5	1625.6	1512.9	1408.1	1321.5	1261.2
32.5°	2689.5	2434.7	2194.4	1999.7	1836.3	1702.7	1580.4	1472.8	1365.5	1280.3	1218.7
35°	2668.5	2421.7	2128.0	1904.1	1740.6	1611.2	1501.0	1401.7	1296.2	1213.6	1150.9
37.5°	2578.3	2370.1	2059.1	1796.5	1625.6	1505.7	1415.8	1329.3	1232.5	1143.5	1084.4
40°	2487.5	2319.3	2005.7	1731.1	1552.6	1429.5	1348.6	1277.9	1184.3	1100.9	1037.4
42.5°	2352.3	2250.1	1954.9	1662.5	1470.0	1351.4	1283.1	1216.9	1134.7	1050.1	990.4
45°	2104.2	2117.7	1851.0	1553.3	1355.6	1236.6	1172.4	1126.3	1053.3	983.4	922.3
47.5°	1793.0	1919.2	1728.9	1436.9	1235.2	1123.5	1067.2	1027.0	977.9	909.3	853.5
50°	1589.8	1770.0	1631.1	1358.9	1159.6	1048.5	992.9	960.4	917.6	863.5	810.4
52.5°	1402.5	1596.0	1513.0	1271.8	1077.7	976.1	921.8	895.0	861.0	810.2	762.1
55°	1143.8	1339.8	1320.8	1140.5	954.8	863.5	822.3	792.1	769.1	731.0	693.0
57.5°	925.1	1111.1	1120.8	994.5	846.6	756.4	720.8	698.1	683.1	654.4	619.1
60°	787.4	958.1	991.4	896.2	769.1	689.7	654.8	636.5	624.7	601.7	574.6
62.5°	673.1	818.3	856.1	787.5	694.8	620.6	593.2	575.6	567.5	547.6	523.8
65°	515.1	635.8	672.3	634.2	585.7	526.2	504.0	489.0	481.8	470.7	453.2
67.5°	387.4	475.2	515.3	488.5	471.0	433.3	419.2	411.1	404.8	397.2	382.5
70°	311.1	376.2	417.5	410.3	396.1	376.2	365.9	360.3	354.0	347.7	335.0
72.5°	250.1	295.0	333.7	337.3	325.6	321.6	312.6	310.2	306.4	298.7	291.8
75°	165.9	196.8	223.8	234.2	238.9	242.9	238.9	238.1	237.3	231.0	227.0
77.5°	108.8	125.4	142.4	160.1	167.4	172.9	174.1	177.0	174.9	171.6	169.7
80°	83.3	87.4	99.2	114.3	126.2	131.0	134.1	135.7	134.9	134.1	131.0
82.5°	60.5	63.8	69.4	80.0	90.0	98.0	99.9	99.6	101.3	101.8	99.2
85°	32.5	33.3	34.9	36.6	42.1	50.8	53.2	54.7	56.4	56.4	51.6
87.5°	12.9	11.8	12.6	12.3	13.8	14.1	17.7	20.5	21.4	19.2	19.6
90°	13.6	11.5	9.3	7.4	5.8	4.0	2.4	0.7	2.4	4.0	5.8
92.5°	26.4	25.0	23.8	22.6	21.5	20.4	19.3	18.2	19.3	20.4	21.5
95°	52.8	51.5	50.1	48.9	47.8	46.6	45.3	44.2	45.3	46.6	47.8
97.5°	84.8	83.9	82.9	82.0	81.2	80.3	79.4	78.6	79.4	80.3	81.2
100°	108.6	107.7	106.8	105.9	104.9	103.9	102.9	101.9	102.9	103.9	104.9
102.5°	134.4	133.3	132.2	131.3	130.7	130.2	129.6	129.0	129.6	130.2	130.7
105°	173.9	172.4	170.9	170.0	169.7	169.4	169.0	168.6	169.0	169.4	169.7
107.5°	217.2	216.6	216.0	215.6	215.4	215.2	215.0	214.8	215.0	215.2	215.4
110°	245.9	245.6	245.3	244.9	244.6	244.3	244.0	243.6	244.0	244.3	244.6



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	274.7	274.6	274.5	274.4	274.2	274.0	273.8	273.6	273.8	274.0	274.2
115°	320.0	320.3	320.6	320.5	320.0	319.5	319.0	318.6	319.0	319.5	320.0
117.5°	364.3	364.7	365.2	365.2	364.9	364.5	364.2	363.9	364.2	364.5	364.9
120°	394.5	395.3	396.1	396.1	395.1	394.0	393.0	392.0	393.0	394.0	395.1
122.5°	423.6	424.0	424.4	424.3	423.6	422.8	422.1	421.4	422.1	422.8	423.6
125°	467.7	468.0	468.3	468.3	467.8	467.3	466.8	466.3	466.8	467.3	467.8
127.5°	511.5	511.9	512.2	511.9	510.8	509.8	508.7	507.6	508.7	509.8	510.8
130°	540.0	540.5	541.0	540.5	539.2	537.9	536.5	535.2	536.5	537.9	539.2
132.5°	567.8	568.3	568.6	568.2	566.7	565.4	564.1	562.8	564.1	565.4	566.7
135°	608.9	609.2	609.4	608.8	607.9	606.9	605.9	604.9	605.9	606.9	607.9
137.5°	648.7	648.2	647.8	647.2	646.4	645.5	644.7	643.9	644.7	645.5	646.4
140°	675.0	674.9	674.7	674.2	673.4	672.6	671.7	670.9	671.7	672.6	673.4
142.5°	699.9	699.6	699.3	698.7	697.9	697.1	696.3	695.5	696.3	697.1	697.9
145°	736.6	736.1	735.6	735.2	734.8	734.5	734.2	733.9	734.2	734.5	734.8
147.5°	771.2	770.8	770.3	769.8	769.2	768.6	768.0	767.4	768.0	768.6	769.2
150°	793.1	792.7	792.4	792.1	791.8	791.4	791.1	790.8	791.1	791.4	791.8
152.5°	812.5	812.3	812.1	811.8	811.4	810.9	810.4	810.0	810.4	810.9	811.4
155°	840.7	840.5	840.3	840.3	840.3	840.3	840.3	840.3	840.3	840.3	840.3
157.5°	865.5	865.4	865.3	865.3	865.5	865.7	865.9	866.1	865.9	865.7	865.5
160°	880.7	880.7	880.7	880.9	881.2	881.6	881.9	882.2	881.9	881.6	881.2
162.5°	894.8	894.7	894.6	894.7	895.2	895.6	896.2	896.7	896.2	895.6	895.2
165°	912.9	912.9	912.9	913.2	913.7	914.2	914.7	915.2	914.7	914.2	913.7
167.5°	927.4	927.3	927.2	927.4	928.1	928.8	929.4	930.1	929.4	928.8	928.1
170°	935.4	935.4	935.4	935.7	936.4	937.2	937.8	938.5	937.8	937.2	936.4
172.5°	942.0	942.0	942.0	942.4	943.0	943.7	944.4	945.0	944.4	943.7	943.0
175°	949.0	949.0	949.0	949.3	950.0	950.6	951.3	951.9	951.3	950.6	950.0
177.5°	952.4	952.4	952.4	952.7	953.2	953.7	954.2	954.8	954.2	953.7	953.2
180°	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1
2.5°	1822.4	1814.1	1808.5	1795.7	1787.5	1778.6	1769.7	1775.4	1774.7	1774.1	1774.1
5°	1761.3	1743.0	1726.4	1705.0	1691.4	1674.8	1662.0	1660.4	1663.7	1652.5	1646.2
7.5°	1700.6	1675.7	1652.0	1628.4	1603.4	1583.4	1570.7	1564.9	1556.8	1549.9	1542.9
10°	1658.1	1628.7	1605.7	1576.3	1549.3	1525.5	1510.5	1500.2	1494.6	1489.0	1478.7
12.5°	1614.3	1585.6	1556.2	1523.0	1497.3	1469.7	1458.3	1446.8	1436.1	1430.0	1415.8
15°	1550.1	1512.9	1481.9	1446.9	1418.4	1391.4	1375.5	1352.5	1349.3	1341.4	1327.1
17.5°	1485.8	1445.3	1402.7	1376.7	1344.5	1316.5	1292.3	1284.5	1261.8	1253.2	1240.9
20°	1435.0	1397.8	1365.2	1331.1	1284.2	1258.1	1239.0	1228.7	1210.4	1199.3	1191.3
22.5°	1391.2	1353.3	1315.7	1275.9	1237.3	1207.9	1194.0	1177.9	1167.9	1152.4	1143.8
25°	1328.7	1287.4	1242.1	1199.3	1171.5	1149.3	1127.1	1112.8	1098.5	1091.4	1075.5
27.5°	1256.0	1212.8	1170.5	1138.0	1103.9	1082.0	1061.9	1049.1	1032.0	1020.0	1011.2
30°	1216.0	1165.2	1128.6	1099.3	1055.6	1035.0	1020.0	1004.1	991.4	978.7	970.0
32.5°	1169.6	1123.3	1088.6	1052.3	1018.9	996.2	976.7	962.8	952.0	939.9	931.2
35°	1096.9	1058.0	1022.3	985.8	961.2	938.2	915.1	903.2	892.9	881.8	873.9
37.5°	1031.2	994.8	960.9	926.2	895.8	877.1	858.5	849.4	835.5	828.0	819.9
40°	990.6	954.8	918.4	885.0	853.2	839.0	822.3	808.8	796.1	790.5	781.8
42.5°	946.1	910.4	879.6	843.7	817.7	798.3	782.9	768.2	758.6	750.5	745.6
45°	880.2	848.5	818.3	782.6	758.0	741.3	723.9	710.3	701.7	696.1	687.3
47.5°	816.3	784.6	753.9	722.8	698.9	679.9	662.5	653.1	641.5	634.7	628.7
50°	769.9	741.3	708.8	680.2	656.4	637.3	623.1	611.2	600.9	592.1	588.1
52.5°	727.4	696.9	668.8	642.1	617.0	595.4	582.4	569.9	562.1	552.1	547.5
55°	657.2	627.8	604.0	577.8	553.2	534.9	519.1	508.0	500.1	489.0	482.6
57.5°	591.3	565.0	536.5	513.8	488.5	473.0	459.9	444.8	435.2	426.4	420.2
60°	546.8	516.7	492.1	470.7	448.5	428.6	416.7	404.8	394.5	385.8	380.2
62.5°	500.5	474.1	450.8	427.5	407.2	389.9	376.1	366.1	357.0	351.4	345.9
65°	429.4	408.8	385.0	365.9	346.9	334.2	323.1	314.3	308.0	304.0	299.2
67.5°	364.0	344.0	323.2	304.5	291.8	282.1	274.8	267.3	264.2	259.0	255.9
70°	321.4	300.8	282.6	268.3	255.6	248.4	243.7	238.1	234.9	228.6	225.4
72.5°	275.1	260.1	247.0	235.3	225.1	218.6	212.6	205.7	200.7	193.7	190.5
75°	216.7	203.2	192.9	184.9	178.5	169.9	161.2	154.0	151.6	149.3	148.5
77.5°	160.5	151.9	144.4	137.7	129.9	123.5	121.6	120.0	119.6	118.3	118.3
80°	126.2	118.3	112.7	104.7	100.0	100.0	100.0	98.5	99.2	99.2	99.2
82.5°	93.8	86.5	83.5	80.7	79.7	80.3	80.3	80.7	80.2	81.4	80.8
85°	48.4	49.2	50.8	50.0	50.8	50.8	52.4	51.6	52.4	50.8	52.4
87.5°	19.3	21.5	22.6	23.7	24.7	24.5	25.3	25.4	26.3	26.4	26.5
90°	7.4	9.3	11.5	13.6	15.9	18.0	18.7	19.3	20.0	20.7	21.1
92.5°	22.6	23.8	25.0	26.4	27.6	28.8	29.3	29.9	30.4	30.9	31.1
95°	48.9	50.1	51.5	52.8	54.1	55.4	56.1	56.8	57.5	58.2	58.5
97.5°	82.0	82.9	83.9	84.8	85.8	86.8	87.6	88.4	89.1	89.9	90.2
100°	105.9	106.8	107.7	108.6	109.4	110.2	110.7	111.2	111.7	112.2	112.6
102.5°	131.3	132.2	133.3	134.4	135.4	136.5	137.0	137.5	138.0	138.6	138.8
105°	170.0	170.9	172.4	173.9	175.4	176.9	176.9	176.9	176.9	176.9	177.0
107.5°	215.6	216.0	216.6	217.2	217.8	218.4	218.9	219.4	220.0	220.6	220.8
110°	244.9	245.3	245.6	245.9	246.3	246.6	247.3	247.9	248.6	249.2	249.4



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	274.4	274.5	274.6	274.7	274.7	274.8	275.6	276.4	277.2	278.0	278.3
115°	320.5	320.6	320.3	320.0	319.6	319.3	319.5	319.6	319.8	320.0	320.0
117.5°	365.2	365.2	364.7	364.3	363.9	363.3	363.3	363.3	363.2	363.2	363.0
120°	396.1	396.1	395.3	394.5	393.6	392.7	392.6	392.4	392.2	392.1	391.8
122.5°	424.3	424.4	424.0	423.6	423.2	422.7	422.3	421.9	421.4	421.0	420.6
125°	468.3	468.3	468.0	467.7	467.3	467.0	466.4	465.6	464.9	464.3	463.6
127.5°	511.9	512.2	511.9	511.5	511.1	510.8	509.8	508.9	508.0	507.1	506.1
130°	540.5	541.0	540.5	540.0	539.5	539.0	538.3	537.7	536.9	536.2	535.3
132.5°	568.2	568.6	568.3	567.8	567.4	567.1	566.3	565.5	564.7	563.9	563.1
135°	608.8	609.4	609.2	608.9	608.8	608.6	607.9	607.3	606.6	606.0	605.5
137.5°	647.2	647.8	648.2	648.7	649.1	649.5	648.8	648.1	647.4	646.8	646.1
140°	674.2	674.7	674.9	675.0	675.2	675.4	675.2	675.0	674.9	674.7	674.0
142.5°	698.7	699.3	699.6	699.9	700.2	700.5	700.3	700.2	700.0	699.8	699.3
145°	735.2	735.6	736.1	736.6	737.1	737.6	737.4	737.2	737.1	736.9	736.5
147.5°	769.8	770.3	770.8	771.2	771.7	772.2	772.2	772.2	772.2	772.2	771.7
150°	792.1	792.4	792.7	793.1	793.5	793.8	793.8	793.8	793.8	793.8	793.2
152.5°	811.8	812.1	812.3	812.5	812.7	812.9	813.2	813.5	813.7	814.1	813.7
155°	840.3	840.3	840.5	840.7	840.8	841.0	841.7	842.3	843.0	843.6	843.4
157.5°	865.3	865.3	865.4	865.5	865.7	865.8	866.5	867.2	867.9	868.6	868.4
160°	880.9	880.7	880.7	880.7	880.7	880.7	881.6	882.4	883.2	884.0	884.1
162.5°	894.7	894.6	894.7	894.8	895.0	895.1	896.0	896.8	897.7	898.5	898.4
165°	913.2	912.9	912.9	912.9	912.9	912.9	913.9	914.9	915.9	917.0	916.9
167.5°	927.4	927.2	927.3	927.4	927.6	927.7	928.7	929.7	930.8	931.8	931.8
170°	935.7	935.4	935.4	935.4	935.4	935.4	936.6	937.8	939.0	940.1	940.1
172.5°	942.4	942.0	942.0	942.0	942.0	942.0	943.1	944.1	945.1	946.1	946.1
175°	949.3	949.0	949.0	949.0	949.0	949.0	950.0	951.0	951.9	952.9	952.9
177.5°	952.7	952.4	952.4	952.4	952.4	952.4	953.2	954.0	954.8	955.6	955.5
180°	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1
2.5°	1766.6	1765.8	1766.6	1763.9	1766.6	1765.8	1766.6	1774.1	1774.1	1774.7	1775.4
5°	1643.8	1643.1	1640.6	1633.5	1640.6	1643.1	1643.8	1646.2	1652.5	1663.7	1660.4
7.5°	1536.6	1535.5	1528.5	1528.7	1528.5	1535.5	1536.6	1542.9	1549.9	1556.8	1564.9
10°	1473.2	1473.9	1464.4	1458.9	1464.4	1473.9	1473.2	1478.7	1489.0	1494.6	1500.2
12.5°	1411.6	1408.0	1400.3	1394.1	1400.3	1408.0	1411.6	1415.8	1430.0	1436.1	1446.8
15°	1330.3	1322.3	1303.3	1304.8	1303.3	1322.3	1330.3	1327.1	1341.4	1349.3	1352.5
17.5°	1234.6	1228.7	1228.4	1217.3	1228.4	1228.7	1234.6	1240.9	1253.2	1261.8	1284.5
20°	1178.7	1174.7	1176.3	1165.2	1176.3	1174.7	1178.7	1191.3	1199.3	1210.4	1228.7
22.5°	1134.9	1130.8	1124.2	1120.7	1124.2	1130.8	1134.9	1143.8	1152.4	1167.9	1177.9
25°	1070.8	1064.4	1058.0	1062.0	1058.0	1064.4	1070.8	1075.5	1091.4	1098.5	1112.8
27.5°	1006.6	1001.9	995.5	994.7	995.5	1001.9	1006.6	1011.2	1020.0	1032.0	1049.1
30°	965.9	961.2	958.1	954.0	958.1	961.2	965.9	970.0	978.7	991.4	1004.1
32.5°	924.7	923.7	918.1	917.3	918.1	923.7	924.7	931.2	939.9	952.0	962.8
35°	870.7	866.0	864.3	865.2	864.3	866.0	870.7	873.9	881.8	892.9	903.2
37.5°	819.4	813.0	810.2	807.4	810.2	813.0	819.4	819.9	828.0	835.5	849.4
40°	782.6	776.3	774.7	773.1	774.7	776.3	782.6	781.8	790.5	796.1	808.8
42.5°	741.3	738.8	737.8	735.0	737.8	738.8	741.3	745.6	750.5	758.6	768.2
45°	685.0	684.2	679.4	681.1	679.4	684.2	685.0	687.3	696.1	701.7	710.3
47.5°	625.6	622.1	618.7	621.0	618.7	622.1	625.6	628.7	634.7	641.5	653.1
50°	585.0	583.4	576.2	577.8	576.2	583.4	585.0	588.1	592.1	600.9	611.2
52.5°	544.3	538.3	535.6	534.6	535.6	538.3	544.3	547.5	552.1	562.1	569.9
55°	477.1	469.9	466.7	465.1	466.7	469.9	477.1	482.6	489.0	500.1	508.0
57.5°	411.0	409.1	406.6	408.3	406.6	409.1	411.0	420.2	426.4	435.2	444.8
60°	372.2	372.2	372.2	371.4	372.2	372.2	372.2	380.2	385.8	394.5	404.8
62.5°	342.4	340.5	339.9	341.0	339.9	340.5	342.4	345.9	351.4	357.0	366.1
65°	296.9	296.1	292.9	292.1	292.9	296.1	296.9	299.2	304.0	308.0	314.3
67.5°	253.9	251.0	250.0	248.9	250.0	251.0	253.9	255.9	259.0	264.2	267.3
70°	221.5	219.8	215.1	215.9	215.1	219.8	221.5	225.4	228.6	234.9	238.1
72.5°	186.5	184.9	184.0	182.9	184.0	184.9	186.5	190.5	193.7	200.7	205.7
75°	147.6	146.8	146.0	149.3	146.0	146.8	147.6	148.5	149.3	151.6	154.0
77.5°	118.3	118.3	118.8	117.4	118.8	118.3	118.3	118.3	118.3	119.6	120.0
80°	99.2	99.2	98.5	98.5	98.5	99.2	99.2	99.2	99.2	99.2	98.5
82.5°	79.6	80.2	80.7	79.4	80.7	80.2	79.6	80.8	81.4	80.2	80.7
85°	52.4	51.6	53.2	52.4	53.2	51.6	52.4	52.4	50.8	52.4	51.6
87.5°	27.8	26.6	26.7	27.4	26.7	26.6	27.8	26.5	26.4	26.3	25.4
90°	21.5	21.8	22.1	22.5	22.1	21.8	21.5	21.1	20.7	20.0	19.3
92.5°	30.9	30.7	30.5	30.3	30.5	30.7	30.9	31.1	30.9	30.4	29.9
95°	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.5	58.2	57.5	56.8
97.5°	90.2	90.1	90.0	90.0	90.0	90.1	90.2	90.2	89.9	89.1	88.4
100°	112.9	113.3	113.6	113.9	113.6	113.3	112.9	112.6	112.2	111.7	111.2
102.5°	138.8	138.7	138.6	138.6	138.6	138.7	138.8	138.8	138.6	138.0	137.5
105°	177.4	177.7	178.0	178.4	178.0	177.7	177.4	177.0	176.9	176.9	176.9
107.5°	220.6	220.4	220.2	219.9	220.2	220.4	220.6	220.8	220.6	220.0	219.4
110°	249.1	248.7	248.4	248.1	248.4	248.7	249.1	249.4	249.2	248.6	247.9



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	278.3	278.2	278.1	278.1	278.1	278.2	278.3	278.3	278.0	277.2	276.4
115°	319.8	319.6	319.5	319.3	319.5	319.6	319.8	320.0	320.0	319.8	319.6
117.5°	362.5	362.0	361.6	361.1	361.6	362.0	362.5	363.0	363.2	363.2	363.3
120°	391.5	391.2	390.8	390.5	390.8	391.2	391.5	391.8	392.1	392.2	392.4
122.5°	420.1	419.6	419.2	418.7	419.2	419.6	420.1	420.6	421.0	421.4	421.9
125°	463.0	462.3	461.6	461.0	461.6	462.3	463.0	463.6	464.3	464.9	465.6
127.5°	505.4	504.6	503.9	503.1	503.9	504.6	505.4	506.1	507.1	508.0	508.9
130°	534.2	533.0	531.9	530.7	531.9	533.0	534.2	535.3	536.2	536.9	537.7
132.5°	562.2	561.3	560.4	559.5	560.4	561.3	562.2	563.1	563.9	564.7	565.5
135°	605.1	604.8	604.5	604.1	604.5	604.8	605.1	605.5	606.0	606.6	607.3
137.5°	645.5	644.8	644.2	643.6	644.2	644.8	645.5	646.1	646.8	647.4	648.1
140°	672.9	671.7	670.6	669.3	670.6	671.7	672.9	674.0	674.7	674.9	675.0
142.5°	698.4	697.5	696.6	695.7	696.6	697.5	698.4	699.3	699.8	700.0	700.2
145°	735.8	735.2	734.5	733.9	734.5	735.2	735.8	736.5	736.9	737.1	737.2
147.5°	770.7	769.7	768.7	767.7	768.7	769.7	770.7	771.7	772.2	772.2	772.2
150°	792.2	791.3	790.3	789.3	790.3	791.3	792.2	793.2	793.8	793.8	793.8
152.5°	812.8	812.0	811.1	810.3	811.1	812.0	812.8	813.7	814.1	813.7	813.5
155°	842.2	841.1	839.9	838.8	839.9	841.1	842.2	843.4	843.6	843.0	842.3
157.5°	867.5	866.6	865.7	864.6	865.7	866.6	867.5	868.4	868.6	867.9	867.2
160°	883.5	882.8	882.1	881.5	882.1	882.8	883.5	884.1	884.0	883.2	882.4
162.5°	897.3	896.3	895.1	894.0	895.1	896.3	897.3	898.4	898.5	897.7	896.8
165°	915.7	914.5	913.4	912.2	913.4	914.5	915.7	916.9	917.0	915.9	914.9
167.5°	930.8	929.7	928.7	927.7	928.7	929.7	930.8	931.8	931.8	930.8	929.7
170°	939.0	937.8	936.6	935.4	936.6	937.8	939.0	940.1	940.1	939.0	937.8
172.5°	944.9	943.8	942.6	941.5	942.6	943.8	944.9	946.1	946.1	945.1	944.1
175°	951.7	950.5	949.4	948.2	949.4	950.5	951.7	952.9	952.9	951.9	951.0
177.5°	954.6	953.6	952.7	951.8	952.7	953.6	954.6	955.5	955.6	954.8	954.0
180°	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1
2.5°	1769.7	1778.6	1787.5	1795.7	1808.5	1814.1	1822.4	1825.5	1835.1	1849.1	1860.5
5°	1662.0	1674.8	1691.4	1705.0	1726.4	1743.0	1761.3	1778.8	1799.4	1828.8	1854.9
7.5°	1570.7	1583.4	1603.4	1628.4	1652.0	1675.7	1700.6	1724.4	1753.9	1796.0	1837.8
10°	1510.5	1525.5	1549.3	1576.3	1605.7	1628.7	1658.1	1688.3	1724.7	1773.2	1823.2
12.5°	1458.3	1469.7	1497.3	1523.0	1556.2	1585.6	1614.3	1649.5	1691.1	1742.7	1802.8
15°	1375.5	1391.4	1418.4	1446.9	1481.9	1512.9	1550.1	1593.0	1633.5	1697.0	1770.0
17.5°	1292.3	1316.5	1344.5	1376.7	1402.7	1445.3	1485.8	1529.8	1579.6	1647.0	1727.2
20°	1239.0	1258.1	1284.2	1331.1	1365.2	1397.8	1435.0	1489.9	1535.8	1612.0	1695.4
22.5°	1194.0	1207.9	1237.3	1275.9	1315.7	1353.3	1391.2	1443.5	1500.3	1572.7	1663.0
25°	1127.1	1149.3	1171.5	1199.3	1242.1	1287.4	1328.7	1373.1	1433.5	1510.5	1608.1
27.5°	1061.9	1082.0	1103.9	1138.0	1170.5	1212.8	1256.0	1307.0	1371.7	1453.2	1552.2
30°	1020.0	1035.0	1055.6	1099.3	1128.6	1165.2	1216.0	1261.2	1321.5	1408.1	1512.9
32.5°	976.7	996.2	1018.9	1052.3	1088.6	1123.3	1169.6	1218.7	1280.3	1365.5	1472.8
35°	915.1	938.2	961.2	985.8	1022.3	1058.0	1096.9	1150.9	1213.6	1296.2	1401.7
37.5°	858.5	877.1	895.8	926.2	960.9	994.8	1031.2	1084.4	1143.5	1232.5	1329.3
40°	822.3	839.0	853.2	885.0	918.4	954.8	990.6	1037.4	1100.9	1184.3	1277.9
42.5°	782.9	798.3	817.7	843.7	879.6	910.4	946.1	990.4	1050.1	1134.7	1216.9
45°	723.9	741.3	758.0	782.6	818.3	848.5	880.2	922.3	983.4	1053.3	1126.3
47.5°	662.5	679.9	698.9	722.8	753.9	784.6	816.3	853.5	909.3	977.9	1027.0
50°	623.1	637.3	656.4	680.2	708.8	741.3	769.9	810.4	863.5	917.6	960.4
52.5°	582.4	595.4	617.0	642.1	668.8	696.9	727.4	762.1	810.2	861.0	895.0
55°	519.1	534.9	553.2	577.8	604.0	627.8	657.2	693.0	731.0	769.1	792.1
57.5°	459.9	473.0	488.5	513.8	536.5	565.0	591.3	619.1	654.4	683.1	698.1
60°	416.7	428.6	448.5	470.7	492.1	516.7	546.8	574.6	601.7	624.7	636.5
62.5°	376.1	389.9	407.2	427.5	450.8	474.1	500.5	523.8	547.6	567.5	575.6
65°	323.1	334.2	346.9	365.9	385.0	408.8	429.4	453.2	470.7	481.8	489.0
67.5°	274.8	282.1	291.8	304.5	323.2	344.0	364.0	382.5	397.2	404.8	411.1
70°	243.7	248.4	255.6	268.3	282.6	300.8	321.4	335.0	347.7	354.0	360.3
72.5°	212.6	218.6	225.1	235.3	247.0	260.1	275.1	291.8	298.7	306.4	310.2
75°	161.2	169.9	178.5	184.9	192.9	203.2	216.7	227.0	231.0	237.3	238.1
77.5°	121.6	123.5	129.9	137.7	144.4	151.9	160.5	169.7	171.6	174.9	177.0
80°	100.0	100.0	100.0	104.7	112.7	118.3	126.2	131.0	134.1	134.9	135.7
82.5°	80.3	80.3	79.7	80.7	83.5	86.5	93.8	99.2	101.8	101.3	99.6
85°	52.4	50.8	50.8	50.0	50.8	49.2	48.4	51.6	56.4	56.4	54.7
87.5°	25.3	24.5	24.7	23.7	22.6	21.5	19.3	19.6	19.2	21.4	20.5
90°	18.7	18.0	15.9	13.6	11.5	9.3	7.4	5.8	4.0	2.4	0.7
92.5°	29.3	28.8	27.6	26.4	25.0	23.8	22.6	21.5	20.4	19.3	18.2
95°	56.1	55.4	54.1	52.8	51.5	50.1	48.9	47.8	46.6	45.3	44.2
97.5°	87.6	86.8	85.8	84.8	83.9	82.9	82.0	81.2	80.3	79.4	78.6
100°	110.7	110.2	109.4	108.6	107.7	106.8	105.9	104.9	103.9	102.9	101.9
102.5°	137.0	136.5	135.4	134.4	133.3	132.2	131.3	130.7	130.2	129.6	129.0
105°	176.9	176.9	175.4	173.9	172.4	170.9	170.0	169.7	169.4	169.0	168.6
107.5°	218.9	218.4	217.8	217.2	216.6	216.0	215.6	215.4	215.2	215.0	214.8
110°	247.3	246.6	246.3	245.9	245.6	245.3	244.9	244.6	244.3	244.0	243.6



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	275.6	274.8	274.7	274.7	274.6	274.5	274.4	274.2	274.0	273.8	273.6
115°	319.5	319.3	319.6	320.0	320.3	320.6	320.5	320.0	319.5	319.0	318.6
117.5°	363.3	363.3	363.9	364.3	364.7	365.2	365.2	364.9	364.5	364.2	363.9
120°	392.6	392.7	393.6	394.5	395.3	396.1	396.1	395.1	394.0	393.0	392.0
122.5°	422.3	422.7	423.2	423.6	424.0	424.4	424.3	423.6	422.8	422.1	421.4
125°	466.4	467.0	467.3	467.7	468.0	468.3	468.3	467.8	467.3	466.8	466.3
127.5°	509.8	510.8	511.1	511.5	511.9	512.2	511.9	510.8	509.8	508.7	507.6
130°	538.3	539.0	539.5	540.0	540.5	541.0	540.5	539.2	537.9	536.5	535.2
132.5°	566.3	567.1	567.4	567.8	568.3	568.6	568.2	566.7	565.4	564.1	562.8
135°	607.9	608.6	608.8	608.9	609.2	609.4	608.8	607.9	606.9	605.9	604.9
137.5°	648.8	649.5	649.1	648.7	648.2	647.8	647.2	646.4	645.5	644.7	643.9
140°	675.2	675.4	675.2	675.0	674.9	674.7	674.2	673.4	672.6	671.7	670.9
142.5°	700.3	700.5	700.2	699.9	699.6	699.3	698.7	697.9	697.1	696.3	695.5
145°	737.4	737.6	737.1	736.6	736.1	735.6	735.2	734.8	734.5	734.2	733.9
147.5°	772.2	772.2	771.7	771.2	770.8	770.3	769.8	769.2	768.6	768.0	767.4
150°	793.8	793.8	793.5	793.1	792.7	792.4	792.1	791.8	791.4	791.1	790.8
152.5°	813.2	812.9	812.7	812.5	812.3	812.1	811.8	811.4	810.9	810.4	810.0
155°	841.7	841.0	840.8	840.7	840.5	840.3	840.3	840.3	840.3	840.3	840.3
157.5°	866.5	865.8	865.7	865.5	865.4	865.3	865.3	865.5	865.7	865.9	866.1
160°	881.6	880.7	880.7	880.7	880.7	880.7	880.9	881.2	881.6	881.9	882.2
162.5°	896.0	895.1	895.0	894.8	894.7	894.6	894.7	895.2	895.6	896.2	896.7
165°	913.9	912.9	912.9	912.9	912.9	912.9	913.2	913.7	914.2	914.7	915.2
167.5°	928.7	927.7	927.6	927.4	927.3	927.2	927.4	928.1	928.8	929.4	930.1
170°	936.6	935.4	935.4	935.4	935.4	935.4	935.7	936.4	937.2	937.8	938.5
172.5°	943.1	942.0	942.0	942.0	942.0	942.0	942.4	943.0	943.7	944.4	945.0
175°	950.0	949.0	949.0	949.0	949.0	949.0	949.3	950.0	950.6	951.3	951.9
177.5°	953.2	952.4	952.4	952.4	952.4	952.4	952.7	953.2	953.7	954.2	954.8
180°	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1
2.5°	1864.3	1871.3	1880.2	1893.5	1903.7	1912.6	1914.5	1917.0	1923.4	1934.1	1942.4
5°	1876.3	1894.6	1924.0	1952.6	1983.5	2008.9	2032.8	2049.4	2065.3	2098.6	2125.6
7.5°	1872.6	1913.2	1959.2	2010.5	2062.4	2112.7	2159.4	2201.1	2242.7	2291.3	2346.7
10°	1870.0	1917.6	1979.5	2045.4	2117.7	2188.3	2256.5	2309.8	2371.7	2427.2	2497.8
12.5°	1857.9	1926.5	2000.5	2084.8	2173.5	2254.9	2344.8	2418.3	2489.1	2569.4	2651.5
15°	1842.2	1925.6	2019.2	2131.1	2266.0	2364.5	2456.6	2584.3	2671.7	2759.0	2876.5
17.5°	1813.5	1915.2	2032.3	2177.7	2290.2	2422.5	2561.0	2662.0	2779.7	2902.7	3009.0
20°	1790.6	1908.9	2039.8	2182.7	2326.4	2470.0	2604.2	2724.8	2846.3	2988.4	3075.6
22.5°	1767.8	1884.8	2020.8	2172.6	2327.0	2478.3	2630.2	2771.9	2908.5	3051.9	3163.3
25°	1719.2	1858.2	2005.7	2160.5	2312.9	2479.6	2660.6	2818.5	2987.6	3135.2	3240.8
27.5°	1670.0	1797.3	1944.3	2101.3	2270.7	2467.7	2680.6	2860.1	3029.5	3135.2	3168.4
30°	1625.6	1760.5	1895.4	2055.0	2238.3	2458.1	2684.3	2889.9	3028.9	3074.8	3040.7
32.5°	1580.4	1702.7	1836.3	1999.7	2194.4	2434.7	2689.5	2872.2	2955.8	2920.6	2781.7
35°	1501.0	1611.2	1740.6	1904.1	2128.0	2421.7	2668.5	2792.3	2771.7	2573.2	2311.3
37.5°	1415.8	1505.7	1625.6	1796.5	2059.1	2370.1	2578.3	2596.6	2418.0	2113.3	1810.8
40°	1348.6	1429.5	1552.6	1731.1	2005.7	2319.3	2487.5	2413.7	2136.7	1797.8	1545.4
42.5°	1283.1	1351.4	1470.0	1662.5	1954.9	2250.1	2352.3	2191.5	1871.9	1551.5	1321.9
45°	1172.4	1236.6	1355.6	1553.3	1851.0	2117.7	2104.2	1824.7	1504.9	1247.0	1056.4
47.5°	1067.2	1123.5	1235.2	1436.9	1728.9	1919.2	1793.0	1495.7	1224.4	1017.4	881.5
50°	992.9	1048.5	1159.6	1358.9	1631.1	1770.0	1589.8	1303.3	1054.9	883.4	775.5
52.5°	921.8	976.1	1077.7	1271.8	1513.0	1596.0	1402.5	1136.9	929.8	781.8	689.1
55°	822.3	863.5	954.8	1140.5	1320.8	1339.8	1143.8	921.5	750.8	647.7	584.2
57.5°	720.8	756.4	846.6	994.5	1120.8	1111.1	925.1	733.0	618.0	541.3	495.2
60°	654.8	689.7	769.1	896.2	991.4	958.1	787.4	632.6	534.2	477.9	441.3
62.5°	593.2	620.6	694.8	787.5	856.1	818.3	673.1	544.9	466.9	419.4	390.5
65°	504.0	526.2	585.7	634.2	672.3	635.8	515.1	426.3	369.9	336.6	316.7
67.5°	419.2	433.3	471.0	488.5	515.3	475.2	387.4	327.8	295.8	267.6	253.9
70°	365.9	376.2	396.1	410.3	417.5	376.2	311.1	267.5	240.4	220.7	212.0
72.5°	312.6	321.6	325.6	337.3	333.7	295.0	250.1	215.4	196.0	182.6	171.3
75°	238.9	242.9	238.9	234.2	223.8	196.8	165.9	148.5	134.1	127.7	123.8
77.5°	174.1	172.9	167.4	160.1	142.4	125.4	108.8	102.9	96.6	93.3	91.9
80°	134.1	131.0	126.2	114.3	99.2	87.4	83.3	79.4	77.0	73.0	72.2
82.5°	99.9	98.0	90.0	80.0	69.4	63.8	60.5	59.1	56.7	54.6	54.4
85°	53.2	50.8	42.1	36.6	34.9	33.3	32.5	32.5	29.4	28.6	28.6
87.5°	17.7	14.1	13.8	12.3	12.6	11.8	12.9	12.0	11.8	12.6	11.5
90°	2.4	4.0	5.8	7.4	9.3	11.5	13.6	15.9	18.0	18.7	19.3
92.5°	19.3	20.4	21.5	22.6	23.8	25.0	26.4	27.6	28.8	29.3	29.9
95°	45.3	46.6	47.8	48.9	50.1	51.5	52.8	54.1	55.4	56.1	56.8
97.5°	79.4	80.3	81.2	82.0	82.9	83.9	84.8	85.8	86.8	87.6	88.4
100°	102.9	103.9	104.9	105.9	106.8	107.7	108.6	109.4	110.2	110.7	111.2
102.5°	129.6	130.2	130.7	131.3	132.2	133.3	134.4	135.4	136.5	137.0	137.5
105°	169.0	169.4	169.7	170.0	170.9	172.4	173.9	175.4	176.9	176.9	176.9
107.5°	215.0	215.2	215.4	215.6	216.0	216.6	217.2	217.8	218.4	218.9	219.4
110°	244.0	244.3	244.6	244.9	245.3	245.6	245.9	246.3	246.6	247.3	247.9



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	273.8	274.0	274.2	274.4	274.5	274.6	274.7	274.7	274.8	275.6	276.4
115°	319.0	319.5	320.0	320.5	320.6	320.3	320.0	319.6	319.3	319.5	319.6
117.5°	364.2	364.5	364.9	365.2	365.2	364.7	364.3	363.9	363.3	363.3	363.3
120°	393.0	394.0	395.1	396.1	396.1	395.3	394.5	393.6	392.7	392.6	392.4
122.5°	422.1	422.8	423.6	424.3	424.4	424.0	423.6	423.2	422.7	422.3	421.9
125°	466.8	467.3	467.8	468.3	468.3	468.0	467.7	467.3	467.0	466.4	465.6
127.5°	508.7	509.8	510.8	511.9	512.2	511.9	511.5	511.1	510.8	509.8	508.9
130°	536.5	537.9	539.2	540.5	541.0	540.5	540.0	539.5	539.0	538.3	537.7
132.5°	564.1	565.4	566.7	568.2	568.6	568.3	567.8	567.4	567.1	566.3	565.5
135°	605.9	606.9	607.9	608.8	609.4	609.2	608.9	608.8	608.6	607.9	607.3
137.5°	644.7	645.5	646.4	647.2	647.8	648.2	648.7	649.1	649.5	648.8	648.1
140°	671.7	672.6	673.4	674.2	674.7	674.9	675.0	675.2	675.4	675.2	675.0
142.5°	696.3	697.1	697.9	698.7	699.3	699.6	699.9	700.2	700.5	700.3	700.2
145°	734.2	734.5	734.8	735.2	735.6	736.1	736.6	737.1	737.6	737.4	737.2
147.5°	768.0	768.6	769.2	769.8	770.3	770.8	771.2	771.7	772.2	772.2	772.2
150°	791.1	791.4	791.8	792.1	792.4	792.7	793.1	793.5	793.8	793.8	793.8
152.5°	810.4	810.9	811.4	811.8	812.1	812.3	812.5	812.7	812.9	813.2	813.5
155°	840.3	840.3	840.3	840.3	840.3	840.5	840.7	840.8	841.0	841.7	842.3
157.5°	865.9	865.7	865.5	865.3	865.3	865.4	865.5	865.7	865.8	866.5	867.2
160°	881.9	881.6	881.2	880.9	880.7	880.7	880.7	880.7	880.7	881.6	882.4
162.5°	896.2	895.6	895.2	894.7	894.6	894.7	894.8	895.0	895.1	896.0	896.8
165°	914.7	914.2	913.7	913.2	912.9	912.9	912.9	912.9	912.9	913.9	914.9
167.5°	929.4	928.8	928.1	927.4	927.2	927.3	927.4	927.6	927.7	928.7	929.7
170°	937.8	937.2	936.4	935.7	935.4	935.4	935.4	935.4	935.4	936.6	937.8
172.5°	944.4	943.7	943.0	942.4	942.0	942.0	942.0	942.0	942.0	943.1	944.1
175°	951.3	950.6	950.0	949.3	949.0	949.0	949.0	949.0	949.0	950.0	951.0
177.5°	954.2	953.7	953.2	952.7	952.4	952.4	952.4	952.4	952.4	953.2	954.0
180°	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2	954.2



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1	1854.1
2.5°	1955.7	1955.7	1958.2	1967.8	1969.0	1977.3	1974.8
5°	2149.4	2164.4	2170.0	2193.8	2208.2	2214.5	2201.8
7.5°	2386.2	2428.8	2448.9	2473.9	2496.0	2502.6	2485.3
10°	2559.0	2603.4	2640.7	2663.7	2685.1	2699.5	2717.7
12.5°	2725.9	2780.6	2816.0	2848.5	2870.5	2888.7	2891.6
15°	2907.4	2989.9	3052.6	3098.7	3121.7	3133.6	3128.9
17.5°	3090.4	3166.9	3211.6	3258.5	3290.4	3292.1	3293.0
20°	3193.9	3268.5	3320.1	3355.1	3390.8	3389.2	3397.1
22.5°	3263.2	3321.8	3361.4	3386.8	3399.0	3393.0	3394.6
25°	3295.5	3313.0	3305.9	3265.4	3255.1	3217.7	3224.1
27.5°	3128.6	3046.0	2960.6	2850.7	2764.1	2694.8	2698.4
30°	2901.8	2755.8	2589.1	2449.4	2324.0	2289.1	2214.5
32.5°	2585.0	2365.9	2170.7	2040.5	1932.9	1903.7	1838.6
35°	2047.8	1835.1	1634.3	1513.6	1466.0	1399.4	1398.6
37.5°	1591.7	1404.4	1298.2	1207.7	1160.2	1119.9	1116.0
40°	1339.0	1193.0	1112.8	1047.7	1000.9	970.7	963.6
42.5°	1162.5	1044.4	969.3	929.0	892.9	877.4	865.8
45°	949.3	869.9	817.5	781.0	764.4	752.5	746.1
47.5°	794.1	740.8	705.2	680.9	667.3	654.8	658.1
50°	709.6	665.9	639.7	616.7	606.4	597.6	598.4
52.5°	641.7	602.5	581.3	564.6	551.8	545.6	542.6
55°	544.5	519.9	498.5	486.6	479.4	470.7	468.3
57.5°	464.4	445.5	428.0	414.4	412.7	404.3	405.5
60°	411.1	395.3	381.0	373.9	368.3	361.1	363.6
62.5°	367.3	354.0	341.0	335.1	329.5	324.3	325.4
65°	300.8	288.1	280.1	277.0	274.6	272.3	269.8
67.5°	239.7	232.0	227.0	220.2	215.3	214.5	212.1
70°	201.6	191.3	182.6	173.8	171.5	170.7	171.5
72.5°	161.6	155.1	152.7	148.5	147.9	145.9	147.3
75°	121.5	119.1	117.4	114.3	114.3	114.3	114.3
77.5°	89.6	88.1	87.2	86.5	85.7	84.6	84.4
80°	69.9	69.1	67.5	67.5	66.7	67.5	66.7
82.5°	52.7	52.5	51.0	51.0	50.2	49.7	50.2
85°	27.0	26.2	27.8	26.2	27.0	25.4	27.0
87.5°	11.6	11.7	11.2	11.3	10.7	12.0	10.8
90°	20.0	20.7	21.1	21.5	21.8	22.1	22.5
92.5°	30.4	30.9	31.1	30.9	30.7	30.5	30.3
95°	57.5	58.2	58.5	58.5	58.5	58.5	58.5
97.5°	89.1	89.9	90.2	90.2	90.1	90.0	90.0
100°	111.7	112.2	112.6	112.9	113.3	113.6	113.9
102.5°	138.0	138.6	138.8	138.8	138.7	138.6	138.6
105°	176.9	176.9	177.0	177.4	177.7	178.0	178.4
107.5°	220.0	220.6	220.8	220.6	220.4	220.2	219.9
110°	248.6	249.2	249.4	249.1	248.7	248.4	248.1



TEST NUMBER: P332475-840

CATALOG NUMBER: S123RDIW-S1165D755U840-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	277.2	278.0	278.3	278.3	278.2	278.1	278.1
115°	319.8	320.0	320.0	319.8	319.6	319.5	319.3
117.5°	363.2	363.2	363.0	362.5	362.0	361.6	361.1
120°	392.2	392.1	391.8	391.5	391.2	390.8	390.5
122.5°	421.4	421.0	420.6	420.1	419.6	419.2	418.7
125°	464.9	464.3	463.6	463.0	462.3	461.6	461.0
127.5°	508.0	507.1	506.1	505.4	504.6	503.9	503.1
130°	536.9	536.2	535.3	534.2	533.0	531.9	530.7
132.5°	564.7	563.9	563.1	562.2	561.3	560.4	559.5
135°	606.6	606.0	605.5	605.1	604.8	604.5	604.1
137.5°	647.4	646.8	646.1	645.5	644.8	644.2	643.6
140°	674.9	674.7	674.0	672.9	671.7	670.6	669.3
142.5°	700.0	699.8	699.3	698.4	697.5	696.6	695.7
145°	737.1	736.9	736.5	735.8	735.2	734.5	733.9
147.5°	772.2	772.2	771.7	770.7	769.7	768.7	767.7
150°	793.8	793.8	793.2	792.2	791.3	790.3	789.3
152.5°	813.7	814.1	813.7	812.8	812.0	811.1	810.3
155°	843.0	843.6	843.4	842.2	841.1	839.9	838.8
157.5°	867.9	868.6	868.4	867.5	866.6	865.7	864.6
160°	883.2	884.0	884.1	883.5	882.8	882.1	881.5
162.5°	897.7	898.5	898.4	897.3	896.3	895.1	894.0
165°	915.9	917.0	916.9	915.7	914.5	913.4	912.2
167.5°	930.8	931.8	931.8	930.8	929.7	928.7	927.7
170°	939.0	940.1	940.1	939.0	937.8	936.6	935.4
172.5°	945.1	946.1	946.1	944.9	943.8	942.6	941.5
175°	951.9	952.9	952.9	951.7	950.5	949.4	948.2
177.5°	954.8	955.6	955.5	954.6	953.6	952.7	951.8
180°	954.2	954.2	954.2	954.2	954.2	954.2	954.2

(END OF REPORT)