

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P332394-840

Luminaire Tested: **S123RDIW-S340D755U840-4F0-1E-UDD-A**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P332394-840  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-5,  
Test Lab: INNOVATION CENTER  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: NEO-RAY  
Catalog Number: S123RDIW-S340D755U840-4F0-1E-UDD-A  
Description: DEFINE 3 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE  
DOWNLIGHT 340 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING  
UPLIGHT 755 LUMENS PER FOOT, NO LENS  
Light Source: -  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 4421.5 lumens  
Efficiency: N/A  
Efficacy: 145.4 lumens/watt  
Spacing Criteria (0/90/45): 1.21 / 1.22 / 1.36  
Luminous Opening: Rectangular (W 4' x L: 0.25' x H: 0')  
CIE Type: Semi-Indirect


Input Watts (W): 30.4  
Input Voltage (V): 120  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

### Luminous Intensity Polar Plot





TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	103	103	103	103	92	92	92	92	73	73	73	55	55	55	39	39	39	31
1	94	90	86	83	84	81	78	75	64	62	60	49	48	46	35	34	33	27
2	86	79	73	68	77	71	66	62	57	53	50	43	41	39	31	30	29	23
3	78	70	63	57	70	63	57	52	50	46	43	39	36	34	28	26	25	20
4	72	62	54	49	64	56	49	45	45	40	37	35	31	29	25	23	22	17
5	66	55	47	42	59	50	43	38	40	35	32	31	28	25	23	21	19	15
6	61	49	42	36	54	45	38	33	36	31	28	28	25	22	21	18	17	14
7	56	44	37	32	50	40	34	29	33	28	24	26	22	20	19	17	15	12
8	52	40	33	28	47	37	30	26	30	25	22	23	20	18	17	15	14	11
9	48	37	30	25	44	34	27	23	27	23	19	22	18	16	16	14	12	10
10	45	34	27	22	41	31	25	21	25	21	17	20	17	14	15	13	11	9

**AVERAGE LUMINANCE (cd/sqm):**

	0°	90°	180°	270°
0°	5916	5916	5916	5916
5°	7052	5942	5232	5942
10°	8805	5908	4726	5908
15°	10336	5846	4310	5846
20°	11535	5756	3956	5756
25°	11351	5662	3739	5662
30°	8158	5574	3515	5574
35°	5447	5460	3369	5460
40°	4013	5323	3219	5323
45°	3367	5083	3073	5083
50°	2971	4767	2869	4767
55°	2607	4406	2586	4406
60°	2321	4060	2370	4060
65°	2038	3691	2203	3691
70°	1599	3361	2014	3361
75°	1406	2936	1838	2936
80°	1227	2492	1810	2492
85°	988	2013	1927	2013



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	54.0	1.2
10°-20°	168.9	3.8
20°-30°	265.3	6.0
30°-40°	276.8	6.3
40°-50°	236.9	5.4
50°-60°	180.5	4.1
60°-70°	115.7	2.6
70°-80°	55.7	1.3
80°-90°	17.5	0.4
90°-100°	36.4	0.8
100°-110°	173.3	3.9
110°-120°	416.3	9.4
120°-130°	530.1	12.0
130°-140°	566.4	12.8
140°-150°	529.7	12.0
150°-160°	427.3	9.7
160°-170°	275.7	6.2
170°-180°	95.0	2.1
0°-30°	488.2	11.0
0°-40°	764.9	17.3
0°-60°	1182.3	26.7
0°-90°	1371.2	31.0
90°-120°	626.0	14.2
90°-150°	2252.2	50.9
90°-180°	3050.0	69.0
0°-180°	4421.5	100.0

**CANDELA DISTRIBUTION:**

	0°	90°	180°	270°	360°	Flux
0°	550	550	550	550	550	
5°	653	550	484	550	653	67
15°	928	525	387	525	928	263
25°	956	477	315	477	956	411
35°	414	416	256	416	414	272
45°	221	334	202	334	221	174
55°	139	235	138	235	139	126
65°	80	145	86	145	80	79
75°	34	71	44	71	34	36
85°	8	16	16	16	8	10
90°	22	1	22	1	22	10
95°	28	45	28	45	28	24
105°	33	222	33	222	33	75
115°	437	415	437	415	437	404
125°	597	586	597	586	597	534
135°	736	729	736	729	736	568
145°	849	841	849	841	849	530
155°	925	927	925	927	925	427
165°	975	977	975	977	975	275
175°	996	1000	996	1000	996	95
180°	1000	1000	1000	1000	1000	



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	585.4	586.1	583.7	583.3	580.5	579.8	579.8	575.7	573.3	570.2	568.3
5°	652.7	656.4	654.5	650.4	643.3	641.6	637.1	630.1	622.1	612.2	607.5
7.5°	736.7	741.8	739.8	733.4	725.9	719.9	707.3	695.6	679.2	664.8	652.5
10°	805.6	800.2	796.0	789.6	782.7	771.7	758.5	740.4	719.5	703.0	684.7
12.5°	857.2	856.3	850.9	844.3	834.8	824.3	808.0	786.0	761.6	737.8	716.8
15°	927.5	928.9	925.3	918.6	904.8	886.3	861.8	852.6	817.8	791.9	766.1
17.5°	976.1	975.8	975.3	965.9	952.0	938.8	916.0	891.9	860.4	823.9	789.1
20°	1007.0	1004.6	1005.1	994.5	984.2	968.9	946.7	911.7	885.9	843.7	807.7
22.5°	1006.2	1005.7	1007.5	1003.9	996.4	984.7	967.2	937.7	904.6	862.1	821.6
25°	955.7	953.8	964.8	968.0	980.0	982.1	976.8	960.7	929.4	885.6	835.5
27.5°	799.8	798.8	819.3	845.1	877.6	902.9	927.4	939.2	929.4	898.0	847.8
30°	656.4	678.5	688.9	726.1	767.5	816.9	860.2	901.3	911.5	897.8	856.7
32.5°	545.0	564.3	573.0	604.8	643.5	701.4	766.3	824.6	865.8	876.2	851.4
35°	414.5	414.8	434.5	448.7	484.4	543.9	607.0	685.1	762.8	821.6	827.7
37.5°	330.8	331.9	344.0	358.0	384.9	416.3	471.8	536.7	626.4	716.7	769.7
40°	285.6	287.7	296.7	310.5	329.8	353.7	396.9	458.1	532.9	633.4	715.5
42.5°	256.6	260.0	264.7	275.4	287.3	309.6	344.6	391.8	459.9	554.9	649.6
45°	221.2	223.1	226.6	231.6	242.4	257.8	281.3	313.2	369.6	446.1	540.9
47.5°	195.1	194.1	197.8	201.8	209.0	219.6	235.4	261.3	301.5	362.9	443.3
50°	177.4	177.1	179.8	182.8	189.7	197.4	210.4	229.8	261.9	312.7	386.4
52.5°	160.9	161.7	163.6	167.3	172.3	178.5	190.2	204.3	231.8	275.6	337.0
55°	138.9	139.6	142.1	144.2	147.7	154.1	161.4	173.2	192.0	222.6	273.2
57.5°	120.2	119.9	122.3	122.9	126.8	132.0	137.6	146.8	160.5	183.2	217.2
60°	107.8	107.0	109.2	110.8	112.9	117.1	121.9	130.8	141.7	158.3	187.5
62.5°	96.4	96.1	97.7	99.4	101.1	104.9	108.9	115.7	124.3	138.4	161.6
65°	80.0	80.7	81.4	82.1	83.0	85.4	89.2	93.9	99.8	109.7	126.3
67.5°	62.9	63.6	63.8	65.2	67.3	68.8	71.1	75.2	79.4	87.7	97.1
70°	50.8	50.6	50.8	51.5	54.1	56.7	59.8	62.8	65.4	71.3	79.3
72.5°	43.6	43.2	43.8	44.0	45.2	45.9	47.9	50.8	54.1	58.1	63.8
75°	33.8	33.8	33.8	33.8	34.8	35.2	36.0	36.7	37.9	39.8	44.0
77.5°	25.0	25.0	25.4	25.7	25.9	26.2	26.6	27.3	27.7	28.7	30.5
80°	19.8	20.0	19.8	20.0	20.0	20.5	20.7	21.4	21.6	22.8	23.5
82.5°	14.8	14.7	14.8	15.1	15.1	15.6	15.7	16.2	16.2	16.8	17.5
85°	8.0	7.6	8.0	7.8	8.3	7.8	8.0	8.5	8.5	8.7	9.7
87.5°	6.4	6.7	6.2	6.4	6.3	6.4	6.3	6.1	6.4	6.1	5.8
90°	22.3	21.9	21.6	21.3	21.0	20.5	19.8	19.2	18.5	17.9	15.7
92.5°	24.6	24.4	24.2	24.0	23.8	23.2	22.2	21.1	20.1	19.0	17.4
95°	28.3	28.3	28.3	28.3	28.3	27.7	26.5	25.3	24.2	23.0	21.2
97.5°	30.6	30.5	30.3	30.1	30.0	29.2	27.9	26.6	25.2	23.9	35.9
100°	31.2	31.0	30.9	30.7	30.6	29.8	28.5	27.2	25.9	24.5	50.3
102.5°	31.8	31.5	31.2	30.9	30.6	32.5	36.7	40.7	44.8	48.9	77.1
105°	32.7	32.4	32.0	31.7	31.4	45.8	75.0	104.3	133.5	162.8	177.6
107.5°	102.7	124.7	146.7	168.7	190.9	212.6	234.0	255.4	276.8	298.3	296.0
110°	204.4	227.9	251.6	275.2	298.8	313.4	318.8	324.3	329.7	335.2	333.4



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	350.6	355.6	360.6	365.6	370.5	373.0	372.9	372.8	372.7	372.6	370.8
115°	437.0	436.3	435.7	434.9	434.3	433.1	431.5	429.9	428.2	426.6	425.1
117.5°	485.4	485.2	485.1	485.0	484.8	484.1	482.8	481.5	480.2	478.9	478.1
120°	518.7	518.7	518.7	518.7	518.7	518.1	516.7	515.4	514.1	512.7	512.3
122.5°	551.4	551.3	551.1	551.0	550.9	550.4	549.4	548.5	547.5	546.6	546.0
125°	597.4	597.1	596.8	596.5	596.1	595.8	595.5	595.1	594.8	594.5	593.8
127.5°	641.8	642.1	642.4	642.8	643.1	643.0	642.5	642.0	641.4	640.9	640.1
130°	670.2	670.7	671.0	671.3	671.7	671.5	670.8	670.1	669.4	668.8	668.1
132.5°	696.4	696.9	697.4	697.8	698.3	698.2	697.5	696.9	696.2	695.6	695.0
135°	736.4	736.9	737.4	737.9	738.4	738.4	737.9	737.4	736.9	736.4	735.8
137.5°	774.1	774.4	774.7	775.1	775.4	775.2	774.4	773.6	772.7	771.9	771.6
140°	796.6	797.0	797.3	797.6	798.0	797.8	797.1	796.5	795.8	795.2	794.7
142.5°	817.4	817.9	818.4	818.8	819.3	819.2	818.7	818.2	817.7	817.2	816.7
145°	849.4	849.4	849.4	849.4	849.4	849.2	848.9	848.6	848.2	847.9	847.6
147.5°	873.1	873.9	874.6	875.5	876.2	876.5	876.1	875.8	875.5	875.0	874.7
150°	891.0	891.5	892.0	892.5	893.0	893.0	892.7	892.4	892.1	891.7	891.4
152.5°	905.2	906.1	906.8	907.6	908.3	908.4	907.8	907.2	906.6	906.1	905.8
155°	925.1	926.1	927.2	928.2	929.2	929.3	928.4	927.6	926.8	925.9	925.7
157.5°	942.0	943.3	944.5	945.8	947.2	947.3	946.2	945.3	944.3	943.3	943.5
160°	952.7	953.8	955.0	956.1	957.4	957.4	956.4	955.4	954.4	953.4	953.6
162.5°	962.8	963.8	964.8	965.8	966.8	966.8	965.7	964.6	963.5	962.3	962.5
165°	974.9	976.1	977.2	978.5	979.6	979.5	978.2	976.8	975.5	974.2	974.4
167.5°	983.7	985.0	986.3	987.7	989.1	989.1	987.7	986.3	985.0	983.7	983.7
170°	989.1	990.4	991.7	993.1	994.4	994.4	993.1	991.7	990.4	989.1	989.1
172.5°	992.1	993.5	995.0	996.4	997.8	997.9	996.6	995.3	994.0	992.7	992.5
175°	996.5	997.8	999.2	1000.5	1001.8	1001.9	1000.8	999.6	998.5	997.2	997.1
177.5°	997.8	999.2	1000.5	1001.8	1003.1	1003.3	1002.2	1001.2	1000.1	999.1	999.0
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	567.4	566.9	564.3	561.3	557.3	554.7	552.6	551.5	548.1	543.9	541.2
5°	602.6	595.5	587.9	578.8	570.3	561.6	556.2	549.9	542.1	533.4	527.3
7.5°	640.1	626.2	611.4	595.9	580.8	567.1	555.0	544.7	532.4	519.9	511.2
10°	668.9	648.6	627.7	606.3	586.8	568.5	554.3	540.5	525.6	511.3	500.4
12.5°	695.1	668.4	644.3	617.9	593.0	571.1	550.8	534.4	516.5	501.3	489.0
15°	728.2	700.8	671.8	631.7	598.5	570.8	546.0	524.6	503.0	484.2	472.2
17.5°	759.1	718.1	678.8	645.5	602.4	567.7	537.6	512.0	488.2	468.3	453.4
20°	771.9	732.2	689.6	647.0	604.7	565.8	530.8	502.5	477.9	455.2	441.6
22.5°	779.6	734.7	689.7	644.0	599.1	558.7	524.0	492.9	466.2	444.7	427.9
25°	788.6	735.0	685.6	640.5	594.5	550.8	509.6	476.7	447.8	425.0	407.1
27.5°	794.6	731.4	673.1	622.9	576.3	532.8	495.0	460.1	430.7	406.6	387.4
30°	795.7	728.6	663.5	609.2	561.9	521.8	481.8	448.5	417.4	391.7	373.9
32.5°	797.2	721.6	650.5	592.8	544.3	504.7	468.5	436.6	404.8	379.5	361.2
35°	791.0	717.8	630.8	564.4	515.9	477.6	444.9	415.5	384.3	359.7	341.1
37.5°	764.3	702.6	610.4	532.5	481.8	446.4	419.7	394.0	365.4	338.9	321.4
40°	737.4	687.5	594.5	513.1	460.2	423.7	399.7	378.8	351.0	326.3	307.5
42.5°	697.3	666.9	579.5	492.8	435.8	400.6	380.3	360.7	336.4	311.2	293.6
45°	623.7	627.7	548.7	460.4	401.8	366.6	347.5	333.9	312.3	291.5	273.4
47.5°	531.5	568.9	512.5	426.0	366.2	333.1	316.4	304.5	289.8	269.5	253.0
50°	471.3	524.6	483.5	402.8	343.8	310.8	294.4	284.7	272.0	256.0	240.2
52.5°	415.8	473.1	448.5	377.0	319.4	289.3	273.3	265.3	255.2	240.1	225.9
55°	339.0	397.2	391.5	338.1	283.1	256.0	243.8	234.8	228.0	216.7	205.4
57.5°	274.3	329.3	332.2	294.8	251.0	224.2	213.7	206.9	202.5	194.0	183.5
60°	233.4	284.0	293.9	265.6	228.0	204.5	194.1	188.6	185.2	178.3	170.4
62.5°	199.5	242.6	253.8	233.5	206.0	183.9	175.8	170.7	168.2	162.4	155.3
65°	152.7	188.4	199.2	188.0	173.6	156.0	149.4	144.9	142.8	139.6	134.3
67.5°	114.8	140.9	152.8	144.8	139.6	128.5	124.3	121.9	120.0	117.8	113.4
70°	92.2	111.5	123.7	121.7	117.4	111.5	108.5	106.8	104.9	103.0	99.3
72.5°	74.1	87.5	98.9	100.0	96.5	95.3	92.6	91.9	90.8	88.6	86.4
75°	49.2	58.4	66.3	69.4	70.8	72.0	70.8	70.6	70.4	68.5	67.3
77.5°	32.2	37.2	42.2	47.5	49.7	51.2	51.6	52.5	51.8	50.9	50.3
80°	24.7	25.9	29.4	33.8	37.4	38.8	39.8	40.2	40.0	39.8	38.8
82.5°	18.0	18.9	20.6	23.7	26.7	29.0	29.6	29.5	30.0	30.2	29.4
85°	9.7	9.9	10.4	10.8	12.4	15.0	15.8	16.3	16.7	16.7	15.2
87.5°	5.8	5.2	5.0	4.6	4.9	4.7	5.6	6.2	6.7	6.3	6.6
90°	13.5	11.4	9.3	7.4	5.7	4.0	2.4	0.7	2.4	4.0	5.7
92.5°	15.8	14.1	12.5	12.0	12.4	12.9	13.3	13.8	13.3	12.9	12.4
95°	19.4	17.6	15.8	18.3	25.0	31.8	38.6	45.3	38.6	31.8	25.0
97.5°	47.7	59.6	71.5	79.0	82.0	85.0	88.1	91.1	88.1	85.0	82.0
100°	76.0	101.8	127.5	138.8	135.5	132.2	128.9	125.6	128.9	132.2	135.5
102.5°	105.1	133.3	161.5	174.3	172.0	169.6	167.2	164.8	167.2	169.6	172.0
105°	192.5	207.3	222.2	228.7	226.9	225.1	223.3	221.5	223.3	225.1	226.9
107.5°	293.6	291.2	288.9	287.0	285.6	284.1	282.7	281.1	282.7	284.1	285.6
110°	331.5	329.7	327.9	326.3	325.0	323.7	322.3	321.0	322.3	323.7	325.0





TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	369.0	367.2	365.4	363.9	362.6	361.4	360.2	359.1	360.2	361.4	362.6
115°	423.5	422.1	420.6	419.4	418.4	417.4	416.4	415.4	416.4	417.4	418.4
117.5°	477.4	476.6	475.8	474.8	473.6	472.4	471.2	470.0	471.2	472.4	473.6
120°	511.8	511.3	510.8	509.8	508.3	506.9	505.3	503.8	505.3	506.9	508.3
122.5°	545.4	544.7	544.1	543.2	542.0	540.8	539.6	538.4	539.6	540.8	542.0
125°	593.2	592.5	591.9	590.9	589.6	588.2	586.9	585.6	586.9	588.2	589.6
127.5°	639.2	638.5	637.7	636.6	635.3	634.0	632.7	631.4	632.7	634.0	635.3
130°	667.5	666.8	666.2	665.2	663.9	662.6	661.3	659.8	661.3	662.6	663.9
132.5°	694.5	694.0	693.5	692.6	691.2	689.8	688.5	687.2	688.5	689.8	691.2
135°	735.1	734.5	733.8	733.0	732.0	730.9	730.0	729.0	730.0	730.9	732.0
137.5°	771.2	770.8	770.5	769.7	768.4	767.2	765.9	764.7	765.9	767.2	768.4
140°	794.2	793.7	793.1	792.4	791.4	790.4	789.4	788.4	789.4	790.4	791.4
142.5°	816.2	815.7	815.2	814.5	813.4	812.4	811.4	810.4	811.4	812.4	813.4
145°	847.3	846.9	846.6	845.9	844.7	843.5	842.3	841.2	842.3	843.5	844.7
147.5°	874.4	874.1	873.7	873.2	872.4	871.7	870.9	870.2	870.9	871.7	872.4
150°	891.1	890.8	890.4	890.0	889.5	889.0	888.5	888.1	888.5	889.0	889.5
152.5°	905.6	905.4	905.2	905.0	904.7	904.5	904.3	904.0	904.3	904.5	904.7
155°	925.6	925.4	925.2	925.3	925.6	926.0	926.3	926.7	926.3	926.0	925.6
157.5°	943.6	943.8	944.0	944.1	944.1	944.1	944.2	944.2	944.2	944.1	944.1
160°	953.7	953.9	954.1	954.2	954.4	954.6	954.7	954.9	954.7	954.6	954.4
162.5°	962.7	962.8	963.0	963.3	963.7	964.1	964.6	965.0	964.6	964.1	963.7
165°	974.5	974.7	974.9	975.2	975.7	976.2	976.7	977.2	976.7	976.2	975.7
167.5°	983.7	983.7	983.7	984.1	984.7	985.4	986.0	986.7	986.0	985.4	984.7
170°	989.1	989.1	989.1	989.5	990.1	990.8	991.4	992.1	991.4	990.8	990.1
172.5°	992.4	992.3	992.1	992.5	993.3	994.0	994.8	995.6	994.8	994.0	993.3
175°	996.9	996.7	996.6	996.9	997.7	998.6	999.4	1000.3	999.4	998.6	997.7
177.5°	998.8	998.7	998.6	998.8	999.5	1000.1	1000.8	1001.4	1000.8	1000.1	999.5
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	540.2	537.8	536.0	532.3	529.9	527.3	524.6	526.2	526.0	525.9	525.9
5°	522.1	516.6	511.7	505.3	501.4	496.4	492.7	492.2	493.1	489.9	488.0
7.5°	504.1	496.8	489.7	482.7	475.2	469.3	465.6	463.8	461.5	459.5	457.4
10°	491.5	482.8	475.9	467.3	459.3	452.2	447.8	444.6	443.0	441.4	438.3
12.5°	478.5	470.0	461.3	451.4	443.8	435.7	432.3	428.9	425.8	423.8	419.7
15°	459.5	448.5	439.3	428.9	420.4	412.4	407.8	400.9	400.0	397.6	393.3
17.5°	440.4	428.5	415.8	408.1	398.6	390.2	383.0	380.8	374.1	371.5	367.8
20°	425.4	414.3	404.7	394.6	380.7	372.9	367.3	364.3	358.8	355.5	353.1
22.5°	412.4	401.1	390.0	378.2	366.8	358.0	353.9	349.1	346.2	341.5	339.0
25°	393.8	381.6	368.2	355.5	347.3	340.7	334.1	329.8	325.6	323.5	318.8
27.5°	372.3	359.5	347.0	337.3	327.2	320.7	314.8	311.0	305.9	302.4	299.7
30°	360.4	345.4	334.6	325.9	313.0	306.8	302.4	297.6	293.9	290.1	287.5
32.5°	346.7	333.0	322.8	311.9	302.1	295.3	289.5	285.4	282.2	278.6	276.0
35°	325.2	313.7	303.1	292.3	284.9	278.1	271.2	267.7	264.7	261.4	259.0
37.5°	305.7	294.9	284.8	274.6	265.5	259.9	254.5	251.8	247.6	245.4	243.1
40°	293.7	283.1	272.3	262.4	253.0	248.7	243.8	239.7	236.0	234.3	231.8
42.5°	280.4	269.8	260.7	250.1	242.4	236.6	232.1	227.7	224.9	222.5	221.1
45°	260.9	251.6	242.6	232.0	224.7	219.7	214.6	210.6	208.0	206.3	203.8
47.5°	242.0	232.6	223.5	214.3	207.2	201.6	196.3	193.6	190.2	188.1	186.4
50°	228.2	219.7	210.2	201.7	194.6	188.9	184.7	181.2	178.1	175.5	174.3
52.5°	215.6	206.6	198.2	190.4	182.9	176.5	172.7	169.0	166.6	163.7	162.3
55°	194.8	186.1	179.0	171.3	164.0	158.5	153.9	150.6	148.2	144.9	143.1
57.5°	175.3	167.4	159.1	152.3	144.8	140.3	136.3	131.9	129.0	126.4	124.5
60°	162.1	153.2	145.8	139.6	132.9	127.0	123.5	120.0	116.9	114.3	112.7
62.5°	148.3	140.6	133.6	126.7	120.7	115.5	111.5	108.6	105.8	104.2	102.5
65°	127.2	121.2	114.1	108.5	102.8	99.1	95.7	93.2	91.3	90.1	88.7
67.5°	107.9	102.0	95.8	90.3	86.4	83.6	81.5	79.3	78.3	76.7	75.8
70°	95.3	89.2	83.7	79.5	75.7	73.6	72.2	70.6	69.7	67.8	66.9
72.5°	81.6	77.2	73.2	69.8	66.8	64.8	63.0	61.0	59.5	57.4	56.5
75°	64.2	60.2	57.2	54.8	52.9	50.4	47.8	45.6	44.9	44.2	44.0
77.5°	47.6	45.0	42.8	40.8	38.5	36.7	36.1	35.5	35.4	35.0	35.0
80°	37.4	35.0	33.4	31.1	29.7	29.7	29.7	29.2	29.4	29.4	29.4
82.5°	27.8	25.7	24.7	23.9	23.6	23.8	23.8	23.9	23.7	24.1	23.9
85°	14.3	14.5	15.0	14.8	15.0	15.0	15.6	15.2	15.6	15.0	15.6
87.5°	6.8	7.7	8.3	8.9	9.5	9.8	10.1	10.2	10.5	10.7	10.8
90°	7.4	9.3	11.4	13.5	15.7	17.9	18.5	19.2	19.8	20.5	21.0
92.5°	12.0	12.5	14.1	15.8	17.4	19.0	20.1	21.1	22.2	23.2	23.8
95°	18.3	15.8	17.6	19.4	21.2	23.0	24.2	25.3	26.5	27.7	28.3
97.5°	79.0	71.5	59.6	47.7	35.9	23.9	25.2	26.6	27.9	29.2	30.0
100°	138.8	127.5	101.8	76.0	50.3	24.5	25.9	27.2	28.5	29.8	30.6
102.5°	174.3	161.5	133.3	105.1	77.1	48.9	44.8	40.7	36.7	32.5	30.6
105°	228.7	222.2	207.3	192.5	177.6	162.8	133.5	104.3	75.0	45.8	31.4
107.5°	287.0	288.9	291.2	293.6	296.0	298.3	276.8	255.4	234.0	212.6	190.9
110°	326.3	327.9	329.7	331.5	333.4	335.2	329.7	324.3	318.8	313.4	298.8



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	363.9	365.4	367.2	369.0	370.8	372.6	372.7	372.8	372.9	373.0	370.5
115°	419.4	420.6	422.1	423.5	425.1	426.6	428.2	429.9	431.5	433.1	434.3
117.5°	474.8	475.8	476.6	477.4	478.1	478.9	480.2	481.5	482.8	484.1	484.8
120°	509.8	510.8	511.3	511.8	512.3	512.7	514.1	515.4	516.7	518.1	518.7
122.5°	543.2	544.1	544.7	545.4	546.0	546.6	547.5	548.5	549.4	550.4	550.9
125°	590.9	591.9	592.5	593.2	593.8	594.5	594.8	595.1	595.5	595.8	596.1
127.5°	636.6	637.7	638.5	639.2	640.1	640.9	641.4	642.0	642.5	643.0	643.1
130°	665.2	666.2	666.8	667.5	668.1	668.8	669.4	670.1	670.8	671.5	671.7
132.5°	692.6	693.5	694.0	694.5	695.0	695.6	696.2	696.9	697.5	698.2	698.3
135°	733.0	733.8	734.5	735.1	735.8	736.4	736.9	737.4	737.9	738.4	738.4
137.5°	769.7	770.5	770.8	771.2	771.6	771.9	772.7	773.6	774.4	775.2	775.4
140°	792.4	793.1	793.7	794.2	794.7	795.2	795.8	796.5	797.1	797.8	798.0
142.5°	814.5	815.2	815.7	816.2	816.7	817.2	817.7	818.2	818.7	819.2	819.3
145°	845.9	846.6	846.9	847.3	847.6	847.9	848.2	848.6	848.9	849.2	849.4
147.5°	873.2	873.7	874.1	874.4	874.7	875.0	875.5	875.8	876.1	876.5	876.2
150°	890.0	890.4	890.8	891.1	891.4	891.7	892.1	892.4	892.7	893.0	893.0
152.5°	905.0	905.2	905.4	905.6	905.8	906.1	906.6	907.2	907.8	908.4	908.3
155°	925.3	925.2	925.4	925.6	925.7	925.9	926.8	927.6	928.4	929.3	929.2
157.5°	944.1	944.0	943.8	943.6	943.5	943.3	944.3	945.3	946.2	947.3	947.2
160°	954.2	954.1	953.9	953.7	953.6	953.4	954.4	955.4	956.4	957.4	957.4
162.5°	963.3	963.0	962.8	962.7	962.5	962.3	963.5	964.6	965.7	966.8	966.8
165°	975.2	974.9	974.7	974.5	974.4	974.2	975.5	976.8	978.2	979.5	979.6
167.5°	984.1	983.7	983.7	983.7	983.7	983.7	985.0	986.3	987.7	989.1	989.1
170°	989.5	989.1	989.1	989.1	989.1	989.1	990.4	991.7	993.1	994.4	994.4
172.5°	992.5	992.1	992.3	992.4	992.5	992.7	994.0	995.3	996.6	997.9	997.8
175°	996.9	996.6	996.7	996.9	997.1	997.2	998.5	999.6	1000.8	1001.9	1001.8
177.5°	998.8	998.6	998.7	998.8	999.0	999.1	1000.1	1001.2	1002.2	1003.3	1003.1
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	523.6	523.4	523.6	522.9	523.6	523.4	523.6	525.9	525.9	526.0	526.2
5°	487.3	487.1	486.4	484.2	486.4	487.1	487.3	488.0	489.9	493.1	492.2
7.5°	455.4	455.1	453.1	453.1	453.1	455.1	455.4	457.4	459.5	461.5	463.8
10°	436.7	436.9	434.0	432.4	434.0	436.9	436.7	438.3	441.4	443.0	444.6
12.5°	418.4	417.4	415.1	413.2	415.1	417.4	418.4	419.7	423.8	425.8	428.9
15°	394.4	391.9	386.4	386.8	386.4	391.9	394.4	393.3	397.6	400.0	400.9
17.5°	366.0	364.3	364.2	360.8	364.2	364.3	366.0	367.8	371.5	374.1	380.8
20°	349.4	348.2	348.7	345.4	348.7	348.2	349.4	353.1	355.5	358.8	364.3
22.5°	336.4	335.2	333.3	332.2	333.3	335.2	336.4	339.0	341.5	346.2	349.1
25°	317.4	315.5	313.7	314.8	313.7	315.5	317.4	318.8	323.5	325.6	329.8
27.5°	298.4	297.0	295.1	294.9	295.1	297.0	298.4	299.7	302.4	305.9	311.0
30°	286.3	284.9	284.0	282.8	284.0	284.9	286.3	287.5	290.1	293.9	297.6
32.5°	274.1	273.8	272.2	271.9	272.2	273.8	274.1	276.0	278.6	282.2	285.4
35°	258.1	256.7	256.2	256.4	256.2	256.7	258.1	259.0	261.4	264.7	267.7
37.5°	242.9	241.1	240.1	239.3	240.1	241.1	242.9	243.1	245.4	247.6	251.8
40°	232.0	230.1	229.6	229.1	229.6	230.1	232.0	231.8	234.3	236.0	239.7
42.5°	219.7	219.0	218.7	217.8	218.7	219.0	219.7	221.1	222.5	224.9	227.7
45°	203.1	202.8	201.4	201.9	201.4	202.8	203.1	203.8	206.3	208.0	210.6
47.5°	185.4	184.4	183.4	184.1	183.4	184.4	185.4	186.4	188.1	190.2	193.6
50°	173.4	172.9	170.8	171.3	170.8	172.9	173.4	174.3	175.5	178.1	181.2
52.5°	161.4	159.6	158.8	158.4	158.8	159.6	161.4	162.3	163.7	166.6	169.0
55°	141.4	139.3	138.4	137.8	138.4	139.3	141.4	143.1	144.9	148.2	150.6
57.5°	121.8	121.3	120.5	121.0	120.5	121.3	121.8	124.5	126.4	129.0	131.9
60°	110.4	110.4	110.4	110.1	110.4	110.4	110.4	112.7	114.3	116.9	120.0
62.5°	101.5	100.9	100.8	101.1	100.8	100.9	101.5	102.5	104.2	105.8	108.6
65°	88.0	87.8	86.8	86.5	86.8	87.8	88.0	88.7	90.1	91.3	93.2
67.5°	75.2	74.4	74.1	73.8	74.1	74.4	75.2	75.8	76.7	78.3	79.3
70°	65.6	65.1	63.7	64.0	63.7	65.1	65.6	66.9	67.8	69.7	70.6
72.5°	55.3	54.8	54.5	54.2	54.5	54.8	55.3	56.5	57.4	59.5	61.0
75°	43.7	43.5	43.3	44.2	43.3	43.5	43.7	44.0	44.2	44.9	45.6
77.5°	35.0	35.0	35.2	34.8	35.2	35.0	35.0	35.0	35.0	35.4	35.5
80°	29.4	29.4	29.2	29.2	29.2	29.4	29.4	29.4	29.4	29.4	29.2
82.5°	23.5	23.7	23.9	23.5	23.9	23.7	23.5	23.9	24.1	23.7	23.9
85°	15.6	15.2	15.8	15.6	15.8	15.2	15.6	15.6	15.0	15.6	15.2
87.5°	11.2	10.9	11.0	11.2	11.0	10.9	11.2	10.8	10.7	10.5	10.2
90°	21.3	21.6	21.9	22.3	21.9	21.6	21.3	21.0	20.5	19.8	19.2
92.5°	24.0	24.2	24.4	24.6	24.4	24.2	24.0	23.8	23.2	22.2	21.1
95°	28.3	28.3	28.3	28.3	28.3	28.3	28.3	28.3	27.7	26.5	25.3
97.5°	30.1	30.3	30.5	30.6	30.5	30.3	30.1	30.0	29.2	27.9	26.6
100°	30.7	30.9	31.0	31.2	31.0	30.9	30.7	30.6	29.8	28.5	27.2
102.5°	30.9	31.2	31.5	31.8	31.5	31.2	30.9	30.6	32.5	36.7	40.7
105°	31.7	32.0	32.4	32.7	32.4	32.0	31.7	31.4	45.8	75.0	104.3
107.5°	168.7	146.7	124.7	102.7	124.7	146.7	168.7	190.9	212.6	234.0	255.4
110°	275.2	251.6	227.9	204.4	227.9	251.6	275.2	298.8	313.4	318.8	324.3



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	365.6	360.6	355.6	350.6	355.6	360.6	365.6	370.5	373.0	372.9	372.8
115°	434.9	435.7	436.3	437.0	436.3	435.7	434.9	434.3	433.1	431.5	429.9
117.5°	485.0	485.1	485.2	485.4	485.2	485.1	485.0	484.8	484.1	482.8	481.5
120°	518.7	518.7	518.7	518.7	518.7	518.7	518.7	518.7	518.1	516.7	515.4
122.5°	551.0	551.1	551.3	551.4	551.3	551.1	551.0	550.9	550.4	549.4	548.5
125°	596.5	596.8	597.1	597.4	597.1	596.8	596.5	596.1	595.8	595.5	595.1
127.5°	642.8	642.4	642.1	641.8	642.1	642.4	642.8	643.1	643.0	642.5	642.0
130°	671.3	671.0	670.7	670.2	670.7	671.0	671.3	671.7	671.5	670.8	670.1
132.5°	697.8	697.4	696.9	696.4	696.9	697.4	697.8	698.3	698.2	697.5	696.9
135°	737.9	737.4	736.9	736.4	736.9	737.4	737.9	738.4	738.4	737.9	737.4
137.5°	775.1	774.7	774.4	774.1	774.4	774.7	775.1	775.4	775.2	774.4	773.6
140°	797.6	797.3	797.0	796.6	797.0	797.3	797.6	798.0	797.8	797.1	796.5
142.5°	818.8	818.4	817.9	817.4	817.9	818.4	818.8	819.3	819.2	818.7	818.2
145°	849.4	849.4	849.4	849.4	849.4	849.4	849.4	849.4	849.2	848.9	848.6
147.5°	875.5	874.6	873.9	873.1	873.9	874.6	875.5	876.2	876.5	876.1	875.8
150°	892.5	892.0	891.5	891.0	891.5	892.0	892.5	893.0	893.0	892.7	892.4
152.5°	907.6	906.8	906.1	905.2	906.1	906.8	907.6	908.3	908.4	907.8	907.2
155°	928.2	927.2	926.1	925.1	926.1	927.2	928.2	929.2	929.3	928.4	927.6
157.5°	945.8	944.5	943.3	942.0	943.3	944.5	945.8	947.2	947.3	946.2	945.3
160°	956.1	955.0	953.8	952.7	953.8	955.0	956.1	957.4	957.4	956.4	955.4
162.5°	965.8	964.8	963.8	962.8	963.8	964.8	965.8	966.8	966.8	965.7	964.6
165°	978.5	977.2	976.1	974.9	976.1	977.2	978.5	979.6	979.5	978.2	976.8
167.5°	987.7	986.3	985.0	983.7	985.0	986.3	987.7	989.1	989.1	987.7	986.3
170°	993.1	991.7	990.4	989.1	990.4	991.7	993.1	994.4	994.4	993.1	991.7
172.5°	996.4	995.0	993.5	992.1	993.5	995.0	996.4	997.8	997.9	996.6	995.3
175°	1000.5	999.2	997.8	996.5	997.8	999.2	1000.5	1001.8	1001.9	1000.8	999.6
177.5°	1001.8	1000.5	999.2	997.8	999.2	1000.5	1001.8	1003.1	1003.3	1002.2	1001.2
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	524.6	527.3	529.9	532.3	536.0	537.8	540.2	541.2	543.9	548.1	551.5
5°	492.7	496.4	501.4	505.3	511.7	516.6	522.1	527.3	533.4	542.1	549.9
7.5°	465.6	469.3	475.2	482.7	489.7	496.8	504.1	511.2	519.9	532.4	544.7
10°	447.8	452.2	459.3	467.3	475.9	482.8	491.5	500.4	511.3	525.6	540.5
12.5°	432.3	435.7	443.8	451.4	461.3	470.0	478.5	489.0	501.3	516.5	534.4
15°	407.8	412.4	420.4	428.9	439.3	448.5	459.5	472.2	484.2	503.0	524.6
17.5°	383.0	390.2	398.6	408.1	415.8	428.5	440.4	453.4	468.3	488.2	512.0
20°	367.3	372.9	380.7	394.6	404.7	414.3	425.4	441.6	455.2	477.9	502.5
22.5°	353.9	358.0	366.8	378.2	390.0	401.1	412.4	427.9	444.7	466.2	492.9
25°	334.1	340.7	347.3	355.5	368.2	381.6	393.8	407.1	425.0	447.8	476.7
27.5°	314.8	320.7	327.2	337.3	347.0	359.5	372.3	387.4	406.6	430.7	460.1
30°	302.4	306.8	313.0	325.9	334.6	345.4	360.4	373.9	391.7	417.4	448.5
32.5°	289.5	295.3	302.1	311.9	322.8	333.0	346.7	361.2	379.5	404.8	436.6
35°	271.2	278.1	284.9	292.3	303.1	313.7	325.2	341.1	359.7	384.3	415.5
37.5°	254.5	259.9	265.5	274.6	284.8	294.9	305.7	321.4	338.9	365.4	394.0
40°	243.8	248.7	253.0	262.4	272.3	283.1	293.7	307.5	326.3	351.0	378.8
42.5°	232.1	236.6	242.4	250.1	260.7	269.8	280.4	293.6	311.2	336.4	360.7
45°	214.6	219.7	224.7	232.0	242.6	251.6	260.9	273.4	291.5	312.3	333.9
47.5°	196.3	201.6	207.2	214.3	223.5	232.6	242.0	253.0	269.5	289.8	304.5
50°	184.7	188.9	194.6	201.7	210.2	219.7	228.2	240.2	256.0	272.0	284.7
52.5°	172.7	176.5	182.9	190.4	198.2	206.6	215.6	225.9	240.1	255.2	265.3
55°	153.9	158.5	164.0	171.3	179.0	186.1	194.8	205.4	216.7	228.0	234.8
57.5°	136.3	140.3	144.8	152.3	159.1	167.4	175.3	183.5	194.0	202.5	206.9
60°	123.5	127.0	132.9	139.6	145.8	153.2	162.1	170.4	178.3	185.2	188.6
62.5°	111.5	115.5	120.7	126.7	133.6	140.6	148.3	155.3	162.4	168.2	170.7
65°	95.7	99.1	102.8	108.5	114.1	121.2	127.2	134.3	139.6	142.8	144.9
67.5°	81.5	83.6	86.4	90.3	95.8	102.0	107.9	113.4	117.8	120.0	121.9
70°	72.2	73.6	75.7	79.5	83.7	89.2	95.3	99.3	103.0	104.9	106.8
72.5°	63.0	64.8	66.8	69.8	73.2	77.2	81.6	86.4	88.6	90.8	91.9
75°	47.8	50.4	52.9	54.8	57.2	60.2	64.2	67.3	68.5	70.4	70.6
77.5°	36.1	36.7	38.5	40.8	42.8	45.0	47.6	50.3	50.9	51.8	52.5
80°	29.7	29.7	29.7	31.1	33.4	35.0	37.4	38.8	39.8	40.0	40.2
82.5°	23.8	23.8	23.6	23.9	24.7	25.7	27.8	29.4	30.2	30.0	29.5
85°	15.6	15.0	15.0	14.8	15.0	14.5	14.3	15.2	16.7	16.7	16.3
87.5°	10.1	9.8	9.5	8.9	8.3	7.7	6.8	6.6	6.3	6.7	6.2
90°	18.5	17.9	15.7	13.5	11.4	9.3	7.4	5.7	4.0	2.4	0.7
92.5°	20.1	19.0	17.4	15.8	14.1	12.5	12.0	12.4	12.9	13.3	13.8
95°	24.2	23.0	21.2	19.4	17.6	15.8	18.3	25.0	31.8	38.6	45.3
97.5°	25.2	23.9	35.9	47.7	59.6	71.5	79.0	82.0	85.0	88.1	91.1
100°	25.9	24.5	50.3	76.0	101.8	127.5	138.8	135.5	132.2	128.9	125.6
102.5°	44.8	48.9	77.1	105.1	133.3	161.5	174.3	172.0	169.6	167.2	164.8
105°	133.5	162.8	177.6	192.5	207.3	222.2	228.7	226.9	225.1	223.3	221.5
107.5°	276.8	298.3	296.0	293.6	291.2	288.9	287.0	285.6	284.1	282.7	281.1
110°	329.7	335.2	333.4	331.5	329.7	327.9	326.3	325.0	323.7	322.3	321.0



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	372.7	372.6	370.8	369.0	367.2	365.4	363.9	362.6	361.4	360.2	359.1
115°	428.2	426.6	425.1	423.5	422.1	420.6	419.4	418.4	417.4	416.4	415.4
117.5°	480.2	478.9	478.1	477.4	476.6	475.8	474.8	473.6	472.4	471.2	470.0
120°	514.1	512.7	512.3	511.8	511.3	510.8	509.8	508.3	506.9	505.3	503.8
122.5°	547.5	546.6	546.0	545.4	544.7	544.1	543.2	542.0	540.8	539.6	538.4
125°	594.8	594.5	593.8	593.2	592.5	591.9	590.9	589.6	588.2	586.9	585.6
127.5°	641.4	640.9	640.1	639.2	638.5	637.7	636.6	635.3	634.0	632.7	631.4
130°	669.4	668.8	668.1	667.5	666.8	666.2	665.2	663.9	662.6	661.3	659.8
132.5°	696.2	695.6	695.0	694.5	694.0	693.5	692.6	691.2	689.8	688.5	687.2
135°	736.9	736.4	735.8	735.1	734.5	733.8	733.0	732.0	730.9	730.0	729.0
137.5°	772.7	771.9	771.6	771.2	770.8	770.5	769.7	768.4	767.2	765.9	764.7
140°	795.8	795.2	794.7	794.2	793.7	793.1	792.4	791.4	790.4	789.4	788.4
142.5°	817.7	817.2	816.7	816.2	815.7	815.2	814.5	813.4	812.4	811.4	810.4
145°	848.2	847.9	847.6	847.3	846.9	846.6	845.9	844.7	843.5	842.3	841.2
147.5°	875.5	875.0	874.7	874.4	874.1	873.7	873.2	872.4	871.7	870.9	870.2
150°	892.1	891.7	891.4	891.1	890.8	890.4	890.0	889.5	889.0	888.5	888.1
152.5°	906.6	906.1	905.8	905.6	905.4	905.2	905.0	904.7	904.5	904.3	904.0
155°	926.8	925.9	925.7	925.6	925.4	925.2	925.3	925.6	926.0	926.3	926.7
157.5°	944.3	943.3	943.5	943.6	943.8	944.0	944.1	944.1	944.1	944.2	944.2
160°	954.4	953.4	953.6	953.7	953.9	954.1	954.2	954.4	954.6	954.7	954.9
162.5°	963.5	962.3	962.5	962.7	962.8	963.0	963.3	963.7	964.1	964.6	965.0
165°	975.5	974.2	974.4	974.5	974.7	974.9	975.2	975.7	976.2	976.7	977.2
167.5°	985.0	983.7	983.7	983.7	983.7	983.7	984.1	984.7	985.4	986.0	986.7
170°	990.4	989.1	989.1	989.1	989.1	989.1	989.5	990.1	990.8	991.4	992.1
172.5°	994.0	992.7	992.5	992.4	992.3	992.1	992.5	993.3	994.0	994.8	995.6
175°	998.5	997.2	997.1	996.9	996.7	996.6	996.9	997.7	998.6	999.4	1000.3
177.5°	1000.1	999.1	999.0	998.8	998.7	998.6	998.8	999.5	1000.1	1000.8	1001.4
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	552.6	554.7	557.3	561.3	564.3	566.9	567.4	568.3	570.2	573.3	575.7
5°	556.2	561.6	570.3	578.8	587.9	595.5	602.6	607.5	612.2	622.1	630.1
7.5°	555.0	567.1	580.8	595.9	611.4	626.2	640.1	652.5	664.8	679.2	695.6
10°	554.3	568.5	586.8	606.3	627.7	648.6	668.9	684.7	703.0	719.5	740.4
12.5°	550.8	571.1	593.0	617.9	644.3	668.4	695.1	716.8	737.8	761.6	786.0
15°	546.0	570.8	598.5	631.7	671.8	700.8	728.2	766.1	791.9	817.8	852.6
17.5°	537.6	567.7	602.4	645.5	678.8	718.1	759.1	789.1	823.9	860.4	891.9
20°	530.8	565.8	604.7	647.0	689.6	732.2	771.9	807.7	843.7	885.9	911.7
22.5°	524.0	558.7	599.1	644.0	689.7	734.7	779.6	821.6	862.1	904.6	937.7
25°	509.6	550.8	594.5	640.5	685.6	735.0	788.6	835.5	885.6	929.4	960.7
27.5°	495.0	532.8	576.3	622.9	673.1	731.4	794.6	847.8	898.0	929.4	939.2
30°	481.8	521.8	561.9	609.2	663.5	728.6	795.7	856.7	897.8	911.5	901.3
32.5°	468.5	504.7	544.3	592.8	650.5	721.6	797.2	851.4	876.2	865.8	824.6
35°	444.9	477.6	515.9	564.4	630.8	717.8	791.0	827.7	821.6	762.8	685.1
37.5°	419.7	446.4	481.8	532.5	610.4	702.6	764.3	769.7	716.7	626.4	536.7
40°	399.7	423.7	460.2	513.1	594.5	687.5	737.4	715.5	633.4	532.9	458.1
42.5°	380.3	400.6	435.8	492.8	579.5	666.9	697.3	649.6	554.9	459.9	391.8
45°	347.5	366.6	401.8	460.4	548.7	627.7	623.7	540.9	446.1	369.6	313.2
47.5°	316.4	333.1	366.2	426.0	512.5	568.9	531.5	443.3	362.9	301.5	261.3
50°	294.4	310.8	343.8	402.8	483.5	524.6	471.3	386.4	312.7	261.9	229.8
52.5°	273.3	289.3	319.4	377.0	448.5	473.1	415.8	337.0	275.6	231.8	204.3
55°	243.8	256.0	283.1	338.1	391.5	397.2	339.0	273.2	222.6	192.0	173.2
57.5°	213.7	224.2	251.0	294.8	332.2	329.3	274.3	217.2	183.2	160.5	146.8
60°	194.1	204.5	228.0	265.6	293.9	284.0	233.4	187.5	158.3	141.7	130.8
62.5°	175.8	183.9	206.0	233.5	253.8	242.6	199.5	161.6	138.4	124.3	115.7
65°	149.4	156.0	173.6	188.0	199.2	188.4	152.7	126.3	109.7	99.8	93.9
67.5°	124.3	128.5	139.6	144.8	152.8	140.9	114.8	97.1	87.7	79.4	75.2
70°	108.5	111.5	117.4	121.7	123.7	111.5	92.2	79.3	71.3	65.4	62.8
72.5°	92.6	95.3	96.5	100.0	98.9	87.5	74.1	63.8	58.1	54.1	50.8
75°	70.8	72.0	70.8	69.4	66.3	58.4	49.2	44.0	39.8	37.9	36.7
77.5°	51.6	51.2	49.7	47.5	42.2	37.2	32.2	30.5	28.7	27.7	27.3
80°	39.8	38.8	37.4	33.8	29.4	25.9	24.7	23.5	22.8	21.6	21.4
82.5°	29.6	29.0	26.7	23.7	20.6	18.9	18.0	17.5	16.8	16.2	16.2
85°	15.8	15.0	12.4	10.8	10.4	9.9	9.7	9.7	8.7	8.5	8.5
87.5°	5.6	4.7	4.9	4.6	5.0	5.2	5.8	5.8	6.1	6.4	6.1
90°	2.4	4.0	5.7	7.4	9.3	11.4	13.5	15.7	17.9	18.5	19.2
92.5°	13.3	12.9	12.4	12.0	12.5	14.1	15.8	17.4	19.0	20.1	21.1
95°	38.6	31.8	25.0	18.3	15.8	17.6	19.4	21.2	23.0	24.2	25.3
97.5°	88.1	85.0	82.0	79.0	71.5	59.6	47.7	35.9	23.9	25.2	26.6
100°	128.9	132.2	135.5	138.8	127.5	101.8	76.0	50.3	24.5	25.9	27.2
102.5°	167.2	169.6	172.0	174.3	161.5	133.3	105.1	77.1	48.9	44.8	40.7
105°	223.3	225.1	226.9	228.7	222.2	207.3	192.5	177.6	162.8	133.5	104.3
107.5°	282.7	284.1	285.6	287.0	288.9	291.2	293.6	296.0	298.3	276.8	255.4
110°	322.3	323.7	325.0	326.3	327.9	329.7	331.5	333.4	335.2	329.7	324.3





TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	360.2	361.4	362.6	363.9	365.4	367.2	369.0	370.8	372.6	372.7	372.8
115°	416.4	417.4	418.4	419.4	420.6	422.1	423.5	425.1	426.6	428.2	429.9
117.5°	471.2	472.4	473.6	474.8	475.8	476.6	477.4	478.1	478.9	480.2	481.5
120°	505.3	506.9	508.3	509.8	510.8	511.3	511.8	512.3	512.7	514.1	515.4
122.5°	539.6	540.8	542.0	543.2	544.1	544.7	545.4	546.0	546.6	547.5	548.5
125°	586.9	588.2	589.6	590.9	591.9	592.5	593.2	593.8	594.5	594.8	595.1
127.5°	632.7	634.0	635.3	636.6	637.7	638.5	639.2	640.1	640.9	641.4	642.0
130°	661.3	662.6	663.9	665.2	666.2	666.8	667.5	668.1	668.8	669.4	670.1
132.5°	688.5	689.8	691.2	692.6	693.5	694.0	694.5	695.0	695.6	696.2	696.9
135°	730.0	730.9	732.0	733.0	733.8	734.5	735.1	735.8	736.4	736.9	737.4
137.5°	765.9	767.2	768.4	769.7	770.5	770.8	771.2	771.6	771.9	772.7	773.6
140°	789.4	790.4	791.4	792.4	793.1	793.7	794.2	794.7	795.2	795.8	796.5
142.5°	811.4	812.4	813.4	814.5	815.2	815.7	816.2	816.7	817.2	817.7	818.2
145°	842.3	843.5	844.7	845.9	846.6	846.9	847.3	847.6	847.9	848.2	848.6
147.5°	870.9	871.7	872.4	873.2	873.7	874.1	874.4	874.7	875.0	875.5	875.8
150°	888.5	889.0	889.5	890.0	890.4	890.8	891.1	891.4	891.7	892.1	892.4
152.5°	904.3	904.5	904.7	905.0	905.2	905.4	905.6	905.8	906.1	906.6	907.2
155°	926.3	926.0	925.6	925.3	925.2	925.4	925.6	925.7	925.9	926.8	927.6
157.5°	944.2	944.1	944.1	944.1	944.0	943.8	943.6	943.5	943.3	944.3	945.3
160°	954.7	954.6	954.4	954.2	954.1	953.9	953.7	953.6	953.4	954.4	955.4
162.5°	964.6	964.1	963.7	963.3	963.0	962.8	962.7	962.5	962.3	963.5	964.6
165°	976.7	976.2	975.7	975.2	974.9	974.7	974.5	974.4	974.2	975.5	976.8
167.5°	986.0	985.4	984.7	984.1	983.7	983.7	983.7	983.7	983.7	985.0	986.3
170°	991.4	990.8	990.1	989.5	989.1	989.1	989.1	989.1	989.1	990.4	991.7
172.5°	994.8	994.0	993.3	992.5	992.1	992.3	992.4	992.5	992.7	994.0	995.3
175°	999.4	998.6	997.7	996.9	996.6	996.7	996.9	997.1	997.2	998.5	999.6
177.5°	1000.8	1000.1	999.5	998.8	998.6	998.7	998.8	999.0	999.1	1000.1	1001.2
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
0°	549.6	549.6	549.6	549.6	549.6	549.6	549.6
2.5°	579.8	579.8	580.5	583.3	583.7	586.1	585.4
5°	637.1	641.6	643.3	650.4	654.5	656.4	652.7
7.5°	707.3	719.9	725.9	733.4	739.8	741.8	736.7
10°	758.5	771.7	782.7	789.6	796.0	800.2	805.6
12.5°	808.0	824.3	834.8	844.3	850.9	856.3	857.2
15°	861.8	886.3	904.8	918.6	925.3	928.9	927.5
17.5°	916.0	938.8	952.0	965.9	975.3	975.8	976.1
20°	946.7	968.9	984.2	994.5	1005.1	1004.6	1007.0
22.5°	967.2	984.7	996.4	1003.9	1007.5	1005.7	1006.2
25°	976.8	982.1	980.0	968.0	964.8	953.8	955.7
27.5°	927.4	902.9	877.6	845.1	819.3	798.8	799.8
30°	860.2	816.9	767.5	726.1	688.9	678.5	656.4
32.5°	766.3	701.4	643.5	604.8	573.0	564.3	545.0
35°	607.0	543.9	484.4	448.7	434.5	414.8	414.5
37.5°	471.8	416.3	384.9	358.0	344.0	331.9	330.8
40°	396.9	353.7	329.8	310.5	296.7	287.7	285.6
42.5°	344.6	309.6	287.3	275.4	264.7	260.0	256.6
45°	281.3	257.8	242.4	231.6	226.6	223.1	221.2
47.5°	235.4	219.6	209.0	201.8	197.8	194.1	195.1
50°	210.4	197.4	189.7	182.8	179.8	177.1	177.4
52.5°	190.2	178.5	172.3	167.3	163.6	161.7	160.9
55°	161.4	154.1	147.7	144.2	142.1	139.6	138.9
57.5°	137.6	132.0	126.8	122.9	122.3	119.9	120.2
60°	121.9	117.1	112.9	110.8	109.2	107.0	107.8
62.5°	108.9	104.9	101.1	99.4	97.7	96.1	96.4
65°	89.2	85.4	83.0	82.1	81.4	80.7	80.0
67.5°	71.1	68.8	67.3	65.2	63.8	63.6	62.9
70°	59.8	56.7	54.1	51.5	50.8	50.6	50.8
72.5°	47.9	45.9	45.2	44.0	43.8	43.2	43.6
75°	36.0	35.2	34.8	33.8	33.8	33.8	33.8
77.5°	26.6	26.2	25.9	25.7	25.4	25.0	25.0
80°	20.7	20.5	20.0	20.0	19.8	20.0	19.8
82.5°	15.7	15.6	15.1	15.1	14.8	14.7	14.8
85°	8.0	7.8	8.3	7.8	8.0	7.6	8.0
87.5°	6.3	6.4	6.3	6.4	6.2	6.7	6.4
90°	19.8	20.5	21.0	21.3	21.6	21.9	22.3
92.5°	22.2	23.2	23.8	24.0	24.2	24.4	24.6
95°	26.5	27.7	28.3	28.3	28.3	28.3	28.3
97.5°	27.9	29.2	30.0	30.1	30.3	30.5	30.6
100°	28.5	29.8	30.6	30.7	30.9	31.0	31.2
102.5°	36.7	32.5	30.6	30.9	31.2	31.5	31.8
105°	75.0	45.8	31.4	31.7	32.0	32.4	32.7
107.5°	234.0	212.6	190.9	168.7	146.7	124.7	102.7
110°	318.8	313.4	298.8	275.2	251.6	227.9	204.4



TEST NUMBER: P332394-840

CATALOG NUMBER: S123RDIW-S340D755U840-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
112.5°	372.9	373.0	370.5	365.6	360.6	355.6	350.6
115°	431.5	433.1	434.3	434.9	435.7	436.3	437.0
117.5°	482.8	484.1	484.8	485.0	485.1	485.2	485.4
120°	516.7	518.1	518.7	518.7	518.7	518.7	518.7
122.5°	549.4	550.4	550.9	551.0	551.1	551.3	551.4
125°	595.5	595.8	596.1	596.5	596.8	597.1	597.4
127.5°	642.5	643.0	643.1	642.8	642.4	642.1	641.8
130°	670.8	671.5	671.7	671.3	671.0	670.7	670.2
132.5°	697.5	698.2	698.3	697.8	697.4	696.9	696.4
135°	737.9	738.4	738.4	737.9	737.4	736.9	736.4
137.5°	774.4	775.2	775.4	775.1	774.7	774.4	774.1
140°	797.1	797.8	798.0	797.6	797.3	797.0	796.6
142.5°	818.7	819.2	819.3	818.8	818.4	817.9	817.4
145°	848.9	849.2	849.4	849.4	849.4	849.4	849.4
147.5°	876.1	876.5	876.2	875.5	874.6	873.9	873.1
150°	892.7	893.0	893.0	892.5	892.0	891.5	891.0
152.5°	907.8	908.4	908.3	907.6	906.8	906.1	905.2
155°	928.4	929.3	929.2	928.2	927.2	926.1	925.1
157.5°	946.2	947.3	947.2	945.8	944.5	943.3	942.0
160°	956.4	957.4	957.4	956.1	955.0	953.8	952.7
162.5°	965.7	966.8	966.8	965.8	964.8	963.8	962.8
165°	978.2	979.5	979.6	978.5	977.2	976.1	974.9
167.5°	987.7	989.1	989.1	987.7	986.3	985.0	983.7
170°	993.1	994.4	994.4	993.1	991.7	990.4	989.1
172.5°	996.6	997.9	997.8	996.4	995.0	993.5	992.1
175°	1000.8	1001.9	1001.8	1000.5	999.2	997.8	996.5
177.5°	1002.2	1003.3	1003.1	1001.8	1000.5	999.2	997.8
180°	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3	1000.3

(END OF REPORT)