

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P332728-830

Luminaire Tested: **S124DIW-S350D1050U830-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P332728-830
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-10,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S124DIW-S350D1050U830-4F0-1E-UDD-A1
Description: DEFINE 4 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 350 LUMENS PER FOOT, ASYMMETRIC DIFFUSER
UPLIGHT 1050 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4914.7 lumens
Efficiency: N/A
Efficacy: 129.3 lumens/watt
Spacing Criteria (0/90/45): 1.31 / 1.23 / 1.41
Luminous Opening: Rectangular (W 4' x L: 0.33' x H: 0')
CIE Type: Semi-Indirect


Input Watts (W): 38
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

Luminous Intensity Polar Plot



— 0°-180° - - 45°-225° - · - · 90°-270° - · - · 135°-315°



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20	
RC	80					70					50					30					10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0	
RCR																						
0	102	102	102	102	92	92	92	92	72	72	72	54	54	54	38	38	38	30				
1	93	89	86	82	84	80	77	74	63	61	59	48	47	45	34	33	32	26				
2	85	78	72	67	76	70	65	61	56	52	49	42	40	38	30	29	27	22				
3	78	69	62	56	70	62	56	51	49	45	42	37	35	32	27	25	23	19				
4	71	61	53	47	64	55	48	43	44	39	35	33	30	28	24	22	20	16				
5	65	54	46	41	58	49	42	37	39	34	31	30	27	24	21	19	18	14				
6	60	48	41	35	54	44	37	32	35	30	27	27	24	21	19	17	16	12				
7	55	44	36	31	50	40	33	28	32	27	23	25	21	19	18	16	14	11				
8	51	39	32	27	46	36	29	25	29	24	21	22	19	17	16	14	12	10				
9	48	36	29	24	43	33	26	22	26	22	18	21	17	15	15	13	11	9				
10	44	33	26	21	40	30	24	20	24	20	16	19	16	13	14	12	10	8				

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	4347	4347	4347	4347
5°	5119	4358	3847	4358
10°	6129	4339	3463	4339
15°	7252	4296	3181	4296
20°	8076	4250	2928	4250
25°	8206	4185	2754	4185
30°	6982	4121	2699	4121
35°	5368	4018	2699	4018
40°	4185	3898	2751	3898
45°	3489	3716	2797	3716
50°	3071	3493	2891	3493
55°	2814	3227	3008	3227
60°	2635	2989	3147	2989
65°	2455	2722	3265	2722
70°	2242	2460	3338	2460
75°	2006	2165	3300	2165
80°	1678	1776	3194	1776
85°	1241	1288	3057	1288



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	52.5	1.1
10°-20°	161.7	3.3
20°-30°	256.4	5.2
30°-40°	285.4	5.8
40°-50°	259.8	5.3
50°-60°	212.3	4.3
60°-70°	151.5	3.1
70°-80°	83.4	1.7
80°-90°	26.5	0.5
90°-100°	81.4	1.7
100°-110°	241.2	4.9
110°-120°	409.4	8.3
120°-130°	539.9	11.0
130°-140°	606.3	12.3
140°-150°	595.8	12.1
150°-160°	501.1	10.2
160°-170°	333.4	6.8
170°-180°	116.7	2.4
0°-30°	470.6	9.6
0°-40°	755.9	15.4
0°-60°	1227.9	25.0
0°-90°	1489.4	30.3
90°-120°	732.1	14.9
90°-150°	2474.1	50.3
90°-180°	3425.0	69.7
0°-180°	4914.7	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	538	538	538	538	538	
5°	632	538	475	538	632	64
15°	868	514	381	514	868	245
25°	921	470	309	470	921	406
35°	545	408	274	408	545	346
45°	306	326	245	326	306	241
55°	200	229	214	229	200	181
65°	128	142	171	142	128	127
75°	64	69	106	69	64	68
85°	13	14	33	14	13	17
90°	29	3	29	3	29	15
95°	75	57	75	57	75	79
105°	233	222	233	222	233	246
115°	412	416	412	416	412	408
125°	602	606	602	606	602	537
135°	783	782	783	782	783	605
145°	951	950	951	950	951	595
155°	1088	1088	1088	1088	1088	501
165°	1182	1185	1182	1185	1182	333
175°	1227	1233	1227	1233	1227	117
180°	1235	1235	1235	1235	1235	



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5
2.5°	573.1	573.0	571.2	570.8	569.6	568.0	567.6	564.7	559.0	556.3	555.6
5°	631.7	636.2	630.4	629.2	628.6	621.2	617.5	613.0	602.8	596.7	592.0
7.5°	701.7	702.2	699.6	697.7	691.9	685.5	675.9	665.6	653.4	640.7	631.1
10°	747.7	749.5	746.6	746.2	734.8	727.6	713.4	701.3	687.5	672.1	658.1
12.5°	796.3	793.8	792.3	782.8	780.6	767.6	751.0	738.7	717.3	699.6	680.9
15°	867.7	862.8	859.7	846.6	840.1	822.0	804.4	790.8	762.9	736.3	716.2
17.5°	909.6	914.5	907.4	901.9	885.2	872.5	854.5	826.0	804.2	771.2	745.8
20°	940.0	940.5	936.4	930.9	917.8	901.6	882.0	850.8	824.7	791.9	757.1
22.5°	948.2	948.3	946.6	941.4	931.4	918.4	898.6	872.5	840.9	805.3	770.4
25°	921.2	920.4	922.4	928.2	924.4	920.4	909.0	889.6	860.2	822.5	784.9
27.5°	821.1	827.4	838.7	852.9	866.7	877.1	880.1	876.1	857.9	826.9	787.6
30°	749.0	756.7	765.2	779.4	807.1	822.9	840.3	853.5	846.1	821.3	784.8
32.5°	669.9	671.8	684.3	700.5	725.9	756.3	783.9	810.7	819.5	806.5	776.0
35°	544.7	547.9	561.5	577.5	608.5	645.8	687.3	724.3	754.9	767.1	751.5
37.5°	444.5	453.5	463.1	480.3	507.7	541.2	584.3	632.3	677.8	708.3	713.5
40°	397.1	402.7	409.5	422.7	445.9	478.9	515.9	570.8	619.3	663.0	677.2
42.5°	359.6	362.9	367.1	379.0	396.6	429.5	463.4	511.6	560.2	612.5	636.4
45°	305.6	309.0	316.1	323.0	336.4	359.1	390.6	430.3	479.2	529.5	573.7
47.5°	266.6	268.7	273.0	280.4	291.8	306.8	332.3	365.5	410.8	459.8	506.8
50°	244.5	246.3	249.6	256.3	265.0	278.4	299.4	330.4	365.8	415.1	461.3
52.5°	227.0	227.7	230.2	234.7	241.7	252.9	270.1	295.8	328.8	372.7	418.7
55°	199.9	200.8	203.0	206.3	212.4	219.5	232.6	251.8	280.6	318.8	358.7
57.5°	177.6	178.2	180.0	181.3	186.3	192.1	202.3	215.9	237.7	270.1	305.8
60°	163.2	162.9	165.0	166.2	169.6	174.5	182.3	195.4	214.3	240.4	273.2
62.5°	149.4	148.7	150.6	152.1	154.0	158.2	164.6	174.8	190.3	213.9	242.2
65°	128.5	127.6	128.8	130.5	132.2	134.5	139.2	148.4	160.6	177.6	199.2
67.5°	107.5	108.5	108.7	109.5	110.6	113.6	116.8	123.3	132.0	145.5	163.8
70°	95.0	95.3	96.1	96.1	96.8	99.5	102.2	105.9	114.4	127.0	141.9
72.5°	82.6	83.5	83.1	83.8	84.4	86.1	88.0	91.7	98.9	108.2	120.8
75°	64.3	64.9	64.9	65.1	65.8	66.4	68.1	70.7	75.9	82.8	91.4
77.5°	46.8	46.9	47.2	48.1	48.1	49.1	50.2	52.4	55.0	59.7	65.0
80°	36.1	36.6	36.4	36.9	36.9	37.7	38.2	40.8	41.9	45.1	49.3
82.5°	26.5	27.0	26.9	27.5	27.9	28.1	28.7	29.8	30.9	33.6	35.3
85°	13.4	13.9	13.4	13.9	14.5	14.7	15.4	15.6	16.5	17.2	18.8
87.5°	9.6	10.1	10.0	10.1	10.4	10.4	10.3	9.9	10.4	10.3	10.7
90°	28.7	28.2	27.8	27.3	27.0	26.1	24.8	23.6	22.2	21.0	19.3
92.5°	42.4	42.1	41.8	41.7	41.4	40.9	40.1	39.3	38.5	37.8	36.7
95°	75.4	75.4	75.4	75.4	75.4	75.1	74.5	73.8	73.2	72.6	71.1
97.5°	118.2	118.2	118.2	118.2	118.2	117.8	117.1	116.3	115.6	114.8	113.0
100°	148.0	148.0	148.0	148.0	148.0	147.8	147.3	146.9	146.5	146.1	144.2
102.5°	181.6	181.4	181.3	181.1	181.0	180.6	179.9	179.4	178.8	178.1	176.4
105°	233.0	232.3	231.7	231.1	230.5	229.8	229.1	228.6	227.9	227.2	226.4
107.5°	283.0	283.0	283.1	283.1	283.1	283.0	282.3	281.7	281.2	280.5	280.4
110°	319.0	318.3	317.6	317.0	316.4	316.2	316.7	317.1	317.5	317.9	318.2



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	355.6	355.4	355.3	355.2	355.1	355.1	355.2	355.2	355.3	355.4	355.8
115°	412.5	412.7	412.9	413.1	413.3	413.6	413.8	414.0	414.2	414.4	414.8
117.5°	466.7	467.1	467.6	468.0	468.4	469.0	469.7	470.4	471.2	471.8	472.2
120°	507.9	507.6	507.1	506.7	506.2	506.6	507.7	508.7	509.8	510.9	511.5
122.5°	542.3	543.1	543.8	544.6	545.4	546.1	546.9	547.6	548.3	549.0	549.3
125°	601.5	602.0	602.4	602.9	603.2	603.7	604.1	604.5	604.9	605.4	605.6
127.5°	656.4	656.7	657.0	657.3	657.7	658.1	658.6	658.9	659.4	659.8	660.2
130°	692.3	693.1	694.0	694.8	695.7	696.3	696.7	697.1	697.6	698.0	698.0
132.5°	730.5	730.8	731.1	731.5	731.8	732.2	732.6	733.0	733.5	733.9	734.1
135°	783.0	783.6	784.2	784.9	785.5	786.1	786.5	786.9	787.3	787.8	787.8
137.5°	838.1	838.0	837.9	837.7	837.6	837.8	838.4	839.0	839.5	840.1	839.7
140°	871.8	871.9	872.2	872.4	872.6	872.8	873.1	873.3	873.5	873.6	873.6
142.5°	905.4	905.4	905.5	905.5	905.5	905.6	905.6	905.7	905.7	905.8	906.0
145°	951.0	951.7	952.3	952.9	953.6	953.9	954.2	954.4	954.6	954.8	954.6
147.5°	997.2	997.4	997.7	997.9	998.1	998.2	998.4	998.6	998.8	998.9	999.1
150°	1025.5	1025.7	1026.0	1026.1	1026.3	1026.4	1026.4	1026.4	1026.4	1026.4	1026.4
152.5°	1051.5	1052.0	1052.5	1053.1	1053.7	1053.7	1053.2	1052.6	1052.2	1051.7	1051.5
155°	1087.6	1088.4	1089.3	1090.1	1091.0	1091.0	1090.1	1089.3	1088.4	1087.6	1087.8
157.5°	1119.8	1120.6	1121.2	1122.0	1122.8	1122.8	1122.1	1121.5	1120.9	1120.2	1120.2
160°	1138.1	1139.3	1140.3	1141.3	1142.4	1142.6	1142.0	1141.3	1140.7	1140.1	1140.3
162.5°	1157.3	1158.3	1159.4	1160.5	1161.5	1161.5	1160.3	1159.1	1158.0	1156.9	1157.1
165°	1182.0	1182.9	1183.7	1184.6	1185.4	1185.2	1184.0	1182.7	1181.5	1180.2	1180.6
167.5°	1199.9	1201.2	1202.5	1203.8	1205.1	1205.1	1203.8	1202.6	1201.3	1200.0	1200.0
170°	1209.8	1211.3	1212.8	1214.3	1215.7	1215.8	1214.6	1213.2	1212.0	1210.7	1210.5
172.5°	1218.1	1219.7	1221.2	1222.7	1224.1	1224.2	1222.7	1221.3	1219.8	1218.3	1218.3
175°	1227.0	1228.4	1229.9	1231.4	1232.9	1232.9	1231.4	1229.9	1228.4	1227.0	1227.2
177.5°	1231.5	1232.9	1234.3	1235.6	1237.0	1237.1	1235.9	1234.7	1233.5	1232.3	1232.3
180°	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5
2.5°	555.8	553.3	551.5	550.1	546.2	543.8	542.1	539.6	536.7	533.7	529.9
5°	587.3	579.8	574.2	565.7	557.7	551.0	544.0	537.8	530.3	522.0	515.9
7.5°	620.5	609.2	594.7	582.2	568.1	555.8	544.9	533.7	522.0	510.6	500.2
10°	641.6	627.1	611.0	592.0	574.2	558.4	543.7	529.3	515.5	501.7	489.8
12.5°	664.2	646.1	622.4	600.2	580.2	559.0	541.3	523.8	507.1	492.6	478.8
15°	694.7	668.5	641.1	611.4	585.1	560.3	536.0	514.0	495.2	476.0	462.6
17.5°	713.3	681.0	649.7	618.7	586.8	555.5	529.3	503.9	480.4	461.4	444.5
20°	725.7	693.5	654.5	623.5	585.6	553.5	523.1	494.7	470.2	450.0	432.5
22.5°	736.3	699.3	660.2	619.3	581.6	547.5	514.3	485.9	460.8	439.4	422.7
25°	742.2	699.6	657.1	616.5	573.7	533.4	503.2	469.8	443.0	420.5	402.7
27.5°	742.8	697.2	649.2	604.2	560.0	522.4	484.4	454.4	426.7	402.8	385.7
30°	740.8	693.3	641.8	593.0	548.6	507.7	474.7	442.1	413.8	390.1	372.3
32.5°	734.5	685.1	632.2	580.4	534.4	494.5	460.4	429.4	401.8	378.5	359.8
35°	716.5	667.6	611.2	557.4	510.4	470.0	439.2	407.7	380.1	358.1	340.0
37.5°	688.2	644.1	586.7	531.1	484.8	444.3	413.8	385.4	360.4	338.0	319.5
40°	663.6	624.8	567.2	513.0	463.1	424.5	396.0	369.9	345.1	323.9	306.2
42.5°	635.3	601.4	548.4	491.0	442.7	404.0	376.2	352.7	329.4	309.8	292.2
45°	584.7	562.3	512.4	459.3	409.1	372.5	346.0	325.5	305.9	286.6	271.9
47.5°	526.5	515.4	473.3	422.9	375.3	339.2	316.2	297.3	280.0	263.8	250.8
50°	487.4	482.0	445.7	397.1	351.6	317.6	294.5	278.1	263.4	249.2	236.9
52.5°	448.8	448.7	415.8	371.4	329.2	296.6	273.5	258.4	245.6	234.0	223.0
55°	389.9	396.2	370.5	330.8	293.1	263.6	242.9	229.3	220.4	210.8	202.6
57.5°	335.8	346.2	325.0	290.0	258.5	231.5	213.4	203.2	193.7	187.8	181.8
60°	300.5	310.3	293.8	264.4	234.7	211.5	194.3	185.1	176.9	172.9	168.6
62.5°	269.1	277.8	265.6	238.3	212.5	190.2	175.7	166.9	161.4	157.0	154.2
65°	224.2	231.6	221.0	201.2	179.1	161.3	149.5	142.5	137.2	135.4	132.2
67.5°	181.3	187.9	182.3	165.4	147.7	134.1	124.9	118.3	115.1	113.6	111.3
70°	155.7	162.4	156.4	141.7	128.0	116.7	107.9	104.2	100.9	100.2	97.1
72.5°	134.1	138.6	132.6	121.1	109.5	99.9	93.1	89.2	87.5	86.2	84.5
75°	100.6	104.6	100.6	91.7	83.4	76.7	71.0	69.4	67.4	66.7	65.6
77.5°	71.2	74.6	71.6	66.1	59.9	54.7	51.6	49.6	49.1	48.0	48.5
80°	54.4	56.6	53.7	50.0	45.1	41.5	39.3	38.2	36.9	36.4	37.2
82.5°	39.1	40.1	38.5	36.0	32.4	30.1	28.6	27.2	27.0	27.1	27.1
85°	20.3	20.1	19.9	17.6	16.5	15.0	14.0	13.9	13.6	14.0	14.5
87.5°	10.3	10.2	9.6	8.5	7.5	6.5	5.8	5.2	5.8	6.5	7.2
90°	17.6	15.9	14.2	12.2	9.9	7.5	5.2	2.8	5.2	7.5	9.9
92.5°	35.4	34.2	33.1	31.1	28.5	25.8	23.1	20.5	23.1	25.8	28.5
95°	69.6	68.1	66.6	64.9	63.1	61.1	59.2	57.3	59.2	61.1	63.1
97.5°	111.3	109.5	107.8	106.2	104.6	103.1	101.6	100.1	101.6	103.1	104.6
100°	142.2	140.3	138.5	137.0	136.2	135.3	134.5	133.7	134.5	135.3	136.2
102.5°	174.7	173.0	171.2	170.1	169.8	169.5	169.2	168.8	169.2	169.5	169.8
105°	225.6	224.7	223.9	223.3	223.1	222.9	222.7	222.4	222.7	222.9	223.1
107.5°	280.3	280.1	280.0	279.8	279.6	279.3	279.1	278.8	279.1	279.3	279.6
110°	318.4	318.6	318.8	318.7	318.3	317.8	317.4	317.0	317.4	317.8	318.3



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	356.2	356.6	356.9	357.0	356.9	356.9	356.8	356.8	356.8	356.9	356.9
115°	415.3	415.7	416.1	416.3	416.3	416.3	416.3	416.3	416.3	416.3	416.3
117.5°	472.5	472.8	473.1	473.2	473.0	472.8	472.6	472.5	472.6	472.8	473.0
120°	512.1	512.7	513.4	513.3	512.5	511.6	510.8	509.9	510.8	511.6	512.5
122.5°	549.6	549.9	550.3	550.2	549.9	549.5	549.2	548.8	549.2	549.5	549.9
125°	605.8	606.0	606.2	606.3	606.3	606.3	606.3	606.3	606.3	606.3	606.3
127.5°	660.4	660.8	661.2	661.0	660.3	659.7	659.1	658.5	659.1	659.7	660.3
130°	698.0	698.0	698.0	697.7	697.0	696.4	695.8	695.1	695.8	696.4	697.0
132.5°	734.2	734.4	734.5	734.4	734.0	733.5	733.0	732.5	733.0	733.5	734.0
135°	787.8	787.8	787.8	787.1	785.8	784.6	783.3	782.0	783.3	784.6	785.8
137.5°	839.4	839.1	838.7	838.2	837.6	837.1	836.4	835.8	836.4	837.1	837.6
140°	873.6	873.6	873.6	873.5	873.1	872.6	872.2	871.8	872.2	872.6	873.1
142.5°	906.1	906.3	906.4	906.3	905.9	905.5	905.0	904.7	905.0	905.5	905.9
145°	954.4	954.2	953.9	953.5	952.6	951.8	950.9	950.1	950.9	951.8	952.6
147.5°	999.3	999.5	999.7	999.2	998.2	997.2	996.2	995.1	996.2	997.2	998.2
150°	1026.4	1026.4	1026.4	1026.1	1025.2	1024.4	1023.5	1022.7	1023.5	1024.4	1025.2
152.5°	1051.3	1051.1	1050.9	1050.7	1050.1	1049.6	1049.1	1048.6	1049.1	1049.6	1050.1
155°	1088.0	1088.2	1088.4	1088.5	1088.5	1088.5	1088.5	1088.5	1088.5	1088.5	1088.5
157.5°	1120.3	1120.3	1120.4	1120.6	1121.0	1121.3	1121.7	1122.1	1121.7	1121.3	1121.0
160°	1140.5	1140.7	1140.9	1141.1	1141.3	1141.5	1141.8	1142.0	1141.8	1141.5	1141.3
162.5°	1157.3	1157.5	1157.7	1158.1	1158.7	1159.2	1159.8	1160.3	1159.8	1159.2	1158.7
165°	1181.0	1181.5	1181.9	1182.4	1183.1	1183.6	1184.3	1185.0	1184.3	1183.6	1183.1
167.5°	1200.0	1200.0	1199.9	1200.3	1201.2	1202.1	1203.0	1203.8	1203.0	1202.1	1201.2
170°	1210.3	1210.1	1209.8	1210.3	1211.4	1212.4	1213.5	1214.6	1213.5	1212.4	1211.4
172.5°	1218.3	1218.2	1218.2	1218.6	1219.6	1220.4	1221.3	1222.2	1221.3	1220.4	1219.6
175°	1227.4	1227.6	1227.9	1228.4	1229.5	1230.6	1231.6	1232.7	1231.6	1230.6	1229.5
177.5°	1232.3	1232.3	1232.3	1232.8	1233.6	1234.4	1235.3	1236.1	1235.3	1234.4	1233.6
180°	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5
2.5°	528.1	526.5	524.2	521.0	518.3	515.5	514.7	513.7	515.9	514.1	513.5
5°	510.9	506.1	500.1	493.2	489.2	483.4	482.3	480.0	477.8	477.6	475.3
7.5°	492.5	485.6	477.7	470.7	464.2	457.8	453.6	452.8	449.5	447.5	445.4
10°	480.7	472.2	463.1	456.4	448.8	442.1	437.4	434.8	432.5	430.1	427.8
12.5°	466.8	457.8	450.3	443.0	434.0	429.0	421.2	416.6	416.1	416.1	410.4
15°	450.6	441.7	430.1	419.8	414.9	405.1	400.9	395.5	392.2	388.8	386.2
17.5°	432.1	420.9	411.9	400.1	390.8	383.0	377.4	374.2	369.1	364.4	361.0
20°	420.5	408.7	399.1	386.5	376.4	366.7	362.0	357.6	353.8	349.8	346.0
22.5°	408.7	396.3	384.7	372.5	363.0	352.8	348.3	342.2	338.7	336.4	332.6
25°	390.1	376.7	363.4	351.8	342.0	333.0	327.1	322.3	318.3	316.5	314.1
27.5°	369.9	356.7	343.7	330.5	319.4	312.9	308.1	304.6	302.3	299.9	298.8
30°	357.1	343.3	329.5	317.2	307.0	300.5	296.1	293.6	291.8	290.7	289.5
32.5°	344.1	330.5	315.9	304.7	295.5	289.7	286.3	283.9	283.0	282.7	282.2
35°	323.2	309.4	296.1	286.0	277.3	275.0	272.1	270.8	270.3	271.9	272.6
37.5°	303.0	290.2	277.9	268.2	262.4	259.2	258.2	258.3	259.9	261.2	262.8
40°	290.0	277.5	265.9	257.4	252.0	250.1	249.6	250.7	252.5	254.1	255.9
42.5°	277.3	265.0	254.5	246.6	242.8	240.9	241.2	242.3	244.9	246.8	249.4
45°	257.7	247.4	237.1	230.6	227.5	228.0	228.0	230.0	232.4	235.4	238.3
47.5°	239.1	228.8	220.4	214.9	213.3	212.9	214.1	216.8	220.3	223.9	227.9
50°	226.7	216.8	209.4	204.5	202.7	203.4	205.2	207.6	211.9	216.4	220.6
52.5°	214.0	205.0	198.2	193.7	192.4	193.6	195.4	199.3	203.0	207.8	212.9
55°	194.3	186.7	181.3	178.0	177.6	178.2	180.2	184.5	189.8	195.9	200.8
57.5°	174.7	168.3	163.4	161.2	161.4	162.0	165.3	170.3	176.1	182.5	188.8
60°	161.5	155.7	151.7	149.9	150.1	151.5	155.5	160.1	167.3	173.5	180.2
62.5°	149.0	143.9	140.1	138.5	138.2	141.1	145.0	149.8	156.9	163.9	171.2
65°	128.9	124.9	121.8	120.9	121.6	123.9	128.8	135.2	141.2	148.5	156.2
67.5°	109.3	106.0	103.9	104.2	105.1	108.4	112.4	118.0	124.9	132.5	140.0
70°	96.8	93.7	91.9	92.1	93.5	97.5	101.0	106.6	114.0	121.8	128.0
72.5°	84.0	81.9	80.3	81.2	82.6	85.3	89.8	95.4	101.9	109.1	115.7
75°	64.5	64.5	63.6	64.3	66.3	68.9	72.3	78.0	84.5	90.4	95.7
77.5°	47.8	47.3	47.9	48.7	49.9	53.1	56.9	61.1	65.9	71.7	76.2
80°	36.6	36.9	37.9	39.3	39.7	42.1	46.2	50.0	53.7	58.6	62.9
82.5°	27.5	27.7	28.3	30.0	30.4	33.1	35.6	39.4	42.9	46.2	49.7
85°	15.0	15.0	16.0	16.8	17.8	19.6	21.2	23.5	26.6	28.7	32.1
87.5°	8.1	8.6	9.6	10.3	11.2	12.4	13.0	15.3	16.2	17.3	19.1
90°	12.2	14.2	15.9	17.6	19.3	21.0	22.2	23.6	24.8	26.1	27.0
92.5°	31.1	33.1	34.2	35.4	36.7	37.8	38.5	39.3	40.1	40.9	41.4
95°	64.9	66.6	68.1	69.6	71.1	72.6	73.2	73.8	74.5	75.1	75.4
97.5°	106.2	107.8	109.5	111.3	113.0	114.8	115.6	116.3	117.1	117.8	118.2
100°	137.0	138.5	140.3	142.2	144.2	146.1	146.5	146.9	147.3	147.8	148.0
102.5°	170.1	171.2	173.0	174.7	176.4	178.1	178.8	179.4	179.9	180.6	181.0
105°	223.3	223.9	224.7	225.6	226.4	227.2	227.9	228.6	229.1	229.8	230.5
107.5°	279.8	280.0	280.1	280.3	280.4	280.5	281.2	281.7	282.3	283.0	283.1
110°	318.7	318.8	318.6	318.4	318.2	317.9	317.5	317.1	316.7	316.2	316.4



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	357.0	356.9	356.6	356.2	355.8	355.4	355.3	355.2	355.2	355.1	355.1
115°	416.3	416.1	415.7	415.3	414.8	414.4	414.2	414.0	413.8	413.6	413.3
117.5°	473.2	473.1	472.8	472.5	472.2	471.8	471.2	470.4	469.7	469.0	468.4
120°	513.3	513.4	512.7	512.1	511.5	510.9	509.8	508.7	507.7	506.6	506.2
122.5°	550.2	550.3	549.9	549.6	549.3	549.0	548.3	547.6	546.9	546.1	545.4
125°	606.3	606.2	606.0	605.8	605.6	605.4	604.9	604.5	604.1	603.7	603.2
127.5°	661.0	661.2	660.8	660.4	660.2	659.8	659.4	658.9	658.6	658.1	657.7
130°	697.7	698.0	698.0	698.0	698.0	698.0	697.6	697.1	696.7	696.3	695.7
132.5°	734.4	734.5	734.4	734.2	734.1	733.9	733.5	733.0	732.6	732.2	731.8
135°	787.1	787.8	787.8	787.8	787.8	787.8	787.3	786.9	786.5	786.1	785.5
137.5°	838.2	838.7	839.1	839.4	839.7	840.1	839.5	839.0	838.4	837.8	837.6
140°	873.5	873.6	873.6	873.6	873.6	873.6	873.5	873.3	873.1	872.8	872.6
142.5°	906.3	906.4	906.3	906.1	906.0	905.8	905.7	905.7	905.6	905.6	905.5
145°	953.5	953.9	954.2	954.4	954.6	954.8	954.6	954.4	954.2	953.9	953.6
147.5°	999.2	999.7	999.5	999.3	999.1	998.9	998.8	998.6	998.4	998.2	998.1
150°	1026.1	1026.4	1026.4	1026.4	1026.4	1026.4	1026.4	1026.4	1026.4	1026.4	1026.3
152.5°	1050.7	1050.9	1051.1	1051.3	1051.5	1051.7	1052.2	1052.6	1053.2	1053.7	1053.7
155°	1088.5	1088.4	1088.2	1088.0	1087.8	1087.6	1088.4	1089.3	1090.1	1091.0	1091.0
157.5°	1120.6	1120.4	1120.3	1120.3	1120.2	1120.2	1120.9	1121.5	1122.1	1122.8	1122.8
160°	1141.1	1140.9	1140.7	1140.5	1140.3	1140.1	1140.7	1141.3	1142.0	1142.6	1142.4
162.5°	1158.1	1157.7	1157.5	1157.3	1157.1	1156.9	1158.0	1159.1	1160.3	1161.5	1161.5
165°	1182.4	1181.9	1181.5	1181.0	1180.6	1180.2	1181.5	1182.7	1184.0	1185.2	1185.4
167.5°	1200.3	1199.9	1200.0	1200.0	1200.0	1200.0	1201.3	1202.6	1203.8	1205.1	1205.1
170°	1210.3	1209.8	1210.1	1210.3	1210.5	1210.7	1212.0	1213.2	1214.6	1215.8	1215.7
172.5°	1218.6	1218.2	1218.2	1218.3	1218.3	1218.3	1219.8	1221.3	1222.7	1224.2	1224.1
175°	1228.4	1227.9	1227.6	1227.4	1227.2	1227.0	1228.4	1229.9	1231.4	1232.9	1232.9
177.5°	1232.8	1232.3	1232.3	1232.3	1232.3	1232.3	1233.5	1234.7	1235.9	1237.1	1237.0
180°	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5
2.5°	513.1	512.8	511.5	511.3	511.5	512.8	513.1	513.5	514.1	515.9	513.7
5°	474.0	472.9	472.2	474.7	472.2	472.9	474.0	475.3	477.6	477.8	480.0
7.5°	444.5	443.7	441.7	441.0	441.7	443.7	444.5	445.4	447.5	449.5	452.8
10°	425.7	424.7	422.9	422.4	422.9	424.7	425.7	427.8	430.1	432.5	434.8
12.5°	407.4	405.7	405.3	405.8	405.3	405.7	407.4	410.4	416.1	416.1	416.6
15°	383.2	382.3	379.8	380.6	379.8	382.3	383.2	386.2	388.8	392.2	395.5
17.5°	359.4	358.4	355.3	358.0	355.3	358.4	359.4	361.0	364.4	369.1	374.2
20°	344.4	342.6	341.1	340.8	341.1	342.6	344.4	346.0	349.8	353.8	357.6
22.5°	330.2	328.6	328.4	327.0	328.4	328.6	330.2	332.6	336.4	338.7	342.2
25°	312.3	310.8	310.3	309.2	310.3	310.8	312.3	314.1	316.5	318.3	322.3
27.5°	298.6	297.8	297.0	297.4	297.0	297.8	298.6	298.8	299.9	302.3	304.6
30°	290.2	290.0	289.5	289.5	289.5	290.0	290.2	289.5	290.7	291.8	293.6
32.5°	283.2	283.2	283.5	283.5	283.5	283.2	283.2	282.2	282.7	283.0	283.9
35°	273.5	274.2	274.6	273.9	274.6	274.2	273.5	272.6	271.9	270.3	270.8
37.5°	264.7	265.3	266.0	266.7	266.0	265.3	264.7	262.8	261.2	259.9	258.3
40°	257.9	259.4	259.9	261.0	259.9	259.4	257.9	255.9	254.1	252.5	250.7
42.5°	251.5	253.2	254.3	254.6	254.3	253.2	251.5	249.4	246.8	244.9	242.3
45°	241.6	243.4	245.0	245.0	245.0	243.4	241.6	238.3	235.4	232.4	230.0
47.5°	231.4	233.9	235.5	235.9	235.5	233.9	231.4	227.9	223.9	220.3	216.8
50°	224.4	227.5	229.1	230.2	229.1	227.5	224.4	220.6	216.4	211.9	207.6
52.5°	217.6	220.7	222.8	223.4	222.8	220.7	217.6	212.9	207.8	203.0	199.3
55°	205.9	210.4	212.8	213.7	212.8	210.4	205.9	200.8	195.9	189.8	184.5
57.5°	194.8	199.0	201.8	202.5	201.8	199.0	194.8	188.8	182.5	176.1	170.3
60°	186.2	190.8	194.3	194.9	194.3	190.8	186.2	180.2	173.5	167.3	160.1
62.5°	177.5	182.2	185.4	187.1	185.4	182.2	177.5	171.2	163.9	156.9	149.8
65°	162.4	167.1	170.2	170.9	170.2	167.1	162.4	156.2	148.5	141.2	135.2
67.5°	145.9	150.6	152.6	153.9	152.6	150.6	145.9	140.0	132.5	124.9	118.0
70°	134.3	138.1	140.3	141.4	140.3	138.1	134.3	128.0	121.8	114.0	106.6
72.5°	121.1	125.1	127.6	127.9	127.6	125.1	121.1	115.7	109.1	101.9	95.4
75°	100.9	104.4	105.8	105.8	105.8	104.4	100.9	95.7	90.4	84.5	78.0
77.5°	79.8	81.6	83.3	83.7	83.3	81.6	79.8	76.2	71.7	65.9	61.1
80°	66.3	67.4	68.7	68.7	68.7	67.4	66.3	62.9	58.6	53.7	50.0
82.5°	52.3	53.3	54.6	54.4	54.6	53.3	52.3	49.7	46.2	42.9	39.4
85°	31.7	33.6	33.5	33.0	33.5	33.6	31.7	32.1	28.7	26.6	23.5
87.5°	19.8	20.0	20.6	21.1	20.6	20.0	19.8	19.1	17.3	16.2	15.3
90°	27.3	27.8	28.2	28.7	28.2	27.8	27.3	27.0	26.1	24.8	23.6
92.5°	41.7	41.8	42.1	42.4	42.1	41.8	41.7	41.4	40.9	40.1	39.3
95°	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.4	75.1	74.5	73.8
97.5°	118.2	118.2	118.2	118.2	118.2	118.2	118.2	118.2	117.8	117.1	116.3
100°	148.0	148.0	148.0	148.0	148.0	148.0	148.0	148.0	147.8	147.3	146.9
102.5°	181.1	181.3	181.4	181.6	181.4	181.3	181.1	181.0	180.6	179.9	179.4
105°	231.1	231.7	232.3	233.0	232.3	231.7	231.1	230.5	229.8	229.1	228.6
107.5°	283.1	283.1	283.0	283.0	283.0	283.1	283.1	283.1	283.0	282.3	281.7
110°	317.0	317.6	318.3	319.0	318.3	317.6	317.0	316.4	316.2	316.7	317.1



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	355.2	355.3	355.4	355.6	355.4	355.3	355.2	355.1	355.1	355.2	355.2
115°	413.1	412.9	412.7	412.5	412.7	412.9	413.1	413.3	413.6	413.8	414.0
117.5°	468.0	467.6	467.1	466.7	467.1	467.6	468.0	468.4	469.0	469.7	470.4
120°	506.7	507.1	507.6	507.9	507.6	507.1	506.7	506.2	506.6	507.7	508.7
122.5°	544.6	543.8	543.1	542.3	543.1	543.8	544.6	545.4	546.1	546.9	547.6
125°	602.9	602.4	602.0	601.5	602.0	602.4	602.9	603.2	603.7	604.1	604.5
127.5°	657.3	657.0	656.7	656.4	656.7	657.0	657.3	657.7	658.1	658.6	658.9
130°	694.8	694.0	693.1	692.3	693.1	694.0	694.8	695.7	696.3	696.7	697.1
132.5°	731.5	731.1	730.8	730.5	730.8	731.1	731.5	731.8	732.2	732.6	733.0
135°	784.9	784.2	783.6	783.0	783.6	784.2	784.9	785.5	786.1	786.5	786.9
137.5°	837.7	837.9	838.0	838.1	838.0	837.9	837.7	837.6	837.8	838.4	839.0
140°	872.4	872.2	871.9	871.8	871.9	872.2	872.4	872.6	872.8	873.1	873.3
142.5°	905.5	905.5	905.4	905.4	905.4	905.5	905.5	905.5	905.6	905.6	905.7
145°	952.9	952.3	951.7	951.0	951.7	952.3	952.9	953.6	953.9	954.2	954.4
147.5°	997.9	997.7	997.4	997.2	997.4	997.7	997.9	998.1	998.2	998.4	998.6
150°	1026.1	1026.0	1025.7	1025.5	1025.7	1026.0	1026.1	1026.3	1026.4	1026.4	1026.4
152.5°	1053.1	1052.5	1052.0	1051.5	1052.0	1052.5	1053.1	1053.7	1053.7	1053.2	1052.6
155°	1090.1	1089.3	1088.4	1087.6	1088.4	1089.3	1090.1	1091.0	1091.0	1090.1	1089.3
157.5°	1122.0	1121.2	1120.6	1119.8	1120.6	1121.2	1122.0	1122.8	1122.8	1122.1	1121.5
160°	1141.3	1140.3	1139.3	1138.1	1139.3	1140.3	1141.3	1142.4	1142.6	1142.0	1141.3
162.5°	1160.5	1159.4	1158.3	1157.3	1158.3	1159.4	1160.5	1161.5	1161.5	1160.3	1159.1
165°	1184.6	1183.7	1182.9	1182.0	1182.9	1183.7	1184.6	1185.4	1185.2	1184.0	1182.7
167.5°	1203.8	1202.5	1201.2	1199.9	1201.2	1202.5	1203.8	1205.1	1205.1	1203.8	1202.6
170°	1214.3	1212.8	1211.3	1209.8	1211.3	1212.8	1214.3	1215.7	1215.8	1214.6	1213.2
172.5°	1222.7	1221.2	1219.7	1218.1	1219.7	1221.2	1222.7	1224.1	1224.2	1222.7	1221.3
175°	1231.4	1229.9	1228.4	1227.0	1228.4	1229.9	1231.4	1232.9	1232.9	1231.4	1229.9
177.5°	1235.6	1234.3	1232.9	1231.5	1232.9	1234.3	1235.6	1237.0	1237.1	1235.9	1234.7
180°	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5
2.5°	514.7	515.5	518.3	521.0	524.2	526.5	528.1	529.9	533.7	536.7	539.6
5°	482.3	483.4	489.2	493.2	500.1	506.1	510.9	515.9	522.0	530.3	537.8
7.5°	453.6	457.8	464.2	470.7	477.7	485.6	492.5	500.2	510.6	522.0	533.7
10°	437.4	442.1	448.8	456.4	463.1	472.2	480.7	489.8	501.7	515.5	529.3
12.5°	421.2	429.0	434.0	443.0	450.3	457.8	466.8	478.8	492.6	507.1	523.8
15°	400.9	405.1	414.9	419.8	430.1	441.7	450.6	462.6	476.0	495.2	514.0
17.5°	377.4	383.0	390.8	400.1	411.9	420.9	432.1	444.5	461.4	480.4	503.9
20°	362.0	366.7	376.4	386.5	399.1	408.7	420.5	432.5	450.0	470.2	494.7
22.5°	348.3	352.8	363.0	372.5	384.7	396.3	408.7	422.7	439.4	460.8	485.9
25°	327.1	333.0	342.0	351.8	363.4	376.7	390.1	402.7	420.5	443.0	469.8
27.5°	308.1	312.9	319.4	330.5	343.7	356.7	369.9	385.7	402.8	426.7	454.4
30°	296.1	300.5	307.0	317.2	329.5	343.3	357.1	372.3	390.1	413.8	442.1
32.5°	286.3	289.7	295.5	304.7	315.9	330.5	344.1	359.8	378.5	401.8	429.4
35°	272.1	275.0	277.3	286.0	296.1	309.4	323.2	340.0	358.1	380.1	407.7
37.5°	258.2	259.2	262.4	268.2	277.9	290.2	303.0	319.5	338.0	360.4	385.4
40°	249.6	250.1	252.0	257.4	265.9	277.5	290.0	306.2	323.9	345.1	369.9
42.5°	241.2	240.9	242.8	246.6	254.5	265.0	277.3	292.2	309.8	329.4	352.7
45°	228.0	228.0	227.5	230.6	237.1	247.4	257.7	271.9	286.6	305.9	325.5
47.5°	214.1	212.9	213.3	214.9	220.4	228.8	239.1	250.8	263.8	280.0	297.3
50°	205.2	203.4	202.7	204.5	209.4	216.8	226.7	236.9	249.2	263.4	278.1
52.5°	195.4	193.6	192.4	193.7	198.2	205.0	214.0	223.0	234.0	245.6	258.4
55°	180.2	178.2	177.6	178.0	181.3	186.7	194.3	202.6	210.8	220.4	229.3
57.5°	165.3	162.0	161.4	161.2	163.4	168.3	174.7	181.8	187.8	193.7	203.2
60°	155.5	151.5	150.1	149.9	151.7	155.7	161.5	168.6	172.9	176.9	185.1
62.5°	145.0	141.1	138.2	138.5	140.1	143.9	149.0	154.2	157.0	161.4	166.9
65°	128.8	123.9	121.6	120.9	121.8	124.9	128.9	132.2	135.4	137.2	142.5
67.5°	112.4	108.4	105.1	104.2	103.9	106.0	109.3	111.3	113.6	115.1	118.3
70°	101.0	97.5	93.5	92.1	91.9	93.7	96.8	97.1	100.2	100.9	104.2
72.5°	89.8	85.3	82.6	81.2	80.3	81.9	84.0	84.5	86.2	87.5	89.2
75°	72.3	68.9	66.3	64.3	63.6	64.5	64.5	65.6	66.7	67.4	69.4
77.5°	56.9	53.1	49.9	48.7	47.9	47.3	47.8	48.5	48.0	49.1	49.6
80°	46.2	42.1	39.7	39.3	37.9	36.9	36.6	37.2	36.4	36.9	38.2
82.5°	35.6	33.1	30.4	30.0	28.3	27.7	27.5	27.1	27.1	27.0	27.2
85°	21.2	19.6	17.8	16.8	16.0	15.0	15.0	14.5	14.0	13.6	13.9
87.5°	13.0	12.4	11.2	10.3	9.6	8.6	8.1	7.2	6.5	5.8	5.2
90°	22.2	21.0	19.3	17.6	15.9	14.2	12.2	9.9	7.5	5.2	2.8
92.5°	38.5	37.8	36.7	35.4	34.2	33.1	31.1	28.5	25.8	23.1	20.5
95°	73.2	72.6	71.1	69.6	68.1	66.6	64.9	63.1	61.1	59.2	57.3
97.5°	115.6	114.8	113.0	111.3	109.5	107.8	106.2	104.6	103.1	101.6	100.1
100°	146.5	146.1	144.2	142.2	140.3	138.5	137.0	136.2	135.3	134.5	133.7
102.5°	178.8	178.1	176.4	174.7	173.0	171.2	170.1	169.8	169.5	169.2	168.8
105°	227.9	227.2	226.4	225.6	224.7	223.9	223.3	223.1	222.9	222.7	222.4
107.5°	281.2	280.5	280.4	280.3	280.1	280.0	279.8	279.6	279.3	279.1	278.8
110°	317.5	317.9	318.2	318.4	318.6	318.8	318.7	318.3	317.8	317.4	317.0



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	355.3	355.4	355.8	356.2	356.6	356.9	357.0	356.9	356.9	356.8	356.8
115°	414.2	414.4	414.8	415.3	415.7	416.1	416.3	416.3	416.3	416.3	416.3
117.5°	471.2	471.8	472.2	472.5	472.8	473.1	473.2	473.0	472.8	472.6	472.5
120°	509.8	510.9	511.5	512.1	512.7	513.4	513.3	512.5	511.6	510.8	509.9
122.5°	548.3	549.0	549.3	549.6	549.9	550.3	550.2	549.9	549.5	549.2	548.8
125°	604.9	605.4	605.6	605.8	606.0	606.2	606.3	606.3	606.3	606.3	606.3
127.5°	659.4	659.8	660.2	660.4	660.8	661.2	661.0	660.3	659.7	659.1	658.5
130°	697.6	698.0	698.0	698.0	698.0	698.0	697.7	697.0	696.4	695.8	695.1
132.5°	733.5	733.9	734.1	734.2	734.4	734.5	734.4	734.0	733.5	733.0	732.5
135°	787.3	787.8	787.8	787.8	787.8	787.8	787.1	785.8	784.6	783.3	782.0
137.5°	839.5	840.1	839.7	839.4	839.1	838.7	838.2	837.6	837.1	836.4	835.8
140°	873.5	873.6	873.6	873.6	873.6	873.6	873.5	873.1	872.6	872.2	871.8
142.5°	905.7	905.8	906.0	906.1	906.3	906.4	906.3	905.9	905.5	905.0	904.7
145°	954.6	954.8	954.6	954.4	954.2	953.9	953.5	952.6	951.8	950.9	950.1
147.5°	998.8	998.9	999.1	999.3	999.5	999.7	999.2	998.2	997.2	996.2	995.1
150°	1026.4	1026.4	1026.4	1026.4	1026.4	1026.4	1026.1	1025.2	1024.4	1023.5	1022.7
152.5°	1052.2	1051.7	1051.5	1051.3	1051.1	1050.9	1050.7	1050.1	1049.6	1049.1	1048.6
155°	1088.4	1087.6	1087.8	1088.0	1088.2	1088.4	1088.5	1088.5	1088.5	1088.5	1088.5
157.5°	1120.9	1120.2	1120.2	1120.3	1120.3	1120.4	1120.6	1121.0	1121.3	1121.7	1122.1
160°	1140.7	1140.1	1140.3	1140.5	1140.7	1140.9	1141.1	1141.3	1141.5	1141.8	1142.0
162.5°	1158.0	1156.9	1157.1	1157.3	1157.5	1157.7	1158.1	1158.7	1159.2	1159.8	1160.3
165°	1181.5	1180.2	1180.6	1181.0	1181.5	1181.9	1182.4	1183.1	1183.6	1184.3	1185.0
167.5°	1201.3	1200.0	1200.0	1200.0	1200.0	1199.9	1200.3	1201.2	1202.1	1203.0	1203.8
170°	1212.0	1210.7	1210.5	1210.3	1210.1	1209.8	1210.3	1211.4	1212.4	1213.5	1214.6
172.5°	1219.8	1218.3	1218.3	1218.3	1218.2	1218.2	1218.6	1219.6	1220.4	1221.3	1222.2
175°	1228.4	1227.0	1227.2	1227.4	1227.6	1227.9	1228.4	1229.5	1230.6	1231.6	1232.7
177.5°	1233.5	1232.3	1232.3	1232.3	1232.3	1232.3	1232.8	1233.6	1234.4	1235.3	1236.1
180°	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5	538.5
2.5°	542.1	543.8	546.2	550.1	551.5	553.3	555.8	555.6	556.3	559.0	564.7
5°	544.0	551.0	557.7	565.7	574.2	579.8	587.3	592.0	596.7	602.8	613.0
7.5°	544.9	555.8	568.1	582.2	594.7	609.2	620.5	631.1	640.7	653.4	665.6
10°	543.7	558.4	574.2	592.0	611.0	627.1	641.6	658.1	672.1	687.5	701.3
12.5°	541.3	559.0	580.2	600.2	622.4	646.1	664.2	680.9	699.6	717.3	738.7
15°	536.0	560.3	585.1	611.4	641.1	668.5	694.7	716.2	736.3	762.9	790.8
17.5°	529.3	555.5	586.8	618.7	649.7	681.0	713.3	745.8	771.2	804.2	826.0
20°	523.1	553.5	585.6	623.5	654.5	693.5	725.7	757.1	791.9	824.7	850.8
22.5°	514.3	547.5	581.6	619.3	660.2	699.3	736.3	770.4	805.3	840.9	872.5
25°	503.2	533.4	573.7	616.5	657.1	699.6	742.2	784.9	822.5	860.2	889.6
27.5°	484.4	522.4	560.0	604.2	649.2	697.2	742.8	787.6	826.9	857.9	876.1
30°	474.7	507.7	548.6	593.0	641.8	693.3	740.8	784.8	821.3	846.1	853.5
32.5°	460.4	494.5	534.4	580.4	632.2	685.1	734.5	776.0	806.5	819.5	810.7
35°	439.2	470.0	510.4	557.4	611.2	667.6	716.5	751.5	767.1	754.9	724.3
37.5°	413.8	444.3	484.8	531.1	586.7	644.1	688.2	713.5	708.3	677.8	632.3
40°	396.0	424.5	463.1	513.0	567.2	624.8	663.6	677.2	663.0	619.3	570.8
42.5°	376.2	404.0	442.7	491.0	548.4	601.4	635.3	636.4	612.5	560.2	511.6
45°	346.0	372.5	409.1	459.3	512.4	562.3	584.7	573.7	529.5	479.2	430.3
47.5°	316.2	339.2	375.3	422.9	473.3	515.4	526.5	506.8	459.8	410.8	365.5
50°	294.5	317.6	351.6	397.1	445.7	482.0	487.4	461.3	415.1	365.8	330.4
52.5°	273.5	296.6	329.2	371.4	415.8	448.7	448.8	418.7	372.7	328.8	295.8
55°	242.9	263.6	293.1	330.8	370.5	396.2	389.9	358.7	318.8	280.6	251.8
57.5°	213.4	231.5	258.5	290.0	325.0	346.2	335.8	305.8	270.1	237.7	215.9
60°	194.3	211.5	234.7	264.4	293.8	310.3	300.5	273.2	240.4	214.3	195.4
62.5°	175.7	190.2	212.5	238.3	265.6	277.8	269.1	242.2	213.9	190.3	174.8
65°	149.5	161.3	179.1	201.2	221.0	231.6	224.2	199.2	177.6	160.6	148.4
67.5°	124.9	134.1	147.7	165.4	182.3	187.9	181.3	163.8	145.5	132.0	123.3
70°	107.9	116.7	128.0	141.7	156.4	162.4	155.7	141.9	127.0	114.4	105.9
72.5°	93.1	99.9	109.5	121.1	132.6	138.6	134.1	120.8	108.2	98.9	91.7
75°	71.0	76.7	83.4	91.7	100.6	104.6	100.6	91.4	82.8	75.9	70.7
77.5°	51.6	54.7	59.9	66.1	71.6	74.6	71.2	65.0	59.7	55.0	52.4
80°	39.3	41.5	45.1	50.0	53.7	56.6	54.4	49.3	45.1	41.9	40.8
82.5°	28.6	30.1	32.4	36.0	38.5	40.1	39.1	35.3	33.6	30.9	29.8
85°	14.0	15.0	16.5	17.6	19.9	20.1	20.3	18.8	17.2	16.5	15.6
87.5°	5.8	6.5	7.5	8.5	9.6	10.2	10.3	10.7	10.3	10.4	9.9
90°	5.2	7.5	9.9	12.2	14.2	15.9	17.6	19.3	21.0	22.2	23.6
92.5°	23.1	25.8	28.5	31.1	33.1	34.2	35.4	36.7	37.8	38.5	39.3
95°	59.2	61.1	63.1	64.9	66.6	68.1	69.6	71.1	72.6	73.2	73.8
97.5°	101.6	103.1	104.6	106.2	107.8	109.5	111.3	113.0	114.8	115.6	116.3
100°	134.5	135.3	136.2	137.0	138.5	140.3	142.2	144.2	146.1	146.5	146.9
102.5°	169.2	169.5	169.8	170.1	171.2	173.0	174.7	176.4	178.1	178.8	179.4
105°	222.7	222.9	223.1	223.3	223.9	224.7	225.6	226.4	227.2	227.9	228.6
107.5°	279.1	279.3	279.6	279.8	280.0	280.1	280.3	280.4	280.5	281.2	281.7
110°	317.4	317.8	318.3	318.7	318.8	318.6	318.4	318.2	317.9	317.5	317.1



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	356.8	356.9	356.9	357.0	356.9	356.6	356.2	355.8	355.4	355.3	355.2
115°	416.3	416.3	416.3	416.3	416.1	415.7	415.3	414.8	414.4	414.2	414.0
117.5°	472.6	472.8	473.0	473.2	473.1	472.8	472.5	472.2	471.8	471.2	470.4
120°	510.8	511.6	512.5	513.3	513.4	512.7	512.1	511.5	510.9	509.8	508.7
122.5°	549.2	549.5	549.9	550.2	550.3	549.9	549.6	549.3	549.0	548.3	547.6
125°	606.3	606.3	606.3	606.3	606.2	606.0	605.8	605.6	605.4	604.9	604.5
127.5°	659.1	659.7	660.3	661.0	661.2	660.8	660.4	660.2	659.8	659.4	658.9
130°	695.8	696.4	697.0	697.7	698.0	698.0	698.0	698.0	698.0	697.6	697.1
132.5°	733.0	733.5	734.0	734.4	734.5	734.4	734.2	734.1	733.9	733.5	733.0
135°	783.3	784.6	785.8	787.1	787.8	787.8	787.8	787.8	787.8	787.3	786.9
137.5°	836.4	837.1	837.6	838.2	838.7	839.1	839.4	839.7	840.1	839.5	839.0
140°	872.2	872.6	873.1	873.5	873.6	873.6	873.6	873.6	873.6	873.5	873.3
142.5°	905.0	905.5	905.9	906.3	906.4	906.3	906.1	906.0	905.8	905.7	905.7
145°	950.9	951.8	952.6	953.5	953.9	954.2	954.4	954.6	954.8	954.6	954.4
147.5°	996.2	997.2	998.2	999.2	999.7	999.5	999.3	999.1	998.9	998.8	998.6
150°	1023.5	1024.4	1025.2	1026.1	1026.4	1026.4	1026.4	1026.4	1026.4	1026.4	1026.4
152.5°	1049.1	1049.6	1050.1	1050.7	1050.9	1051.1	1051.3	1051.5	1051.7	1052.2	1052.6
155°	1088.5	1088.5	1088.5	1088.5	1088.4	1088.2	1088.0	1087.8	1087.6	1088.4	1089.3
157.5°	1121.7	1121.3	1121.0	1120.6	1120.4	1120.3	1120.3	1120.2	1120.2	1120.9	1121.5
160°	1141.8	1141.5	1141.3	1141.1	1140.9	1140.7	1140.5	1140.3	1140.1	1140.7	1141.3
162.5°	1159.8	1159.2	1158.7	1158.1	1157.7	1157.5	1157.3	1157.1	1156.9	1158.0	1159.1
165°	1184.3	1183.6	1183.1	1182.4	1181.9	1181.5	1181.0	1180.6	1180.2	1181.5	1182.7
167.5°	1203.0	1202.1	1201.2	1200.3	1199.9	1200.0	1200.0	1200.0	1200.0	1201.3	1202.6
170°	1213.5	1212.4	1211.4	1210.3	1209.8	1210.1	1210.3	1210.5	1210.7	1212.0	1213.2
172.5°	1221.3	1220.4	1219.6	1218.6	1218.2	1218.2	1218.3	1218.3	1218.3	1219.8	1221.3
175°	1231.6	1230.6	1229.5	1228.4	1227.9	1227.6	1227.4	1227.2	1227.0	1228.4	1229.9
177.5°	1235.3	1234.4	1233.6	1232.8	1232.3	1232.3	1232.3	1232.3	1232.3	1233.5	1234.7
180°	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	538.5	538.5	538.5	538.5	538.5	538.5	538.5
2.5°	567.6	568.0	569.6	570.8	571.2	573.0	573.1
5°	617.5	621.2	628.6	629.2	630.4	636.2	631.7
7.5°	675.9	685.5	691.9	697.7	699.6	702.2	701.7
10°	713.4	727.6	734.8	746.2	746.6	749.5	747.7
12.5°	751.0	767.6	780.6	782.8	792.3	793.8	796.3
15°	804.4	822.0	840.1	846.6	859.7	862.8	867.7
17.5°	854.5	872.5	885.2	901.9	907.4	914.5	909.6
20°	882.0	901.6	917.8	930.9	936.4	940.5	940.0
22.5°	898.6	918.4	931.4	941.4	946.6	948.3	948.2
25°	909.0	920.4	924.4	928.2	922.4	920.4	921.2
27.5°	880.1	877.1	866.7	852.9	838.7	827.4	821.1
30°	840.3	822.9	807.1	779.4	765.2	756.7	749.0
32.5°	783.9	756.3	725.9	700.5	684.3	671.8	669.9
35°	687.3	645.8	608.5	577.5	561.5	547.9	544.7
37.5°	584.3	541.2	507.7	480.3	463.1	453.5	444.5
40°	515.9	478.9	445.9	422.7	409.5	402.7	397.1
42.5°	463.4	429.5	396.6	379.0	367.1	362.9	359.6
45°	390.6	359.1	336.4	323.0	316.1	309.0	305.6
47.5°	332.3	306.8	291.8	280.4	273.0	268.7	266.6
50°	299.4	278.4	265.0	256.3	249.6	246.3	244.5
52.5°	270.1	252.9	241.7	234.7	230.2	227.7	227.0
55°	232.6	219.5	212.4	206.3	203.0	200.8	199.9
57.5°	202.3	192.1	186.3	181.3	180.0	178.2	177.6
60°	182.3	174.5	169.6	166.2	165.0	162.9	163.2
62.5°	164.6	158.2	154.0	152.1	150.6	148.7	149.4
65°	139.2	134.5	132.2	130.5	128.8	127.6	128.5
67.5°	116.8	113.6	110.6	109.5	108.7	108.5	107.5
70°	102.2	99.5	96.8	96.1	96.1	95.3	95.0
72.5°	88.0	86.1	84.4	83.8	83.1	83.5	82.6
75°	68.1	66.4	65.8	65.1	64.9	64.9	64.3
77.5°	50.2	49.1	48.1	48.1	47.2	46.9	46.8
80°	38.2	37.7	36.9	36.9	36.4	36.6	36.1
82.5°	28.7	28.1	27.9	27.5	26.9	27.0	26.5
85°	15.4	14.7	14.5	13.9	13.4	13.9	13.4
87.5°	10.3	10.4	10.4	10.1	10.0	10.1	9.6
90°	24.8	26.1	27.0	27.3	27.8	28.2	28.7
92.5°	40.1	40.9	41.4	41.7	41.8	42.1	42.4
95°	74.5	75.1	75.4	75.4	75.4	75.4	75.4
97.5°	117.1	117.8	118.2	118.2	118.2	118.2	118.2
100°	147.3	147.8	148.0	148.0	148.0	148.0	148.0
102.5°	179.9	180.6	181.0	181.1	181.3	181.4	181.6
105°	229.1	229.8	230.5	231.1	231.7	232.3	233.0
107.5°	282.3	283.0	283.1	283.1	283.1	283.0	283.0
110°	316.7	316.2	316.4	317.0	317.6	318.3	319.0



TEST NUMBER: P332728-830

CATALOG NUMBER: S124DIW-S350D1050U830-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	355.2	355.1	355.1	355.2	355.3	355.4	355.6
115°	413.8	413.6	413.3	413.1	412.9	412.7	412.5
117.5°	469.7	469.0	468.4	468.0	467.6	467.1	466.7
120°	507.7	506.6	506.2	506.7	507.1	507.6	507.9
122.5°	546.9	546.1	545.4	544.6	543.8	543.1	542.3
125°	604.1	603.7	603.2	602.9	602.4	602.0	601.5
127.5°	658.6	658.1	657.7	657.3	657.0	656.7	656.4
130°	696.7	696.3	695.7	694.8	694.0	693.1	692.3
132.5°	732.6	732.2	731.8	731.5	731.1	730.8	730.5
135°	786.5	786.1	785.5	784.9	784.2	783.6	783.0
137.5°	838.4	837.8	837.6	837.7	837.9	838.0	838.1
140°	873.1	872.8	872.6	872.4	872.2	871.9	871.8
142.5°	905.6	905.6	905.5	905.5	905.5	905.4	905.4
145°	954.2	953.9	953.6	952.9	952.3	951.7	951.0
147.5°	998.4	998.2	998.1	997.9	997.7	997.4	997.2
150°	1026.4	1026.4	1026.3	1026.1	1026.0	1025.7	1025.5
152.5°	1053.2	1053.7	1053.7	1053.1	1052.5	1052.0	1051.5
155°	1090.1	1091.0	1091.0	1090.1	1089.3	1088.4	1087.6
157.5°	1122.1	1122.8	1122.8	1122.0	1121.2	1120.6	1119.8
160°	1142.0	1142.6	1142.4	1141.3	1140.3	1139.3	1138.1
162.5°	1160.3	1161.5	1161.5	1160.5	1159.4	1158.3	1157.3
165°	1184.0	1185.2	1185.4	1184.6	1183.7	1182.9	1182.0
167.5°	1203.8	1205.1	1205.1	1203.8	1202.5	1201.2	1199.9
170°	1214.6	1215.8	1215.7	1214.3	1212.8	1211.3	1209.8
172.5°	1222.7	1224.2	1224.1	1222.7	1221.2	1219.7	1218.1
175°	1231.4	1232.9	1232.9	1231.4	1229.9	1228.4	1227.0
177.5°	1235.9	1237.1	1237.0	1235.6	1234.3	1232.9	1231.5
180°	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6	1234.6

(END OF REPORT)