

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P332770-940

Luminaire Tested: **S124DIW-S575D1560U940-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P332770-940
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-10,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S124DIW-S575D1560U940-4F0-1E-UDD-A1
Description: DEFINE 4 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 575 LUMENS PER FOOT, ASYMMETRIC DIFFUSER
UPLIGHT 1560 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7139.3 lumens
Efficiency: N/A
Efficacy: 117.8 lumens/watt
Spacing Criteria (0/90/45): 1.31 / 1.23 / 1.41
Luminous Opening: Rectangular (W 4' x L: 0.33' x H: 0')
CIE Type: Semi-Indirect


Input Watts (W): 60.6
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

Luminous Intensity Polar Plot





TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				20
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	103	103	103	103	93	93	93	93	74	74	74	56	56	56	40	40	40	32			32
1	94	90	86	83	84	81	78	75	65	62	60	49	48	47	35	35	34	28			28
2	86	79	73	68	77	71	66	62	57	53	50	44	41	39	31	30	29	23			23
3	78	69	62	57	70	63	57	52	50	46	42	39	36	33	28	26	25	20			20
4	72	61	54	48	64	55	49	44	45	40	36	34	31	29	25	23	21	17			17
5	66	54	47	41	59	49	43	38	40	35	31	31	28	25	23	20	19	15			15
6	60	49	41	35	54	44	38	33	36	31	27	28	24	22	21	18	16	13			13
7	56	44	36	31	50	40	33	29	32	27	24	25	22	19	19	16	15	12			12
8	52	40	32	27	46	36	30	25	30	25	21	23	20	17	17	15	13	11			11
9	48	36	29	24	43	33	27	22	27	22	19	21	18	15	16	14	12	10			10
10	45	33	26	22	40	30	24	20	25	20	17	20	16	14	15	12	11	9			9

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	6761	6761	6761	6761
5°	7963	6779	5983	6779
10°	9534	6749	5387	6749
15°	11280	6680	4947	6680
20°	12560	6611	4554	6611
25°	12764	6509	4284	6509
30°	10860	6411	4198	6411
35°	8349	6250	4199	6250
40°	6509	6062	4278	6062
45°	5426	5779	4349	5779
50°	4775	5434	4496	5434
55°	4376	5020	4677	5020
60°	4101	4648	4897	4648
65°	3817	4235	5075	4235
70°	3489	3824	5193	3824
75°	3119	3366	5128	3366
80°	2613	2757	4965	2757
85°	1927	1991	4761	1991



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	81.6	1.1
10°-20°	251.5	3.5
20°-30°	398.8	5.6
30°-40°	443.8	6.2
40°-50°	404.0	5.7
50°-60°	330.1	4.6
60°-70°	235.7	3.3
70°-80°	129.8	1.8
80°-90°	40.6	0.6
90°-100°	114.7	1.6
100°-110°	339.7	4.8
110°-120°	576.5	8.1
120°-130°	760.2	10.6
130°-140°	853.8	12.0
140°-150°	839.0	11.8
150°-160°	705.6	9.9
160°-170°	469.5	6.6
170°-180°	164.4	2.3
0°-30°	731.9	10.3
0°-40°	1175.7	16.5
0°-60°	1909.9	26.8
0°-90°	2316.0	32.4
90°-120°	1030.9	14.4
90°-150°	3483.9	48.8
90°-180°	4823.0	67.6
0°-180°	7139.3	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	838	838	838	838	838	
5°	983	836	738	836	983	100
15°	1350	799	592	799	1350	381
25°	1433	731	481	731	1433	632
35°	847	634	426	634	847	538
45°	475	506	381	506	475	374
55°	311	357	332	357	311	281
65°	200	222	266	222	200	198
75°	100	108	164	108	100	106
85°	21	22	51	22	21	26
90°	40	4	40	4	40	21
95°	106	81	106	81	106	111
105°	328	313	328	313	328	346
115°	581	586	581	586	581	574
125°	847	854	847	854	847	756
135°	1102	1101	1102	1101	1102	851
145°	1339	1338	1339	1338	1339	838
155°	1531	1533	1531	1533	1531	705
165°	1665	1669	1665	1669	1665	469
175°	1728	1736	1728	1736	1728	164
180°	1738	1738	1738	1738	1738	



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5
2.5°	891.4	891.1	888.3	887.8	885.8	883.3	882.8	878.3	869.4	865.3	864.2
5°	982.6	989.5	980.4	978.7	977.7	966.3	960.4	953.4	937.5	928.1	920.8
7.5°	1091.4	1092.2	1088.2	1085.0	1076.2	1066.2	1051.2	1035.3	1016.3	996.5	981.6
10°	1163.0	1165.7	1161.3	1160.6	1142.8	1131.8	1109.6	1090.8	1069.3	1045.4	1023.5
12.5°	1238.5	1234.6	1232.3	1217.5	1214.2	1193.9	1168.1	1148.8	1115.6	1088.1	1059.0
15°	1349.6	1342.0	1337.1	1316.7	1306.6	1278.5	1251.1	1229.9	1186.6	1145.3	1114.0
17.5°	1414.9	1422.5	1411.2	1402.8	1376.8	1357.1	1329.1	1284.7	1250.7	1199.4	1160.0
20°	1462.0	1462.8	1456.5	1447.8	1427.4	1402.4	1371.8	1323.3	1282.6	1231.6	1177.5
22.5°	1474.8	1475.0	1472.3	1464.2	1448.7	1428.4	1397.7	1357.1	1308.0	1252.5	1198.4
25°	1432.9	1431.6	1434.7	1443.7	1437.8	1431.6	1413.8	1383.7	1337.8	1279.2	1220.9
27.5°	1277.2	1286.7	1304.4	1326.6	1348.0	1364.2	1368.9	1362.7	1334.3	1286.0	1225.0
30°	1165.0	1176.9	1190.0	1212.3	1255.3	1279.9	1307.0	1327.4	1316.0	1277.5	1220.6
32.5°	1041.8	1044.7	1064.3	1089.6	1129.0	1176.3	1219.2	1260.8	1274.6	1254.5	1206.9
35°	847.2	852.1	873.3	898.2	946.5	1004.4	1069.0	1126.5	1174.1	1193.2	1168.9
37.5°	691.4	705.3	720.2	747.1	789.6	841.8	908.8	983.3	1054.2	1101.6	1109.6
40°	617.6	626.2	637.0	657.5	693.6	744.9	802.5	887.9	963.1	1031.2	1053.4
42.5°	559.3	564.4	571.0	589.4	617.0	668.0	720.6	795.7	871.3	952.6	989.8
45°	475.3	480.5	491.6	502.4	523.2	558.6	607.5	669.2	745.2	823.7	892.3
47.5°	414.6	418.0	424.6	436.1	453.8	477.2	516.9	568.5	638.9	715.1	788.3
50°	380.2	383.0	388.3	398.7	412.1	433.0	465.6	513.8	569.0	645.7	717.5
52.5°	353.0	354.2	358.0	365.1	375.9	393.3	420.1	459.9	511.3	579.6	651.1
55°	310.9	312.3	315.8	320.9	330.3	341.4	361.9	391.7	436.5	495.8	557.9
57.5°	276.2	277.1	280.1	282.0	289.8	298.8	314.5	335.8	369.8	420.1	475.5
60°	254.0	253.2	256.7	258.5	263.7	271.3	283.5	303.9	333.4	374.0	425.0
62.5°	232.3	231.3	234.3	236.6	239.5	246.0	256.0	272.0	296.0	332.7	376.7
65°	199.8	198.5	200.2	203.0	205.7	209.2	216.5	230.7	249.8	276.2	309.8
67.5°	167.2	168.7	169.0	170.3	171.9	176.6	181.6	191.7	205.2	226.3	254.8
70°	147.8	148.1	149.5	149.5	150.6	154.7	158.9	164.8	178.0	197.4	220.7
72.5°	128.4	129.8	129.3	130.4	131.2	133.9	137.0	142.6	153.8	168.3	187.9
75°	100.0	100.9	100.9	101.3	102.4	103.3	105.8	109.9	118.0	128.7	142.2
77.5°	72.9	73.0	73.5	74.7	74.7	76.4	78.2	81.5	85.5	92.8	101.1
80°	56.2	56.9	56.5	57.2	57.2	58.7	59.3	63.5	65.2	70.1	76.7
82.5°	41.2	41.9	41.8	42.8	43.3	43.6	44.6	46.3	48.0	52.3	55.0
85°	20.8	21.5	20.8	21.5	22.6	22.9	23.9	24.3	25.7	26.8	29.2
87.5°	14.2	14.9	14.8	14.9	15.3	15.4	15.3	14.7	15.4	15.3	16.0
90°	40.3	39.8	39.1	38.5	38.0	36.7	35.0	33.2	31.4	29.6	27.2
92.5°	59.7	59.3	58.9	58.6	58.2	57.5	56.4	55.4	54.3	53.2	51.5
95°	106.2	106.2	106.2	106.2	106.2	105.8	104.9	104.0	103.1	102.2	100.1
97.5°	166.5	166.5	166.5	166.5	166.5	165.9	164.9	163.8	162.6	161.6	159.2
100°	208.4	208.4	208.4	208.4	208.4	208.1	207.5	206.9	206.3	205.7	203.0
102.5°	255.7	255.5	255.3	255.0	254.8	254.2	253.4	252.5	251.7	250.9	248.4
105°	328.1	327.2	326.3	325.4	324.5	323.6	322.7	321.8	320.9	320.0	318.8
107.5°	398.5	398.6	398.7	398.7	398.8	398.4	397.5	396.7	395.8	395.0	394.8
110°	449.1	448.2	447.3	446.4	445.5	445.3	445.9	446.6	447.1	447.7	448.0



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	500.7	500.5	500.3	500.2	500.0	500.0	500.1	500.2	500.3	500.4	501.0
115°	580.9	581.1	581.5	581.8	582.0	582.4	582.6	582.9	583.3	583.5	584.2
117.5°	657.2	657.8	658.4	659.0	659.6	660.4	661.5	662.5	663.4	664.5	664.9
120°	715.3	714.7	714.1	713.5	712.9	713.4	714.9	716.3	717.8	719.3	720.2
122.5°	763.8	764.8	765.9	767.0	768.0	769.1	770.1	771.1	772.1	773.1	773.6
125°	847.0	847.7	848.3	848.8	849.4	850.1	850.7	851.2	851.9	852.5	852.7
127.5°	924.3	924.7	925.2	925.7	926.1	926.7	927.3	927.9	928.4	929.1	929.6
130°	974.8	976.0	977.2	978.4	979.5	980.4	981.1	981.7	982.3	982.8	982.8
132.5°	1028.6	1029.0	1029.6	1030.0	1030.5	1031.0	1031.6	1032.2	1032.9	1033.4	1033.7
135°	1102.5	1103.4	1104.3	1105.2	1106.1	1106.9	1107.5	1108.0	1108.7	1109.3	1109.3
137.5°	1180.3	1180.1	1179.9	1179.7	1179.6	1179.8	1180.6	1181.4	1182.1	1182.9	1182.5
140°	1227.6	1227.9	1228.2	1228.5	1228.8	1229.0	1229.4	1229.7	1229.9	1230.3	1230.3
142.5°	1274.9	1275.0	1275.1	1275.1	1275.1	1275.2	1275.2	1275.3	1275.4	1275.4	1275.7
145°	1339.2	1340.1	1341.0	1341.8	1342.7	1343.4	1343.6	1344.0	1344.3	1344.5	1344.3
147.5°	1404.3	1404.5	1404.9	1405.2	1405.4	1405.7	1406.0	1406.2	1406.4	1406.7	1406.9
150°	1444.0	1444.4	1444.7	1444.9	1445.3	1445.4	1445.4	1445.4	1445.4	1445.4	1445.4
152.5°	1480.6	1481.4	1482.2	1482.9	1483.7	1483.7	1483.0	1482.3	1481.6	1480.9	1480.7
155°	1531.4	1532.7	1533.8	1535.0	1536.2	1536.2	1535.0	1533.8	1532.7	1531.4	1531.8
157.5°	1576.9	1577.9	1579.0	1579.9	1580.9	1581.0	1580.1	1579.2	1578.3	1577.4	1577.5
160°	1602.7	1604.2	1605.7	1607.2	1608.6	1609.0	1608.1	1607.2	1606.3	1605.4	1605.7
162.5°	1629.6	1631.1	1632.6	1634.1	1635.6	1635.5	1633.9	1632.3	1630.7	1629.1	1629.3
165°	1664.6	1665.7	1667.0	1668.1	1669.4	1669.0	1667.2	1665.4	1663.7	1661.9	1662.5
167.5°	1689.5	1691.4	1693.3	1695.1	1697.0	1697.0	1695.2	1693.4	1691.7	1689.9	1689.8
170°	1703.5	1705.7	1707.7	1709.9	1711.9	1712.1	1710.3	1708.5	1706.6	1704.9	1704.6
172.5°	1715.4	1717.4	1719.6	1721.6	1723.8	1723.8	1721.7	1719.8	1717.7	1715.7	1715.6
175°	1727.8	1729.8	1732.0	1734.0	1736.2	1736.2	1734.0	1732.0	1729.8	1727.8	1728.0
177.5°	1734.2	1736.2	1738.0	1739.9	1741.9	1742.0	1740.3	1738.7	1737.0	1735.3	1735.3
180°	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5
2.5°	864.4	860.6	857.8	855.6	849.4	845.9	843.1	839.2	834.7	830.0	824.2
5°	913.6	901.7	893.0	879.9	867.4	856.9	846.2	836.5	824.7	811.9	802.5
7.5°	965.1	947.5	925.1	905.5	883.6	864.5	847.5	830.0	811.8	794.2	778.0
10°	997.8	975.3	950.3	920.8	893.0	868.4	845.5	823.3	801.8	780.2	761.9
12.5°	1033.0	1005.0	968.0	933.5	902.5	869.5	841.9	814.7	788.7	766.2	744.7
15°	1080.4	1039.8	997.1	951.0	910.1	871.6	833.7	799.3	770.3	740.4	719.6
17.5°	1109.5	1059.3	1010.5	962.2	912.7	864.1	823.3	783.7	747.2	717.6	691.3
20°	1128.6	1078.7	1018.0	969.7	910.7	860.8	813.6	769.5	731.4	699.8	672.7
22.5°	1145.3	1087.5	1026.8	963.3	904.6	851.6	800.0	755.6	716.7	683.4	657.5
25°	1154.3	1088.1	1022.1	958.9	892.3	829.6	782.7	730.7	689.0	654.0	626.2
27.5°	1155.3	1084.4	1009.9	939.7	870.9	812.4	753.3	706.8	663.6	626.5	599.9
30°	1152.2	1078.3	998.2	922.2	853.2	789.6	738.3	687.7	643.5	606.8	579.1
32.5°	1142.5	1065.5	983.2	902.8	831.3	769.1	716.1	668.0	625.0	588.8	559.6
35°	1114.4	1038.4	950.7	867.0	793.8	731.0	683.1	634.2	591.2	556.9	528.8
37.5°	1070.5	1001.7	912.6	826.0	754.1	691.1	643.5	599.4	560.6	525.7	496.9
40°	1032.2	971.8	882.3	798.0	720.2	660.2	615.8	575.2	536.7	503.7	476.4
42.5°	988.0	935.4	852.8	763.6	688.6	628.3	585.1	548.6	512.3	481.9	454.4
45°	909.4	874.7	796.9	714.3	636.3	579.4	538.1	506.2	475.6	445.9	422.9
47.5°	818.9	801.6	736.2	657.8	583.7	527.6	491.9	462.4	435.6	410.3	390.1
50°	758.0	749.8	693.2	617.6	546.8	494.1	458.0	432.7	409.7	387.5	368.5
52.5°	698.1	697.9	646.8	577.6	512.1	461.3	425.5	401.8	382.0	363.9	346.8
55°	606.5	616.2	576.3	514.5	455.9	410.1	377.8	356.7	342.8	327.9	315.0
57.5°	522.3	538.4	505.5	451.1	402.2	360.0	331.9	316.0	301.2	292.2	282.9
60°	467.3	482.6	456.9	411.2	365.0	328.9	302.2	287.9	275.1	268.9	262.3
62.5°	418.5	432.1	413.0	370.6	330.6	295.9	273.3	259.7	251.0	244.2	239.8
65°	348.7	360.2	343.8	313.0	278.6	250.8	232.5	221.7	213.4	210.6	205.7
67.5°	281.9	292.3	283.5	257.3	229.7	208.7	194.3	184.0	179.1	176.6	173.2
70°	242.2	252.6	243.2	220.3	199.1	181.5	167.9	162.0	156.9	155.8	151.0
72.5°	208.6	215.7	206.3	188.4	170.3	155.3	144.9	138.8	136.0	134.1	131.5
75°	156.5	162.7	156.5	142.6	129.7	119.3	110.3	107.9	104.8	103.7	102.0
77.5°	110.8	116.2	111.4	102.7	93.1	85.1	80.3	77.1	76.4	74.6	75.4
80°	84.6	88.1	83.6	77.8	70.1	64.6	61.1	59.3	57.2	56.5	58.0
82.5°	60.8	62.3	60.0	56.1	50.4	46.7	44.4	42.4	42.0	42.1	42.1
85°	31.6	31.2	30.9	27.4	25.7	23.3	21.8	21.5	21.1	21.8	22.6
87.5°	15.5	15.3	14.5	12.8	11.4	9.9	8.9	8.0	8.9	9.9	10.8
90°	24.8	22.4	20.1	17.2	13.9	10.6	7.3	4.0	7.3	10.6	13.9
92.5°	49.9	48.2	46.5	43.9	40.0	36.3	32.5	28.8	32.5	36.3	40.0
95°	98.0	95.9	93.8	91.4	88.7	86.1	83.4	80.7	83.4	86.1	88.7
97.5°	156.7	154.3	151.9	149.5	147.4	145.2	143.0	140.9	143.0	145.2	147.4
100°	200.4	197.7	194.9	193.1	191.8	190.6	189.4	188.2	189.4	190.6	191.8
102.5°	246.0	243.5	241.1	239.6	239.2	238.7	238.2	237.7	238.2	238.7	239.2
105°	317.6	316.4	315.2	314.5	314.1	313.9	313.6	313.3	313.6	313.9	314.1
107.5°	394.7	394.5	394.3	394.0	393.7	393.3	393.0	392.6	393.0	393.3	393.7
110°	448.4	448.6	449.0	448.8	448.2	447.5	447.0	446.4	447.0	447.5	448.2



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	501.5	502.0	502.6	502.8	502.7	502.6	502.5	502.3	502.5	502.6	502.7
115°	584.7	585.3	585.9	586.2	586.2	586.2	586.2	586.2	586.2	586.2	586.2
117.5°	665.3	665.8	666.2	666.3	666.0	665.8	665.5	665.3	665.5	665.8	666.0
120°	721.1	722.0	722.9	722.7	721.6	720.4	719.2	718.0	719.2	720.4	721.6
122.5°	773.9	774.4	774.8	774.7	774.3	773.8	773.3	772.8	773.3	773.8	774.3
125°	853.0	853.4	853.6	853.8	853.8	853.8	853.8	853.8	853.8	853.8	853.8
127.5°	930.1	930.5	931.0	930.8	929.9	929.0	928.1	927.2	928.1	929.0	929.9
130°	982.8	982.8	982.8	982.4	981.5	980.6	979.7	978.8	979.7	980.6	981.5
132.5°	1033.9	1034.1	1034.4	1034.2	1033.5	1032.9	1032.2	1031.5	1032.2	1032.9	1033.5
135°	1109.3	1109.3	1109.3	1108.4	1106.6	1104.7	1103.0	1101.2	1103.0	1104.7	1106.6
137.5°	1182.0	1181.5	1181.1	1180.4	1179.6	1178.7	1177.9	1177.1	1177.9	1178.7	1179.6
140°	1230.3	1230.3	1230.3	1229.9	1229.4	1228.8	1228.2	1227.6	1228.2	1228.8	1229.4
142.5°	1275.9	1276.1	1276.4	1276.2	1275.6	1275.1	1274.4	1273.8	1274.4	1275.1	1275.6
145°	1344.0	1343.6	1343.4	1342.6	1341.4	1340.2	1339.0	1337.8	1339.0	1340.2	1341.4
147.5°	1407.1	1407.4	1407.7	1407.0	1405.6	1404.2	1402.8	1401.3	1402.8	1404.2	1405.6
150°	1445.4	1445.4	1445.4	1444.8	1443.6	1442.4	1441.2	1440.0	1441.2	1442.4	1443.6
152.5°	1480.4	1480.2	1480.0	1479.4	1478.7	1478.0	1477.3	1476.6	1477.3	1478.0	1478.7
155°	1532.0	1532.3	1532.7	1532.8	1532.8	1532.8	1532.8	1532.8	1532.8	1532.8	1532.8
157.5°	1577.5	1577.6	1577.7	1578.0	1578.5	1579.0	1579.6	1580.1	1579.6	1579.0	1578.5
160°	1606.0	1606.3	1606.6	1606.9	1607.2	1607.5	1607.8	1608.1	1607.8	1607.5	1607.2
162.5°	1629.7	1630.0	1630.2	1630.8	1631.6	1632.4	1633.2	1633.9	1633.2	1632.4	1631.6
165°	1663.0	1663.7	1664.3	1665.0	1665.9	1666.8	1667.7	1668.6	1667.7	1666.8	1665.9
167.5°	1689.7	1689.7	1689.6	1690.2	1691.5	1692.7	1694.0	1695.2	1694.0	1692.7	1691.5
170°	1704.3	1704.0	1703.7	1704.3	1705.8	1707.3	1708.8	1710.3	1708.8	1707.3	1705.8
172.5°	1715.6	1715.5	1715.4	1716.0	1717.3	1718.5	1719.8	1721.0	1719.8	1718.5	1717.3
175°	1728.3	1728.7	1728.9	1729.8	1731.3	1732.9	1734.3	1735.8	1734.3	1732.9	1731.3
177.5°	1735.3	1735.3	1735.3	1735.9	1737.1	1738.3	1739.5	1740.6	1739.5	1738.3	1737.1
180°	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5
2.5°	821.4	818.9	815.3	810.3	806.2	801.7	800.6	799.0	802.3	799.5	798.7
5°	794.5	787.2	777.8	767.1	760.9	751.8	750.1	746.6	743.2	742.8	739.3
7.5°	766.0	755.3	743.1	732.1	721.9	712.1	705.6	704.3	699.1	696.2	692.7
10°	747.7	734.5	720.2	709.9	698.0	687.7	680.4	676.2	672.7	668.9	665.5
12.5°	726.0	712.0	700.3	689.0	675.0	667.1	655.1	647.9	647.2	647.3	638.3
15°	700.8	687.0	668.9	653.0	645.3	630.1	623.5	615.1	609.9	604.8	600.6
17.5°	672.1	654.8	640.7	622.3	607.8	595.7	586.9	581.9	574.2	566.8	561.4
20°	654.0	635.6	620.7	601.3	585.3	570.4	563.1	556.2	550.3	544.0	538.1
22.5°	635.7	616.4	598.2	579.3	564.5	548.8	541.7	532.3	526.6	523.2	517.3
25°	606.8	586.0	565.2	547.2	531.9	518.0	508.6	501.3	495.1	492.3	488.5
27.5°	575.4	554.7	534.7	514.2	496.9	486.8	479.3	473.8	470.2	466.5	464.8
30°	555.4	534.0	512.5	493.4	477.4	467.3	460.4	456.6	453.8	452.1	450.3
32.5°	535.2	514.0	491.3	473.9	459.7	450.7	445.4	441.6	440.2	439.6	439.0
35°	502.7	481.3	460.4	444.8	431.2	427.8	423.3	421.2	420.5	422.9	424.0
37.5°	471.3	451.3	432.1	417.1	408.1	403.1	401.5	401.6	404.1	406.3	408.8
40°	451.0	431.6	413.6	400.4	392.1	389.0	388.3	389.9	392.7	395.2	398.0
42.5°	431.3	412.1	395.8	383.4	377.6	374.8	375.2	376.9	380.8	383.8	388.0
45°	400.7	384.8	368.8	358.7	353.9	354.5	354.5	357.7	361.5	366.0	370.5
47.5°	371.9	355.8	342.7	334.2	331.7	331.1	333.1	337.2	342.7	348.2	354.5
50°	352.5	337.2	325.7	318.2	315.4	316.4	319.2	323.0	329.6	336.5	343.1
52.5°	332.8	318.9	308.3	301.2	299.3	301.1	303.9	310.0	315.8	323.2	331.2
55°	302.2	290.4	282.0	276.9	276.2	277.2	280.4	287.0	295.2	304.6	312.3
57.5°	271.7	261.9	254.2	250.7	251.0	252.0	257.1	264.9	273.8	283.8	293.6
60°	251.2	242.2	235.9	233.2	233.5	235.6	241.8	249.1	260.2	269.9	280.4
62.5°	231.8	223.8	217.8	215.3	214.9	219.5	225.4	233.0	244.2	254.9	266.2
65°	200.5	194.3	189.4	188.1	189.0	192.5	200.2	210.3	219.6	231.0	242.9
67.5°	170.0	164.9	161.6	162.2	163.5	168.5	175.0	183.6	194.2	206.1	217.8
70°	150.6	145.7	142.9	143.3	145.3	151.6	157.2	165.9	177.3	189.4	199.1
72.5°	130.6	127.4	124.9	126.4	128.4	132.8	139.6	148.4	158.5	169.7	180.0
75°	100.2	100.2	98.9	100.0	103.1	107.2	112.4	121.5	131.5	140.5	148.8
77.5°	74.4	73.7	74.5	75.8	77.6	82.5	88.5	95.0	102.5	111.6	118.4
80°	56.9	57.2	58.9	61.1	61.8	65.5	71.8	77.8	83.6	91.2	97.8
82.5°	42.7	43.1	44.0	46.6	47.3	51.5	55.5	61.3	66.7	71.8	77.3
85°	23.3	23.3	25.0	26.0	27.7	30.5	33.0	36.5	41.3	44.8	49.9
87.5°	12.3	12.9	14.4	15.5	16.9	18.7	19.6	23.0	24.5	26.2	29.0
90°	17.2	20.1	22.4	24.8	27.2	29.6	31.4	33.2	35.0	36.7	38.0
92.5°	43.9	46.5	48.2	49.9	51.5	53.2	54.3	55.4	56.4	57.5	58.2
95°	91.4	93.8	95.9	98.0	100.1	102.2	103.1	104.0	104.9	105.8	106.2
97.5°	149.5	151.9	154.3	156.7	159.2	161.6	162.6	163.8	164.9	165.9	166.5
100°	193.1	194.9	197.7	200.4	203.0	205.7	206.3	206.9	207.5	208.1	208.4
102.5°	239.6	241.1	243.5	246.0	248.4	250.9	251.7	252.5	253.4	254.2	254.8
105°	314.5	315.2	316.4	317.6	318.8	320.0	320.9	321.8	322.7	323.6	324.5
107.5°	394.0	394.3	394.5	394.7	394.8	395.0	395.8	396.7	397.5	398.4	398.8
110°	448.8	449.0	448.6	448.4	448.0	447.7	447.1	446.6	445.9	445.3	445.5



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	502.8	502.6	502.0	501.5	501.0	500.4	500.3	500.2	500.1	500.0	500.0
115°	586.2	585.9	585.3	584.7	584.2	583.5	583.3	582.9	582.6	582.4	582.0
117.5°	666.3	666.2	665.8	665.3	664.9	664.5	663.4	662.5	661.5	660.4	659.6
120°	722.7	722.9	722.0	721.1	720.2	719.3	717.8	716.3	714.9	713.4	712.9
122.5°	774.7	774.8	774.4	773.9	773.6	773.1	772.1	771.1	770.1	769.1	768.0
125°	853.8	853.6	853.4	853.0	852.7	852.5	851.9	851.2	850.7	850.1	849.4
127.5°	930.8	931.0	930.5	930.1	929.6	929.1	928.4	927.9	927.3	926.7	926.1
130°	982.4	982.8	982.8	982.8	982.8	982.8	982.3	981.7	981.1	980.4	979.5
132.5°	1034.2	1034.4	1034.1	1033.9	1033.7	1033.4	1032.9	1032.2	1031.6	1031.0	1030.5
135°	1108.4	1109.3	1109.3	1109.3	1109.3	1109.3	1108.7	1108.0	1107.5	1106.9	1106.1
137.5°	1180.4	1181.1	1181.5	1182.0	1182.5	1182.9	1182.1	1181.4	1180.6	1179.8	1179.6
140°	1229.9	1230.3	1230.3	1230.3	1230.3	1230.3	1229.9	1229.7	1229.4	1229.0	1228.8
142.5°	1276.2	1276.4	1276.1	1275.9	1275.7	1275.4	1275.4	1275.3	1275.2	1275.2	1275.1
145°	1342.6	1343.4	1343.6	1344.0	1344.3	1344.5	1344.3	1344.0	1343.6	1343.4	1342.7
147.5°	1407.0	1407.7	1407.4	1407.1	1406.9	1406.7	1406.4	1406.2	1406.0	1405.7	1405.4
150°	1444.8	1445.4	1445.4	1445.4	1445.4	1445.4	1445.4	1445.4	1445.4	1445.4	1445.3
152.5°	1479.4	1480.0	1480.2	1480.4	1480.7	1480.9	1481.6	1482.3	1483.0	1483.7	1483.7
155°	1532.8	1532.7	1532.3	1532.0	1531.8	1531.4	1532.7	1533.8	1535.0	1536.2	1536.2
157.5°	1578.0	1577.7	1577.6	1577.5	1577.5	1577.4	1578.3	1579.2	1580.1	1581.0	1580.9
160°	1606.9	1606.6	1606.3	1606.0	1605.7	1605.4	1606.3	1607.2	1608.1	1609.0	1608.6
162.5°	1630.8	1630.2	1630.0	1629.7	1629.3	1629.1	1630.7	1632.3	1633.9	1635.5	1635.6
165°	1665.0	1664.3	1663.7	1663.0	1662.5	1661.9	1663.7	1665.4	1667.2	1669.0	1669.4
167.5°	1690.2	1689.6	1689.7	1689.7	1689.8	1689.9	1691.7	1693.4	1695.2	1697.0	1697.0
170°	1704.3	1703.7	1704.0	1704.3	1704.6	1704.9	1706.6	1708.5	1710.3	1712.1	1711.9
172.5°	1716.0	1715.4	1715.5	1715.6	1715.6	1715.7	1717.7	1719.8	1721.7	1723.8	1723.8
175°	1729.8	1728.9	1728.7	1728.3	1728.0	1727.8	1729.8	1732.0	1734.0	1736.2	1736.2
177.5°	1735.9	1735.3	1735.3	1735.3	1735.3	1735.3	1737.0	1738.7	1740.3	1742.0	1741.9
180°	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5
2.5°	798.1	797.5	795.6	795.3	795.6	797.5	798.1	798.7	799.5	802.3	799.0
5°	737.3	735.6	734.5	738.3	734.5	735.6	737.3	739.3	742.8	743.2	746.6
7.5°	691.4	690.0	687.0	686.0	687.0	690.0	691.4	692.7	696.2	699.1	704.3
10°	662.0	660.6	657.8	657.1	657.8	660.6	662.0	665.5	668.9	672.7	676.2
12.5°	633.6	630.9	630.4	631.1	630.4	630.9	633.6	638.3	647.3	647.2	647.9
15°	596.0	594.7	590.8	591.9	590.8	594.7	596.0	600.6	604.8	609.9	615.1
17.5°	559.0	557.3	552.7	556.8	552.7	557.3	559.0	561.4	566.8	574.2	581.9
20°	535.7	532.9	530.5	530.1	530.5	532.9	535.7	538.1	544.0	550.3	556.2
22.5°	513.4	511.0	510.8	508.5	510.8	511.0	513.4	517.3	523.2	526.6	532.3
25°	485.7	483.3	482.6	480.9	482.6	483.3	485.7	488.5	492.3	495.1	501.3
27.5°	464.4	463.2	462.0	462.5	462.0	463.2	464.4	464.8	466.5	470.2	473.8
30°	451.4	451.0	450.3	450.3	450.3	451.0	451.4	450.3	452.1	453.8	456.6
32.5°	440.6	440.5	440.9	440.9	440.9	440.5	440.6	439.0	439.6	440.2	441.6
35°	425.3	426.4	427.1	426.1	427.1	426.4	425.3	424.0	422.9	420.5	421.2
37.5°	411.6	412.7	413.7	414.8	413.7	412.7	411.6	408.8	406.3	404.1	401.6
40°	401.1	403.5	404.2	405.9	404.2	403.5	401.1	398.0	395.2	392.7	389.9
42.5°	391.1	393.8	395.6	395.9	395.6	393.8	391.1	388.0	383.8	380.8	376.9
45°	375.8	378.5	380.9	380.9	380.9	378.5	375.8	370.5	366.0	361.5	357.7
47.5°	359.9	363.9	366.3	366.9	366.3	363.9	359.9	354.5	348.2	342.7	337.2
50°	349.0	353.9	356.3	358.0	356.3	353.9	349.0	343.1	336.5	329.6	323.0
52.5°	338.5	343.3	346.6	347.5	346.6	343.3	338.5	331.2	323.2	315.8	310.0
55°	320.2	327.2	331.0	332.3	331.0	327.2	320.2	312.3	304.6	295.2	287.0
57.5°	303.0	309.4	313.9	314.9	313.9	309.4	303.0	293.6	283.8	273.8	264.9
60°	289.7	296.7	302.2	303.3	302.2	296.7	289.7	280.4	269.9	260.2	249.1
62.5°	276.1	283.3	288.3	291.1	288.3	283.3	276.1	266.2	254.9	244.2	233.0
65°	252.6	259.8	264.7	265.7	264.7	259.8	252.6	242.9	231.0	219.6	210.3
67.5°	226.9	234.2	237.4	239.4	237.4	234.2	226.9	217.8	206.1	194.2	183.6
70°	208.8	214.7	218.2	220.0	218.2	214.7	208.8	199.1	189.4	177.3	165.9
72.5°	188.3	194.5	198.5	198.9	198.5	194.5	188.3	180.0	169.7	158.5	148.4
75°	156.9	162.4	164.4	164.4	164.4	162.4	156.9	148.8	140.5	131.5	121.5
77.5°	124.1	127.0	129.7	130.2	129.7	127.0	124.1	118.4	111.6	102.5	95.0
80°	103.1	104.8	106.8	106.8	106.8	104.8	103.1	97.8	91.2	83.6	77.8
82.5°	81.4	82.8	84.9	84.6	84.9	82.8	81.4	77.3	71.8	66.7	61.3
85°	49.2	52.4	52.1	51.4	52.1	52.4	49.2	49.9	44.8	41.3	36.5
87.5°	29.9	30.3	31.3	31.9	31.3	30.3	29.9	29.0	26.2	24.5	23.0
90°	38.5	39.1	39.8	40.3	39.8	39.1	38.5	38.0	36.7	35.0	33.2
92.5°	58.6	58.9	59.3	59.7	59.3	58.9	58.6	58.2	57.5	56.4	55.4
95°	106.2	106.2	106.2	106.2	106.2	106.2	106.2	106.2	105.8	104.9	104.0
97.5°	166.5	166.5	166.5	166.5	166.5	166.5	166.5	166.5	165.9	164.9	163.8
100°	208.4	208.4	208.4	208.4	208.4	208.4	208.4	208.4	208.1	207.5	206.9
102.5°	255.0	255.3	255.5	255.7	255.5	255.3	255.0	254.8	254.2	253.4	252.5
105°	325.4	326.3	327.2	328.1	327.2	326.3	325.4	324.5	323.6	322.7	321.8
107.5°	398.7	398.7	398.6	398.5	398.6	398.7	398.7	398.8	398.4	397.5	396.7
110°	446.4	447.3	448.2	449.1	448.2	447.3	446.4	445.5	445.3	445.9	446.6



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	500.2	500.3	500.5	500.7	500.5	500.3	500.2	500.0	500.0	500.1	500.2
115°	581.8	581.5	581.1	580.9	581.1	581.5	581.8	582.0	582.4	582.6	582.9
117.5°	659.0	658.4	657.8	657.2	657.8	658.4	659.0	659.6	660.4	661.5	662.5
120°	713.5	714.1	714.7	715.3	714.7	714.1	713.5	712.9	713.4	714.9	716.3
122.5°	767.0	765.9	764.8	763.8	764.8	765.9	767.0	768.0	769.1	770.1	771.1
125°	848.8	848.3	847.7	847.0	847.7	848.3	848.8	849.4	850.1	850.7	851.2
127.5°	925.7	925.2	924.7	924.3	924.7	925.2	925.7	926.1	926.7	927.3	927.9
130°	978.4	977.2	976.0	974.8	976.0	977.2	978.4	979.5	980.4	981.1	981.7
132.5°	1030.0	1029.6	1029.0	1028.6	1029.0	1029.6	1030.0	1030.5	1031.0	1031.6	1032.2
135°	1105.2	1104.3	1103.4	1102.5	1103.4	1104.3	1105.2	1106.1	1106.9	1107.5	1108.0
137.5°	1179.7	1179.9	1180.1	1180.3	1180.1	1179.9	1179.7	1179.6	1179.8	1180.6	1181.4
140°	1228.5	1228.2	1227.9	1227.6	1227.9	1228.2	1228.5	1228.8	1229.0	1229.4	1229.7
142.5°	1275.1	1275.1	1275.0	1274.9	1275.0	1275.1	1275.1	1275.1	1275.2	1275.2	1275.3
145°	1341.8	1341.0	1340.1	1339.2	1340.1	1341.0	1341.8	1342.7	1343.4	1343.6	1344.0
147.5°	1405.2	1404.9	1404.5	1404.3	1404.5	1404.9	1405.2	1405.4	1405.7	1406.0	1406.2
150°	1444.9	1444.7	1444.4	1444.0	1444.4	1444.7	1444.9	1445.3	1445.4	1445.4	1445.4
152.5°	1482.9	1482.2	1481.4	1480.6	1481.4	1482.2	1482.9	1483.7	1483.7	1483.0	1482.3
155°	1535.0	1533.8	1532.7	1531.4	1532.7	1533.8	1535.0	1536.2	1536.2	1535.0	1533.8
157.5°	1579.9	1579.0	1577.9	1576.9	1577.9	1579.0	1579.9	1580.9	1581.0	1580.1	1579.2
160°	1607.2	1605.7	1604.2	1602.7	1604.2	1605.7	1607.2	1608.6	1609.0	1608.1	1607.2
162.5°	1634.1	1632.6	1631.1	1629.6	1631.1	1632.6	1634.1	1635.6	1635.5	1633.9	1632.3
165°	1668.1	1667.0	1665.7	1664.6	1665.7	1667.0	1668.1	1669.4	1669.0	1667.2	1665.4
167.5°	1695.1	1693.3	1691.4	1689.5	1691.4	1693.3	1695.1	1697.0	1697.0	1695.2	1693.4
170°	1709.9	1707.7	1705.7	1703.5	1705.7	1707.7	1709.9	1711.9	1712.1	1710.3	1708.5
172.5°	1721.6	1719.6	1717.4	1715.4	1717.4	1719.6	1721.6	1723.8	1723.8	1721.7	1719.8
175°	1734.0	1732.0	1729.8	1727.8	1729.8	1732.0	1734.0	1736.2	1736.2	1734.0	1732.0
177.5°	1739.9	1738.0	1736.2	1734.2	1736.2	1738.0	1739.9	1741.9	1742.0	1740.3	1738.7
180°	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5
2.5°	800.6	801.7	806.2	810.3	815.3	818.9	821.4	824.2	830.0	834.7	839.2
5°	750.1	751.8	760.9	767.1	777.8	787.2	794.5	802.5	811.9	824.7	836.5
7.5°	705.6	712.1	721.9	732.1	743.1	755.3	766.0	778.0	794.2	811.8	830.0
10°	680.4	687.7	698.0	709.9	720.2	734.5	747.7	761.9	780.2	801.8	823.3
12.5°	655.1	667.1	675.0	689.0	700.3	712.0	726.0	744.7	766.2	788.7	814.7
15°	623.5	630.1	645.3	653.0	668.9	687.0	700.8	719.6	740.4	770.3	799.3
17.5°	586.9	595.7	607.8	622.3	640.7	654.8	672.1	691.3	717.6	747.2	783.7
20°	563.1	570.4	585.3	601.3	620.7	635.6	654.0	672.7	699.8	731.4	769.5
22.5°	541.7	548.8	564.5	579.3	598.2	616.4	635.7	657.5	683.4	716.7	755.6
25°	508.6	518.0	531.9	547.2	565.2	586.0	606.8	626.2	654.0	689.0	730.7
27.5°	479.3	486.8	496.9	514.2	534.7	554.7	575.4	599.9	626.5	663.6	706.8
30°	460.4	467.3	477.4	493.4	512.5	534.0	555.4	579.1	606.8	643.5	687.7
32.5°	445.4	450.7	459.7	473.9	491.3	514.0	535.2	559.6	588.8	625.0	668.0
35°	423.3	427.8	431.2	444.8	460.4	481.3	502.7	528.8	556.9	591.2	634.2
37.5°	401.5	403.1	408.1	417.1	432.1	451.3	471.3	496.9	525.7	560.6	599.4
40°	388.3	389.0	392.1	400.4	413.6	431.6	451.0	476.4	503.7	536.7	575.2
42.5°	375.2	374.8	377.6	383.4	395.8	412.1	431.3	454.4	481.9	512.3	548.6
45°	354.5	354.5	353.9	358.7	368.8	384.8	400.7	422.9	445.9	475.6	506.2
47.5°	333.1	331.1	331.7	334.2	342.7	355.8	371.9	390.1	410.3	435.6	462.4
50°	319.2	316.4	315.4	318.2	325.7	337.2	352.5	368.5	387.5	409.7	432.7
52.5°	303.9	301.1	299.3	301.2	308.3	318.9	332.8	346.8	363.9	382.0	401.8
55°	280.4	277.2	276.2	276.9	282.0	290.4	302.2	315.0	327.9	342.8	356.7
57.5°	257.1	252.0	251.0	250.7	254.2	261.9	271.7	282.9	292.2	301.2	316.0
60°	241.8	235.6	233.5	233.2	235.9	242.2	251.2	262.3	268.9	275.1	287.9
62.5°	225.4	219.5	214.9	215.3	217.8	223.8	231.8	239.8	244.2	251.0	259.7
65°	200.2	192.5	189.0	188.1	189.4	194.3	200.5	205.7	210.6	213.4	221.7
67.5°	175.0	168.5	163.5	162.2	161.6	164.9	170.0	173.2	176.6	179.1	184.0
70°	157.2	151.6	145.3	143.3	142.9	145.7	150.6	151.0	155.8	156.9	162.0
72.5°	139.6	132.8	128.4	126.4	124.9	127.4	130.6	131.5	134.1	136.0	138.8
75°	112.4	107.2	103.1	100.0	98.9	100.2	100.2	102.0	103.7	104.8	107.9
77.5°	88.5	82.5	77.6	75.8	74.5	73.7	74.4	75.4	74.6	76.4	77.1
80°	71.8	65.5	61.8	61.1	58.9	57.2	56.9	58.0	56.5	57.2	59.3
82.5°	55.5	51.5	47.3	46.6	44.0	43.1	42.7	42.1	42.1	42.0	42.4
85°	33.0	30.5	27.7	26.0	25.0	23.3	23.3	22.6	21.8	21.1	21.5
87.5°	19.6	18.7	16.9	15.5	14.4	12.9	12.3	10.8	9.9	8.9	8.0
90°	31.4	29.6	27.2	24.8	22.4	20.1	17.2	13.9	10.6	7.3	4.0
92.5°	54.3	53.2	51.5	49.9	48.2	46.5	43.9	40.0	36.3	32.5	28.8
95°	103.1	102.2	100.1	98.0	95.9	93.8	91.4	88.7	86.1	83.4	80.7
97.5°	162.6	161.6	159.2	156.7	154.3	151.9	149.5	147.4	145.2	143.0	140.9
100°	206.3	205.7	203.0	200.4	197.7	194.9	193.1	191.8	190.6	189.4	188.2
102.5°	251.7	250.9	248.4	246.0	243.5	241.1	239.6	239.2	238.7	238.2	237.7
105°	320.9	320.0	318.8	317.6	316.4	315.2	314.5	314.1	313.9	313.6	313.3
107.5°	395.8	395.0	394.8	394.7	394.5	394.3	394.0	393.7	393.3	393.0	392.6
110°	447.1	447.7	448.0	448.4	448.6	449.0	448.8	448.2	447.5	447.0	446.4



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	500.3	500.4	501.0	501.5	502.0	502.6	502.8	502.7	502.6	502.5	502.3
115°	583.3	583.5	584.2	584.7	585.3	585.9	586.2	586.2	586.2	586.2	586.2
117.5°	663.4	664.5	664.9	665.3	665.8	666.2	666.3	666.0	665.8	665.5	665.3
120°	717.8	719.3	720.2	721.1	722.0	722.9	722.7	721.6	720.4	719.2	718.0
122.5°	772.1	773.1	773.6	773.9	774.4	774.8	774.7	774.3	773.8	773.3	772.8
125°	851.9	852.5	852.7	853.0	853.4	853.6	853.8	853.8	853.8	853.8	853.8
127.5°	928.4	929.1	929.6	930.1	930.5	931.0	930.8	929.9	929.0	928.1	927.2
130°	982.3	982.8	982.8	982.8	982.8	982.8	982.4	981.5	980.6	979.7	978.8
132.5°	1032.9	1033.4	1033.7	1033.9	1034.1	1034.4	1034.2	1033.5	1032.9	1032.2	1031.5
135°	1108.7	1109.3	1109.3	1109.3	1109.3	1109.3	1108.4	1106.6	1104.7	1103.0	1101.2
137.5°	1182.1	1182.9	1182.5	1182.0	1181.5	1181.1	1180.4	1179.6	1178.7	1177.9	1177.1
140°	1229.9	1230.3	1230.3	1230.3	1230.3	1230.3	1229.9	1229.4	1228.8	1228.2	1227.6
142.5°	1275.4	1275.4	1275.7	1275.9	1276.1	1276.4	1276.2	1275.6	1275.1	1274.4	1273.8
145°	1344.3	1344.5	1344.3	1344.0	1343.6	1343.4	1342.6	1341.4	1340.2	1339.0	1337.8
147.5°	1406.4	1406.7	1406.9	1407.1	1407.4	1407.7	1407.0	1405.6	1404.2	1402.8	1401.3
150°	1445.4	1445.4	1445.4	1445.4	1445.4	1445.4	1444.8	1443.6	1442.4	1441.2	1440.0
152.5°	1481.6	1480.9	1480.7	1480.4	1480.2	1480.0	1479.4	1478.7	1478.0	1477.3	1476.6
155°	1532.7	1531.4	1531.8	1532.0	1532.3	1532.7	1532.8	1532.8	1532.8	1532.8	1532.8
157.5°	1578.3	1577.4	1577.5	1577.5	1577.6	1577.7	1578.0	1578.5	1579.0	1579.6	1580.1
160°	1606.3	1605.4	1605.7	1606.0	1606.3	1606.6	1606.9	1607.2	1607.5	1607.8	1608.1
162.5°	1630.7	1629.1	1629.3	1629.7	1630.0	1630.2	1630.8	1631.6	1632.4	1633.2	1633.9
165°	1663.7	1661.9	1662.5	1663.0	1663.7	1664.3	1665.0	1665.9	1666.8	1667.7	1668.6
167.5°	1691.7	1689.9	1689.8	1689.7	1689.7	1689.6	1690.2	1691.5	1692.7	1694.0	1695.2
170°	1706.6	1704.9	1704.6	1704.3	1704.0	1703.7	1704.3	1705.8	1707.3	1708.8	1710.3
172.5°	1717.7	1715.7	1715.6	1715.6	1715.5	1715.4	1716.0	1717.3	1718.5	1719.8	1721.0
175°	1729.8	1727.8	1728.0	1728.3	1728.7	1728.9	1729.8	1731.3	1732.9	1734.3	1735.8
177.5°	1737.0	1735.3	1735.3	1735.3	1735.3	1735.3	1735.9	1737.1	1738.3	1739.5	1740.6
180°	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5	837.5
2.5°	843.1	845.9	849.4	855.6	857.8	860.6	864.4	864.2	865.3	869.4	878.3
5°	846.2	856.9	867.4	879.9	893.0	901.7	913.6	920.8	928.1	937.5	953.4
7.5°	847.5	864.5	883.6	905.5	925.1	947.5	965.1	981.6	996.5	1016.3	1035.3
10°	845.5	868.4	893.0	920.8	950.3	975.3	997.8	1023.5	1045.4	1069.3	1090.8
12.5°	841.9	869.5	902.5	933.5	968.0	1005.0	1033.0	1059.0	1088.1	1115.6	1148.8
15°	833.7	871.6	910.1	951.0	997.1	1039.8	1080.4	1114.0	1145.3	1186.6	1229.9
17.5°	823.3	864.1	912.7	962.2	1010.5	1059.3	1109.5	1160.0	1199.4	1250.7	1284.7
20°	813.6	860.8	910.7	969.7	1018.0	1078.7	1128.6	1177.5	1231.6	1282.6	1323.3
22.5°	800.0	851.6	904.6	963.3	1026.8	1087.5	1145.3	1198.4	1252.5	1308.0	1357.1
25°	782.7	829.6	892.3	958.9	1022.1	1088.1	1154.3	1220.9	1279.2	1337.8	1383.7
27.5°	753.3	812.4	870.9	939.7	1009.9	1084.4	1155.3	1225.0	1286.0	1334.3	1362.7
30°	738.3	789.6	853.2	922.2	998.2	1078.3	1152.2	1220.6	1277.5	1316.0	1327.4
32.5°	716.1	769.1	831.3	902.8	983.2	1065.5	1142.5	1206.9	1254.5	1274.6	1260.8
35°	683.1	731.0	793.8	867.0	950.7	1038.4	1114.4	1168.9	1193.2	1174.1	1126.5
37.5°	643.5	691.1	754.1	826.0	912.6	1001.7	1070.5	1109.6	1101.6	1054.2	983.3
40°	615.8	660.2	720.2	798.0	882.3	971.8	1032.2	1053.4	1031.2	963.1	887.9
42.5°	585.1	628.3	688.6	763.6	852.8	935.4	988.0	989.8	952.6	871.3	795.7
45°	538.1	579.4	636.3	714.3	796.9	874.7	909.4	892.3	823.7	745.2	669.2
47.5°	491.9	527.6	583.7	657.8	736.2	801.6	818.9	788.3	715.1	638.9	568.5
50°	458.0	494.1	546.8	617.6	693.2	749.8	758.0	717.5	645.7	569.0	513.8
52.5°	425.5	461.3	512.1	577.6	646.8	697.9	698.1	651.1	579.6	511.3	459.9
55°	377.8	410.1	455.9	514.5	576.3	616.2	606.5	557.9	495.8	436.5	391.7
57.5°	331.9	360.0	402.2	451.1	505.5	538.4	522.3	475.5	420.1	369.8	335.8
60°	302.2	328.9	365.0	411.2	456.9	482.6	467.3	425.0	374.0	333.4	303.9
62.5°	273.3	295.9	330.6	370.6	413.0	432.1	418.5	376.7	332.7	296.0	272.0
65°	232.5	250.8	278.6	313.0	343.8	360.2	348.7	309.8	276.2	249.8	230.7
67.5°	194.3	208.7	229.7	257.3	283.5	292.3	281.9	254.8	226.3	205.2	191.7
70°	167.9	181.5	199.1	220.3	243.2	252.6	242.2	220.7	197.4	178.0	164.8
72.5°	144.9	155.3	170.3	188.4	206.3	215.7	208.6	187.9	168.3	153.8	142.6
75°	110.3	119.3	129.7	142.6	156.5	162.7	156.5	142.2	128.7	118.0	109.9
77.5°	80.3	85.1	93.1	102.7	111.4	116.2	110.8	101.1	92.8	85.5	81.5
80°	61.1	64.6	70.1	77.8	83.6	88.1	84.6	76.7	70.1	65.2	63.5
82.5°	44.4	46.7	50.4	56.1	60.0	62.3	60.8	55.0	52.3	48.0	46.3
85°	21.8	23.3	25.7	27.4	30.9	31.2	31.6	29.2	26.8	25.7	24.3
87.5°	8.9	9.9	11.4	12.8	14.5	15.3	15.5	16.0	15.3	15.4	14.7
90°	7.3	10.6	13.9	17.2	20.1	22.4	24.8	27.2	29.6	31.4	33.2
92.5°	32.5	36.3	40.0	43.9	46.5	48.2	49.9	51.5	53.2	54.3	55.4
95°	83.4	86.1	88.7	91.4	93.8	95.9	98.0	100.1	102.2	103.1	104.0
97.5°	143.0	145.2	147.4	149.5	151.9	154.3	156.7	159.2	161.6	162.6	163.8
100°	189.4	190.6	191.8	193.1	194.9	197.7	200.4	203.0	205.7	206.3	206.9
102.5°	238.2	238.7	239.2	239.6	241.1	243.5	246.0	248.4	250.9	251.7	252.5
105°	313.6	313.9	314.1	314.5	315.2	316.4	317.6	318.8	320.0	320.9	321.8
107.5°	393.0	393.3	393.7	394.0	394.3	394.5	394.7	394.8	395.0	395.8	396.7
110°	447.0	447.5	448.2	448.8	449.0	448.6	448.4	448.0	447.7	447.1	446.6



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	502.5	502.6	502.7	502.8	502.6	502.0	501.5	501.0	500.4	500.3	500.2
115°	586.2	586.2	586.2	586.2	585.9	585.3	584.7	584.2	583.5	583.3	582.9
117.5°	665.5	665.8	666.0	666.3	666.2	665.8	665.3	664.9	664.5	663.4	662.5
120°	719.2	720.4	721.6	722.7	722.9	722.0	721.1	720.2	719.3	717.8	716.3
122.5°	773.3	773.8	774.3	774.7	774.8	774.4	773.9	773.6	773.1	772.1	771.1
125°	853.8	853.8	853.8	853.8	853.6	853.4	853.0	852.7	852.5	851.9	851.2
127.5°	928.1	929.0	929.9	930.8	931.0	930.5	930.1	929.6	929.1	928.4	927.9
130°	979.7	980.6	981.5	982.4	982.8	982.8	982.8	982.8	982.8	982.3	981.7
132.5°	1032.2	1032.9	1033.5	1034.2	1034.4	1034.1	1033.9	1033.7	1033.4	1032.9	1032.2
135°	1103.0	1104.7	1106.6	1108.4	1109.3	1109.3	1109.3	1109.3	1109.3	1108.7	1108.0
137.5°	1177.9	1178.7	1179.6	1180.4	1181.1	1181.5	1182.0	1182.5	1182.9	1182.1	1181.4
140°	1228.2	1228.8	1229.4	1229.9	1230.3	1230.3	1230.3	1230.3	1230.3	1229.9	1229.7
142.5°	1274.4	1275.1	1275.6	1276.2	1276.4	1276.1	1275.9	1275.7	1275.4	1275.4	1275.3
145°	1339.0	1340.2	1341.4	1342.6	1343.4	1343.6	1344.0	1344.3	1344.5	1344.3	1344.0
147.5°	1402.8	1404.2	1405.6	1407.0	1407.7	1407.4	1407.1	1406.9	1406.7	1406.4	1406.2
150°	1441.2	1442.4	1443.6	1444.8	1445.4	1445.4	1445.4	1445.4	1445.4	1445.4	1445.4
152.5°	1477.3	1478.0	1478.7	1479.4	1480.0	1480.2	1480.4	1480.7	1480.9	1481.6	1482.3
155°	1532.8	1532.8	1532.8	1532.8	1532.7	1532.3	1532.0	1531.8	1531.4	1532.7	1533.8
157.5°	1579.6	1579.0	1578.5	1578.0	1577.7	1577.6	1577.5	1577.5	1577.4	1578.3	1579.2
160°	1607.8	1607.5	1607.2	1606.9	1606.6	1606.3	1606.0	1605.7	1605.4	1606.3	1607.2
162.5°	1633.2	1632.4	1631.6	1630.8	1630.2	1630.0	1629.7	1629.3	1629.1	1630.7	1632.3
165°	1667.7	1666.8	1665.9	1665.0	1664.3	1663.7	1663.0	1662.5	1661.9	1663.7	1665.4
167.5°	1694.0	1692.7	1691.5	1690.2	1689.6	1689.7	1689.7	1689.8	1689.9	1691.7	1693.4
170°	1708.8	1707.3	1705.8	1704.3	1703.7	1704.0	1704.3	1704.6	1704.9	1706.6	1708.5
172.5°	1719.8	1718.5	1717.3	1716.0	1715.4	1715.5	1715.6	1715.6	1715.7	1717.7	1719.8
175°	1734.3	1732.9	1731.3	1729.8	1728.9	1728.7	1728.3	1728.0	1727.8	1729.8	1732.0
177.5°	1739.5	1738.3	1737.1	1735.9	1735.3	1735.3	1735.3	1735.3	1735.3	1737.0	1738.7
180°	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	837.5	837.5	837.5	837.5	837.5	837.5	837.5
2.5°	882.8	883.3	885.8	887.8	888.3	891.1	891.4
5°	960.4	966.3	977.7	978.7	980.4	989.5	982.6
7.5°	1051.2	1066.2	1076.2	1085.0	1088.2	1092.2	1091.4
10°	1109.6	1131.8	1142.8	1160.6	1161.3	1165.7	1163.0
12.5°	1168.1	1193.9	1214.2	1217.5	1232.3	1234.6	1238.5
15°	1251.1	1278.5	1306.6	1316.7	1337.1	1342.0	1349.6
17.5°	1329.1	1357.1	1376.8	1402.8	1411.2	1422.5	1414.9
20°	1371.8	1402.4	1427.4	1447.8	1456.5	1462.8	1462.0
22.5°	1397.7	1428.4	1448.7	1464.2	1472.3	1475.0	1474.8
25°	1413.8	1431.6	1437.8	1443.7	1434.7	1431.6	1432.9
27.5°	1368.9	1364.2	1348.0	1326.6	1304.4	1286.7	1277.2
30°	1307.0	1279.9	1255.3	1212.3	1190.0	1176.9	1165.0
32.5°	1219.2	1176.3	1129.0	1089.6	1064.3	1044.7	1041.8
35°	1069.0	1004.4	946.5	898.2	873.3	852.1	847.2
37.5°	908.8	841.8	789.6	747.1	720.2	705.3	691.4
40°	802.5	744.9	693.6	657.5	637.0	626.2	617.6
42.5°	720.6	668.0	617.0	589.4	571.0	564.4	559.3
45°	607.5	558.6	523.2	502.4	491.6	480.5	475.3
47.5°	516.9	477.2	453.8	436.1	424.6	418.0	414.6
50°	465.6	433.0	412.1	398.7	388.3	383.0	380.2
52.5°	420.1	393.3	375.9	365.1	358.0	354.2	353.0
55°	361.9	341.4	330.3	320.9	315.8	312.3	310.9
57.5°	314.5	298.8	289.8	282.0	280.1	277.1	276.2
60°	283.5	271.3	263.7	258.5	256.7	253.2	254.0
62.5°	256.0	246.0	239.5	236.6	234.3	231.3	232.3
65°	216.5	209.2	205.7	203.0	200.2	198.5	199.8
67.5°	181.6	176.6	171.9	170.3	169.0	168.7	167.2
70°	158.9	154.7	150.6	149.5	149.5	148.1	147.8
72.5°	137.0	133.9	131.2	130.4	129.3	129.8	128.4
75°	105.8	103.3	102.4	101.3	100.9	100.9	100.0
77.5°	78.2	76.4	74.7	74.7	73.5	73.0	72.9
80°	59.3	58.7	57.2	57.2	56.5	56.9	56.2
82.5°	44.6	43.6	43.3	42.8	41.8	41.9	41.2
85°	23.9	22.9	22.6	21.5	20.8	21.5	20.8
87.5°	15.3	15.4	15.3	14.9	14.8	14.9	14.2
90°	35.0	36.7	38.0	38.5	39.1	39.8	40.3
92.5°	56.4	57.5	58.2	58.6	58.9	59.3	59.7
95°	104.9	105.8	106.2	106.2	106.2	106.2	106.2
97.5°	164.9	165.9	166.5	166.5	166.5	166.5	166.5
100°	207.5	208.1	208.4	208.4	208.4	208.4	208.4
102.5°	253.4	254.2	254.8	255.0	255.3	255.5	255.7
105°	322.7	323.6	324.5	325.4	326.3	327.2	328.1
107.5°	397.5	398.4	398.8	398.7	398.7	398.6	398.5
110°	445.9	445.3	445.5	446.4	447.3	448.2	449.1



TEST NUMBER: P332770-940

CATALOG NUMBER: S124DIW-S575D1560U940-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	500.1	500.0	500.0	500.2	500.3	500.5	500.7
115°	582.6	582.4	582.0	581.8	581.5	581.1	580.9
117.5°	661.5	660.4	659.6	659.0	658.4	657.8	657.2
120°	714.9	713.4	712.9	713.5	714.1	714.7	715.3
122.5°	770.1	769.1	768.0	767.0	765.9	764.8	763.8
125°	850.7	850.1	849.4	848.8	848.3	847.7	847.0
127.5°	927.3	926.7	926.1	925.7	925.2	924.7	924.3
130°	981.1	980.4	979.5	978.4	977.2	976.0	974.8
132.5°	1031.6	1031.0	1030.5	1030.0	1029.6	1029.0	1028.6
135°	1107.5	1106.9	1106.1	1105.2	1104.3	1103.4	1102.5
137.5°	1180.6	1179.8	1179.6	1179.7	1179.9	1180.1	1180.3
140°	1229.4	1229.0	1228.8	1228.5	1228.2	1227.9	1227.6
142.5°	1275.2	1275.2	1275.1	1275.1	1275.1	1275.0	1274.9
145°	1343.6	1343.4	1342.7	1341.8	1341.0	1340.1	1339.2
147.5°	1406.0	1405.7	1405.4	1405.2	1404.9	1404.5	1404.3
150°	1445.4	1445.4	1445.3	1444.9	1444.7	1444.4	1444.0
152.5°	1483.0	1483.7	1483.7	1482.9	1482.2	1481.4	1480.6
155°	1535.0	1536.2	1536.2	1535.0	1533.8	1532.7	1531.4
157.5°	1580.1	1581.0	1580.9	1579.9	1579.0	1577.9	1576.9
160°	1608.1	1609.0	1608.6	1607.2	1605.7	1604.2	1602.7
162.5°	1633.9	1635.5	1635.6	1634.1	1632.6	1631.1	1629.6
165°	1667.2	1669.0	1669.4	1668.1	1667.0	1665.7	1664.6
167.5°	1695.2	1697.0	1697.0	1695.1	1693.3	1691.4	1689.5
170°	1710.3	1712.1	1711.9	1709.9	1707.7	1705.7	1703.5
172.5°	1721.7	1723.8	1723.8	1721.6	1719.6	1717.4	1715.4
175°	1734.0	1736.2	1736.2	1734.0	1732.0	1729.8	1727.8
177.5°	1740.3	1742.0	1741.9	1739.9	1738.0	1736.2	1734.2
180°	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5	1738.5

(END OF REPORT)