

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P333713-830

Luminaire Tested: **S125RDIW-S1090D1340U830-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P333713-830  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-11,  
Test Lab: INNOVATION CENTER  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: NEO-RAY  
Catalog Number: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1  
Description: DEFINE 5 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE  
DOWNLIGHT 1090 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING  
UPLIGHT 1340 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER  
Light Source: -  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 8402.4 lumens  
Efficiency: N/A  
Efficacy: 120.4 lumens/watt  
Spacing Criteria (0/90/45): 1.4 / 1.22 / 1.47  
Luminous Opening: Rectangular (W 4' x L: 0.42' x H: 0')  
CIE Type: General Diffuse  
  
Input Watts (W): 69.8  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

### Luminous Intensity Polar Plot





TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	107	107	107	107	98	98	98	98	82	82	82	68	68	68	54	54	54	48	48	48	48	48	48	48		
1	98	94	90	86	90	86	83	80	73	70	68	60	59	57	48	47	47	41	41	41	41	41	41	41		
2	89	82	76	71	82	76	71	66	64	60	57	53	51	48	43	41	40	35	35	35	35	35	35	35		
3	82	72	65	60	75	67	61	56	57	52	48	47	44	41	38	36	34	30	30	30	30	30	30	30		
4	75	64	57	51	69	60	53	48	51	46	41	42	39	36	35	32	30	26	26	26	26	26	26	26		
5	69	57	49	44	63	53	46	41	45	40	36	38	34	31	31	28	26	23	23	23	23	23	23	23		
6	63	52	44	38	58	48	41	36	41	35	31	34	30	27	28	25	23	20	20	20	20	20	20	20		
7	59	47	39	33	54	43	36	31	37	32	28	31	27	24	26	23	21	18	18	18	18	18	18	18		
8	54	42	35	29	50	39	33	28	34	29	25	29	25	22	24	21	18	16	16	16	16	16	16	16		
9	51	39	31	26	47	36	29	25	31	26	22	26	22	19	22	19	17	14	14	14	14	14	14	14		
10	47	35	28	24	44	33	27	22	29	23	20	24	20	17	20	17	15	13	13	13	13	13	13	13		

**AVERAGE LUMINANCE (cd/sqm):**

	0°	90°	180°	270°
0°	10008	10008	10008	10008
5°	11514	10022	8851	10022
10°	13208	9971	7810	9971
15°	14266	9868	6942	9868
20°	15731	9750	6410	9750
25°	18206	9592	5947	9592
30°	19812	9426	5646	9426
35°	16712	9234	5367	9234
40°	11671	8887	5127	8887
45°	8658	8419	4892	8419
50°	6903	7932	4691	7932
55°	5860	7328	4513	7328
60°	5062	6788	4224	6788
65°	4511	6203	3636	6203
70°	3964	5682	3316	5682
75°	3429	4921	3112	4921
80°	2600	4139	2600	4139
85°	2164	3253	2453	3253



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	148.6	1.8
10°-20°	435.5	5.2
20°-30°	690.5	8.2
30°-40°	832.7	9.9
40°-50°	743.6	8.9
50°-60°	570.3	6.8
60°-70°	370.6	4.4
70°-80°	180.2	2.1
80°-90°	46.4	0.6
90°-100°	105.2	1.3
100°-110°	310.7	3.7
110°-120°	526.3	6.3
120°-130°	692.7	8.2
130°-140°	776.1	9.2
140°-150°	760.7	9.1
150°-160°	638.9	7.6
160°-170°	424.7	5.1
170°-180°	148.6	1.8
0°-30°	1274.6	15.2
0°-40°	2107.3	25.1
0°-60°	3421.2	40.7
0°-90°	4018.4	47.8
90°-120°	942.3	11.2
90°-150°	3171.8	37.7
90°-180°	4384.0	52.2
0°-180°	8402.4	100.0

**CANDELA DISTRIBUTION:**

	0°	90°	180°	270°	360°	Flux
0°	1550	1550	1550	1550	1550	
5°	1776	1546	1365	1546	1776	177
15°	2134	1476	1038	1476	2134	611
25°	2555	1346	835	1346	2555	1173
35°	2120	1171	681	1171	2120	1280
45°	948	922	536	922	948	756
55°	520	651	401	651	520	472
65°	295	406	238	406	295	294
75°	137	197	125	197	137	146
85°	29	44	33	44	29	34
90°	29	1	29	1	29	18
95°	105	80	105	80	105	107
105°	303	279	303	279	303	321
115°	532	527	532	527	532	526
125°	774	769	774	769	774	691
135°	1004	1000	1004	1000	1004	774
145°	1216	1212	1216	1212	1216	759
155°	1386	1386	1386	1386	1386	638
165°	1504	1508	1504	1508	1504	424
175°	1561	1567	1561	1567	1561	148
180°	1571	1571	1571	1571	1571	



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7
2.5°	1630.1	1629.1	1631.2	1625.5	1626.1	1617.4	1617.4	1610.8	1602.1	1595.5	1592.4
5°	1776.1	1777.4	1774.9	1765.4	1759.0	1749.5	1738.6	1719.6	1703.6	1688.4	1676.3
7.5°	1926.6	1927.4	1919.0	1916.1	1900.1	1888.4	1864.3	1838.3	1815.3	1786.1	1763.7
10°	2014.1	2013.5	2004.5	1997.5	1983.6	1965.8	1942.2	1911.7	1883.0	1851.2	1820.7
12.5°	2065.0	2063.3	2060.5	2052.0	2039.0	2023.3	2003.3	1973.2	1938.0	1903.2	1867.6
15°	2133.7	2129.2	2121.0	2110.2	2091.7	2073.2	2051.0	2024.3	1990.6	1951.1	1918.1
17.5°	2218.7	2218.8	2206.1	2191.0	2166.0	2133.4	2099.0	2056.0	2010.2	1966.8	1931.6
20°	2288.9	2287.0	2274.3	2245.0	2216.4	2175.7	2136.3	2083.4	2027.4	1970.9	1926.9
22.5°	2389.7	2384.7	2371.4	2333.1	2288.7	2236.3	2176.0	2111.4	2043.7	1979.4	1921.8
25°	2554.9	2551.0	2524.9	2480.4	2418.1	2337.2	2258.3	2169.9	2072.7	1988.0	1918.1
27.5°	2667.8	2663.6	2644.3	2607.3	2549.8	2464.7	2358.0	2239.8	2118.3	2001.9	1901.0
30°	2656.7	2666.2	2663.6	2646.5	2603.2	2526.9	2428.3	2295.3	2150.9	2014.1	1893.9
32.5°	2496.8	2505.4	2527.7	2561.5	2564.0	2533.5	2459.8	2337.0	2187.5	2031.9	1888.3
35°	2119.7	2131.2	2174.4	2242.5	2331.6	2405.9	2421.2	2355.0	2220.8	2053.5	1879.9
37.5°	1629.6	1692.1	1728.6	1800.3	1934.9	2071.7	2203.4	2251.9	2194.7	2044.7	1866.2
40°	1384.3	1399.6	1464.4	1545.2	1658.5	1801.0	1988.7	2124.1	2128.6	2024.3	1844.8
42.5°	1184.8	1204.1	1248.7	1313.2	1410.1	1552.7	1746.4	1925.1	2008.0	1968.3	1816.8
45°	947.9	962.5	994.9	1044.6	1119.0	1236.7	1403.4	1610.1	1774.2	1838.5	1741.8
47.5°	778.6	786.6	814.8	852.6	907.7	993.4	1122.5	1301.9	1498.8	1636.8	1623.2
50°	687.0	696.0	717.6	746.2	792.7	865.2	968.3	1117.8	1320.7	1489.2	1523.0
52.5°	615.8	623.2	636.7	663.7	702.1	757.8	841.0	976.3	1158.9	1338.1	1416.1
55°	520.4	525.5	536.3	551.6	582.1	622.2	694.1	787.6	935.2	1115.8	1230.3
57.5°	441.8	444.3	451.2	465.3	486.4	515.7	567.6	646.9	752.7	915.4	1041.8
60°	391.9	394.5	403.3	412.8	429.4	456.1	496.8	552.1	653.9	788.2	916.1
62.5°	352.1	353.7	357.5	367.0	381.5	402.2	434.2	479.4	560.3	678.3	799.0
65°	295.2	295.8	297.1	304.7	313.6	328.9	349.9	381.7	442.8	531.9	638.7
67.5°	240.4	241.4	245.8	248.5	257.8	265.8	278.1	302.5	345.4	405.5	488.6
70°	209.9	209.3	213.8	217.0	220.1	229.7	237.9	257.7	284.4	330.2	399.5
72.5°	181.4	179.7	181.7	182.9	187.0	193.5	201.8	213.9	234.5	266.1	319.1
75°	137.4	138.1	138.1	139.3	142.5	145.1	147.6	153.9	165.4	186.4	215.0
77.5°	96.4	95.4	98.1	98.5	100.4	103.2	105.4	107.9	112.6	121.2	136.0
80°	69.9	69.9	70.6	72.5	71.9	73.1	76.3	78.9	84.6	89.7	94.8
82.5°	53.7	53.2	53.8	54.2	54.1	55.3	56.5	57.0	59.2	61.7	65.2
85°	29.2	29.2	29.9	29.9	30.5	30.5	31.2	31.2	31.2	31.8	32.4
87.5°	17.1	16.4	15.7	15.6	15.9	16.7	15.9	15.2	14.9	14.6	14.7
90°	29.3	28.6	27.7	26.9	26.1	25.0	23.7	22.2	20.9	19.6	17.6
92.5°	57.7	57.1	56.6	55.9	55.3	54.1	52.3	50.5	48.7	46.9	44.6
95°	105.2	104.6	104.1	103.5	102.9	101.8	99.8	97.9	96.0	94.2	91.4
97.5°	159.5	159.1	158.8	158.4	158.2	157.0	155.2	153.4	151.7	149.9	146.2
100°	200.5	200.0	199.4	198.9	198.3	196.8	194.4	192.0	189.5	187.1	183.5
102.5°	241.6	240.8	240.1	239.3	238.6	236.9	234.1	231.5	228.8	226.2	224.4
105°	303.2	302.4	301.6	300.8	299.9	298.7	297.1	295.5	293.9	292.2	290.6
107.5°	366.3	366.4	366.4	366.5	366.6	366.2	365.3	364.5	363.7	362.9	361.7
110°	413.2	413.5	413.8	414.1	414.3	414.1	413.2	412.5	411.6	410.8	410.0



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	459.2	459.7	460.2	460.7	461.2	461.2	460.8	460.4	460.1	459.7	458.6
115°	531.9	532.2	532.3	532.6	532.9	533.2	533.5	533.8	534.0	534.3	533.8
117.5°	602.8	603.9	604.9	606.1	607.1	607.6	607.3	607.1	606.9	606.7	606.1
120°	651.7	652.7	653.8	654.9	656.0	656.6	656.6	656.6	656.6	656.6	656.3
122.5°	700.6	701.4	702.3	703.1	704.1	704.6	704.8	705.0	705.2	705.5	704.7
125°	773.9	774.2	774.5	774.8	775.1	775.4	776.0	776.5	777.0	777.6	777.3
127.5°	844.3	844.9	845.5	846.0	846.5	847.0	847.2	847.4	847.7	848.0	847.7
130°	891.3	891.8	892.4	893.0	893.4	893.9	894.2	894.4	894.7	894.9	894.4
132.5°	935.3	936.0	936.8	937.6	938.4	938.9	939.1	939.4	939.7	940.0	940.1
135°	1003.8	1004.8	1006.0	1007.0	1008.1	1008.7	1008.7	1008.7	1008.7	1008.7	1008.4
137.5°	1070.8	1072.1	1073.5	1074.9	1076.2	1076.8	1076.4	1076.1	1075.7	1075.4	1074.9
140°	1113.8	1115.2	1116.5	1117.9	1119.3	1119.6	1119.1	1118.6	1118.0	1117.5	1116.6
142.5°	1154.9	1156.2	1157.6	1159.0	1160.4	1160.8	1160.6	1160.2	1159.9	1159.5	1158.5
145°	1216.5	1217.3	1218.1	1219.0	1219.7	1220.2	1220.2	1220.2	1220.2	1220.2	1219.4
147.5°	1269.1	1270.9	1272.8	1274.6	1276.5	1277.1	1276.4	1275.7	1275.2	1274.5	1273.8
150°	1308.2	1308.7	1309.3	1309.9	1310.4	1310.7	1310.7	1310.7	1310.7	1310.7	1309.6
152.5°	1340.5	1341.4	1342.5	1343.4	1344.4	1344.5	1343.9	1343.2	1342.7	1342.0	1341.5
155°	1386.5	1387.8	1389.2	1390.5	1391.9	1392.0	1390.9	1389.9	1388.7	1387.7	1387.4
157.5°	1424.8	1426.6	1428.4	1430.2	1432.0	1432.4	1431.3	1430.2	1429.1	1428.0	1427.8
160°	1451.2	1452.6	1454.0	1455.4	1456.7	1456.8	1455.8	1454.6	1453.6	1452.5	1452.2
162.5°	1473.8	1475.4	1476.9	1478.5	1480.1	1480.2	1478.8	1477.6	1476.3	1475.0	1474.9
165°	1503.8	1505.4	1507.1	1508.7	1510.3	1510.6	1509.6	1508.4	1507.4	1506.3	1506.0
167.5°	1527.8	1529.5	1531.2	1532.9	1534.6	1534.6	1533.0	1531.3	1529.7	1528.0	1528.0
170°	1540.5	1542.4	1544.4	1546.2	1548.1	1548.2	1546.6	1545.0	1543.4	1541.7	1541.7
172.5°	1551.2	1552.9	1554.6	1556.3	1558.0	1558.0	1556.4	1554.8	1553.1	1551.5	1551.5
175°	1561.3	1563.2	1565.1	1567.0	1568.9	1569.1	1567.4	1565.8	1564.1	1562.5	1562.5
177.5°	1567.2	1568.7	1570.2	1571.7	1573.3	1573.4	1572.1	1570.7	1569.4	1568.1	1568.4
180°	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7
2.5°	1592.4	1588.8	1582.2	1576.1	1568.5	1561.9	1557.4	1551.7	1544.6	1536.0	1528.8
5°	1662.9	1648.9	1630.5	1614.6	1594.2	1578.3	1561.8	1545.9	1529.9	1509.6	1491.8
7.5°	1741.1	1712.1	1684.0	1648.7	1616.6	1588.0	1560.5	1532.7	1505.4	1476.5	1448.7
10°	1788.9	1753.9	1715.1	1670.6	1629.8	1591.0	1555.4	1520.4	1483.6	1451.0	1416.1
12.5°	1833.7	1788.5	1744.1	1687.9	1639.0	1591.6	1546.2	1502.6	1463.2	1421.1	1383.6
15°	1874.2	1829.6	1780.0	1711.3	1643.2	1585.9	1532.5	1475.9	1426.9	1379.8	1337.8
17.5°	1889.8	1843.0	1785.5	1719.4	1645.0	1573.0	1504.1	1442.1	1384.4	1329.6	1282.3
20°	1883.7	1838.5	1779.3	1716.4	1636.8	1561.8	1487.3	1418.6	1354.4	1296.5	1246.2
22.5°	1868.9	1822.2	1765.1	1698.6	1623.1	1543.4	1464.0	1390.6	1323.3	1263.4	1208.6
25°	1846.8	1783.2	1724.7	1659.7	1587.9	1509.0	1426.9	1346.1	1274.2	1213.1	1153.4
27.5°	1823.7	1744.4	1669.9	1605.4	1529.5	1459.1	1380.0	1297.1	1221.5	1159.3	1098.0
30°	1802.9	1713.8	1631.7	1558.6	1486.7	1419.9	1344.8	1264.0	1186.5	1122.2	1059.9
32.5°	1776.9	1682.2	1592.0	1507.7	1438.3	1372.1	1304.1	1226.9	1151.3	1085.1	1021.7
35°	1744.4	1623.5	1525.5	1435.8	1358.9	1294.6	1233.5	1171.2	1095.5	1026.8	965.1
37.5°	1701.6	1564.4	1451.0	1353.4	1272.1	1207.7	1159.4	1102.5	1033.4	967.6	910.3
40°	1675.7	1521.7	1397.6	1301.0	1215.7	1147.6	1102.5	1054.1	991.2	929.4	872.1
42.5°	1641.1	1482.5	1343.7	1242.9	1157.2	1091.7	1045.9	1003.7	950.9	892.8	831.4
45°	1573.2	1406.6	1260.8	1152.7	1066.2	1001.9	959.3	921.8	881.7	828.3	774.9
47.5°	1484.9	1327.3	1174.9	1056.8	972.0	912.4	871.0	841.4	812.8	767.3	715.4
50°	1414.2	1262.2	1113.2	998.8	908.4	851.8	813.0	789.5	763.4	722.1	678.8
52.5°	1330.7	1195.0	1049.1	932.1	846.9	793.8	756.5	733.0	711.5	677.8	636.5
55°	1199.2	1080.2	946.6	840.4	762.1	708.7	673.1	650.8	638.1	609.4	577.0
57.5°	1047.4	962.1	844.3	741.9	672.7	619.9	593.8	574.9	560.4	540.3	517.4
60°	941.5	881.7	776.1	678.8	615.2	564.9	541.4	525.5	512.1	494.9	477.1
62.5°	834.2	790.6	698.8	615.2	556.7	514.5	492.5	478.2	462.8	451.2	433.9
65°	690.2	651.4	587.8	522.3	468.3	434.5	418.6	405.9	396.3	383.6	371.6
67.5°	537.0	521.1	477.2	432.1	393.2	363.3	349.5	340.6	329.1	321.5	313.2
70°	442.8	435.2	404.0	374.1	337.8	317.4	304.7	300.9	286.9	279.3	273.5
72.5°	359.3	355.7	337.8	317.1	291.5	273.7	261.9	257.7	248.7	242.6	238.9
75°	246.2	247.5	244.3	230.9	221.4	209.9	199.7	197.2	190.9	185.8	182.6
77.5°	155.7	162.2	162.5	161.8	158.1	151.0	146.8	145.0	138.6	136.8	136.0
80°	106.9	113.9	120.3	119.6	118.3	116.4	113.2	111.3	108.1	106.2	105.0
82.5°	71.3	77.8	83.0	86.5	86.2	84.4	82.2	81.3	80.7	79.3	79.0
85°	33.7	35.0	36.9	41.4	44.5	45.1	44.5	43.9	41.9	42.6	43.3
87.5°	14.9	14.5	14.6	14.2	13.3	15.4	16.5	16.5	15.9	15.4	14.8
90°	15.7	13.9	12.0	9.9	7.7	5.6	3.4	1.2	3.4	5.6	7.7
92.5°	42.3	40.0	37.6	35.6	34.1	32.6	31.1	29.6	31.1	32.6	34.1
95°	88.7	86.0	83.3	81.6	81.1	80.6	80.0	79.5	80.0	80.6	81.1
97.5°	142.4	138.6	134.9	132.9	132.7	132.5	132.2	132.1	132.2	132.5	132.7
100°	180.0	176.4	173.0	171.2	171.2	171.2	171.2	171.2	171.2	171.2	171.2
102.5°	222.6	220.8	219.0	217.5	216.5	215.4	214.3	213.2	214.3	215.4	216.5
105°	289.0	287.3	285.7	284.2	282.9	281.4	280.1	278.8	280.1	281.4	282.9
107.5°	360.3	359.1	357.9	356.6	355.2	353.8	352.5	351.1	352.5	353.8	355.2
110°	409.2	408.4	407.6	406.4	405.1	403.8	402.4	401.1	402.4	403.8	405.1





TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	457.6	456.6	455.6	454.7	454.0	453.3	452.6	451.9	452.6	453.3	454.0
115°	533.2	532.6	532.2	531.3	530.2	529.1	528.0	527.0	528.0	529.1	530.2
117.5°	605.7	605.2	604.7	604.3	603.7	603.2	602.8	602.3	602.8	603.2	603.7
120°	656.0	655.7	655.4	654.7	653.3	652.0	650.5	649.2	650.5	652.0	653.3
122.5°	704.1	703.3	702.7	702.0	701.5	701.1	700.6	700.1	700.6	701.1	701.5
125°	777.0	776.7	776.5	775.5	773.9	772.3	770.6	769.0	770.6	772.3	773.9
127.5°	847.3	847.1	846.7	846.1	845.2	844.2	843.3	842.4	843.3	844.2	845.2
130°	893.9	893.3	892.8	891.8	890.5	889.1	887.8	886.4	887.8	889.1	890.5
132.5°	940.2	940.3	940.4	939.3	937.1	934.9	932.6	930.4	932.6	934.9	937.1
135°	1008.1	1007.9	1007.6	1006.6	1005.0	1003.3	1001.7	1000.1	1001.7	1003.3	1005.0
137.5°	1074.2	1073.7	1073.0	1072.0	1070.4	1068.8	1067.2	1065.6	1067.2	1068.8	1070.4
140°	1115.9	1115.0	1114.2	1113.1	1111.8	1110.4	1109.1	1107.7	1109.1	1110.4	1111.8
142.5°	1157.4	1156.4	1155.4	1154.3	1153.2	1152.1	1150.9	1149.8	1150.9	1152.1	1153.2
145°	1218.5	1217.8	1216.9	1216.0	1214.8	1213.8	1212.7	1211.6	1212.7	1213.8	1214.8
147.5°	1273.2	1272.5	1271.9	1271.2	1270.6	1270.1	1269.4	1268.9	1269.4	1270.1	1270.6
150°	1308.5	1307.4	1306.3	1305.9	1306.2	1306.5	1306.7	1307.0	1306.7	1306.5	1306.2
152.5°	1341.0	1340.7	1340.2	1339.8	1339.4	1339.1	1338.7	1338.3	1338.7	1339.1	1339.4
155°	1387.1	1386.9	1386.6	1386.5	1386.5	1386.5	1386.5	1386.5	1386.5	1386.5	1386.5
157.5°	1427.5	1427.2	1426.9	1427.1	1427.7	1428.3	1428.9	1429.5	1428.9	1428.3	1427.7
160°	1452.0	1451.7	1451.4	1451.7	1452.5	1453.3	1454.2	1454.9	1454.2	1453.3	1452.5
162.5°	1474.9	1474.8	1474.8	1475.1	1475.6	1476.2	1476.9	1477.4	1476.9	1476.2	1475.6
165°	1505.7	1505.4	1505.2	1505.3	1505.9	1506.4	1506.9	1507.5	1506.9	1506.4	1505.9
167.5°	1528.0	1528.0	1528.0	1528.6	1529.7	1530.8	1531.8	1533.0	1531.8	1530.8	1529.7
170°	1541.7	1541.7	1541.7	1542.3	1543.4	1544.5	1545.6	1546.6	1545.6	1544.5	1543.4
172.5°	1551.5	1551.5	1551.5	1552.1	1553.1	1554.3	1555.3	1556.4	1555.3	1554.3	1553.1
175°	1562.5	1562.5	1562.5	1563.1	1564.1	1565.3	1566.3	1567.4	1566.3	1565.3	1564.1
177.5°	1568.6	1568.8	1569.1	1569.5	1570.5	1571.3	1572.2	1573.0	1572.2	1571.3	1570.5
180°	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7
2.5°	1523.7	1516.6	1511.6	1501.4	1494.2	1491.2	1485.5	1484.0	1489.6	1485.5	1485.1
5°	1478.5	1460.0	1445.4	1430.7	1414.9	1404.7	1389.4	1386.9	1383.0	1377.2	1376.0
7.5°	1424.1	1400.1	1381.2	1357.1	1336.1	1319.2	1300.0	1291.0	1286.1	1278.7	1268.8
10°	1387.4	1358.9	1333.4	1309.2	1283.2	1262.2	1243.0	1228.4	1218.9	1209.9	1206.2
12.5°	1351.3	1322.2	1289.6	1260.4	1231.2	1207.7	1186.6	1177.0	1166.5	1156.0	1147.2
15°	1295.2	1256.4	1220.8	1187.0	1162.2	1136.8	1116.4	1102.5	1086.6	1082.1	1065.0
17.5°	1235.7	1197.6	1155.9	1120.4	1091.7	1063.7	1041.2	1025.4	1013.4	997.0	989.1
20°	1198.5	1153.4	1112.7	1080.2	1048.4	1015.3	992.4	979.0	967.6	954.2	947.9
22.5°	1158.9	1114.7	1073.0	1034.9	1002.6	970.1	953.8	939.9	926.9	914.5	906.2
25°	1100.5	1056.0	1012.1	972.7	939.0	915.4	896.4	880.4	873.5	861.4	852.4
27.5°	1042.9	995.6	950.1	910.7	884.3	861.0	845.4	832.7	820.1	809.5	801.8
30°	1005.8	957.4	907.8	876.7	848.7	826.3	809.2	797.1	787.6	778.1	772.3
32.5°	968.7	918.8	874.7	841.0	814.5	795.3	777.6	766.1	756.0	745.5	738.7
35°	909.1	858.2	822.6	789.5	763.4	745.6	733.5	717.0	708.7	701.1	694.1
37.5°	853.8	806.4	767.9	738.9	716.1	698.5	682.9	673.9	663.7	656.9	651.0
40°	813.0	769.8	734.8	704.3	687.7	668.0	653.4	641.9	634.2	625.4	619.0
42.5°	776.4	736.1	702.2	674.7	654.1	637.4	623.3	611.9	602.2	595.9	590.5
45°	724.6	684.5	651.4	625.9	606.9	591.0	576.4	570.6	557.9	550.3	547.7
47.5°	671.0	635.2	603.2	579.8	560.2	545.2	531.4	519.7	512.7	505.2	501.1
50°	634.9	600.5	570.6	547.7	528.7	512.1	499.4	491.7	482.2	475.2	470.1
52.5°	598.8	566.9	537.1	515.2	498.6	482.1	467.9	460.2	451.2	446.7	443.2
55°	547.1	513.4	488.0	466.3	449.1	433.9	420.5	412.8	407.2	402.7	401.4
57.5°	488.6	461.8	438.2	418.7	400.9	386.5	374.8	367.6	362.5	361.8	358.1
60°	450.4	426.2	404.6	383.6	368.3	355.0	344.8	336.5	331.4	330.8	329.5
62.5°	412.3	389.1	369.0	350.5	336.8	324.0	314.2	305.0	301.9	298.8	296.0
65°	355.6	334.6	318.1	303.4	288.8	278.0	268.4	262.8	255.7	251.9	245.0
67.5°	300.0	283.7	267.9	255.5	244.0	233.8	225.8	217.4	212.6	209.5	204.4
70°	263.3	250.6	234.8	221.4	212.4	204.2	197.8	188.3	185.1	182.6	180.0
72.5°	228.8	217.5	204.2	193.4	184.5	176.7	169.4	164.9	161.7	159.2	157.7
75°	180.0	169.2	157.8	150.1	143.7	137.4	133.6	130.4	129.1	128.5	125.9
77.5°	132.2	126.5	117.3	111.2	107.0	104.4	101.0	99.3	99.2	96.4	95.6
80°	101.1	97.9	90.3	87.8	84.6	82.1	80.1	77.0	73.8	72.5	70.6
82.5°	75.2	72.0	69.0	64.8	62.2	60.7	58.8	57.6	58.1	56.3	55.3
85°	40.1	36.9	35.6	35.0	33.7	35.0	34.3	33.7	33.1	32.4	33.1
87.5°	14.7	15.1	15.0	16.4	15.3	16.1	16.4	16.1	16.4	16.7	16.4
90°	9.9	12.0	13.9	15.7	17.6	19.6	20.9	22.2	23.7	25.0	26.1
92.5°	35.6	37.6	40.0	42.3	44.6	46.9	48.7	50.5	52.3	54.1	55.3
95°	81.6	83.3	86.0	88.7	91.4	94.2	96.0	97.9	99.8	101.8	102.9
97.5°	132.9	134.9	138.6	142.4	146.2	149.9	151.7	153.4	155.2	157.0	158.2
100°	171.2	173.0	176.4	180.0	183.5	187.1	189.5	192.0	194.4	196.8	198.3
102.5°	217.5	219.0	220.8	222.6	224.4	226.2	228.8	231.5	234.1	236.9	238.6
105°	284.2	285.7	287.3	289.0	290.6	292.2	293.9	295.5	297.1	298.7	299.9
107.5°	356.6	357.9	359.1	360.3	361.7	362.9	363.7	364.5	365.3	366.2	366.6
110°	406.4	407.6	408.4	409.2	410.0	410.8	411.6	412.5	413.2	414.1	414.3



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	454.7	455.6	456.6	457.6	458.6	459.7	460.1	460.4	460.8	461.2	461.2
115°	531.3	532.2	532.6	533.2	533.8	534.3	534.0	533.8	533.5	533.2	532.9
117.5°	604.3	604.7	605.2	605.7	606.1	606.7	606.9	607.1	607.3	607.6	607.1
120°	654.7	655.4	655.7	656.0	656.3	656.6	656.6	656.6	656.6	656.6	656.0
122.5°	702.0	702.7	703.3	704.1	704.7	705.5	705.2	705.0	704.8	704.6	704.1
125°	775.5	776.5	776.7	777.0	777.3	777.6	777.0	776.5	776.0	775.4	775.1
127.5°	846.1	846.7	847.1	847.3	847.7	848.0	847.7	847.4	847.2	847.0	846.5
130°	891.8	892.8	893.3	893.9	894.4	894.9	894.7	894.4	894.2	893.9	893.4
132.5°	939.3	940.4	940.3	940.2	940.1	940.0	939.7	939.4	939.1	938.9	938.4
135°	1006.6	1007.6	1007.9	1008.1	1008.4	1008.7	1008.7	1008.7	1008.7	1008.7	1008.1
137.5°	1072.0	1073.0	1073.7	1074.2	1074.9	1075.4	1075.7	1076.1	1076.4	1076.8	1076.2
140°	1113.1	1114.2	1115.0	1115.9	1116.6	1117.5	1118.0	1118.6	1119.1	1119.6	1119.3
142.5°	1154.3	1155.4	1156.4	1157.4	1158.5	1159.5	1159.9	1160.2	1160.6	1160.8	1160.4
145°	1216.0	1216.9	1217.8	1218.5	1219.4	1220.2	1220.2	1220.2	1220.2	1220.2	1219.7
147.5°	1271.2	1271.9	1272.5	1273.2	1273.8	1274.5	1275.2	1275.7	1276.4	1277.1	1276.5
150°	1305.9	1306.3	1307.4	1308.5	1309.6	1310.7	1310.7	1310.7	1310.7	1310.7	1310.4
152.5°	1339.8	1340.2	1340.7	1341.0	1341.5	1342.0	1342.7	1343.2	1343.9	1344.5	1344.4
155°	1386.5	1386.6	1386.9	1387.1	1387.4	1387.7	1388.7	1389.9	1390.9	1392.0	1391.9
157.5°	1427.1	1426.9	1427.2	1427.5	1427.8	1428.0	1429.1	1430.2	1431.3	1432.4	1432.0
160°	1451.7	1451.4	1451.7	1452.0	1452.2	1452.5	1453.6	1454.6	1455.8	1456.8	1456.7
162.5°	1475.1	1474.8	1474.8	1474.9	1474.9	1475.0	1476.3	1477.6	1478.8	1480.2	1480.1
165°	1505.3	1505.2	1505.4	1505.7	1506.0	1506.3	1507.4	1508.4	1509.6	1510.6	1510.3
167.5°	1528.6	1528.0	1528.0	1528.0	1528.0	1528.0	1529.7	1531.3	1533.0	1534.6	1534.6
170°	1542.3	1541.7	1541.7	1541.7	1541.7	1541.7	1543.4	1545.0	1546.6	1548.2	1548.1
172.5°	1552.1	1551.5	1551.5	1551.5	1551.5	1551.5	1553.1	1554.8	1556.4	1558.0	1558.0
175°	1563.1	1562.5	1562.5	1562.5	1562.5	1562.5	1564.1	1565.8	1567.4	1569.1	1568.9
177.5°	1569.5	1569.1	1568.8	1568.6	1568.4	1568.1	1569.4	1570.7	1572.1	1573.4	1573.3
180°	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7
2.5°	1484.5	1478.9	1477.4	1479.4	1477.4	1478.9	1484.5	1485.1	1485.5	1489.6	1484.0
5°	1369.7	1363.3	1366.5	1365.2	1366.5	1363.3	1369.7	1376.0	1377.2	1383.0	1386.9
7.5°	1268.7	1260.7	1252.4	1255.0	1252.4	1260.7	1268.7	1268.8	1278.7	1286.1	1291.0
10°	1197.9	1191.6	1187.7	1190.9	1187.7	1191.6	1197.9	1206.2	1209.9	1218.9	1228.4
12.5°	1138.3	1134.5	1131.2	1129.8	1131.2	1134.5	1138.3	1147.2	1156.0	1166.5	1177.0
15°	1057.3	1049.7	1046.5	1038.2	1046.5	1049.7	1057.3	1065.0	1082.1	1086.6	1102.5
17.5°	982.6	980.1	971.8	968.3	971.8	980.1	982.6	989.1	997.0	1013.4	1025.4
20°	938.3	935.8	927.6	932.6	927.6	935.8	938.3	947.9	954.2	967.6	979.0
22.5°	901.7	896.1	893.4	891.9	893.4	896.1	901.7	906.2	914.5	926.9	939.9
25°	849.9	841.6	838.5	834.6	838.5	841.6	849.9	852.4	861.4	873.5	880.4
27.5°	798.2	793.8	789.6	788.6	789.6	793.8	798.2	801.8	809.5	820.1	832.7
30°	764.7	760.3	757.1	757.1	757.1	760.3	764.7	772.3	778.1	787.6	797.1
32.5°	734.6	731.2	728.0	727.5	728.0	731.2	734.6	738.7	745.5	756.0	766.1
35°	690.9	685.8	684.5	680.7	684.5	685.8	690.9	694.1	701.1	708.7	717.0
37.5°	645.5	641.2	641.1	640.7	641.1	641.2	645.5	651.0	656.9	663.7	673.9
40°	616.4	613.2	612.7	608.1	612.7	613.2	616.4	619.0	625.4	634.2	641.9
42.5°	585.4	583.7	581.5	579.7	581.5	583.7	585.4	590.5	595.9	602.2	611.9
45°	543.3	538.9	538.9	535.6	538.9	538.9	543.3	547.7	550.3	557.9	570.6
47.5°	499.7	496.3	496.7	493.4	496.7	496.3	499.7	501.1	505.2	512.7	519.7
50°	470.8	468.8	468.3	466.9	468.3	468.8	470.8	470.1	475.2	482.2	491.7
52.5°	441.8	440.8	443.3	440.5	443.3	440.8	441.8	443.2	446.7	451.2	460.2
55°	402.7	400.8	404.6	400.8	404.6	400.8	402.7	401.4	402.7	407.2	412.8
57.5°	357.8	356.0	359.4	357.5	359.4	356.0	357.8	358.1	361.8	362.5	367.6
60°	328.3	324.4	326.3	327.0	326.3	324.4	328.3	329.5	330.8	331.4	336.5
62.5°	293.1	290.9	292.3	289.4	292.3	290.9	293.1	296.0	298.8	301.9	305.0
65°	243.6	241.8	239.2	237.9	239.2	241.8	243.6	245.0	251.9	255.7	262.8
67.5°	204.7	200.1	200.0	201.0	200.0	200.1	204.7	204.4	209.5	212.6	217.4
70°	176.3	176.3	175.6	175.6	175.6	176.3	176.3	180.0	182.6	185.1	188.3
72.5°	156.4	155.9	154.7	154.2	154.7	155.9	156.4	157.7	159.2	161.7	164.9
75°	125.9	126.6	125.4	124.7	125.4	126.6	125.9	125.9	128.5	129.1	130.4
77.5°	93.0	90.3	91.7	90.3	91.7	90.3	93.0	95.6	96.4	99.2	99.3
80°	70.6	69.9	71.9	69.9	71.9	69.9	70.6	70.6	72.5	73.8	77.0
82.5°	55.9	55.2	56.1	54.7	56.1	55.2	55.9	55.3	56.3	58.1	57.6
85°	33.7	33.1	32.4	33.1	32.4	33.1	33.7	33.1	32.4	33.1	33.7
87.5°	17.1	16.8	16.9	17.1	16.9	16.8	17.1	16.4	16.7	16.4	16.1
90°	26.9	27.7	28.6	29.3	28.6	27.7	26.9	26.1	25.0	23.7	22.2
92.5°	55.9	56.6	57.1	57.7	57.1	56.6	55.9	55.3	54.1	52.3	50.5
95°	103.5	104.1	104.6	105.2	104.6	104.1	103.5	102.9	101.8	99.8	97.9
97.5°	158.4	158.8	159.1	159.5	159.1	158.8	158.4	158.2	157.0	155.2	153.4
100°	198.9	199.4	200.0	200.5	200.0	199.4	198.9	198.3	196.8	194.4	192.0
102.5°	239.3	240.1	240.8	241.6	240.8	240.1	239.3	238.6	236.9	234.1	231.5
105°	300.8	301.6	302.4	303.2	302.4	301.6	300.8	299.9	298.7	297.1	295.5
107.5°	366.5	366.4	366.4	366.3	366.4	366.4	366.5	366.6	366.2	365.3	364.5
110°	414.1	413.8	413.5	413.2	413.5	413.8	414.1	414.3	414.1	413.2	412.5



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	460.7	460.2	459.7	459.2	459.7	460.2	460.7	461.2	461.2	460.8	460.4
115°	532.6	532.3	532.2	531.9	532.2	532.3	532.6	532.9	533.2	533.5	533.8
117.5°	606.1	604.9	603.9	602.8	603.9	604.9	606.1	607.1	607.6	607.3	607.1
120°	654.9	653.8	652.7	651.7	652.7	653.8	654.9	656.0	656.6	656.6	656.6
122.5°	703.1	702.3	701.4	700.6	701.4	702.3	703.1	704.1	704.6	704.8	705.0
125°	774.8	774.5	774.2	773.9	774.2	774.5	774.8	775.1	775.4	776.0	776.5
127.5°	846.0	845.5	844.9	844.3	844.9	845.5	846.0	846.5	847.0	847.2	847.4
130°	893.0	892.4	891.8	891.3	891.8	892.4	893.0	893.4	893.9	894.2	894.4
132.5°	937.6	936.8	936.0	935.3	936.0	936.8	937.6	938.4	938.9	939.1	939.4
135°	1007.0	1006.0	1004.8	1003.8	1004.8	1006.0	1007.0	1008.1	1008.7	1008.7	1008.7
137.5°	1074.9	1073.5	1072.1	1070.8	1072.1	1073.5	1074.9	1076.2	1076.8	1076.4	1076.1
140°	1117.9	1116.5	1115.2	1113.8	1115.2	1116.5	1117.9	1119.3	1119.6	1119.1	1118.6
142.5°	1159.0	1157.6	1156.2	1154.9	1156.2	1157.6	1159.0	1160.4	1160.8	1160.6	1160.2
145°	1219.0	1218.1	1217.3	1216.5	1217.3	1218.1	1219.0	1219.7	1220.2	1220.2	1220.2
147.5°	1274.6	1272.8	1270.9	1269.1	1270.9	1272.8	1274.6	1276.5	1277.1	1276.4	1275.7
150°	1309.9	1309.3	1308.7	1308.2	1308.7	1309.3	1309.9	1310.4	1310.7	1310.7	1310.7
152.5°	1343.4	1342.5	1341.4	1340.5	1341.4	1342.5	1343.4	1344.4	1344.5	1343.9	1343.2
155°	1390.5	1389.2	1387.8	1386.5	1387.8	1389.2	1390.5	1391.9	1392.0	1390.9	1389.9
157.5°	1430.2	1428.4	1426.6	1424.8	1426.6	1428.4	1430.2	1432.0	1432.4	1431.3	1430.2
160°	1455.4	1454.0	1452.6	1451.2	1452.6	1454.0	1455.4	1456.7	1456.8	1455.8	1454.6
162.5°	1478.5	1476.9	1475.4	1473.8	1475.4	1476.9	1478.5	1480.1	1480.2	1478.8	1477.6
165°	1508.7	1507.1	1505.4	1503.8	1505.4	1507.1	1508.7	1510.3	1510.6	1509.6	1508.4
167.5°	1532.9	1531.2	1529.5	1527.8	1529.5	1531.2	1532.9	1534.6	1534.6	1533.0	1531.3
170°	1546.2	1544.4	1542.4	1540.5	1542.4	1544.4	1546.2	1548.1	1548.2	1546.6	1545.0
172.5°	1556.3	1554.6	1552.9	1551.2	1552.9	1554.6	1556.3	1558.0	1558.0	1556.4	1554.8
175°	1567.0	1565.1	1563.2	1561.3	1563.2	1565.1	1567.0	1568.9	1569.1	1567.4	1565.8
177.5°	1571.7	1570.2	1568.7	1567.2	1568.7	1570.2	1571.7	1573.3	1573.4	1572.1	1570.7
180°	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7
2.5°	1485.5	1491.2	1494.2	1501.4	1511.6	1516.6	1523.7	1528.8	1536.0	1544.6	1551.7
5°	1389.4	1404.7	1414.9	1430.7	1445.4	1460.0	1478.5	1491.8	1509.6	1529.9	1545.9
7.5°	1300.0	1319.2	1336.1	1357.1	1381.2	1400.1	1424.1	1448.7	1476.5	1505.4	1532.7
10°	1243.0	1262.2	1283.2	1309.2	1333.4	1358.9	1387.4	1416.1	1451.0	1483.6	1520.4
12.5°	1186.6	1207.7	1231.2	1260.4	1289.6	1322.2	1351.3	1383.6	1421.1	1463.2	1502.6
15°	1116.4	1136.8	1162.2	1187.0	1220.8	1256.4	1295.2	1337.8	1379.8	1426.9	1475.9
17.5°	1041.2	1063.7	1091.7	1120.4	1155.9	1197.6	1235.7	1282.3	1329.6	1384.4	1442.1
20°	992.4	1015.3	1048.4	1080.2	1112.7	1153.4	1198.5	1246.2	1296.5	1354.4	1418.6
22.5°	953.8	970.1	1002.6	1034.9	1073.0	1114.7	1158.9	1208.6	1263.4	1323.3	1390.6
25°	896.4	915.4	939.0	972.7	1012.1	1056.0	1100.5	1153.4	1213.1	1274.2	1346.1
27.5°	845.4	861.0	884.3	910.7	950.1	995.6	1042.9	1098.0	1159.3	1221.5	1297.1
30°	809.2	826.3	848.7	876.7	907.8	957.4	1005.8	1059.9	1122.2	1186.5	1264.0
32.5°	777.6	795.3	814.5	841.0	874.7	918.8	968.7	1021.7	1085.1	1151.3	1226.9
35°	733.5	745.6	763.4	789.5	822.6	858.2	909.1	965.1	1026.8	1095.5	1171.2
37.5°	682.9	698.5	716.1	738.9	767.9	806.4	853.8	910.3	967.6	1033.4	1102.5
40°	653.4	668.0	687.7	704.3	734.8	769.8	813.0	872.1	929.4	991.2	1054.1
42.5°	623.3	637.4	654.1	674.7	702.2	736.1	776.4	831.4	892.8	950.9	1003.7
45°	576.4	591.0	606.9	625.9	651.4	684.5	724.6	774.9	828.3	881.7	921.8
47.5°	531.4	545.2	560.2	579.8	603.2	635.2	671.0	715.4	767.3	812.8	841.4
50°	499.4	512.1	528.7	547.7	570.6	600.5	634.9	678.8	722.1	763.4	789.5
52.5°	467.9	482.1	498.6	515.2	537.1	566.9	598.8	636.5	677.8	711.5	733.0
55°	420.5	433.9	449.1	466.3	488.0	513.4	547.1	577.0	609.4	638.1	650.8
57.5°	374.8	386.5	400.9	418.7	438.2	461.8	488.6	517.4	540.3	560.4	574.9
60°	344.8	355.0	368.3	383.6	404.6	426.2	450.4	477.1	494.9	512.1	525.5
62.5°	314.2	324.0	336.8	350.5	369.0	389.1	412.3	433.9	451.2	462.8	478.2
65°	268.4	278.0	288.8	303.4	318.1	334.6	355.6	371.6	383.6	396.3	405.9
67.5°	225.8	233.8	244.0	255.5	267.9	283.7	300.0	313.2	321.5	329.1	340.6
70°	197.8	204.2	212.4	221.4	234.8	250.6	263.3	273.5	279.3	286.9	300.9
72.5°	169.4	176.7	184.5	193.4	204.2	217.5	228.8	238.9	242.6	248.7	257.7
75°	133.6	137.4	143.7	150.1	157.8	169.2	180.0	182.6	185.8	190.9	197.2
77.5°	101.0	104.4	107.0	111.2	117.3	126.5	132.2	136.0	136.8	138.6	145.0
80°	80.1	82.1	84.6	87.8	90.3	97.9	101.1	105.0	106.2	108.1	111.3
82.5°	58.8	60.7	62.2	64.8	69.0	72.0	75.2	79.0	79.3	80.7	81.3
85°	34.3	35.0	33.7	35.0	35.6	36.9	40.1	43.3	42.6	41.9	43.9
87.5°	16.4	16.1	15.3	16.4	15.0	15.1	14.7	14.8	15.4	15.9	16.5
90°	20.9	19.6	17.6	15.7	13.9	12.0	9.9	7.7	5.6	3.4	1.2
92.5°	48.7	46.9	44.6	42.3	40.0	37.6	35.6	34.1	32.6	31.1	29.6
95°	96.0	94.2	91.4	88.7	86.0	83.3	81.6	81.1	80.6	80.0	79.5
97.5°	151.7	149.9	146.2	142.4	138.6	134.9	132.9	132.7	132.5	132.2	132.1
100°	189.5	187.1	183.5	180.0	176.4	173.0	171.2	171.2	171.2	171.2	171.2
102.5°	228.8	226.2	224.4	222.6	220.8	219.0	217.5	216.5	215.4	214.3	213.2
105°	293.9	292.2	290.6	289.0	287.3	285.7	284.2	282.9	281.4	280.1	278.8
107.5°	363.7	362.9	361.7	360.3	359.1	357.9	356.6	355.2	353.8	352.5	351.1
110°	411.6	410.8	410.0	409.2	408.4	407.6	406.4	405.1	403.8	402.4	401.1



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	460.1	459.7	458.6	457.6	456.6	455.6	454.7	454.0	453.3	452.6	451.9
115°	534.0	534.3	533.8	533.2	532.6	532.2	531.3	530.2	529.1	528.0	527.0
117.5°	606.9	606.7	606.1	605.7	605.2	604.7	604.3	603.7	603.2	602.8	602.3
120°	656.6	656.6	656.3	656.0	655.7	655.4	654.7	653.3	652.0	650.5	649.2
122.5°	705.2	705.5	704.7	704.1	703.3	702.7	702.0	701.5	701.1	700.6	700.1
125°	777.0	777.6	777.3	777.0	776.7	776.5	775.5	773.9	772.3	770.6	769.0
127.5°	847.7	848.0	847.7	847.3	847.1	846.7	846.1	845.2	844.2	843.3	842.4
130°	894.7	894.9	894.4	893.9	893.3	892.8	891.8	890.5	889.1	887.8	886.4
132.5°	939.7	940.0	940.1	940.2	940.3	940.4	939.3	937.1	934.9	932.6	930.4
135°	1008.7	1008.7	1008.4	1008.1	1007.9	1007.6	1006.6	1005.0	1003.3	1001.7	1000.1
137.5°	1075.7	1075.4	1074.9	1074.2	1073.7	1073.0	1072.0	1070.4	1068.8	1067.2	1065.6
140°	1118.0	1117.5	1116.6	1115.9	1115.0	1114.2	1113.1	1111.8	1110.4	1109.1	1107.7
142.5°	1159.9	1159.5	1158.5	1157.4	1156.4	1155.4	1154.3	1153.2	1152.1	1150.9	1149.8
145°	1220.2	1220.2	1219.4	1218.5	1217.8	1216.9	1216.0	1214.8	1213.8	1212.7	1211.6
147.5°	1275.2	1274.5	1273.8	1273.2	1272.5	1271.9	1271.2	1270.6	1270.1	1269.4	1268.9
150°	1310.7	1310.7	1309.6	1308.5	1307.4	1306.3	1305.9	1306.2	1306.5	1306.7	1307.0
152.5°	1342.7	1342.0	1341.5	1341.0	1340.7	1340.2	1339.8	1339.4	1339.1	1338.7	1338.3
155°	1388.7	1387.7	1387.4	1387.1	1386.9	1386.6	1386.5	1386.5	1386.5	1386.5	1386.5
157.5°	1429.1	1428.0	1427.8	1427.5	1427.2	1426.9	1427.1	1427.7	1428.3	1428.9	1429.5
160°	1453.6	1452.5	1452.2	1452.0	1451.7	1451.4	1451.7	1452.5	1453.3	1454.2	1454.9
162.5°	1476.3	1475.0	1474.9	1474.9	1474.8	1474.8	1475.1	1475.6	1476.2	1476.9	1477.4
165°	1507.4	1506.3	1506.0	1505.7	1505.4	1505.2	1505.3	1505.9	1506.4	1506.9	1507.5
167.5°	1529.7	1528.0	1528.0	1528.0	1528.0	1528.0	1528.6	1529.7	1530.8	1531.8	1533.0
170°	1543.4	1541.7	1541.7	1541.7	1541.7	1541.7	1542.3	1543.4	1544.5	1545.6	1546.6
172.5°	1553.1	1551.5	1551.5	1551.5	1551.5	1551.5	1552.1	1553.1	1554.3	1555.3	1556.4
175°	1564.1	1562.5	1562.5	1562.5	1562.5	1562.5	1563.1	1564.1	1565.3	1566.3	1567.4
177.5°	1569.4	1568.1	1568.4	1568.6	1568.8	1569.1	1569.5	1570.5	1571.3	1572.2	1573.0
180°	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7
2.5°	1557.4	1561.9	1568.5	1576.1	1582.2	1588.8	1592.4	1592.4	1595.5	1602.1	1610.8
5°	1561.8	1578.3	1594.2	1614.6	1630.5	1648.9	1662.9	1676.3	1688.4	1703.6	1719.6
7.5°	1560.5	1588.0	1616.6	1648.7	1684.0	1712.1	1741.1	1763.7	1786.1	1815.3	1838.3
10°	1555.4	1591.0	1629.8	1670.6	1715.1	1753.9	1788.9	1820.7	1851.2	1883.0	1911.7
12.5°	1546.2	1591.6	1639.0	1687.9	1744.1	1788.5	1833.7	1867.6	1903.2	1938.0	1973.2
15°	1532.5	1585.9	1643.2	1711.3	1780.0	1829.6	1874.2	1918.1	1951.1	1990.6	2024.3
17.5°	1504.1	1573.0	1645.0	1719.4	1785.5	1843.0	1889.8	1931.6	1966.8	2010.2	2056.0
20°	1487.3	1561.8	1636.8	1716.4	1779.3	1838.5	1883.7	1926.9	1970.9	2027.4	2083.4
22.5°	1464.0	1543.4	1623.1	1698.6	1765.1	1822.2	1868.9	1921.8	1979.4	2043.7	2111.4
25°	1426.9	1509.0	1587.9	1659.7	1724.7	1783.2	1846.8	1918.1	1988.0	2072.7	2169.9
27.5°	1380.0	1459.1	1529.5	1605.4	1669.9	1744.4	1823.7	1901.0	2001.9	2118.3	2239.8
30°	1344.8	1419.9	1486.7	1558.6	1631.7	1713.8	1802.9	1893.9	2014.1	2150.9	2295.3
32.5°	1304.1	1372.1	1438.3	1507.7	1592.0	1682.2	1776.9	1888.3	2031.9	2187.5	2337.0
35°	1233.5	1294.6	1358.9	1435.8	1525.5	1623.5	1744.4	1879.9	2053.5	2220.8	2355.0
37.5°	1159.4	1207.7	1272.1	1353.4	1451.0	1564.4	1701.6	1866.2	2044.7	2194.7	2251.9
40°	1102.5	1147.6	1215.7	1301.0	1397.6	1521.7	1675.7	1844.8	2024.3	2128.6	2124.1
42.5°	1045.9	1091.7	1157.2	1242.9	1343.7	1482.5	1641.1	1816.8	1968.3	2008.0	1925.1
45°	959.3	1001.9	1066.2	1152.7	1260.8	1406.6	1573.2	1741.8	1838.5	1774.2	1610.1
47.5°	871.0	912.4	972.0	1056.8	1174.9	1327.3	1484.9	1623.2	1636.8	1498.8	1301.9
50°	813.0	851.8	908.4	998.8	1113.2	1262.2	1414.2	1523.0	1489.2	1320.7	1117.8
52.5°	756.5	793.8	846.9	932.1	1049.1	1195.0	1330.7	1416.1	1338.1	1158.9	976.3
55°	673.1	708.7	762.1	840.4	946.6	1080.2	1199.2	1230.3	1115.8	935.2	787.6
57.5°	593.8	619.9	672.7	741.9	844.3	962.1	1047.4	1041.8	915.4	752.7	646.9
60°	541.4	564.9	615.2	678.8	776.1	881.7	941.5	916.1	788.2	653.9	552.1
62.5°	492.5	514.5	556.7	615.2	698.8	790.6	834.2	799.0	678.3	560.3	479.4
65°	418.6	434.5	468.3	522.3	587.8	651.4	690.2	638.7	531.9	442.8	381.7
67.5°	349.5	363.3	393.2	432.1	477.2	521.1	537.0	488.6	405.5	345.4	302.5
70°	304.7	317.4	337.8	374.1	404.0	435.2	442.8	399.5	330.2	284.4	257.7
72.5°	261.9	273.7	291.5	317.1	337.8	355.7	359.3	319.1	266.1	234.5	213.9
75°	199.7	209.9	221.4	230.9	244.3	247.5	246.2	215.0	186.4	165.4	153.9
77.5°	146.8	151.0	158.1	161.8	162.5	162.2	155.7	136.0	121.2	112.6	107.9
80°	113.2	116.4	118.3	119.6	120.3	113.9	106.9	94.8	89.7	84.6	78.9
82.5°	82.2	84.4	86.2	86.5	83.0	77.8	71.3	65.2	61.7	59.2	57.0
85°	44.5	45.1	44.5	41.4	36.9	35.0	33.7	32.4	31.8	31.2	31.2
87.5°	16.5	15.4	13.3	14.2	14.6	14.5	14.9	14.7	14.6	14.9	15.2
90°	3.4	5.6	7.7	9.9	12.0	13.9	15.7	17.6	19.6	20.9	22.2
92.5°	31.1	32.6	34.1	35.6	37.6	40.0	42.3	44.6	46.9	48.7	50.5
95°	80.0	80.6	81.1	81.6	83.3	86.0	88.7	91.4	94.2	96.0	97.9
97.5°	132.2	132.5	132.7	132.9	134.9	138.6	142.4	146.2	149.9	151.7	153.4
100°	171.2	171.2	171.2	171.2	173.0	176.4	180.0	183.5	187.1	189.5	192.0
102.5°	214.3	215.4	216.5	217.5	219.0	220.8	222.6	224.4	226.2	228.8	231.5
105°	280.1	281.4	282.9	284.2	285.7	287.3	289.0	290.6	292.2	293.9	295.5
107.5°	352.5	353.8	355.2	356.6	357.9	359.1	360.3	361.7	362.9	363.7	364.5
110°	402.4	403.8	405.1	406.4	407.6	408.4	409.2	410.0	410.8	411.6	412.5





TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	452.6	453.3	454.0	454.7	455.6	456.6	457.6	458.6	459.7	460.1	460.4
115°	528.0	529.1	530.2	531.3	532.2	532.6	533.2	533.8	534.3	534.0	533.8
117.5°	602.8	603.2	603.7	604.3	604.7	605.2	605.7	606.1	606.7	606.9	607.1
120°	650.5	652.0	653.3	654.7	655.4	655.7	656.0	656.3	656.6	656.6	656.6
122.5°	700.6	701.1	701.5	702.0	702.7	703.3	704.1	704.7	705.5	705.2	705.0
125°	770.6	772.3	773.9	775.5	776.5	776.7	777.0	777.3	777.6	777.0	776.5
127.5°	843.3	844.2	845.2	846.1	846.7	847.1	847.3	847.7	848.0	847.7	847.4
130°	887.8	889.1	890.5	891.8	892.8	893.3	893.9	894.4	894.9	894.7	894.4
132.5°	932.6	934.9	937.1	939.3	940.4	940.3	940.2	940.1	940.0	939.7	939.4
135°	1001.7	1003.3	1005.0	1006.6	1007.6	1007.9	1008.1	1008.4	1008.7	1008.7	1008.7
137.5°	1067.2	1068.8	1070.4	1072.0	1073.0	1073.7	1074.2	1074.9	1075.4	1075.7	1076.1
140°	1109.1	1110.4	1111.8	1113.1	1114.2	1115.0	1115.9	1116.6	1117.5	1118.0	1118.6
142.5°	1150.9	1152.1	1153.2	1154.3	1155.4	1156.4	1157.4	1158.5	1159.5	1159.9	1160.2
145°	1212.7	1213.8	1214.8	1216.0	1216.9	1217.8	1218.5	1219.4	1220.2	1220.2	1220.2
147.5°	1269.4	1270.1	1270.6	1271.2	1271.9	1272.5	1273.2	1273.8	1274.5	1275.2	1275.7
150°	1306.7	1306.5	1306.2	1305.9	1306.3	1307.4	1308.5	1309.6	1310.7	1310.7	1310.7
152.5°	1338.7	1339.1	1339.4	1339.8	1340.2	1340.7	1341.0	1341.5	1342.0	1342.7	1343.2
155°	1386.5	1386.5	1386.5	1386.5	1386.6	1386.9	1387.1	1387.4	1387.7	1388.7	1389.9
157.5°	1428.9	1428.3	1427.7	1427.1	1426.9	1427.2	1427.5	1427.8	1428.0	1429.1	1430.2
160°	1454.2	1453.3	1452.5	1451.7	1451.4	1451.7	1452.0	1452.2	1452.5	1453.6	1454.6
162.5°	1476.9	1476.2	1475.6	1475.1	1474.8	1474.8	1474.9	1474.9	1475.0	1476.3	1477.6
165°	1506.9	1506.4	1505.9	1505.3	1505.2	1505.4	1505.7	1506.0	1506.3	1507.4	1508.4
167.5°	1531.8	1530.8	1529.7	1528.6	1528.0	1528.0	1528.0	1528.0	1528.0	1529.7	1531.3
170°	1545.6	1544.5	1543.4	1542.3	1541.7	1541.7	1541.7	1541.7	1541.7	1543.4	1545.0
172.5°	1555.3	1554.3	1553.1	1552.1	1551.5	1551.5	1551.5	1551.5	1551.5	1553.1	1554.8
175°	1566.3	1565.3	1564.1	1563.1	1562.5	1562.5	1562.5	1562.5	1562.5	1564.1	1565.8
177.5°	1572.2	1571.3	1570.5	1569.5	1569.1	1568.8	1568.6	1568.4	1568.1	1569.4	1570.7
180°	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
0°	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7	1549.7
2.5°	1617.4	1617.4	1626.1	1625.5	1631.2	1629.1	1630.1
5°	1738.6	1749.5	1759.0	1765.4	1774.9	1777.4	1776.1
7.5°	1864.3	1888.4	1900.1	1916.1	1919.0	1927.4	1926.6
10°	1942.2	1965.8	1983.6	1997.5	2004.5	2013.5	2014.1
12.5°	2003.3	2023.3	2039.0	2052.0	2060.5	2063.3	2065.0
15°	2051.0	2073.2	2091.7	2110.2	2121.0	2129.2	2133.7
17.5°	2099.0	2133.4	2166.0	2191.0	2206.1	2218.8	2218.7
20°	2136.3	2175.7	2216.4	2245.0	2274.3	2287.0	2288.9
22.5°	2176.0	2236.3	2288.7	2333.1	2371.4	2384.7	2389.7
25°	2258.3	2337.2	2418.1	2480.4	2524.9	2551.0	2554.9
27.5°	2358.0	2464.7	2549.8	2607.3	2644.3	2663.6	2667.8
30°	2428.3	2526.9	2603.2	2646.5	2663.6	2666.2	2656.7
32.5°	2459.8	2533.5	2564.0	2561.5	2527.7	2505.4	2496.8
35°	2421.2	2405.9	2331.6	2242.5	2174.4	2131.2	2119.7
37.5°	2203.4	2071.7	1934.9	1800.3	1728.6	1692.1	1629.6
40°	1988.7	1801.0	1658.5	1545.2	1464.4	1399.6	1384.3
42.5°	1746.4	1552.7	1410.1	1313.2	1248.7	1204.1	1184.8
45°	1403.4	1236.7	1119.0	1044.6	994.9	962.5	947.9
47.5°	1122.5	993.4	907.7	852.6	814.8	786.6	778.6
50°	968.3	865.2	792.7	746.2	717.6	696.0	687.0
52.5°	841.0	757.8	702.1	663.7	636.7	623.2	615.8
55°	694.1	622.2	582.1	551.6	536.3	525.5	520.4
57.5°	567.6	515.7	486.4	465.3	451.2	444.3	441.8
60°	496.8	456.1	429.4	412.8	403.3	394.5	391.9
62.5°	434.2	402.2	381.5	367.0	357.5	353.7	352.1
65°	349.9	328.9	313.6	304.7	297.1	295.8	295.2
67.5°	278.1	265.8	257.8	248.5	245.8	241.4	240.4
70°	237.9	229.7	220.1	217.0	213.8	209.3	209.9
72.5°	201.8	193.5	187.0	182.9	181.7	179.7	181.4
75°	147.6	145.1	142.5	139.3	138.1	138.1	137.4
77.5°	105.4	103.2	100.4	98.5	98.1	95.4	96.4
80°	76.3	73.1	71.9	72.5	70.6	69.9	69.9
82.5°	56.5	55.3	54.1	54.2	53.8	53.2	53.7
85°	31.2	30.5	30.5	29.9	29.9	29.2	29.2
87.5°	15.9	16.7	15.9	15.6	15.7	16.4	17.1
90°	23.7	25.0	26.1	26.9	27.7	28.6	29.3
92.5°	52.3	54.1	55.3	55.9	56.6	57.1	57.7
95°	99.8	101.8	102.9	103.5	104.1	104.6	105.2
97.5°	155.2	157.0	158.2	158.4	158.8	159.1	159.5
100°	194.4	196.8	198.3	198.9	199.4	200.0	200.5
102.5°	234.1	236.9	238.6	239.3	240.1	240.8	241.6
105°	297.1	298.7	299.9	300.8	301.6	302.4	303.2
107.5°	365.3	366.2	366.6	366.5	366.4	366.4	366.3
110°	413.2	414.1	414.3	414.1	413.8	413.5	413.2



TEST NUMBER: P333713-830

CATALOG NUMBER: S125RDIW-S1090D1340U830-4F0-1E-UDD-A1

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
112.5°	460.8	461.2	461.2	460.7	460.2	459.7	459.2
115°	533.5	533.2	532.9	532.6	532.3	532.2	531.9
117.5°	607.3	607.6	607.1	606.1	604.9	603.9	602.8
120°	656.6	656.6	656.0	654.9	653.8	652.7	651.7
122.5°	704.8	704.6	704.1	703.1	702.3	701.4	700.6
125°	776.0	775.4	775.1	774.8	774.5	774.2	773.9
127.5°	847.2	847.0	846.5	846.0	845.5	844.9	844.3
130°	894.2	893.9	893.4	893.0	892.4	891.8	891.3
132.5°	939.1	938.9	938.4	937.6	936.8	936.0	935.3
135°	1008.7	1008.7	1008.1	1007.0	1006.0	1004.8	1003.8
137.5°	1076.4	1076.8	1076.2	1074.9	1073.5	1072.1	1070.8
140°	1119.1	1119.6	1119.3	1117.9	1116.5	1115.2	1113.8
142.5°	1160.6	1160.8	1160.4	1159.0	1157.6	1156.2	1154.9
145°	1220.2	1220.2	1219.7	1219.0	1218.1	1217.3	1216.5
147.5°	1276.4	1277.1	1276.5	1274.6	1272.8	1270.9	1269.1
150°	1310.7	1310.7	1310.4	1309.9	1309.3	1308.7	1308.2
152.5°	1343.9	1344.5	1344.4	1343.4	1342.5	1341.4	1340.5
155°	1390.9	1392.0	1391.9	1390.5	1389.2	1387.8	1386.5
157.5°	1431.3	1432.4	1432.0	1430.2	1428.4	1426.6	1424.8
160°	1455.8	1456.8	1456.7	1455.4	1454.0	1452.6	1451.2
162.5°	1478.8	1480.2	1480.1	1478.5	1476.9	1475.4	1473.8
165°	1509.6	1510.6	1510.3	1508.7	1507.1	1505.4	1503.8
167.5°	1533.0	1534.6	1534.6	1532.9	1531.2	1529.5	1527.8
170°	1546.6	1548.2	1548.1	1546.2	1544.4	1542.4	1540.5
172.5°	1556.4	1558.0	1558.0	1556.3	1554.6	1552.9	1551.2
175°	1567.4	1569.1	1568.9	1567.0	1565.1	1563.2	1561.3
177.5°	1572.1	1573.4	1573.3	1571.7	1570.2	1568.7	1567.2
180°	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1	1571.1

(END OF REPORT)