

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P333374-930

Luminaire Tested: **S125DIW-S610D470U930-4F0-1E-UDD-F**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P333374-930
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-7,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S125DIW-S610D470U930-4F0-1E-UDD-F
Description: DEFINE 5 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 610 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER
UPLIGHT 470 LUMENS PER FOOT, NO LENS
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3566.4 lumens
Efficiency: N/A
Efficacy: 118.1 lumens/watt
Spacing Criteria (0/90/45): 1.21 / 1.18 / 1.31
Luminous Opening: Rectangular (W 0.42' x L: 4' x H: 0')
CIE Type: General Diffuse


Input Watts (W): 30.2
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P333374-930

CATALOG NUMBER: S125DIW-S610D470U930-4F0-1E-UDD-F

Luminous Intensity Polar Plot





TEST NUMBER: P333374-930

CATALOG NUMBER: S125DIW-S610D470U930-4F0-1E-UDD-F

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	109	109	109	109	101	101	101	101	87	87	87	74	74	74	63	63	63	57
1	99	95	91	87	92	88	85	82	76	74	72	65	64	62	55	54	53	48
2	90	83	77	71	84	77	72	67	67	63	59	57	54	52	49	46	44	40
3	82	73	65	59	76	68	61	56	59	54	50	51	47	44	43	40	38	34
4	75	64	56	50	70	60	53	48	52	47	42	45	41	37	38	35	33	29
5	69	57	49	43	64	54	46	41	47	41	37	41	36	32	35	31	28	25
6	64	52	43	37	59	48	41	36	42	36	32	37	32	28	31	28	25	22
7	59	47	39	33	55	44	36	31	38	33	28	33	29	25	29	25	22	20
8	55	42	34	29	51	40	33	28	35	29	25	31	26	22	26	23	20	18
9	51	39	31	26	48	36	30	25	32	26	22	28	24	20	24	21	18	16
10	48	36	28	23	44	34	27	22	30	24	20	26	22	18	23	19	16	14

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	5057	5057	5057
5°	5068	5020	5052
10°	5037	4985	5013
15°	4983	4924	4945
20°	4904	4841	4849
25°	4821	4741	4737
30°	4716	4633	4610
35°	4606	4518	4454
40°	4491	4392	4330
45°	4369	4277	4192
50°	4233	4140	4015
55°	4102	3983	3871
60°	3945	3825	3689
65°	3758	3636	3512
70°	3580	3416	3299
75°	3261	3154	3047
80°	2901	2856	2786
85°	2527	2571	2438



TEST NUMBER: P333374-930

CATALOG NUMBER: S125DIW-S610D470U930-4F0-1E-UDD-F

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	73.8	2.1
10°-20°	208.5	5.8
20°-30°	307.9	8.6
30°-40°	359.3	10.1
40°-50°	360.9	10.1
50°-60°	316.8	8.9
60°-70°	236.0	6.6
70°-80°	135.0	3.8
80°-90°	40.3	1.1
90°-100°	18.1	0.5
100°-110°	111.4	3.1
110°-120°	202.1	5.7
120°-130°	259.4	7.3
130°-140°	279.0	7.8
140°-150°	261.9	7.3
150°-160°	211.8	5.9
160°-170°	137.0	3.8
170°-180°	47.3	1.3
0°-30°	590.3	16.6
0°-40°	949.6	26.6
0°-60°	1627.2	45.6
0°-90°	2038.5	57.2
90°-120°	331.6	9.3
90°-150°	1131.8	31.7
90°-180°	1528.0	42.8
0°-180°	3566.4	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	783	783	783	783	783	
5°	782	780	774	780	779	74
15°	745	743	736	739	740	210
25°	676	673	665	666	665	311
35°	584	581	573	570	565	365
45°	478	476	468	461	459	368
55°	364	362	354	348	344	325
65°	246	244	238	232	230	244
75°	131	129	126	124	122	139
85°	34	35	35	34	33	38
90°	0	3	6	8	9	3
95°	21	19	6	8	8	27
105°	108	110	110	110	110	115
115°	204	205	206	204	202	202
125°	290	292	292	291	290	259
135°	361	363	363	362	360	278
145°	419	419	419	420	418	262
155°	461	459	460	460	458	212
165°	486	484	485	487	484	137
175°	498	496	496	498	495	47
180°	498	498	498	498	498	



TEST NUMBER: P333374-930

CATALOG NUMBER: S125DIW-S610D470U930-4F0-1E-UDD-F

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	783.0	783.0	783.0	783.0	783.0	783.0	783.0	783.0	783.0	783.0	783.0
2.5°	785.0	784.6	784.3	784.0	783.7	782.9	781.9	780.7	779.7	778.5	779.7
5°	781.8	781.5	781.2	780.9	780.6	779.8	778.4	777.1	775.7	774.3	775.6
7.5°	774.5	774.3	774.0	773.7	773.5	772.6	771.0	769.6	768.0	766.5	767.7
10°	768.1	767.8	767.6	767.3	767.0	766.1	764.6	763.1	761.6	760.1	761.2
12.5°	760.2	759.7	759.2	758.7	758.2	757.2	755.9	754.5	753.0	751.6	752.5
15°	745.2	744.8	744.4	744.0	743.6	742.6	741.1	739.6	738.0	736.5	737.2
17.5°	728.0	727.4	726.8	726.2	725.5	724.5	722.9	721.3	719.7	718.2	719.0
20°	713.6	713.3	713.1	712.8	712.5	711.5	709.7	707.9	706.1	704.3	705.3
22.5°	699.2	698.7	698.2	697.7	697.2	696.2	694.5	692.8	691.1	689.4	690.1
25°	676.5	675.7	675.1	674.4	673.7	672.5	670.7	668.9	667.1	665.3	665.6
27.5°	649.8	649.4	649.0	648.6	648.2	647.0	645.1	643.4	641.5	639.7	639.7
30°	632.4	632.0	631.6	631.2	630.8	629.6	627.5	625.4	623.4	621.3	621.0
32.5°	613.6	613.0	612.4	611.7	611.1	609.8	608.1	606.2	604.3	602.5	602.0
35°	584.2	583.6	583.0	582.5	582.0	580.7	578.8	576.8	574.9	573.0	572.3
37.5°	553.5	552.9	552.2	551.5	550.8	549.5	547.7	545.9	544.0	542.3	541.3
40°	532.7	532.1	531.3	530.7	529.9	528.6	526.8	524.8	522.9	521.0	519.8
42.5°	510.5	509.9	509.2	508.7	508.1	506.9	504.9	503.0	501.1	499.1	498.1
45°	478.3	477.7	477.1	476.5	476.1	474.9	473.3	471.7	469.9	468.3	466.7
47.5°	443.5	443.5	443.6	443.6	443.6	442.6	440.7	438.7	436.8	434.7	433.1
50°	421.3	420.8	420.4	420.0	419.6	418.6	416.9	415.2	413.6	412.0	410.2
52.5°	398.4	398.1	397.9	397.5	397.2	396.2	394.4	392.6	390.9	389.1	387.6
55°	364.3	363.8	363.4	363.0	362.6	361.4	359.5	357.6	355.6	353.7	352.5
57.5°	328.2	328.0	327.8	327.5	327.3	326.4	324.7	323.1	321.5	319.9	318.3
60°	305.4	304.8	304.3	303.7	303.2	302.1	300.7	299.1	297.6	296.1	294.7
62.5°	281.6	281.2	280.7	280.3	279.8	279.0	277.7	276.4	275.1	273.8	272.3
65°	245.9	245.6	245.4	245.1	244.8	243.9	242.4	240.9	239.4	237.9	236.6
67.5°	211.3	210.8	210.2	209.6	209.0	208.2	207.1	205.9	204.8	203.7	202.6
70°	189.6	188.9	188.2	187.5	186.8	185.8	184.6	183.4	182.1	180.9	180.0
72.5°	165.8	165.3	164.9	164.4	163.9	163.2	162.5	161.7	160.9	160.0	159.1
75°	130.7	130.4	130.1	129.9	129.6	129.1	128.4	127.8	127.0	126.4	126.0
77.5°	98.4	98.2	98.2	98.0	97.9	97.7	97.3	96.9	96.5	96.1	95.9
80°	78.0	78.0	78.0	78.0	78.0	77.9	77.6	77.4	77.1	76.8	76.6
82.5°	60.3	60.0	59.8	59.5	59.4	59.2	59.1	59.1	59.0	58.9	58.7
85°	34.1	34.2	34.3	34.5	34.7	34.7	34.7	34.7	34.7	34.7	34.6
87.5°	13.5	13.6	13.7	13.9	13.9	14.0	14.0	14.0	14.0	14.1	14.2
90°	0.4	1.1	1.7	2.4	3.0	3.6	4.2	4.7	5.3	5.9	6.3
92.5°	5.7	5.2	4.7	4.3	3.8	3.8	4.4	4.9	5.4	5.9	6.3
95°	21.0	20.8	20.5	20.3	20.1	18.3	15.2	12.1	9.0	5.9	6.3
97.5°	43.9	44.4	44.8	45.2	45.7	42.8	36.6	30.5	24.3	18.2	15.8
100°	61.6	61.9	62.1	62.4	62.6	62.9	63.2	63.5	63.8	64.2	51.9
102.5°	79.6	79.9	80.2	80.6	80.9	81.1	81.3	81.4	81.7	81.9	79.6
105°	108.4	108.8	109.1	109.4	109.7	109.9	109.9	109.9	109.9	109.9	109.9
107.5°	138.4	138.4	138.4	138.4	138.4	138.4	138.6	138.8	138.9	139.1	139.2
110°	157.8	157.8	157.8	157.8	157.8	157.9	158.1	158.2	158.4	158.6	158.3



TEST NUMBER: P333374-930

CATALOG NUMBER: S125DIW-S610D470U930-4F0-1E-UDD-F

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	176.2	176.3	176.5	176.8	176.9	177.1	177.2	177.3	177.4	177.5	177.2
115°	203.6	204.0	204.4	204.8	205.2	205.5	205.5	205.6	205.7	205.8	205.5
117.5°	232.0	232.0	232.0	232.0	232.0	232.1	232.4	232.7	233.0	233.3	232.9
120°	249.7	249.6	249.6	249.5	249.4	249.5	249.7	250.0	250.2	250.5	250.3
122.5°	265.4	265.6	266.0	266.3	266.6	266.8	266.9	267.0	267.2	267.3	267.1
125°	289.5	290.1	290.7	291.2	291.8	292.1	292.1	292.1	292.1	292.1	291.8
127.5°	312.6	313.1	313.5	313.9	314.3	314.5	314.4	314.4	314.3	314.2	314.1
130°	326.8	327.2	327.6	328.0	328.4	328.6	328.7	328.8	328.9	329.0	328.7
132.5°	341.0	341.4	341.9	342.3	342.8	343.0	342.8	342.7	342.4	342.3	342.3
135°	361.1	361.6	362.1	362.6	363.1	363.2	363.1	362.9	362.7	362.6	362.4
137.5°	379.6	380.0	380.4	380.9	381.3	381.5	381.3	381.2	381.0	380.8	380.9
140°	391.7	391.8	392.0	392.2	392.3	392.4	392.3	392.2	392.2	392.1	392.2
142.5°	402.6	402.8	402.8	402.9	403.0	403.1	403.2	403.3	403.5	403.6	403.6
145°	418.7	418.8	419.0	419.1	419.3	419.4	419.4	419.4	419.4	419.4	419.5
147.5°	432.7	432.6	432.6	432.5	432.5	432.5	432.7	432.8	432.8	432.9	433.0
150°	441.5	441.3	441.2	441.0	440.8	440.8	441.0	441.2	441.3	441.5	441.6
152.5°	450.0	449.7	449.3	449.0	448.6	448.5	448.7	448.8	449.0	449.1	449.3
155°	461.1	460.6	460.1	459.6	459.1	458.9	459.1	459.3	459.4	459.6	459.8
157.5°	469.5	469.2	469.0	468.6	468.3	468.2	468.2	468.2	468.2	468.3	468.6
160°	475.4	474.9	474.4	473.9	473.4	473.3	473.4	473.4	473.5	473.6	473.9
162.5°	480.1	479.6	479.2	478.7	478.2	478.0	478.1	478.2	478.3	478.3	478.7
165°	486.5	486.0	485.5	485.0	484.5	484.3	484.4	484.5	484.5	484.6	485.1
167.5°	491.2	490.7	490.2	489.7	489.2	488.9	489.0	489.1	489.2	489.3	489.9
170°	493.9	493.3	492.7	492.1	491.5	491.3	491.4	491.5	491.5	491.6	492.3
172.5°	495.6	495.0	494.5	493.9	493.3	493.2	493.3	493.4	493.6	493.7	494.3
175°	497.6	497.1	496.6	496.1	495.6	495.4	495.5	495.5	495.6	495.7	496.4
177.5°	498.5	498.1	497.7	497.3	496.8	496.7	496.8	496.8	496.9	497.0	497.4
180°	497.6	497.6	497.6	497.6	497.6	497.6	497.6	497.6	497.6	497.6	497.6



TEST NUMBER: P333374-930

CATALOG NUMBER: S125DIW-S610D470U930-4F0-1E-UDD-F

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°
0°	783.0	783.0	783.0	783.0	783.0	783.0	783.0	783.0
2.5°	780.7	781.9	782.9	783.4	783.3	783.2	783.1	783.0
5°	776.8	778.0	779.3	779.8	779.7	779.6	779.4	779.3
7.5°	768.9	770.1	771.4	771.9	771.8	771.6	771.5	771.4
10°	762.3	763.4	764.5	765.0	764.8	764.7	764.5	764.4
12.5°	753.4	754.3	755.1	755.6	755.5	755.5	755.5	755.5
15°	737.9	738.6	739.3	739.6	739.6	739.6	739.6	739.6
17.5°	719.9	720.7	721.6	721.7	721.0	720.3	719.7	718.9
20°	706.2	707.2	708.2	708.3	707.6	706.9	706.2	705.6
22.5°	690.7	691.4	692.0	692.1	691.6	691.1	690.6	690.2
25°	665.9	666.1	666.4	666.3	665.9	665.5	665.1	664.7
27.5°	639.8	639.8	639.8	639.7	639.3	638.9	638.5	638.1
30°	620.8	620.5	620.2	619.9	619.5	619.1	618.6	618.2
32.5°	601.5	601.0	600.5	599.9	599.2	598.4	597.6	596.9
35°	571.6	571.0	570.2	569.3	568.3	567.1	566.1	564.9
37.5°	540.2	539.2	538.2	537.4	536.7	536.1	535.5	534.8
40°	518.4	517.2	516.0	515.2	514.8	514.4	514.0	513.6
42.5°	496.9	495.8	494.6	493.7	493.1	492.5	491.9	491.2
45°	465.0	463.3	461.7	460.6	460.2	459.8	459.4	459.0
47.5°	431.4	429.7	428.0	426.7	425.7	424.8	423.8	422.8
50°	408.4	406.6	404.8	403.4	402.4	401.5	400.5	399.6
52.5°	386.0	384.4	382.9	381.6	380.5	379.4	378.3	377.2
55°	351.2	350.0	348.8	347.6	346.7	345.7	344.8	343.8
57.5°	316.7	315.1	313.5	312.4	311.9	311.4	310.9	310.4
60°	293.3	292.0	290.6	289.4	288.5	287.5	286.5	285.6
62.5°	270.8	269.4	267.8	266.8	266.0	265.2	264.5	263.7
65°	235.4	234.2	232.9	232.0	231.5	230.9	230.4	229.8
67.5°	201.6	200.6	199.5	198.8	198.4	198.1	197.8	197.5
70°	179.2	178.4	177.6	176.9	176.3	175.8	175.2	174.7
72.5°	158.2	157.3	156.3	155.6	155.0	154.5	153.9	153.4
75°	125.6	125.1	124.7	124.3	123.7	123.1	122.6	122.1
77.5°	95.6	95.4	95.1	94.8	94.4	94.1	93.7	93.3
80°	76.6	76.4	76.2	76.1	75.7	75.5	75.3	74.9
82.5°	58.5	58.2	58.0	57.8	57.8	57.7	57.6	57.6
85°	34.4	34.2	34.2	33.9	33.7	33.3	33.1	32.9
87.5°	14.3	14.3	14.4	14.3	14.2	14.0	13.9	13.7
90°	6.7	7.1	7.5	7.9	8.2	8.4	8.6	8.9
92.5°	6.7	7.1	7.5	7.8	7.9	8.1	8.2	8.2
95°	6.7	7.1	7.5	7.7	7.7	7.7	7.7	7.7
97.5°	13.5	11.3	8.9	7.7	7.7	7.7	7.7	7.7
100°	39.8	27.6	15.3	9.0	8.7	8.4	8.1	7.7
102.5°	77.3	74.9	72.6	68.7	63.1	57.6	51.9	46.4
105°	109.9	109.9	109.9	109.9	109.8	109.7	109.7	109.6
107.5°	139.2	139.2	139.2	139.1	138.8	138.6	138.4	138.1
110°	158.1	157.8	157.6	157.5	157.6	157.7	157.8	157.8



TEST NUMBER: P333374-930

CATALOG NUMBER: S125DIW-S610D470U930-4F0-1E-UDD-F

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°
112.5°	176.8	176.5	176.3	176.0	175.9	175.8	175.7	175.5
115°	205.1	204.8	204.5	204.1	203.6	203.1	202.6	202.1
117.5°	232.4	232.0	231.6	231.3	231.1	230.9	230.6	230.5
120°	250.1	250.0	249.8	249.5	249.1	248.7	248.3	247.9
122.5°	266.9	266.8	266.6	266.3	265.8	265.3	264.9	264.4
125°	291.5	291.1	290.8	290.5	290.2	290.0	289.8	289.5
127.5°	313.9	313.7	313.6	313.2	312.5	311.9	311.3	310.7
130°	328.5	328.2	328.0	327.7	327.3	326.9	326.4	326.0
132.5°	342.2	342.1	342.1	341.9	341.4	341.0	340.6	340.2
135°	362.2	362.1	361.9	361.6	361.1	360.6	360.1	359.6
137.5°	380.9	381.0	381.0	380.8	380.3	379.9	379.5	379.1
140°	392.4	392.6	392.7	392.6	392.1	391.6	391.1	390.6
142.5°	403.7	403.7	403.7	403.5	403.0	402.5	402.0	401.5
145°	419.6	419.6	419.7	419.5	419.0	418.5	418.0	417.5
147.5°	433.2	433.3	433.3	433.1	432.5	431.9	431.3	430.7
150°	441.8	442.0	442.1	441.9	441.2	440.6	439.9	439.3
152.5°	449.5	449.6	449.8	449.6	449.0	448.4	447.8	447.3
155°	460.1	460.3	460.6	460.3	459.7	459.0	458.4	457.7
157.5°	468.8	469.0	469.3	469.1	468.5	467.8	467.2	466.5
160°	474.3	474.6	474.9	474.7	474.1	473.4	472.8	472.1
162.5°	479.2	479.7	480.1	480.0	479.3	478.6	477.8	477.1
165°	485.7	486.2	486.7	486.6	485.9	485.2	484.5	483.9
167.5°	490.5	491.1	491.6	491.6	490.8	490.1	489.3	488.6
170°	492.9	493.7	494.3	494.2	493.5	492.8	492.0	491.3
172.5°	494.9	495.5	496.1	496.0	495.3	494.6	493.8	493.1
175°	497.0	497.7	498.3	498.3	497.6	496.8	496.1	495.4
177.5°	497.9	498.3	498.8	498.8	498.2	497.7	497.2	496.7
180°	497.6	497.6	497.6	497.6	497.6	497.6	497.6	497.6

(END OF REPORT)