

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P333460

Luminaire Tested: **S125DIW-S1270D470U835-4F0-1E-UDD-A**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P333460
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-7,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S125DIW-S1270D470U835-4F0-1E-UDD-A
Description: DEFINE 5 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 1270 LUMENS PER FOOT, ASYMMETRIC DIFFUSER
UPLIGHT 470 LUMENS PER FOOT, NO LENS
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7057.7 lumens
Efficiency: N/A
Efficacy: 134.7 lumens/watt
Spacing Criteria (0/90/45): 1.43 / 1.23 / 1.52
Luminous Opening: Rectangular (W 4' x L: 0.42' x H: 0')
CIE Type: Semi-Direct


Input Watts (W): 52.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

Luminous Intensity Polar Plot





TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	113	113	113	113	107	107	107	107	96	96	96	87	87	87	78	78	78	73
1	103	99	95	92	98	94	91	88	85	83	80	77	75	73	69	68	66	63
2	94	87	81	75	89	83	77	72	75	71	67	68	64	61	61	59	56	53
3	86	77	69	63	82	73	66	61	66	61	57	60	56	52	55	51	48	45
4	79	68	60	54	75	65	58	52	59	53	49	54	49	45	49	45	42	39
5	73	61	53	46	69	58	51	45	53	47	42	49	43	39	44	40	37	34
6	67	55	46	40	64	52	45	39	48	42	37	44	39	35	40	36	32	30
7	62	50	41	36	59	48	40	35	44	37	33	40	35	31	37	32	29	26
8	58	45	37	32	55	43	36	31	40	34	29	37	31	27	34	29	26	24
9	54	41	34	28	51	40	33	28	37	31	26	34	29	25	31	27	23	21
10	51	38	31	26	48	37	30	25	34	28	24	31	26	22	29	24	21	19

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	11861	11861	11861	11861
5°	13736	11902	10421	11902
10°	15980	11840	9130	11840
15°	17690	11753	8423	11753
20°	19801	11615	7854	11615
25°	23197	11460	7577	11460
30°	25055	11307	7337	11307
35°	20601	11020	7179	11020
40°	14643	10620	7006	10620
45°	11249	10082	6906	10082
50°	9602	9414	6893	9414
55°	8550	8760	6952	8760
60°	7713	8045	7129	8045
65°	7124	7326	7314	7326
70°	6477	6579	7419	6579
75°	5719	5797	7354	5797
80°	4813	4727	6724	4727
85°	3809	3409	5432	3409



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	176.8	2.5
10°-20°	526.4	7.5
20°-30°	854.8	12.1
30°-40°	1042.7	14.8
40°-50°	948.5	13.4
50°-60°	755.5	10.7
60°-70°	526.2	7.5
70°-80°	280.6	4.0
80°-90°	72.1	1.0
90°-100°	22.2	0.3
100°-110°	136.7	1.9
110°-120°	247.9	3.5
120°-130°	318.1	4.5
130°-140°	342.2	4.8
140°-150°	321.2	4.6
150°-160°	259.8	3.7
160°-170°	168.0	2.4
170°-180°	58.0	0.8
0°-30°	1558.0	22.1
0°-40°	2600.7	36.8
0°-60°	4304.7	61.0
0°-90°	5183.7	73.4
90°-120°	406.7	5.8
90°-150°	1388.2	19.7
90°-180°	1874.0	26.6
0°-180°	7057.7	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1837	1837	1837	1837	1837	
5°	2119	1836	1607	1836	2119	214
15°	2646	1758	1260	1758	2646	757
25°	3255	1608	1063	1608	3255	1487
35°	2613	1398	910	1398	2613	1599
45°	1232	1104	756	1104	1232	986
55°	759	778	617	778	759	684
65°	466	479	479	479	466	463
75°	229	232	295	232	229	247
85°	51	46	73	46	51	60
90°	11	0	11	0	11	7
95°	10	26	10	26	10	8
105°	134	133	134	133	134	121
115°	248	250	248	250	248	246
125°	355	355	355	355	355	316
135°	441	443	441	443	441	340
145°	512	514	512	514	512	320
155°	561	566	561	566	561	259
165°	594	597	594	597	594	168
175°	608	610	608	610	608	58
180°	610	610	610	610	610	



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6
2.5°	1942.6	1940.1	1937.6	1932.6	1936.3	1925.7	1920.7	1912.0	1901.4	1897.7	1893.3
5°	2118.7	2122.6	2126.5	2110.2	2111.7	2100.8	2075.9	2055.6	2039.2	2018.2	2003.4
7.5°	2330.8	2321.6	2320.8	2310.2	2292.0	2277.3	2251.1	2217.7	2185.5	2148.7	2118.3
10°	2436.8	2437.6	2430.6	2418.1	2398.6	2384.6	2350.3	2317.5	2277.8	2231.0	2197.5
12.5°	2516.6	2519.9	2511.0	2494.2	2484.6	2453.2	2426.3	2387.4	2340.1	2302.7	2251.7
15°	2645.7	2637.1	2630.9	2609.8	2593.5	2560.7	2517.9	2477.3	2425.9	2378.3	2330.8
17.5°	2770.1	2777.0	2765.3	2746.1	2695.3	2657.1	2599.6	2544.0	2480.0	2416.2	2359.5
20°	2881.1	2887.4	2869.4	2835.9	2775.1	2736.9	2661.3	2589.6	2515.5	2433.7	2371.3
22.5°	3019.6	3014.6	2990.4	2939.4	2886.7	2816.1	2734.3	2646.9	2554.2	2461.7	2378.8
25°	3255.3	3222.5	3207.7	3144.6	3075.2	2971.5	2859.3	2731.4	2616.1	2493.7	2387.7
27.5°	3385.9	3375.6	3359.1	3315.2	3242.2	3131.3	2999.0	2843.2	2680.5	2526.0	2387.2
30°	3359.7	3361.3	3362.9	3348.8	3302.1	3218.6	3086.9	2919.3	2726.0	2552.2	2391.6
32.5°	3127.8	3156.1	3183.3	3215.4	3228.5	3212.4	3129.9	2978.6	2779.6	2582.1	2389.1
35°	2613.0	2621.5	2709.6	2796.9	2915.4	3007.4	3069.0	3001.9	2834.3	2607.5	2386.1
37.5°	2037.4	2079.5	2140.4	2239.1	2410.1	2563.2	2760.1	2850.7	2796.6	2615.8	2380.7
40°	1736.8	1775.8	1815.5	1916.1	2060.3	2245.8	2469.5	2660.5	2704.9	2589.6	2362.0
42.5°	1504.8	1535.7	1579.8	1655.4	1775.9	1940.2	2154.0	2403.6	2557.1	2513.5	2322.7
45°	1231.6	1251.1	1285.4	1345.5	1432.8	1561.4	1750.0	2022.9	2260.6	2339.3	2229.4
47.5°	1054.2	1054.1	1080.7	1122.2	1185.2	1294.5	1434.0	1647.8	1901.7	2089.6	2080.9
50°	955.7	951.8	972.8	1008.7	1058.6	1131.1	1264.4	1435.1	1679.1	1891.9	1951.1
52.5°	870.9	871.3	884.3	910.8	952.6	1014.5	1114.1	1268.0	1476.4	1694.8	1806.5
55°	759.3	756.1	770.9	788.9	819.3	859.8	931.5	1049.2	1218.4	1433.5	1578.5
57.5°	657.0	665.6	671.5	684.0	709.2	736.3	796.8	883.2	1017.4	1202.0	1355.3
60°	597.1	605.7	610.4	622.8	643.1	666.5	713.3	783.4	896.5	1055.5	1207.5
62.5°	543.5	550.2	551.7	563.0	579.5	602.3	639.1	698.0	787.3	926.4	1075.3
65°	466.2	466.2	469.3	481.0	488.8	509.0	537.1	580.0	651.7	760.0	887.1
67.5°	391.6	395.4	394.6	399.7	406.9	422.7	442.8	478.2	531.3	610.4	712.0
70°	343.0	346.1	345.3	349.2	357.0	367.2	383.5	417.0	455.2	523.1	610.4
72.5°	299.3	300.6	298.6	303.7	308.4	317.3	335.5	353.4	389.1	446.4	518.1
75°	229.2	230.7	232.3	235.4	240.1	244.8	254.1	272.1	295.4	338.3	384.3
77.5°	171.8	168.8	172.6	172.1	174.8	178.4	186.6	196.1	215.3	242.4	278.0
80°	129.4	130.2	130.2	131.0	134.9	137.2	144.2	151.2	166.0	186.3	211.3
82.5°	94.5	96.5	95.3	96.7	99.9	101.6	105.5	111.3	119.9	135.8	153.9
85°	51.4	47.6	49.1	50.7	50.7	51.4	54.6	56.9	61.6	67.8	74.8
87.5°	17.1	18.3	18.9	18.8	19.4	19.3	21.7	21.6	23.4	25.1	27.5
90°	10.9	10.6	10.3	10.0	9.7	9.2	8.7	8.2	7.7	7.2	6.5
92.5°	10.1	10.0	9.9	9.7	9.6	9.2	8.7	8.2	7.7	7.2	6.6
95°	9.5	9.5	9.5	9.5	9.5	9.2	8.7	8.2	7.7	7.2	11.1
97.5°	9.5	9.5	9.5	9.5	9.5	10.9	13.8	16.6	19.4	22.3	29.8
100°	9.5	9.9	10.3	10.7	11.1	18.8	33.8	48.8	63.7	78.7	78.3
102.5°	56.9	63.7	70.6	77.4	84.3	89.1	91.9	94.8	97.6	100.4	100.2
105°	134.4	134.5	134.6	134.7	134.8	134.8	134.8	134.8	134.8	134.8	134.8
107.5°	169.4	169.7	170.0	170.3	170.6	170.7	170.7	170.7	170.7	170.6	170.4
110°	193.6	193.5	193.4	193.3	193.2	193.3	193.6	193.9	194.2	194.5	194.3



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	215.3	215.5	215.6	215.8	215.9	216.2	216.5	216.9	217.3	217.7	217.6
115°	247.9	248.5	249.1	249.7	250.3	250.8	251.2	251.6	252.0	252.4	252.3
117.5°	282.7	282.9	283.2	283.4	283.7	284.1	284.6	285.1	285.7	286.2	285.8
120°	304.0	304.5	305.0	305.5	306.0	306.4	306.6	306.8	307.0	307.2	306.9
122.5°	324.3	324.9	325.4	326.0	326.6	327.0	327.2	327.4	327.6	327.8	327.7
125°	355.1	355.4	355.7	356.0	356.3	356.7	357.1	357.5	357.9	358.3	358.3
127.5°	381.1	381.8	382.6	383.3	384.1	384.6	384.8	385.0	385.2	385.4	385.5
130°	399.9	400.4	400.9	401.4	401.9	402.3	402.6	402.9	403.2	403.5	403.4
132.5°	417.3	417.8	418.3	418.8	419.3	419.6	419.6	419.7	419.8	419.8	420.0
135°	441.1	441.7	442.3	442.9	443.5	443.9	444.1	444.3	444.5	444.7	444.9
137.5°	465.0	465.5	466.0	466.5	467.1	467.3	467.3	467.2	467.2	467.1	467.3
140°	479.1	479.7	480.3	480.9	481.5	481.7	481.5	481.3	481.1	480.9	481.0
142.5°	492.5	493.1	493.7	494.3	494.9	495.2	495.1	495.1	495.0	495.0	494.9
145°	512.1	512.7	513.3	513.9	514.5	514.8	514.7	514.6	514.5	514.4	514.4
147.5°	528.3	529.0	529.8	530.5	531.2	531.5	531.4	531.3	531.1	531.0	530.9
150°	538.8	539.6	540.4	541.2	542.0	542.3	542.1	541.9	541.7	541.5	541.3
152.5°	548.6	549.3	550.0	550.7	551.5	551.7	551.5	551.3	551.1	550.9	550.7
155°	561.4	562.2	563.0	563.8	564.6	564.9	564.6	564.3	564.0	563.7	563.5
157.5°	572.2	573.0	573.8	574.6	575.4	575.6	575.3	575.0	574.7	574.4	574.3
160°	579.1	579.9	580.7	581.5	582.3	582.5	582.1	581.7	581.3	580.9	580.8
162.5°	585.2	586.1	587.0	587.9	588.8	588.9	588.4	587.8	587.2	586.7	586.6
165°	593.5	594.3	595.1	596.0	596.8	596.9	596.3	595.7	595.0	594.4	594.3
167.5°	599.3	600.2	601.1	602.0	603.0	603.0	602.3	601.6	600.9	600.1	600.0
170°	602.6	603.5	604.4	605.3	606.2	606.3	605.5	604.6	603.8	603.0	602.9
172.5°	604.8	605.7	606.6	607.5	608.4	608.5	607.7	607.0	606.3	605.6	605.4
175°	607.6	608.5	609.4	610.3	611.2	611.2	610.4	609.6	608.8	608.0	607.9
177.5°	609.2	609.8	610.5	611.1	611.8	611.8	611.2	610.7	610.1	609.6	609.5
180°	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6
2.5°	1889.6	1885.2	1880.2	1871.5	1860.9	1855.3	1846.5	1840.9	1829.7	1820.3	1810.4
5°	1985.4	1965.2	1946.5	1922.3	1895.8	1878.6	1858.4	1835.8	1812.4	1788.2	1761.7
7.5°	2084.8	2048.9	2009.9	1968.0	1927.0	1889.2	1853.2	1817.8	1784.8	1744.9	1711.1
10°	2151.5	2106.3	2057.9	2001.0	1945.7	1897.4	1848.2	1805.4	1761.7	1714.9	1673.6
12.5°	2218.2	2158.0	2089.7	2027.2	1960.7	1902.3	1844.5	1789.8	1734.9	1683.1	1635.0
15°	2265.3	2212.3	2149.1	2060.3	1985.4	1905.2	1828.8	1757.8	1691.6	1633.9	1573.1
17.5°	2296.3	2228.0	2160.2	2074.9	1976.9	1887.1	1800.5	1719.3	1644.6	1571.5	1512.9
20°	2301.9	2231.8	2160.8	2077.4	1976.9	1874.0	1787.4	1690.0	1609.7	1534.1	1462.4
22.5°	2300.1	2220.5	2143.4	2057.5	1959.4	1864.6	1760.0	1660.7	1573.5	1499.2	1424.3
25°	2282.4	2197.5	2100.8	2014.3	1917.6	1817.1	1711.1	1608.2	1519.3	1434.3	1360.3
27.5°	2267.8	2157.6	2048.1	1947.2	1853.9	1761.7	1660.2	1554.8	1456.3	1370.2	1300.4
30°	2249.7	2128.9	2005.7	1900.5	1804.6	1714.9	1619.1	1516.2	1413.3	1329.1	1254.3
32.5°	2233.5	2092.7	1962.7	1848.1	1746.6	1659.4	1571.0	1473.1	1372.1	1286.7	1211.8
35°	2202.2	2039.2	1890.3	1760.9	1652.6	1562.9	1488.9	1397.7	1304.9	1222.3	1150.6
37.5°	2162.4	1969.1	1809.3	1673.6	1554.8	1460.4	1391.4	1321.4	1232.4	1152.8	1087.9
40°	2131.2	1919.2	1750.0	1611.3	1488.1	1389.9	1326.0	1259.7	1185.7	1111.6	1043.0
42.5°	2091.9	1874.3	1690.2	1540.8	1418.9	1323.2	1256.1	1199.8	1134.5	1065.5	1001.8
45°	2019.7	1792.9	1593.3	1432.8	1309.6	1215.3	1145.9	1103.8	1054.7	989.2	935.4
47.5°	1913.6	1695.1	1488.7	1323.0	1195.9	1108.5	1043.5	1003.1	968.5	919.8	871.0
50°	1819.4	1622.2	1413.3	1248.8	1121.7	1033.6	973.6	937.0	907.4	869.9	828.6
52.5°	1714.0	1530.5	1339.1	1176.5	1050.6	963.8	905.0	872.8	848.1	821.3	780.6
55°	1546.6	1390.7	1212.9	1058.6	942.4	857.5	806.0	778.0	757.7	737.4	712.5
57.5°	1362.1	1240.2	1082.8	941.7	834.7	757.4	709.4	682.1	666.3	655.9	641.2
60°	1232.4	1128.0	992.3	863.7	759.3	690.7	643.9	622.8	609.6	601.0	590.1
62.5°	1112.1	1026.3	900.7	783.3	691.9	627.0	585.3	564.8	552.2	548.0	539.0
65°	934.6	868.4	764.7	667.3	589.3	534.0	498.9	479.4	471.6	466.9	467.7
67.5°	759.9	719.5	636.2	553.1	490.9	444.5	416.4	401.5	397.6	391.3	391.2
70°	653.2	622.8	552.7	480.2	424.8	389.0	364.0	348.4	344.5	341.4	340.7
72.5°	559.1	532.4	471.6	413.5	363.7	332.2	311.7	302.3	295.9	294.0	293.9
75°	420.2	405.4	357.0	311.0	276.7	254.9	240.9	232.3	227.6	226.8	227.6
77.5°	298.7	285.8	255.1	222.5	200.8	184.3	172.4	169.5	164.2	164.3	163.5
80°	224.5	215.9	196.4	170.7	152.8	138.8	132.5	127.1	125.5	123.2	125.5
82.5°	162.8	153.6	140.3	123.9	109.1	100.7	94.5	92.8	91.8	90.7	91.2
85°	80.3	81.1	73.3	60.8	54.6	49.9	46.0	46.0	45.2	44.4	45.2
87.5°	28.6	27.2	24.6	22.6	19.3	17.2	16.5	16.9	15.2	14.8	15.5
90°	5.8	5.1	4.4	3.7	2.9	2.1	1.3	0.5	1.3	2.1	2.9
92.5°	6.0	5.4	4.7	4.7	5.3	5.8	6.4	7.0	6.4	5.8	5.3
95°	14.9	18.7	22.5	24.6	24.9	25.2	25.5	25.8	25.5	25.2	24.9
97.5°	37.4	44.9	52.5	56.0	55.5	54.9	54.4	53.8	54.4	54.9	55.5
100°	77.9	77.5	77.1	76.8	76.5	76.2	75.9	75.5	75.9	76.2	76.5
102.5°	99.9	99.7	99.5	99.2	98.8	98.4	98.0	97.6	98.0	98.4	98.8
105°	134.8	134.8	134.8	134.6	134.2	133.8	133.4	133.0	133.4	133.8	134.2
107.5°	170.2	170.0	169.8	169.7	169.7	169.7	169.7	169.7	169.7	169.7	169.7
110°	194.1	193.9	193.7	193.6	193.6	193.6	193.6	193.6	193.6	193.6	193.6



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	217.5	217.3	217.2	217.0	216.8	216.5	216.3	216.1	216.3	216.5	216.8
115°	252.2	252.1	252.0	251.7	251.2	250.7	250.2	249.7	250.2	250.7	251.2
117.5°	285.4	285.0	284.7	284.5	284.5	284.5	284.5	284.6	284.5	284.5	284.5
120°	306.6	306.3	306.0	305.9	306.0	306.1	306.2	306.3	306.2	306.1	306.0
122.5°	327.5	327.4	327.2	327.0	326.6	326.2	325.8	325.5	325.8	326.2	326.6
125°	358.3	358.3	358.3	357.9	357.2	356.5	355.8	355.1	355.8	356.5	357.2
127.5°	385.6	385.6	385.7	385.5	385.0	384.5	384.0	383.4	384.0	384.5	385.0
130°	403.3	403.2	403.1	402.8	402.3	401.8	401.3	400.8	401.3	401.8	402.3
132.5°	420.3	420.5	420.7	420.5	419.9	419.4	418.8	418.2	418.8	419.4	419.9
135°	445.1	445.3	445.5	445.3	444.7	444.1	443.5	442.9	443.5	444.1	444.7
137.5°	467.5	467.7	467.9	467.7	467.2	466.6	466.1	465.6	466.1	466.6	467.2
140°	481.1	481.2	481.3	481.2	481.0	480.8	480.6	480.4	480.6	480.8	481.0
142.5°	494.7	494.6	494.4	494.3	494.2	494.1	494.0	493.8	494.0	494.1	494.2
145°	514.4	514.4	514.4	514.3	514.1	513.9	513.7	513.5	513.7	513.9	514.1
147.5°	530.8	530.7	530.5	530.5	530.5	530.6	530.6	530.7	530.6	530.6	530.5
150°	541.1	540.9	540.7	540.7	540.9	541.1	541.3	541.5	541.3	541.1	540.9
152.5°	550.5	550.3	550.1	550.2	550.7	551.1	551.6	552.0	551.6	551.1	550.7
155°	563.3	563.1	562.9	563.1	563.7	564.3	564.9	565.5	564.9	564.3	563.7
157.5°	574.3	574.3	574.3	574.4	574.8	575.2	575.5	575.9	575.5	575.2	574.8
160°	580.7	580.6	580.5	580.7	581.3	581.9	582.5	583.1	582.5	581.9	581.3
162.5°	586.5	586.4	586.3	586.5	587.1	587.7	588.3	588.9	588.3	587.7	587.1
165°	594.2	594.1	594.0	594.3	594.9	595.5	596.1	596.7	596.1	595.5	594.9
167.5°	599.9	599.8	599.7	600.0	600.6	601.3	601.9	602.5	601.9	601.3	600.6
170°	602.8	602.7	602.6	602.9	603.6	604.3	605.1	605.8	605.1	604.3	603.6
172.5°	605.2	605.0	604.9	605.1	605.8	606.5	607.2	607.9	607.2	606.5	605.8
175°	607.8	607.7	607.6	607.9	608.5	609.1	609.7	610.3	609.7	609.1	608.5
177.5°	609.4	609.3	609.2	609.4	609.9	610.4	610.9	611.4	610.9	610.4	609.9
180°	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6
2.5°	1804.7	1797.9	1792.3	1779.8	1772.9	1763.6	1756.1	1764.2	1755.5	1759.2	1753.6
5°	1748.5	1726.6	1711.1	1688.4	1669.0	1651.0	1637.8	1635.4	1629.2	1626.1	1616.7
7.5°	1680.8	1653.5	1626.7	1597.1	1572.1	1546.7	1530.5	1517.1	1508.2	1496.5	1488.6
10°	1640.9	1604.3	1573.1	1537.2	1506.0	1478.8	1456.9	1446.0	1435.9	1421.1	1415.6
12.5°	1591.6	1553.7	1515.7	1477.4	1447.4	1417.0	1398.3	1381.8	1374.8	1358.1	1356.4
15°	1532.5	1475.6	1438.2	1399.2	1357.9	1333.0	1317.4	1299.5	1291.7	1280.0	1271.4
17.5°	1462.1	1411.2	1364.5	1324.1	1288.7	1267.7	1248.3	1236.0	1222.6	1215.0	1200.9
20°	1410.9	1362.6	1315.8	1273.0	1245.7	1221.5	1205.9	1194.2	1180.2	1176.3	1162.3
22.5°	1367.9	1314.6	1269.7	1233.7	1203.9	1176.6	1159.8	1151.8	1142.2	1130.2	1127.3
25°	1297.9	1242.6	1204.4	1168.5	1142.0	1117.1	1105.4	1095.2	1085.9	1077.3	1074.2
27.5°	1237.4	1188.0	1142.6	1110.2	1087.1	1064.4	1054.1	1041.8	1034.9	1028.0	1019.6
30°	1195.0	1144.3	1104.6	1073.4	1048.5	1028.2	1017.3	1008.7	1002.5	996.2	991.6
32.5°	1151.4	1104.4	1065.9	1035.4	1010.4	995.1	985.5	979.4	972.5	965.0	959.1
35°	1093.7	1042.2	1004.8	978.3	958.8	947.1	936.2	930.7	923.0	923.0	916.7
37.5°	1028.7	984.2	951.2	927.0	909.5	899.1	887.3	883.5	878.5	875.2	873.1
40°	990.0	948.7	917.5	893.3	874.6	866.0	856.7	850.5	847.3	843.4	841.9
42.5°	950.1	910.6	880.7	858.4	842.2	834.9	826.1	821.8	815.5	810.4	809.5
45°	889.4	851.2	824.0	806.0	792.0	783.4	778.0	768.6	765.5	759.3	758.5
47.5°	831.9	795.3	768.5	753.8	741.5	734.5	725.9	716.5	713.0	709.8	709.5
50°	788.9	755.4	730.4	716.4	704.7	694.6	686.0	679.7	677.4	677.4	679.0
52.5°	745.2	716.7	695.5	678.3	667.3	656.5	648.6	644.8	641.2	645.0	647.8
55°	681.3	652.5	636.9	620.5	609.6	597.1	593.2	591.7	589.3	595.6	598.7
57.5°	613.6	593.4	575.1	558.9	549.1	541.9	536.6	535.7	540.1	543.0	553.1
60°	570.6	547.2	530.9	518.4	506.7	502.0	500.5	498.9	502.0	510.6	523.8
62.5°	523.2	504.2	486.6	477.2	468.6	460.9	460.5	461.5	467.7	477.5	490.8
65°	453.7	437.3	425.6	414.7	407.7	403.0	404.6	407.7	414.7	428.0	442.8
67.5°	383.1	371.8	361.4	352.5	345.8	345.8	347.4	352.0	360.3	375.6	389.1
70°	337.5	325.1	316.5	312.6	307.1	304.0	308.7	316.5	323.5	337.5	349.2
72.5°	292.0	281.4	274.7	272.1	269.7	267.2	268.8	277.2	286.7	300.7	314.3
75°	224.5	220.6	215.9	212.8	210.5	212.0	213.6	221.4	229.2	244.0	259.6
77.5°	163.9	159.8	157.0	156.2	155.0	155.7	160.1	165.9	173.5	184.3	196.1
80°	123.9	122.4	120.8	120.0	120.0	120.8	127.1	131.0	138.0	148.1	157.5
82.5°	90.3	89.3	89.0	88.9	89.5	89.6	93.4	98.5	104.3	111.9	120.0
85°	47.6	46.0	48.3	49.1	47.6	49.9	51.4	54.6	56.9	60.8	64.7
87.5°	16.3	17.7	17.2	18.0	18.1	19.5	19.0	21.6	23.0	24.3	23.8
90°	3.7	4.4	5.1	5.8	6.5	7.2	7.7	8.2	8.7	9.2	9.7
92.5°	4.7	4.7	5.4	6.0	6.6	7.2	7.7	8.2	8.7	9.2	9.6
95°	24.6	22.5	18.7	14.9	11.1	7.2	7.7	8.2	8.7	9.2	9.5
97.5°	56.0	52.5	44.9	37.4	29.8	22.3	19.4	16.6	13.8	10.9	9.5
100°	76.8	77.1	77.5	77.9	78.3	78.7	63.7	48.8	33.8	18.8	11.1
102.5°	99.2	99.5	99.7	99.9	100.2	100.4	97.6	94.8	91.9	89.1	84.3
105°	134.6	134.8	134.8	134.8	134.8	134.8	134.8	134.8	134.8	134.8	134.8
107.5°	169.7	169.8	170.0	170.2	170.4	170.6	170.7	170.7	170.7	170.7	170.6
110°	193.6	193.7	193.9	194.1	194.3	194.5	194.2	193.9	193.6	193.3	193.2



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	217.0	217.2	217.3	217.5	217.6	217.7	217.3	216.9	216.5	216.2	215.9
115°	251.7	252.0	252.1	252.2	252.3	252.4	252.0	251.6	251.2	250.8	250.3
117.5°	284.5	284.7	285.0	285.4	285.8	286.2	285.7	285.1	284.6	284.1	283.7
120°	305.9	306.0	306.3	306.6	306.9	307.2	307.0	306.8	306.6	306.4	306.0
122.5°	327.0	327.2	327.4	327.5	327.7	327.8	327.6	327.4	327.2	327.0	326.6
125°	357.9	358.3	358.3	358.3	358.3	358.3	357.9	357.5	357.1	356.7	356.3
127.5°	385.5	385.7	385.6	385.6	385.5	385.4	385.2	385.0	384.8	384.6	384.1
130°	402.8	403.1	403.2	403.3	403.4	403.5	403.2	402.9	402.6	402.3	401.9
132.5°	420.5	420.7	420.5	420.3	420.0	419.8	419.8	419.7	419.6	419.6	419.3
135°	445.3	445.5	445.3	445.1	444.9	444.7	444.5	444.3	444.1	443.9	443.5
137.5°	467.7	467.9	467.7	467.5	467.3	467.1	467.2	467.2	467.3	467.3	467.1
140°	481.2	481.3	481.2	481.1	481.0	480.9	481.1	481.3	481.5	481.7	481.5
142.5°	494.3	494.4	494.6	494.7	494.9	495.0	495.0	495.1	495.1	495.2	494.9
145°	514.3	514.4	514.4	514.4	514.4	514.4	514.5	514.6	514.7	514.8	514.5
147.5°	530.5	530.5	530.7	530.8	530.9	531.0	531.1	531.3	531.4	531.5	531.2
150°	540.7	540.7	540.9	541.1	541.3	541.5	541.7	541.9	542.1	542.3	542.0
152.5°	550.2	550.1	550.3	550.5	550.7	550.9	551.1	551.3	551.5	551.7	551.5
155°	563.1	562.9	563.1	563.3	563.5	563.7	564.0	564.3	564.6	564.9	564.6
157.5°	574.4	574.3	574.3	574.3	574.3	574.4	574.7	575.0	575.3	575.6	575.4
160°	580.7	580.5	580.6	580.7	580.8	580.9	581.3	581.7	582.1	582.5	582.3
162.5°	586.5	586.3	586.4	586.5	586.6	586.7	587.2	587.8	588.4	588.9	588.8
165°	594.3	594.0	594.1	594.2	594.3	594.4	595.0	595.7	596.3	596.9	596.8
167.5°	600.0	599.7	599.8	599.9	600.0	600.1	600.9	601.6	602.3	603.0	603.0
170°	602.9	602.6	602.7	602.8	602.9	603.0	603.8	604.6	605.5	606.3	606.2
172.5°	605.1	604.9	605.0	605.2	605.4	605.6	606.3	607.0	607.7	608.5	608.4
175°	607.9	607.6	607.7	607.8	607.9	608.0	608.8	609.6	610.4	611.2	611.2
177.5°	609.4	609.2	609.3	609.4	609.5	609.6	610.1	610.7	611.2	611.8	611.8
180°	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6
2.5°	1749.9	1754.2	1750.5	1755.5	1750.5	1754.2	1749.9	1753.6	1759.2	1755.5	1764.2
5°	1612.8	1605.8	1610.5	1607.4	1610.5	1605.8	1612.8	1616.7	1626.1	1629.2	1635.4
7.5°	1486.2	1479.5	1471.9	1468.3	1471.9	1479.5	1486.2	1488.6	1496.5	1508.2	1517.1
10°	1407.0	1398.5	1397.7	1392.2	1397.7	1398.5	1407.0	1415.6	1421.1	1435.9	1446.0
12.5°	1349.0	1341.1	1332.2	1329.9	1332.2	1341.1	1349.0	1356.4	1358.1	1374.8	1381.8
15°	1266.7	1260.5	1255.0	1259.7	1255.0	1260.5	1266.7	1271.4	1280.0	1291.7	1299.5
17.5°	1198.3	1193.1	1192.2	1186.4	1192.2	1193.1	1198.3	1200.9	1215.0	1222.6	1236.0
20°	1155.3	1151.4	1152.9	1142.8	1152.9	1151.4	1155.3	1162.3	1176.3	1180.2	1194.2
22.5°	1121.0	1113.3	1112.4	1110.4	1112.4	1113.3	1121.0	1127.3	1130.2	1142.2	1151.8
25°	1067.2	1063.3	1059.4	1063.3	1059.4	1063.3	1067.2	1074.2	1077.3	1085.9	1095.2
27.5°	1020.2	1015.6	1014.5	1014.9	1014.5	1015.6	1020.2	1019.6	1028.0	1034.9	1041.8
30°	991.6	983.8	984.5	983.8	984.5	983.8	991.6	991.6	996.2	1002.5	1008.7
32.5°	960.4	955.1	954.0	952.6	954.0	955.1	960.4	959.1	965.0	972.5	979.4
35°	914.4	914.4	910.5	910.5	910.5	914.4	914.4	916.7	923.0	923.0	930.7
37.5°	871.2	870.4	868.1	868.4	868.1	870.4	871.2	873.1	875.2	878.5	883.5
40°	838.8	838.0	835.6	831.0	835.6	838.0	838.8	841.9	843.4	847.3	850.5
42.5°	807.6	804.9	803.8	802.3	803.8	804.9	807.6	809.5	810.4	815.5	821.8
45°	758.5	758.5	756.9	756.1	756.9	758.5	758.5	758.5	759.3	765.5	768.6
47.5°	710.8	712.2	715.1	714.7	715.1	712.2	710.8	709.5	709.8	713.0	716.5
50°	682.1	682.9	685.2	686.0	685.2	682.9	682.1	679.0	677.4	677.4	679.7
52.5°	650.3	654.8	657.8	657.3	657.8	654.8	650.3	647.8	645.0	641.2	644.8
55°	605.7	611.1	616.6	617.4	616.6	611.1	605.7	598.7	595.6	589.3	591.7
57.5°	561.6	569.2	575.0	576.8	575.0	569.2	561.6	553.1	543.0	540.1	535.7
60°	531.6	541.8	548.8	551.9	548.8	541.8	531.6	523.8	510.6	502.0	498.9
62.5°	502.9	514.3	521.3	522.0	521.3	514.3	502.9	490.8	477.5	467.7	461.5
65°	456.0	467.7	473.9	478.6	473.9	467.7	456.0	442.8	428.0	414.7	407.7
67.5°	405.5	417.2	424.1	427.8	424.1	417.2	405.5	389.1	375.6	360.3	352.0
70°	368.7	380.4	389.8	392.9	389.8	380.4	368.7	349.2	337.5	323.5	316.5
72.5°	332.5	343.0	350.5	354.2	350.5	343.0	332.5	314.3	300.7	286.7	277.2
75°	269.7	283.7	290.8	294.7	290.8	283.7	269.7	259.6	244.0	229.2	221.4
77.5°	208.0	220.8	225.0	227.0	225.0	220.8	208.0	196.1	184.3	173.5	165.9
80°	166.8	174.6	180.1	180.8	180.1	174.6	166.8	157.5	148.1	138.0	131.0
82.5°	128.2	134.7	136.4	138.4	136.4	134.7	128.2	120.0	111.9	104.3	98.5
85°	70.2	73.3	74.1	73.3	74.1	73.3	70.2	64.7	60.8	56.9	54.6
87.5°	25.1	24.5	24.6	25.9	24.6	24.5	25.1	23.8	24.3	23.0	21.6
90°	10.0	10.3	10.6	10.9	10.6	10.3	10.0	9.7	9.2	8.7	8.2
92.5°	9.7	9.9	10.0	10.1	10.0	9.9	9.7	9.6	9.2	8.7	8.2
95°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.2	8.7	8.2
97.5°	9.5	9.5	9.5	9.5	9.5	9.5	9.5	9.5	10.9	13.8	16.6
100°	10.7	10.3	9.9	9.5	9.9	10.3	10.7	11.1	18.8	33.8	48.8
102.5°	77.4	70.6	63.7	56.9	63.7	70.6	77.4	84.3	89.1	91.9	94.8
105°	134.7	134.6	134.5	134.4	134.5	134.6	134.7	134.8	134.8	134.8	134.8
107.5°	170.3	170.0	169.7	169.4	169.7	170.0	170.3	170.6	170.7	170.7	170.7
110°	193.3	193.4	193.5	193.6	193.5	193.4	193.3	193.2	193.3	193.6	193.9



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	215.8	215.6	215.5	215.3	215.5	215.6	215.8	215.9	216.2	216.5	216.9
115°	249.7	249.1	248.5	247.9	248.5	249.1	249.7	250.3	250.8	251.2	251.6
117.5°	283.4	283.2	282.9	282.7	282.9	283.2	283.4	283.7	284.1	284.6	285.1
120°	305.5	305.0	304.5	304.0	304.5	305.0	305.5	306.0	306.4	306.6	306.8
122.5°	326.0	325.4	324.9	324.3	324.9	325.4	326.0	326.6	327.0	327.2	327.4
125°	356.0	355.7	355.4	355.1	355.4	355.7	356.0	356.3	356.7	357.1	357.5
127.5°	383.3	382.6	381.8	381.1	381.8	382.6	383.3	384.1	384.6	384.8	385.0
130°	401.4	400.9	400.4	399.9	400.4	400.9	401.4	401.9	402.3	402.6	402.9
132.5°	418.8	418.3	417.8	417.3	417.8	418.3	418.8	419.3	419.6	419.6	419.7
135°	442.9	442.3	441.7	441.1	441.7	442.3	442.9	443.5	443.9	444.1	444.3
137.5°	466.5	466.0	465.5	465.0	465.5	466.0	466.5	467.1	467.3	467.3	467.2
140°	480.9	480.3	479.7	479.1	479.7	480.3	480.9	481.5	481.7	481.5	481.3
142.5°	494.3	493.7	493.1	492.5	493.1	493.7	494.3	494.9	495.2	495.1	495.1
145°	513.9	513.3	512.7	512.1	512.7	513.3	513.9	514.5	514.8	514.7	514.6
147.5°	530.5	529.8	529.0	528.3	529.0	529.8	530.5	531.2	531.5	531.4	531.3
150°	541.2	540.4	539.6	538.8	539.6	540.4	541.2	542.0	542.3	542.1	541.9
152.5°	550.7	550.0	549.3	548.6	549.3	550.0	550.7	551.5	551.7	551.5	551.3
155°	563.8	563.0	562.2	561.4	562.2	563.0	563.8	564.6	564.9	564.6	564.3
157.5°	574.6	573.8	573.0	572.2	573.0	573.8	574.6	575.4	575.6	575.3	575.0
160°	581.5	580.7	579.9	579.1	579.9	580.7	581.5	582.3	582.5	582.1	581.7
162.5°	587.9	587.0	586.1	585.2	586.1	587.0	587.9	588.8	588.9	588.4	587.8
165°	596.0	595.1	594.3	593.5	594.3	595.1	596.0	596.8	596.9	596.3	595.7
167.5°	602.0	601.1	600.2	599.3	600.2	601.1	602.0	603.0	603.0	602.3	601.6
170°	605.3	604.4	603.5	602.6	603.5	604.4	605.3	606.2	606.3	605.5	604.6
172.5°	607.5	606.6	605.7	604.8	605.7	606.6	607.5	608.4	608.5	607.7	607.0
175°	610.3	609.4	608.5	607.6	608.5	609.4	610.3	611.2	611.2	610.4	609.6
177.5°	611.1	610.5	609.8	609.2	609.8	610.5	611.1	611.8	611.8	611.2	610.7
180°	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6
2.5°	1756.1	1763.6	1772.9	1779.8	1792.3	1797.9	1804.7	1810.4	1820.3	1829.7	1840.9
5°	1637.8	1651.0	1669.0	1688.4	1711.1	1726.6	1748.5	1761.7	1788.2	1812.4	1835.8
7.5°	1530.5	1546.7	1572.1	1597.1	1626.7	1653.5	1680.8	1711.1	1744.9	1784.8	1817.8
10°	1456.9	1478.8	1506.0	1537.2	1573.1	1604.3	1640.9	1673.6	1714.9	1761.7	1805.4
12.5°	1398.3	1417.0	1447.4	1477.4	1515.7	1553.7	1591.6	1635.0	1683.1	1734.9	1789.8
15°	1317.4	1333.0	1357.9	1399.2	1438.2	1475.6	1532.5	1573.1	1633.9	1691.6	1757.8
17.5°	1248.3	1267.7	1288.7	1324.1	1364.5	1411.2	1462.1	1512.9	1571.5	1644.6	1719.3
20°	1205.9	1221.5	1245.7	1273.0	1315.8	1362.6	1410.9	1462.4	1534.1	1609.7	1690.0
22.5°	1159.8	1176.6	1203.9	1233.7	1269.7	1314.6	1367.9	1424.3	1499.2	1573.5	1660.7
25°	1105.4	1117.1	1142.0	1168.5	1204.4	1242.6	1297.9	1360.3	1434.3	1519.3	1608.2
27.5°	1054.1	1064.4	1087.1	1110.2	1142.6	1188.0	1237.4	1300.4	1370.2	1456.3	1554.8
30°	1017.3	1028.2	1048.5	1073.4	1104.6	1144.3	1195.0	1254.3	1329.1	1413.3	1516.2
32.5°	985.5	995.1	1010.4	1035.4	1065.9	1104.4	1151.4	1211.8	1286.7	1372.1	1473.1
35°	936.2	947.1	958.8	978.3	1004.8	1042.2	1093.7	1150.6	1222.3	1304.9	1397.7
37.5°	887.3	899.1	909.5	927.0	951.2	984.2	1028.7	1087.9	1152.8	1232.4	1321.4
40°	856.7	866.0	874.6	893.3	917.5	948.7	990.0	1043.0	1111.6	1185.7	1259.7
42.5°	826.1	834.9	842.2	858.4	880.7	910.6	950.1	1001.8	1065.5	1134.5	1199.8
45°	778.0	783.4	792.0	806.0	824.0	851.2	889.4	935.4	989.2	1054.7	1103.8
47.5°	725.9	734.5	741.5	753.8	768.5	795.3	831.9	871.0	919.8	968.5	1003.1
50°	686.0	694.6	704.7	716.4	730.4	755.4	788.9	828.6	869.9	907.4	937.0
52.5°	648.6	656.5	667.3	678.3	695.5	716.7	745.2	780.6	821.3	848.1	872.8
55°	593.2	597.1	609.6	620.5	636.9	652.5	681.3	712.5	737.4	757.7	778.0
57.5°	536.6	541.9	549.1	558.9	575.1	593.4	613.6	641.2	655.9	666.3	682.1
60°	500.5	502.0	506.7	518.4	530.9	547.2	570.6	590.1	601.0	609.6	622.8
62.5°	460.5	460.9	468.6	477.2	486.6	504.2	523.2	539.0	548.0	552.2	564.8
65°	404.6	403.0	407.7	414.7	425.6	437.3	453.7	467.7	466.9	471.6	479.4
67.5°	347.4	345.8	345.8	352.5	361.4	371.8	383.1	391.2	391.3	397.6	401.5
70°	308.7	304.0	307.1	312.6	316.5	325.1	337.5	340.7	341.4	344.5	348.4
72.5°	268.8	267.2	269.7	272.1	274.7	281.4	292.0	293.9	294.0	295.9	302.3
75°	213.6	212.0	210.5	212.8	215.9	220.6	224.5	227.6	226.8	227.6	232.3
77.5°	160.1	155.7	155.0	156.2	157.0	159.8	163.9	163.5	164.3	164.2	169.5
80°	127.1	120.8	120.0	120.0	120.8	122.4	123.9	125.5	123.2	125.5	127.1
82.5°	93.4	89.6	89.5	88.9	89.0	89.3	90.3	91.2	90.7	91.8	92.8
85°	51.4	49.9	47.6	49.1	48.3	46.0	47.6	45.2	44.4	45.2	46.0
87.5°	19.0	19.5	18.1	18.0	17.2	17.7	16.3	15.5	14.8	15.2	16.9
90°	7.7	7.2	6.5	5.8	5.1	4.4	3.7	2.9	2.1	1.3	0.5
92.5°	7.7	7.2	6.6	6.0	5.4	4.7	4.7	5.3	5.8	6.4	7.0
95°	7.7	7.2	11.1	14.9	18.7	22.5	24.6	24.9	25.2	25.5	25.8
97.5°	19.4	22.3	29.8	37.4	44.9	52.5	56.0	55.5	54.9	54.4	53.8
100°	63.7	78.7	78.3	77.9	77.5	77.1	76.8	76.5	76.2	75.9	75.5
102.5°	97.6	100.4	100.2	99.9	99.7	99.5	99.2	98.8	98.4	98.0	97.6
105°	134.8	134.8	134.8	134.8	134.8	134.8	134.6	134.2	133.8	133.4	133.0
107.5°	170.7	170.6	170.4	170.2	170.0	169.8	169.7	169.7	169.7	169.7	169.7
110°	194.2	194.5	194.3	194.1	193.9	193.7	193.6	193.6	193.6	193.6	193.6



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	217.3	217.7	217.6	217.5	217.3	217.2	217.0	216.8	216.5	216.3	216.1
115°	252.0	252.4	252.3	252.2	252.1	252.0	251.7	251.2	250.7	250.2	249.7
117.5°	285.7	286.2	285.8	285.4	285.0	284.7	284.5	284.5	284.5	284.5	284.6
120°	307.0	307.2	306.9	306.6	306.3	306.0	305.9	306.0	306.1	306.2	306.3
122.5°	327.6	327.8	327.7	327.5	327.4	327.2	327.0	326.6	326.2	325.8	325.5
125°	357.9	358.3	358.3	358.3	358.3	358.3	357.9	357.2	356.5	355.8	355.1
127.5°	385.2	385.4	385.5	385.6	385.6	385.7	385.5	385.0	384.5	384.0	383.4
130°	403.2	403.5	403.4	403.3	403.2	403.1	402.8	402.3	401.8	401.3	400.8
132.5°	419.8	419.8	420.0	420.3	420.5	420.7	420.5	419.9	419.4	418.8	418.2
135°	444.5	444.7	444.9	445.1	445.3	445.5	445.3	444.7	444.1	443.5	442.9
137.5°	467.2	467.1	467.3	467.5	467.7	467.9	467.7	467.2	466.6	466.1	465.6
140°	481.1	480.9	481.0	481.1	481.2	481.3	481.2	481.0	480.8	480.6	480.4
142.5°	495.0	495.0	494.9	494.7	494.6	494.4	494.3	494.2	494.1	494.0	493.8
145°	514.5	514.4	514.4	514.4	514.4	514.4	514.3	514.1	513.9	513.7	513.5
147.5°	531.1	531.0	530.9	530.8	530.7	530.5	530.5	530.5	530.6	530.6	530.7
150°	541.7	541.5	541.3	541.1	540.9	540.7	540.7	540.9	541.1	541.3	541.5
152.5°	551.1	550.9	550.7	550.5	550.3	550.1	550.2	550.7	551.1	551.6	552.0
155°	564.0	563.7	563.5	563.3	563.1	562.9	563.1	563.7	564.3	564.9	565.5
157.5°	574.7	574.4	574.3	574.3	574.3	574.3	574.4	574.8	575.2	575.5	575.9
160°	581.3	580.9	580.8	580.7	580.6	580.5	580.7	581.3	581.9	582.5	583.1
162.5°	587.2	586.7	586.6	586.5	586.4	586.3	586.5	587.1	587.7	588.3	588.9
165°	595.0	594.4	594.3	594.2	594.1	594.0	594.3	594.9	595.5	596.1	596.7
167.5°	600.9	600.1	600.0	599.9	599.8	599.7	600.0	600.6	601.3	601.9	602.5
170°	603.8	603.0	602.9	602.8	602.7	602.6	602.9	603.6	604.3	605.1	605.8
172.5°	606.3	605.6	605.4	605.2	605.0	604.9	605.1	605.8	606.5	607.2	607.9
175°	608.8	608.0	607.9	607.8	607.7	607.6	607.9	608.5	609.1	609.7	610.3
177.5°	610.1	609.6	609.5	609.4	609.3	609.2	609.4	609.9	610.4	610.9	611.4
180°	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6
2.5°	1846.5	1855.3	1860.9	1871.5	1880.2	1885.2	1889.6	1893.3	1897.7	1901.4	1912.0
5°	1858.4	1878.6	1895.8	1922.3	1946.5	1965.2	1985.4	2003.4	2018.2	2039.2	2055.6
7.5°	1853.2	1889.2	1927.0	1968.0	2009.9	2048.9	2084.8	2118.3	2148.7	2185.5	2217.7
10°	1848.2	1897.4	1945.7	2001.0	2057.9	2106.3	2151.5	2197.5	2231.0	2277.8	2317.5
12.5°	1844.5	1902.3	1960.7	2027.2	2089.7	2158.0	2218.2	2251.7	2302.7	2340.1	2387.4
15°	1828.8	1905.2	1985.4	2060.3	2149.1	2212.3	2265.3	2330.8	2378.3	2425.9	2477.3
17.5°	1800.5	1887.1	1976.9	2074.9	2160.2	2228.0	2296.3	2359.5	2416.2	2480.0	2544.0
20°	1787.4	1874.0	1976.9	2077.4	2160.8	2231.8	2301.9	2371.3	2433.7	2515.5	2589.6
22.5°	1760.0	1864.6	1959.4	2057.5	2143.4	2220.5	2300.1	2378.8	2461.7	2554.2	2646.9
25°	1711.1	1817.1	1917.6	2014.3	2100.8	2197.5	2282.4	2387.7	2493.7	2616.1	2731.4
27.5°	1660.2	1761.7	1853.9	1947.2	2048.1	2157.6	2267.8	2387.2	2526.0	2680.5	2843.2
30°	1619.1	1714.9	1804.6	1900.5	2005.7	2128.9	2249.7	2391.6	2552.2	2726.0	2919.3
32.5°	1571.0	1659.4	1746.6	1848.1	1962.7	2092.7	2233.5	2389.1	2582.1	2779.6	2978.6
35°	1488.9	1562.9	1652.6	1760.9	1890.3	2039.2	2202.2	2386.1	2607.5	2834.3	3001.9
37.5°	1391.4	1460.4	1554.8	1673.6	1809.3	1969.1	2162.4	2380.7	2615.8	2796.6	2850.7
40°	1326.0	1389.9	1488.1	1611.3	1750.0	1919.2	2131.2	2362.0	2589.6	2704.9	2660.5
42.5°	1256.1	1323.2	1418.9	1540.8	1690.2	1874.3	2091.9	2322.7	2513.5	2557.1	2403.6
45°	1145.9	1215.3	1309.6	1432.8	1593.3	1792.9	2019.7	2229.4	2339.3	2260.6	2022.9
47.5°	1043.5	1108.5	1195.9	1323.0	1488.7	1695.1	1913.6	2080.9	2089.6	1901.7	1647.8
50°	973.6	1033.6	1121.7	1248.8	1413.3	1622.2	1819.4	1951.1	1891.9	1679.1	1435.1
52.5°	905.0	963.8	1050.6	1176.5	1339.1	1530.5	1714.0	1806.5	1694.8	1476.4	1268.0
55°	806.0	857.5	942.4	1058.6	1212.9	1390.7	1546.6	1578.5	1433.5	1218.4	1049.2
57.5°	709.4	757.4	834.7	941.7	1082.8	1240.2	1362.1	1355.3	1202.0	1017.4	883.2
60°	643.9	690.7	759.3	863.7	992.3	1128.0	1232.4	1207.5	1055.5	896.5	783.4
62.5°	585.3	627.0	691.9	783.3	900.7	1026.3	1112.1	1075.3	926.4	787.3	698.0
65°	498.9	534.0	589.3	667.3	764.7	868.4	934.6	887.1	760.0	651.7	580.0
67.5°	416.4	444.5	490.9	553.1	636.2	719.5	759.9	712.0	610.4	531.3	478.2
70°	364.0	389.0	424.8	480.2	552.7	622.8	653.2	610.4	523.1	455.2	417.0
72.5°	311.7	332.2	363.7	413.5	471.6	532.4	559.1	518.1	446.4	389.1	353.4
75°	240.9	254.9	276.7	311.0	357.0	405.4	420.2	384.3	338.3	295.4	272.1
77.5°	172.4	184.3	200.8	222.5	255.1	285.8	298.7	278.0	242.4	215.3	196.1
80°	132.5	138.8	152.8	170.7	196.4	215.9	224.5	211.3	186.3	166.0	151.2
82.5°	94.5	100.7	109.1	123.9	140.3	153.6	162.8	153.9	135.8	119.9	111.3
85°	46.0	49.9	54.6	60.8	73.3	81.1	80.3	74.8	67.8	61.6	56.9
87.5°	16.5	17.2	19.3	22.6	24.6	27.2	28.6	27.5	25.1	23.4	21.6
90°	1.3	2.1	2.9	3.7	4.4	5.1	5.8	6.5	7.2	7.7	8.2
92.5°	6.4	5.8	5.3	4.7	4.7	5.4	6.0	6.6	7.2	7.7	8.2
95°	25.5	25.2	24.9	24.6	22.5	18.7	14.9	11.1	7.2	7.7	8.2
97.5°	54.4	54.9	55.5	56.0	52.5	44.9	37.4	29.8	22.3	19.4	16.6
100°	75.9	76.2	76.5	76.8	77.1	77.5	77.9	78.3	78.7	63.7	48.8
102.5°	98.0	98.4	98.8	99.2	99.5	99.7	99.9	100.2	100.4	97.6	94.8
105°	133.4	133.8	134.2	134.6	134.8	134.8	134.8	134.8	134.8	134.8	134.8
107.5°	169.7	169.7	169.7	169.7	169.8	170.0	170.2	170.4	170.6	170.7	170.7
110°	193.6	193.6	193.6	193.6	193.7	193.9	194.1	194.3	194.5	194.2	193.9



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	216.3	216.5	216.8	217.0	217.2	217.3	217.5	217.6	217.7	217.3	216.9
115°	250.2	250.7	251.2	251.7	252.0	252.1	252.2	252.3	252.4	252.0	251.6
117.5°	284.5	284.5	284.5	284.5	284.7	285.0	285.4	285.8	286.2	285.7	285.1
120°	306.2	306.1	306.0	305.9	306.0	306.3	306.6	306.9	307.2	307.0	306.8
122.5°	325.8	326.2	326.6	327.0	327.2	327.4	327.5	327.7	327.8	327.6	327.4
125°	355.8	356.5	357.2	357.9	358.3	358.3	358.3	358.3	358.3	357.9	357.5
127.5°	384.0	384.5	385.0	385.5	385.7	385.6	385.6	385.5	385.4	385.2	385.0
130°	401.3	401.8	402.3	402.8	403.1	403.2	403.3	403.4	403.5	403.2	402.9
132.5°	418.8	419.4	419.9	420.5	420.7	420.5	420.3	420.0	419.8	419.8	419.7
135°	443.5	444.1	444.7	445.3	445.5	445.3	445.1	444.9	444.7	444.5	444.3
137.5°	466.1	466.6	467.2	467.7	467.9	467.7	467.5	467.3	467.1	467.2	467.2
140°	480.6	480.8	481.0	481.2	481.3	481.2	481.1	481.0	480.9	481.1	481.3
142.5°	494.0	494.1	494.2	494.3	494.4	494.6	494.7	494.9	495.0	495.0	495.1
145°	513.7	513.9	514.1	514.3	514.4	514.4	514.4	514.4	514.4	514.5	514.6
147.5°	530.6	530.6	530.5	530.5	530.5	530.7	530.8	530.9	531.0	531.1	531.3
150°	541.3	541.1	540.9	540.7	540.7	540.9	541.1	541.3	541.5	541.7	541.9
152.5°	551.6	551.1	550.7	550.2	550.1	550.3	550.5	550.7	550.9	551.1	551.3
155°	564.9	564.3	563.7	563.1	562.9	563.1	563.3	563.5	563.7	564.0	564.3
157.5°	575.5	575.2	574.8	574.4	574.3	574.3	574.3	574.3	574.4	574.7	575.0
160°	582.5	581.9	581.3	580.7	580.5	580.6	580.7	580.8	580.9	581.3	581.7
162.5°	588.3	587.7	587.1	586.5	586.3	586.4	586.5	586.6	586.7	587.2	587.8
165°	596.1	595.5	594.9	594.3	594.0	594.1	594.2	594.3	594.4	595.0	595.7
167.5°	601.9	601.3	600.6	600.0	599.7	599.8	599.9	600.0	600.1	600.9	601.6
170°	605.1	604.3	603.6	602.9	602.6	602.7	602.8	602.9	603.0	603.8	604.6
172.5°	607.2	606.5	605.8	605.1	604.9	605.0	605.2	605.4	605.6	606.3	607.0
175°	609.7	609.1	608.5	607.9	607.6	607.7	607.8	607.9	608.0	608.8	609.6
177.5°	610.9	610.4	609.9	609.4	609.2	609.3	609.4	609.5	609.6	610.1	610.7
180°	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3	610.3



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6	1836.6
2.5°	1920.7	1925.7	1936.3	1932.6	1937.6	1940.1	1942.6
5°	2075.9	2100.8	2111.7	2110.2	2126.5	2122.6	2118.7
7.5°	2251.1	2277.3	2292.0	2310.2	2320.8	2321.6	2330.8
10°	2350.3	2384.6	2398.6	2418.1	2430.6	2437.6	2436.8
12.5°	2426.3	2453.2	2484.6	2494.2	2511.0	2519.9	2516.6
15°	2517.9	2560.7	2593.5	2609.8	2630.9	2637.1	2645.7
17.5°	2599.6	2657.1	2695.3	2746.1	2765.3	2777.0	2770.1
20°	2661.3	2736.9	2775.1	2835.9	2869.4	2887.4	2881.1
22.5°	2734.3	2816.1	2886.7	2939.4	2990.4	3014.6	3019.6
25°	2859.3	2971.5	3075.2	3144.6	3207.7	3222.5	3255.3
27.5°	2999.0	3131.3	3242.2	3315.2	3359.1	3375.6	3385.9
30°	3086.9	3218.6	3302.1	3348.8	3362.9	3361.3	3359.7
32.5°	3129.9	3212.4	3228.5	3215.4	3183.3	3156.1	3127.8
35°	3069.0	3007.4	2915.4	2796.9	2709.6	2621.5	2613.0
37.5°	2760.1	2563.2	2410.1	2239.1	2140.4	2079.5	2037.4
40°	2469.5	2245.8	2060.3	1916.1	1815.5	1775.8	1736.8
42.5°	2154.0	1940.2	1775.9	1655.4	1579.8	1535.7	1504.8
45°	1750.0	1561.4	1432.8	1345.5	1285.4	1251.1	1231.6
47.5°	1434.0	1294.5	1185.2	1122.2	1080.7	1054.1	1054.2
50°	1264.4	1131.1	1058.6	1008.7	972.8	951.8	955.7
52.5°	1114.1	1014.5	952.6	910.8	884.3	871.3	870.9
55°	931.5	859.8	819.3	788.9	770.9	756.1	759.3
57.5°	796.8	736.3	709.2	684.0	671.5	665.6	657.0
60°	713.3	666.5	643.1	622.8	610.4	605.7	597.1
62.5°	639.1	602.3	579.5	563.0	551.7	550.2	543.5
65°	537.1	509.0	488.8	481.0	469.3	466.2	466.2
67.5°	442.8	422.7	406.9	399.7	394.6	395.4	391.6
70°	383.5	367.2	357.0	349.2	345.3	346.1	343.0
72.5°	335.5	317.3	308.4	303.7	298.6	300.6	299.3
75°	254.1	244.8	240.1	235.4	232.3	230.7	229.2
77.5°	186.6	178.4	174.8	172.1	172.6	168.8	171.8
80°	144.2	137.2	134.9	131.0	130.2	130.2	129.4
82.5°	105.5	101.6	99.9	96.7	95.3	96.5	94.5
85°	54.6	51.4	50.7	50.7	49.1	47.6	51.4
87.5°	21.7	19.3	19.4	18.8	18.9	18.3	17.1
90°	8.7	9.2	9.7	10.0	10.3	10.6	10.9
92.5°	8.7	9.2	9.6	9.7	9.9	10.0	10.1
95°	8.7	9.2	9.5	9.5	9.5	9.5	9.5
97.5°	13.8	10.9	9.5	9.5	9.5	9.5	9.5
100°	33.8	18.8	11.1	10.7	10.3	9.9	9.5
102.5°	91.9	89.1	84.3	77.4	70.6	63.7	56.9
105°	134.8	134.8	134.8	134.7	134.6	134.5	134.4
107.5°	170.7	170.7	170.6	170.3	170.0	169.7	169.4
110°	193.6	193.3	193.2	193.3	193.4	193.5	193.6



TEST NUMBER: P333460

CATALOG NUMBER: S125DIW-S1270D470U835-4F0-1E-UDD-A

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	216.5	216.2	215.9	215.8	215.6	215.5	215.3
115°	251.2	250.8	250.3	249.7	249.1	248.5	247.9
117.5°	284.6	284.1	283.7	283.4	283.2	282.9	282.7
120°	306.6	306.4	306.0	305.5	305.0	304.5	304.0
122.5°	327.2	327.0	326.6	326.0	325.4	324.9	324.3
125°	357.1	356.7	356.3	356.0	355.7	355.4	355.1
127.5°	384.8	384.6	384.1	383.3	382.6	381.8	381.1
130°	402.6	402.3	401.9	401.4	400.9	400.4	399.9
132.5°	419.6	419.6	419.3	418.8	418.3	417.8	417.3
135°	444.1	443.9	443.5	442.9	442.3	441.7	441.1
137.5°	467.3	467.3	467.1	466.5	466.0	465.5	465.0
140°	481.5	481.7	481.5	480.9	480.3	479.7	479.1
142.5°	495.1	495.2	494.9	494.3	493.7	493.1	492.5
145°	514.7	514.8	514.5	513.9	513.3	512.7	512.1
147.5°	531.4	531.5	531.2	530.5	529.8	529.0	528.3
150°	542.1	542.3	542.0	541.2	540.4	539.6	538.8
152.5°	551.5	551.7	551.5	550.7	550.0	549.3	548.6
155°	564.6	564.9	564.6	563.8	563.0	562.2	561.4
157.5°	575.3	575.6	575.4	574.6	573.8	573.0	572.2
160°	582.1	582.5	582.3	581.5	580.7	579.9	579.1
162.5°	588.4	588.9	588.8	587.9	587.0	586.1	585.2
165°	596.3	596.9	596.8	596.0	595.1	594.3	593.5
167.5°	602.3	603.0	603.0	602.0	601.1	600.2	599.3
170°	605.5	606.3	606.2	605.3	604.4	603.5	602.6
172.5°	607.7	608.5	608.4	607.5	606.6	605.7	604.8
175°	610.4	611.2	611.2	610.3	609.4	608.5	607.6
177.5°	611.2	611.8	611.8	611.1	610.5	609.8	609.2
180°	610.3	610.3	610.3	610.3	610.3	610.3	610.3

(END OF REPORT)