

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P333737-935

Luminaire Tested: **S125RDIW-S1270D1560U935-4F0-1E-UDD-A1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-79-08
Report Number: P333737-935
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-11,
Test Lab: INNOVATION CENTER
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: NEO-RAY
Catalog Number: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1
Description: DEFINE 5 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE
DOWNLIGHT 1270 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING
UPLIGHT 1560 LUMENS PER FOOT, FLUSH SATIN WHITE DIFFUSER
Light Source: -
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8895.7 lumens
Efficiency: N/A
Efficacy: 107.3 lumens/watt
Spacing Criteria (0/90/45): 1.4 / 1.22 / 1.47
Luminous Opening: Rectangular (W 4' x L: 0.42' x H: 0')
CIE Type: General Diffuse


Input Watts (W): 82.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

Luminous Intensity Polar Plot





TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20									
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																														
0	107	107	107	107	98	98	98	98	82	82	82	67	67	67	54	54	54	48									48																			
1	98	94	90	86	90	86	83	80	73	70	68	60	58	57	48	47	46	41									41																			
2	89	82	76	71	82	76	71	66	64	60	57	53	50	48	43	41	40	35									35																			
3	82	72	65	60	75	67	61	56	57	52	48	47	44	41	38	36	34	30									30																			
4	75	64	57	51	69	60	53	48	51	45	41	42	38	35	34	32	30	26									26																			
5	69	57	49	44	63	53	46	41	45	40	36	38	34	31	31	28	26	23									23																			
6	63	52	44	38	58	48	41	36	41	35	31	34	30	27	28	25	23	20									20																			
7	59	47	39	33	54	43	36	31	37	32	28	31	27	24	26	23	20	18									18																			
8	54	42	35	29	50	39	33	28	34	28	25	29	25	21	24	21	18	16									16																			
9	51	39	31	26	47	36	29	25	31	26	22	26	22	19	22	19	17	14									14																			
10	47	35	28	24	44	33	27	22	29	23	20	24	20	17	20	17	15	13									13																			

AVERAGE LUMINANCE (cd/sqm):

	0°	90°	180°	270°
0°	10559	10559	10559	10559
5°	12149	10573	9337	10573
10°	13935	10519	8239	10519
15°	15051	10411	7324	10411
20°	16597	10287	6763	10287
25°	19207	10120	6274	10120
30°	20901	9945	5956	9945
35°	17631	9742	5662	9742
40°	12312	9377	5409	9377
45°	9134	8882	5161	8882
50°	7283	8368	4950	8368
55°	6182	7731	4761	7731
60°	5341	7161	4456	7161
65°	4759	6544	3836	6544
70°	4181	5995	3497	5995
75°	3618	5190	3284	5190
80°	2745	4366	2745	4366
85°	2290	3431	2586	3431



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	156.8	1.8
10°-20°	459.5	5.2
20°-30°	728.5	8.2
30°-40°	878.5	9.9
40°-50°	784.5	8.8
50°-60°	601.6	6.8
60°-70°	391.0	4.4
70°-80°	190.1	2.1
80°-90°	49.0	0.6
90°-100°	111.8	1.3
100°-110°	330.0	3.7
110°-120°	559.0	6.3
120°-130°	735.7	8.3
130°-140°	824.3	9.3
140°-150°	807.9	9.1
150°-160°	678.6	7.6
160°-170°	451.1	5.1
170°-180°	157.9	1.8
0°-30°	1344.7	15.1
0°-40°	2223.3	25.0
0°-60°	3609.4	40.6
0°-90°	4239.5	47.7
90°-120°	1000.8	11.3
90°-150°	3368.6	37.9
90°-180°	4656.0	52.3
0°-180°	8895.7	100.0

CANDELA DISTRIBUTION:

	0°	90°	180°	270°	360°	Flux
0°	1635	1635	1635	1635	1635	
5°	1874	1631	1440	1631	1874	187
15°	2251	1557	1095	1557	2251	645
25°	2695	1420	880	1420	2695	1238
35°	2236	1236	718	1236	2236	1351
45°	1000	972	565	972	1000	798
55°	549	687	423	687	549	498
65°	311	428	251	428	311	310
75°	145	208	132	208	145	154
85°	31	46	35	46	31	36
90°	31	1	31	1	31	19
95°	112	84	112	84	112	114
105°	322	296	322	296	322	341
115°	565	560	565	560	565	559
125°	822	817	822	817	822	734
135°	1066	1062	1066	1062	1066	822
145°	1292	1287	1292	1287	1292	807
155°	1473	1473	1473	1473	1473	678
165°	1597	1601	1597	1601	1597	450
175°	1658	1665	1658	1665	1658	158
180°	1669	1669	1669	1669	1669	



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (FULL):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0
2.5°	1719.8	1718.7	1720.9	1714.9	1715.5	1706.3	1706.3	1699.4	1690.2	1683.3	1680.1
5°	1873.9	1875.3	1872.5	1862.4	1855.8	1845.7	1834.3	1814.1	1797.3	1781.2	1768.5
7.5°	2032.6	2033.5	2024.6	2021.5	2004.6	1992.3	1966.9	1939.5	1915.2	1884.4	1860.7
10°	2124.9	2124.3	2114.8	2107.5	2092.7	2073.9	2049.1	2016.8	1986.7	1953.1	1920.9
12.5°	2178.6	2176.9	2173.9	2164.9	2151.2	2134.6	2113.5	2081.8	2044.6	2007.9	1970.2
15°	2251.1	2246.3	2237.7	2226.2	2206.7	2187.3	2163.8	2135.6	2100.1	2058.5	2023.5
17.5°	2340.7	2340.9	2327.5	2311.6	2285.2	2250.8	2214.6	2169.0	2120.7	2074.9	2037.8
20°	2414.8	2412.8	2399.4	2368.5	2338.3	2295.3	2253.8	2198.0	2139.0	2079.2	2032.9
22.5°	2521.2	2515.9	2502.0	2461.4	2414.6	2359.2	2295.6	2227.6	2156.2	2088.4	2027.6
25°	2695.4	2691.3	2663.8	2616.8	2551.1	2465.8	2382.6	2289.3	2186.7	2097.4	2023.5
27.5°	2814.6	2810.1	2789.7	2750.7	2690.0	2600.3	2487.7	2363.0	2234.8	2112.0	2005.5
30°	2802.7	2812.8	2810.1	2792.1	2746.4	2665.8	2561.8	2421.6	2269.2	2124.9	1998.0
32.5°	2634.1	2643.2	2666.8	2702.3	2705.0	2672.8	2595.1	2465.6	2307.8	2143.7	1992.1
35°	2236.3	2248.4	2294.0	2365.9	2459.8	2538.3	2554.4	2484.7	2343.0	2166.5	1983.3
37.5°	1719.2	1785.3	1823.7	1899.3	2041.3	2185.7	2324.6	2375.8	2315.5	2157.1	1968.9
40°	1460.4	1476.5	1545.0	1630.2	1749.7	1900.1	2098.1	2241.0	2245.7	2135.6	1946.4
42.5°	1250.0	1270.4	1317.3	1385.4	1487.7	1638.1	1842.5	2031.1	2118.5	2076.6	1916.8
45°	1000.1	1015.5	1049.7	1102.1	1180.6	1304.8	1480.6	1698.7	1871.9	1939.7	1837.6
47.5°	821.5	829.8	859.6	899.5	957.6	1048.1	1184.2	1373.6	1581.2	1726.9	1712.5
50°	724.9	734.3	757.1	787.3	836.3	912.7	1021.5	1179.2	1393.4	1571.2	1606.8
52.5°	649.7	657.5	671.7	700.3	740.7	799.5	887.3	1029.9	1222.6	1411.7	1494.0
55°	549.0	554.4	565.8	581.9	614.2	656.4	732.2	830.9	986.6	1177.2	1298.0
57.5°	466.1	468.7	476.0	490.9	513.2	544.1	598.8	682.4	794.1	965.8	1099.1
60°	413.5	416.1	425.5	435.6	453.1	481.2	524.2	582.6	689.9	831.6	966.5
62.5°	371.5	373.2	377.2	387.3	402.6	424.3	458.1	505.8	591.2	715.6	843.0
65°	311.4	312.1	313.4	321.5	330.9	347.0	369.1	402.7	467.1	561.1	673.8
67.5°	253.7	254.6	259.3	262.2	272.0	280.4	293.4	319.1	364.5	427.8	515.5
70°	221.4	220.8	225.5	228.9	232.2	242.3	251.0	271.8	300.0	348.4	421.5
72.5°	191.4	189.7	191.7	192.9	197.3	204.1	212.9	225.7	247.4	280.7	336.7
75°	145.0	145.7	145.7	147.0	150.3	153.0	155.7	162.4	174.5	196.7	226.9
77.5°	101.8	100.7	103.5	103.9	105.9	108.8	111.2	113.8	118.8	127.9	143.5
80°	73.8	73.8	74.5	76.5	75.9	77.1	80.5	83.3	89.3	94.6	100.0
82.5°	56.7	56.1	56.7	57.2	57.1	58.4	59.6	60.1	62.4	65.1	68.9
85°	30.9	30.9	31.5	31.5	32.2	32.2	32.9	32.9	32.9	33.6	34.3
87.5°	18.1	17.3	16.6	16.4	16.8	17.7	16.9	16.0	15.8	15.4	15.6
90°	31.2	30.3	29.4	28.6	27.7	26.5	25.1	23.7	22.2	20.8	18.8
92.5°	61.3	60.6	60.0	59.4	58.7	57.5	55.5	53.6	51.7	49.9	47.4
95°	111.7	111.1	110.6	109.9	109.3	108.1	106.1	104.0	102.0	100.0	97.1
97.5°	169.4	169.0	168.7	168.3	168.0	166.8	164.9	163.0	161.1	159.2	155.2
100°	212.9	212.4	211.8	211.2	210.7	209.1	206.5	203.9	201.3	198.6	194.9
102.5°	256.6	255.8	254.9	254.2	253.4	251.5	248.7	245.9	243.1	240.2	238.3
105°	322.0	321.2	320.3	319.4	318.6	317.3	315.6	313.8	312.1	310.4	308.6
107.5°	389.0	389.1	389.2	389.2	389.3	388.8	388.0	387.1	386.2	385.4	384.1
110°	438.9	439.2	439.5	439.8	440.1	439.8	438.9	438.1	437.1	436.3	435.4



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	487.8	488.3	488.8	489.3	489.8	489.8	489.5	489.0	488.6	488.3	487.2
115°	564.9	565.2	565.4	565.8	566.0	566.3	566.6	566.9	567.1	567.5	566.9
117.5°	640.2	641.4	642.5	643.6	644.8	645.2	645.1	644.8	644.5	644.4	643.8
120°	692.2	693.3	694.4	695.6	696.7	697.3	697.3	697.3	697.3	697.3	697.0
122.5°	744.1	744.9	745.9	746.8	747.8	748.3	748.6	748.8	749.0	749.2	748.5
125°	822.0	822.3	822.5	822.9	823.1	823.5	824.1	824.8	825.3	825.9	825.6
127.5°	896.7	897.3	897.9	898.5	899.1	899.5	899.8	900.1	900.3	900.7	900.3
130°	946.7	947.2	947.8	948.4	948.9	949.3	949.7	949.9	950.2	950.5	949.9
132.5°	993.3	994.2	995.0	995.8	996.6	997.1	997.5	997.7	998.0	998.3	998.4
135°	1066.1	1067.2	1068.4	1069.5	1070.7	1071.3	1071.3	1071.3	1071.3	1071.3	1071.0
137.5°	1137.2	1138.7	1140.1	1141.6	1143.1	1143.6	1143.2	1142.9	1142.5	1142.2	1141.5
140°	1182.9	1184.4	1185.9	1187.3	1188.7	1189.1	1188.6	1188.0	1187.4	1186.9	1186.0
142.5°	1226.6	1228.0	1229.5	1230.9	1232.3	1233.0	1232.5	1232.2	1231.8	1231.5	1230.5
145°	1292.0	1292.9	1293.7	1294.6	1295.5	1295.9	1295.9	1295.9	1295.9	1295.9	1295.0
147.5°	1347.9	1349.9	1351.8	1353.8	1355.7	1356.3	1355.6	1355.0	1354.3	1353.6	1352.9
150°	1389.4	1390.0	1390.6	1391.1	1391.7	1392.1	1392.1	1392.1	1392.1	1392.1	1390.9
152.5°	1423.7	1424.8	1425.8	1426.8	1427.9	1428.1	1427.4	1426.7	1426.0	1425.3	1424.8
155°	1472.6	1473.9	1475.4	1476.9	1478.3	1478.4	1477.3	1476.1	1475.0	1473.9	1473.5
157.5°	1513.3	1515.2	1517.1	1519.0	1521.0	1521.3	1520.2	1519.0	1517.9	1516.7	1516.4
160°	1541.4	1542.8	1544.2	1545.7	1547.1	1547.3	1546.1	1545.0	1543.8	1542.7	1542.4
162.5°	1565.2	1566.9	1568.6	1570.3	1571.9	1572.1	1570.7	1569.3	1568.0	1566.5	1566.5
165°	1597.2	1599.0	1600.7	1602.4	1604.1	1604.4	1603.3	1602.1	1600.9	1599.8	1599.5
167.5°	1622.6	1624.4	1626.3	1628.0	1629.8	1629.8	1628.1	1626.3	1624.6	1622.9	1622.9
170°	1636.2	1638.1	1640.2	1642.2	1644.3	1644.3	1642.6	1640.9	1639.2	1637.4	1637.4
172.5°	1647.6	1649.3	1651.1	1652.9	1654.8	1654.8	1653.0	1651.3	1649.6	1647.9	1647.9
175°	1658.2	1660.3	1662.2	1664.3	1666.3	1666.5	1664.7	1663.0	1661.2	1659.5	1659.5
177.5°	1664.5	1666.0	1667.7	1669.3	1670.9	1671.0	1669.7	1668.3	1666.9	1665.5	1665.7
180°	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0
2.5°	1680.1	1676.3	1669.3	1662.8	1654.8	1647.9	1643.0	1637.1	1629.6	1620.5	1612.9
5°	1754.4	1739.7	1720.2	1703.4	1682.0	1665.2	1647.7	1630.9	1614.1	1592.7	1573.9
7.5°	1836.9	1806.4	1776.7	1739.4	1705.6	1675.3	1646.3	1617.0	1588.2	1557.7	1528.4
10°	1887.3	1850.4	1809.5	1762.5	1719.5	1678.6	1641.0	1604.0	1565.1	1530.9	1494.0
12.5°	1934.6	1886.9	1840.0	1780.7	1729.1	1679.1	1631.3	1585.3	1543.7	1499.3	1459.7
15°	1977.2	1930.3	1877.9	1805.4	1733.6	1673.2	1616.8	1557.1	1505.4	1455.8	1411.4
17.5°	1993.7	1944.5	1883.7	1814.0	1735.5	1659.5	1586.9	1521.4	1460.6	1402.7	1352.9
20°	1987.3	1939.7	1877.2	1810.8	1726.9	1647.7	1569.2	1496.7	1428.9	1367.8	1314.8
22.5°	1971.8	1922.4	1862.2	1792.0	1712.4	1628.4	1544.5	1467.1	1396.1	1332.9	1275.1
25°	1948.4	1881.3	1819.6	1751.0	1675.2	1592.0	1505.4	1420.1	1344.4	1279.9	1216.9
27.5°	1924.1	1840.3	1761.8	1693.8	1613.6	1539.4	1455.9	1368.5	1288.7	1223.1	1158.4
30°	1902.0	1808.1	1721.5	1644.3	1568.5	1498.1	1418.8	1333.6	1251.7	1184.0	1118.2
32.5°	1874.7	1774.8	1679.6	1590.6	1517.5	1447.6	1375.9	1294.4	1214.7	1144.7	1077.9
35°	1840.3	1712.8	1609.5	1514.8	1433.6	1365.8	1301.4	1235.6	1155.7	1083.2	1018.1
37.5°	1795.2	1650.5	1530.9	1427.8	1342.2	1274.1	1223.2	1163.1	1090.2	1020.8	960.4
40°	1767.8	1605.4	1474.5	1372.5	1282.5	1210.7	1163.1	1112.2	1045.7	980.6	920.2
42.5°	1731.3	1564.1	1417.6	1311.3	1220.8	1151.7	1103.5	1058.9	1003.2	941.9	877.2
45°	1659.7	1483.9	1330.2	1216.2	1124.9	1057.0	1012.1	972.5	930.2	873.8	817.4
47.5°	1566.6	1400.3	1239.5	1114.9	1025.5	962.6	918.9	887.7	857.5	809.5	754.8
50°	1492.0	1331.6	1174.5	1053.7	958.4	898.7	857.7	832.9	805.4	761.7	716.1
52.5°	1403.9	1260.7	1106.9	983.3	893.5	837.5	798.1	773.4	750.6	715.1	671.6
55°	1265.2	1139.6	998.7	886.6	804.1	747.7	710.1	686.6	673.2	643.0	608.7
57.5°	1105.0	1015.0	890.8	782.7	709.7	654.0	626.5	606.5	591.3	570.0	545.8
60°	993.3	930.2	818.8	716.1	649.0	596.0	571.2	554.4	540.3	522.2	503.3
62.5°	880.0	834.1	737.2	649.0	587.3	542.9	519.6	504.5	488.2	476.0	457.7
65°	728.2	687.3	620.2	551.0	494.0	458.4	441.6	428.2	418.1	404.7	391.9
67.5°	566.5	549.8	503.5	455.8	414.9	383.2	368.8	359.4	347.2	339.2	330.5
70°	467.1	459.1	426.2	394.7	356.4	334.9	321.5	317.5	302.7	294.6	288.6
72.5°	379.1	375.3	356.4	334.5	307.5	288.7	276.4	271.8	262.4	256.0	252.1
75°	259.8	261.1	257.7	243.7	233.6	221.4	210.8	208.0	201.4	196.0	192.6
77.5°	164.3	171.2	171.4	170.7	166.7	159.4	154.9	152.9	146.3	144.3	143.5
80°	112.8	120.1	126.8	126.1	124.8	122.9	119.5	117.4	114.1	112.1	110.7
82.5°	75.2	82.1	87.6	91.3	91.0	89.0	86.7	85.8	85.1	83.6	83.3
85°	35.6	36.9	38.9	43.7	47.0	47.6	47.0	46.3	44.3	44.9	45.6
87.5°	15.7	15.3	15.4	15.0	14.0	16.2	17.4	17.5	16.8	16.2	15.6
90°	16.7	14.7	12.7	10.5	8.3	5.9	3.6	1.3	3.6	5.9	8.3
92.5°	44.9	42.4	40.0	37.9	36.2	34.7	33.1	31.4	33.1	34.7	36.2
95°	94.2	91.4	88.4	86.7	86.1	85.6	85.0	84.4	85.0	85.6	86.1
97.5°	151.3	147.2	143.3	141.2	140.9	140.7	140.4	140.3	140.4	140.7	140.9
100°	191.1	187.4	183.7	181.8	181.8	181.8	181.8	181.8	181.8	181.8	181.8
102.5°	236.4	234.5	232.6	231.1	229.9	228.8	227.6	226.4	227.6	228.8	229.9
105°	306.9	305.1	303.4	301.9	300.4	298.9	297.5	296.1	297.5	298.9	300.4
107.5°	382.7	381.4	380.1	378.7	377.3	375.8	374.4	372.9	374.4	375.8	377.3
110°	434.5	433.7	432.8	431.7	430.2	428.8	427.4	425.9	427.4	428.8	430.2



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	486.0	484.9	483.9	482.9	482.2	481.5	480.7	479.9	480.7	481.5	482.2
115°	566.3	565.8	565.2	564.3	563.1	562.0	560.9	559.6	560.9	562.0	563.1
117.5°	643.3	642.7	642.2	641.7	641.2	640.7	640.2	639.6	640.2	640.7	641.2
120°	696.7	696.5	696.1	695.3	693.9	692.4	691.0	689.5	691.0	692.4	693.9
122.5°	747.8	747.0	746.2	745.6	745.1	744.6	744.1	743.6	744.1	744.6	745.1
125°	825.3	825.0	824.8	823.7	822.0	820.3	818.5	816.7	818.5	820.3	822.0
127.5°	900.0	899.7	899.3	898.6	897.6	896.6	895.7	894.7	895.7	896.6	897.6
130°	949.3	948.8	948.2	947.2	945.7	944.3	942.9	941.4	942.9	944.3	945.7
132.5°	998.5	998.7	998.8	997.6	995.3	992.9	990.6	988.2	990.6	992.9	995.3
135°	1070.7	1070.4	1070.1	1069.1	1067.4	1065.7	1063.9	1062.2	1063.9	1065.7	1067.4
137.5°	1140.9	1140.3	1139.6	1138.5	1136.8	1135.1	1133.5	1131.8	1133.5	1135.1	1136.8
140°	1185.2	1184.2	1183.4	1182.2	1180.8	1179.3	1177.9	1176.5	1177.9	1179.3	1180.8
142.5°	1229.3	1228.2	1227.1	1226.0	1224.8	1223.6	1222.4	1221.2	1222.4	1223.6	1224.8
145°	1294.2	1293.3	1292.4	1291.5	1290.3	1289.2	1288.0	1286.9	1288.0	1289.2	1290.3
147.5°	1352.2	1351.5	1350.8	1350.1	1349.5	1348.8	1348.2	1347.6	1348.2	1348.8	1349.5
150°	1389.7	1388.5	1387.4	1387.0	1387.2	1387.6	1387.8	1388.1	1387.8	1387.6	1387.2
152.5°	1424.4	1423.9	1423.4	1423.0	1422.5	1422.2	1421.8	1421.3	1421.8	1422.2	1422.5
155°	1473.3	1473.0	1472.7	1472.6	1472.6	1472.6	1472.6	1472.6	1472.6	1472.6	1472.6
157.5°	1516.1	1515.8	1515.5	1515.7	1516.3	1517.0	1517.6	1518.2	1517.6	1517.0	1516.3
160°	1542.1	1541.8	1541.5	1541.8	1542.7	1543.5	1544.4	1545.2	1544.4	1543.5	1542.7
162.5°	1566.4	1566.3	1566.3	1566.6	1567.3	1567.9	1568.5	1569.2	1568.5	1567.9	1567.3
165°	1599.2	1599.0	1598.6	1598.8	1599.4	1599.9	1600.5	1601.1	1600.5	1599.9	1599.4
167.5°	1622.9	1622.9	1622.9	1623.5	1624.6	1625.8	1626.9	1628.1	1626.9	1625.8	1624.6
170°	1637.4	1637.4	1637.4	1638.1	1639.2	1640.3	1641.5	1642.6	1641.5	1640.3	1639.2
172.5°	1647.9	1647.9	1647.9	1648.4	1649.6	1650.7	1651.9	1653.0	1651.9	1650.7	1649.6
175°	1659.5	1659.5	1659.5	1660.1	1661.2	1662.4	1663.5	1664.7	1663.5	1662.4	1661.2
177.5°	1665.9	1666.2	1666.4	1667.0	1667.9	1668.9	1669.7	1670.7	1669.7	1668.9	1667.9
180°	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0
2.5°	1607.6	1600.1	1594.7	1583.9	1576.4	1573.2	1567.3	1565.6	1571.6	1567.3	1566.8
5°	1559.8	1540.3	1524.9	1509.4	1492.6	1482.0	1465.9	1463.1	1459.1	1453.0	1451.7
7.5°	1502.4	1477.1	1457.2	1431.8	1409.5	1391.7	1371.6	1362.0	1356.8	1349.0	1338.6
10°	1463.8	1433.6	1406.8	1381.2	1353.8	1331.6	1311.5	1296.0	1285.9	1276.5	1272.6
12.5°	1425.6	1394.9	1360.6	1329.7	1299.0	1274.1	1251.8	1241.8	1230.6	1219.6	1210.2
15°	1366.5	1325.5	1288.0	1252.4	1226.2	1199.4	1177.8	1163.1	1146.3	1141.7	1123.5
17.5°	1303.6	1263.5	1219.5	1182.1	1151.7	1122.1	1098.5	1081.8	1069.2	1051.9	1043.5
20°	1264.5	1216.9	1173.9	1139.6	1106.0	1071.2	1047.0	1032.9	1020.8	1006.8	1000.1
22.5°	1222.6	1176.0	1132.0	1091.8	1057.7	1023.4	1006.2	991.6	977.8	964.8	956.0
25°	1161.1	1114.1	1067.8	1026.2	990.7	965.8	945.6	928.8	921.5	908.8	899.3
27.5°	1100.3	1050.3	1002.3	960.8	932.9	908.4	891.8	878.6	865.2	854.1	845.9
30°	1061.1	1010.1	957.8	924.9	895.4	871.8	853.7	840.9	830.9	820.8	814.8
32.5°	1021.9	969.3	922.8	887.3	859.4	839.0	820.4	808.2	797.6	786.4	779.4
35°	959.1	905.4	867.8	832.9	805.4	786.6	773.9	756.4	747.7	739.6	732.2
37.5°	900.7	850.8	810.1	779.5	755.6	736.9	720.4	711.0	700.3	693.0	686.9
40°	857.7	812.1	775.2	743.0	725.6	704.7	689.3	677.2	669.2	659.8	653.1
42.5°	819.1	776.7	740.8	711.9	690.1	672.5	657.6	645.5	635.3	628.6	622.9
45°	764.5	722.2	687.3	660.4	640.3	623.5	608.0	602.0	588.6	580.6	577.9
47.5°	707.9	670.1	636.4	611.7	591.0	575.1	560.7	548.4	541.0	533.0	528.7
50°	669.9	633.6	602.0	577.9	557.8	540.3	526.8	518.8	508.8	501.4	496.0
52.5°	631.7	598.1	566.6	543.5	526.1	508.6	493.6	485.5	476.0	471.3	467.5
55°	577.2	541.7	514.8	492.0	473.8	457.7	443.7	435.6	429.6	424.8	423.5
57.5°	515.5	487.2	462.3	441.8	422.9	407.8	395.5	387.8	382.5	381.8	377.7
60°	475.2	449.7	426.9	404.7	388.6	374.5	363.8	355.1	349.7	349.0	347.7
62.5°	434.9	410.4	389.3	369.8	355.3	341.7	331.6	321.8	318.6	315.2	312.2
65°	375.1	353.0	335.6	320.1	304.7	293.3	283.3	277.2	269.8	265.8	258.4
67.5°	316.5	299.4	282.6	269.6	257.4	246.6	238.2	229.3	224.3	221.1	215.7
70°	277.8	264.4	247.6	233.6	224.2	215.4	208.7	198.6	195.3	192.6	189.9
72.5°	241.3	229.5	215.4	204.1	194.7	186.4	178.7	173.9	170.7	167.9	166.3
75°	189.9	178.6	166.4	158.4	151.7	145.0	140.9	137.6	136.2	135.6	132.9
77.5°	139.5	133.5	123.7	117.4	112.9	110.2	106.6	104.9	104.7	101.8	100.8
80°	106.7	103.3	95.3	92.6	89.3	86.6	84.6	81.2	77.8	76.5	74.5
82.5°	79.3	75.9	72.8	68.4	65.6	64.1	62.0	60.8	61.2	59.3	58.4
85°	42.3	38.9	37.6	36.9	35.6	36.9	36.2	35.6	34.9	34.3	34.9
87.5°	15.5	15.9	15.8	17.3	16.1	17.0	17.3	17.0	17.4	17.7	17.4
90°	10.5	12.7	14.7	16.7	18.8	20.8	22.2	23.7	25.1	26.5	27.7
92.5°	37.9	40.0	42.4	44.9	47.4	49.9	51.7	53.6	55.5	57.5	58.7
95°	86.7	88.4	91.4	94.2	97.1	100.0	102.0	104.0	106.1	108.1	109.3
97.5°	141.2	143.3	147.2	151.3	155.2	159.2	161.1	163.0	164.9	166.8	168.0
100°	181.8	183.7	187.4	191.1	194.9	198.6	201.3	203.9	206.5	209.1	210.7
102.5°	231.1	232.6	234.5	236.4	238.3	240.2	243.1	245.9	248.7	251.5	253.4
105°	301.9	303.4	305.1	306.9	308.6	310.4	312.1	313.8	315.6	317.3	318.6
107.5°	378.7	380.1	381.4	382.7	384.1	385.4	386.2	387.1	388.0	388.8	389.3
110°	431.7	432.8	433.7	434.5	435.4	436.3	437.1	438.1	438.9	439.8	440.1



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	482.9	483.9	484.9	486.0	487.2	488.3	488.6	489.0	489.5	489.8	489.8
115°	564.3	565.2	565.8	566.3	566.9	567.5	567.1	566.9	566.6	566.3	566.0
117.5°	641.7	642.2	642.7	643.3	643.8	644.4	644.5	644.8	645.1	645.2	644.8
120°	695.3	696.1	696.5	696.7	697.0	697.3	697.3	697.3	697.3	697.3	696.7
122.5°	745.6	746.2	747.0	747.8	748.5	749.2	749.0	748.8	748.6	748.3	747.8
125°	823.7	824.8	825.0	825.3	825.6	825.9	825.3	824.8	824.1	823.5	823.1
127.5°	898.6	899.3	899.7	900.0	900.3	900.7	900.3	900.1	899.8	899.5	899.1
130°	947.2	948.2	948.8	949.3	949.9	950.5	950.2	949.9	949.7	949.3	948.9
132.5°	997.6	998.8	998.7	998.5	998.4	998.3	998.0	997.7	997.5	997.1	996.6
135°	1069.1	1070.1	1070.4	1070.7	1071.0	1071.3	1071.3	1071.3	1071.3	1071.3	1070.7
137.5°	1138.5	1139.6	1140.3	1140.9	1141.5	1142.2	1142.5	1142.9	1143.2	1143.6	1143.1
140°	1182.2	1183.4	1184.2	1185.2	1186.0	1186.9	1187.4	1188.0	1188.6	1189.1	1188.7
142.5°	1226.0	1227.1	1228.2	1229.3	1230.5	1231.5	1231.8	1232.2	1232.5	1233.0	1232.3
145°	1291.5	1292.4	1293.3	1294.2	1295.0	1295.9	1295.9	1295.9	1295.9	1295.9	1295.5
147.5°	1350.1	1350.8	1351.5	1352.2	1352.9	1353.6	1354.3	1355.0	1355.6	1356.3	1355.7
150°	1387.0	1387.4	1388.5	1389.7	1390.9	1392.1	1392.1	1392.1	1392.1	1392.1	1391.7
152.5°	1423.0	1423.4	1423.9	1424.4	1424.8	1425.3	1426.0	1426.7	1427.4	1428.1	1427.9
155°	1472.6	1472.7	1473.0	1473.3	1473.5	1473.9	1475.0	1476.1	1477.3	1478.4	1478.3
157.5°	1515.7	1515.5	1515.8	1516.1	1516.4	1516.7	1517.9	1519.0	1520.2	1521.3	1521.0
160°	1541.8	1541.5	1541.8	1542.1	1542.4	1542.7	1543.8	1545.0	1546.1	1547.3	1547.1
162.5°	1566.6	1566.3	1566.3	1566.4	1566.5	1566.5	1568.0	1569.3	1570.7	1572.1	1571.9
165°	1598.8	1598.6	1599.0	1599.2	1599.5	1599.8	1600.9	1602.1	1603.3	1604.4	1604.1
167.5°	1623.5	1622.9	1622.9	1622.9	1622.9	1622.9	1624.6	1626.3	1628.1	1629.8	1629.8
170°	1638.1	1637.4	1637.4	1637.4	1637.4	1637.4	1639.2	1640.9	1642.6	1644.3	1644.3
172.5°	1648.4	1647.9	1647.9	1647.9	1647.9	1647.9	1649.6	1651.3	1653.0	1654.8	1654.8
175°	1660.1	1659.5	1659.5	1659.5	1659.5	1659.5	1661.2	1663.0	1664.7	1666.5	1666.3
177.5°	1667.0	1666.4	1666.2	1665.9	1665.7	1665.5	1666.9	1668.3	1669.7	1671.0	1670.9
180°	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0
2.5°	1566.2	1560.3	1558.7	1560.8	1558.7	1560.3	1566.2	1566.8	1567.3	1571.6	1565.6
5°	1445.0	1438.3	1441.7	1440.3	1441.7	1438.3	1445.0	1451.7	1453.0	1459.1	1463.1
7.5°	1338.4	1330.1	1321.2	1324.0	1321.2	1330.1	1338.4	1338.6	1349.0	1356.8	1362.0
10°	1263.8	1257.1	1253.0	1256.4	1253.0	1257.1	1263.8	1272.6	1276.5	1285.9	1296.0
12.5°	1201.0	1197.0	1193.4	1192.0	1193.4	1197.0	1201.0	1210.2	1219.6	1230.6	1241.8
15°	1115.4	1107.4	1104.1	1095.4	1104.1	1107.4	1115.4	1123.5	1141.7	1146.3	1163.1
17.5°	1036.6	1034.0	1025.3	1021.5	1025.3	1034.0	1036.6	1043.5	1051.9	1069.2	1081.8
20°	990.0	987.3	978.5	984.0	978.5	987.3	990.0	1000.1	1006.8	1020.8	1032.9
22.5°	951.3	945.4	942.5	941.0	942.5	945.4	951.3	956.0	964.8	977.8	991.6
25°	896.6	887.9	884.6	880.5	884.6	887.9	896.6	899.3	908.8	921.5	928.8
27.5°	842.1	837.5	833.0	832.0	833.0	837.5	842.1	845.9	854.1	865.2	878.6
30°	806.8	802.0	798.7	798.7	798.7	802.0	806.8	814.8	820.8	830.9	840.9
32.5°	775.1	771.5	768.1	767.6	768.1	771.5	775.1	779.4	786.4	797.6	808.2
35°	728.9	723.5	722.2	718.2	722.2	723.5	728.9	732.2	739.6	747.7	756.4
37.5°	681.0	676.5	676.4	676.0	676.4	676.5	681.0	686.9	693.0	700.3	711.0
40°	650.3	647.0	646.4	641.6	646.4	647.0	650.3	653.1	659.8	669.2	677.2
42.5°	617.6	615.9	613.5	611.6	613.5	615.9	617.6	622.9	628.6	635.3	645.5
45°	573.2	568.4	568.4	565.1	568.4	568.4	573.2	577.9	580.6	588.6	602.0
47.5°	527.3	523.7	524.0	520.6	524.0	523.7	527.3	528.7	533.0	541.0	548.4
50°	496.6	494.6	494.0	492.7	494.0	494.6	496.6	496.0	501.4	508.8	518.8
52.5°	466.1	465.1	467.7	464.7	467.7	465.1	466.1	467.5	471.3	476.0	485.5
55°	424.8	422.8	426.9	422.8	426.9	422.8	424.8	423.5	424.8	429.6	435.6
57.5°	377.5	375.6	379.2	377.2	379.2	375.6	377.5	377.7	381.8	382.5	387.8
60°	346.3	342.3	344.3	345.0	344.3	342.3	346.3	347.7	349.0	349.7	355.1
62.5°	309.3	306.9	308.3	305.2	308.3	306.9	309.3	312.2	315.2	318.6	321.8
65°	257.1	255.0	252.4	251.0	252.4	255.0	257.1	258.4	265.8	269.8	277.2
67.5°	215.9	211.1	211.0	212.1	211.0	211.1	215.9	215.7	221.1	224.3	229.3
70°	185.9	185.9	185.2	185.2	185.2	185.9	185.9	189.9	192.6	195.3	198.6
72.5°	165.0	164.5	163.2	162.7	163.2	164.5	165.0	166.3	167.9	170.7	173.9
75°	132.9	133.5	132.2	131.6	132.2	133.5	132.9	132.9	135.6	136.2	137.6
77.5°	98.2	95.3	96.8	95.3	96.8	95.3	98.2	100.8	101.8	104.7	104.9
80°	74.5	73.8	75.9	73.8	75.9	73.8	74.5	74.5	76.5	77.8	81.2
82.5°	58.9	58.3	59.2	57.7	59.2	58.3	58.9	58.4	59.3	61.2	60.8
85°	35.6	34.9	34.3	34.9	34.3	34.9	35.6	34.9	34.3	34.9	35.6
87.5°	18.1	17.7	17.9	18.1	17.9	17.7	18.1	17.4	17.7	17.4	17.0
90°	28.6	29.4	30.3	31.2	30.3	29.4	28.6	27.7	26.5	25.1	23.7
92.5°	59.4	60.0	60.6	61.3	60.6	60.0	59.4	58.7	57.5	55.5	53.6
95°	109.9	110.6	111.1	111.7	111.1	110.6	109.9	109.3	108.1	106.1	104.0
97.5°	168.3	168.7	169.0	169.4	169.0	168.7	168.3	168.0	166.8	164.9	163.0
100°	211.2	211.8	212.4	212.9	212.4	211.8	211.2	210.7	209.1	206.5	203.9
102.5°	254.2	254.9	255.8	256.6	255.8	254.9	254.2	253.4	251.5	248.7	245.9
105°	319.4	320.3	321.2	322.0	321.2	320.3	319.4	318.6	317.3	315.6	313.8
107.5°	389.2	389.2	389.1	389.0	389.1	389.2	389.2	389.3	388.8	388.0	387.1
110°	439.8	439.5	439.2	438.9	439.2	439.5	439.8	440.1	439.8	438.9	438.1



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	489.3	488.8	488.3	487.8	488.3	488.8	489.3	489.8	489.8	489.5	489.0
115°	565.8	565.4	565.2	564.9	565.2	565.4	565.8	566.0	566.3	566.6	566.9
117.5°	643.6	642.5	641.4	640.2	641.4	642.5	643.6	644.8	645.2	645.1	644.8
120°	695.6	694.4	693.3	692.2	693.3	694.4	695.6	696.7	697.3	697.3	697.3
122.5°	746.8	745.9	744.9	744.1	744.9	745.9	746.8	747.8	748.3	748.6	748.8
125°	822.9	822.5	822.3	822.0	822.3	822.5	822.9	823.1	823.5	824.1	824.8
127.5°	898.5	897.9	897.3	896.7	897.3	897.9	898.5	899.1	899.5	899.8	900.1
130°	948.4	947.8	947.2	946.7	947.2	947.8	948.4	948.9	949.3	949.7	949.9
132.5°	995.8	995.0	994.2	993.3	994.2	995.0	995.8	996.6	997.1	997.5	997.7
135°	1069.5	1068.4	1067.2	1066.1	1067.2	1068.4	1069.5	1070.7	1071.3	1071.3	1071.3
137.5°	1141.6	1140.1	1138.7	1137.2	1138.7	1140.1	1141.6	1143.1	1143.6	1143.2	1142.9
140°	1187.3	1185.9	1184.4	1182.9	1184.4	1185.9	1187.3	1188.7	1189.1	1188.6	1188.0
142.5°	1230.9	1229.5	1228.0	1226.6	1228.0	1229.5	1230.9	1232.3	1233.0	1232.5	1232.2
145°	1294.6	1293.7	1292.9	1292.0	1292.9	1293.7	1294.6	1295.5	1295.9	1295.9	1295.9
147.5°	1353.8	1351.8	1349.9	1347.9	1349.9	1351.8	1353.8	1355.7	1356.3	1355.6	1355.0
150°	1391.1	1390.6	1390.0	1389.4	1390.0	1390.6	1391.1	1391.7	1392.1	1392.1	1392.1
152.5°	1426.8	1425.8	1424.8	1423.7	1424.8	1425.8	1426.8	1427.9	1428.1	1427.4	1426.7
155°	1476.9	1475.4	1473.9	1472.6	1473.9	1475.4	1476.9	1478.3	1478.4	1477.3	1476.1
157.5°	1519.0	1517.1	1515.2	1513.3	1515.2	1517.1	1519.0	1521.0	1521.3	1520.2	1519.0
160°	1545.7	1544.2	1542.8	1541.4	1542.8	1544.2	1545.7	1547.1	1547.3	1546.1	1545.0
162.5°	1570.3	1568.6	1566.9	1565.2	1566.9	1568.6	1570.3	1571.9	1572.1	1570.7	1569.3
165°	1602.4	1600.7	1599.0	1597.2	1599.0	1600.7	1602.4	1604.1	1604.4	1603.3	1602.1
167.5°	1628.0	1626.3	1624.4	1622.6	1624.4	1626.3	1628.0	1629.8	1629.8	1628.1	1626.3
170°	1642.2	1640.2	1638.1	1636.2	1638.1	1640.2	1642.2	1644.3	1644.3	1642.6	1640.9
172.5°	1652.9	1651.1	1649.3	1647.6	1649.3	1651.1	1652.9	1654.8	1654.8	1653.0	1651.3
175°	1664.3	1662.2	1660.3	1658.2	1660.3	1662.2	1664.3	1666.3	1666.5	1664.7	1663.0
177.5°	1669.3	1667.7	1666.0	1664.5	1666.0	1667.7	1669.3	1670.9	1671.0	1669.7	1668.3
180°	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0
2.5°	1567.3	1573.2	1576.4	1583.9	1594.7	1600.1	1607.6	1612.9	1620.5	1629.6	1637.1
5°	1465.9	1482.0	1492.6	1509.4	1524.9	1540.3	1559.8	1573.9	1592.7	1614.1	1630.9
7.5°	1371.6	1391.7	1409.5	1431.8	1457.2	1477.1	1502.4	1528.4	1557.7	1588.2	1617.0
10°	1311.5	1331.6	1353.8	1381.2	1406.8	1433.6	1463.8	1494.0	1530.9	1565.1	1604.0
12.5°	1251.8	1274.1	1299.0	1329.7	1360.6	1394.9	1425.6	1459.7	1499.3	1543.7	1585.3
15°	1177.8	1199.4	1226.2	1252.4	1288.0	1325.5	1366.5	1411.4	1455.8	1505.4	1557.1
17.5°	1098.5	1122.1	1151.7	1182.1	1219.5	1263.5	1303.6	1352.9	1402.7	1460.6	1521.4
20°	1047.0	1071.2	1106.0	1139.6	1173.9	1216.9	1264.5	1314.8	1367.8	1428.9	1496.7
22.5°	1006.2	1023.4	1057.7	1091.8	1132.0	1176.0	1222.6	1275.1	1332.9	1396.1	1467.1
25°	945.6	965.8	990.7	1026.2	1067.8	1114.1	1161.1	1216.9	1279.9	1344.4	1420.1
27.5°	891.8	908.4	932.9	960.8	1002.3	1050.3	1100.3	1158.4	1223.1	1288.7	1368.5
30°	853.7	871.8	895.4	924.9	957.8	1010.1	1061.1	1118.2	1184.0	1251.7	1333.6
32.5°	820.4	839.0	859.4	887.3	922.8	969.3	1021.9	1077.9	1144.7	1214.7	1294.4
35°	773.9	786.6	805.4	832.9	867.8	905.4	959.1	1018.1	1083.2	1155.7	1235.6
37.5°	720.4	736.9	755.6	779.5	810.1	850.8	900.7	960.4	1020.8	1090.2	1163.1
40°	689.3	704.7	725.6	743.0	775.2	812.1	857.7	920.2	980.6	1045.7	1112.2
42.5°	657.6	672.5	690.1	711.9	740.8	776.7	819.1	877.2	941.9	1003.2	1058.9
45°	608.0	623.5	640.3	660.4	687.3	722.2	764.5	817.4	873.8	930.2	972.5
47.5°	560.7	575.1	591.0	611.7	636.4	670.1	707.9	754.8	809.5	857.5	887.7
50°	526.8	540.3	557.8	577.9	602.0	633.6	669.9	716.1	761.7	805.4	832.9
52.5°	493.6	508.6	526.1	543.5	566.6	598.1	631.7	671.6	715.1	750.6	773.4
55°	443.7	457.7	473.8	492.0	514.8	541.7	577.2	608.7	643.0	673.2	686.6
57.5°	395.5	407.8	422.9	441.8	462.3	487.2	515.5	545.8	570.0	591.3	606.5
60°	363.8	374.5	388.6	404.7	426.9	449.7	475.2	503.3	522.2	540.3	554.4
62.5°	331.6	341.7	355.3	369.8	389.3	410.4	434.9	457.7	476.0	488.2	504.5
65°	283.3	293.3	304.7	320.1	335.6	353.0	375.1	391.9	404.7	418.1	428.2
67.5°	238.2	246.6	257.4	269.6	282.6	299.4	316.5	330.5	339.2	347.2	359.4
70°	208.7	215.4	224.2	233.6	247.6	264.4	277.8	288.6	294.6	302.7	317.5
72.5°	178.7	186.4	194.7	204.1	215.4	229.5	241.3	252.1	256.0	262.4	271.8
75°	140.9	145.0	151.7	158.4	166.4	178.6	189.9	192.6	196.0	201.4	208.0
77.5°	106.6	110.2	112.9	117.4	123.7	133.5	139.5	143.5	144.3	146.3	152.9
80°	84.6	86.6	89.3	92.6	95.3	103.3	106.7	110.7	112.1	114.1	117.4
82.5°	62.0	64.1	65.6	68.4	72.8	75.9	79.3	83.3	83.6	85.1	85.8
85°	36.2	36.9	35.6	36.9	37.6	38.9	42.3	45.6	44.9	44.3	46.3
87.5°	17.3	17.0	16.1	17.3	15.8	15.9	15.5	15.6	16.2	16.8	17.5
90°	22.2	20.8	18.8	16.7	14.7	12.7	10.5	8.3	5.9	3.6	1.3
92.5°	51.7	49.9	47.4	44.9	42.4	40.0	37.9	36.2	34.7	33.1	31.4
95°	102.0	100.0	97.1	94.2	91.4	88.4	86.7	86.1	85.6	85.0	84.4
97.5°	161.1	159.2	155.2	151.3	147.2	143.3	141.2	140.9	140.7	140.4	140.3
100°	201.3	198.6	194.9	191.1	187.4	183.7	181.8	181.8	181.8	181.8	181.8
102.5°	243.1	240.2	238.3	236.4	234.5	232.6	231.1	229.9	228.8	227.6	226.4
105°	312.1	310.4	308.6	306.9	305.1	303.4	301.9	300.4	298.9	297.5	296.1
107.5°	386.2	385.4	384.1	382.7	381.4	380.1	378.7	377.3	375.8	374.4	372.9
110°	437.1	436.3	435.4	434.5	433.7	432.8	431.7	430.2	428.8	427.4	425.9



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	488.6	488.3	487.2	486.0	484.9	483.9	482.9	482.2	481.5	480.7	479.9
115°	567.1	567.5	566.9	566.3	565.8	565.2	564.3	563.1	562.0	560.9	559.6
117.5°	644.5	644.4	643.8	643.3	642.7	642.2	641.7	641.2	640.7	640.2	639.6
120°	697.3	697.3	697.0	696.7	696.5	696.1	695.3	693.9	692.4	691.0	689.5
122.5°	749.0	749.2	748.5	747.8	747.0	746.2	745.6	745.1	744.6	744.1	743.6
125°	825.3	825.9	825.6	825.3	825.0	824.8	823.7	822.0	820.3	818.5	816.7
127.5°	900.3	900.7	900.3	900.0	899.7	899.3	898.6	897.6	896.6	895.7	894.7
130°	950.2	950.5	949.9	949.3	948.8	948.2	947.2	945.7	944.3	942.9	941.4
132.5°	998.0	998.3	998.4	998.5	998.7	998.8	997.6	995.3	992.9	990.6	988.2
135°	1071.3	1071.3	1071.0	1070.7	1070.4	1070.1	1069.1	1067.4	1065.7	1063.9	1062.2
137.5°	1142.5	1142.2	1141.5	1140.9	1140.3	1139.6	1138.5	1136.8	1135.1	1133.5	1131.8
140°	1187.4	1186.9	1186.0	1185.2	1184.2	1183.4	1182.2	1180.8	1179.3	1177.9	1176.5
142.5°	1231.8	1231.5	1230.5	1229.3	1228.2	1227.1	1226.0	1224.8	1223.6	1222.4	1221.2
145°	1295.9	1295.9	1295.0	1294.2	1293.3	1292.4	1291.5	1290.3	1289.2	1288.0	1286.9
147.5°	1354.3	1353.6	1352.9	1352.2	1351.5	1350.8	1350.1	1349.5	1348.8	1348.2	1347.6
150°	1392.1	1392.1	1390.9	1389.7	1388.5	1387.4	1387.0	1387.2	1387.6	1387.8	1388.1
152.5°	1426.0	1425.3	1424.8	1424.4	1423.9	1423.4	1423.0	1422.5	1422.2	1421.8	1421.3
155°	1475.0	1473.9	1473.5	1473.3	1473.0	1472.7	1472.6	1472.6	1472.6	1472.6	1472.6
157.5°	1517.9	1516.7	1516.4	1516.1	1515.8	1515.5	1515.7	1516.3	1517.0	1517.6	1518.2
160°	1543.8	1542.7	1542.4	1542.1	1541.8	1541.5	1541.8	1542.7	1543.5	1544.4	1545.2
162.5°	1568.0	1566.5	1566.5	1566.4	1566.3	1566.3	1566.6	1567.3	1567.9	1568.5	1569.2
165°	1600.9	1599.8	1599.5	1599.2	1599.0	1598.6	1598.8	1599.4	1599.9	1600.5	1601.1
167.5°	1624.6	1622.9	1622.9	1622.9	1622.9	1622.9	1623.5	1624.6	1625.8	1626.9	1628.1
170°	1639.2	1637.4	1637.4	1637.4	1637.4	1637.4	1638.1	1639.2	1640.3	1641.5	1642.6
172.5°	1649.6	1647.9	1647.9	1647.9	1647.9	1647.9	1648.4	1649.6	1650.7	1651.9	1653.0
175°	1661.2	1659.5	1659.5	1659.5	1659.5	1659.5	1660.1	1661.2	1662.4	1663.5	1664.7
177.5°	1666.9	1665.5	1665.7	1665.9	1666.2	1666.4	1667.0	1667.9	1668.9	1669.7	1670.7
180°	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0
2.5°	1643.0	1647.9	1654.8	1662.8	1669.3	1676.3	1680.1	1680.1	1683.3	1690.2	1699.4
5°	1647.7	1665.2	1682.0	1703.4	1720.2	1739.7	1754.4	1768.5	1781.2	1797.3	1814.1
7.5°	1646.3	1675.3	1705.6	1739.4	1776.7	1806.4	1836.9	1860.7	1884.4	1915.2	1939.5
10°	1641.0	1678.6	1719.5	1762.5	1809.5	1850.4	1887.3	1920.9	1953.1	1986.7	2016.8
12.5°	1631.3	1679.1	1729.1	1780.7	1840.0	1886.9	1934.6	1970.2	2007.9	2044.6	2081.8
15°	1616.8	1673.2	1733.6	1805.4	1877.9	1930.3	1977.2	2023.5	2058.5	2100.1	2135.6
17.5°	1586.9	1659.5	1735.5	1814.0	1883.7	1944.5	1993.7	2037.8	2074.9	2120.7	2169.0
20°	1569.2	1647.7	1726.9	1810.8	1877.2	1939.7	1987.3	2032.9	2079.2	2139.0	2198.0
22.5°	1544.5	1628.4	1712.4	1792.0	1862.2	1922.4	1971.8	2027.6	2088.4	2156.2	2227.6
25°	1505.4	1592.0	1675.2	1751.0	1819.6	1881.3	1948.4	2023.5	2097.4	2186.7	2289.3
27.5°	1455.9	1539.4	1613.6	1693.8	1761.8	1840.3	1924.1	2005.5	2112.0	2234.8	2363.0
30°	1418.8	1498.1	1568.5	1644.3	1721.5	1808.1	1902.0	1998.0	2124.9	2269.2	2421.6
32.5°	1375.9	1447.6	1517.5	1590.6	1679.6	1774.8	1874.7	1992.1	2143.7	2307.8	2465.6
35°	1301.4	1365.8	1433.6	1514.8	1609.5	1712.8	1840.3	1983.3	2166.5	2343.0	2484.7
37.5°	1223.2	1274.1	1342.2	1427.8	1530.9	1650.5	1795.2	1968.9	2157.1	2315.5	2375.8
40°	1163.1	1210.7	1282.5	1372.5	1474.5	1605.4	1767.8	1946.4	2135.6	2245.7	2241.0
42.5°	1103.5	1151.7	1220.8	1311.3	1417.6	1564.1	1731.3	1916.8	2076.6	2118.5	2031.1
45°	1012.1	1057.0	1124.9	1216.2	1330.2	1483.9	1659.7	1837.6	1939.7	1871.9	1698.7
47.5°	918.9	962.6	1025.5	1114.9	1239.5	1400.3	1566.6	1712.5	1726.9	1581.2	1373.6
50°	857.7	898.7	958.4	1053.7	1174.5	1331.6	1492.0	1606.8	1571.2	1393.4	1179.2
52.5°	798.1	837.5	893.5	983.3	1106.9	1260.7	1403.9	1494.0	1411.7	1222.6	1029.9
55°	710.1	747.7	804.1	886.6	998.7	1139.6	1265.2	1298.0	1177.2	986.6	830.9
57.5°	626.5	654.0	709.7	782.7	890.8	1015.0	1105.0	1099.1	965.8	794.1	682.4
60°	571.2	596.0	649.0	716.1	818.8	930.2	993.3	966.5	831.6	689.9	582.6
62.5°	519.6	542.9	587.3	649.0	737.2	834.1	880.0	843.0	715.6	591.2	505.8
65°	441.6	458.4	494.0	551.0	620.2	687.3	728.2	673.8	561.1	467.1	402.7
67.5°	368.8	383.2	414.9	455.8	503.5	549.8	566.5	515.5	427.8	364.5	319.1
70°	321.5	334.9	356.4	394.7	426.2	459.1	467.1	421.5	348.4	300.0	271.8
72.5°	276.4	288.7	307.5	334.5	356.4	375.3	379.1	336.7	280.7	247.4	225.7
75°	210.8	221.4	233.6	243.7	257.7	261.1	259.8	226.9	196.7	174.5	162.4
77.5°	154.9	159.4	166.7	170.7	171.4	171.2	164.3	143.5	127.9	118.8	113.8
80°	119.5	122.9	124.8	126.1	126.8	120.1	112.8	100.0	94.6	89.3	83.3
82.5°	86.7	89.0	91.0	91.3	87.6	82.1	75.2	68.9	65.1	62.4	60.1
85°	47.0	47.6	47.0	43.7	38.9	36.9	35.6	34.3	33.6	32.9	32.9
87.5°	17.4	16.2	14.0	15.0	15.4	15.3	15.7	15.6	15.4	15.8	16.0
90°	3.6	5.9	8.3	10.5	12.7	14.7	16.7	18.8	20.8	22.2	23.7
92.5°	33.1	34.7	36.2	37.9	40.0	42.4	44.9	47.4	49.9	51.7	53.6
95°	85.0	85.6	86.1	86.7	88.4	91.4	94.2	97.1	100.0	102.0	104.0
97.5°	140.4	140.7	140.9	141.2	143.3	147.2	151.3	155.2	159.2	161.1	163.0
100°	181.8	181.8	181.8	181.8	183.7	187.4	191.1	194.9	198.6	201.3	203.9
102.5°	227.6	228.8	229.9	231.1	232.6	234.5	236.4	238.3	240.2	243.1	245.9
105°	297.5	298.9	300.4	301.9	303.4	305.1	306.9	308.6	310.4	312.1	313.8
107.5°	374.4	375.8	377.3	378.7	380.1	381.4	382.7	384.1	385.4	386.2	387.1
110°	427.4	428.8	430.2	431.7	432.8	433.7	434.5	435.4	436.3	437.1	438.1



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	480.7	481.5	482.2	482.9	483.9	484.9	486.0	487.2	488.3	488.6	489.0
115°	560.9	562.0	563.1	564.3	565.2	565.8	566.3	566.9	567.5	567.1	566.9
117.5°	640.2	640.7	641.2	641.7	642.2	642.7	643.3	643.8	644.4	644.5	644.8
120°	691.0	692.4	693.9	695.3	696.1	696.5	696.7	697.0	697.3	697.3	697.3
122.5°	744.1	744.6	745.1	745.6	746.2	747.0	747.8	748.5	749.2	749.0	748.8
125°	818.5	820.3	822.0	823.7	824.8	825.0	825.3	825.6	825.9	825.3	824.8
127.5°	895.7	896.6	897.6	898.6	899.3	899.7	900.0	900.3	900.7	900.3	900.1
130°	942.9	944.3	945.7	947.2	948.2	948.8	949.3	949.9	950.5	950.2	949.9
132.5°	990.6	992.9	995.3	997.6	998.8	998.7	998.5	998.4	998.3	998.0	997.7
135°	1063.9	1065.7	1067.4	1069.1	1070.1	1070.4	1070.7	1071.0	1071.3	1071.3	1071.3
137.5°	1133.5	1135.1	1136.8	1138.5	1139.6	1140.3	1140.9	1141.5	1142.2	1142.5	1142.9
140°	1177.9	1179.3	1180.8	1182.2	1183.4	1184.2	1185.2	1186.0	1186.9	1187.4	1188.0
142.5°	1222.4	1223.6	1224.8	1226.0	1227.1	1228.2	1229.3	1230.5	1231.5	1231.8	1232.2
145°	1288.0	1289.2	1290.3	1291.5	1292.4	1293.3	1294.2	1295.0	1295.9	1295.9	1295.9
147.5°	1348.2	1348.8	1349.5	1350.1	1350.8	1351.5	1352.2	1352.9	1353.6	1354.3	1355.0
150°	1387.8	1387.6	1387.2	1387.0	1387.4	1388.5	1389.7	1390.9	1392.1	1392.1	1392.1
152.5°	1421.8	1422.2	1422.5	1423.0	1423.4	1423.9	1424.4	1424.8	1425.3	1426.0	1426.7
155°	1472.6	1472.6	1472.6	1472.6	1472.7	1473.0	1473.3	1473.5	1473.9	1475.0	1476.1
157.5°	1517.6	1517.0	1516.3	1515.7	1515.5	1515.8	1516.1	1516.4	1516.7	1517.9	1519.0
160°	1544.4	1543.5	1542.7	1541.8	1541.5	1541.8	1542.1	1542.4	1542.7	1543.8	1545.0
162.5°	1568.5	1567.9	1567.3	1566.6	1566.3	1566.3	1566.4	1566.5	1566.5	1568.0	1569.3
165°	1600.5	1599.9	1599.4	1598.8	1598.6	1599.0	1599.2	1599.5	1599.8	1600.9	1602.1
167.5°	1626.9	1625.8	1624.6	1623.5	1622.9	1622.9	1622.9	1622.9	1622.9	1624.6	1626.3
170°	1641.5	1640.3	1639.2	1638.1	1637.4	1637.4	1637.4	1637.4	1637.4	1639.2	1640.9
172.5°	1651.9	1650.7	1649.6	1648.4	1647.9	1647.9	1647.9	1647.9	1647.9	1649.6	1651.3
175°	1663.5	1662.4	1661.2	1660.1	1659.5	1659.5	1659.5	1659.5	1659.5	1661.2	1663.0
177.5°	1669.7	1668.9	1667.9	1667.0	1666.4	1666.2	1665.9	1665.7	1665.5	1666.9	1668.3
180°	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
0°	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0	1635.0
2.5°	1706.3	1706.3	1715.5	1714.9	1720.9	1718.7	1719.8
5°	1834.3	1845.7	1855.8	1862.4	1872.5	1875.3	1873.9
7.5°	1966.9	1992.3	2004.6	2021.5	2024.6	2033.5	2032.6
10°	2049.1	2073.9	2092.7	2107.5	2114.8	2124.3	2124.9
12.5°	2113.5	2134.6	2151.2	2164.9	2173.9	2176.9	2178.6
15°	2163.8	2187.3	2206.7	2226.2	2237.7	2246.3	2251.1
17.5°	2214.6	2250.8	2285.2	2311.6	2327.5	2340.9	2340.7
20°	2253.8	2295.3	2338.3	2368.5	2399.4	2412.8	2414.8
22.5°	2295.6	2359.2	2414.6	2461.4	2502.0	2515.9	2521.2
25°	2382.6	2465.8	2551.1	2616.8	2663.8	2691.3	2695.4
27.5°	2487.7	2600.3	2690.0	2750.7	2789.7	2810.1	2814.6
30°	2561.8	2665.8	2746.4	2792.1	2810.1	2812.8	2802.7
32.5°	2595.1	2672.8	2705.0	2702.3	2666.8	2643.2	2634.1
35°	2554.4	2538.3	2459.8	2365.9	2294.0	2248.4	2236.3
37.5°	2324.6	2185.7	2041.3	1899.3	1823.7	1785.3	1719.2
40°	2098.1	1900.1	1749.7	1630.2	1545.0	1476.5	1460.4
42.5°	1842.5	1638.1	1487.7	1385.4	1317.3	1270.4	1250.0
45°	1480.6	1304.8	1180.6	1102.1	1049.7	1015.5	1000.1
47.5°	1184.2	1048.1	957.6	899.5	859.6	829.8	821.5
50°	1021.5	912.7	836.3	787.3	757.1	734.3	724.9
52.5°	887.3	799.5	740.7	700.3	671.7	657.5	649.7
55°	732.2	656.4	614.2	581.9	565.8	554.4	549.0
57.5°	598.8	544.1	513.2	490.9	476.0	468.7	466.1
60°	524.2	481.2	453.1	435.6	425.5	416.1	413.5
62.5°	458.1	424.3	402.6	387.3	377.2	373.2	371.5
65°	369.1	347.0	330.9	321.5	313.4	312.1	311.4
67.5°	293.4	280.4	272.0	262.2	259.3	254.6	253.7
70°	251.0	242.3	232.2	228.9	225.5	220.8	221.4
72.5°	212.9	204.1	197.3	192.9	191.7	189.7	191.4
75°	155.7	153.0	150.3	147.0	145.7	145.7	145.0
77.5°	111.2	108.8	105.9	103.9	103.5	100.7	101.8
80°	80.5	77.1	75.9	76.5	74.5	73.8	73.8
82.5°	59.6	58.4	57.1	57.2	56.7	56.1	56.7
85°	32.9	32.2	32.2	31.5	31.5	30.9	30.9
87.5°	16.9	17.7	16.8	16.4	16.6	17.3	18.1
90°	25.1	26.5	27.7	28.6	29.4	30.3	31.2
92.5°	55.5	57.5	58.7	59.4	60.0	60.6	61.3
95°	106.1	108.1	109.3	109.9	110.6	111.1	111.7
97.5°	164.9	166.8	168.0	168.3	168.7	169.0	169.4
100°	206.5	209.1	210.7	211.2	211.8	212.4	212.9
102.5°	248.7	251.5	253.4	254.2	254.9	255.8	256.6
105°	315.6	317.3	318.6	319.4	320.3	321.2	322.0
107.5°	388.0	388.8	389.3	389.2	389.2	389.1	389.0
110°	438.9	439.8	440.1	439.8	439.5	439.2	438.9



TEST NUMBER: P333737-935

CATALOG NUMBER: S125RDIW-S1270D1560U935-4F0-1E-UDD-A1

CANDELA DISTRIBUTION (continued):

	330°	335°	340°	345°	350°	355°	360°
112.5°	489.5	489.8	489.8	489.3	488.8	488.3	487.8
115°	566.6	566.3	566.0	565.8	565.4	565.2	564.9
117.5°	645.1	645.2	644.8	643.6	642.5	641.4	640.2
120°	697.3	697.3	696.7	695.6	694.4	693.3	692.2
122.5°	748.6	748.3	747.8	746.8	745.9	744.9	744.1
125°	824.1	823.5	823.1	822.9	822.5	822.3	822.0
127.5°	899.8	899.5	899.1	898.5	897.9	897.3	896.7
130°	949.7	949.3	948.9	948.4	947.8	947.2	946.7
132.5°	997.5	997.1	996.6	995.8	995.0	994.2	993.3
135°	1071.3	1071.3	1070.7	1069.5	1068.4	1067.2	1066.1
137.5°	1143.2	1143.6	1143.1	1141.6	1140.1	1138.7	1137.2
140°	1188.6	1189.1	1188.7	1187.3	1185.9	1184.4	1182.9
142.5°	1232.5	1233.0	1232.3	1230.9	1229.5	1228.0	1226.6
145°	1295.9	1295.9	1295.5	1294.6	1293.7	1292.9	1292.0
147.5°	1355.6	1356.3	1355.7	1353.8	1351.8	1349.9	1347.9
150°	1392.1	1392.1	1391.7	1391.1	1390.6	1390.0	1389.4
152.5°	1427.4	1428.1	1427.9	1426.8	1425.8	1424.8	1423.7
155°	1477.3	1478.4	1478.3	1476.9	1475.4	1473.9	1472.6
157.5°	1520.2	1521.3	1521.0	1519.0	1517.1	1515.2	1513.3
160°	1546.1	1547.3	1547.1	1545.7	1544.2	1542.8	1541.4
162.5°	1570.7	1572.1	1571.9	1570.3	1568.6	1566.9	1565.2
165°	1603.3	1604.4	1604.1	1602.4	1600.7	1599.0	1597.2
167.5°	1628.1	1629.8	1629.8	1628.0	1626.3	1624.4	1622.6
170°	1642.6	1644.3	1644.3	1642.2	1640.2	1638.1	1636.2
172.5°	1653.0	1654.8	1654.8	1652.9	1651.1	1649.3	1647.6
175°	1664.7	1666.5	1666.3	1664.3	1662.2	1660.3	1658.2
177.5°	1669.7	1671.0	1670.9	1669.3	1667.7	1666.0	1664.5
180°	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6	1668.6

(END OF REPORT)