

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: NEO-RAY

Report Number: P333696-935

Luminaire Tested: **S125RDIW-S850D1560U935-4F0-1E-UDD-A**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P333696-935  
REPORT IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1807-864-7,  
Test Lab: INNOVATION CENTER  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: NEO-RAY  
Catalog Number: S125RDIW-S850D1560U935-4F0-1E-UDD-A  
Description: DEFINE 5 DIRECT-INDIRECT WALL MOUNT LED LUMINAIRE  
DOWNLIGHT 850 LUMENS PER FOOT, ASYMMETRIC DIFFUSER, REGRESSED HOUSING  
UPLIGHT 1560 LUMENS PER FOOT, NO LENS  
Light Source: -  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 8194.5 lumens  
Efficiency: N/A  
Efficacy: 120.3 lumens/watt  
Spacing Criteria (0/90/45): 1.4 / 1.22 / 1.47  
Luminous Opening: Rectangular (W 4' x L: 0.42' x H: 0')  
CIE Type: Semi-Indirect


Input Watts (W): 68.1  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

### Luminous Intensity Polar Plot





TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				20
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	103	103	103	103	93	93	93	93	75	75	75	58	58	58	42	42	42	34			34
1	95	90	87	83	85	82	79	76	66	64	62	51	50	48	37	37	36	30			30
2	86	79	73	69	78	72	67	63	58	55	52	45	43	41	33	32	31	25			25
3	79	70	63	57	71	63	57	53	51	47	44	40	37	35	30	28	26	22			22
4	72	62	54	49	65	56	50	45	46	41	37	36	33	30	27	25	23	19			19
5	66	55	47	42	60	50	43	38	41	36	32	32	29	26	24	22	20	16			16
6	61	49	42	36	55	45	38	33	37	32	28	29	25	23	22	19	18	14			14
7	56	45	37	32	51	41	34	29	33	28	25	26	23	20	20	18	16	13			13
8	52	40	33	28	47	37	30	26	30	25	22	24	21	18	18	16	14	12			12
9	49	37	30	25	44	34	27	23	28	23	19	22	19	16	17	14	13	10			10
10	45	34	27	22	41	31	25	20	25	21	17	20	17	14	16	13	12	9			9

**AVERAGE LUMINANCE (cd/sqm):**

	0°	90°	180°	270°
0°	7034	7034	7034	7034
5°	8092	7043	6220	7043
10°	9282	7007	5488	7007
15°	10026	6935	4878	6935
20°	11056	6852	4504	6852
25°	12794	6741	4180	6741
30°	13923	6624	3967	6624
35°	11744	6489	3772	6489
40°	8201	6246	3603	6246
45°	6085	5917	3438	5917
50°	4851	5574	3297	5574
55°	4118	5150	3171	5150
60°	3557	4770	2968	4770
65°	3169	4358	2555	4358
70°	2787	3994	2330	3994
75°	2410	3459	2186	3459
80°	1830	2912	1830	2912
85°	1526	2282	1719	2282



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	104.4	1.3
10°-20°	306.1	3.7
20°-30°	485.3	5.9
30°-40°	585.2	7.1
40°-50°	522.6	6.4
50°-60°	400.8	4.9
60°-70°	260.4	3.2
70°-80°	126.6	1.5
80°-90°	33.9	0.4
90°-100°	63.5	0.8
100°-110°	391.6	4.8
110°-120°	710.2	8.7
120°-130°	911.5	11.1
130°-140°	980.4	12.0
140°-150°	920.2	11.2
150°-160°	744.4	9.1
160°-170°	481.4	5.9
170°-180°	166.0	2.0
0°-30°	895.8	10.9
0°-40°	1481.0	18.1
0°-60°	2404.3	29.3
0°-90°	2825.2	34.5
90°-120°	1165.3	14.2
90°-150°	3977.4	48.5
90°-180°	5369.0	65.5
0°-180°	8194.5	100.0

**CANDELA DISTRIBUTION:**

	0°	90°	180°	270°	360°	Flux
0°	1089	1089	1089	1089	1089	
5°	1248	1086	959	1086	1248	125
15°	1500	1037	730	1037	1500	430
25°	1795	946	587	946	1795	824
35°	1490	823	478	823	1490	900
45°	666	648	376	648	666	532
55°	366	457	282	457	366	332
65°	207	285	167	285	207	206
75°	97	139	88	139	97	103
85°	21	31	23	31	21	24
90°	31	1	31	1	31	14
95°	27	74	27	74	27	22
105°	385	381	385	381	385	348
115°	710	716	710	716	710	705
125°	1017	1017	1017	1017	1017	905
135°	1264	1269	1264	1269	1264	975
145°	1467	1471	1467	1471	1467	916
155°	1608	1620	1608	1620	1608	741
165°	1700	1710	1700	1710	1700	480
175°	1741	1748	1741	1748	1741	166
180°	1748	1748	1748	1748	1748	



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (FULL):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
0°	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1
2.5°	1145.6	1144.9	1146.3	1142.4	1142.7	1136.6	1136.6	1132.0	1125.9	1121.3	1119.1
5°	1248.2	1249.1	1247.3	1240.6	1236.1	1229.4	1221.8	1208.4	1197.2	1186.5	1178.0
7.5°	1353.9	1354.5	1348.7	1346.6	1335.3	1327.1	1310.2	1291.9	1275.7	1255.2	1239.5
10°	1415.4	1415.0	1408.8	1403.8	1394.0	1381.5	1364.9	1343.4	1323.4	1301.0	1279.5
12.5°	1451.2	1450.0	1448.0	1442.1	1433.0	1421.9	1407.8	1386.7	1361.9	1337.5	1312.4
15°	1499.5	1496.3	1490.6	1482.9	1470.0	1457.0	1441.4	1422.6	1398.9	1371.1	1347.9
17.5°	1559.2	1559.3	1550.4	1539.8	1522.2	1499.3	1475.2	1444.8	1412.6	1382.2	1357.4
20°	1608.6	1607.2	1598.3	1577.7	1557.6	1529.0	1501.2	1464.1	1424.8	1385.0	1354.2
22.5°	1679.4	1675.9	1666.6	1639.6	1608.4	1571.6	1529.1	1483.8	1436.2	1391.1	1350.7
25°	1795.4	1792.8	1774.4	1743.2	1699.4	1642.5	1587.1	1525.0	1456.6	1397.1	1347.9
27.5°	1874.8	1871.9	1858.3	1832.3	1791.9	1732.2	1657.1	1574.1	1488.7	1406.9	1335.9
30°	1867.0	1873.7	1871.9	1859.8	1829.5	1775.8	1706.5	1613.1	1511.6	1415.4	1330.9
32.5°	1754.6	1760.7	1776.4	1800.1	1801.9	1780.5	1728.6	1642.4	1537.3	1428.0	1327.0
35°	1489.6	1497.7	1528.1	1576.0	1638.5	1690.8	1701.6	1655.1	1560.7	1443.1	1321.1
37.5°	1145.2	1189.2	1214.8	1265.2	1359.7	1456.0	1548.5	1582.5	1542.4	1436.9	1311.6
40°	972.8	983.5	1029.2	1086.0	1165.5	1265.7	1397.6	1492.8	1495.9	1422.6	1296.5
42.5°	832.6	846.2	877.5	922.8	991.0	1091.1	1227.3	1353.0	1411.2	1383.3	1276.9
45°	666.2	676.4	699.2	734.1	786.4	869.1	986.3	1131.5	1246.9	1292.0	1224.1
47.5°	547.3	552.8	572.7	599.2	637.9	698.2	788.8	915.0	1053.3	1150.3	1140.7
50°	482.8	489.1	504.3	524.4	557.1	608.0	680.4	785.5	928.2	1046.6	1070.3
52.5°	432.7	438.0	447.5	466.5	493.4	532.5	591.0	686.0	814.4	940.4	995.1
55°	365.7	369.3	376.9	387.6	409.1	437.2	487.8	553.5	657.2	784.2	864.6
57.5°	310.5	312.2	317.1	327.0	341.8	362.4	398.9	454.6	529.0	643.3	732.1
60°	275.4	277.2	283.4	290.2	301.8	320.6	349.1	388.1	459.6	553.9	643.8
62.5°	247.5	248.6	251.2	258.0	268.1	282.7	305.1	336.9	393.8	476.6	561.5
65°	207.4	207.9	208.8	214.1	220.4	231.2	245.9	268.2	311.2	373.8	448.8
67.5°	169.0	169.6	172.7	174.6	181.2	186.8	195.4	212.6	242.8	285.0	343.4
70°	147.6	147.1	150.2	152.5	154.7	161.4	167.2	181.1	199.8	232.0	280.8
72.5°	127.5	126.3	127.7	128.5	131.5	136.0	141.8	150.3	164.8	186.9	224.3
75°	96.6	97.0	97.0	97.9	100.1	101.9	103.8	108.2	116.2	131.0	151.1
77.5°	67.8	67.1	69.0	69.2	70.5	72.5	74.0	75.9	79.1	85.2	95.6
80°	49.2	49.2	49.6	51.0	50.5	51.4	53.6	55.4	59.5	63.0	66.6
82.5°	37.7	37.4	37.8	38.1	38.0	38.9	39.7	40.0	41.6	43.4	45.9
85°	20.6	20.6	21.0	21.0	21.4	21.4	21.9	21.9	21.9	22.4	22.8
87.5°	14.1	13.5	13.0	12.8	13.0	13.5	12.9	12.2	12.0	11.6	11.6
90°	31.1	30.2	29.4	28.5	27.6	26.5	25.1	23.6	22.2	20.8	18.7
92.5°	29.0	28.7	28.2	27.8	27.4	26.5	25.1	23.6	22.2	20.8	18.9
95°	27.2	27.2	27.2	27.2	27.2	26.5	25.1	23.6	22.2	20.8	31.7
97.5°	27.2	27.2	27.2	27.2	27.2	31.3	39.4	47.5	55.6	63.8	85.4
100°	27.2	28.4	29.5	30.7	31.9	53.9	96.8	139.7	182.6	225.5	224.4
102.5°	163.1	182.6	202.2	221.8	241.4	255.3	263.4	271.5	279.7	287.7	287.1
105°	385.0	385.2	385.6	385.8	386.1	386.2	386.2	386.2	386.2	386.2	386.2
107.5°	485.3	486.1	487.0	487.8	488.7	489.1	489.0	489.0	489.0	488.9	488.4
110°	554.7	554.5	554.1	553.9	553.6	553.9	554.7	555.6	556.5	557.3	556.7



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°
112.5°	616.9	617.3	617.8	618.2	618.5	619.3	620.4	621.5	622.6	623.7	623.4
115°	710.2	712.0	713.7	715.5	717.2	718.6	719.8	720.9	722.0	723.2	723.0
117.5°	809.8	810.5	811.3	812.1	812.8	813.9	815.5	816.9	818.4	819.9	818.8
120°	871.0	872.5	873.8	875.3	876.8	877.8	878.3	878.9	879.5	880.0	879.2
122.5°	929.0	930.7	932.4	934.1	935.7	936.9	937.5	938.0	938.6	939.2	938.7
125°	1017.4	1018.3	1019.2	1020.0	1020.9	1021.9	1023.0	1024.2	1025.4	1026.5	1026.5
127.5°	1091.8	1094.0	1096.1	1098.2	1100.4	1101.7	1102.4	1103.0	1103.6	1104.3	1104.5
130°	1145.7	1147.2	1148.7	1150.1	1151.5	1152.7	1153.6	1154.4	1155.3	1156.2	1155.8
132.5°	1195.5	1197.0	1198.4	1199.9	1201.3	1202.1	1202.3	1202.5	1202.6	1202.8	1203.4
135°	1263.7	1265.4	1267.1	1268.9	1270.6	1271.8	1272.4	1272.9	1273.5	1274.1	1274.6
137.5°	1332.1	1333.6	1335.2	1336.6	1338.2	1338.9	1338.7	1338.6	1338.5	1338.3	1338.9
140°	1372.6	1374.3	1376.1	1377.8	1379.5	1380.1	1379.5	1378.9	1378.4	1377.8	1378.0
142.5°	1410.9	1412.6	1414.4	1416.1	1417.9	1418.7	1418.6	1418.4	1418.3	1418.2	1417.8
145°	1467.2	1469.0	1470.7	1472.4	1474.1	1474.8	1474.5	1474.3	1473.9	1473.7	1473.7
147.5°	1513.6	1515.7	1517.8	1519.8	1521.9	1522.8	1522.4	1522.1	1521.7	1521.4	1521.0
150°	1543.7	1546.0	1548.3	1550.6	1552.9	1553.8	1553.2	1552.6	1552.0	1551.4	1550.8
152.5°	1571.7	1573.7	1575.8	1577.9	1579.9	1580.7	1580.1	1579.6	1579.0	1578.4	1577.9
155°	1608.4	1610.8	1613.1	1615.4	1617.6	1618.4	1617.6	1616.7	1615.8	1615.0	1614.4
157.5°	1639.3	1641.6	1643.9	1646.2	1648.6	1649.2	1648.3	1647.4	1646.5	1645.5	1645.5
160°	1659.1	1661.3	1663.6	1665.9	1668.3	1668.8	1667.7	1666.5	1665.3	1664.2	1663.9
162.5°	1676.6	1679.2	1681.7	1684.3	1686.8	1687.2	1685.7	1684.0	1682.4	1680.8	1680.5
165°	1700.5	1702.8	1705.1	1707.4	1709.7	1710.0	1708.3	1706.5	1704.8	1703.1	1702.8
167.5°	1717.1	1719.7	1722.3	1724.8	1727.4	1727.7	1725.6	1723.5	1721.5	1719.4	1719.2
170°	1726.4	1729.0	1731.6	1734.2	1736.8	1736.9	1734.7	1732.3	1730.0	1727.7	1727.4
172.5°	1732.7	1735.3	1737.8	1740.4	1743.0	1743.3	1741.2	1739.1	1737.1	1735.0	1734.5
175°	1740.7	1743.3	1745.8	1748.4	1751.0	1751.2	1748.9	1746.5	1744.3	1742.0	1741.7
177.5°	1745.3	1747.1	1749.0	1750.8	1752.7	1752.8	1751.2	1749.6	1748.0	1746.4	1746.1
180°	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
0°	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1
2.5°	1119.1	1116.6	1112.0	1107.7	1102.3	1097.7	1094.4	1090.5	1085.5	1079.4	1074.4
5°	1168.6	1158.8	1145.8	1134.7	1120.3	1109.2	1097.6	1086.4	1075.2	1060.9	1048.4
7.5°	1223.6	1203.2	1183.5	1158.6	1136.1	1115.9	1096.7	1077.1	1058.0	1037.7	1018.0
10°	1257.1	1232.6	1205.3	1174.0	1145.4	1118.1	1093.1	1068.5	1042.6	1019.8	995.1
12.5°	1288.7	1256.9	1225.7	1186.2	1151.8	1118.5	1086.7	1056.0	1028.3	998.7	972.3
15°	1317.1	1285.8	1250.9	1202.6	1154.8	1114.6	1077.0	1037.2	1002.8	969.7	940.2
17.5°	1328.1	1295.3	1254.7	1208.3	1156.1	1105.4	1057.0	1013.4	972.9	934.4	901.2
20°	1323.8	1292.0	1250.4	1206.2	1150.3	1097.6	1045.3	997.0	951.8	911.1	875.8
22.5°	1313.4	1280.6	1240.4	1193.7	1140.7	1084.7	1028.8	977.3	930.0	887.9	849.4
25°	1297.9	1253.2	1212.0	1166.4	1115.9	1060.5	1002.8	946.0	895.5	852.6	810.5
27.5°	1281.7	1225.9	1173.5	1128.3	1074.9	1025.4	969.8	911.5	858.5	814.8	771.6
30°	1267.0	1204.5	1146.8	1095.4	1044.8	997.9	945.1	888.3	833.8	788.7	744.9
32.5°	1248.8	1182.2	1118.9	1059.5	1010.8	964.2	916.5	862.2	809.1	762.5	718.0
35°	1225.9	1140.9	1072.1	1009.0	954.9	909.8	866.9	823.0	769.8	721.6	678.2
37.5°	1195.8	1099.4	1019.8	951.1	894.1	848.7	814.9	774.8	726.3	680.0	639.7
40°	1177.6	1069.4	982.2	914.3	854.4	806.5	774.8	740.8	696.5	653.2	612.9
42.5°	1153.3	1041.9	944.3	873.5	813.2	767.2	735.0	705.4	668.3	627.4	584.4
45°	1105.6	988.5	886.1	810.1	749.3	704.1	674.2	647.8	619.7	582.1	544.5
47.5°	1043.5	932.8	825.6	742.7	683.1	641.2	612.2	591.3	571.2	539.2	502.7
50°	993.9	887.0	782.4	701.9	638.4	598.7	571.4	554.8	536.5	507.4	477.0
52.5°	935.2	839.8	737.3	655.0	595.1	557.8	531.7	515.1	500.0	476.3	447.4
55°	842.7	759.1	665.2	590.6	535.6	498.0	473.0	457.4	448.4	428.3	405.5
57.5°	736.1	676.1	593.3	521.3	472.8	435.7	417.3	404.0	393.9	379.6	363.6
60°	661.7	619.7	545.4	477.0	432.3	397.0	380.5	369.3	359.9	347.8	335.3
62.5°	586.2	555.6	491.0	432.3	391.2	361.6	346.1	336.0	325.2	317.1	304.9
65°	485.1	457.8	413.1	367.0	329.1	305.3	294.2	285.2	278.5	269.6	261.1
67.5°	377.3	366.3	335.4	303.7	276.4	255.3	245.6	239.4	231.4	225.9	220.2
70°	311.2	305.8	283.9	262.9	237.4	223.1	214.1	211.5	201.6	196.3	192.3
72.5°	252.5	250.0	237.4	222.8	204.8	192.3	184.1	181.1	174.8	170.5	167.9
75°	173.0	173.9	171.7	162.3	155.6	147.6	140.3	138.6	134.1	130.5	128.3
77.5°	109.4	114.0	114.2	113.7	111.1	106.2	103.1	101.9	97.5	96.1	95.6
80°	75.1	80.0	84.5	84.0	83.2	81.8	79.6	78.3	76.0	74.6	73.8
82.5°	50.1	54.7	58.4	60.8	60.6	59.3	57.8	57.2	56.7	55.7	55.5
85°	23.7	24.6	25.9	29.1	31.3	31.8	31.3	30.8	29.5	30.0	30.4
87.5°	11.5	11.2	11.1	10.7	9.9	11.2	11.8	11.7	11.5	11.2	10.9
90°	16.7	14.7	12.7	10.5	8.2	5.9	3.6	1.3	3.6	5.9	8.2
92.5°	17.1	15.4	13.6	13.5	15.2	16.7	18.3	20.0	18.3	16.7	15.2
95°	42.6	53.6	64.5	70.4	71.3	72.2	73.0	73.9	73.0	72.2	71.3
97.5°	107.1	128.7	150.4	160.5	158.9	157.3	155.8	154.2	155.8	157.3	158.9
100°	223.3	222.1	220.9	219.9	219.0	218.2	217.3	216.5	217.3	218.2	219.0
102.5°	286.4	285.7	285.0	284.0	283.0	281.9	280.8	279.7	280.8	281.9	283.0
105°	386.2	386.2	386.2	385.6	384.5	383.4	382.2	381.1	382.2	383.4	384.5
107.5°	487.8	487.2	486.6	486.3	486.3	486.3	486.3	486.3	486.3	486.3	486.3
110°	556.2	555.6	555.0	554.7	554.7	554.7	554.7	554.7	554.7	554.7	554.7





TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	55°	60°	65°	70°	75°	80°	85°	90°	95°	100°	105°
112.5°	623.0	622.7	622.3	621.8	621.1	620.4	619.7	619.1	619.7	620.4	621.1
115°	722.6	722.4	722.0	721.2	719.8	718.3	716.9	715.5	716.9	718.3	719.8
117.5°	817.7	816.7	815.5	815.0	815.1	815.1	815.2	815.3	815.2	815.1	815.1
120°	878.3	877.4	876.6	876.3	876.6	876.9	877.2	877.4	877.2	876.9	876.6
122.5°	938.3	938.0	937.5	936.8	935.7	934.6	933.5	932.5	933.5	934.6	935.7
125°	1026.5	1026.5	1026.5	1025.5	1023.5	1021.5	1019.4	1017.4	1019.4	1021.5	1023.5
127.5°	1104.7	1104.8	1105.0	1104.3	1102.9	1101.5	1100.0	1098.5	1100.0	1101.5	1102.9
130°	1155.5	1155.3	1154.9	1154.1	1152.7	1151.2	1149.8	1148.3	1149.8	1151.2	1152.7
132.5°	1204.0	1204.7	1205.3	1204.8	1203.2	1201.4	1199.8	1198.1	1199.8	1201.4	1203.2
135°	1275.2	1275.8	1276.3	1275.8	1274.1	1272.4	1270.6	1268.9	1270.6	1272.4	1274.1
137.5°	1339.4	1339.9	1340.4	1340.0	1338.4	1337.0	1335.4	1333.9	1335.4	1337.0	1338.4
140°	1378.4	1378.6	1378.9	1378.8	1378.2	1377.6	1377.1	1376.5	1377.1	1377.6	1378.2
142.5°	1417.4	1417.0	1416.6	1416.2	1415.8	1415.5	1415.1	1414.8	1415.1	1415.5	1415.8
145°	1473.7	1473.7	1473.7	1473.4	1472.8	1472.2	1471.6	1471.1	1471.6	1472.2	1472.8
147.5°	1520.7	1520.4	1520.0	1519.8	1520.0	1520.1	1520.2	1520.4	1520.2	1520.1	1520.0
150°	1550.3	1549.7	1549.1	1549.1	1549.7	1550.3	1550.8	1551.4	1550.8	1550.3	1549.7
152.5°	1577.3	1576.7	1576.1	1576.4	1577.7	1579.0	1580.3	1581.5	1580.3	1579.0	1577.7
155°	1613.8	1613.3	1612.7	1613.3	1615.0	1616.7	1618.4	1620.1	1618.4	1616.7	1615.0
157.5°	1645.5	1645.4	1645.3	1645.8	1646.8	1647.9	1648.9	1649.9	1648.9	1647.9	1646.8
160°	1663.6	1663.4	1663.0	1663.8	1665.5	1667.2	1669.0	1670.7	1669.0	1667.2	1665.5
162.5°	1680.2	1679.9	1679.6	1680.3	1682.0	1683.9	1685.6	1687.3	1685.6	1683.9	1682.0
165°	1702.5	1702.2	1701.9	1702.6	1704.3	1706.1	1707.9	1709.6	1707.9	1706.1	1704.3
167.5°	1718.8	1718.6	1718.3	1719.0	1720.8	1722.6	1724.4	1726.1	1724.4	1722.6	1720.8
170°	1727.2	1726.8	1726.6	1727.4	1729.4	1731.5	1733.5	1735.5	1733.5	1731.5	1729.4
172.5°	1734.0	1733.5	1732.9	1733.6	1735.7	1737.7	1739.7	1741.7	1739.7	1737.7	1735.7
175°	1741.4	1741.1	1740.9	1741.5	1743.3	1745.0	1746.7	1748.4	1746.7	1745.0	1743.3
177.5°	1745.9	1745.7	1745.4	1746.0	1747.4	1748.8	1750.2	1751.5	1750.2	1748.8	1747.4
180°	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
0°	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1
2.5°	1070.8	1065.8	1062.2	1055.1	1050.1	1047.9	1044.0	1042.9	1046.9	1044.0	1043.6
5°	1039.0	1026.1	1015.7	1005.5	994.3	987.1	976.4	974.7	971.9	967.9	967.0
7.5°	1000.8	984.0	970.7	953.7	938.9	927.0	913.6	907.3	903.8	898.6	891.7
10°	975.1	954.9	937.0	920.1	901.7	887.0	873.6	863.3	856.6	850.3	847.7
12.5°	949.7	929.2	906.3	885.7	865.3	848.7	833.9	827.2	819.8	812.4	806.2
15°	910.2	883.0	857.9	834.2	816.8	798.9	784.6	774.8	763.6	760.4	748.4
17.5°	868.4	841.6	812.4	787.4	767.2	747.5	731.8	720.6	712.2	700.7	695.1
20°	842.3	810.5	782.0	759.1	736.8	713.5	697.4	688.0	680.0	670.6	666.2
22.5°	814.4	783.3	754.1	727.3	704.6	681.7	670.3	660.5	651.3	642.7	636.8
25°	773.4	742.2	711.3	683.5	659.9	643.3	629.9	618.7	613.8	605.4	599.1
27.5°	733.0	699.6	667.6	640.1	621.5	605.1	594.1	585.2	576.4	568.9	563.5
30°	706.8	672.9	638.0	616.0	596.4	580.7	568.7	560.2	553.5	546.7	542.8
32.5°	680.7	645.7	614.8	591.0	572.4	559.0	546.5	538.4	531.3	523.9	519.2
35°	638.9	603.1	578.1	554.8	536.5	524.0	515.5	503.9	498.0	492.7	487.8
37.5°	599.9	566.7	539.6	519.3	503.3	490.9	479.9	473.6	466.5	461.7	457.5
40°	571.4	541.0	516.3	494.9	483.3	469.4	459.2	451.1	445.7	439.5	435.0
42.5°	545.6	517.4	493.4	474.2	459.7	448.0	438.1	430.0	423.2	418.7	415.0
45°	509.2	481.0	457.8	439.9	426.5	415.3	405.0	401.1	392.1	386.8	385.0
47.5°	471.6	446.3	424.0	407.4	393.7	383.1	373.5	365.2	360.3	355.1	352.2
50°	446.2	422.1	401.1	385.0	371.5	359.9	350.9	345.6	338.9	334.0	330.4
52.5°	420.8	398.5	377.5	362.1	350.4	338.8	328.8	323.4	317.1	313.9	311.4
55°	384.5	360.8	342.9	327.7	315.6	304.9	295.5	290.2	286.1	283.0	282.1
57.5°	343.4	324.6	308.0	294.3	281.7	271.6	263.4	258.3	254.8	254.3	251.6
60°	316.5	299.5	284.3	269.6	258.8	249.4	242.3	236.5	232.9	232.5	231.6
62.5°	289.7	273.5	259.3	246.3	236.7	227.6	220.8	214.3	212.2	209.9	208.0
65°	249.9	235.1	223.5	213.3	202.9	195.4	188.6	184.6	179.7	177.0	172.1
67.5°	210.9	199.4	188.2	179.5	171.5	164.3	158.7	152.7	149.4	147.2	143.7
70°	185.1	176.2	165.0	155.6	149.3	143.5	139.1	132.3	130.1	128.3	126.5
72.5°	160.7	152.9	143.5	136.0	129.7	124.2	119.0	115.9	113.7	111.8	110.8
75°	126.5	118.9	110.9	105.5	101.1	96.6	93.8	91.6	90.7	90.3	88.5
77.5°	92.9	88.9	82.4	78.2	75.2	73.4	71.0	69.8	69.7	67.8	67.2
80°	71.1	68.9	63.5	61.7	59.5	57.7	56.3	54.1	51.8	51.0	49.6
82.5°	52.9	50.6	48.5	45.6	43.7	42.6	41.3	40.5	40.8	39.5	38.9
85°	28.2	25.9	25.1	24.6	23.7	24.6	24.1	23.7	23.2	22.8	23.2
87.5°	11.0	11.5	11.5	12.7	12.0	12.7	13.0	12.9	13.3	13.5	13.4
90°	10.5	12.7	14.7	16.7	18.7	20.8	22.2	23.6	25.1	26.5	27.6
92.5°	13.5	13.6	15.4	17.1	18.9	20.8	22.2	23.6	25.1	26.5	27.4
95°	70.4	64.5	53.6	42.6	31.7	20.8	22.2	23.6	25.1	26.5	27.2
97.5°	160.5	150.4	128.7	107.1	85.4	63.8	55.6	47.5	39.4	31.3	27.2
100°	219.9	220.9	222.1	223.3	224.4	225.5	182.6	139.7	96.8	53.9	31.9
102.5°	284.0	285.0	285.7	286.4	287.1	287.7	279.7	271.5	263.4	255.3	241.4
105°	385.6	386.2	386.2	386.2	386.2	386.2	386.2	386.2	386.2	386.2	386.1
107.5°	486.3	486.6	487.2	487.8	488.4	488.9	489.0	489.0	489.0	489.1	488.7
110°	554.7	555.0	555.6	556.2	556.7	557.3	556.5	555.6	554.7	553.9	553.6



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	110°	115°	120°	125°	130°	135°	140°	145°	150°	155°	160°
112.5°	621.8	622.3	622.7	623.0	623.4	623.7	622.6	621.5	620.4	619.3	618.5
115°	721.2	722.0	722.4	722.6	723.0	723.2	722.0	720.9	719.8	718.6	717.2
117.5°	815.0	815.5	816.7	817.7	818.8	819.9	818.4	816.9	815.5	813.9	812.8
120°	876.3	876.6	877.4	878.3	879.2	880.0	879.5	878.9	878.3	877.8	876.8
122.5°	936.8	937.5	938.0	938.3	938.7	939.2	938.6	938.0	937.5	936.9	935.7
125°	1025.5	1026.5	1026.5	1026.5	1026.5	1026.5	1025.4	1024.2	1023.0	1021.9	1020.9
127.5°	1104.3	1105.0	1104.8	1104.7	1104.5	1104.3	1103.6	1103.0	1102.4	1101.7	1100.4
130°	1154.1	1154.9	1155.3	1155.5	1155.8	1156.2	1155.3	1154.4	1153.6	1152.7	1151.5
132.5°	1204.8	1205.3	1204.7	1204.0	1203.4	1202.8	1202.6	1202.5	1202.3	1202.1	1201.3
135°	1275.8	1276.3	1275.8	1275.2	1274.6	1274.1	1273.5	1272.9	1272.4	1271.8	1270.6
137.5°	1340.0	1340.4	1339.9	1339.4	1338.9	1338.3	1338.5	1338.6	1338.7	1338.9	1338.2
140°	1378.8	1378.9	1378.6	1378.4	1378.0	1377.8	1378.4	1378.9	1379.5	1380.1	1379.5
142.5°	1416.2	1416.6	1417.0	1417.4	1417.8	1418.2	1418.3	1418.4	1418.6	1418.7	1417.9
145°	1473.4	1473.7	1473.7	1473.7	1473.7	1473.7	1473.9	1474.3	1474.5	1474.8	1474.1
147.5°	1519.8	1520.0	1520.4	1520.7	1521.0	1521.4	1521.7	1522.1	1522.4	1522.8	1521.9
150°	1549.1	1549.1	1549.7	1550.3	1550.8	1551.4	1552.0	1552.6	1553.2	1553.8	1552.9
152.5°	1576.4	1576.1	1576.7	1577.3	1577.9	1578.4	1579.0	1579.6	1580.1	1580.7	1579.9
155°	1613.3	1612.7	1613.3	1613.8	1614.4	1615.0	1615.8	1616.7	1617.6	1618.4	1617.6
157.5°	1645.8	1645.3	1645.4	1645.5	1645.5	1645.5	1646.5	1647.4	1648.3	1649.2	1648.6
160°	1663.8	1663.0	1663.4	1663.6	1663.9	1664.2	1665.3	1666.5	1667.7	1668.8	1668.3
162.5°	1680.3	1679.6	1679.9	1680.2	1680.5	1680.8	1682.4	1684.0	1685.7	1687.2	1686.8
165°	1702.6	1701.9	1702.2	1702.5	1702.8	1703.1	1704.8	1706.5	1708.3	1710.0	1709.7
167.5°	1719.0	1718.3	1718.6	1718.8	1719.2	1719.4	1721.5	1723.5	1725.6	1727.7	1727.4
170°	1727.4	1726.6	1726.8	1727.2	1727.4	1727.7	1730.0	1732.3	1734.7	1736.9	1736.8
172.5°	1733.6	1732.9	1733.5	1734.0	1734.5	1735.0	1737.1	1739.1	1741.2	1743.3	1743.0
175°	1741.5	1740.9	1741.1	1741.4	1741.7	1742.0	1744.3	1746.5	1748.9	1751.2	1751.0
177.5°	1746.0	1745.4	1745.7	1745.9	1746.1	1746.4	1748.0	1749.6	1751.2	1752.8	1752.7
180°	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
0°	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1
2.5°	1043.3	1039.4	1038.3	1039.7	1038.3	1039.4	1043.3	1043.6	1044.0	1046.9	1042.9
5°	962.5	958.1	960.3	959.4	960.3	958.1	962.5	967.0	967.9	971.9	974.7
7.5°	891.6	886.0	880.1	882.0	880.1	886.0	891.6	891.7	898.6	903.8	907.3
10°	841.8	837.4	834.7	836.9	834.7	837.4	841.8	847.7	850.3	856.6	863.3
12.5°	800.0	797.3	795.0	794.0	795.0	797.3	800.0	806.2	812.4	819.8	827.2
15°	743.0	737.7	735.5	729.6	735.5	737.7	743.0	748.4	760.4	763.6	774.8
17.5°	690.5	688.8	682.9	680.4	682.9	688.8	690.5	695.1	700.7	712.2	720.6
20°	659.4	657.6	651.9	655.4	651.9	657.6	659.4	666.2	670.6	680.0	688.0
22.5°	633.7	629.7	627.8	626.8	627.8	629.7	633.7	636.8	642.7	651.3	660.5
25°	597.3	591.5	589.3	586.6	589.3	591.5	597.3	599.1	605.4	613.8	618.7
27.5°	561.0	557.8	554.9	554.2	554.9	557.8	561.0	563.5	568.9	576.4	585.2
30°	537.4	534.3	532.0	532.0	532.0	534.3	537.4	542.8	546.7	553.5	560.2
32.5°	516.3	513.8	511.6	511.3	511.6	513.8	516.3	519.2	523.9	531.3	538.4
35°	485.5	482.0	481.0	478.4	481.0	482.0	485.5	487.8	492.7	498.0	503.9
37.5°	453.6	450.6	450.6	450.3	450.6	450.6	453.6	457.5	461.7	466.5	473.6
40°	433.3	431.0	430.5	427.4	430.5	431.0	433.3	435.0	439.5	445.7	451.1
42.5°	411.4	410.3	408.7	407.3	408.7	410.3	411.4	415.0	418.7	423.2	430.0
45°	381.8	378.7	378.7	376.4	378.7	378.7	381.8	385.0	386.8	392.1	401.1
47.5°	351.2	348.8	349.0	346.7	349.0	348.8	351.2	352.2	355.1	360.3	365.2
50°	330.8	329.5	329.1	328.1	329.1	329.5	330.8	330.4	334.0	338.9	345.6
52.5°	310.5	309.8	311.5	309.5	311.5	309.8	310.5	311.4	313.9	317.1	323.4
55°	283.0	281.6	284.3	281.6	284.3	281.6	283.0	282.1	283.0	286.1	290.2
57.5°	251.4	250.2	252.6	251.2	252.6	250.2	251.4	251.6	254.3	254.8	258.3
60°	230.7	228.0	229.4	229.8	229.4	228.0	230.7	231.6	232.5	232.9	236.5
62.5°	206.0	204.4	205.3	203.4	205.3	204.4	206.0	208.0	209.9	212.2	214.3
65°	171.3	169.9	168.1	167.2	168.1	169.9	171.3	172.1	177.0	179.7	184.6
67.5°	143.9	140.7	140.6	141.3	140.6	140.7	143.9	143.7	147.2	149.4	152.7
70°	123.8	123.8	123.4	123.4	123.4	123.8	123.8	126.5	128.3	130.1	132.3
72.5°	109.9	109.5	108.7	108.4	108.7	109.5	109.9	110.8	111.8	113.7	115.9
75°	88.5	88.9	88.1	87.6	88.1	88.9	88.5	88.5	90.3	90.7	91.6
77.5°	65.3	63.5	64.5	63.5	64.5	63.5	65.3	67.2	67.8	69.7	69.8
80°	49.6	49.2	50.5	49.2	50.5	49.2	49.6	49.6	51.0	51.8	54.1
82.5°	39.3	38.8	39.4	38.5	39.4	38.8	39.3	38.9	39.5	40.8	40.5
85°	23.7	23.2	22.8	23.2	22.8	23.2	23.7	23.2	22.8	23.2	23.7
87.5°	13.9	13.8	13.9	14.1	13.9	13.8	13.9	13.4	13.5	13.3	12.9
90°	28.5	29.4	30.2	31.1	30.2	29.4	28.5	27.6	26.5	25.1	23.6
92.5°	27.8	28.2	28.7	29.0	28.7	28.2	27.8	27.4	26.5	25.1	23.6
95°	27.2	27.2	27.2	27.2	27.2	27.2	27.2	27.2	26.5	25.1	23.6
97.5°	27.2	27.2	27.2	27.2	27.2	27.2	27.2	27.2	31.3	39.4	47.5
100°	30.7	29.5	28.4	27.2	28.4	29.5	30.7	31.9	53.9	96.8	139.7
102.5°	221.8	202.2	182.6	163.1	182.6	202.2	221.8	241.4	255.3	263.4	271.5
105°	385.8	385.6	385.2	385.0	385.2	385.6	385.8	386.1	386.2	386.2	386.2
107.5°	487.8	487.0	486.1	485.3	486.1	487.0	487.8	488.7	489.1	489.0	489.0
110°	553.9	554.1	554.5	554.7	554.5	554.1	553.9	553.6	553.9	554.7	555.6



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	165°	170°	175°	180°	185°	190°	195°	200°	205°	210°	215°
112.5°	618.2	617.8	617.3	616.9	617.3	617.8	618.2	618.5	619.3	620.4	621.5
115°	715.5	713.7	712.0	710.2	712.0	713.7	715.5	717.2	718.6	719.8	720.9
117.5°	812.1	811.3	810.5	809.8	810.5	811.3	812.1	812.8	813.9	815.5	816.9
120°	875.3	873.8	872.5	871.0	872.5	873.8	875.3	876.8	877.8	878.3	878.9
122.5°	934.1	932.4	930.7	929.0	930.7	932.4	934.1	935.7	936.9	937.5	938.0
125°	1020.0	1019.2	1018.3	1017.4	1018.3	1019.2	1020.0	1020.9	1021.9	1023.0	1024.2
127.5°	1098.2	1096.1	1094.0	1091.8	1094.0	1096.1	1098.2	1100.4	1101.7	1102.4	1103.0
130°	1150.1	1148.7	1147.2	1145.7	1147.2	1148.7	1150.1	1151.5	1152.7	1153.6	1154.4
132.5°	1199.9	1198.4	1197.0	1195.5	1197.0	1198.4	1199.9	1201.3	1202.1	1202.3	1202.5
135°	1268.9	1267.1	1265.4	1263.7	1265.4	1267.1	1268.9	1270.6	1271.8	1272.4	1272.9
137.5°	1336.6	1335.2	1333.6	1332.1	1333.6	1335.2	1336.6	1338.2	1338.9	1338.7	1338.6
140°	1377.8	1376.1	1374.3	1372.6	1374.3	1376.1	1377.8	1379.5	1380.1	1379.5	1378.9
142.5°	1416.1	1414.4	1412.6	1410.9	1412.6	1414.4	1416.1	1417.9	1418.7	1418.6	1418.4
145°	1472.4	1470.7	1469.0	1467.2	1469.0	1470.7	1472.4	1474.1	1474.8	1474.5	1474.3
147.5°	1519.8	1517.8	1515.7	1513.6	1515.7	1517.8	1519.8	1521.9	1522.8	1522.4	1522.1
150°	1550.6	1548.3	1546.0	1543.7	1546.0	1548.3	1550.6	1552.9	1553.8	1553.2	1552.6
152.5°	1577.9	1575.8	1573.7	1571.7	1573.7	1575.8	1577.9	1579.9	1580.7	1580.1	1579.6
155°	1615.4	1613.1	1610.8	1608.4	1610.8	1613.1	1615.4	1617.6	1618.4	1617.6	1616.7
157.5°	1646.2	1643.9	1641.6	1639.3	1641.6	1643.9	1646.2	1648.6	1649.2	1648.3	1647.4
160°	1665.9	1663.6	1661.3	1659.1	1661.3	1663.6	1665.9	1668.3	1668.8	1667.7	1666.5
162.5°	1684.3	1681.7	1679.2	1676.6	1679.2	1681.7	1684.3	1686.8	1687.2	1685.7	1684.0
165°	1707.4	1705.1	1702.8	1700.5	1702.8	1705.1	1707.4	1709.7	1710.0	1708.3	1706.5
167.5°	1724.8	1722.3	1719.7	1717.1	1719.7	1722.3	1724.8	1727.4	1727.7	1725.6	1723.5
170°	1734.2	1731.6	1729.0	1726.4	1729.0	1731.6	1734.2	1736.8	1736.9	1734.7	1732.3
172.5°	1740.4	1737.8	1735.3	1732.7	1735.3	1737.8	1740.4	1743.0	1743.3	1741.2	1739.1
175°	1748.4	1745.8	1743.3	1740.7	1743.3	1745.8	1748.4	1751.0	1751.2	1748.9	1746.5
177.5°	1750.8	1749.0	1747.1	1745.3	1747.1	1749.0	1750.8	1752.7	1752.8	1751.2	1749.6
180°	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
0°	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1
2.5°	1044.0	1047.9	1050.1	1055.1	1062.2	1065.8	1070.8	1074.4	1079.4	1085.5	1090.5
5°	976.4	987.1	994.3	1005.5	1015.7	1026.1	1039.0	1048.4	1060.9	1075.2	1086.4
7.5°	913.6	927.0	938.9	953.7	970.7	984.0	1000.8	1018.0	1037.7	1058.0	1077.1
10°	873.6	887.0	901.7	920.1	937.0	954.9	975.1	995.1	1019.8	1042.6	1068.5
12.5°	833.9	848.7	865.3	885.7	906.3	929.2	949.7	972.3	998.7	1028.3	1056.0
15°	784.6	798.9	816.8	834.2	857.9	883.0	910.2	940.2	969.7	1002.8	1037.2
17.5°	731.8	747.5	767.2	787.4	812.4	841.6	868.4	901.2	934.4	972.9	1013.4
20°	697.4	713.5	736.8	759.1	782.0	810.5	842.3	875.8	911.1	951.8	997.0
22.5°	670.3	681.7	704.6	727.3	754.1	783.3	814.4	849.4	887.9	930.0	977.3
25°	629.9	643.3	659.9	683.5	711.3	742.2	773.4	810.5	852.6	895.5	946.0
27.5°	594.1	605.1	621.5	640.1	667.6	699.6	733.0	771.6	814.8	858.5	911.5
30°	568.7	580.7	596.4	616.0	638.0	672.9	706.8	744.9	788.7	833.8	888.3
32.5°	546.5	559.0	572.4	591.0	614.8	645.7	680.7	718.0	762.5	809.1	862.2
35°	515.5	524.0	536.5	554.8	578.1	603.1	638.9	678.2	721.6	769.8	823.0
37.5°	479.9	490.9	503.3	519.3	539.6	566.7	599.9	639.7	680.0	726.3	774.8
40°	459.2	469.4	483.3	494.9	516.3	541.0	571.4	612.9	653.2	696.5	740.8
42.5°	438.1	448.0	459.7	474.2	493.4	517.4	545.6	584.4	627.4	668.3	705.4
45°	405.0	415.3	426.5	439.9	457.8	481.0	509.2	544.5	582.1	619.7	647.8
47.5°	373.5	383.1	393.7	407.4	424.0	446.3	471.6	502.7	539.2	571.2	591.3
50°	350.9	359.9	371.5	385.0	401.1	422.1	446.2	477.0	507.4	536.5	554.8
52.5°	328.8	338.8	350.4	362.1	377.5	398.5	420.8	447.4	476.3	500.0	515.1
55°	295.5	304.9	315.6	327.7	342.9	360.8	384.5	405.5	428.3	448.4	457.4
57.5°	263.4	271.6	281.7	294.3	308.0	324.6	343.4	363.6	379.6	393.9	404.0
60°	242.3	249.4	258.8	269.6	284.3	299.5	316.5	335.3	347.8	359.9	369.3
62.5°	220.8	227.6	236.7	246.3	259.3	273.5	289.7	304.9	317.1	325.2	336.0
65°	188.6	195.4	202.9	213.3	223.5	235.1	249.9	261.1	269.6	278.5	285.2
67.5°	158.7	164.3	171.5	179.5	188.2	199.4	210.9	220.2	225.9	231.4	239.4
70°	139.1	143.5	149.3	155.6	165.0	176.2	185.1	192.3	196.3	201.6	211.5
72.5°	119.0	124.2	129.7	136.0	143.5	152.9	160.7	167.9	170.5	174.8	181.1
75°	93.8	96.6	101.1	105.5	110.9	118.9	126.5	128.3	130.5	134.1	138.6
77.5°	71.0	73.4	75.2	78.2	82.4	88.9	92.9	95.6	96.1	97.5	101.9
80°	56.3	57.7	59.5	61.7	63.5	68.9	71.1	73.8	74.6	76.0	78.3
82.5°	41.3	42.6	43.7	45.6	48.5	50.6	52.9	55.5	55.7	56.7	57.2
85°	24.1	24.6	23.7	24.6	25.1	25.9	28.2	30.4	30.0	29.5	30.8
87.5°	13.0	12.7	12.0	12.7	11.5	11.5	11.0	10.9	11.2	11.5	11.7
90°	22.2	20.8	18.7	16.7	14.7	12.7	10.5	8.2	5.9	3.6	1.3
92.5°	22.2	20.8	18.9	17.1	15.4	13.6	13.5	15.2	16.7	18.3	20.0
95°	22.2	20.8	31.7	42.6	53.6	64.5	70.4	71.3	72.2	73.0	73.9
97.5°	55.6	63.8	85.4	107.1	128.7	150.4	160.5	158.9	157.3	155.8	154.2
100°	182.6	225.5	224.4	223.3	222.1	220.9	219.9	219.0	218.2	217.3	216.5
102.5°	279.7	287.7	287.1	286.4	285.7	285.0	284.0	283.0	281.9	280.8	279.7
105°	386.2	386.2	386.2	386.2	386.2	386.2	385.6	384.5	383.4	382.2	381.1
107.5°	489.0	488.9	488.4	487.8	487.2	486.6	486.3	486.3	486.3	486.3	486.3
110°	556.5	557.3	556.7	556.2	555.6	555.0	554.7	554.7	554.7	554.7	554.7



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	220°	225°	230°	235°	240°	245°	250°	255°	260°	265°	270°
112.5°	622.6	623.7	623.4	623.0	622.7	622.3	621.8	621.1	620.4	619.7	619.1
115°	722.0	723.2	723.0	722.6	722.4	722.0	721.2	719.8	718.3	716.9	715.5
117.5°	818.4	819.9	818.8	817.7	816.7	815.5	815.0	815.1	815.1	815.2	815.3
120°	879.5	880.0	879.2	878.3	877.4	876.6	876.3	876.6	876.9	877.2	877.4
122.5°	938.6	939.2	938.7	938.3	938.0	937.5	936.8	935.7	934.6	933.5	932.5
125°	1025.4	1026.5	1026.5	1026.5	1026.5	1026.5	1025.5	1023.5	1021.5	1019.4	1017.4
127.5°	1103.6	1104.3	1104.5	1104.7	1104.8	1105.0	1104.3	1102.9	1101.5	1100.0	1098.5
130°	1155.3	1156.2	1155.8	1155.5	1155.3	1154.9	1154.1	1152.7	1151.2	1149.8	1148.3
132.5°	1202.6	1202.8	1203.4	1204.0	1204.7	1205.3	1204.8	1203.2	1201.4	1199.8	1198.1
135°	1273.5	1274.1	1274.6	1275.2	1275.8	1276.3	1275.8	1274.1	1272.4	1270.6	1268.9
137.5°	1338.5	1338.3	1338.9	1339.4	1339.9	1340.4	1340.0	1338.4	1337.0	1335.4	1333.9
140°	1378.4	1377.8	1378.0	1378.4	1378.6	1378.9	1378.8	1378.2	1377.6	1377.1	1376.5
142.5°	1418.3	1418.2	1417.8	1417.4	1417.0	1416.6	1416.2	1415.8	1415.5	1415.1	1414.8
145°	1473.9	1473.7	1473.7	1473.7	1473.7	1473.7	1473.4	1472.8	1472.2	1471.6	1471.1
147.5°	1521.7	1521.4	1521.0	1520.7	1520.4	1520.0	1519.8	1520.0	1520.1	1520.2	1520.4
150°	1552.0	1551.4	1550.8	1550.3	1549.7	1549.1	1549.1	1549.7	1550.3	1550.8	1551.4
152.5°	1579.0	1578.4	1577.9	1577.3	1576.7	1576.1	1576.4	1577.7	1579.0	1580.3	1581.5
155°	1615.8	1615.0	1614.4	1613.8	1613.3	1612.7	1613.3	1615.0	1616.7	1618.4	1620.1
157.5°	1646.5	1645.5	1645.5	1645.5	1645.4	1645.3	1645.8	1646.8	1647.9	1648.9	1649.9
160°	1665.3	1664.2	1663.9	1663.6	1663.4	1663.0	1663.8	1665.5	1667.2	1669.0	1670.7
162.5°	1682.4	1680.8	1680.5	1680.2	1679.9	1679.6	1680.3	1682.0	1683.9	1685.6	1687.3
165°	1704.8	1703.1	1702.8	1702.5	1702.2	1701.9	1702.6	1704.3	1706.1	1707.9	1709.6
167.5°	1721.5	1719.4	1719.2	1718.8	1718.6	1718.3	1719.0	1720.8	1722.6	1724.4	1726.1
170°	1730.0	1727.7	1727.4	1727.2	1726.8	1726.6	1727.4	1729.4	1731.5	1733.5	1735.5
172.5°	1737.1	1735.0	1734.5	1734.0	1733.5	1732.9	1733.6	1735.7	1737.7	1739.7	1741.7
175°	1744.3	1742.0	1741.7	1741.4	1741.1	1740.9	1741.5	1743.3	1745.0	1746.7	1748.4
177.5°	1748.0	1746.4	1746.1	1745.9	1745.7	1745.4	1746.0	1747.4	1748.8	1750.2	1751.5
180°	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
0°	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1
2.5°	1094.4	1097.7	1102.3	1107.7	1112.0	1116.6	1119.1	1119.1	1121.3	1125.9	1132.0
5°	1097.6	1109.2	1120.3	1134.7	1145.8	1158.8	1168.6	1178.0	1186.5	1197.2	1208.4
7.5°	1096.7	1115.9	1136.1	1158.6	1183.5	1203.2	1223.6	1239.5	1255.2	1275.7	1291.9
10°	1093.1	1118.1	1145.4	1174.0	1205.3	1232.6	1257.1	1279.5	1301.0	1323.4	1343.4
12.5°	1086.7	1118.5	1151.8	1186.2	1225.7	1256.9	1288.7	1312.4	1337.5	1361.9	1386.7
15°	1077.0	1114.6	1154.8	1202.6	1250.9	1285.8	1317.1	1347.9	1371.1	1398.9	1422.6
17.5°	1057.0	1105.4	1156.1	1208.3	1254.7	1295.3	1328.1	1357.4	1382.2	1412.6	1444.8
20°	1045.3	1097.6	1150.3	1206.2	1250.4	1292.0	1323.8	1354.2	1385.0	1424.8	1464.1
22.5°	1028.8	1084.7	1140.7	1193.7	1240.4	1280.6	1313.4	1350.7	1391.1	1436.2	1483.8
25°	1002.8	1060.5	1115.9	1166.4	1212.0	1253.2	1297.9	1347.9	1397.1	1456.6	1525.0
27.5°	969.8	1025.4	1074.9	1128.3	1173.5	1225.9	1281.7	1335.9	1406.9	1488.7	1574.1
30°	945.1	997.9	1044.8	1095.4	1146.8	1204.5	1267.0	1330.9	1415.4	1511.6	1613.1
32.5°	916.5	964.2	1010.8	1059.5	1118.9	1182.2	1248.8	1327.0	1428.0	1537.3	1642.4
35°	866.9	909.8	954.9	1009.0	1072.1	1140.9	1225.9	1321.1	1443.1	1560.7	1655.1
37.5°	814.9	848.7	894.1	951.1	1019.8	1099.4	1195.8	1311.6	1436.9	1542.4	1582.5
40°	774.8	806.5	854.4	914.3	982.2	1069.4	1177.6	1296.5	1422.6	1495.9	1492.8
42.5°	735.0	767.2	813.2	873.5	944.3	1041.9	1153.3	1276.9	1383.3	1411.2	1353.0
45°	674.2	704.1	749.3	810.1	886.1	988.5	1105.6	1224.1	1292.0	1246.9	1131.5
47.5°	612.2	641.2	683.1	742.7	825.6	932.8	1043.5	1140.7	1150.3	1053.3	915.0
50°	571.4	598.7	638.4	701.9	782.4	887.0	993.9	1070.3	1046.6	928.2	785.5
52.5°	531.7	557.8	595.1	655.0	737.3	839.8	935.2	995.1	940.4	814.4	686.0
55°	473.0	498.0	535.6	590.6	665.2	759.1	842.7	864.6	784.2	657.2	553.5
57.5°	417.3	435.7	472.8	521.3	593.3	676.1	736.1	732.1	643.3	529.0	454.6
60°	380.5	397.0	432.3	477.0	545.4	619.7	661.7	643.8	553.9	459.6	388.1
62.5°	346.1	361.6	391.2	432.3	491.0	555.6	586.2	561.5	476.6	393.8	336.9
65°	294.2	305.3	329.1	367.0	413.1	457.8	485.1	448.8	373.8	311.2	268.2
67.5°	245.6	255.3	276.4	303.7	335.4	366.3	377.3	343.4	285.0	242.8	212.6
70°	214.1	223.1	237.4	262.9	283.9	305.8	311.2	280.8	232.0	199.8	181.1
72.5°	184.1	192.3	204.8	222.8	237.4	250.0	252.5	224.3	186.9	164.8	150.3
75°	140.3	147.6	155.6	162.3	171.7	173.9	173.0	151.1	131.0	116.2	108.2
77.5°	103.1	106.2	111.1	113.7	114.2	114.0	109.4	95.6	85.2	79.1	75.9
80°	79.6	81.8	83.2	84.0	84.5	80.0	75.1	66.6	63.0	59.5	55.4
82.5°	57.8	59.3	60.6	60.8	58.4	54.7	50.1	45.9	43.4	41.6	40.0
85°	31.3	31.8	31.3	29.1	25.9	24.6	23.7	22.8	22.4	21.9	21.9
87.5°	11.8	11.2	9.9	10.7	11.1	11.2	11.5	11.6	11.6	12.0	12.2
90°	3.6	5.9	8.2	10.5	12.7	14.7	16.7	18.7	20.8	22.2	23.6
92.5°	18.3	16.7	15.2	13.5	13.6	15.4	17.1	18.9	20.8	22.2	23.6
95°	73.0	72.2	71.3	70.4	64.5	53.6	42.6	31.7	20.8	22.2	23.6
97.5°	155.8	157.3	158.9	160.5	150.4	128.7	107.1	85.4	63.8	55.6	47.5
100°	217.3	218.2	219.0	219.9	220.9	222.1	223.3	224.4	225.5	182.6	139.7
102.5°	280.8	281.9	283.0	284.0	285.0	285.7	286.4	287.1	287.7	279.7	271.5
105°	382.2	383.4	384.5	385.6	386.2	386.2	386.2	386.2	386.2	386.2	386.2
107.5°	486.3	486.3	486.3	486.3	486.6	487.2	487.8	488.4	488.9	489.0	489.0
110°	554.7	554.7	554.7	554.7	555.0	555.6	556.2	556.7	557.3	556.5	555.6





TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	275°	280°	285°	290°	295°	300°	305°	310°	315°	320°	325°
112.5°	619.7	620.4	621.1	621.8	622.3	622.7	623.0	623.4	623.7	622.6	621.5
115°	716.9	718.3	719.8	721.2	722.0	722.4	722.6	723.0	723.2	722.0	720.9
117.5°	815.2	815.1	815.1	815.0	815.5	816.7	817.7	818.8	819.9	818.4	816.9
120°	877.2	876.9	876.6	876.3	876.6	877.4	878.3	879.2	880.0	879.5	878.9
122.5°	933.5	934.6	935.7	936.8	937.5	938.0	938.3	938.7	939.2	938.6	938.0
125°	1019.4	1021.5	1023.5	1025.5	1026.5	1026.5	1026.5	1026.5	1026.5	1025.4	1024.2
127.5°	1100.0	1101.5	1102.9	1104.3	1105.0	1104.8	1104.7	1104.5	1104.3	1103.6	1103.0
130°	1149.8	1151.2	1152.7	1154.1	1154.9	1155.3	1155.5	1155.8	1156.2	1155.3	1154.4
132.5°	1199.8	1201.4	1203.2	1204.8	1205.3	1204.7	1204.0	1203.4	1202.8	1202.6	1202.5
135°	1270.6	1272.4	1274.1	1275.8	1276.3	1275.8	1275.2	1274.6	1274.1	1273.5	1272.9
137.5°	1335.4	1337.0	1338.4	1340.0	1340.4	1339.9	1339.4	1338.9	1338.3	1338.5	1338.6
140°	1377.1	1377.6	1378.2	1378.8	1378.9	1378.6	1378.4	1378.0	1377.8	1378.4	1378.9
142.5°	1415.1	1415.5	1415.8	1416.2	1416.6	1417.0	1417.4	1417.8	1418.2	1418.3	1418.4
145°	1471.6	1472.2	1472.8	1473.4	1473.7	1473.7	1473.7	1473.7	1473.7	1473.9	1474.3
147.5°	1520.2	1520.1	1520.0	1519.8	1520.0	1520.4	1520.7	1521.0	1521.4	1521.7	1522.1
150°	1550.8	1550.3	1549.7	1549.1	1549.1	1549.7	1550.3	1550.8	1551.4	1552.0	1552.6
152.5°	1580.3	1579.0	1577.7	1576.4	1576.1	1576.7	1577.3	1577.9	1578.4	1579.0	1579.6
155°	1618.4	1616.7	1615.0	1613.3	1612.7	1613.3	1613.8	1614.4	1615.0	1615.8	1616.7
157.5°	1648.9	1647.9	1646.8	1645.8	1645.3	1645.4	1645.5	1645.5	1645.5	1646.5	1647.4
160°	1669.0	1667.2	1665.5	1663.8	1663.0	1663.4	1663.6	1663.9	1664.2	1665.3	1666.5
162.5°	1685.6	1683.9	1682.0	1680.3	1679.6	1679.9	1680.2	1680.5	1680.8	1682.4	1684.0
165°	1707.9	1706.1	1704.3	1702.6	1701.9	1702.2	1702.5	1702.8	1703.1	1704.8	1706.5
167.5°	1724.4	1722.6	1720.8	1719.0	1718.3	1718.6	1718.8	1719.2	1719.4	1721.5	1723.5
170°	1733.5	1731.5	1729.4	1727.4	1726.6	1726.8	1727.2	1727.4	1727.7	1730.0	1732.3
172.5°	1739.7	1737.7	1735.7	1733.6	1732.9	1733.5	1734.0	1734.5	1735.0	1737.1	1739.1
175°	1746.7	1745.0	1743.3	1741.5	1740.9	1741.1	1741.4	1741.7	1742.0	1744.3	1746.5
177.5°	1750.2	1748.8	1747.4	1746.0	1745.4	1745.7	1745.9	1746.1	1746.4	1748.0	1749.6
180°	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
0°	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1	1089.1
2.5°	1136.6	1136.6	1142.7	1142.4	1146.3	1144.9	1145.6
5°	1221.8	1229.4	1236.1	1240.6	1247.3	1249.1	1248.2
7.5°	1310.2	1327.1	1335.3	1346.6	1348.7	1354.5	1353.9
10°	1364.9	1381.5	1394.0	1403.8	1408.8	1415.0	1415.4
12.5°	1407.8	1421.9	1433.0	1442.1	1448.0	1450.0	1451.2
15°	1441.4	1457.0	1470.0	1482.9	1490.6	1496.3	1499.5
17.5°	1475.2	1499.3	1522.2	1539.8	1550.4	1559.3	1559.2
20°	1501.2	1529.0	1557.6	1577.7	1598.3	1607.2	1608.6
22.5°	1529.1	1571.6	1608.4	1639.6	1666.6	1675.9	1679.4
25°	1587.1	1642.5	1699.4	1743.2	1774.4	1792.8	1795.4
27.5°	1657.1	1732.2	1791.9	1832.3	1858.3	1871.9	1874.8
30°	1706.5	1775.8	1829.5	1859.8	1871.9	1873.7	1867.0
32.5°	1728.6	1780.5	1801.9	1800.1	1776.4	1760.7	1754.6
35°	1701.6	1690.8	1638.5	1576.0	1528.1	1497.7	1489.6
37.5°	1548.5	1456.0	1359.7	1265.2	1214.8	1189.2	1145.2
40°	1397.6	1265.7	1165.5	1086.0	1029.2	983.5	972.8
42.5°	1227.3	1091.1	991.0	922.8	877.5	846.2	832.6
45°	986.3	869.1	786.4	734.1	699.2	676.4	666.2
47.5°	788.8	698.2	637.9	599.2	572.7	552.8	547.3
50°	680.4	608.0	557.1	524.4	504.3	489.1	482.8
52.5°	591.0	532.5	493.4	466.5	447.5	438.0	432.7
55°	487.8	437.2	409.1	387.6	376.9	369.3	365.7
57.5°	398.9	362.4	341.8	327.0	317.1	312.2	310.5
60°	349.1	320.6	301.8	290.2	283.4	277.2	275.4
62.5°	305.1	282.7	268.1	258.0	251.2	248.6	247.5
65°	245.9	231.2	220.4	214.1	208.8	207.9	207.4
67.5°	195.4	186.8	181.2	174.6	172.7	169.6	169.0
70°	167.2	161.4	154.7	152.5	150.2	147.1	147.6
72.5°	141.8	136.0	131.5	128.5	127.7	126.3	127.5
75°	103.8	101.9	100.1	97.9	97.0	97.0	96.6
77.5°	74.0	72.5	70.5	69.2	69.0	67.1	67.8
80°	53.6	51.4	50.5	51.0	49.6	49.2	49.2
82.5°	39.7	38.9	38.0	38.1	37.8	37.4	37.7
85°	21.9	21.4	21.4	21.0	21.0	20.6	20.6
87.5°	12.9	13.5	13.0	12.8	13.0	13.5	14.1
90°	25.1	26.5	27.6	28.5	29.4	30.2	31.1
92.5°	25.1	26.5	27.4	27.8	28.2	28.7	29.0
95°	25.1	26.5	27.2	27.2	27.2	27.2	27.2
97.5°	39.4	31.3	27.2	27.2	27.2	27.2	27.2
100°	96.8	53.9	31.9	30.7	29.5	28.4	27.2
102.5°	263.4	255.3	241.4	221.8	202.2	182.6	163.1
105°	386.2	386.2	386.1	385.8	385.6	385.2	385.0
107.5°	489.0	489.1	488.7	487.8	487.0	486.1	485.3
110°	554.7	553.9	553.6	553.9	554.1	554.5	554.7



TEST NUMBER: P333696-935

CATALOG NUMBER: S125RDIW-S850D1560U935-4F0-1E-UDD-A

**CANDELA DISTRIBUTION (continued):**

	330°	335°	340°	345°	350°	355°	360°
112.5°	620.4	619.3	618.5	618.2	617.8	617.3	616.9
115°	719.8	718.6	717.2	715.5	713.7	712.0	710.2
117.5°	815.5	813.9	812.8	812.1	811.3	810.5	809.8
120°	878.3	877.8	876.8	875.3	873.8	872.5	871.0
122.5°	937.5	936.9	935.7	934.1	932.4	930.7	929.0
125°	1023.0	1021.9	1020.9	1020.0	1019.2	1018.3	1017.4
127.5°	1102.4	1101.7	1100.4	1098.2	1096.1	1094.0	1091.8
130°	1153.6	1152.7	1151.5	1150.1	1148.7	1147.2	1145.7
132.5°	1202.3	1202.1	1201.3	1199.9	1198.4	1197.0	1195.5
135°	1272.4	1271.8	1270.6	1268.9	1267.1	1265.4	1263.7
137.5°	1338.7	1338.9	1338.2	1336.6	1335.2	1333.6	1332.1
140°	1379.5	1380.1	1379.5	1377.8	1376.1	1374.3	1372.6
142.5°	1418.6	1418.7	1417.9	1416.1	1414.4	1412.6	1410.9
145°	1474.5	1474.8	1474.1	1472.4	1470.7	1469.0	1467.2
147.5°	1522.4	1522.8	1521.9	1519.8	1517.8	1515.7	1513.6
150°	1553.2	1553.8	1552.9	1550.6	1548.3	1546.0	1543.7
152.5°	1580.1	1580.7	1579.9	1577.9	1575.8	1573.7	1571.7
155°	1617.6	1618.4	1617.6	1615.4	1613.1	1610.8	1608.4
157.5°	1648.3	1649.2	1648.6	1646.2	1643.9	1641.6	1639.3
160°	1667.7	1668.8	1668.3	1665.9	1663.6	1661.3	1659.1
162.5°	1685.7	1687.2	1686.8	1684.3	1681.7	1679.2	1676.6
165°	1708.3	1710.0	1709.7	1707.4	1705.1	1702.8	1700.5
167.5°	1725.6	1727.7	1727.4	1724.8	1722.3	1719.7	1717.1
170°	1734.7	1736.9	1736.8	1734.2	1731.6	1729.0	1726.4
172.5°	1741.2	1743.3	1743.0	1740.4	1737.8	1735.3	1732.7
175°	1748.9	1751.2	1751.0	1748.4	1745.8	1743.3	1740.7
177.5°	1751.2	1752.8	1752.7	1750.8	1749.0	1747.1	1745.3
180°	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4	1748.4

(END OF REPORT)