

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P402267

Luminaire Tested: **LD1MR022D010 ED1M22509030SB1MW**

Issue Date: 6/3/2020

Test Information

Test Method: LM-41-14
Report Number: P402267
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1912-604-8)
Test Lab: INNOVATION CENTER (G3)
Issue Date: 6/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD1MR022D010 ED1M22509030SB1MW
Description: 1 INCH 50° OPTIC WITH SPECULAR BLACK BAFFLE
Light Source: HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 432.1 lumens
Efficiency: N/A
Efficacy: 75.8 lumens/watt
Spacing Criteria (0/90/45): 0.77 / 0.77 / 0.71
Luminous Opening: Rectangular (W 0.1' x L: 1.29' x H: 0')
CIE Type: Direct

Input Watts (W): 5.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P402267

CATALOG NUMBER: LD1MR022D010 ED1M22509030SB1MW

Luminous Intensity Polar Plot





TEST NUMBER: P402267

CATALOG NUMBER: LD1MR022D010 ED1M22509030SB1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95					95			
2	110	105	102	99	107	104	100	98	100	98	96	98	95	94	95	93	92	90					90			
3	105	99	95	92	103	98	94	91	96	92	90	93	90	88	91	89	87	85					85			
4	101	94	89	86	99	93	89	85	91	87	84	89	86	83	87	85	82	81					81			
5	97	89	84	81	95	89	84	80	87	83	80	85	82	79	84	81	78	77					77			
6	93	85	80	76	91	84	79	76	83	79	75	82	78	75	80	77	75	73					73			
7	89	81	76	72	88	80	76	72	79	75	72	78	74	71	77	74	71	70					70			
8	85	77	72	69	84	77	72	69	76	71	68	75	71	68	74	70	68	67					67			
9	82	74	69	65	81	73	69	65	73	68	65	72	68	65	71	67	65	64					64			
10	79	71	66	62	78	70	66	62	70	65	62	69	65	62	68	64	62	61					61			

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	61240	61240	61240
5°	59691	59771	59739
10°	55272	55190	55101
15°	50381	50439	50505
20°	43214	43350	43180
25°	29297	29659	29606
30°	14512	14605	14549
35°	4844	4873	4580
40°	1107	1076	929
45°	430	475	396
50°	348	373	311
55°	321	321	279
60°	256	272	224
65°	151	189	133
70°	0	23	0
75°	0	0	0
80°	0	0	0
85°	0	0	0



TEST NUMBER: P402267

CATALOG NUMBER: LD1MR022D010 ED1M22509030SB1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	68.9	15.9
10°-20°	168.9	39.1
20°-30°	150.4	34.8
30°-40°	37.5	8.7
40°-50°	3.6	0.8
50°-60°	2.0	0.5
60°-70°	0.8	0.2
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	388.2	89.8
0°-40°	425.8	98.5
0°-60°	431.3	99.8
0°-90°	432.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	432.1	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	766	766	766	766	766	
5°	743	746	744	744	744	69
15°	608	611	609	608	610	169
25°	332	336	336	338	335	150
35°	50	52	50	49	47	37
45°	4	4	4	4	4	4
55°	2	2	2	2	2	2
65°	1	1	1	1	1	1
75°	0	0	0	0	0	0
85°	0	0	0	0	0	0
90°	0	0	0	0	0	0



TEST NUMBER: P402267

CATALOG NUMBER: LD1MR022D010 ED1M22509030SB1MW

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	765.5	765.5	765.5	765.5	765.5
2.5°	761.1	764.5	762.1	762.3	762.4
5°	743.3	746.0	744.3	743.8	743.9
7.5°	713.2	715.6	712.9	713.9	712.8
10°	680.4	682.8	679.4	679.4	678.3
12.5°	647.0	649.6	645.5	645.1	647.7
15°	608.3	611.4	609.0	607.9	609.8
17.5°	569.1	568.7	567.3	566.6	565.9
20°	507.6	510.2	509.2	504.9	507.2
22.5°	426.7	426.9	428.3	429.0	427.2
25°	331.9	335.5	336.0	338.2	335.4
27.5°	245.9	246.6	242.8	243.1	245.7
30°	157.1	159.2	158.1	159.2	157.5
32.5°	90.6	92.5	91.8	92.6	92.8
35°	49.6	51.5	49.9	49.2	46.9
37.5°	24.6	24.6	25.2	23.2	22.1
40°	10.6	10.9	10.3	9.8	8.9
42.5°	5.4	5.4	5.7	4.8	4.7
45°	3.8	3.8	4.2	3.7	3.5
47.5°	3.3	3.3	3.5	3.1	3.0
50°	2.8	2.8	3.0	2.7	2.5
52.5°	2.5	2.5	2.7	2.4	2.3
55°	2.3	2.3	2.3	2.1	2.0
57.5°	1.8	2.0	2.0	1.8	1.7
60°	1.6	1.6	1.7	1.6	1.4
62.5°	1.3	1.3	1.3	1.3	1.1
65°	0.8	0.8	1.0	0.8	0.7
67.5°	0.1	0.3	0.7	0.0	0.0
70°	0.0	0.0	0.1	0.0	0.0
72.5°	0.0	0.0	0.0	0.0	0.0
75°	0.0	0.0	0.0	0.0	0.0
77.5°	0.0	0.0	0.0	0.0	0.0
80°	0.0	0.0	0.0	0.0	0.0
82.5°	0.0	0.0	0.0	0.0	0.0
85°	0.0	0.0	0.0	0.0	0.0
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180° - - 45°-225° - - - - 90°-270°







(END OF REPORT)