

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P225068

Luminaire Tested: **LSRWM2B10FL409035D010 2LBD\*WH**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P225068  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14829)  
Test Lab: INNOVATION CENTER (G1)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LSRWM2B10FL409035D010 2LBD\*WH  
Description: 1000 Lumen, 2inch Portfolio LED Cylinder  
FLOOD OPTIC  
SPUN ROUND TRIM WITH WHEAT HAZE FINISH  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 871.2 lumens  
Efficiency: N/A  
Efficacy: 84.6 lumens/watt  
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.59  
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 10.3  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P225068

CATALOG NUMBER: LSRWM2B10FL409035D010 2LBD\*WH

### Luminous Intensity Polar Plot





TEST NUMBER: P225068

CATALOG NUMBER: LSRWM2B10FL409035D010 2LBD\*WH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0					
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100								
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95								
2	110	106	102	100	108	104	101	98	101	98	96	98	96	94	95	94	92	91								
3	106	100	96	93	104	99	95	92	96	93	91	94	91	89	92	90	88	87								
4	102	95	91	87	100	94	90	87	92	89	86	90	87	85	88	86	84	82								
5	98	91	86	82	96	90	85	82	88	84	81	87	83	81	85	82	80	79								
6	94	87	82	78	93	86	81	78	85	80	77	83	80	77	82	79	76	75								
7	91	83	78	75	89	82	78	74	81	77	74	80	76	74	79	76	73	72								
8	87	79	75	71	86	79	74	71	78	74	71	77	73	70	76	73	70	69								
9	84	76	71	68	83	76	71	68	75	71	68	74	70	68	73	70	67	66								
10	81	73	69	65	80	73	68	65	72	68	65	71	68	65	71	67	65	64								

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	803820
5°	773413
10°	680761
15°	534707
20°	363565
25°	212284
30°	108105
35°	51164
40°	22349
45°	9696
50°	4640
55°	2971
60°	1704
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P225068

CATALOG NUMBER: LSRWM2B10FL409035D010 2LBD\*WH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	181.7	20.9
10°-20°	362.6	41.6
20°-30°	232.7	26.7
30°-40°	73.8	8.5
40°-50°	15.8	1.8
50°-60°	4.0	0.5
60°-70°	0.5	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	777.0	89.2
0°-40°	850.8	97.7
0°-60°	870.6	99.9
0°-90°	871.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	871.2	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2075	
5°	1989	182
15°	1333	363
25°	497	233
35°	108	74
45°	18	16
55°	4	4
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P225068

CATALOG NUMBER: LSRWM2B10FL409035D010 2LBD\*WH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	2075.2
2.5°	2055.3
5°	1989.1
7.5°	1880.9
10°	1730.8
12.5°	1547.6
15°	1333.4
17.5°	1104.9
20°	882.0
22.5°	673.3
25°	496.7
27.5°	354.3
30°	241.7
32.5°	162.3
35°	108.2
37.5°	71.7
40°	44.2
42.5°	27.6
45°	17.7
47.5°	12.1
50°	7.7
52.5°	5.5
55°	4.4
57.5°	3.3
60°	2.2
62.5°	1.1
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)