

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P222327

Luminaire Tested: **LSR2B15NFL259727D010 2LBDLC*MMS**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P222327
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (155)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR2B15NFL259727D010 2LBDLC*MMS
Description: 1500 Lumen, 2inch Portfolio LED Cylinder
NARROW FLOOD OPTIC
LENSED CAST ROUND TRIM WITH MATTE METALLIC SILVER
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 890.7 lumens
Efficiency: N/A
Efficacy: 62.3 lumens/watt
Spacing Criteria (0/90/45): 0.39 / 0.39 / 0.35
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P222327

CATALOG NUMBER: LSR2B15NFL259727D010 2LBDLC*MMS

Luminous Intensity Polar Plot





TEST NUMBER: P222327

CATALOG NUMBER: LSR2B15NFL259727D010 2LBDLC*MMS

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10		0		
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100
1	115	113	112	110	113	111	110	108	107	106	105	104	103	102	100	100	99	97			97
2	112	109	106	104	110	107	104	102	104	102	100	101	99	98	98	97	96	95			95
3	109	105	101	99	107	103	100	98	101	98	96	99	97	95	96	95	93	92			92
4	106	101	97	95	104	100	97	94	98	95	93	96	94	92	95	93	91	90			90
5	103	98	94	91	102	97	94	91	95	92	90	94	91	89	93	90	89	88			88
6	101	95	91	89	99	94	91	88	93	90	88	92	89	87	91	88	87	86			86
7	98	92	89	86	97	92	88	86	91	88	85	90	87	85	89	86	85	84			84
8	96	90	86	84	95	90	86	84	89	86	83	88	85	83	87	85	83	82			82
9	94	88	84	82	93	88	84	82	87	84	82	86	83	81	85	83	81	80			80
10	92	86	82	80	91	86	82	80	85	82	80	84	82	80	84	81	79	79			79

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2046814
5°	1889848
10°	1279199
15°	435216
20°	159853
25°	84751
30°	43564
35°	20333
40°	6675
45°	3342
50°	1567
55°	608
60°	697
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P222327

CATALOG NUMBER: LSR2B15NFL259727D010 2LBDLC*MMS

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	413.4	46.4
10°-20°	347.6	39.0
20°-30°	95.4	10.7
30°-40°	27.8	3.1
40°-50°	5.1	0.6
50°-60°	1.2	0.1
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	856.5	96.2
0°-40°	884.3	99.3
0°-60°	890.6	100.0
0°-90°	890.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	890.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5284	
5°	4860	413
15°	1085	348
25°	198	95
35°	43	28
45°	6	5
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P222327

CATALOG NUMBER: LSR2B15NFL259727D010 2LBDLC*MMS

CANDELA DISTRIBUTION (FULL):

0°	
0°	5284.2
1°	5253.5
2°	5199.1
3°	5121.0
4°	5014.0
5°	4860.4
6°	4650.8
7°	4388.4
8°	4068.2
9°	3690.1
10°	3252.3
11°	2772.4
12°	2273.2
13°	1796.8
14°	1390.6
15°	1085.3
17.5°	612.4
20°	387.8
22.5°	276.4
25°	198.3
27.5°	140.4
30°	97.4
32.5°	68.4
35°	43.0
37.5°	17.5
40°	13.2
42.5°	9.7
45°	6.1
47.5°	3.5
50°	2.6
52.5°	1.8
55°	0.9
57.5°	0.9
60°	0.9
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P222327

CATALOG NUMBER: LSR2B15NFL259727D010 2LBDLC*MMS

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)