

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P224876

Luminaire Tested: **LSSQWM2B15FL409030D2WD010 2LBD*B**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P224876
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14834)
Test Lab: INNOVATION CENTER (G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSSQWM2B15FL409030D2WD010 2LBD*B
Description: 1500 Lumen, 2inch Portfolio LED Cylinder
FLOOD OPTIC
SPUN ROUND TRIM WITH BLACK FINISH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 809.2 lumens
Efficiency: N/A
Efficacy: 56.6 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.6
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P224876

CATALOG NUMBER: LSSQWM2B15FL409030D2WD010 2LBD*B

Luminous Intensity Polar Plot





TEST NUMBER: P224876

CATALOG NUMBER: LSSQWM2B15FL409030D2WD010 2LBD*B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95					95			
2	110	106	103	100	108	104	101	99	101	99	96	98	96	94	96	94	92	91					91			
3	106	100	96	93	104	99	95	92	97	93	91	94	92	89	92	90	88	87					87			
4	102	95	91	87	100	94	90	87	92	89	86	90	87	85	89	86	84	83					83			
5	98	91	86	83	96	90	86	82	88	85	82	87	84	81	85	83	80	79					79			
6	94	87	82	79	93	86	82	78	85	81	78	84	80	77	82	79	77	76					76			
7	91	83	78	75	90	83	78	75	81	77	74	80	77	74	79	76	74	72					72			
8	87	80	75	72	86	79	75	71	78	74	71	77	74	71	76	73	71	69					69			
9	84	77	72	69	83	76	72	68	75	71	68	74	71	68	74	70	68	67					67			
10	82	74	69	66	81	73	69	66	73	68	65	72	68	65	71	68	65	64					64			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	732239
5°	719483
10°	641822
15°	507318
20°	338297
25°	196257
30°	98220
35°	46199
40°	18052
45°	8053
50°	3796
55°	2161
60°	775
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P224876

CATALOG NUMBER: LSSQWM2B15FL409030D2WD010 2LBD*B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	169.6	21.0
10°-20°	342.4	42.3
20°-30°	215.4	26.6
30°-40°	65.8	8.1
40°-50°	12.9	1.6
50°-60°	2.9	0.4
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	727.5	89.9
0°-40°	793.3	98.0
0°-60°	809.1	100.0
0°-90°	809.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	809.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1890	
5°	1850	170
15°	1265	342
25°	459	215
35°	98	66
45°	15	13
55°	3	3
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P224876

CATALOG NUMBER: LSSQWM2B15FL409030D2WD010 2LBD*B

CANDELA DISTRIBUTION (FULL):

	0°
0°	1890.4
2.5°	1886.1
5°	1850.4
7.5°	1766.4
10°	1631.8
12.5°	1463.7
15°	1265.1
17.5°	1044.5
20°	820.7
22.5°	629.4
25°	459.2
27.5°	323.6
30°	219.6
32.5°	148.1
35°	97.7
37.5°	59.9
40°	35.7
42.5°	23.1
45°	14.7
47.5°	9.5
50°	6.3
52.5°	4.2
55°	3.2
57.5°	2.1
60°	1.0
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)