

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P#

Luminaire Tested: **LSSQ2B20WFL559024D010 2LBDL*WMH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P#
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14805)
Test Lab: INNOVATION CENTER (G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSSQ2B20WFL559024D010 2LBDL*WMH
Description: 2000 Lumen, 2inch Portfolio LED Cylinder
WIDE FLOOD OPTIC
LENSED SPUN ROUND TRIM WITH WHEAT METALLIC HAZE FINISH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1155.6 lumens
Efficiency: N/A
Efficacy: 55.3 lumens/watt
Spacing Criteria (0/90/45): 0.78 / 0.78 / 0.83
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 20.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P#

CATALOG NUMBER: LSSQ2B20WFL559024D010 2LBDL*WMH

Luminous Intensity Polar Plot





TEST NUMBER: P#

CATALOG NUMBER: LSSQ2B20WFL559024D010 2LBDL*WMH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	113	111	108	106	111	108	106	104		104	103	101			101	99	98			97
2	108	103	99	95	105	101	97	94		98	95	92			95	92	90			92
3	102	95	90	86	100	94	89	86		91	87	84			89	86	83			87
4	97	89	83	79	95	88	83	79		86	81	78			84	80	77			82
5	92	83	77	73	90	82	77	72		80	75	72			79	74	71			77
6	87	78	72	67	85	77	71	67		75	70	67			74	70	66			73
7	82	73	67	63	81	72	67	62		71	66	62			70	65	62			69
8	78	69	63	58	77	68	62	58		67	62	58			66	61	58			65
9	75	65	59	55	73	64	59	55		63	58	54			62	58	54			62
10	71	61	55	51	70	61	55	51		60	55	51			59	54	51			58

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	550341
5°	543811
10°	502625
15°	440510
20°	380177
25°	323619
30°	256330
35°	177891
40°	115590
45°	69569
50°	40194
55°	22488
60°	9839
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P#

CATALOG NUMBER: LSSQ2B20WFL559024D010 2LBDL*WMH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	129.7	11.2
10°-20°	306.0	26.5
20°-30°	344.5	29.8
30°-40°	238.0	20.6
40°-50°	103.1	8.9
50°-60°	31.9	2.8
60°-70°	2.3	0.2
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	780.3	67.5
0°-40°	1018.2	88.1
0°-60°	1153.3	99.8
0°-90°	1155.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1155.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1421	
5°	1399	130
15°	1098	306
25°	757	345
35°	376	238
45°	127	103
55°	33	32
65°	0	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P#

CATALOG NUMBER: LSSQ2B20WFL559024D010 2LBDL*WMH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1420.8
2.5°	1417.6
5°	1398.6
7.5°	1354.1
10°	1277.9
12.5°	1190.6
15°	1098.5
17.5°	1003.3
20°	922.3
22.5°	841.4
25°	757.2
27.5°	671.5
30°	573.1
32.5°	469.9
35°	376.2
37.5°	295.3
40°	228.6
42.5°	173.0
45°	127.0
47.5°	93.7
50°	66.7
52.5°	47.6
55°	33.3
57.5°	23.8
60°	12.7
62.5°	3.2
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)