

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P224841

Luminaire Tested: **LSR2WM2B20FL408027D010 2LBDL*B**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P224841
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14834)
Test Lab: INNOVATION CENTER (G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR2WM2B20FL408027D010 2LBDL*B
Description: 2000 Lumen, 2inch Portfolio LED Cylinder
FLOOD OPTIC
LENSED SPUN ROUND TRIM WITH BLACK FINISH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1683.7 lumens
Efficiency: N/A
Efficacy: 80.6 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.6
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 20.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P224841

CATALOG NUMBER: LSR2WM2B20FL408027D010 2LBDL*B

Luminous Intensity Polar Plot





TEST NUMBER: P224841

CATALOG NUMBER: LSR2WM2B20FL408027D010 2LBDL*B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			50
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			102
1	114	112	110	108	112	110	108	106		106	104	103			102	101	100			99
2	110	106	103	100	108	104	101	99		101	99	96			98	96	94			96
3	106	100	96	93	104	99	95	92		97	93	91			94	92	89			92
4	102	95	91	87	100	94	90	87		92	89	86			90	87	85			89
5	98	91	86	83	96	90	86	82		88	85	82			87	84	81			85
6	94	87	82	79	93	86	82	78		85	81	78			84	80	77			82
7	91	83	78	75	90	83	78	75		81	77	74			80	77	74			79
8	87	80	75	72	86	79	75	71		78	74	71			77	74	71			76
9	84	77	72	69	83	76	72	68		75	71	68			74	71	68			74
10	82	74	69	66	81	73	69	66		73	68	65			72	68	65			71

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1523393
5°	1496901
10°	1335366
15°	1055499
20°	703799
25°	408327
30°	204357
35°	96133
40°	37569
45°	16762
50°	7894
55°	4457
60°	1704
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P224841

CATALOG NUMBER: LSR2WM2B20FL408027D010 2LBDL*B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	352.9	21.0
10°-20°	712.5	42.3
20°-30°	448.2	26.6
30°-40°	137.0	8.1
40°-50°	26.9	1.6
50°-60°	6.0	0.4
60°-70°	0.3	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1513.5	89.9
0°-40°	1650.5	98.0
0°-60°	1683.4	100.0
0°-90°	1683.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1683.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3933	
5°	3850	353
15°	2632	712
25°	955	448
35°	203	137
45°	31	27
55°	7	6
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P224841

CATALOG NUMBER: LSR2WM2B20FL408027D010 2LBDL*B

CANDELA DISTRIBUTION (FULL):

	0°
0°	3932.9
2.5°	3924.2
5°	3849.8
7.5°	3675.0
10°	3395.1
12.5°	3045.3
15°	2632.1
17.5°	2173.1
20°	1707.4
22.5°	1309.5
25°	955.4
27.5°	673.3
30°	456.9
32.5°	308.2
35°	203.3
37.5°	124.6
40°	74.3
42.5°	48.1
45°	30.6
47.5°	19.7
50°	13.1
52.5°	8.7
55°	6.6
57.5°	4.4
60°	2.2
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)