

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P#

Luminaire Tested: **LSR2B05WFL558027D010 2LBDC**MW***

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P#
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14810)
Test Lab: INNOVATION CENTER (G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR2B05WFL558027D010 2LBDC*MW
Description: 500 Lumen, 2inch Portfolio LED Cylinder
WIDE FLOOD OPTIC
CAST ROUND TRIM WITH MATTE WHITE FINISH
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 710.0 lumens
Efficiency: N/A
Efficacy: 97.3 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.84
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')
CIE Type: Direct

Input Watts (W): 7.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P#
CATALOG NUMBER: LSR2B05WFL558027D010 2LBDC*MW

Luminous Intensity Polar Plot





TEST NUMBER: P#

CATALOG NUMBER: LSR2B05WFL558027D010 2LBDC*MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20																	
RC	80									50									30									10									0								
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0															
RCR	0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100	100	100	100	100	100	100	100																
	1	113	110	108	106	111	108	106	104	104	102	101	101	99	98	97	96	95	93	93	93	93	93	93	93	93	93	93	93																
	2	108	102	98	95	105	101	97	94	98	94	92	95	92	90	92	90	88	86	86	86	86	86	86	86	86	86	86	86																
	3	102	95	90	86	100	94	89	85	91	87	84	89	85	83	87	84	81	80	80	80	80	80	80	80	80	80	80	80																
	4	97	89	83	79	95	88	82	78	85	81	77	83	80	76	82	78	76	74	74	74	74	74	74	74	74	74	74	74																
	5	91	83	77	72	90	82	76	72	80	75	71	78	74	71	77	73	70	69	69	69	69	69	69	69	69	69	69	69																
	6	87	78	71	67	85	77	71	67	75	70	66	74	69	66	73	69	65	64	64	64	64	64	64	64	64	64	64	64																
	7	82	73	67	62	81	72	66	62	71	66	62	70	65	62	69	64	61	60	60	60	60	60	60	60	60	60	60	60																
	8	78	69	62	58	77	68	62	58	67	62	58	66	61	58	65	61	57	56	56	56	56	56	56	56	56	56	56	56																
	9	74	65	59	55	73	64	58	54	63	58	54	62	57	54	61	57	54	53	53	53	53	53	53	53	53	53	53	53																
	10	71	61	55	51	70	61	55	51	60	55	51	59	54	51	58	54	51	49	49	49	49	49	49	49	49	49	49	49																

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	333040
5°	330929
10°	307656
15°	270080
20°	232813
25°	199078
30°	157975
35°	110130
40°	69678
45°	42509
50°	25129
55°	13776
60°	3021
65°	2658
70°	2152
75°	2844
80°	2231
85°	4444



TEST NUMBER: P#

CATALOG NUMBER: LSR2B05WFL558027D010 2LBDC*MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	79.0	11.1
10°-20°	187.6	26.4
20°-30°	211.6	29.8
30°-40°	146.4	20.6
40°-50°	62.4	8.8
50°-60°	18.1	2.5
60°-70°	2.6	0.4
70°-80°	1.6	0.2
80°-90°	0.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	478.2	67.4
0°-40°	624.6	88.0
0°-60°	705.0	99.3
0°-90°	710.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	710.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	860	
5°	851	79
15°	674	188
25°	466	212
35°	233	146
45°	78	62
55°	20	18
65°	3	3
75°	2	2
85°	1	1
90°	0	



TEST NUMBER: P#

CATALOG NUMBER: LSR2B05WFL558027D010 2LBDC*MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	859.8
2.5°	858.9
5°	851.1
7.5°	824.9
10°	782.2
12.5°	729.8
15°	673.5
17.5°	615.3
20°	564.8
22.5°	517.3
25°	465.8
27.5°	411.5
30°	353.2
32.5°	290.2
35°	232.9
37.5°	180.5
40°	137.8
42.5°	103.8
45°	77.6
47.5°	56.3
50°	41.7
52.5°	30.1
55°	20.4
57.5°	8.7
60°	3.9
62.5°	2.9
65°	2.9
67.5°	1.9
70°	1.9
72.5°	1.9
75°	1.9
77.5°	1.0
80°	1.0
82.5°	1.0
85°	1.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)