

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P225089

Luminaire Tested: **LSR2B05FL408035D010 2LBD*WH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P225089
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14829)
Test Lab: INNOVATION CENTER (G1)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LSR2B05FL408035D010 2LBD*WH
Description: 500 Lumen, 2inch Portfolio LED Cylinder
FLOOD OPTIC
SPUN ROUND TRIM WITH WHEAT HAZE FINISH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 789.0 lumens
Efficiency: N/A
Efficacy: 108.1 lumens/watt
Spacing Criteria (0/90/45): 0.6 / 0.6 / 0.59
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 7.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P225089

CATALOG NUMBER: LSR2B05FL408035D010 2LBD*WH

Luminous Intensity Polar Plot





TEST NUMBER: P225089

CATALOG NUMBER: LSR2B05FL408035D010 2LBD*WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95			95																
2	110	106	102	100	108	104	101	98	101	98	96	98	96	94	95	94	92	91			91																
3	106	100	96	93	104	99	95	92	96	93	91	94	91	89	92	90	88	87			87																
4	102	95	91	87	100	94	90	87	92	89	86	90	87	85	88	86	84	82			82																
5	98	91	86	82	96	90	85	82	88	84	81	87	83	81	85	82	80	79			79																
6	94	87	82	78	93	86	81	78	85	80	77	83	80	77	82	79	76	75			75																
7	90	83	78	75	89	82	78	74	81	77	74	80	76	74	79	76	73	72			72																
8	87	79	75	71	86	79	74	71	78	74	71	77	73	70	76	73	70	69			69																
9	84	76	71	68	83	76	71	68	75	71	68	74	70	68	73	70	67	66			66																
10	81	73	69	65	80	73	68	65	72	68	65	71	68	65	71	67	65	64			64																

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	727978
5°	700430
10°	616531
15°	484260
20°	329228
25°	192282
30°	97907
35°	46340
40°	20226
45°	8765
50°	4218
55°	2701
60°	1549
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P225089

CATALOG NUMBER: LSR2B05FL408035D010 2LBD*WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	164.5	20.9
10°-20°	328.4	41.6
20°-30°	210.8	26.7
30°-40°	66.9	8.5
40°-50°	14.3	1.8
50°-60°	3.7	0.5
60°-70°	0.5	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	703.7	89.2
0°-40°	770.6	97.7
0°-60°	788.5	99.9
0°-90°	789.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	789.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1879	
5°	1801	165
15°	1208	328
25°	450	211
35°	98	67
45°	16	14
55°	4	4
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P225089

CATALOG NUMBER: LSR2B05FL408035D010 2LBD*WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1879.4
2.5°	1861.4
5°	1801.4
7.5°	1703.5
10°	1567.5
12.5°	1401.6
15°	1207.6
17.5°	1000.7
20°	798.7
22.5°	609.8
25°	449.9
27.5°	320.9
30°	218.9
32.5°	147.0
35°	98.0
37.5°	65.0
40°	40.0
42.5°	25.0
45°	16.0
47.5°	11.0
50°	7.0
52.5°	5.0
55°	4.0
57.5°	3.0
60°	2.0
62.5°	1.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)