

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P223579

Luminaire Tested: **LD2B10D010 EU2B10SP159730 2LBD*GPH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P223579
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (150)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD2B10D010 EU2B10SP159730 2LBD*GPH
Description: 1000 Lumen, 2inch Portfolio LED Downlight
SPOT OPTIC
SPUN ROUND TRIM WITH GRAPHITE FINISH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 421.6 lumens
Efficiency: N/A
Efficacy: 40.9 lumens/watt
Spacing Criteria (0/90/45): 0.24 / 0.24 / 0.23
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 10.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P223579

CATALOG NUMBER: LD2B10D010 EU2B10SP159730 2LBD*GPH

Luminous Intensity Polar Plot





TEST NUMBER: P223579

CATALOG NUMBER: LD2B10D010 EU2B10SP159730 2LBD*GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0													
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						100													
1	116	114	112	111	113	112	110	109	108	107	106	104	103	103	101	100	100	98						98													
2	113	110	107	105	111	108	106	104	105	103	102	102	101	100	100	99	98	96						96													
3	110	106	103	101	108	105	102	100	102	100	98	100	99	97	98	97	96	94						94													
4	108	103	100	97	106	102	99	97	100	98	96	98	96	95	97	95	94	93						93													
5	105	101	97	95	104	100	97	94	98	96	94	97	95	93	95	94	92	91						91													
6	103	98	95	93	102	98	95	92	96	94	92	95	93	91	94	92	91	90						90													
7	101	96	93	91	100	96	93	90	95	92	90	94	91	90	93	91	89	88						88													
8	100	94	91	89	99	94	91	89	93	90	89	92	90	88	92	90	88	87						87													
9	98	93	90	88	97	92	89	87	92	89	87	91	89	87	90	88	87	86						86													
10	96	91	88	86	96	91	88	86	90	88	86	90	87	86	89	87	86	85						85													

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2025858
5°	1464512
10°	426360
15°	149617
20°	64057
25°	28806
30°	11137
35°	5532
40°	3691
45°	2410
50°	1326
55°	1013
60°	542
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P223579

CATALOG NUMBER: LD2B10D010 EU2B10SP159730 2LBD*GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	266.5	63.2
10°-20°	108.4	25.7
20°-30°	33.3	7.9
30°-40°	8.2	1.9
40°-50°	3.4	0.8
50°-60°	1.5	0.4
60°-70°	0.3	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	408.2	96.8
0°-40°	416.4	98.8
0°-60°	421.3	99.9
0°-90°	421.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	421.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5230	
5°	3766	267
15°	373	108
25°	67	33
35°	12	8
45°	4	3
55°	2	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P223579

CATALOG NUMBER: LD2B10D010 EU2B10SP159730 2LBD*GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	5230.1
1°	5150.3
2°	4955.3
3°	4644.5
4°	4238.5
5°	3766.5
6°	3234.4
7°	2656.8
8°	2071.2
9°	1523.7
10°	1084.0
11°	776.9
12°	584.1
13°	475.7
14°	416.3
15°	373.1
17.5°	230.1
20°	155.4
22.5°	104.1
25°	67.4
27.5°	41.0
30°	24.9
32.5°	16.1
35°	11.7
37.5°	9.5
40°	7.3
42.5°	5.9
45°	4.4
47.5°	2.9
50°	2.2
52.5°	2.2
55°	1.5
57.5°	1.5
60°	0.7
62.5°	0.7
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P223579

CATALOG NUMBER: LD2B10D010 EU2B10SP159730 2LBD*GPH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)