

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P224502

Luminaire Tested: **LD2B10D010 EU2B10FL409035 2LBDL\*WMH**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P224502  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14831)  
Test Lab: INNOVATION CENTER (G1)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LD2B10D010 EU2B10FL409035 2LBDL\*WMH  
Description: 1000 Lumen, 2inch Portfolio LED Downlight  
FLOOD OPTIC  
LENSED SPUN ROUND TRIM WITH WHEAT METALLIC HAZE FINISH  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 823.9 lumens  
Efficiency: N/A  
Efficacy: 80.0 lumens/watt  
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.59  
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 10.3  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P224502

CATALOG NUMBER: LD2B10D010 EU2B10FL409035 2LBDL\*WMH

### Luminous Intensity Polar Plot





TEST NUMBER: P224502

CATALOG NUMBER: LD2B10D010 EU2B10FL409035 2LBDL\*WMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																			
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95																			
2	110	106	102	100	108	104	101	98	101	98	96	98	96	94	95	94	92	91																			
3	106	100	96	93	104	99	95	92	96	93	91	94	91	89	92	90	88	87																			
4	102	95	91	87	100	94	90	87	92	89	86	90	87	85	88	86	84	82																			
5	98	91	86	82	96	90	85	82	88	84	81	87	83	81	85	82	80	79																			
6	94	87	82	78	93	86	81	78	85	81	77	83	80	77	82	79	77	75																			
7	91	83	78	75	89	82	78	74	81	77	74	80	76	74	79	76	73	72																			
8	87	79	75	71	86	79	74	71	78	74	71	77	73	70	76	73	70	69																			
9	84	76	71	68	83	76	71	68	75	71	68	74	70	68	73	70	67	66																			
10	81	73	69	65	80	73	68	65	72	68	65	72	68	65	71	67	65	64																			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	747616
5°	732197
10°	648626
15°	509684
20°	342666
25°	199078
30°	99517
35°	46908
40°	22198
45°	9751
50°	5062
55°	2836
60°	1627
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P224502

CATALOG NUMBER: LD2B10D010 EU2B10FL409035 2LBDL\*WMH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	172.3	20.9
10°-20°	344.7	41.8
20°-30°	217.9	26.5
30°-40°	68.2	8.3
40°-50°	15.8	1.9
50°-60°	4.2	0.5
60°-70°	0.8	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	735.0	89.2
0°-40°	803.1	97.5
0°-60°	823.1	99.9
0°-90°	823.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	823.9	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1930	
5°	1883	172
15°	1271	345
25°	466	218
35°	99	68
45°	18	16
55°	4	4
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P224502

CATALOG NUMBER: LD2B10D010 EU2B10FL409035 2LBDL\*WMH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1930.1
2.5°	1920.7
5°	1883.1
7.5°	1794.3
10°	1649.1
12.5°	1476.8
15°	1271.0
17.5°	1046.5
20°	831.3
22.5°	632.9
25°	465.8
27.5°	329.0
30°	222.5
32.5°	148.3
35°	99.2
37.5°	66.8
40°	43.9
42.5°	27.2
45°	17.8
47.5°	12.5
50°	8.4
52.5°	6.3
55°	4.2
57.5°	3.1
60°	2.1
62.5°	2.1
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)