

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P264943

Luminaire Tested: **LD2B20D010 EU2B2010SP159027 2LBDL*WH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P264943
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-1711-432-2)
Test Lab: INNOVATION CENTER(G3)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD2B20D010 EU2B2010SP159027 2LBDL*WH
Description: 2000 Lumen, 2inch Portfolio LED Downlight
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1397.0 lumens
Efficiency: N/A
Efficacy: 66.8 lumens/watt
Spacing Criteria (0/90/45): 0.31 / 0.31 / 0.32
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 20.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P264943

CATALOG NUMBER: LD2B20D010 EU2B2010SP159027 2LBDL*WH

Luminous Intensity Polar Plot





TEST NUMBER: P264943

CATALOG NUMBER: LD2B20D010 EU2B2010SP159027 2LBDL*WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			100																
1	115	113	111	110	113	111	110	108	107	106	105	104	103	102	100	99	99	97			97																
2	112	108	106	103	110	107	104	102	104	102	100	101	99	98	98	97	96	94			94																
3	109	104	101	98	107	103	100	97	100	98	96	98	96	94	96	94	93	92			92																
4	105	100	97	94	104	99	96	93	97	95	92	96	93	91	94	92	90	89			89																
5	103	97	93	91	101	96	93	90	95	92	89	93	91	89	92	90	88	87			87																
6	100	94	90	88	99	94	90	87	92	89	87	91	88	86	90	88	86	85			85																
7	98	92	88	85	97	91	88	85	90	87	85	89	86	84	88	86	84	83			83																
8	95	89	86	83	94	89	85	83	88	85	82	87	84	82	86	84	82	81			81																
9	93	87	83	81	92	87	83	81	86	83	81	85	82	80	85	82	80	79			79																
10	91	85	82	79	91	85	81	79	84	81	79	84	81	79	83	80	78	78			78																

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	4931694
5°	4013922
10°	2168210
15°	864522
20°	346674
25°	165977
30°	86079
35°	45472
40°	25246
45°	15629
50°	10745
55°	7225
60°	5526
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P264943

CATALOG NUMBER: LD2B20D010 EU2B2010SP159027 2LBDL*WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	651.8	46.7
10°-20°	514.3	36.8
20°-30°	151.7	10.9
30°-40°	50.5	3.6
40°-50°	19.0	1.4
50°-60°	8.4	0.6
60°-70°	1.4	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1317.8	94.3
0°-40°	1368.3	97.9
0°-60°	1395.7	99.9
0°-90°	1397.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1397.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	9996	
5°	8105	652
15°	1693	514
25°	305	152
35°	76	51
45°	22	19
55°	8	8
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P264943

CATALOG NUMBER: LD2B20D010 EU2B2010SP159027 2LBDL*WH

CANDELA DISTRIBUTION (FULL):

	0°
0°	9996.1
2.5°	9593.2
5°	8104.9
7.5°	6244.4
10°	4328.0
12.5°	2769.7
15°	1692.6
17.5°	1032.3
20°	660.3
22.5°	442.0
25°	304.9
27.5°	215.4
30°	151.1
32.5°	106.3
35°	75.5
37.5°	53.2
40°	39.2
42.5°	30.8
45°	22.4
47.5°	19.6
50°	14.0
52.5°	11.2
55°	8.4
57.5°	8.4
60°	5.6
62.5°	2.8
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)