

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P264159

Luminaire Tested: **LD2B20D010 EU2B2010SP158050 2LBD*LI**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P264159
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1805-787-1)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD2B20D010 EU2B2010SP158050 2LBD*LI
Description: 2000 Lumen, 2inch Portfolio LED Downlight
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1829.0 lumens
Efficiency: N/A
Efficacy: 87.5 lumens/watt
Spacing Criteria (0/90/45): 0.28 / 0.28 / 0.28
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 20.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P264159

CATALOG NUMBER: LD2B20D010 EU2B2010SP158050 2LBD*LI

Luminous Intensity Polar Plot





TEST NUMBER: P264159

CATALOG NUMBER: LD2B20D010 EU2B2010SP158050 2LBD*LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	116	114	112	111	113	112	110	109	108	107	106	104	103	102	101	100	100	98			
2	113	109	107	105	111	108	106	104	105	103	101	102	101	99	99	98	97	96			
3	110	106	103	100	108	105	102	100	102	100	98	100	98	97	98	96	95	94			
4	107	103	99	97	106	102	99	96	100	97	95	98	96	94	96	95	93	92			
5	105	100	97	94	104	99	96	94	98	95	93	96	94	92	95	93	91	90			
6	103	98	94	92	102	97	94	91	96	93	91	95	92	90	93	91	90	89			
7	101	95	92	90	100	95	92	89	94	91	89	93	90	89	92	90	88	87			
8	99	93	90	88	98	93	90	88	92	89	87	91	89	87	91	88	87	86			
9	97	92	88	86	96	91	88	86	91	88	86	90	87	86	89	87	85	85			
10	95	90	87	85	95	90	87	85	89	86	85	89	86	84	88	86	84	83			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	8630328
5°	6917651
10°	3019262
15°	935672
20°	326198
25°	144039
30°	65229
35°	33909
40°	19321
45°	9140
50°	5757
55°	3269
60°	1875
65°	2218
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P264159

CATALOG NUMBER: LD2B20D010 EU2B2010SP158050 2LBD*LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1060.7	58.0
10°-20°	580.9	31.8
20°-30°	132.4	7.2
30°-40°	38.1	2.1
40°-50°	11.7	0.6
50°-60°	3.5	0.2
60°-70°	1.6	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1774.0	97.0
0°-40°	1812.1	99.1
0°-60°	1827.4	99.9
0°-90°	1829.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1829.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	17493	
5°	13968	###
15°	1832	581
25°	265	132
35°	56	38
45°	13	12
55°	4	4
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P264159

CATALOG NUMBER: LD2B20D010 EU2B2010SP158050 2LBD*LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	17492.9
1°	17275.2
2°	16822.9
3°	16120.9
4°	15156.1
5°	13968.1
6°	12511.6
7°	10884.3
8°	9185.7
9°	7541.5
10°	6026.8
11°	4744.9
12°	3735.1
13°	2939.3
14°	2321.8
15°	1831.9
16°	1445.2
17°	1150.6
18°	925.3
19°	752.6
20°	621.3
22.5°	401.7
25°	264.6
26°	223.4
27°	189.6
28°	159.5
29°	133.3
30°	114.5
32.5°	78.8
35°	56.3
37.5°	41.3
40°	30.0
42.5°	20.6
45°	13.1
47.5°	9.4
50°	7.5
52.5°	5.6
55°	3.8
57.5°	1.9
60°	1.9
62.5°	1.9
65°	1.9
67.5°	1.9



TEST NUMBER: P264159

CATALOG NUMBER: LD2B20D010 EU2B2010SP158050 2LBD*LI

CANDELA DISTRIBUTION (continued):

	0°
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







70°		0.0
72.5°		0.0



(END OF REPORT)