

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P222380

Luminaire Tested: **LD2B05D010 EU2B05NFL259727 2LBDSQLC*MW**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P222380
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (155)
Test Lab: INNOVATION CENTER-P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD2B05D010 EU2B05NFL259727 2LBDSQLC*MW
Description: 500 Lumen, 2inch Portfolio LED Downlight
NARROW FLOOD OPTIC
LENSED SQUARE CAST TRIM WITH MATTE WHITE FINISH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 471.0 lumens
Efficiency: N/A
Efficacy: 64.5 lumens/watt
Spacing Criteria (0/90/45): 0.39 / 0.39 / 0.35
Luminous Opening: Rectangular (W 0.17' x L: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 7.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P222380

CATALOG NUMBER: LD2B05D010 EU2B05NFL259727 2LBDSQLC*MW

Luminous Intensity Polar Plot





TEST NUMBER: P222380

CATALOG NUMBER: LD2B05D010 EU2B05NFL259727 2LBDSQLC*MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20									
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																			
RCR																																														
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100									100																			
1	115	113	112	110	113	111	110	108	107	106	105	104	103	102	100	100	99	97									97																			
2	112	109	106	104	110	107	104	102	104	102	100	101	99	98	98	97	96	95									95																			
3	109	105	101	99	107	103	100	98	101	98	96	99	97	95	96	95	93	92									92																			
4	106	101	97	95	104	100	97	94	98	95	93	96	94	92	95	93	91	90									90																			
5	103	98	94	91	102	97	94	91	95	92	90	94	91	89	93	90	89	88									88																			
6	101	95	91	89	99	94	91	88	93	90	88	92	89	87	91	88	87	86									86																			
7	98	92	89	86	97	92	88	86	91	88	85	90	87	85	89	86	85	84									84																			
8	96	90	86	84	95	90	86	84	89	86	83	88	85	83	87	85	83	82									82																			
9	94	88	84	82	93	88	84	82	87	84	82	86	83	81	85	83	81	80									80																			
10	92	86	82	80	91	86	82	80	85	82	80	84	82	80	84	81	79	79									79																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1082361
5°	999360
10°	676434
15°	230140
20°	84543
25°	44790
30°	23034
35°	10734
40°	3540
45°	1753
50°	844
55°	338
60°	387
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P222380

CATALOG NUMBER: LD2B05D010 EU2B05NFL259727 2LBDSQLC*MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	218.6	46.4
10°-20°	183.8	39.0
20°-30°	50.4	10.7
30°-40°	14.7	3.1
40°-50°	2.7	0.6
50°-60°	0.6	0.1
60°-70°	0.1	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	452.9	96.2
0°-40°	467.6	99.3
0°-60°	471.0	100.0
0°-90°	471.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	471.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2794	
5°	2570	219
15°	574	184
25°	105	50
35°	23	15
45°	3	3
55°	0	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P222380

CATALOG NUMBER: LD2B05D010 EU2B05NFL259727 2LBDSQLC*MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	2794.3
1°	2778.0
2°	2749.3
3°	2708.0
4°	2651.4
5°	2570.2
6°	2459.3
7°	2320.6
8°	2151.3
9°	1951.3
10°	1719.8
11°	1466.0
12°	1202.0
13°	950.1
14°	735.3
15°	573.9
17.5°	323.8
20°	205.1
22.5°	146.1
25°	104.8
27.5°	74.2
30°	51.5
32.5°	36.2
35°	22.7
37.5°	9.3
40°	7.0
42.5°	5.1
45°	3.2
47.5°	1.9
50°	1.4
52.5°	0.9
55°	0.5
57.5°	0.5
60°	0.5
62.5°	0.0
65°	0.0
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P222380

CATALOG NUMBER: LD2B05D010 EU2B05NFL259727 2LBDSQLC*MW

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)