

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P279428

Luminaire Tested: **LDA2B108027D010 EU2B10FL408027 2LBAD1MW**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P279428
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-3)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA2B108027D010 EU2B10FL408027 2LBAD1MW
Description: PORTFOLIO 2IN ADJ 1000 LUMEN LED LUMINAIRE WITH FLOOD OPTIC AND 2in
ADJ spun Refl, Self-Flanged, MW
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1141.0 lumens
Efficiency: N/A
Efficacy: 114.1 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.55
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 10
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P279428

CATALOG NUMBER: LDA2B108027D010 EU2B10FL408027 2LBAD1MW

Luminous Intensity Polar Plot





TEST NUMBER: P279428

CATALOG NUMBER: LDA2B108027D010 EU2B10FL408027 2LBAD1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
| RF | 20 | | | | 20 | | | | 20 | | | | 20 | | | | 20 | | | |
| RC | 80 | | | | 70 | | | | 50 | | | | 30 | | | | 10 | | 0 | |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 |
| RCR | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | | |
| 1 | 115 | 113 | 111 | 109 | 112 | 110 | 109 | 107 | 106 | 105 | 104 | 103 | 102 | 101 | 99 | 99 | 98 | 96 | | |
| 2 | 111 | 107 | 104 | 101 | 109 | 105 | 102 | 100 | 102 | 100 | 98 | 99 | 97 | 96 | 97 | 95 | 94 | 92 | | |
| 3 | 107 | 102 | 98 | 95 | 105 | 101 | 97 | 94 | 98 | 95 | 93 | 96 | 94 | 92 | 94 | 92 | 90 | 89 | | |
| 4 | 103 | 98 | 93 | 90 | 102 | 97 | 93 | 90 | 95 | 91 | 89 | 93 | 90 | 88 | 91 | 89 | 87 | 85 | | |
| 5 | 100 | 94 | 89 | 86 | 98 | 93 | 89 | 86 | 91 | 88 | 85 | 90 | 87 | 84 | 88 | 86 | 84 | 82 | | |
| 6 | 97 | 90 | 85 | 82 | 95 | 89 | 85 | 82 | 88 | 84 | 82 | 87 | 83 | 81 | 85 | 83 | 80 | 79 | | |
| 7 | 94 | 87 | 82 | 79 | 92 | 86 | 82 | 79 | 85 | 81 | 78 | 84 | 81 | 78 | 83 | 80 | 78 | 77 | | |
| 8 | 91 | 84 | 79 | 76 | 90 | 83 | 79 | 76 | 82 | 78 | 76 | 81 | 78 | 75 | 80 | 77 | 75 | 74 | | |
| 9 | 88 | 81 | 76 | 73 | 87 | 80 | 76 | 73 | 79 | 76 | 73 | 79 | 75 | 73 | 78 | 75 | 73 | 72 | | |
| 10 | 85 | 78 | 74 | 71 | 84 | 78 | 74 | 71 | 77 | 73 | 71 | 76 | 73 | 70 | 76 | 72 | 70 | 69 | | |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|---------|
| | 0° |
| 0° | 1569038 |
| 5° | 1535858 |
| 10° | 1399818 |
| 15° | 1093549 |
| 20° | 647408 |
| 25° | 240664 |
| 30° | 75198 |
| 35° | 33427 |
| 40° | 15521 |
| 45° | 7326 |
| 50° | 3991 |
| 55° | 2236 |
| 60° | 987 |
| 65° | 584 |
| 70° | 721 |
| 75° | 0 |
| 80° | 0 |
| 85° | 0 |



TEST NUMBER: P279428

CATALOG NUMBER: LDA2B108027D010 EU2B10FL408027 2LBAD1MW

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 286.7 | 25.1 |
| 10°-20° | 570.1 | 50.0 |
| 20°-30° | 233.5 | 20.5 |
| 30°-40° | 38.6 | 3.4 |
| 40°-50° | 9.1 | 0.8 |
| 50°-60° | 2.4 | 0.2 |
| 60°-70° | 0.6 | 0.0 |
| 70°-80° | 0.1 | 0.0 |
| 80°-90° | 0.0 | 0.0 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 1090.2 | 95.5 |
| 0°-40° | 1128.8 | 98.9 |
| 0°-60° | 1140.4 | 99.9 |
| 0°-90° | 1141.0 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 1141.0 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|------|------|
| 0° | 3180 | |
| 5° | 3101 | 287 |
| 15° | 2141 | 570 |
| 25° | 442 | 233 |
| 35° | 56 | 39 |
| 45° | 10 | 9 |
| 55° | 3 | 2 |
| 65° | 0 | 1 |
| 75° | 0 | 0 |
| 85° | 0 | 0 |
| 90° | 0 | |



TEST NUMBER: P279428

CATALOG NUMBER: LDA2B108027D010 EU2B10FL408027 2LBAD1MW

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|--------|
| 0° | 3180.3 |
| 1° | 3169.3 |
| 2° | 3154.6 |
| 3° | 3141.5 |
| 4° | 3124.2 |
| 5° | 3101.2 |
| 6° | 3067.1 |
| 7° | 3022.6 |
| 8° | 2959.2 |
| 9° | 2882.2 |
| 10° | 2794.2 |
| 11° | 2692.0 |
| 12° | 2576.8 |
| 13° | 2445.3 |
| 14° | 2299.2 |
| 15° | 2141.0 |
| 17.5° | 1697.8 |
| 20° | 1233.1 |
| 22.5° | 789.4 |
| 25° | 442.1 |
| 27.5° | 233.1 |
| 30° | 132.0 |
| 32.5° | 83.8 |
| 35° | 55.5 |
| 37.5° | 36.7 |
| 40° | 24.1 |
| 42.5° | 15.7 |
| 45° | 10.5 |
| 47.5° | 7.3 |
| 50° | 5.2 |
| 52.5° | 3.7 |
| 55° | 2.6 |
| 57.5° | 1.6 |
| 60° | 1.0 |
| 62.5° | 0.5 |
| 65° | 0.5 |
| 67.5° | 0.5 |
| 70° | 0.5 |
| 72.5° | 0.0 |
| 75° | 0.0 |
| 77.5° | 0.0 |
| 80° | 0.0 |
| 82.5° | 0.0 |



TEST NUMBER: P279428

CATALOG NUMBER: LDA2B108027D010 EU2B10FL408027 2LBAD1MW

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







| | | |
|-------|--|-----|
| 85° | | 0.0 |
| 87.5° | | 0.0 |



(END OF REPORT)