

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P280341

Luminaire Tested: **LDA2B108030D010 EU2B10WFL558030 2LBAD1B**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P280341  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-5)  
Test Lab: INNOVATION CENTER(G2)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LDA2B108030D010 EU2B10WFL558030 2LBAD1B  
Description: PORTFOLIO 2IN ADJ 1000 LUMEN LED LUMINAIRE WITH WIDE FLOOD OPTIC AND  
2in ADJ spun Refl, Self-Flanged, B  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1147.7 lumens  
Efficiency: N/A  
Efficacy: 114.8 lumens/watt  
Spacing Criteria (0/90/45): 0.74 / 0.74 / 0.73  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 10  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P280341

CATALOG NUMBER: LDA2B108030D010 EU2B10WFL558030 2LBAD1B

### Luminous Intensity Polar Plot





TEST NUMBER: P280341

CATALOG NUMBER: LDA2B108030D010 EU2B10WFL558030 2LBAD1B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	112	109	107	112	110	108	106	106	104	103	102	101	99	98	97	97	95			
2	109	105	101	98	107	103	100	97	100	98	95	97	95	93	95	93	91	90			
3	105	99	95	91	103	98	94	91	95	92	89	93	90	88	91	88	86	85			
4	100	94	89	85	99	93	88	85	91	87	84	89	85	83	87	84	82	80			
5	96	89	84	80	95	88	83	80	86	82	79	85	81	78	83	80	78	76			
6	92	84	79	75	91	84	79	75	82	78	75	81	77	74	80	76	74	72			
7	88	80	75	71	87	80	75	71	78	74	71	77	73	70	76	73	70	69			
8	85	76	71	68	84	76	71	67	75	70	67	74	70	67	73	69	67	65			
9	81	73	68	64	80	72	68	64	72	67	64	71	67	64	70	66	64	62			
10	78	70	65	61	77	69	64	61	69	64	61	68	64	61	67	63	61	59			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	980211
5°	960233
10°	892934
15°	779633
20°	645465
25°	493684
30°	270145
35°	100039
40°	34649
45°	15629
50°	7368
55°	3699
60°	1085
65°	584
70°	721
75°	0
80°	0
85°	0



TEST NUMBER: P280341

CATALOG NUMBER: LDA2B108030D010 EU2B10WFL558030 2LBAD1B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	180.2	15.7
10°-20°	421.9	36.8
20°-30°	398.8	34.7
30°-40°	122.8	10.7
40°-50°	19.4	1.7
50°-60°	4.1	0.4
60°-70°	0.6	0.0
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1000.8	87.2
0°-40°	1123.6	97.9
0°-60°	1147.1	99.9
0°-90°	1147.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1147.7	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1987	
5°	1939	180
15°	1526	422
25°	907	399
35°	166	123
45°	22	19
55°	4	4
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P280341

CATALOG NUMBER: LDA2B108030D010 EU2B10WFL558030 2LBAD1B

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1986.8
1°	1979.3
2°	1970.3
3°	1962.8
4°	1953.3
5°	1938.9
6°	1920.3
7°	1895.3
8°	1861.7
9°	1822.9
10°	1782.4
11°	1737.7
12°	1690.3
13°	1638.7
14°	1585.0
15°	1526.4
17.5°	1371.5
20°	1229.4
22.5°	1085.2
25°	906.9
27.5°	691.9
30°	474.2
32.5°	291.1
35°	166.1
37.5°	92.6
40°	53.8
42.5°	33.5
45°	22.4
47.5°	14.9
50°	9.6
52.5°	6.4
55°	4.3
57.5°	2.7
60°	1.1
62.5°	0.5
65°	0.5
67.5°	0.5
70°	0.5
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P280341

CATALOG NUMBER: LDA2B108030D010 EU2B10WFL558030 2LBAD1B

**CANDELA DISTRIBUTION (continued):**

0°  
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)