

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P495400

Luminaire Tested: **LDA2B108050R60D010 2LBDLC1MB**

Issue Date: 3/9/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



Test Information

Test Method: LM-79-08
Report Number: P495400
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-55)
Test Lab: INNOVATION CENTER
Issue Date: 3/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDA2B108050R60D010 2LBDLC1MB
Description: 1000 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 80 CRI LEDS AND 5000K CCT LEDS
Light Source: -
Ballast/Driver: -

Luminaire Equipment: Sample No. Condition Description


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1090.2 lumens
Efficiency: N/A
Efficacy: 109.0 lumens/watt
Spacing Criteria (0/90/45): 0.9 / 0.9 / 0.86
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct

Input Watts (W): 10
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P495400
CATALOG NUMBER: LDA2B108050R60D010 2LBDLC1MB

Luminous Intensity Polar Plot





TEST NUMBER: P495400

CATALOG NUMBER: LDA2B108050R60D010 2LBDLC1MB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	111	109	106	111	109	107	105	105	103	101	101	100	98	98	97	96	94
2	108	103	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88
3	103	97	92	88	101	95	91	87	93	89	86	90	87	85	88	85	83	82
4	98	90	85	81	96	89	84	81	87	83	80	85	82	79	83	80	78	76
5	93	85	79	75	91	84	79	75	82	78	74	81	77	73	79	76	73	71
6	88	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67
7	84	75	69	65	83	74	69	65	73	68	65	72	68	64	71	67	64	63
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59
9	76	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55
10	73	63	58	54	72	63	58	54	62	57	54	61	57	54	61	57	53	52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	645219
5°	628418
10°	611086
15°	580792
20°	530695
25°	455688
30°	339077
35°	199055
40°	94867
45°	44305
50°	22028
55°	7741
60°	1776
65°	1401
70°	865
75°	1144
80°	0
85°	0



TEST NUMBER: P495400

CATALOG NUMBER: LDA2B108050R60D010 2LBDLC1MB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	119.4	11.0
10°-20°	316.4	29.0
20°-30°	375.7	34.5
30°-40°	212.0	19.5
40°-50°	55.1	5.1
50°-60°	10.0	0.9
60°-70°	1.0	0.1
70°-80°	0.4	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	811.5	74.4
0°-40°	1023.6	93.9
0°-60°	1088.7	99.9
0°-90°	1090.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1090.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1308	
5°	1269	119
15°	1137	316
25°	837	376
35°	330	212
45°	64	55
55°	9	10
65°	1	1
75°	1	0
85°	0	0
90°	0	



TEST NUMBER: P495400

CATALOG NUMBER: LDA2B108050R60D010 2LBDLC1MB

CANDELA DISTRIBUTION (FULL):

0°	
0°	1307.8
1°	1308.4
2°	1299.4
3°	1291.6
4°	1276.7
5°	1268.9
6°	1255.1
7°	1244.9
8°	1235.3
9°	1228.8
10°	1219.8
11°	1202.4
12°	1186.2
13°	1177.3
14°	1156.3
15°	1137.1
16°	1115.0
17°	1088.6
18°	1063.5
19°	1033.5
20°	1010.8
21°	979.7
22.5°	928.2
23°	919.2
24°	875.5
25°	837.1
26°	794.6
27°	745.5
28°	697.0
29°	649.7
30°	595.2
32.5°	458.1
35°	330.5
37.5°	225.8
40°	147.3
42.5°	96.4
45°	63.5
47.5°	43.1
50°	28.7
52.5°	18.0
55°	9.0
57.5°	3.6
60°	1.8
62.5°	1.2
65°	1.2



TEST NUMBER: P495400

CATALOG NUMBER: LDA2B108050R60D010 2LBDLC1MB

CANDELA DISTRIBUTION (continued):

	0°
67.5°	0.6
70°	0.6
72.5°	0.6
75°	0.6
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)