

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P495580

Luminaire Tested: **LDA2B109024R45D010 2LBD1WH**

Issue Date: 3/8/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



Test Information

Test Method: LM-79-08
Report Number: P495580
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-40)
Test Lab: INNOVATION CENTER
Issue Date: 3/8/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDA2B109024R45D010 2LBD1WH
Description: 1000 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 90 CRI LEDS AND 2400K CCT LEDS
Light Source: -
Ballast/Driver: -

Luminaire Equipment: Sample No. Condition Description

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 783.5 lumens
Efficiency: N/A
Efficacy: 78.4 lumens/watt
Spacing Criteria (0/90/45): 0.71 / 0.71 / 0.65
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct

Input Watts (W): 10
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P495580

CATALOG NUMBER: LDA2B109024R45D010 2LBD1WH

Luminous Intensity Polar Plot





TEST NUMBER: P495580

CATALOG NUMBER: LDA2B109024R45D010 2LBD1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	110	108	112	110	108	106	106	104	103	102	101	100	99	98	97	95
2	110	106	102	99	108	104	101	98	101	98	96	98	96	94	95	94	92	91
3	105	100	96	93	104	99	95	92	96	93	90	94	91	89	92	90	88	86
4	101	95	90	87	100	94	90	86	92	88	85	90	87	84	88	86	83	82
5	97	90	86	82	96	90	85	82	88	84	81	86	83	80	85	82	80	78
6	94	86	81	78	92	86	81	77	84	80	77	83	79	76	82	78	76	75
7	90	82	77	74	89	82	77	74	81	76	73	80	76	73	78	75	73	71
8	87	79	74	70	86	78	74	70	77	73	70	76	73	70	76	72	70	68
9	84	76	71	67	83	75	70	67	74	70	67	73	70	67	73	69	67	66
10	81	73	68	65	80	72	68	64	71	67	64	71	67	64	70	67	64	63

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	777588
5°	765750
10°	714587
15°	623645
20°	476827
25°	276918
30°	117469
35°	48604
40°	21511
45°	11094
50°	5526
55°	1290
60°	789
65°	467
70°	577
75°	0
80°	0
85°	0



TEST NUMBER: P495580

CATALOG NUMBER: LDA2B109024R45D010 2LBD1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	143.9	18.4
10°-20°	333.0	42.5
20°-30°	232.8	29.7
30°-40°	57.6	7.4
40°-50°	13.3	1.7
50°-60°	2.2	0.3
60°-70°	0.4	0.1
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	709.7	90.6
0°-40°	767.3	97.9
0°-60°	782.9	99.9
0°-90°	783.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	783.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1576	
5°	1546	144
15°	1221	333
25°	509	233
35°	81	58
45°	16	13
55°	2	2
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P495580

CATALOG NUMBER: LDA2B109024R45D010 2LBD1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1576.1
1°	1572.7
2°	1572.0
3°	1567.0
4°	1553.0
5°	1546.2
6°	1532.2
7°	1512.1
8°	1487.4
9°	1462.0
10°	1426.4
11°	1397.2
12°	1361.6
13°	1315.3
14°	1268.3
15°	1221.0
16°	1168.6
17°	1106.5
18°	1043.6
19°	978.7
20°	908.2
21°	823.7
22.5°	714.2
23°	669.0
24°	587.9
25°	508.7
26°	434.4
27°	365.0
28°	304.0
29°	250.9
30°	206.2
32.5°	127.0
35°	80.7
37.5°	52.3
40°	33.4
42.5°	22.7
45°	15.9
47.5°	11.4
50°	7.2
52.5°	3.8
55°	1.5
57.5°	0.8
60°	0.8
62.5°	0.4
65°	0.4



TEST NUMBER: P495580

CATALOG NUMBER: LDA2B109024R45D010 2LBD1WH

CANDELA DISTRIBUTION (continued):

	0°
67.5°	0.4
70°	0.4
72.5°	0.4
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)