

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P495988

Luminaire Tested: **LDA2B109030R35D010 2LBDL1B**

Issue Date: 3/9/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



**Test Information**

Test Method: LM-79-08  
Report Number: P495988  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-29)  
Test Lab: INNOVATION CENTER  
Issue Date: 3/9/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LDA2B109030R35D010 2LBDL1B  
Description: 1000 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 90 CRI LEDS AND 3000K CCT LEDS  
Light Source: -  
Ballast/Driver: -

Luminaire Equipment: Sample No.    Condition    Description


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 814.3 lumens  
Efficiency: N/A  
Efficacy: 81.4 lumens/watt  
Spacing Criteria (0/90/45): 0.54 / 0.54 / 0.51  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct

Input Watts (W): 10  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P495988  
CATALOG NUMBER: LDA2B109030R35D010 2LBDL1B

### Luminous Intensity Polar Plot





TEST NUMBER: P495988

CATALOG NUMBER: LDA2B109030R35D010 2LBDL1B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92
3	107	102	98	95	105	101	97	94	98	95	93	96	93	91	94	92	90	89
4	103	97	93	90	102	96	92	89	94	91	88	92	90	87	91	88	87	85
5	100	93	89	86	98	93	88	85	91	87	85	89	86	84	88	85	83	82
6	96	90	85	82	95	89	85	82	88	84	81	86	83	81	85	82	80	79
7	93	86	82	79	92	86	82	79	85	81	78	84	80	78	83	80	77	76
8	90	83	79	76	89	83	79	76	82	78	75	81	78	75	80	77	75	74
9	88	81	76	73	87	80	76	73	79	76	73	79	75	73	78	75	72	71
10	85	78	74	71	84	78	73	71	77	73	70	76	73	70	76	72	70	69

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	1242877
5°	1201616
10°	1050089
15°	734124
20°	385473
25°	165596
30°	75711
35°	36679
40°	18677
45°	9489
50°	5219
55°	2236
60°	888
65°	467
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P495988

CATALOG NUMBER: LDA2B109030R35D010 2LBDL1B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	221.2	27.2
10°-20°	383.5	47.1
20°-30°	153.1	18.8
30°-40°	41.7	5.1
40°-50°	11.6	1.4
50°-60°	2.7	0.3
60°-70°	0.5	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	757.8	93.1
0°-40°	799.5	98.2
0°-60°	813.8	99.9
0°-90°	814.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	814.3	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2519	
5°	2426	221
15°	1437	384
25°	304	153
35°	61	42
45°	14	12
55°	3	3
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P495988

CATALOG NUMBER: LDA2B109030R35D010 2LBDL1B

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	2519.2
1°	2508.6
2°	2498.3
3°	2483.0
4°	2460.0
5°	2426.3
6°	2382.4
7°	2327.9
8°	2265.7
9°	2179.6
10°	2096.1
11°	1992.5
12°	1860.0
13°	1726.6
14°	1590.7
15°	1437.3
16°	1286.5
17°	1131.3
18°	992.0
19°	860.3
20°	734.2
21°	618.3
22.5°	479.4
23°	434.6
24°	364.8
25°	304.2
26°	256.1
27°	213.9
28°	181.1
29°	154.3
30°	132.9
32.5°	89.1
35°	60.9
37.5°	42.6
40°	29.0
42.5°	19.6
45°	13.6
47.5°	9.8
50°	6.8
52.5°	4.7
55°	2.6
57.5°	1.3
60°	0.9
62.5°	0.9
65°	0.4



TEST NUMBER: P495988

CATALOG NUMBER: LDA2B109030R35D010 2LBDL1B

**CANDELA DISTRIBUTION (continued):**

	0°
67.5°	0.4
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)