

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P279587

Luminaire Tested: **LDA2B109050D010 EU2B10FL409050 2LBAD1LI**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P279587
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-3)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA2B109050D010 EU2B10FL409050 2LBAD1LI
Description: PORTFOLIO 2IN ADJ 1000 LUMEN LED LUMINAIRE WITH FLOOD OPTIC AND 2in
ADJ spun Refl, Self-Flanged, LI
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1030.8 lumens
Efficiency: N/A
Efficacy: 103.1 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.55
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 10
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P279587

CATALOG NUMBER: LDA2B109050D010 EU2B10FL409050 2LBAD1LI

Luminous Intensity Polar Plot





TEST NUMBER: P279587

CATALOG NUMBER: LDA2B109050D010 EU2B10FL409050 2LBAD1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20																		
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																
RCR	0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100	100	100	100	100	100	100	100	100																
	1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96	96	96	96	96	96	96	96	96	96	96	96																
	2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92	92	92	92	92	92	92	92	92	92	92	92	92															
	3	107	102	98	95	105	101	97	94	98	95	93	96	94	92	94	92	90	89	89	89	89	89	89	89	89	89	89	89	89	89															
	4	103	98	93	90	102	97	93	90	95	91	89	93	90	88	91	89	87	85	85	85	85	85	85	85	85	85	85	85	85	85															
	5	100	94	89	86	98	93	89	86	91	88	85	90	87	84	88	86	83	82	82	82	82	82	82	82	82	82	82	82	82	82															
	6	97	90	85	82	95	89	85	82	88	84	82	87	83	81	85	83	80	79	79	79	79	79	79	79	79	79	79	79	79	79															
	7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77	77	77	77	77	77	77	77	77	77	77	77	77	77														
	8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74	74	74	74	74	74	74	74	74	74	74	74	74	74														
	9	88	81	76	73	87	80	76	73	79	76	73	79	75	73	78	75	73	72	72	72	72	72	72	72	72	72	72	72	72	72	72														
	10	85	78	74	71	84	78	74	71	77	73	71	76	73	70	76	72	70	69	69	69	69	69	69	69	69	69	69	69	69	69	69														

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1417379
5°	1387383
10°	1264505
15°	987821
20°	584825
25°	217419
30°	67906
35°	30235
40°	14040
45°	6628
50°	3607
55°	2064
60°	888
65°	584
70°	721
75°	0
80°	0
85°	0



TEST NUMBER: P279587

CATALOG NUMBER: LDA2B109050D010 EU2B10FL409050 2LBAD1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	259.0	25.1
10°-20°	515.0	50.0
20°-30°	210.9	20.5
30°-40°	34.9	3.4
40°-50°	8.3	0.8
50°-60°	2.2	0.2
60°-70°	0.5	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	984.8	95.5
0°-40°	1019.7	98.9
0°-60°	1030.2	99.9
0°-90°	1030.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1030.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2873	
5°	2801	259
15°	1934	515
25°	399	211
35°	50	35
45°	10	8
55°	2	2
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P279587

CATALOG NUMBER: LDA2B109050D010 EU2B10FL409050 2LBAD1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	2872.9
1°	2862.9
2°	2849.7
3°	2837.9
4°	2822.2
5°	2801.4
6°	2770.7
7°	2730.4
8°	2673.2
9°	2603.6
10°	2524.1
11°	2431.8
12°	2327.7
13°	2209.0
14°	2076.9
15°	1934.0
17.5°	1533.7
20°	1113.9
22.5°	713.1
25°	399.4
27.5°	210.6
30°	119.2
32.5°	75.7
35°	50.2
37.5°	33.1
40°	21.8
42.5°	14.2
45°	9.5
47.5°	6.6
50°	4.7
52.5°	3.3
55°	2.4
57.5°	1.4
60°	0.9
62.5°	0.5
65°	0.5
67.5°	0.5
70°	0.5
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P279587

CATALOG NUMBER: LDA2B109050D010 EU2B10FL409050 2LBAD1LI

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)