

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P496361

Luminaire Tested: **LDA2B109040R30D010 2LBD1LI-30DEG TILT**

Issue Date: 3/8/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



**Test Information**

Test Method: LM-79-08  
Report Number: P496361  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-15)  
Test Lab: INNOVATION CENTER  
Issue Date: 3/8/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LDA2B109040R30D010 2LBD1LI-30DEG TILT  
Description: 1000 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 90 CRI LEDS AND 4000K CCT LEDS  
Light Source: -  
Ballast/Driver: -

Luminaire Equipment: Sample No.    Condition    Description

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 623.3 lumens  
Efficiency: N/A  
Efficacy: 62.3 lumens/watt  
Spacing Criteria (0/90/45): 3.2 / 0.53 / 1.4  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct

Input Watts (W): 10  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P496361

CATALOG NUMBER: LDA2B109040R30D010 2LBD1LI-30DEG TILT

### Luminous Intensity Polar Plot



— 0°-180°    - - 45°-225°    - - - 90°-270°



TEST NUMBER: P496361

CATALOG NUMBER: LDA2B109040R30D010 2LBD1LI-30DEG TILT

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	112	109	106	103	109	106	104	101	102	100	98	98	97	95	95	94	92					90				
2	104	98	93	89	102	97	92	88	93	89	86	90	87	84	87	85	82					80				
3	97	89	83	77	95	87	82	77	85	80	76	82	78	74	80	76	73					71				
4	90	80	73	68	88	79	72	67	77	71	66	75	70	66	73	68	65					63				
5	83	73	65	60	82	72	65	59	70	63	59	68	62	58	66	61	57					56				
6	77	66	58	52	76	65	58	52	63	57	52	62	56	51	60	55	51					49				
7	72	60	52	46	70	59	51	46	57	51	46	56	50	46	55	49	45					44				
8	66	54	46	41	65	54	46	41	52	46	41	51	45	41	50	44	40					39				
9	62	49	42	37	60	49	42	37	48	41	36	47	41	36	46	40	36					34				
10	57	45	38	33	56	45	37	33	44	37	32	43	37	32	42	36	32					31				

**AVERAGE LUMINANCE (cd/sqm):**

	0°	90°	180°
0°	6907	6907	6907
5°	15006	6290	4457
10°	45037	5411	2956
15°	273209	3933	2298
20°	978226	2153	945
25°	1589708	762	0
30°	1744775	285	0
35°	1585572	0	0
40°	1360852	0	0
45°	1008692	0	0
50°	682108	0	0
55°	230434	430	0
60°	32957	888	0
65°	2685	1051	0
70°	0	1298	0
75°	0	2669	0
80°	0	2557	0
85°	0	5095	0



TEST NUMBER: P496361

CATALOG NUMBER: LDA2B109040R30D010 2LBD1LI-30DEG TILT

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	1.8	0.3
10°-20°	32.1	5.2
20°-30°	182.2	29.2
30°-40°	237.4	38.1
40°-50°	139.1	22.3
50°-60°	28.1	4.5
60°-70°	1.1	0.2
70°-80°	0.8	0.1
80°-90°	0.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	216.2	34.7
0°-40°	453.6	72.8
0°-60°	620.8	99.6
0°-90°	623.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	623.3	100.0

**CANDELA DISTRIBUTION:**

	0°	45°	90°	135°	180°	Flux
0°	14	14	14	14	14	
5°	30	22	13	10	9	5
15°	535	61	8	5	4	226
25°	2920	103	1	1	0	1291
35°	2633	75	0	0	0	1639
45°	1446	18	0	0	0	1129
55°	268	2	0	0	0	313
65°	2	0	1	1	0	6
75°	0	1	1	1	0	0
85°	0	1	1	1	0	0
90°	0	0	0	0	0	



TEST NUMBER: P496361

CATALOG NUMBER: LDA2B109040R30D010 2LBD1LI-30DEG TILT

**CANDELA DISTRIBUTION (FULL):**

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°
0°	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0	14.0
2.5°	19.0	17.6	16.7	14.5	13.1	12.2	11.7	11.3	10.8
5°	30.3	28.0	21.7	15.8	12.7	10.8	9.9	9.0	9.0
7.5°	52.0	42.0	28.5	16.7	11.7	9.5	8.6	7.2	6.8
10°	89.9	70.0	38.9	17.6	10.8	8.6	6.8	6.3	5.9
12.5°	211.0	127.9	49.2	17.6	9.5	7.2	5.9	5.4	5.0
15°	534.9	260.7	61.0	16.7	7.7	5.4	5.0	4.5	4.5
17.5°	1109.6	535.4	74.1	15.4	6.3	4.1	3.6	3.2	3.2
20°	1863.2	959.6	86.7	13.1	4.1	2.7	2.3	1.8	1.8
21°	2140.6	1113.7	93.1	12.2	3.6	2.3	1.8	1.8	1.4
22°	2389.9	1255.1	96.7	11.7	2.7	1.8	1.8	1.4	1.4
23°	2550.8	1434.4	99.8	10.4	2.3	1.4	1.4	0.9	0.5
24°	2793.4	1574.9	101.2	9.5	1.8	1.4	0.9	0.5	0.5
25°	2920.3	1702.3	102.6	8.6	1.4	1.4	0.9	0.5	0.0
26°	3011.6	1803.1	107.5	8.1	1.4	0.9	0.9	0.5	0.0
27°	3083.0	1867.2	110.2	7.2	0.9	0.9	0.9	0.0	0.0
28°	3078.9	1913.8	108.0	6.3	0.9	0.9	0.5	0.0	0.0
29°	3098.3	1945.4	106.6	5.4	0.5	0.5	0.5	0.0	0.0
30°	3062.7	1948.1	101.7	5.0	0.5	0.5	0.5	0.0	0.0
31°	3008.4	1915.1	99.8	4.5	0.0	0.5	0.5	0.0	0.0
32°	2957.4	1900.2	94.0	3.6	0.0	0.5	0.5	0.0	0.0
33°	2869.7	1833.3	88.1	3.2	0.0	0.5	0.0	0.0	0.0
34°	2752.3	1767.8	82.7	2.7	0.0	0.5	0.0	0.0	0.0
35°	2632.6	1713.6	75.0	2.7	0.0	0.5	0.0	0.0	0.0
36°	2533.2	1615.1	69.6	2.3	0.0	0.5	0.0	0.0	0.0
37°	2412.5	1530.7	62.3	1.8	0.0	0.0	0.0	0.0	0.0
38°	2330.3	1411.8	56.9	1.8	0.0	0.0	0.0	0.0	0.0
39°	2219.6	1311.5	50.1	1.4	0.0	0.0	0.0	0.0	0.0
40°	2113.0	1207.6	43.4	0.9	0.0	0.0	0.0	0.0	0.0
42.5°	1807.1	931.6	29.8	0.5	0.0	0.0	0.0	0.0	0.0
45°	1445.7	683.1	18.5	0.0	0.0	0.0	0.0	0.0	0.0
47.5°	1148.0	461.3	11.7	0.0	0.0	0.0	0.0	0.0	0.0
50°	888.7	237.6	6.8	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	590.9	100.7	4.1	0.0	0.0	0.5	0.0	0.0	0.0
55°	267.9	52.4	1.8	0.0	0.5	0.5	0.5	0.0	0.0
57.5°	108.0	22.6	0.9	0.5	0.5	0.5	0.5	0.0	0.0
60°	33.4	6.3	0.5	0.5	0.9	0.9	0.5	0.0	0.0
62.5°	6.8	1.4	0.5	0.9	0.9	0.9	0.5	0.0	0.0
65°	2.3	0.5	0.5	0.9	0.9	0.9	0.9	0.0	0.0
67.5°	0.5	0.5	0.5	0.9	0.9	0.9	0.9	0.5	0.0
70°	0.0	0.5	0.9	0.9	0.9	1.4	0.9	0.5	0.0
72.5°	0.0	0.5	0.9	0.9	0.9	0.9	0.9	0.5	0.0
75°	0.0	0.5	0.9	0.9	1.4	1.4	0.9	0.5	0.0
77.5°	0.0	0.5	0.9	0.9	0.9	0.9	0.9	0.5	0.0
80°	0.0	0.5	0.9	0.9	0.9	0.9	0.9	0.5	0.0



TEST NUMBER: P496361

CATALOG NUMBER: LDA2B109040R30D010 2LBD1LI-30DEG TILT

**CANDELA DISTRIBUTION (continued):**

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°
82.5°	0.0	0.5	0.9	0.9	0.9	0.9	0.9	0.5	0.0
85°	0.0	0.5	0.9	0.9	0.9	0.9	0.9	0.0	0.0
87.5°	0.0	0.5	0.9	0.9	0.9	0.9	0.5	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)