

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P280450

Luminaire Tested: **LDA2B109035D010 EU2B10WFL559035 2LBAD1H**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P280450  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-5)  
Test Lab: INNOVATION CENTER(G2)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LDA2B109035D010 EU2B10WFL559035 2LBAD1H  
Description: PORTFOLIO 2IN ADJ 1000 LUMEN LED LUMINAIRE WITH WIDE FLOOD OPTIC AND  
2in ADJ spun Refl, Self-Flanged, H  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 965.0 lumens  
Efficiency: N/A  
Efficacy: 96.5 lumens/watt  
Spacing Criteria (0/90/45): 0.74 / 0.74 / 0.73  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 10  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P280450

CATALOG NUMBER: LDA2B109035D010 EU2B10WFL559035 2LBAD1H

### Luminous Intensity Polar Plot





TEST NUMBER: P280450

CATALOG NUMBER: LDA2B109035D010 EU2B10WFL559035 2LBAD1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10		0		
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	112	109	107	112	110	108	106	106	104	103	102	101	99	98	97	97	95			
2	109	105	101	98	107	103	100	97	100	98	95	97	95	93	95	93	91	90			
3	105	99	95	91	103	98	94	91	95	92	89	93	90	88	91	88	86	85			
4	100	94	89	85	99	93	88	85	91	87	84	89	85	83	87	84	82	80			
5	96	89	84	80	95	88	83	80	86	82	79	85	81	78	83	80	78	76			
6	92	84	79	75	91	84	79	75	82	78	75	81	77	74	80	76	74	72			
7	88	80	75	71	87	80	75	71	78	74	71	77	73	70	76	73	70	69			
8	85	76	71	68	84	76	71	67	75	70	67	74	70	67	73	69	67	65			
9	81	73	68	64	80	72	68	64	72	67	64	71	67	64	70	66	64	62			
10	78	70	65	61	77	69	64	61	69	64	61	68	64	61	67	63	61	60			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	824210
5°	807400
10°	750808
15°	655568
20°	542718
25°	415132
30°	227133
35°	84079
40°	29111
45°	13117
50°	6217
55°	3097
60°	888
65°	467
70°	577
75°	0
80°	0
85°	0



TEST NUMBER: P280450

CATALOG NUMBER: LDA2B109035D010 EU2B10WFL559035 2LBAD1H

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	151.5	15.7
10°-20°	354.7	36.8
20°-30°	335.3	34.7
30°-40°	103.2	10.7
40°-50°	16.3	1.7
50°-60°	3.5	0.4
60°-70°	0.5	0.0
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	841.5	87.2
0°-40°	944.7	97.9
0°-60°	964.5	99.9
0°-90°	965.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	965.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1671	
5°	1630	151
15°	1284	355
25°	763	335
35°	140	103
45°	19	16
55°	4	3
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P280450

CATALOG NUMBER: LDA2B109035D010 EU2B10WFL559035 2LBAD1H

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	1670.6
1°	1664.3
2°	1656.7
3°	1650.4
4°	1642.4
5°	1630.3
6°	1614.6
7°	1593.6
8°	1565.4
9°	1532.7
10°	1498.7
11°	1461.1
12°	1421.3
13°	1377.9
14°	1332.7
15°	1283.5
17.5°	1153.2
20°	1033.7
22.5°	912.5
25°	762.6
27.5°	581.8
30°	398.7
32.5°	244.8
35°	139.6
37.5°	77.9
40°	45.2
42.5°	28.2
45°	18.8
47.5°	12.5
50°	8.1
52.5°	5.4
55°	3.6
57.5°	2.2
60°	0.9
62.5°	0.4
65°	0.4
67.5°	0.4
70°	0.4
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P280450

CATALOG NUMBER: LDA2B109035D010 EU2B10WFL559035 2LBAD1H

CANDELA DISTRIBUTION (continued):

0°  
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)