

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P280621

Luminaire Tested: **LDA2B158050D010 EU2B15WFL558050 2LBALD1B**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P280621  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-5)  
Test Lab: INNOVATION CENTER(G2)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LDA2B158050D010 EU2B15WFL558050 2LBALD1B  
Description: PORTFOLIO 2IN ADJ 1500 LUMEN LED LUMINAIRE WITH WIDE FLOOD OPTIC AND  
2in ADJ spun Refl w/lens Self-Flanged, B  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1575.5 lumens  
Efficiency: N/A  
Efficacy: 111.7 lumens/watt  
Spacing Criteria (0/90/45): 0.74 / 0.74 / 0.73  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 14.1  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P280621

CATALOG NUMBER: LDA2B158050D010 EU2B15WFL558050 2LBALD1B

### Luminous Intensity Polar Plot





TEST NUMBER: P280621

CATALOG NUMBER: LDA2B158050D010 EU2B15WFL558050 2LBALD1B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20				
RC	80				70				50				30				10			0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	114	112	109	107	112	110	108	106	106	104	103	102	101	99	98	97	97	95			
2	109	105	101	98	107	103	100	97	100	98	95	97	95	93	95	93	91	90			
3	105	99	95	91	103	98	94	91	95	92	89	93	90	88	91	88	86	85			
4	100	94	89	85	99	93	88	85	91	87	84	89	85	83	87	84	82	80			
5	96	89	84	80	95	88	83	80	86	82	79	85	81	78	83	80	78	76			
6	92	84	79	75	91	84	79	75	82	78	75	81	77	74	80	76	74	72			
7	88	80	75	71	87	80	75	71	78	74	71	77	73	70	76	73	70	69			
8	85	76	71	68	84	76	71	67	75	70	67	74	70	67	73	69	67	65			
9	81	73	68	64	80	72	68	64	72	67	64	71	67	64	70	66	64	62			
10	78	70	65	61	77	69	64	61	69	64	61	68	64	61	67	63	61	59			

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	1345546
5°	1318098
10°	1225730
15°	1070207
20°	886084
25°	677679
30°	370865
35°	137260
40°	47530
45°	21420
50°	10131
55°	4989
60°	1480
65°	817
70°	1010
75°	0
80°	0
85°	0



TEST NUMBER: P280621

CATALOG NUMBER: LDA2B158050D010 EU2B15WFL558050 2LBALD1B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	247.3	15.7
10°-20°	579.1	36.8
20°-30°	547.4	34.7
30°-40°	168.5	10.7
40°-50°	26.6	1.7
50°-60°	5.7	0.4
60°-70°	0.8	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1373.8	87.2
0°-40°	1542.3	97.9
0°-60°	1574.6	99.9
0°-90°	1575.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1575.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2727	
5°	2662	247
15°	2095	579
25°	1245	547
35°	228	168
45°	31	27
55°	6	6
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P280621

CATALOG NUMBER: LDA2B158050D010 EU2B15WFL558050 2LBALD1B

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	2727.3
1°	2717.1
2°	2704.6
3°	2694.4
4°	2681.3
5°	2661.5
6°	2636.0
7°	2601.6
8°	2555.6
9°	2502.3
10°	2446.7
11°	2385.4
12°	2320.3
13°	2249.5
14°	2175.7
15°	2095.3
17.5°	1882.7
20°	1687.7
22.5°	1489.7
25°	1244.9
27.5°	949.8
30°	651.0
32.5°	399.6
35°	227.9
37.5°	127.1
40°	73.8
42.5°	46.0
45°	30.7
47.5°	20.5
50°	13.2
52.5°	8.8
55°	5.8
57.5°	3.7
60°	1.5
62.5°	0.7
65°	0.7
67.5°	0.7
70°	0.7
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P280621

CATALOG NUMBER: LDA2B158050D010 EU2B15WFL558050 2LBALD1B

**CANDELA DISTRIBUTION (continued):**

0°  
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)