

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P278905

Luminaire Tested: **LDA2B159040D010 EU2B15NFL259040 2LBAD1GPH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P278905
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-2)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA2B159040D010 EU2B15NFL259040 2LBAD1GPH
Description: PORTFOLIO 2IN ADJ 1500 LUMEN LED LUMINAIRE WITH NARROW FLOOD OPTIC
AND 2in ADJ spun Refl, Self-Flanged, GPH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1289.5 lumens
Efficiency: N/A
Efficacy: 91.5 lumens/watt
Spacing Criteria (0/90/45): 0.39 / 0.39 / 0.39
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 14.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P278905

CATALOG NUMBER: LDA2B159040D010 EU2B15NFL259040 2LBAD1GPH

Luminous Intensity Polar Plot





TEST NUMBER: P278905

CATALOG NUMBER: LDA2B159040D010 EU2B15NFL259040 2LBAD1GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20									
RC	80									70									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																			
RCR																																														
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100										100																		
1	115	113	111	110	113	111	109	108	107	106	105	103	102	102	100	99	99	97										97																		
2	112	108	105	103	110	107	104	102	103	101	100	101	99	98	98	97	96	94										94																		
3	108	104	100	98	107	103	99	97	100	98	95	98	96	94	96	94	93	91										91																		
4	105	100	96	94	104	99	96	93	97	94	92	95	93	91	94	92	90	89										89																		
5	102	97	93	90	101	96	92	90	94	91	89	93	90	88	92	89	87	86										86																		
6	100	94	90	87	98	93	89	87	92	89	86	91	88	86	89	87	85	84										84																		
7	97	91	87	84	96	90	87	84	89	86	84	88	85	83	87	85	83	82										82																		
8	95	88	85	82	94	88	84	82	87	84	81	86	83	81	85	83	81	80										80																		
9	92	86	82	80	92	86	82	80	85	82	79	84	81	79	84	81	79	78										78																		
10	90	84	80	78	90	84	80	78	83	80	78	82	79	77	82	79	77	76										76																		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	3300590
5°	3043982
10°	2051233
15°	1011367
20°	431990
25°	169842
30°	66881
35°	29331
40°	14104
45°	6768
50°	3761
55°	2064
60°	1184
65°	700
70°	865
75°	0
80°	0
85°	0



TEST NUMBER: P278905

CATALOG NUMBER: LDA2B159040D010 EU2B15NFL259040 2LBAD1GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	520.6	40.4
10°-20°	560.7	43.5
20°-30°	161.9	12.6
30°-40°	34.2	2.7
40°-50°	8.4	0.7
50°-60°	2.4	0.2
60°-70°	0.8	0.1
70°-80°	0.4	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1243.3	96.4
0°-40°	1277.4	99.1
0°-60°	1288.3	99.9
0°-90°	1289.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1289.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6690	
5°	6146	521
15°	1980	561
25°	312	162
35°	49	34
45°	10	8
55°	2	2
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P278905

CATALOG NUMBER: LDA2B159040D010 EU2B15NFL259040 2LBAD1GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	6690.0
1°	6648.1
2°	6576.9
3°	6480.8
4°	6344.6
5°	6146.4
6°	5878.8
7°	5529.7
8°	5100.4
9°	4599.9
10°	4094.5
11°	3583.7
12°	3101.5
13°	2673.3
14°	2296.9
15°	1980.1
17.5°	1308.7
20°	822.8
22.5°	506.0
25°	312.0
27.5°	190.3
30°	117.4
32.5°	74.2
35°	48.7
37.5°	32.2
40°	21.9
42.5°	15.2
45°	9.7
47.5°	6.1
50°	4.9
52.5°	3.6
55°	2.4
57.5°	1.8
60°	1.2
62.5°	1.2
65°	0.6
67.5°	0.6
70°	0.6
72.5°	0.6
75°	0.0
77.5°	0.6
80°	0.0
82.5°	0.0



TEST NUMBER: P278905

CATALOG NUMBER: LDA2B159040D010 EU2B15NFL259040 2LBAD1GPH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)