

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P498936

Luminaire Tested: **LDA2B159035R20D010 2LBDL1MMS-30DEG TILT**

Issue Date: 3/8/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



**Test Information**

Test Method: LM-79-08  
Report Number: P498936  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-2)  
Test Lab: INNOVATION CENTER  
Issue Date: 3/8/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LDA2B159035R20D010 2LBDL1MMS-30DEG TILT  
Description: 1500 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 90 CRI LEDS AND 3500K CCT LEDS  
Light Source: -  
Ballast/Driver: -

Luminaire Equipment: Sample No.    Condition    Description

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 657.3 lumens  
Efficiency: N/A  
Efficacy: 46.6 lumens/watt  
Spacing Criteria (0/90/45): 2.56 / 0.56 / 1.2  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct

Input Watts (W): 14.1  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P498936

CATALOG NUMBER: LDA2B159035R20D010 2LBDL1MMS-30DEG TILT

### Luminous Intensity Polar Plot



— 0°-180°    - - 45°-225°    - - - 90°-270°



TEST NUMBER: P498936

CATALOG NUMBER: LDA2B159035R20D010 2LBDL1MMS-30DEG TILT

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91					91			
2	105	100	95	91	103	98	93	90	95	91	88	91	88	86	89	86	84	82					82			
3	99	91	85	80	96	89	84	79	87	82	78	84	80	77	82	78	76	74					74			
4	92	83	76	71	90	82	75	70	79	74	70	77	73	69	75	71	68	66					66			
5	86	75	68	63	84	74	68	63	73	67	62	71	66	62	69	65	61	59					59			
6	80	69	62	56	78	68	61	56	66	60	56	65	59	55	63	59	55	53					53			
7	74	63	55	50	73	62	55	50	61	54	50	59	54	50	58	53	49	48					48			
8	69	57	50	45	68	57	50	45	56	49	45	54	49	44	53	48	44	43					43			
9	64	53	45	40	63	52	45	40	51	45	40	50	44	40	49	44	40	38					38			
10	60	48	41	36	59	48	41	36	47	41	36	46	40	36	45	40	36	34					34			

**AVERAGE LUMINANCE (cd/sqm):**

	0°	90°	180°
0°	10459	10459	10459
5°	19958	9212	6735
10°	47693	8066	4559
15°	278010	6436	1788
20°	1386695	3990	525
25°	2528519	1361	0
30°	2965667	0	0
35°	2595722	0	0
40°	1916851	0	0
45°	690951	0	0
50°	143913	0	0
55°	32944	430	0
60°	10459	493	0
65°	2335	1167	0
70°	0	1442	721
75°	0	1906	0
80°	0	2841	0
85°	0	5661	0



TEST NUMBER: P498936

CATALOG NUMBER: LDA2B159035R20D010 2LBDL1MMS-30DEG TILT

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	2.4	0.4
10°-20°	36.1	5.5
20°-30°	243.4	37.0
30°-40°	284.4	43.3
40°-50°	82.9	12.6
50°-60°	5.5	0.8
60°-70°	1.0	0.2
70°-80°	0.8	0.1
80°-90°	0.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	281.9	42.9
0°-40°	566.3	86.2
0°-60°	654.8	99.6
0°-90°	657.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	657.3	100.0

**CANDELA DISTRIBUTION:**

	0°	45°	90°	135°	180°	Flux
0°	21	21	21	21	21	
5°	40	29	19	16	14	5
15°	544	62	13	7	4	284
25°	4645	95	2	0	0	2057
35°	4310	51	0	0	0	2648
45°	990	11	0	0	0	912
55°	38	2	0	0	0	49
65°	2	1	1	1	0	3
75°	0	1	1	1	0	0
85°	0	1	1	1	0	0
90°	0	0	0	0	0	



TEST NUMBER: P498936

CATALOG NUMBER: LDA2B159035R20D010 2LBDL1MMS-30DEG TILT

**CANDELA DISTRIBUTION (FULL):**

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°
0°	21.2	21.2	21.2	21.2	21.2	21.2	21.2	21.2	21.2
2.5°	27.2	27.2	24.2	21.7	19.7	18.6	18.1	17.1	16.6
5°	40.3	35.3	29.2	22.7	18.6	17.1	15.6	14.1	13.6
7.5°	59.0	51.4	35.3	23.2	17.6	15.1	13.6	12.1	11.1
10°	95.2	74.1	43.3	23.2	16.1	13.1	11.1	9.6	9.1
12.5°	175.9	113.4	51.9	22.7	14.6	11.1	8.6	7.6	6.0
15°	544.3	234.8	61.5	21.7	12.6	8.6	6.6	4.0	3.5
17.5°	1407.5	548.3	68.5	19.2	10.1	6.0	3.0	2.5	2.5
20°	2641.2	994.3	78.6	16.6	7.6	4.0	2.0	1.5	1.0
21°	3013.1	1216.5	83.7	15.6	6.6	2.5	1.5	0.5	0.5
22°	3591.1	1458.9	87.7	14.6	5.5	1.5	1.0	0.5	0.0
23°	4002.9	1613.6	91.7	13.1	4.0	1.5	0.5	0.0	0.0
24°	4414.6	1810.7	94.2	12.1	3.5	1.0	0.5	0.0	0.0
25°	4644.9	1975.0	95.2	11.1	2.5	0.5	0.0	0.0	0.0
26°	4834.4	2084.8	95.8	10.1	1.5	0.0	0.0	0.0	0.0
27°	4996.7	2212.3	94.7	9.1	1.5	0.0	0.0	0.0	0.0
28°	5088.9	2233.5	93.2	8.1	0.5	0.0	0.0	0.0	0.0
29°	5128.7	2207.8	88.7	7.1	0.5	0.0	0.0	0.0	0.0
30°	5205.8	2183.6	84.2	6.6	0.0	0.0	0.0	0.0	0.0
31°	5134.7	2103.5	78.6	5.5	0.0	0.0	0.0	0.0	0.0
32°	4856.6	2036.0	72.1	4.5	0.0	0.0	0.0	0.0	0.0
33°	4773.4	1897.4	65.0	4.0	0.0	0.0	0.0	0.0	0.0
34°	4616.7	1691.3	59.0	3.5	0.0	0.0	0.0	0.0	0.0
35°	4309.8	1520.9	51.4	3.0	0.0	0.0	0.0	0.0	0.0
36°	4095.6	1326.4	44.9	2.5	0.0	0.0	0.0	0.0	0.0
37°	3871.3	1156.6	39.8	2.0	0.0	0.0	0.0	0.0	0.0
38°	3592.7	978.2	33.8	1.5	0.0	0.0	0.0	0.0	0.0
39°	3268.1	808.3	28.7	1.5	0.0	0.0	0.0	0.0	0.0
40°	2976.3	651.6	24.7	1.0	0.0	0.0	0.0	0.0	0.0
42.5°	1836.9	371.9	14.6	1.0	0.0	0.0	0.0	0.0	0.0
45°	990.3	225.8	10.6	0.5	0.0	0.0	0.0	0.0	0.0
47.5°	456.1	105.3	7.6	0.5	0.0	0.0	0.0	0.0	0.0
50°	187.5	46.9	5.5	0.0	0.0	0.0	0.0	0.0	0.0
52.5°	67.5	26.2	3.5	0.0	0.0	0.5	0.0	0.0	0.0
55°	38.3	15.1	2.0	0.5	0.5	0.5	0.5	0.0	0.0
57.5°	18.1	8.6	0.5	0.5	0.5	0.5	0.5	0.0	0.0
60°	10.6	4.5	0.5	0.5	0.5	1.0	0.5	0.0	0.0
62.5°	5.0	1.5	0.5	1.0	1.0	1.0	1.0	0.5	0.0
65°	2.0	0.5	1.0	1.0	1.0	1.5	1.0	0.5	0.0
67.5°	0.5	0.5	1.0	1.0	1.0	1.5	1.0	0.5	0.5
70°	0.0	0.5	1.0	1.0	1.0	1.5	1.0	0.5	0.5
72.5°	0.0	0.5	1.0	1.0	1.0	1.5	1.0	0.5	0.5
75°	0.0	0.5	1.0	1.0	1.0	1.0	1.0	0.5	0.0
77.5°	0.0	0.5	1.0	1.0	1.0	1.0	1.0	0.5	0.0
80°	0.0	0.5	1.0	1.0	1.0	1.0	1.0	0.5	0.0



TEST NUMBER: P498936

CATALOG NUMBER: LDA2B159035R20D010 2LBDL1MMS-30DEG TILT

**CANDELA DISTRIBUTION (continued):**

	0°	22.5°	45°	67.5°	90°	112.5°	135°	157.5°	180°
82.5°	0.0	0.5	1.0	1.0	1.0	1.0	1.0	0.5	0.0
85°	0.0	0.5	1.0	1.0	1.0	1.0	1.0	0.5	0.0
87.5°	0.0	0.5	1.0	1.0	1.0	1.0	0.5	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

(END OF REPORT)