

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P499232

Luminaire Tested: **LDA2B159040R35D010 2LBDL1MB**

Issue Date: 3/9/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



**Test Information**

Test Method: LM-79-08  
Report Number: P499232  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-29)  
Test Lab: INNOVATION CENTER  
Issue Date: 3/9/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LDA2B159040R35D010 2LBDL1MB  
Description: 1500 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 90 CRI LEDS AND 4000K CCT LEDS  
Light Source: -  
Ballast/Driver: -

Luminaire Equipment: Sample No.    Condition    Description

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1148.8 lumens  
Efficiency: N/A  
Efficacy: 81.5 lumens/watt  
Spacing Criteria (0/90/45): 0.54 / 0.54 / 0.51  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct

Input Watts (W): 14.1  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P499232

CATALOG NUMBER: LDA2B159040R35D010 2LBDL1MB

### Luminous Intensity Polar Plot





TEST NUMBER: P499232

CATALOG NUMBER: LDA2B159040R35D010 2LBDL1MB

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	115	113	111	109	112	110	109	107	106	105	104		103	102	101		99	99	98	96
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		97	95	94	92
3	107	102	98	95	105	101	97	94	98	95	93		96	93	91		94	92	90	89
4	103	97	93	90	102	96	92	89	94	91	88		92	90	87		91	88	87	85
5	100	93	89	86	98	93	88	85	91	87	85		89	86	84		88	85	83	82
6	96	90	85	82	95	89	85	82	88	84	81		86	83	81		85	82	80	79
7	93	86	82	79	92	86	82	79	85	81	78		84	80	78		83	80	77	76
8	90	83	79	76	89	83	79	76	82	78	75		81	78	75		80	77	75	74
9	88	81	76	73	87	80	76	73	79	76	73		79	75	73		78	75	72	71
10	85	78	74	71	84	78	73	71	77	73	70		76	73	70		76	72	70	69

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	1753408
5°	1695179
10°	1481376
15°	1035680
20°	543821
25°	233641
30°	106873
35°	51796
40°	26341
45°	13396
50°	7368
55°	3097
60°	1184
65°	700
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P499232

CATALOG NUMBER: LDA2B159040R35D010 2LBDL1MB

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	312.0	27.2
10°-20°	541.1	47.1
20°-30°	215.9	18.8
30°-40°	58.9	5.1
40°-50°	16.3	1.4
50°-60°	3.8	0.3
60°-70°	0.7	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1069.0	93.1
0°-40°	1127.9	98.2
0°-60°	1148.1	99.9
0°-90°	1148.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1148.8	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3554	
5°	3423	312
15°	2028	541
25°	429	216
35°	86	59
45°	19	16
55°	4	4
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P499232

CATALOG NUMBER: LDA2B159040R35D010 2LBDL1MB

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	3554.0
1°	3538.9
2°	3524.5
3°	3502.9
4°	3470.4
5°	3422.9
6°	3361.0
7°	3284.1
8°	3196.3
9°	3074.9
10°	2957.0
11°	2811.0
12°	2624.0
13°	2435.8
14°	2244.1
15°	2027.7
16°	1814.9
17°	1596.0
18°	1399.5
19°	1213.7
20°	1035.8
21°	872.3
22.5°	676.3
23°	613.2
24°	514.6
25°	429.2
26°	361.3
27°	301.8
28°	255.5
29°	217.6
30°	187.6
32.5°	125.6
35°	86.0
37.5°	60.1
40°	40.9
42.5°	27.7
45°	19.2
47.5°	13.8
50°	9.6
52.5°	6.6
55°	3.6
57.5°	1.8
60°	1.2
62.5°	1.2
65°	0.6



TEST NUMBER: P499232

CATALOG NUMBER: LDA2B159040R35D010 2LBDL1MB

**CANDELA DISTRIBUTION (continued):**

	0°
67.5°	0.6
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)