

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P279008

Luminaire Tested: **LDA2B208030D010 EU2B20NFL258030 2LBALD1WHH**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P279008
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-2)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA2B208030D010 EU2B20NFL258030 2LBALD1WHH
Description: PORTFOLIO 2IN ADJ 2000 LUMEN LED LUMINAIRE WITH NARROW FLOOD OPTIC AND 2in ADJ spun Refl w/lens Self-Flanged, WHH
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1956.6 lumens
Efficiency: N/A
Efficacy: 95.0 lumens/watt
Spacing Criteria (0/90/45): 0.39 / 0.39 / 0.39
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 20.6
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P279008

CATALOG NUMBER: LDA2B208030D010 EU2B20NFL258030 2LBALD1WHH

Luminous Intensity Polar Plot





TEST NUMBER: P279008

CATALOG NUMBER: LDA2B208030D010 EU2B20NFL258030 2LBALD1WHH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

| | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|----|---|-----|--|--|--|--|--|----|--|--|--|--|--|--|--|--|---|
| RF | 20 | | | | | | | | | 20 | | | | | | | | | 20 | | | | | | | | | 20 | | | | | | | | | |
| RC | 80 | | | | | | | | | 50 | | | | | | | | | 30 | | | | | | | | | 10 | | | | | | | | | 0 |
| RW | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 50 | 30 | 10 | 0 | | | | | | | | | | | | | | | | |
| RCR | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 0 | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 | | | | 100 | | | | | | | | | | | | | | | |
| 1 | 115 | 113 | 111 | 110 | 113 | 111 | 109 | 108 | 107 | 106 | 105 | 103 | 102 | 102 | 100 | 99 | 99 | 97 | | | | 97 | | | | | | | | | | | | | | | |
| 2 | 112 | 108 | 105 | 103 | 110 | 107 | 104 | 102 | 103 | 101 | 100 | 101 | 99 | 98 | 98 | 97 | 96 | 94 | | | | 94 | | | | | | | | | | | | | | | |
| 3 | 108 | 104 | 100 | 98 | 107 | 103 | 99 | 97 | 100 | 98 | 95 | 98 | 96 | 94 | 96 | 94 | 93 | 91 | | | | 91 | | | | | | | | | | | | | | | |
| 4 | 105 | 100 | 96 | 94 | 104 | 99 | 96 | 93 | 97 | 94 | 92 | 95 | 93 | 91 | 94 | 92 | 90 | 89 | | | | 89 | | | | | | | | | | | | | | | |
| 5 | 102 | 97 | 93 | 90 | 101 | 96 | 92 | 90 | 94 | 91 | 89 | 93 | 90 | 88 | 92 | 89 | 87 | 86 | | | | 86 | | | | | | | | | | | | | | | |
| 6 | 100 | 94 | 90 | 87 | 98 | 93 | 89 | 87 | 92 | 89 | 86 | 91 | 88 | 86 | 89 | 87 | 85 | 84 | | | | 84 | | | | | | | | | | | | | | | |
| 7 | 97 | 91 | 87 | 84 | 96 | 90 | 87 | 84 | 89 | 86 | 84 | 88 | 85 | 83 | 87 | 85 | 83 | 82 | | | | 82 | | | | | | | | | | | | | | | |
| 8 | 95 | 88 | 85 | 82 | 94 | 88 | 84 | 82 | 87 | 84 | 81 | 86 | 83 | 81 | 85 | 83 | 81 | 80 | | | | 80 | | | | | | | | | | | | | | | |
| 9 | 92 | 86 | 82 | 80 | 92 | 86 | 82 | 80 | 85 | 82 | 79 | 84 | 81 | 79 | 84 | 81 | 79 | 78 | | | | 78 | | | | | | | | | | | | | | | |
| 10 | 90 | 84 | 80 | 78 | 90 | 84 | 80 | 78 | 83 | 80 | 77 | 82 | 79 | 77 | 82 | 79 | 77 | 76 | | | | 76 | | | | | | | | | | | | | | | |

AVERAGE LUMINANCE (cd/sqm):

| | |
|-----|---------|
| | 0° |
| 0° | 5008264 |
| 5° | 4618816 |
| 10° | 3112493 |
| 15° | 1534596 |
| 20° | 655493 |
| 25° | 257702 |
| 30° | 101461 |
| 35° | 44449 |
| 40° | 21382 |
| 45° | 10326 |
| 50° | 5680 |
| 55° | 3183 |
| 60° | 1776 |
| 65° | 1051 |
| 70° | 1298 |
| 75° | 0 |
| 80° | 0 |
| 85° | 0 |



TEST NUMBER: P279008

CATALOG NUMBER: LDA2B208030D010 EU2B20NFL258030 2LBALD1WHH

ZONAL LUMENS:

| Zone | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10° | 790.0 | 40.4 |
| 10°-20° | 850.8 | 43.5 |
| 20°-30° | 245.7 | 12.6 |
| 30°-40° | 51.9 | 2.7 |
| 40°-50° | 12.8 | 0.7 |
| 50°-60° | 3.7 | 0.2 |
| 60°-70° | 1.2 | 0.1 |
| 70°-80° | 0.6 | 0.0 |
| 80°-90° | 0.0 | 0.0 |
| 90°-100° | 0.0 | 0.0 |
| 100°-110° | 0.0 | 0.0 |
| 110°-120° | 0.0 | 0.0 |
| 120°-130° | 0.0 | 0.0 |
| 130°-140° | 0.0 | 0.0 |
| 140°-150° | 0.0 | 0.0 |
| 150°-160° | 0.0 | 0.0 |
| 160°-170° | 0.0 | 0.0 |
| 170°-180° | 0.0 | 0.0 |
| 0°-30° | 1886.5 | 96.4 |
| 0°-40° | 1938.4 | 99.1 |
| 0°-60° | 1954.8 | 99.9 |
| 0°-90° | 1956.6 | 100.0 |
| 90°-120° | 0.0 | 0.0 |
| 90°-150° | 0.0 | 0.0 |
| 90°-180° | 0.0 | 0.0 |
| 0°-180° | 1956.6 | 100.0 |

CANDELA DISTRIBUTION:

| | 0° | Flux |
|-----|-------|------|
| 0° | 10151 | |
| 5° | 9326 | 790 |
| 15° | 3004 | 851 |
| 25° | 473 | 246 |
| 35° | 74 | 52 |
| 45° | 15 | 13 |
| 55° | 4 | 4 |
| 65° | 1 | 1 |
| 75° | 0 | 1 |
| 85° | 0 | 0 |
| 90° | 0 | |



TEST NUMBER: P279008

CATALOG NUMBER: LDA2B208030D010 EU2B20NFL258030 2LBALD1WHH

CANDELA DISTRIBUTION (FULL):

| | 0° |
|-------|---------|
| 0° | 10151.3 |
| 1° | 10087.6 |
| 2° | 9979.6 |
| 3° | 9833.9 |
| 4° | 9627.2 |
| 5° | 9326.3 |
| 6° | 8920.3 |
| 7° | 8390.7 |
| 8° | 7739.2 |
| 9° | 6979.8 |
| 10° | 6212.9 |
| 11° | 5437.8 |
| 12° | 4706.1 |
| 13° | 4056.5 |
| 14° | 3485.3 |
| 15° | 3004.5 |
| 17.5° | 1985.8 |
| 20° | 1248.5 |
| 22.5° | 767.7 |
| 25° | 473.4 |
| 27.5° | 288.8 |
| 30° | 178.1 |
| 32.5° | 112.6 |
| 35° | 73.8 |
| 37.5° | 48.9 |
| 40° | 33.2 |
| 42.5° | 23.1 |
| 45° | 14.8 |
| 47.5° | 9.2 |
| 50° | 7.4 |
| 52.5° | 5.5 |
| 55° | 3.7 |
| 57.5° | 2.8 |
| 60° | 1.8 |
| 62.5° | 1.8 |
| 65° | 0.9 |
| 67.5° | 0.9 |
| 70° | 0.9 |
| 72.5° | 0.9 |
| 75° | 0.0 |
| 77.5° | 0.9 |
| 80° | 0.0 |
| 82.5° | 0.0 |



TEST NUMBER: P279008

CATALOG NUMBER: LDA2B208030D010 EU2B20NFL258030 2LBALD1WHH

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







| | | |
|-------|--|-----|
| 85° | | 0.0 |
| 87.5° | | 0.0 |



(END OF REPORT)