

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P278214

Luminaire Tested: **LDA2B208035D010 EU2B20SP158035 2LBAD1WMH**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P278214  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-1)  
Test Lab: INNOVATION CENTER(G2)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LDA2B208035D010 EU2B20SP158035 2LBAD1WMH  
Description: PORTFOLIO 2IN ADJ 2000 LUMEN LED LUMINAIRE WITH SPOT OPTIC AND 2in  
ADJ spun Refl, Self-Flanged, WMH  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 2025.0 lumens  
Efficiency: N/A  
Efficacy: 98.3 lumens/watt  
Spacing Criteria (0/90/45): 0.28 / 0.28 / 0.28  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 20.6  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P278214

CATALOG NUMBER: LDA2B208035D010 EU2B20SP158035 2LBAD1WMH

### Luminous Intensity Polar Plot





TEST NUMBER: P278214

CATALOG NUMBER: LDA2B208035D010 EU2B20SP158035 2LBAD1WMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	116	114	112	110	113	112	110	109	108	106	105	104	103	102	101	100	99	98	98	98
2	112	109	107	104	110	108	105	103	105	103	101	102	100	99	99	98	97	96	96	96
3	109	105	102	100	108	104	101	99	102	99	98	100	98	96	97	96	95	93	93	93
4	107	102	99	96	105	101	98	96	99	97	95	98	95	94	96	94	93	92	92	92
5	104	99	96	93	103	99	95	93	97	94	92	96	93	91	94	92	91	90	90	90
6	102	97	93	91	101	96	93	91	95	92	90	94	91	89	93	91	89	88	88	88
7	100	95	91	89	99	94	91	88	93	90	88	92	90	88	91	89	87	86	86	86
8	98	93	89	87	97	92	89	87	91	88	86	90	88	86	90	87	86	85	85	85
9	96	91	87	85	95	90	87	85	90	87	85	89	86	84	88	86	84	83	83	83
10	94	89	86	83	94	89	85	83	88	85	83	87	85	83	87	85	83	82	82	82

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	9148161
5°	7293493
10°	3166448
15°	1094009
20°	448529
25°	202612
30°	81522
35°	37944
40°	20609
45°	7675
50°	4605
55°	3441
60°	1973
65°	1167
70°	1442
75°	0
80°	0
85°	0



TEST NUMBER: P278214

CATALOG NUMBER: LDA2B208035D010 EU2B20SP158035 2LBAD1WMH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	1113.0	55.0
10°-20°	668.4	33.0
20°-30°	184.0	9.1
30°-40°	43.8	2.2
40°-50°	10.8	0.5
50°-60°	3.6	0.2
60°-70°	1.4	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1965.4	97.1
0°-40°	2009.2	99.2
0°-60°	2023.5	99.9
0°-90°	2025.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2025.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	18542	
5°	14727	###
15°	2142	668
25°	372	184
35°	63	44
45°	11	11
55°	4	4
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P278214

CATALOG NUMBER: LDA2B208035D010 EU2B20SP158035 2LBAD1WMH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	18542.5
1°	18337.4
2°	17846.2
3°	17096.9
4°	16039.5
5°	14727.0
6°	13124.3
7°	11368.6
8°	9523.9
9°	7827.2
10°	6320.6
11°	5045.0
12°	4015.6
13°	3238.3
14°	2620.1
15°	2141.9
17.5°	1329.5
20°	854.3
22.5°	560.2
25°	372.2
27.5°	239.1
30°	143.1
32.5°	90.0
35°	63.0
37.5°	46.0
40°	32.0
42.5°	19.0
45°	11.0
47.5°	8.0
50°	6.0
52.5°	5.0
55°	4.0
57.5°	3.0
60°	2.0
62.5°	2.0
65°	1.0
67.5°	1.0
70°	1.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P278214

CATALOG NUMBER: LDA2B208035D010 EU2B20SP158035 2LBAD1WMH

**CANDELA DISTRIBUTION (continued):**

0°  
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)