

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P500540

Luminaire Tested: **LDA2B208035R35D010 2LBPIN1H**

Issue Date: 3/12/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



**Test Information**

Test Method: LM-79-08  
Report Number: P500540  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-27)  
Test Lab: INNOVATION CENTER  
Issue Date: 3/12/2021  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LDA2B208035R35D010 2LBPIN1H  
Description: 2000 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 80 CRI LEDS AND 3500K CCT LEDS  
Light Source: -  
Ballast/Driver: -

Luminaire Equipment: Sample No.    Condition    Description

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 1622.6 lumens  
Efficiency: N/A  
Efficacy: 78.8 lumens/watt  
Spacing Criteria (0/90/45): 0.55 / 0.55 / 0.5  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct

Input Watts (W): 20.6  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT

TEST NUMBER: P500540

CATALOG NUMBER: LDA2B208035R35D010 2LBPIN1H

### Luminous Intensity Polar Plot





TEST NUMBER: P500540

CATALOG NUMBER: LDA2B208035R35D010 2LBPIN1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	115	113	111	109	112	111	109	107	107	105	104		103	102	101		100	99	98	96
2	111	107	104	101	109	106	103	100	102	100	98		100	98	96		97	95	94	93
3	107	102	99	96	105	101	98	95	99	96	93		96	94	92		94	92	91	89
4	104	98	94	91	102	97	93	90	95	92	89		93	90	88		91	89	87	86
5	100	94	90	87	99	93	89	86	92	88	86		90	87	85		89	86	84	83
6	97	91	86	83	96	90	86	83	89	85	82		87	84	82		86	83	81	80
7	94	87	83	80	93	87	83	80	86	82	79		85	81	79		84	81	79	78
8	91	84	80	77	90	84	80	77	83	79	77		82	79	76		81	78	76	75
9	89	82	77	75	88	81	77	74	80	77	74		80	76	74		79	76	74	73
10	86	79	75	72	85	79	75	72	78	74	72		77	74	72		77	74	72	71

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	2549990
5°	2452955
10°	2221563
15°	1546394
20°	757821
25°	282688
30°	124134
35°	60349
40°	27629
45°	15001
50°	7292
55°	2064
60°	789
65°	934
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P500540

CATALOG NUMBER: LDA2B208035R35D010 2LBPIN1H

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	457.6	28.2
10°-20°	802.2	49.4
20°-30°	273.4	16.8
30°-40°	68.0	4.2
40°-50°	17.5	1.1
50°-60°	3.2	0.2
60°-70°	0.7	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1533.2	94.5
0°-40°	1601.2	98.7
0°-60°	1621.9	100.0
0°-90°	1622.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1622.6	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	5169	
5°	4953	458
15°	3028	802
25°	519	273
35°	100	68
45°	22	18
55°	2	3
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P500540

CATALOG NUMBER: LDA2B208035R35D010 2LBPIN1H

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	5168.6
1°	5158.2
2°	5118.5
3°	5080.3
4°	5019.0
5°	4953.0
6°	4888.6
7°	4828.2
8°	4697.7
9°	4571.3
10°	4434.5
11°	4210.2
12°	3966.9
13°	3653.5
14°	3363.3
15°	3027.6
16°	2700.0
17°	2358.8
18°	2039.9
19°	1717.0
20°	1443.4
21°	1182.6
22.5°	867.7
23°	779.4
24°	636.2
25°	519.3
26°	429.5
27°	358.7
28°	302.2
29°	255.3
30°	217.9
32.5°	147.9
35°	100.2
37.5°	67.6
40°	42.9
42.5°	29.4
45°	21.5
47.5°	15.1
50°	9.5
52.5°	5.6
55°	2.4
57.5°	1.6
60°	0.8
62.5°	0.8
65°	0.8



TEST NUMBER: P500540

CATALOG NUMBER: LDA2B208035R35D010 2LBPIN1H

**CANDELA DISTRIBUTION (continued):**

	0°
67.5°	0.8
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)