

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P500597

Luminaire Tested: **LDA2B208035R65D010 2LBDL1B**

Issue Date: 3/9/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



Test Information

Test Method: LM-79-08
Report Number: P500597
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-68)
Test Lab: INNOVATION CENTER
Issue Date: 3/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDA2B208035R65D010 2LBDL1B
Description: 2000 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 80 CRI LEDS AND 3500K CCT LEDS
Light Source: -
Ballast/Driver: -

Luminaire Equipment: Sample No. Condition Description


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1850.8 lumens
Efficiency: N/A
Efficacy: 89.8 lumens/watt
Spacing Criteria (0/90/45): 0.94 / 0.94 / 0.94
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct

Input Watts (W): 20.6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P500597
CATALOG NUMBER: LDA2B208035R65D010 2LBDL1B

Luminous Intensity Polar Plot





TEST NUMBER: P500597

CATALOG NUMBER: LDA2B208035R65D010 2LBDL1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	111	108	106	111	108	106	104	104	103	101		101	99	98		97	96	95	93
2	108	103	99	95	105	101	97	94	98	95	92		95	92	90		92	90	88	87
3	102	96	90	86	100	94	89	86	91	88	84		89	86	83		87	84	82	80
4	97	89	83	79	95	88	83	79	86	81	78		84	80	77		82	78	76	74
5	92	83	77	73	90	82	76	72	80	75	72		79	74	71		77	73	70	69
6	87	78	72	67	85	77	71	67	75	70	66		74	69	66		73	69	65	64
7	82	73	67	62	81	72	66	62	71	66	62		70	65	61		68	64	61	60
8	78	68	62	58	77	68	62	58	67	61	58		66	61	57		65	60	57	56
9	74	64	58	54	73	64	58	54	63	57	54		62	57	54		61	57	53	52
10	71	61	55	51	70	60	54	51	59	54	50		59	54	50		58	53	50	49

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	968321
5°	927943
10°	883716
15°	839852
20°	781289
25°	721283
30°	625799
35°	449002
40°	243897
45°	104169
50°	44747
55°	16171
60°	2960
65°	2335
70°	1442
75°	0
80°	0
85°	0



TEST NUMBER: P500597

CATALOG NUMBER: LDA2B208035R65D010 2LBDL1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	175.4	9.5
10°-20°	460.6	24.9
20°-30°	602.2	32.5
30°-40°	458.1	24.8
40°-50°	132.4	7.2
50°-60°	19.9	1.1
60°-70°	1.7	0.1
70°-80°	0.4	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1238.2	66.9
0°-40°	1696.4	91.7
0°-60°	1848.7	99.9
0°-90°	1850.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1850.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1963	
5°	1874	175
15°	1644	461
25°	1325	602
35°	746	458
45°	149	132
55°	19	20
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P500597

CATALOG NUMBER: LDA2B208035R65D010 2LBDL1B

CANDELA DISTRIBUTION (FULL):

0°	
0°	1962.7
1°	1955.8
2°	1944.9
3°	1923.2
4°	1899.4
5°	1873.7
6°	1849.0
7°	1827.3
8°	1806.5
9°	1787.7
10°	1764.0
11°	1743.2
12°	1721.5
13°	1699.7
14°	1676.0
15°	1644.3
16°	1620.6
17°	1591.9
18°	1548.4
19°	1525.7
20°	1488.1
21°	1454.5
22.5°	1403.1
23°	1383.3
24°	1352.7
25°	1325.0
26°	1288.4
27°	1247.8
28°	1203.3
29°	1155.9
30°	1098.5
32.5°	941.3
35°	745.5
37.5°	549.8
40°	378.7
42.5°	240.3
45°	149.3
47.5°	92.9
50°	58.3
52.5°	34.6
55°	18.8
57.5°	6.9
60°	3.0
62.5°	2.0
65°	2.0



TEST NUMBER: P500597

CATALOG NUMBER: LDA2B208035R65D010 2LBDL1B

CANDELA DISTRIBUTION (continued):

	0°
67.5°	1.0
70°	1.0
72.5°	1.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)