

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P280914

Luminaire Tested: **LDA2B209040D010 EU2B20WFL559040 2LBAD1H**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P280914  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-5)  
Test Lab: INNOVATION CENTER(G2)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LDA2B209040D010 EU2B20WFL559040 2LBAD1H  
Description: PORTFOLIO 2IN ADJ 2000 LUMEN LED LUMINAIRE WITH WIDE FLOOD OPTIC AND  
2in ADJ spun Refl, Self-Flanged, H  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1824.4 lumens  
Efficiency: N/A  
Efficacy: 88.6 lumens/watt  
Spacing Criteria (0/90/45): 0.74 / 0.74 / 0.73  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 20.6  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P280914

CATALOG NUMBER: LDA2B209040D010 EU2B20WFL559040 2LBAD1H

### Luminous Intensity Polar Plot





TEST NUMBER: P280914

CATALOG NUMBER: LDA2B209040D010 EU2B20WFL559040 2LBAD1H

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	114	112	109	107	112	110	108	106	106	104	103	102	101	99	98	97	97	95
2	109	105	101	98	107	103	100	97	100	98	95	97	95	93	95	93	91	90
3	105	99	95	91	103	98	94	91	95	92	89	93	90	88	91	88	86	85
4	100	94	89	85	99	93	88	85	91	87	84	89	85	83	87	84	82	80
5	96	89	84	80	95	88	83	80	86	82	79	85	81	78	83	80	78	76
6	92	84	79	75	91	84	79	75	82	78	75	81	77	74	80	76	74	72
7	88	80	75	71	87	80	75	71	78	74	71	77	73	70	76	73	70	69
8	85	76	71	68	84	76	71	67	75	70	67	74	70	67	73	69	67	65
9	81	73	68	64	80	72	68	64	72	67	64	71	67	64	70	66	64	62
10	78	70	65	61	77	69	64	61	69	64	61	68	64	61	67	63	61	59

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	1558135
5°	1526349
10°	1419406
15°	1239322
20°	1026056
25°	784756
30°	429429
35°	159003
40°	55001
45°	24769
50°	11667
55°	5849
60°	1677
65°	934
70°	1154
75°	0
80°	0
85°	0



TEST NUMBER: P280914

CATALOG NUMBER: LDA2B209040D010 EU2B20WFL559040 2LBAD1H

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	286.4	15.7
10°-20°	670.6	36.8
20°-30°	633.9	34.7
30°-40°	195.1	10.7
40°-50°	30.8	1.7
50°-60°	6.5	0.4
60°-70°	0.9	0.0
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1590.9	87.2
0°-40°	1786.0	97.9
0°-60°	1823.4	99.9
0°-90°	1824.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1824.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3158	
5°	3082	286
15°	2426	671
25°	1442	634
35°	264	195
45°	36	31
55°	7	7
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P280914

CATALOG NUMBER: LDA2B209040D010 EU2B20WFL559040 2LBAD1H

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	3158.2
1°	3146.3
2°	3131.9
3°	3120.1
4°	3104.9
5°	3082.0
6°	3052.4
7°	3012.7
8°	2959.4
9°	2897.6
10°	2833.3
11°	2762.2
12°	2686.9
13°	2604.9
14°	2519.4
15°	2426.4
17.5°	2180.2
20°	1954.3
22.5°	1725.0
25°	1441.6
27.5°	1099.8
30°	753.8
32.5°	462.8
35°	264.0
37.5°	147.2
40°	85.4
42.5°	53.3
45°	35.5
47.5°	23.7
50°	15.2
52.5°	10.2
55°	6.8
57.5°	4.2
60°	1.7
62.5°	0.8
65°	0.8
67.5°	0.8
70°	0.8
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P280914

CATALOG NUMBER: LDA2B209040D010 EU2B20WFL559040 2LBAD1H

**CANDELA DISTRIBUTION (continued):**

0°  
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)