

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P279978

Luminaire Tested: **LDA2B209027D010 EU2B20FL409027 2LBALD1LI**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P279978
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-3)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA2B209027D010 EU2B20FL409027 2LBALD1LI
Description: PORTFOLIO 2IN ADJ 2000 LUMEN LED LUMINAIRE WITH FLOOD OPTIC AND 2in
ADJ spun Refl w/lens Self-Flanged, H
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1656.6 lumens
Efficiency: N/A
Efficacy: 80.4 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.55
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 20.6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P279978

CATALOG NUMBER: LDA2B209027D010 EU2B20FL409027 2LBALD1LI

Luminous Intensity Polar Plot





TEST NUMBER: P279978

CATALOG NUMBER: LDA2B209027D010 EU2B20FL409027 2LBALD1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									
RC	80									50									30									10									0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0													
RCR																																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100						100													
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96						96													
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92						92													
3	107	102	98	95	105	101	97	94	98	95	93	96	94	92	94	92	90	89						89													
4	103	98	93	90	102	97	93	90	95	91	89	93	90	88	91	89	87	85						85													
5	100	94	89	86	98	93	89	86	91	88	85	90	87	84	88	86	83	82						82													
6	97	90	85	82	95	89	85	82	88	84	82	87	83	81	85	83	80	79						79													
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77						77													
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74						74													
9	88	81	76	73	87	80	76	73	79	76	73	79	75	73	78	75	73	72						72													
10	85	78	74	71	84	78	74	71	77	73	71	76	73	70	76	72	70	69						69													

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2277851
5°	2229649
10°	2032196
15°	1587511
20°	939899
25°	349428
30°	109152
35°	48544
40°	22541
45°	10605
50°	5833
55°	3269
60°	1480
65°	934
70°	1154
75°	0
80°	0
85°	0



TEST NUMBER: P279978

CATALOG NUMBER: LDA2B209027D010 EU2B20FL409027 2LBALD1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	416.2	25.1
10°-20°	827.6	50.0
20°-30°	338.9	20.5
30°-40°	56.1	3.4
40°-50°	13.3	0.8
50°-60°	3.5	0.2
60°-70°	0.9	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1582.7	95.5
0°-40°	1638.8	98.9
0°-60°	1655.6	99.9
0°-90°	1656.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1656.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4617	
5°	4502	416
15°	3108	828
25°	642	339
35°	81	56
45°	15	13
55°	4	4
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P279978

CATALOG NUMBER: LDA2B209027D010 EU2B20FL409027 2LBALD1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	4617.0
1°	4601.0
2°	4579.7
3°	4560.7
4°	4535.6
5°	4502.1
6°	4452.7
7°	4388.1
8°	4296.0
9°	4184.2
10°	4056.5
11°	3908.2
12°	3740.9
13°	3550.0
14°	3337.8
15°	3108.1
17.5°	2464.8
20°	1790.2
22.5°	1146.1
25°	641.9
27.5°	338.4
30°	191.6
32.5°	121.7
35°	80.6
37.5°	53.2
40°	35.0
42.5°	22.8
45°	15.2
47.5°	10.6
50°	7.6
52.5°	5.3
55°	3.8
57.5°	2.3
60°	1.5
62.5°	0.8
65°	0.8
67.5°	0.8
70°	0.8
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P279978

CATALOG NUMBER: LDA2B209027D010 EU2B20FL409027 2LBALD1LI

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)