

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P280074

Luminaire Tested: **LDA2B209730D010 EU2B20FL409730 2LBALD1LI**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P280074  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-3)  
Test Lab: INNOVATION CENTER(G2)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LDA2B209730D010 EU2B20FL409730 2LBALD1LI  
Description: PORTFOLIO 2IN ADJ 2000 LUMEN LED LUMINAIRE WITH FLOOD OPTIC AND 2in  
ADJ spun Refl w/lens Self-Flanged, H  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1586.3 lumens  
Efficiency: N/A  
Efficacy: 77.0 lumens/watt  
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.55  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 20.6  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P280074

CATALOG NUMBER: LDA2B209730D010 EU2B20FL409730 2LBALD1LI

### Luminous Intensity Polar Plot





TEST NUMBER: P280074

CATALOG NUMBER: LDA2B209730D010 EU2B20FL409730 2LBALD1LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10		0	
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96		
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92		
3	107	102	98	95	105	101	97	94	98	95	93	96	94	92	94	92	90	89		
4	103	98	93	90	102	97	93	90	95	91	89	93	90	88	91	89	87	85		
5	100	94	89	86	98	93	89	86	91	88	85	90	87	84	88	86	83	82		
6	97	90	85	82	95	89	85	82	88	84	82	87	83	81	85	83	80	79		
7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77		
8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74		
9	88	81	76	73	87	80	76	73	79	76	73	79	75	73	78	75	73	72		
10	85	78	74	71	84	78	74	71	77	73	71	76	73	70	76	72	70	69		

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	2181300
5°	2135205
10°	1946079
15°	1520243
20°	900050
25°	334621
30°	104537
35°	46496
40°	21575
45°	10187
50°	5603
55°	3097
60°	1480
65°	817
70°	1010
75°	0
80°	0
85°	0



TEST NUMBER: P280074

CATALOG NUMBER: LDA2B209730D010 EU2B20FL409730 2LBALD1LI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	398.5	25.1
10°-20°	792.5	50.0
20°-30°	324.6	20.5
30°-40°	53.7	3.4
40°-50°	12.7	0.8
50°-60°	3.4	0.2
60°-70°	0.8	0.0
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1515.6	95.5
0°-40°	1569.4	98.9
0°-60°	1585.4	99.9
0°-90°	1586.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1586.3	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4421	
5°	4311	399
15°	2976	793
25°	615	325
35°	77	54
45°	15	13
55°	4	3
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P280074

CATALOG NUMBER: LDA2B209730D010 EU2B20FL409730 2LBALD1LI

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	4421.3
1°	4406.0
2°	4385.6
3°	4367.4
4°	4343.4
5°	4311.4
6°	4264.0
7°	4202.1
8°	4114.0
9°	4006.9
10°	3884.6
11°	3742.6
12°	3582.4
13°	3399.6
14°	3196.4
15°	2976.4
17.5°	2360.3
20°	1714.3
22.5°	1097.5
25°	614.7
27.5°	324.1
30°	183.5
32.5°	116.5
35°	77.2
37.5°	51.0
40°	33.5
42.5°	21.8
45°	14.6
47.5°	10.2
50°	7.3
52.5°	5.1
55°	3.6
57.5°	2.2
60°	1.5
62.5°	0.7
65°	0.7
67.5°	0.7
70°	0.7
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P280074

CATALOG NUMBER: LDA2B209730D010 EU2B20FL409730 2LBALD1LI

**CANDELA DISTRIBUTION (continued):**

0°  
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)