

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P491725

Luminaire Tested: **LDA2B058027R60D010 2LBDL1WH**

Issue Date: 3/9/2021

This test was performed under the Supervised Manufacturer's Testing Program. The results of this test have not been influenced by sources from within Cooper Lighting Solutions or from external interests.



Test Information

Test Method: LM-79-08
Report Number: P491725
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2011-037-55)
Test Lab: INNOVATION CENTER
Issue Date: 3/9/2021
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LDA2B058027R60D010 2LBDL1WH
Description: 500 LUMEN 2IN ADJUSTABLE LED LUMINAIRE WITH 80 CRI LEDS AND 2700K CCT LEDS
Light Source: -
Ballast/Driver: -

Luminaire Equipment: Sample No. Condition Description


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 694.5 lumens
Efficiency: N/A
Efficacy: 99.2 lumens/watt
Spacing Criteria (0/90/45): 0.9 / 0.9 / 0.86
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct

Input Watts (W): 7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT

TEST NUMBER: P491725
CATALOG NUMBER: LDA2B058027R60D010 2LBDL1WH

Luminous Intensity Polar Plot





TEST NUMBER: P491725

CATALOG NUMBER: LDA2B058027R60D010 2LBDL1WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20					
RC	80					70					50					30					10					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																										
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100					100			
1	114	111	109	106	111	109	107	105	105	103	101	101	100	98	98	97	96	94					94			
2	108	103	100	96	106	102	98	95	99	96	93	96	93	91	93	91	89	88					88			
3	103	97	92	88	101	95	91	87	93	89	86	90	87	85	88	85	83	82					82			
4	98	90	85	81	96	89	84	81	87	83	80	85	82	79	83	80	78	76					76			
5	93	85	79	75	91	84	79	75	82	78	74	81	77	73	79	76	73	71					71			
6	88	80	74	70	87	79	74	70	78	73	69	76	72	69	75	71	68	67					67			
7	84	75	69	65	83	74	69	65	73	68	65	72	68	64	71	67	64	63					63			
8	80	71	65	61	79	70	65	61	69	64	61	68	64	60	67	63	60	59					59			
9	76	67	61	57	75	67	61	57	66	61	57	65	60	57	64	60	57	55					55			
10	73	63	58	54	72	63	58	54	62	57	54	61	57	54	61	57	54	52					52			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	411069
5°	400357
10°	389306
15°	370050
20°	338116
25°	290310
30°	216025
35°	126841
40°	60411
45°	28188
50°	14046
55°	4903
60°	1085
65°	934
70°	577
75°	762
80°	0
85°	0



TEST NUMBER: P491725

CATALOG NUMBER: LDA2B058027R60D010 2LBDL1WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	76.1	11.0
10°-20°	201.6	29.0
20°-30°	239.4	34.5
30°-40°	135.1	19.4
40°-50°	35.1	5.1
50°-60°	6.4	0.9
60°-70°	0.7	0.1
70°-80°	0.3	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	517.0	74.4
0°-40°	652.1	93.9
0°-60°	693.6	99.9
0°-90°	694.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	694.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	833	
5°	808	76
15°	724	202
25°	533	239
35°	211	135
45°	40	35
55°	6	6
65°	1	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P491725

CATALOG NUMBER: LDA2B058027R60D010 2LBDL1WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	833.2
1°	833.6
2°	827.9
3°	822.9
4°	813.4
5°	808.4
6°	799.6
7°	793.1
8°	787.0
9°	782.8
10°	777.1
11°	766.1
12°	755.8
13°	750.0
14°	736.7
15°	724.5
16°	710.4
17°	693.6
18°	677.5
19°	658.5
20°	644.0
21°	624.1
22.5°	591.3
23°	585.6
24°	557.8
25°	533.3
26°	506.3
27°	475.0
28°	444.1
29°	413.9
30°	379.2
32.5°	291.8
35°	210.6
37.5°	143.8
40°	93.8
42.5°	61.4
45°	40.4
47.5°	27.5
50°	18.3
52.5°	11.4
55°	5.7
57.5°	2.3
60°	1.1
62.5°	0.8
65°	0.8



TEST NUMBER: P491725

CATALOG NUMBER: LDA2B058027R60D010 2LBDL1WH

CANDELA DISTRIBUTION (continued):

	0°
67.5°	0.4
70°	0.4
72.5°	0.4
75°	0.4
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)