

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P279236

Luminaire Tested: **LDA2B058035D010 EU2B05FL408035 2LBAD1MW**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P279236
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-1811-033-3)
Test Lab: INNOVATION CENTER(G2)
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LDA2B058035D010 EU2B05FL408035 2LBAD1MW
Description: PORTFOLIO 2IN ADJ 500 LUMEN LED LUMINAIRE WITH FLOOD OPTIC AND 2in
ADJ spun Refl, Self-Flanged, MW
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 865.6 lumens
Efficiency: N/A
Efficacy: 123.7 lumens/watt
Spacing Criteria (0/90/45): 0.61 / 0.61 / 0.55
Luminous Opening: Circular (Dia: 0.17' x H: 0')
CIE Type: Direct


Input Watts (W): 7
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P279236

CATALOG NUMBER: LDA2B058035D010 EU2B05FL408035 2LBAD1MW

Luminous Intensity Polar Plot





TEST NUMBER: P279236

CATALOG NUMBER: LDA2B058035D010 EU2B05FL408035 2LBAD1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20									20									20									20									20									20								
RC	80									70									50									30									10									0								
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0																					
RCR	0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100																																			
	1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96																																			
	2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92																																			
	3	107	102	98	95	105	101	97	94	98	95	93	96	94	92	94	92	90	89																																			
	4	103	98	93	90	102	97	93	90	95	91	89	93	90	88	91	89	87	85																																			
	5	100	94	89	86	98	93	89	86	91	88	85	90	87	84	88	86	83	82																																			
	6	97	90	85	82	95	89	85	82	88	84	82	87	83	81	85	83	80	79																																			
	7	94	87	82	79	92	86	82	79	85	81	78	84	81	78	83	80	78	77																																			
	8	91	84	79	76	90	83	79	76	82	78	76	81	78	75	80	77	75	74																																			
	9	88	81	76	73	87	80	76	73	79	76	73	79	75	73	78	75	73	72																																			
	10	85	78	74	71	84	78	74	71	77	73	71	76	73	70	76	72	70	69																																			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1190235
5°	1165067
10°	1061862
15°	829535
20°	491108
25°	182580
30°	57025
35°	25356
40°	11786
45°	5512
50°	3070
55°	1720
60°	789
65°	467
70°	577
75°	0
80°	0
85°	0



TEST NUMBER: P279236

CATALOG NUMBER: LDA2B058035D010 EU2B05FL408035 2LBAD1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	217.5	25.1
10°-20°	432.4	50.0
20°-30°	177.1	20.5
30°-40°	29.3	3.4
40°-50°	6.9	0.8
50°-60°	1.9	0.2
60°-70°	0.4	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	827.0	95.5
0°-40°	856.3	98.9
0°-60°	865.1	99.9
0°-90°	865.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	865.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2412	
5°	2352	217
15°	1624	432
25°	335	177
35°	42	29
45°	8	7
55°	2	2
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P279236

CATALOG NUMBER: LDA2B058035D010 EU2B05FL408035 2LBAD1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	2412.5
1°	2404.2
2°	2393.0
3°	2383.1
4°	2370.0
5°	2352.5
6°	2326.7
7°	2292.9
8°	2244.8
9°	2186.4
10°	2119.6
11°	2042.2
12°	1954.7
13°	1855.0
14°	1744.1
15°	1624.1
17.5°	1287.9
20°	935.4
22.5°	598.9
25°	335.4
27.5°	176.8
30°	100.1
32.5°	63.6
35°	42.1
37.5°	27.8
40°	18.3
42.5°	11.9
45°	7.9
47.5°	5.6
50°	4.0
52.5°	2.8
55°	2.0
57.5°	1.2
60°	0.8
62.5°	0.4
65°	0.4
67.5°	0.4
70°	0.4
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0



TEST NUMBER: P279236

CATALOG NUMBER: LDA2B058035D010 EU2B05FL408035 2LBAD1MW

CANDELA DISTRIBUTION (continued):

0°
90° | 0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







85°		0.0
87.5°		0.0



(END OF REPORT)